
Submit 1 Copy To Appropriate District	State of N	New Me	xico		Form C-103	
Office District I – (575) 393-6161	Energy, Minerals a	nd Natu	ral Resources	Revised July 18, 2013		
1625 N. French Dr., Hobbs, NM 88240				WELL API NO.		
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERV.	ATION	DIVISION	30-025-32179		
<u>District III</u> – (505) 334-6178	1220 South	St. Fran	icis Dr.	5. Indicate Type of Le		
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe,			STATE 6. State Oil & Gas Lea	FEE 🗵	
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	Sunta 1 0,	, 1 1111 0 7	202	0. State Off & Gas Lea	ise ino.	
87505						
SUNDRY NOTI	ICES AND REPORTS ON			7. Lease Name or Unit SKELLY PENROSE		
DIFFERENT RESERVOIR. USE "APPLIE					AUNII	
PROPOSALS.)	G W II 🗆 04			8. Well Number #71		
Type of Well: Oil Well Name of Operator	Gas Well Other			9. OGRID Number		
Legacy Reserves Operating LP				240974		
3. Address of Operator				10. Pool name or Wild	lcat	
15 Smith Road, Suite 3000, Midla	and, TX 79705			JUSTIS; BLINEBRY	-TUBB-DRKRD	
4. Well Location						
Unit Letter N :	990 feet from the	S	line and1980	feet from the V	V line	
Section 34	Township 22S	Rang	ge 37E	NMPM Co	ounty LEA	
	11. Elevation (Show whe					
		3320'	GR			
12. Check A	Appropriate Box to Ind	licate N	ature of Notice, l	Report or Other Data	a	
NOTICE OF IN	ITENTION TO:		SUBS	SEQUENT REPOR	RT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	П	REMEDIAL WORK		ERING CASING	
TEMPORARILY ABANDON	CHANGE PLANS		COMMENCE DRII		ND A	
PULL OR ALTER CASING	MULTIPLE COMPL		CASING/CEMENT	JOB 🔲		
DOWNHOLE COMMINGLE						
CLOSED-LOOP SYSTEM			071150			
OTHER: 13. Describe proposed or comp	lated operations (Clearly	state all r	OTHER:	aive pertinent dates in	cluding astimated data	
of starting any proposed we						
proposed completion or rec			. Tor wantpre con	ipietions. Tituen went	ore anagram or	
	-					
02/20/23 MIRU plugging equipme						
drill bit & scrapper to 3520'. POH						
C cmt @ 3500-3259'. WOC. 02/22 2514-2273'. WOC. 02/23/23 Tagge						
1320'. Pressured up on perfs to 50						
Spooted 25 sx class C cmt @ 150'						
Kerry Fortner w/ OCD verified cr						
2' concrete form w/ 6 sx cmt. Back	afilled cellar, cut off dead	men, cle	aned location, and	moved off.		
Spud Date:	Rig R	elease Da	ite:			
I hereby certify that the information	above is true and complete	to the be	est of my knowledge	and belief.		
SIGNATURE Melanie K	Peyes TITL	Е	Regulatory Tech	DATE	3/01/2023	
· · · · · · · · · · · · · · · · · · ·	<u>ie Reyes</u> E-mail	address:	_mreyes@legacyre	serves.com PHONE:	<u>(432) 221-6358</u>	
For State Use Only						
APPROVED BY:	TITLE	E Pe	troleum Specialis	t DATE	05/04/2023	
Conditions of Approval (if any):	1111/1		1			

Released to Imaging: 5/4/2023 2:39:37 PM



Skelly Per	nrose A Unit #71	API#:	30-02	5-32179		
Field/Pool:	Langlie-Mattix; 7 Rvrs- Queen-Grayburg	Section:		34		
County:	Lea	Township:	22S	Range:	37E	
State:	New Mexico	Location:	Ç	990' FSL x 19	80' FWL	Author:
Spud Date:	10/19/1993	GL:	3320'	PBTD:	3885'	J. Valdez
· · · · · · · · · · · · · · · · · · ·	•	· ·	·	· ·	· ·	· ·



Description	O.D.	Weight	Тор	Depth	Hole	Cmt Sx	TOC
Surface	8.625	24	0	1141	12.25	650 Sx	Circ'd
Production	5.5	15.5	0	5800	7.875	2245 Sx/ Top Job 450 Sx	1500' TS/
CIBP	5.5	15.5	5375	5410	5.5	CIBP w/ 35' cmt cap	5375
CIBP	5.5	15.5	5065	5100	5.5	CIBP w/ 35' cmt cap	5065
CIBP	5.5	15.5	3885	3920	5.5	CIBP w/ 35' cmt cap	3829

- 7. Cut off well head, verify cmt at surface, weld on dry hole marker.
- 6. Spot 25 sx @100' 0'. (surface plug)

Formation Tops:

Rustler (T-Salt) 1270' *

Transil (B-Salt) 2464' *

Yates 2861

7Rivers 2968

Queen

Delaware

8.625" Surface Casing @ 1141'

Top Job- 450 Sx down 5.5" x 8.625" Annulus.

5. Perf & Sqz 46 sx cmt @ 1320'-1091'. WOC & Tag. (Rustler T-salt/ Surf. Csg Shoe)

* Used offset well SPAU #63

Est TOC @ 1500' TS

- 4. Spot 25 sx cmt @ 1600'-1450'. WOC & Tag (Est TOC 5.5")
- 3. Spot 25 sx cmt @ 2514'-2414'. WOC & Tag (Transil B-salt)
- 2. Spot 25 sx cmt @ 2911'-2811'. (Yates)
- 1. Set CIBP @ 3500' w/ 25 sx cmt. Load hole with MLF. P/T casing to 500 psi. NMOCD witness.

Perfs: 3553'-3574'

CIBP @ 3920' w/ 35' Cement cap.PBTD @ 3885' (2/8/94)

Perfs 3951'-4097'

CIBP @ 5100' w/ 35' Cement cap (1/20/94)

Perfs: 5175'-5242'

CIBP @ 5410' w/ 35' Cement cap (1/13/94)

Perfs: 5505'-5558'

5.5" Production Casing 0'- 5800'

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 192028

CONDITIONS

Operator:	OGRID:
LEGACY RESERVES OPERATING, LP	240974
15 Smith Road	Action Number:
Midland, TX 79705	192028
	Action Type:
	[C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By		Condition Date
john.harrisor	None	5/4/2023