
Cesived by Copy Po Appropriate Distance of the Copy Po Appropriate Distance of the Copy Point Provided		State of field filed					Form C-183 Revised July 18, 2013			
<u>District I</u> – (575) 393-61 1625 N. French Dr., Hob	bs, NM 88240	Energy, Minerals and Natural Resources					API NO.	30-015-50		
	rict II – (575) 748-1283 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISIO				SION	5 Indic	ate Type of	fLease		
<u>District III</u> – (505) 334-6 1000 Rio Brazos Rd., Az		1220 South St. Francis Dr.				STATE FEE 6. State Oil & Gas Lease No.				
<u>District IV</u> – (505) 476-3 1220 S. St. Francis Dr., 5 87505	460	Santa Fe, NM 87505								
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)					7. Lease	e Name or	Unit Agreer	nent Name		
					MORRISON					
1. Type of Well: Oil Well 🔀 Gas Well 🗌 Other						8. Well Number 104H				
2. Name of Operator SILVERBACK OPERATING II, LLC						9. OGRID Number 330968				
3. Address of Operation	19707 110	est IH 10, Suite 2 nio, TX 78257	201				l name or V SCO DRAV		O (ASSOC)	
4. Well Location		, , ,							- ()	
Unit Letter			rom the <u>N</u>			729		the W_{\sim}	line	
Section	10		nship 19S Show whether I	0	25E T. GR. etc.	NMPM		County	Eddy	
			3498' G	BR	1, ON, CIC.					
						_				
	12. Check A	ppropriate Bo	ox to Indicate	e Nature o	f Notice,	Report o	r Other I	Data		
NO		TENTION TO	D:		SUB	SEQUE	NT REP	ORT OF	:	
PERFORM REMED		PLUG AND AE		REME	DIAL WOR				CASING 🗌	
TEMPORARILY AB	_	CHANGE PLA			IENCE DRI		_	P AND A		
PULL OR ALTER C		MULTIPLE CC	MPL	CASIN	G/CEMEN	T JOB				
DOWNHOLE COMM CLOSED-LOOP SY										
OTHER:				OTHE	R:					
13. Describe pro	posed or compl	eted operations.	(Clearly state a	all pertinent	details, and	d give nert	inent dates	, including e	estimated date	
		-	· •	-				-		
	y proposed work	x). SEE RULE 1	19.15.7.14 NMA	-				-		
completion of	y proposed work recompletion.			AC. For Mu				-		
completion of	y proposed work recompletion.	x). SEE RULE 1		AC. For Mu				-		
completion of Silverback	y proposed work recompletion. Operating II, Ll	LC plans to plug	and abandon th	AC. For Mu	ıltiple Com	pletions:	Attach wel	lbore diagra	m of proposed	
completion of Silverback Our plan is	y proposed work recompletion. Operating II, Ll to tag the top of	LC plans to plug f fish at 417' and	and abandon th l pump approxim	AC. For Mu nis well. mately 400 s	ıltiple Com sx of Class	C Neat ce	Attach well	lbore diagra	m of proposed cf/sx	
completion or Silverback Our plan is yield). One	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer	LC plans to plug	and abandon th I pump approxim will pull out of	AC. For Mu his well. mately 400 s the hole with	Iltiple Com sx of Class th drill pipe	C Neat ce and top o	Attach well ment at 14. ff the ceme	lbore diagra .8 ppg (1.12 ent within th	m of proposed cf/sx e	
completion of Silverback Our plan is yield). One conductor of the cap at a	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10	LC plans to plug f fish at 417' and t to surface, we WOC approxim)' below ground	and abandon th l pump approxin will pull out of ately 8 hrs and level. Back fill	AC. For Mu his well. mately 400 s the hole wit then tag to l and installa	Iltiple Com sx of Class th drill pipe verify befor	C Neat ce e and top o re cutting t	Attach well ment at 14 ff the ceme he conduct	lbore diagra 8 ppg (1.12 ent within th for and weld	m of proposed cf/sx e ling on	
completion of Silverback Our plan is yield). One conductor of the cap at a	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10	LC plans to plug f fish at 417' and tt to surface, we WOC approxim	and abandon th l pump approxin will pull out of ately 8 hrs and level. Back fill	AC. For Mu his well. mately 400 s the hole wit then tag to l and installa	Iltiple Com sx of Class th drill pipe verify befor	C Neat ce e and top o re cutting t	Attach well ment at 14 ff the ceme he conduct	lbore diagra 8 ppg (1.12 ent within th for and weld	m of proposed cf/sx e ling on	
completion of Silverback Our plan is yield). One conductor of the cap at a	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10	LC plans to plug f fish at 417' and t to surface, we WOC approxim)' below ground	and abandon th l pump approxin will pull out of ately 8 hrs and level. Back fill	AC. For Mu his well. mately 400 s the hole wit then tag to l and installa	Iltiple Com sx of Class th drill pipe verify befor	C Neat ce e and top o re cutting t	Attach well ment at 14 ff the ceme he conduct	lbore diagra 8 ppg (1.12 ent within th for and weld	m of proposed cf/sx e ling on	
completion of Silverback Our plan is yield). One conductor of the cap at a drilling rig	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10	LC plans to plug f fish at 417' and tt to surface, we WOC approxim)' below ground location within	and abandon th l pump approxin will pull out of ately 8 hrs and level. Back fill	AC. For Mu his well. mately 400 s the hole wit then tag to l and installa	Iltiple Com sx of Class th drill pipe verify befor	C Neat ce e and top o re cutting t	Attach well ment at 14 ff the ceme he conduct	lbore diagra 8 ppg (1.12 ent within th for and weld	m of proposed cf/sx e ling on	
completion of Silverback Our plan is yield). One conductor of the cap at a drilling rig	y proposed work recompletion. Operating II, Ll to tag the top of ce we see cemer casing. We will pproximately 10 is moved off of	LC plans to plug f fish at 417' and tt to surface, we WOC approxim)' below ground location within	and abandon th l pump approxin will pull out of ately 8 hrs and level. Back fill	AC. For Mu his well. mately 400 s the hole wit then tag to l and installa	Iltiple Com sx of Class th drill pipe verify befor	C Neat ce e and top o re cutting t	Attach well ment at 14 ff the ceme he conduct	lbore diagra 8 ppg (1.12 ent within th for and weld	m of proposed cf/sx e ling on	
completion of Silverback Our plan is yield). One conductor of the cap at a drilling rig Wellbore so	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10 is moved off of chematics attach	LC plans to plug f fish at 417' and tt to surface, we WOC approxim)' below ground location within	and abandon th l pump approxin will pull out of ately 8 hrs and level. Back fill the next week o	AC. For Mu nis well. mately 400 s the hole wit then tag to v l and installa or so.	Iltiple Com sx of Class th drill pipe verify befor	C Neat ce e and top o re cutting t	Attach well ment at 14 ff the ceme he conduct	lbore diagra 8 ppg (1.12 ent within th for and weld	m of proposed cf/sx e ling on	
completion of Silverback Our plan is yield). One conductor of the cap at a drilling rig	y proposed work recompletion. Operating II, Ll to tag the top of ce we see cemer casing. We will pproximately 10 is moved off of	LC plans to plug f fish at 417' and tt to surface, we WOC approxim)' below ground location within	and abandon th l pump approxin will pull out of ately 8 hrs and level. Back fill	AC. For Mu nis well. mately 400 s the hole wit then tag to v l and installa or so.	Iltiple Com sx of Class th drill pipe verify befor	C Neat ce e and top o re cutting t	Attach well ment at 14 ff the ceme he conduct	lbore diagra 8 ppg (1.12 ent within th for and weld	m of proposed cf/sx e ling on	
completion of Silverback Our plan is yield). One conductor of the cap at a drilling rig Wellbore se	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10 is moved off of chematics attach	LC plans to plug f fish at 417' and tt to surface, we WOC approxim)' below ground location within	and abandon th l pump approxin will pull out of ately 8 hrs and level. Back fill the next week o	AC. For Mu nis well. mately 400 s the hole wit then tag to v l and installa or so.	Iltiple Com sx of Class th drill pipe verify befor	C Neat ce e and top o re cutting t	Attach well ment at 14 ff the ceme he conduct	lbore diagra 8 ppg (1.12 ent within th for and weld	m of proposed cf/sx e ling on	
completion of Silverback Our plan is yield). One conductor of the cap at a drilling rig Wellbore se	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10 is moved off of chematics attach	LC plans to plug f fish at 417' and it to surface, we WOC approxim)' below ground location within ted.	and abandon th l pump approxin will pull out of lately 8 hrs and level. Back fill the next week o Rig Release	AC. For Mu nis well. (the hole with then tag to well and installa or so.	Iltiple Com sx of Class th drill pipe verify befor ation of the	C Neat ce e and top o re cutting t P&A mar	Attach well ment at 14. ff the ceme he conduct ker will tak	lbore diagra 8 ppg (1.12 ent within th for and weld	m of proposed cf/sx e ling on	
completion of Silverback Our plan is yield). One conductor of the cap at a drilling rig Wellbore se	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10 is moved off of chematics attach	LC plans to plug f fish at 417' and it to surface, we WOC approxim)' below ground location within ted.	and abandon th l pump approxin will pull out of lately 8 hrs and level. Back fill the next week o Rig Release	AC. For Mu nis well. (the hole with then tag to well and installa or so.	Iltiple Com sx of Class th drill pipe verify befor ation of the	C Neat ce e and top o re cutting t P&A mar	Attach well ment at 14. ff the ceme he conduct ker will tak	lbore diagra 8 ppg (1.12 ent within th for and weld	m of proposed cf/sx e ling on	
completion of Silverback Our plan is yield). One conductor of the cap at a drilling rig Wellbore so Spud Date:	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10 is moved off of chematics attach	C plans to plug f fish at 417' and it to surface, we WOC approxim)' below ground location within hed.	and abandon the l pump approximately approximately 8 hrs and level. Back fill the next week of Rig Release	AC. For Mu nis well. (the hole with then tag to well and installa or so.	Iltiple Com sx of Class th drill pipe verify befor ation of the	C Neat ce e and top o re cutting t P&A mar	Attach well ment at 14. ff the ceme he conduct ker will tak	lbore diagra 8 ppg (1.12 ent within th for and weld	m of proposed cf/sx e ling on er the	
completion of Silverback Our plan is yield). One conductor of the cap at a drilling rig Wellbore so Spud Date:	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10 is moved off of chematics attach 5/27/2023 he information a	C plans to plug f fish at 417' and it to surface, we WOC approxim by below ground location within the ned.	and abandon the l pump approximation will pull out of the part of the level. Back fill the next week of Rig Release complete to the 	AC. For Mu nis well. mately 400 s the hole wit then tag to v l and installa or so.	Iltiple Com sx of Class th drill pipe verify befor ation of the verify befor ation of the	C Neat ce e and top o re cutting t P&A mar	Attach well ment at 14. ff the ceme he conduct ker will tak	lbore diagra	m of proposed cf/sx e ling on er the 2023	
completion of Silverback Our plan is yield). One conductor of the cap at a drilling rig Wellbore so Spud Date:	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10 is moved off of chematics attach 5/27/2023 he information a	C plans to plug f fish at 417' and it to surface, we WOC approxim by below ground location within the ned.	and abandon the l pump approximation will pull out of the part of the level. Back fill the next week of Rig Release complete to the 	AC. For Mu nis well. mately 400 s the hole wit then tag to v l and installa or so.	Iltiple Com sx of Class th drill pipe verify befor ation of the verify befor ation of the	C Neat ce e and top o re cutting t P&A mar	Attach well ment at 14. ff the ceme he conduct ker will tak	lbore diagra	m of proposed cf/sx e ling on er the 2023	
completion of Silverback Our plan is yield). One conductor of the cap at a drilling rig Wellbore so Spud Date:	y proposed work recompletion. Operating II, LI to tag the top of ce we see cemer casing. We will pproximately 10 is moved off of chematics attach 5/27/2023 he information a	C plans to plug f fish at 417' and it to surface, we WOC approxim by below ground location within the ned.	and abandon the l pump approximation will pull out of lately 8 hrs and level. Back fill the next week of Rig Release complete to the TITLE_Reg E-mail add	AC. For Mu nis well. mately 400 s the hole wit then tag to v l and installa or so.	Iltiple Com sx of Class th drill pipe verify befor ation of the verify befor ation of the verify befor ation of the <u>verify befor</u> ation of the <u>nager</u> <u>llah@silve</u>	C Neat ce e and top o re cutting t P&A mar e and belic	Attach well ment at 14. ff the ceme he conduct ker will tak	Ibore diagra	m of proposed cf/sx e ling on r the 2023 585-3316	

•



District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:			
Silverback Operating II, LLC	330968			
19707 IH10 West, Suite 201	Action Number:			
San Antonio, TX 78256	222467			
	Action Type:			
	[C-103] NOI Plug & Abandon (C-103F)			

CONDITIONS

Created By	Condition	Condition Date
john.harrison	None	5/31/2023

Action 222467

.