

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised July 18, 2013

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. Zia AGI #1 30-025-42208 Zia AGI D#2 30-025-42207
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other: Acid Gas Injection Well <input checked="" type="checkbox"/>		5. Indicate Type of Lease BLM STATE <input type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator DCP Operating Company, LP		6. State Oil & Gas Lease No. NMLC065863
3. Address of Operator 6900 E. Layton Ave, Suite 900, Denver, CO 80237		7. Lease Name or Unit Agreement Name Zia AGI
4. Well Location Surface Zia AGI#1 Unit Letter <u>L</u> : <u>2,100</u> feet from the SOUTH line and <u>950</u> feet from the WEST line Zia AGI D#2 Unit Letter <u>L</u> : <u>1893</u> feet from the SOUTH line and <u>950</u> feet from the WEST line Section <u>19</u> Township <u>19S</u> Range <u>32E</u> NMPM County <u>Lea</u>		8. Well Number #1 and D#2
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,550 (GR)		9. OGRID Number 36785
10. Pool name or Wildcat #1 AGI: Cherry Canyon/Brushy Canyon D#2 AGI: Devonian/Fusselman/Montoya		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: Quarterly Injection Data Reports <input checked="" type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. **Wellbore Diagrams attached.**

**Zia AGI#1 MAOP 2,233 psig NMOCC Order R-13809 / Zia AGI D#2 MAOP 5,208 psig NMOCC Order R-14207**

**Quarterly Report for the period from April 1 to June 30, 2023 (Q2) Pursuant to NMOCC Orders 13809 and 14207 for Zia AGI #1 and AGI D#2, respectively.**

This report includes the data and analysis of surface injection pressure, TAG temperature, casing annular pressure as well as downhole injection pressure, temperature, and annular pressure for the Zia AGI#1 and for the Zia AGI D#2 for Q2 2023. AGI D#2 is the primary well for this facility with the Zia AGI#1 to be used only as a redundant and backup well. Based on data for surface injection/annular pressure and their current MITs both wells continue to show excellent integrity. For this quarter, the values for injection parameters are generally stable and yielded the following results which are graphed in detail in attached Figures 1 through 10. All the values presented below are averages for the static conditions in the AGI #1 since the well was not in operation for the entire reporting period. Only AGI D#2 was operated during this quarter and its average values represent the normal operational condition of the well. Average injection rates for AGI D#2 have increased slightly (8.03 vs 7.95 MMSCFD) from the previous quarter. Injection to AGI D#2 was shut down from June 13-14 for a scheduled plant turnaround for maintenance.

**AGI#1 Surface Measurements (inactive):** Average TAG Line Pressure: 7 psig, Average Annular Pressure: 319 psig, Average Pressure Differential: -312psig, Average Tag Line Temperature: 95°F, Average TAG injection rate: 0.00 MMSCFD (not in use this quarter).

**AGI#1 Downhole Measurements (inactive):** Average bottom hole pressure: 3,274 psig, Average annular bottom hole pressure: 2,285 psig, Average annular bottom hole temperature: 98°F, Average bottom hole TAG Temperature: 98°F (all unchanged since 2021).

**AGI D#2 Surface Measurements:** Average TAG Injection Pressure: 1,989 psig, Average Annular Pressure: 324 psig, Average Pressure Differential: 1,666 psig, Average Tag Temperature: 120°F, Average TAG injection rate: 8.03 MMSCFD.

**AGI D#2 Downhole Measurements:** Average bottom hole pressure 6,591 psig, Average bottom hole TAG Temperature: 167°F. Only AGI D#2 was operated during this reporting period.

Note that the injection rate for AGI D#2 for the quarter is slightly higher than last quarter. This resulted in a commensurate increase in bottom hole pressure which has also increased. The well is behaving appropriately with concurrent changes in injection pressure and annular pressure.

The data gathered throughout this quarter demonstrate the correlative behavior of the annular pressure with the flowrate, injection pressure and temperature confirming that both wells have good integrity and are functioning appropriately within the requirements of their respective NMOCC orders. No mechanical changes to the either well or wellhead have been made since the last quarterly report. Well AGI D#2 displays excellent reservoir characteristics easily accommodating the required volumes of TAG from the facility. This well will be used as the primary disposal well for the facility with the AGI #1 well being operated as needed to confirm functionality and to allow for any required future maintenance on the AGI D#2 well.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.



SIGNATURE \_\_\_\_\_ TITLE Consultant to DCP Midstream LP DATE 7-6-2023


Type or print name: Alberto A Gutiérrez, RG E-mail address: [aag@geolex.com](mailto:aag@geolex.com) PHONE: 505-842-8000

**For State Use Only**

APPROVED BY: \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

Conditions of Approval (if any):

**FIGURE 1: ZIA AGI #1 AND AGI D#2 INJECTION RATES**



**FIGURE 2: ZIA AGI #1 SURFACE INJECTION PRESSURE, ANNULAR PRESSURE AND INJECTION RATE**




FIGURE 3: ZIA AGI #1 SURFACE INJECTION PRESSURE, ANNULAR PRESSURE AND INJECTION TEMPERATURE




FIGURE 4: ZIA AGI #1 SURFACE INJECTION PRESSURE AND BOTTOM HOLE PRESSURE






FIGURE 5: ZIA AGI D#2 SURFACE INJECTION PRESSURE, ANNULAR PRESSURE AND INJECTION RATE




**FIGURE 6: ZIA AGI D#2 SURFACE INJECTION PRESSURE, ANNULAR PRESSURE AND INJECTION TEMPERATURE**







**FIGURE 7: ZIA AGI D#2 SURFACE INJECTION PRESSURE AND BOTTOM HOLE PRESSURE**




**FIGURE 8: ZIA AGI #1 BOTTOM HOLE PRESSURE AND TEMPERATURE**



**FIGURE 9: ZIA AGI D#2 BOTTOM HOLE PRESSURE AND TEMPERATURE**



**FIGURE 10: ZIA AGI #1 AND D#2 DIFFERENTIAL PRESSURE**



**WELL SCHEMATICS**

<b>Zia AGI #1</b>	<b>API# 30-025-42208</b>
<b>Zia AGI D #2</b>	<b>API# 30-025-42207</b>




## ZIA AGI #1 AS-BUILT WELL SCHEMATIC



**Location:** DCP Zia AGI #1 (API: 30-025-42208)  
**STR** Section 19(L), T19S-R32E (2100' FSL & 950' FWL)  
**County, St.:** LEA COUNTY, NEW MEXICO

## 16.2 DEGREE SLANT

**CONDUCTOR CASING**

20" Conductor at 120' (cement to surface)

**SURFACE CASING**

13 3/8", 68.0#/ft, J55, BTC at 842' (cement to surface)

**ANNULAR FLUID:**

Diesel Fuel from top of packer to surface

**INTERMEDIATE CASING:**

9 5/8", 40.0 #/ft, J55, LT&amp;C at 4,921' (4,830 Ft TVD) cement to surface

**PRODUCTION CASING:**

7 5/8", 29.7 #/ft, HCL-80 LT&amp;C, Surf. To 319' (MTD)

7", 26 #/ft, HCL-80 LT&amp;C, 319' to 5,306' (MTD)

7", 26 #/ft, 28Cr VAM TOP, 5,306' to 5,615' (MTD)

7", 26 #/ft, HCL-80 LT&amp;C, 5,615' to 6,344' (MTD) cement to surface

**TUBING:**

Subsurface Safety Valve at 242' MD (242' TVD)

3 1/2", 9.3#/ft, L-80 Fiberglass Lined Tubing surf. to 5,443' MD, ID=2.684", Drift=2.559"

3 1/2", 9.3#/ft, SM2550 from 5,443' to 5,575' MD

All tubing to include premium threads utilizing metal to metal sealing in collars

**PACKER:**

Permanent Production Packer @ 5,579' MD (5,450' TVD)

Adj. Choke (if needed, placed in nipple below packer)

Check valve (if needed, placed in nipple below packer)

**PERFORATIONS:**

**MD**  
 5,682' - 5,756' complete and inject  
 5,788' - 5,890' complete and inject  
 5,907' - 6,010' complete and inject  
 6,030' - 6,136' complete and inject  
 6,162' - 6,260' complete and inject


**NOT TO SCALE**

Bottom Hole Location: Section 19(G), T19S, R32E (2,099' FNL &amp; 862' FWL)

**DCP Zia AGI D #2 As-Built Well Schematic**

**Well Name:** Zia AGI D #2  
**API:** 30-025-42207  
**STR:** Sec. 19(L), T19S-R32E  
**County, St.:** Lea County, New Mexico

**Footage:** 1893' FSL & 950' FWL  
**Well Type:** Devonian AGI Expl.  
**KB/GL:** 3574'/3547'  
**Lat, Long:** 32.643950, -103.777782



Schematic is properly scaled

TD Location: Sec. 19, T19S-R32E (1963' FSL &amp; 1024' FWL)



## DCP MIDSTREAM

ZIA AGI #2  
LEA COUNTY, NEW MEXICO  
1/22/17

Company Rep.  
Tool Specialist

GARY HENRICH  
SCOTT WALTON  
Office ODESSA  
SAP No. 903711839

Final Installation							
Installation	Length	Depth	Description			OD	ID
1	25.00	7.52	KB CORRECTION				
2	0.50	32.52	TUBING HANGER				
	3.62	33.02	DOUBLE PIN ADAPTER			3.500	2.925
3	2	31.41	1 JOINT 3.5" 9.3# L-80 BTS8 TUBING			3.500	2.925
	3	17.48	3.5" 9.3# L80 BTS8- TUBING SUBS(9.73, 7.75)			3.500	2.925
4	188.39	85.53	6 JOINT 3.5" 9.3# L-80 BTS8 TUBING			3.500	2.925
	5	3.72	3.5" 9.3# X-OVER SUB BTS8 BOX X AB-TC-II PIN			3.940	2.910
6	4.40	277.64	HALLIBURTON TUBING RETRIEVABLE SAFETY VALVE 3.5" 9.2# AB-TC-II BOX X PIN 478HRE18 102588547 SN-0003667054-2 NICKLE ALLOY 925 15,000# PRESSURE RATING 750 PSI CLOSING 2300 PSI OPENING 2.813 'R' PROFILE IN TOP OF VALVE.			5.290	2.813
5			3.5" 9.3# X-OVER SUB AB-TC-II BOX X BTS8 PIN			3.940	2.910
6	7	3.75					
7	8	12911.35	411 JOINTS 3.5" 9.3# L80 BTS8 TUBING			3.500	2.684
	9	3.75	X-OVER PUP JOINT 3.5" 9.3# BTS8 box X 3.5" 9.3# VAMTOP pin			3.930	2.684
10	317.56	13,197.14	9 JOINTS 3.5" 9.3# VAMTOP SM2550 NICKELTUBING			3.500	2.992
	11	1.33	HALLIBURTON 2.562 X 3.5# 9.3# L-80 VAM TOP LANDING NIPPLE (811R25635)(102204262)(SN-0003744132-3) NICKEL ALLOY 925			3.940	2.562
8	12	6.35	3.5" 9.2# G3-125 VAMTOP BOX X PIN SUB (COUPLING ON BTM)			3.930	2.992
	13	4.32	HALLIBURTON ROC GAUGE MANDREL 3.5" VAMTOP PXP 102329817 SN-ATM-16-106669-1 ROC GAUGE ROC16K175C 101863926 WD#9381-6034 ADDRESS 094 SN-ROC004482			4.670	2.950
	14	3.75	3.5" 9.2# G3-125 VAMTOP BOX X PIN SUB			3.930	2.992
A			HALLIBURTON SEAL ASSEMBLY				
a-1	1.73	13,534.20	STRAIGHT SLOT LOCATOR 3.5" VAMTOP X 3.5" 10.2# VAMINSIDE INCOLOY 925 (212S4042-D)(102351212)(SN-G3362241-1)			4.460	2.886
	a-2	4.33	EXTENSION 3.5" 10.2# VAMINSIDE NICKEL ALLOY 925 (212X38814-D) (158726)(SN-G3362256-1)			3.860	2.902
9	a-3	4.33	EXTENSION 3.5" 10.2# VAMINSIDE NICKEL ALLOY 925 (212X38814-D) (158726)(SN-G3362256-1)			3.860	2.902
	a-4	5.00	5 - SEAL UNITS 4" X 3.5" 10.2 VAM TOP NICKEL ALLOY 925 MOLDED AFLAS SEALS 4.07 OD, 8000 PSI (812MSA40003-D)(102133617)(SN-0003744129-1 0003744129-4) (0003744129-3 0003744129-2 0003744129-5) (METAL OD 3.95") (TOP 2 SEAL ARE FLOUREL BOTTOM 3 SEALS ARE AFLAS)			4.050	2.883
10			MULE SHOE GUIDE 3.5" 10.2# VAMINSIDE NICKEL ALLOY 925 (812G40137-D) (102133560)(SN-3744130)			3.950	2.980
11	a-5	0.54	LAND HANGER WITH 26,000# COMPRESSION PUTS 20,000# COMPRESSION ON PACKER PICK UP WEIGHT IS 132,000# SLACK OFF IS 120,000# HALLIBURTON PACKER ASSEMBLY				
12			HALLIBURTON 7" 26-32# BWD PERMANENT PACKER WITH 4" BORE, 4.75" 8UN BOX THREAD, INCOLOY 925 (212BWD70412-D)(101303583)(SN C3774119) WAS RUN ON W/L AND TOP @ 13535' ELEMENTS @ 13533.21'			5.880	4.000
13	15	3.11					
14	16	11.41	SEAL BORE EXTENSION 4" X 8" INCOLOY 925 4.75 8UN PXP (PN212C7674)(120051359)(SN-0003744131-1)			5.030	4.000
15	17	0.83	X-OVER 4 75" 8UN BOX X 3.5" 9.3# VAM INCOLOY 925 (212N100131)(101719647)(SN-0003744131-1)			5.680	2.963
16	18	5.76	PUP JOINT 3.5" 9.3# VAM TOP INCOLOY 925 WITH COUPLING			3.520	2.940
17	19	1.33	HALLIBURTON 2.562"R' X 3.5" VAMTOP LANDING NIPPLE (811X25635) (102204262) ( SN- 0003744132-1) NICKEL ALLOY 925			3.940	2.562
18	20	5.76	PUP JOINT 3.5" 9.3# VAM INCOLOY 925 WITH COUPLING			3.520	2.930
19	21	1.33	HALLIBURTON 2.562" X 3.5" VAMTOP LANDING NIPPLE (811X25635) (102204262) ( SN- 0003744132-2) NICKEL ALLOY 925			3.940	2.562
20	22	0.73	WIRELINE RE-ENTRY GUIDE 3.5" 9.3# VAM INCOLOY 925			3.970	3.000
21			BOTTOM OF ASSEMBLY				
22			EOC @ 13,622' TD @ 14,750'				
			DIESEL USED FOR PACKER FLUID				
			Filename:				



**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

CONDITIONS  
  
Action 237931

CONDITIONS

Operator: DCP OPERATING COMPANY, LP 6900 E. Layton Ave Denver, CO 80237	OGRID: 36785
	Action Number: 237931
	Action Type: [C-103] Sub. General Sundry (C-103Z)

CONDITIONS

Created By	Condition	Condition Date
mgebremichael	None	7/14/2023