

Well Name: COLD SNACK FED COM	Well Location: T25S / R25E / SEC 14 / SWNW / 32.1329447 / -104.3736346	County or Parish/State: EDDY / NM
Well Number: 211H	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:
Lease Number: NMNM28169	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001553318	Well Status: Drilling Well	Operator: TAP ROCK OPERATING LLC

Subsequent Report

Sundry ID: 2725124

Type of Submission: Subsequent Report

Date Sundry Submitted: 04/11/2023

Date Operation Actually Began: 03/04/2023

Type of Action: Drilling Operations

Time Sundry Submitted: 09:06

Actual Procedure: Well spud on 3/4/2023 at 12:00 3/4/2023: Drill 17.5 inch surface hole to 325. 3/4/2023: Run 13.375 inch 54.5 lb J55 surface casing to 311 ft. Pump 20 bbls water spacer, followed by 455 sks of 14.8 ppg tail cmt. Drop plug and displace with 44 bbls fresh water. Top Job cmt of 19bbls 14.8 ppg. 2 bbls of cement returned back to surface. EST TOC at 0 ft. Pressure test casing to 1500 PSI for 30 minutes, good test. 3/18/2023: Test BOPS. Drill 12.25 intermediate hole to 1517 ft. 3/19/2023: Run 9.625 inch 40 lb J-55 intermediate casing to 1502 ft. Pump 20 bbls fresh water spacer, followed by 280 sks of 12.9 ppg lead cmt, 150 sks of 14.8 ppg tail cmt. Drop plug and displace with 110 bbls of fresh water. 30 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 1500 for 30 minutes, good test. 4/1/2023: Drill 8.75 inch production hole to 7750 ft then 6.75 inch hole to 18395 ft. 4/9/2023: Run 5.5 inch 20 lb P-110 production casing to 18376 ft MD. Pump 40 bbls gel spacer, then 555 sks of 10.5 ppg lead cmt then 1130 sks of 13.2 ppg tail cmt. Drop plug and displace with 20 bbls MMCR water and 387 bbls fresh water. 30 bbls cement returned to surface. Est TOC at 0 ft. Surface Casing Details: Casing ran: 3/4/2023, Fluid Type Fresh Water, Hole 17.5 inch, Csg Size 13.375 inch, Weight 54.5 lbs, Grade J55, Est TOC 0 ft, Depth set 312 ft, Cement 474 sacks, Yield 1.35 tail, Class C. Pressure test: 1500 PSI, Pressure Drop: 0. Intermediate Casing Details: Casing ran: 3/19/2023, Fluid Type brine, Hole 12.55 inch to 1517, Csg Size 9.625 inch, Weight 40 lbs, Grade J-55, Est TOC 0 ft, Depth set 1502 ft, Cement 430 sks, Yield 1.90 lead/1.35 tail, Class C, Pressure Held 1500 psi, Pres Drop 0. Production Casing details: Casing Date: 4/9/2023, Fluid Type cut brine, Hole 8.75 inch hole to 7750 ft then 6.75 inch hole to 18395 ft, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 18376 ft, EST TOC 0 ft, Cement 1685 sacks, yield 3.38 lead/1.44 tail, Class C. 4/8/2023: TD Reached at 18395 ft MD, 8368 ft TVD. Plug Back Measured depth at 18324 ft MD, 8373 ft TVD. Rig Release on 4/10/2023 at 23:30

Well Name: COLD SNACK FED COM	Well Location: T25S / R25E / SEC 14 / SWNW / 32.1329447 / -104.3736346	County or Parish/State: EDDY / NM
Well Number: 211H	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:
Lease Number: NMNM28169	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001553318	Well Status: Drilling Well	Operator: TAP ROCK OPERATING LLC

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: JEFFREY TRLICA	Signed on: APR 11, 2023 09:06 AM
Name: TAP ROCK OPERATING LLC	
Title: Regulatory Analyst	
Street Address: 523 PARK POINT DRIVE SUITE 200	
City: GOLDEN	State: CO
Phone: (720) 772-5910	
Email address: JTRLICA@TAPRK.COM	

Field

Representative Name:		
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		

BLM Point of Contact

BLM POC Name: JONATHON W SHEPARD	BLM POC Title: Petroleum Engineer
BLM POC Phone: 5752345972	BLM POC Email Address: jshepard@blm.gov
Disposition: Accepted	Disposition Date: 04/14/2023
Signature: Jonathon Shepard	

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 209057

CONDITIONS

Operator: TAP ROCK OPERATING, LLC 523 Park Point Drive Golden, CO 80401	OGRID: 372043
	Action Number: 209057
	Action Type: [C-103] Sub. Drilling (C-103N)

CONDITIONS

Created By	Condition	Condition Date
smcgrath	Please run a CBL and submit to OCD Permitting/ Well Logs. The APD approved Class H cement for the production casing, but Class C was documented.	1/2/2024