

Well Name: LOGAN 35 FEDERAL	Well Location: T17S / R27E / SEC 35 / SESE / 32.7870018 / -104.242091	County or Parish/State: EDDY / NM
Well Number: 11	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM117806	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001530749	Operator: RILEY PERMIAN OPERATING COMPANY LLC	

NMOCD- Accepted for record gc 5/7/2024  
See Conditions of Approval

Notice of Intent

Sundry ID: 2783107

Type of Submission: Notice of Intent	Type of Action: Plug and Abandonment
Date Sundry Submitted: 04/02/2024	Time Sundry Submitted: 03:25
Date proposed operation will begin: 04/17/2024	

Procedure Description:

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

- Logan\_35\_Fed\_11\_WBD\_\_\_Proposed\_PA\_WBD\_20240402152455.pdf
- Logan\_35\_Fed\_11\_WBD\_current\_20240402152407.pdf
- Logan\_35\_Fed\_11\_\_\_Plug\_and\_Abandon\_Procedures\_20240402152307.pdf

Well Name: LOGAN 35 FEDERAL

Well Location: T17S / R27E / SEC 35 / SESE / 32.7870018 / -104.242091

County or Parish/State: EDDY / NM

Well Number: 11

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM117806

Unit or CA Name:

Unit or CA Number:

US Well Number: 3001530749

Operator: RILEY PERMIAN OPERATING COMPANY LLC

Conditions of Approval

Specialist Review

2783107\_\_Logan\_35\_Federal\_11\_\_3001530749\_\_COA\_and\_Procedure\_20240418112408.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: DEB FIORDA

Signed on: APR 02, 2024 03:24 PM

Name: RILEY PERMIAN OPERATING COMPANY LLC

Title: REGULATORY SPECIALIST

Street Address: 29 E RENO AVENUE

City: OKLAHOMA CITY State: OK

Phone: (405) 754-6968

Email address: DEBFIORDA@RILEYPERMIAN.COM

Field

Representative Name:

Street Address:

City: State: Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: KEITH P IMMATTY

BLM POC Title: ENGINEER

BLM POC Phone: 5759884722

BLM POC Email Address: KIMMATTY@BLM.GOV

Disposition: Approved

Disposition Date: 04/18/2024

Signature: KEITH IMMATTY

Form 3160-5 (June 2019)	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT	FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2021
<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <i>Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.</i>		5. Lease Serial No. NMNM117806
		6. If Indian, Allottee or Tribe Name

<b>SUBMIT IN TRIPLICATE - Other instructions on page 2</b>		7. If Unit of CA/Agreement, Name and/or No.
1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		8. Well Name and No. LOGAN 35 FEDERAL/11
2. Name of Operator RILEY PERMIAN OPERATING COMPANY LLC		9. API Well No. 3001530749
3a. Address 29 E RENO AVENUE SUITE 500, OKLAHOMA C	3b. Phone No. (include area code) (405) 543-1411	10. Field and Pool or Exploratory Area RED LAKE/RED LAKE
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) SEC 35/T17S/R27E/NMP		11. Country or Parish, State EDDY/NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA				
TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be perfonned or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has detennined that the site is ready for final inspection.)

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) DEB FIORDA / Ph: (405) 754-6968	Title REGULATORY SPECIALIST
Signature (Electronic Submission)	Date 04/02/2024

<b>THE SPACE FOR FEDERAL OR STATE OFFICE USE</b>		
Approved by KEITH P IMMATTY / Ph: (575) 988-4722 / Approved	Title ENGINEER	Date 04/18/2024
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office CARLSBAD	

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

## GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

## SPECIFIC INSTRUCTIONS

*Item 4* - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

*Item 13*: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

## NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

## Additional Information

### Location of Well

0. SHL: SESE / 1310 FSL / 400 FEL / TWSP: 17S / RANGE: 27E / SECTION: 35 / LAT: 32.7870018 / LONG: -104.242091 ( TVD: 0 feet, MD: 0 feet )

BHL: SESE / 1310 FSL / 400 FEL / TWSP: 17S / SECTION: / LAT: 0.0 / LONG: 0.0 ( TVD: 0 feet, MD: 0 feet )

**Well Name:** Logan 35 Federal 11  
**API:** 30-015-30749  
**Location:** 1310' FSL, 400' FEL  
Sec 35, T17S, R27E  
**State:** Eddy Co., NM

Proposed PA

**Surface CSG**  
8 5/8", 24#, J-55  
Set @ 1142' w/500 sxs to surface

Formation	Tops
BOWERS	784
QUEEN	992
GRAYBURG	1400
PREMIER	1692
GLORIETA	3099
YESO	3188

GL: 3642'

Spot 260 sx 0-500'

11" hole

Note: Possible H2S

PBTC 1788'

Upper San Andres  
2096 TO 2505

CIBP 2046, tagged at 1781'

Lower San Andres  
2851 TO 3001

Yeso  
3210 TO 3520

7 7/8" hole

**Production CSG**  
5 1/2", 15.5#, J-55  
Set @ 3793' w/875 sxs to surface

TD 3800'

**Well Name:** Logan 35 Federal 11  
**API:** 30-015-30749  
**Location:** 1310' FSL, 400' FEL  
Sec 35, T17S, R27E  
**State:** Eddy Co., NM

CURRENT

**Surface CSG**  
8 5/8", 24#, J-55  
Set @ 1142' w/500 sxs to surface

Formation	Tops
BOWERS	784
QUEEN	992
GRAYBURG	1400
PREMIER	1692
GLORIETA	3099
YESO	3188

GL: 3642'

11" hole

Note: Possible H2S

PBTC 1788'

Upper San Andres  
2096 TO 2505

CIBP 2046, tagged at 1781'

Lower San Andres  
2851 TO 3001

Yeso  
3210 TO 3520

7 7/8" hole

**Production CSG**  
5 1/2", 15.5#, J-55  
Set @ 3793' w/875 sxs to surface

TD 3800'



**Logan 35 Federal 11**  
**Procedure to P&A**  
**AFE: 24PA0001**  
**API # 30-015-30749**  
**1310' FSL & 400' FEL**  
**Sec 35-T17S-R27E**  
**Eddy County, New Mexico**

---

**GL: 3642' MD**  
**TD: 3800' MD**

**Current PBTD: 1788'**

All perms are currently plugged off by CIBP and cement.

**Deviation: Vertical**

Perfs ordered top-down				
Form	Top	Bot	Plugged?	Plug Method
Upper San Andres	2096	2505	Y	CIBP @ 2046', tagged plug @ 1788'
Lower San Andres	2851	3001	Y	CIBP @ 2046', tagged plug @ 1788'
Yeso	3210	3520	Y	CIBP @ 2046', tagged plug @ 1788'

**PRESENT WELL DATA**

Material	Description	Burst (psi) (100%)	Burst (psi) (80%)	Collapse (psi)	ID (in)	Drift (in)
Surface Casing	8 5/8" 24# J-55 @ 1142'	2,950	2,360	1,370	8.097	7.972
Production Casing	5 1/2" 15.5# J-55 @ Surf – 3,793'	4,810	3,848	4,040	4.950	4.825

**FORMATION DATA**

Zone	Depth	EST BHP EST BHT
"Yeso & San Andres"	~3,400' TVD AVE.	~1,000 psi 106° F





**Logan 35 Federal 11**  
**Procedure to P&A**  
**AFE: 24PA0001**  
**API # 30-015-30749**  
**1310' FSL & 400' FEL**  
**Sec 35-T17S-R27E**  
**Eddy County, New Mexico**

**RILEY EXPLORATION REQUIRES HARD HATS, STEEL TOED BOOTS, FRC AND SAFETY GLASSES TO BE WORN ON LOCATION.**

**HOLD SAFETY MEETING PRIOR TO COMMENCING OPERATIONS.**

The well is currently temporarily abandoned with all perfs plugged off with a cast iron bridge plug and cement on top. The objective of this procedure is to finish the plugging requirements as per NMOCD.

**PROCEDURE:**

1. Notifications
  - a. Contact the appropriate BLM office at least 24 hours prior to the commencement of any plugging operations. For wells in Eddy County, call 575-361-2822
  - b. Contact Production Foreman, Steve Forister (505) 400-4571, prior to commencing ops. Check anchor tags prior to RU to ensure anchors have been tested in the last 2 years.
2. Check wellhead pressure on 8-5/8" x 5 1/2" annulus and report.
  - a. Note: Remain aware of the possibility of H2S.
3. MIRU plugging rig and equipment.
4. During the TA procedures, the hole was filled with packer fluid. The last available report shows that the only equipment still in hole is 1 joint of 2-7/8" tubing hanging from wellhead.
5. Confirm hole is full and top off with MLF (minimum 9 ppg). Pressure test casing to 500 psi for 30 mins. Chart and report.

Plug Info										
Plug	Plug Length, ft	Plug Btm, ft	Plug Top, ft	Inner Capacity, bbl	Annular Cap., bbl	Excess into perfs, bbl	Total cmt, bbl	Total cmt, sx	Disp. Mud, bbl	Perf /Cir c
Surf Plug	500	500	0	31.8	17.2		49.0	260		*



**Logan 35 Federal 11**  
**Procedure to P&A**  
**AFE: 24PA0001**  
**API # 30-015-30749**  
**1310' FSL & 400' FEL**  
**Sec 35-T17S-R27E**  
**Eddy County, New Mexico**

---

The table above represents all the plugs required for the completion of this job, and it is for reference, only. Please proceed with the below procedures in the steps they are presented.

6. Spot 260 sx cement plug @ 500' to surface.
7. Cut off wellhead. Verify cement @ surface.
8. Weld on dry hole marker.
9. Trash – clean all trash, junk, and other waste material from the location.
10. The rig used for the plugging procedure cannot be released and moved off without the approval of the authorized officer. Once approved, RDMO.



**Logan 35 Federal 11**  
**Procedure to P&A**  
**AFE: 24PA0001**  
**API # 30-015-30749**  
**1310' FSL & 400' FEL**  
**Sec 35-T17S-R27E**  
**Eddy County, New Mexico**

---

**In Case of an Emergency Call – 911**  
**Artesia NM Ambulance – 575-746-5051**  
**Artesia General Hospital – 575-748-3333**

**GPS Coordinates of Well Head:**  
Lat = 32.786983 N Long = -104.242119 W

**Riley Permian Operating Company**

**Corporate Office**

29 E. Reno Ave  
Oklahoma City, OK 73104  
Ph: 405-415-8600

Name	Title	Office No.	Mobile No.
Bobby Riley	President & CEO	(405) 415-8683	(405) 795-0007
Dan Doherty	Sr. VP Eng & Ops	(405) 768-1015	(405) 227-9174
Taylor Vincent	Operations Engineer		(337) 852-3192
Austin Cantwell	Operations Engineer		(832) 217-9994
Spence Laird	EH&S Manager	(405) 543-1411	
Steve Forister	Production Foreman		(505) 400-4571



**Logan 35 Federal 11**  
**Procedure to P&A**  
**AFE: 24PA0001**  
**API # 30-015-30749**  
**1310' FSL & 400' FEL**  
**Sec 35-T17S-R27E**  
**Eddy County, New Mexico**

---

**GL: 3642' MD**  
**TD: 3800' MD**

**Current PBTD: 1788'**

All perms are currently plugged off by CIBP and cement.

**Deviation: Vertical**

Perfs ordered top-down				
Form	Top	Bot	Plugged?	Plug Method
Upper San Andres	2096	2505	Y	CIBP @ 2046', tagged plug @ 1788'
Lower San Andres	2851	3001	Y	CIBP @ 2046', tagged plug @ 1788'
Yeso	3210	3520	Y	CIBP @ 2046', tagged plug @ 1788'

**PRESENT WELL DATA**

Material	Description	Burst (psi) (100%)	Burst (psi) (80%)	Collapse (psi)	ID (in)	Drift (in)
Surface Casing	8 5/8" 24# J-55 @ 1142'	2,950	2,360	1,370	8.097	7.972
Production Casing	5 1/2" 15.5# J-55 @ Surf – 3,793'	4,810	3,848	4,040	4.950	4.825

**FORMATION DATA**

Zone	Depth	EST BHP EST BHT
"Yeso & San Andres"	~3,400' TVD AVE.	~1,000 psi 106° F



**Logan 35 Federal 11**  
**Procedure to P&A**  
**AFE: 24PA0001**  
**API # 30-015-30749**  
**1310' FSL & 400' FEL**  
**Sec 35-T17S-R27E**  
**Eddy County, New Mexico**

**RILEY EXPLORATION REQUIRES HARD HATS, STEEL TOED BOOTS, FRC AND SAFETY GLASSES TO BE WORN ON LOCATION.**

**HOLD SAFETY MEETING PRIOR TO COMMENCING OPERATIONS.**

The well is currently temporarily abandoned with all perfs plugged off with a cast iron bridge plug and cement on top. The objective of this procedure is to finish the plugging requirements as per NMOCD.

**PROCEDURE:**

1. Notifications
  - a. Contact the appropriate BLM office at least 24 hours prior to the commencement of any plugging operations. For wells in Eddy County, call 575-361-2822
  - b. Contact Production Foreman, Steve Forister (505) 400-4571, prior to commencing ops. Check anchor tags prior to RU to ensure anchors have been tested in the last 2 years.
2. Check wellhead pressure on 8-5/8" x 5 1/2" annulus and report.
  - a. Note: Remain aware of the possibility of H2S.
3. MIRU plugging rig and equipment.
4. During the TA procedures, the hole was filled with packer fluid. The last available report shows that the only equipment still in hole is 1 joint of 2-7/8" tubing hanging from wellhead.
5. Confirm hole is full and top off with MLF (minimum 9 ppg). Pressure test casing to 500 psi for 30 mins. Chart and report.

Plug Info										
Plug	Plug Length, ft	Plug Btm, ft	Plug Top, ft	Inner Capacity, bbl	Annular Cap., bbl	Excess into perfs, bbl	Total cmt, bbl	Total cmt, sx	Disp. Mud, bbl	Perf /Cir c
Surf Plug	500	500	0	31.8	17.2		49.0	260		*

**Spot 1192' to 1180'. WOC, Tag and Verify**



**Logan 35 Federal 11  
Procedure to P&A  
AFE: 24PA0001  
API # 30-015-30749  
1310' FSL & 400' FEL  
Sec 35-T17S-R27E  
Eddy County, New Mexico**

---

The table above represents all the plugs required for the completion of this job, and it is for reference, only. Please proceed with the below procedures in the steps they are presented.

6. **Spot 1192' to 1180'. ~25sks. WOC, Tag and Verify**
7. Spot 260 sx cement plug @ 500' to surface.
8. Cut off wellhead. Verify cement @ surface.
9. Weld on dry hole marker.
10. Trash – clean all trash, junk, and other waste material from the location.
11. The rig used for the plugging procedure cannot be released and moved off without the approval of the authorized officer. Once approved, RDMO.

**KEITH  
IMMATTY** Digitally signed by  
KEITH IMMATTY  
Date: 2024.04.18  
11:23:33 -06'00'



**Logan 35 Federal 11**  
**Procedure to P&A**  
**AFE: 24PA0001**  
**API # 30-015-30749**  
**1310' FSL & 400' FEL**  
**Sec 35-T17S-R27E**  
**Eddy County, New Mexico**

---

**In Case of an Emergency Call – 911**  
**Artesia NM Ambulance – 575-746-5051**  
**Artesia General Hospital – 575-748-3333**

**GPS Coordinates of Well Head:**  
Lat = 32.786983 N Long = -104.242119 W

**Riley Permian Operating Company**

**Corporate Office**

29 E. Reno Ave  
Oklahoma City, OK 73104  
Ph: 405-415-8600

Name	Title	Office No.	Mobile No.
Bobby Riley	President & CEO	(405) 415-8683	(405) 795-0007
Dan Doherty	Sr. VP Eng & Ops	(405) 768-1015	(405) 227-9174
Taylor Vincent	Operations Engineer		(337) 852-3192
Austin Cantwell	Operations Engineer		(832) 217-9994
Spence Laird	EH&S Manager	(405) 543-1411	
Steve Forister	Production Foreman		(505) 400-4571

**Well Name:** Logan 35 Federal 11  
**API:** 30-015-30749  
**Location:** 1310' FSL, 400' FEL  
Sec 35, T17S, R27E  
**State:** Eddy Co., NM

**Proposed PA**

**Surface CSG**  
8 5/8", 24#, J-55  
Set @ 1142' w/500 sxs to surface

Formation	Tops
BOWERS	784
QUEEN	992
GRAYBURG	1400
PREMIER	1692
GLORIETA	3099
YESO	3188

GL: 3642'

Spot 260 sx 0-500'

11" hole

Spot 1192' to 1180'. WOC, Tag and Verify

Note: Possible H2S

PBTC 1788'

Upper San Andres  
2096 TO 2505

CIBP 2046, tagged at 1781'

Lower San Andres  
2851 TO 3001

Yeso  
3210 TO 3520

7 7/8" hole

**Production CSG**  
5 1/2", 15.5#, J-55  
Set @ 3793' w/875 sxs to surface

TD 3800'



**Well Name:** Logan 35 Federal 11  
**API:** 30-015-30749  
**Location:** 1310' FSL, 400' FEL  
Sec 35, T17S, R27E  
**State:** Eddy Co., NM

CURRENT

**Surface CSG**  
8 5/8", 24#, J-55  
Set @ 1142' w/500 sxs to surface

Formation	Tops
BOWERS	784
QUEEN	992
GRAYBURG	1400
PREMIER	1692
GLORIETA	3099
YESO	3188

GL: 3642'

11" hole

Note: Possible H2S

PBTC 1788'

Upper San Andres  
2096 TO 2505

CIBP 2046, tagged at 1781'

Lower San Andres  
2851 TO 3001

Yeso  
3210 TO 3520

7 7/8" hole

**Production CSG**  
5 1/2", 15.5#, J-55  
Set @ 3793' w/875 sxs to surface

TD 3800'

Sundry ID 2783107

Plug Type	Top	Bottom	Length	Tag	Sacks	Notes
Surface Plug	0.00	500.00	500.00	Verify circulated to surface	260.00	Surface, FW, Yates and Karst plug
Yates @ 135	83.65	185.00	101.35			
Fresh Water @ 350	296.50	400.00	103.50			
Shoe Plug	1080.58	1192.00	111.42	WOC and Tag	25.00	
CIBP Plug	2011.00	2046.00	35.00	WOC and Tag		Leak test 500psi, 30mins

No more than 2000' is to be allowed between plugs in open hole, and no more than 3000' between plugs in cased hole.
Class H >7500'
Class C<7500'
Fluid used to mix the cement in R111P shall be saturated with the salts common to the section penetrated, and in suitable proportions, but not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.
Critical, High Cave Karst: Cave Karst depth to surface
R111P: Solid plug in all annuli - 50' from bottom of salt to surface.

Class C: 1.32 ft^3/sx
Class H: 1.06 ft^3/sx

Onshore Order 2.III.G Drilling Abandonment Requirements: "All formations bearing usable-quality water, oil, gas, or geothermal resources, and/or a prospectively valuable deposit of minerals shall be protected.

Cave Karst/Potash Cement	High	KARST DEPTH/TOS to surface	500.00
--------------------------	------	----------------------------	--------

Shoe @	1142.00
Shoe @	3793.00

Perforatons Top @	2096.00	Perforations	3520.00
-------------------	---------	--------------	---------

CIBP @	2046.00
--------	---------

**BUREAU OF LAND MANAGEMENT  
Carlsbad Field Office  
620 East Greene Street  
Carlsbad, New Mexico 88220  
575-234-5972**

**Permanent Abandonment of Federal Wells  
Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from the approval date of this Notice of Intent to Abandon.

**If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.**

**The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.**

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-689-5981.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours. Tagging the plug means running in the hole with a string of tubing or drill pipe and placing sufficient weight on the plug to ensure its integrity. Other methods of tagging the plug may be approved by the BLM authorized officer or BLM field representative.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified *BY PHONE* (numbers listed in 2. Notifications,) minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds). A weep hole shall be left if a metal plate is welded in place.

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



# United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Carlsbad Field Office  
620 E. Greene St.  
Carlsbad, New Mexico 88220-6292  
www.blm.gov/nm



In Reply Refer To: 1310

### Reclamation Objectives and Procedures

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo “interim” reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo “final” reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any/all contaminants, scrap/trash, equipment, pipelines and powerlines **(Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure)**. Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. **This will apply to well pads, facilities, and access roads.** Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

- have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
  6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
  7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos  
Supervisory Petroleum Engineering Tech/Environmental Protection Specialist  
575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias  
Environmental Protection Specialist  
575-234-6230

Crisha Morgan  
Environmental Protection Specialist  
575-234-5987

Jose Martinez-Colon  
Environmental Protection Specialist  
575-234-5951

Mark Mattozzi  
Environmental Protection Specialist  
575-234-5713

Robert Duenas  
Environmental Protection Specialist  
575-234-2229

Doris Lauger Martinez  
Environmental Protection Specialist  
575-234-5926

Jaden Johnston  
Environmental Protection Asst. (Intern)  
575-234-6252

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

CONDITIONS  
  
Action 336060

CONDITIONS

Operator: RILEY PERMIAN OPERATING COMPANY, LLC 29 E Reno Avenue, Suite 500 Oklahoma City, OK 73104	OGRID: 372290
	Action Number: 336060
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	Must set CIBP @ 3160' test 500psi/30min. Dump Bail 35' cement. Set CIBP @ 2046'. Spot 15 sacks cement at 1450' - 1350'. T Grayburg. Spot 15 sacks cement at 1040' - 940' T Queen.	5/7/2024