R	U.S. Department of the Interior BUREAU OF LAND MANAGEMENT		Sundry Print Report 09/17/2024
	Well Name: AVION FEDERAL	Well Location: T23S / R32E / SEC 22 / SESE / 32.2856178 / -103.6550357	County or Parish/State: LEA /
	Well Number: 02	Type of Well: OIL WELL	Allottee or Tribe Name:
	Lease Number: NMNM88163	Unit or CA Name:	Unit or CA Number:
	US Well Number: 3002533862	Operator: COG OPERATING LLC	

Notice of Intent

Sundry ID: 2794613

Type of Submission: Notice of Intent

Date Sundry Submitted: 06/11/2024

Date proposed operation will begin: 09/10/2024

Type of Action: Plug and Abandonment Time Sundry Submitted: 08:50

Procedure Description: Notify BLM. MIRU Set 4 1/2" CIBP @8,145' with 3 sx class "H" cmt dumpbailed on top. Circ hole with 10 ppg brine. Pressure test to 500 psi for 30 min Spot 25 sx class "H" cmt from 7,068-6,718'. (Brushy Canyon) Perf and Squeeze 30 sx class "C" cmt with CaCl from 5,786-5,586'. WOC 4 hrs. &Tag. (Cherry Canyon) Perf & Squeeze 30 sx class "C" cmt with CaCl from 4,930' to 4,730'. OC 4 hrs. & Tag. (Bell Canyon/ Inter Shoe) Perf & Squeeze 30 sxs class "C" cmt with CaCl from 2,000' to 1,800'. OC 4 hrs. & Tag. (Spacer) Perf & Circ 100 sx class "C" cmt from 675' to surface. (Surface shoe,Surface Plug) Cut off wellhead, verify cmt at surface, weld on Dry Hole Marker.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Avion_Federal_2_Proposed_WBD_20240611085009.pdf

Avion_Federal_2_Current_WBD_20240611085002.pdf

Avion_Federal_2_Proposed_NOI_20240611084950.pdf

Received by OCD: 9/17/2024 8:39:59 AM Well Name: AVION FEDERAL	Well Location: T23S / R32E / SEC 22 / SESE / 32.2856178 / -103.6550357	County or Parish/State: LEA
Well Number: 02	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM88163	Unit or CA Name:	Unit or CA Number:
US Well Number: 3002533862	Operator: COG OPERATING LLC	
	-)
Conditions of Approv	<i>r</i> al	
Specialist Review		
Avion_Fed_2_P_A_Revised_Procedu	re_20240914150409.pdf	

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: RUTH SHOCKENCY

Signed on: JUN 11, 2024 08:50 AM

Name: COG OPERATING LLC

Title: Regulatory Analyst

Street Address: 600 W. ILLINOIS AVE.

City: MIDLAND

Phone: (575) 703-8321

Email address: RUTH.SHOCKENCY@CONOCOPHILLIPS.COM

State:

State: TX

Field

Representative Name: Street Address:

Phone:

City:

Email address:

BLM Point of Contact

BLM POC Name: ZOTA M STEVENS BLM POC Phone: 5752345998 Disposition: Approved Signature: Zota Stevens

BLM POC Title: Petroleum Engineer BLM POC Email Address: ZSTEVENS@BLM.GOV Disposition Date: 09/14/2024

Zip:

K

Received by OCD: 9/17	/2024 8:3	39:59 AM					Page 3 of
Form 3160-5 (June 2019)	ES NTERIOR AGEMENT			ON Expir 5. Lease Serial No. NN	ORM APPROVED MB No. 1004-0137 res: October 31, 2021 MNM88163		
Do not u	se this f	OTICES AND REPO orm for proposals a Jse Form 3160-3 (A	o drill or to	o re-enter an		6. If Indian, Allottee or	Iribe Name
S	JBMIT IN T	RIPLICATE - Other instru	uctions on pag	e 2		7. If Unit of CA/Agreer	ment, Name and/or No.
1. Type of Well V Oil Well	Gas W	/ell Other				8. Well Name and No.	AVION FEDERAL/02
2. Name of Operator COG	OPERATIN	NG LLC				9. API Well No. 30025	33862
3a. Address 600 West Illin			3b. Phone No. (432) 683-744	(include area cod 43	le)	10. Field and Pool or E: DIAMONDTAIL/DIA	xploratory Area
4. Location of Well (Footag SEC 22/T23S/R32E/NM		.,M., or Survey Description,				11. Country or Parish, S LEA/NM	State
	12. CHEC	CK THE APPROPRIATE B	OX(ES) TO INI	DICATE NATUR	E OF NOTI	ICE, REPORT OR OTHI	ER DATA
TYPE OF SUBMISS	ION			TY	PE OF AC	TION	
Notice of Intent Subsequent Report		Acidize Alter Casing Casing Repair Change Plans	New	en aulic Fracturing Construction and Abandon	Recl	luction (Start/Resume) amation omplete porarily Abandon	Water Shut-Off Well Integrity Other
Final Abandonment	Notice	Convert to Injection	Plug	Back	Wate	er Disposal	
the proposal is to deepe the Bond under which the completion of the invol-	n directional ne work will ved operatio onment Not	lly or recomplete horizontal be perfonned or provide th ns. If the operation results in	ly, give subsurfa e Bond No. on f 1 a multiple com	ice locations and n ile with BLM/BIA apletion or recomp	measured and A. Required pletion in a	nd true vertical depths of subsequent reports must new interval, a Form 310	k and approximate duration thereof. If Sall pertinent markers and zones. Attach t be filed within 30 days following 60-4 must be filed once testing has been e operator has detennined that the site
Notify BLM. MIRU							
Set 4 1/2" CIBP @8	,145' with 3	3 sx class "H" cmt dumpb	ailed on top.				
	-	essure test to 500 psi for					
		7,068-6,718'. (Brushy Ca		~			
4 hrs. &Tag. (Cherry		"C" cmt with CaCl from 5	786-5,586′. W	OC			
		" cmt with CaCl from 4,93	20' to 1 730'				
OC 4 hrs. & Tag. (B			10 10 4,700 .				
	-	C" cmt with CaCl from 2,0	000' to 1,800'.				
OC 4 hrs. & Tag. (S							
Perf & Circ 100 sx c	lass "C" cn	nt from 675' to surface. (S	Surface shoe,S	urface Plug)			
Cut off wellhead, ve	rify cmt at s	surface, weld on Dry Hole	e Marker.				
14. I hereby certify that the f	oregoing is	true and correct. Name (Pr	inted/Typed)				
RUTH SHOCKENCY / P	h: (575) 70	3-8321		Regulato Title	ry Analyst		
(Electronic Signature	Submissio	n)		Date		06/11/20	24
		THE SPACE	FOR FED	ERAL OR ST		ICE USE	
						1	

Approved by		
ZOTA M STEVENS / Ph: (575) 234-5998 / Approved	Petroleum Engineer Title	09/14/2024 Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office CARLSBAD	
	·	

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

0. SHL: SESE / 990 FSL / 330 FEL / TWSP: 23S / RANGE: 32E / SECTION: 22 / LAT: 32.2856178 / LONG: -103.6550357 (TVD: 0 feet, MD: 0 feet) BHL: SESE / 990 FSL / 330 FEL / TWSP: 23S / SECTION: / LAT: 0.0 / LONG: 0.0 (TVD: 0 feet, MD: 0 feet)

•

COG Operating	g		PROPOSED		Description	0.D.	Grade	Weight	Depth	Hole	Cmt Sx	TOC
Author:	Kelton @ JMR				Surf Csg	13.325		48	625	17 1/2	800	Surface
Well Name	Avion Federal	Well No.	2									
Field/Pool County	Delaware Lea	API #: Location:	30-025-33862 Sec 22, T23S, R32E		Interm Csg	8.625	J55	24	4,874	11	1,656	Surface
State	NM		990'FSL &330'FEL	-,								
Spud Date	2/4/1999	GL:	3660'		Prod Csg	4.5	K55	11.6	8,410	7 7/8	290	6,898
·											Formation	Тор
											Durat	440
											Rust	119 488
											Bcyn Ccyn	573
											Bcyn	701
		13 3/8	3 48 CSG @	625							Bones Sp	875
411				ass "C" cmt from (675' to surface.	(Surfac	e shoe	. Surface P	lua)			
						(,	5,			
		7. Per	f & Squeeze 30 s	xs class "C" cmt w	vith CaCl from 2	2.000' to	1.800'	WOC 4 hr	s. & Taq	(Space	er)	
		/e	i a oqueeze oo o			.,000 10	1,000		3. u 1ag	. (opace	1)	
		0.5/0	24 Csg @									
				2 500								
4		N 8 5/8		3,500 x alaaa "C" amt wi	th CoCl from 4	0201 40	4 7201		• Tog		nvon/Intor	Chao)
				3,500 x class "C" cmt wi	ith CaCl from 4,	930' to 4	4,730'.	WOC 4 hrs	. & Tag.	(Bell Ca	nyon/ Inter	Shoe)
4					ith CaCl from 4,9	930' to 4	4,730'.	WOC 4 hrs	. & Tag.	(Bell Ca	nyon/ Inter	Shoe)
					ith CaCl from 4,	930' to 4	4,730'. '	WOC 4 hrs	. & Tag.	(Bell Ca	nyon/ Inter	Shoe)
И					ith CaCl from 4,	930' to 4	4,730'. '	WOC 4 hrs	. & Tag.	(Bell Ca	nyon/ Inter	Shoe)
					ith CaCl from 4,	930' to 4	4,730'. '	WOC 4 hrs	. & Tag.	(Bell Ca	nyon/ Inter a	Shoe)
					ith CaCl from 4,	930' to 4	4,730'. '	WOC 4 hrs	. & Tag.	(Bell Ca	nyon/ Inter :	Shoe)
					ith CaCl from 4,	930' to 4	4,730'. '	WOC 4 hrs	. & Tag.	(Bell Ca	nyon/ Inter :	Shoe)
		6. Per	f & Squeeze 30 s	x class "C" cmt wi								Shoe)
		6. Per	f & Squeeze 30 s									Shoe)
		6. Per	f & Squeeze 30 s f and Squeeze 30	x class "C" cmt wi								Shoe)
		6. Per	f & Squeeze 30 s	x class "C" cmt wi								Shoe)
		6. Per	f & Squeeze 30 s f and Squeeze 30	x class "C" cmt wi								Shoe)
		6. Per	f & Squeeze 30 s f and Squeeze 30	x class "C" cmt wi								Shoe)
		6. Per 5. Per	f & Squeeze 30 s; f and Squeeze 30 TOC ~ 6,898'	x class "C" cmt wi) sx class "C" cmt	with CaCl from	5,786-5	,586'. V					Shoe)
		6. Per 5. Per	f & Squeeze 30 s; f and Squeeze 30 TOC ~ 6,898'	x class "C" cmt wi	with CaCl from	5,786-5	,586'. V					Shoe)
		6. Per 5. Per	f & Squeeze 30 s; f and Squeeze 30 TOC ~ 6,898'	x class "C" cmt wi) sx class "C" cmt	with CaCl from	5,786-5	,586'. V					Shoe)
		6. Per 5. Per	f & Squeeze 30 s; f and Squeeze 30 TOC ~ 6,898'	x class "C" cmt wi) sx class "C" cmt	with CaCl from	5,786-5	,586'. V					Shoe)
		6. Per 5. Per	f & Squeeze 30 s; f and Squeeze 30 TOC ~ 6,898'	x class "C" cmt wi) sx class "C" cmt	with CaCl from	5,786-5	,586'. V					Shoe)
		6. Per 5. Per	f & Squeeze 30 sy f and Squeeze 30 TOC ~ 6,898'	x class "C" cmt wi) sx class "C" cmt	with CaCl from	5,786-5	,586'. V					Shoe)
		6. Per 5. Per 4. Spo	f & Squeeze 30 sy f and Squeeze 30 TOC ~ 6,898' ot 25 sx class "H"	x class "C" cmt wi) sx class "C" cmt ¹ cmt from 7,068-6,	with CaCl from 718'. (Brushy C	5,786-5 anyon)	,586'. V	VOC 4 hrs.				Shoe)
		6. Per 5. Per 4. Spo 3. Ciru	f & Squeeze 30 sy f and Squeeze 30 TOC ~ 6,898' ot 25 sx class "H" c hole with 10 ppg	x class "C" cmt wi) sx class "C" cmt ¹ cmt from 7,068-6, g brine. Pressure t	with CaCl from 718'. (Brushy C	5,786-5 anyon) 500 psi 1	,586'. ₩ for 30 r	VOC 4 hrs. nin				Shoe)
		6. Per 5. Per 4. Spo 3. Cirr 2. Set	f & Squeeze 30 s; f and Squeeze 30 TOC ~ 6,898' ot 25 sx class "H" c hole with 10 ppg : 4 1/2" CIBP @8;	x class "C" cmt wi) sx class "C" cmt ¹ cmt from 7,068-6,	with CaCl from 718'. (Brushy C	5,786-5 anyon) 500 psi 1	,586'. ₩ for 30 r	VOC 4 hrs. nin				Shoe)
		6. Per 5. Per 4. Spo 3. Cir 2. Set 1. Not	f & Squeeze 30 sy f and Squeeze 30 TOC ~ 6,898' ot 25 sx class "H" c hole with 10 ppg t 4 1/2" CIBP @8, tify BLM. MIRU	x class "C" cmt wi 9 sx class "C" cmt 1 cmt from 7,068-6, g brine. Pressure t 145' with 3 sx clas	with CaCl from 718'. (Brushy C	5,786-5 anyon) 500 psi 1	,586'. ₩ for 30 r	VOC 4 hrs. nin				Shoe)
		6. Per 5. Per 4. Spo 3. Cir 2. Set 1. Not	f & Squeeze 30 s; f and Squeeze 30 TOC ~ 6,898' ot 25 sx class "H" c hole with 10 ppg : 4 1/2" CIBP @8;	x class "C" cmt wi 9 sx class "C" cmt 1 cmt from 7,068-6, g brine. Pressure t 145' with 3 sx clas	with CaCl from 718'. (Brushy C	5,786-5 anyon) 500 psi 1	,586'. ₩ for 30 r	VOC 4 hrs. nin				Shoe)
		6. Per 5. Per 4. Spo 3. Cir 2. Set 1. Not	f & Squeeze 30 sy f and Squeeze 30 TOC ~ 6,898' ot 25 sx class "H" c hole with 10 ppg t 4 1/2" CIBP @8, tify BLM. MIRU	x class "C" cmt wi 9 sx class "C" cmt 1 cmt from 7,068-6, g brine. Pressure t 145' with 3 sx clas	with CaCl from 718'. (Brushy C	5,786-5 anyon) 500 psi 1	,586'. ₩ for 30 r	VOC 4 hrs. nin				Shoe)
		6. Per 5. Per 4. Spo 3. Cir 2. Set 1. Not	f & Squeeze 30 sy f and Squeeze 30 TOC ~ 6,898' ot 25 sx class "H" c hole with 10 ppg t 4 1/2" CIBP @8, tify BLM. MIRU	x class "C" cmt wi 9 sx class "C" cmt 1 cmt from 7,068-6, g brine. Pressure t 145' with 3 sx clas	with CaCl from 718'. (Brushy C	5,786-5 anyon) 500 psi 1	,586'. ₩ for 30 r	VOC 4 hrs. nin				Shoe)
		6. Per 5. Per 4. Spo 3. Cir 2. Set 1. Not	f & Squeeze 30 s; f and Squeeze 30 TOC ~ 6,898' ot 25 sx class "H" c hole with 10 ppg : 4 1/2" CIBP @8; tify BLM. MIRU @ 8,195' to 8,208	x class "C" cmt wi) sx class "C" cmt ' cmt from 7,068-6, g brine. Pressure t 145' with 3 sx clas 3'	with CaCl from 718'. (Brushy C test csg&CIBP 5 is "H" cmt dump	5,786-5 anyon) 500 psi 1	,586'. ₩ for 30 r	VOC 4 hrs. nin				Shoe)
		6. Per 5. Per 4. Spo 3. Cir 2. Set 1. Not	f & Squeeze 30 sy f and Squeeze 30 TOC ~ 6,898' ot 25 sx class "H" c hole with 10 ppg t 4 1/2" CIBP @8, tify BLM. MIRU	x class "C" cmt wi 9 sx class "C" cmt 1 cmt from 7,068-6, g brine. Pressure t 145' with 3 sx clas	with CaCl from 718'. (Brushy C test csg&CIBP 5 is "H" cmt dump	5,786-5 anyon) 500 psi 1	,586'. ₩ for 30 r	VOC 4 hrs. nin				Shoe)
TDPB @ TD @		6. Per 5. Per 4. Spo 3. Cir 2. Set 1. Not	f & Squeeze 30 s; f and Squeeze 30 TOC ~ 6,898' ot 25 sx class "H" c hole with 10 ppg : 4 1/2" CIBP @8; tify BLM. MIRU @ 8,195' to 8,208	x class "C" cmt wi) sx class "C" cmt ' cmt from 7,068-6, g brine. Pressure t 145' with 3 sx clas 3'	with CaCl from 718'. (Brushy C test csg&CIBP 5 is "H" cmt dump	5,786-5 anyon) 500 psi 1	,586'. ₩ for 30 r	VOC 4 hrs. nin				Shoe)

•

	ng	C	URRENT			Description	0.D.	Grade	Weight	Depth	Hole	Cmt Sx	TOC
Author:	JJC					Surf Csg	13.325		48	625	17 1/2		Surface
Vell Name	Avion Federal	Well No.	2			Sun Csy	13.323	11-40	40	020	17 1/2	000	Surrace
ield/Pool	Delaware	API #:	30-025-33			Interm Csg	8.625	J55	24	4,874	11	1,656	Surface
County	Lea	Location:				interim 65g	0.020	000		4,014	••	1,000	Ourrace
State Spud Date	NM 2/4/1999	GL:	990'FSL 8	\$330'FEL		Prod Csg	4.5	K55	11.6	8,410	7 7/8	290	6,898
·							u					Formation	Тор
												Davia	40
												Bcyn	488 573
												Ccyn	573 701
			13.325	48 CSG @	625							Bcyn Bones Sp	875
4			13.325	40 000 @	025							Dones op	01.
_													
		IN											
			8.625	24 Csg @	1 971								
			0.020	24 03g @	4,014								
į.													
		1											
Į.													
4													
i		i											
i		li											
!													
i			TOC ~ 6	202'									
			100~0	,090									
i i													
-													
		Perfs	@ 8 195'	to 8 208'									
		Perfs (@ 8,195'	to 8,208'									
		Perfs (@ 8,195'	to 8,208'									
		Perfs											
	@ 0.004	Perfs (to 8,208' 11.6 CSG @	8,410								
	@ 8,364' @ 8,410'	Perfs (8,410								

Plug Abandonment NOI Proposed

OPERATOR NAME: COG Operating LLC LEASE NO.: NMNM88163 WELL NAME & NO.: Avion Federal #2 US WELL NUMBER: 30-025-33862 LOCATION: Sec 22, T23S, R32E COUNTY: Lea County, NM

1. Notify BLM. MIRU

2. Set 4 1/2" CIBP @8,145' with 3 sx class "H" cmt dumpbailed on top.

3. Circ hole with 10 ppg brine. Pressure test to 500 psi for 30 min

4. Spot 25 sx class "H" cmt from 7,068-6,718'. (Brushy Canyon)

5. Perf and Squeeze 30 sx class "C" cmt with CaCl from 5,786-5,586'. WOC

4 hrs. & Tag. (Cherry Canyon)

6. Perf & Squeeze 30 sx class "C" cmt with CaCl from 4,930' to 4,730'.

WOC 4 hrs. & Tag. (Bell Canyon/ Inter Shoe)

7. Perf & Squeeze 30 sxs class "C" cmt with CaCl from 2,000' to 1,800'. WOC 4 hrs. & Tag. (Spacer)

8. Perf & Circ 100 sx class "C" cmt from 675' to surface. (Surface shoe, Surface Plug)

9. Cut off wellhead, verify cmt at surface, weld on Dry Hole Marker.

BLM P&A Procedure

1. Notify BLM. MIRU

- 2. Set 4 1/2" CIBP @8,145' with 35ft class "H" cmt dump bailed on top. Pressure Test. WOC and TAG
- 3. Spot 25 sx class "H" cmt from 7,068-6,718'. (Brushy Canyon)
- 4. Perf and Squeeze 30 sx class "C" cmt with CaCl from 5,786-5,586'. WOC 4 hrs. & Tag. (Cherry Canyon)
- Perf & Squeeze 30 sx class "C" cmt with CaCl from 4,930' to 4,730'. WOC 4 hrs. & Tag. (Bell Canyon/ Inter Shoe)
- 6. Perf & Squeeze 30 sxs class "C" cmt with CaCl from 2,000' to 1,800'. WOC 4 hrs. & Tag. (Spacer)
- 7. Perf & Circ 100 sx class "C" cmt from 675' to surface. (Surface shoe, Surface Plug)
- 8. Cut off wellhead, verify cmt at surface, weld on Dry Hole Marker.

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-689-5981.

3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds). A weep hole shall be left if a metal plate is welded in place.

7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any/all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech/Environmental Protection Specialist 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist 575-234-5987

Jose Martinez-Colon Environmental Protection Specialist 575-234-5951

Mark Mattozzi Environmental Protection Specialist 575-234-5713

Robert Duenas Environmental Protection Specialist 575-234-2229

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612

District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:
COG OPERATING LLC	229137
600 W Illinois Ave	Action Number:
Midland, TX 79701	384169
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition
		Date
gcordero	Run CBL from 8145' to surface CBL must be submitted to OCD via OCD Permitting prior to submitting C-103P	9/26/2024

Page 15 of 15

Action 384169