

Form 3160-5
(June 2019)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 2021

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.	NMNM113420
6. If Indian, Allottee or Tribe Name	

SUBMIT IN TRIPLICATE - Other instructions on page 2		7. If Unit of CA/Agreement, Name and/or No.
1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		8. Well Name and No. PISTOLERO 15 FED COM/432H
2. Name of Operator EOG RESOURCES INCORPORATED		9. API Well No. 30-025-52636
3a. Address 1111 BAGBY SKY LOBBY 2, HOUSTON, TX 770	3b. Phone No. (include area code) (713) 651-7000	10. Field and Pool or Exploratory Area RED HILLS; UPPER BONE SPRING, SHALE
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) SEC 15/T25S/R34E/NMP		11. Country or Parish, State LEA/NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA				
TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input checked="" type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be perfonned or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has detennined that the site is ready for final inspection.)

Pistolero 15 Fed Com 307H (FKA 432H) API #: 30-025-52636

EOG respectfully requests an amendment to our approved APD for this well to reflect the following changes:

Change name from Pistolero 15 Fed Com 432H to Pistolero 15 Fed Com 307H.

Change BHL from T-25-S, R-34-E, Sec 27, 100' FSL, 1815' FWL, Lea Co., NM, to T-25-S, R-34-E, Sec 27, 100' FSL, 1250' FWL, Lea Co., N.M.

Change target formation to Leonard B.

Update casing and cement program to current design - Batch Sundry #2779173

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) STAR HARRELL / Ph: (432) 848-9161	Title Regulatory Specialist
Signature (Electronic Submission)	Date 03/11/2024

THE SPACE FOR FEDERAL OR STATE OFFICE USE		
Approved by KEITH P IMMATTY / Ph: (575) 988-4722 / Approved	Title ENGINEER	Date 03/19/2024
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office CARLSBAD	

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office
☐ AMENDED REPORT



Pistolero 15 Fed Com 307H

Revised Permit Information 02/01/2024:

Well Name: Pistolero 15 Fed Com 307H; FKA Pistolero 15 Fed Com 432H

Location: SHL: 276' FNL & 333' FWL, Section 15, T-25-S, R-34-E, Lea Co., N.M.

BHL: 100' FSL & 1250' FWL, Section 27, T-25-S, R-34-E, Lea Co., N.M.

1. CASING PROGRAM

Hole Size	Interval MD		Interval TVD		Csg OD	Weight	Grade	Conn
	From (ft)	To (ft)	From (ft)	To (ft)				
16"	0	990	0	1,000	13-3/8"	54.5#	J-55	STC
11"	0	5,233	0	5,160	9-5/8"	40#	J-55	LTC
7-7/8"	0	9,916	0	9,518	6"	22.3#	P110-EC	DWC/C IS
6-3/4"	9,916	25,905	9,518	10,352	5-1/2"	20#	P110-EC	DWC/C IS MS

**For highlighted rows above, variance is requested to run entire string of either 6" or 5-1/2" casing string above due to availability.

Variance is requested to waive the centralizer requirements for the 9-5/8" casing in the 11" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 11" hole interval to maximize cement bond and zonal isolation.

Variance is also requested to waive any centralizer requirements for the 6" and 5-1/2" casings in the 7-7/8" and 6-3/4" hole sizes. An expansion additive will be utilized, in the cement slurry, for the entire length of the 7-7/8" and 6-3/4" hole intervals to maximize cement bond and zonal isolation.

EOG requests permission to allow deviation from the 0.422" annulus clearance requirement for the intermediate (salt) section from Onshore Order #2 under the following conditions:

- The variance is not applicable within the Potash Boundaries or Capitan Reef areas.
- Operator takes responsibility to get casing to set point in the event that the clearance causes stuck pipe issues.

2. CEMENTING PROGRAM:

Depth	No. Sacks	Wt. ppg	Yld Ft3/sk	Slurry Description
1,000' 13-3/8"	260	13.5	1.73	Lead: Class C + 4.0% Bentonite Gel + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	160	14.8	1.34	Tail: Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate (TOC @ 800')
5,160' 9-5/8"	480	12.7	2.22	Lead: Class C + 10% NaCl + 6% Bentonite Gel + 3% MagOx (TOC @ Surface)
	170	14.8	1.32	Tail: Class C + 10% NaCl + 3% MagOx (TOC @ 4186')
25,905' 6"	550	10.5	3.21	Lead: Class H + 0.4% Halad-344 + 0.35% HR-601 + 3% Microbond (TOC @ 4740')
	1880	13.2	1.52	Tail: Class H + 5% NEX-020 + 0.2% NAC-102 + 0.15% NAS-725 + 0.5% NFL-549 + 0.2% NFP-703 + 1% NBE-737 + 0.3% NRT-241 (TOC @ 9950')



Pistolero 15 Fed Com 307H

Additive	Purpose
Bentonite Gel	Lightweight/Lost circulation prevention
Calcium Chloride	Accelerator
Cello-flake	Lost circulation prevention
Sodium Metasilicate	Accelerator
MagOx	Expansive agent
Pre-Mag-M	Expansive agent
Sodium Chloride	Accelerator
FL-62	Fluid loss control
Halad-344	Fluid loss control
Halad-9	Fluid loss control
HR-601	Retarder
Microbond	Expansive Agent

Cement integrity tests will be performed immediately following plug bump.

Note: Cement volumes based on bit size plus at least 25% excess in the open hole plus 10% excess in the cased-hole overlap section.

3. MUD PROGRAM:

Depth (TVD)	Type	Weight (ppg)	Viscosity	Water Loss
0 – 1,000'	Fresh - Gel	8.6-8.8	28-34	N/c
1,000' – 5,160'	Brine	9.0-10.5	28-34	N/c
5,160' – 25,905'	Oil Base	8.8-9.5	58-68	N/c - 6



Pistolero 15 Fed Com 307H

4. VARIANCE REQUESTS:

EOG requests the additional variance(s) in the attached document(s):

Variances requested include (supporting documents attached):

- BOP Break Testing for 5M Intermediate Intervals (EOG BLM Variance 3a_b)
- Offline Cementing for Surface and Intermediate Intervals (EOG BLM Variance 3a_b)
- Salt Interval Washout Annular Clearance (EOG BLM Variance 4a)



Pistolero 15 Fed Com 307H

8. TUBING REQUIREMENTS:

EOG respectfully requests an exception to the following NMOCD rule:

- 19.15.16.10 Casing AND TUBING REQUIREMENTS:
J (3): "The operator shall set tubing as near the bottom as practical and tubing perforations shall not be more than 250 feet above top of pay zone."

With horizontal flowing and gas lifted wells an end of tubing depth placed at or slightly above KOP is a conservative way to ensure the tubing stays clean from debris, plugging, and allows for fewer well interventions post offset completion. The deeper the tubulars are run into the curve, the higher the probability is that the tubing will become stuck in sand and or well debris as the well produces over time. An additional consideration for EOT placement during artificial lift installations is avoiding the high dog leg severity and inclinations found in the curve section of the wellbore to help improve reliability and performance. Dog leg severity and inclinations tend not to hamper gas lifted or flowing wells, but they do effect other forms of artificial lift like rod pump or ESP (electric submersible pump). Keeping the EOT above KOP is an industry best practice for those respective forms of artificial lift.




Pistolero 15 Fed Com 307H

276' FNL
333' FWL
Section 15
T-25-S, R-34-E

Proposed Wellbore

API: 30-025-*****

KB: 3359'
GL: 3334'





Pistolero 15 Fed Com 307H

1. GEOLOGIC NAME OF SURFACE FORMATION:

Permian

2. ESTIMATED TOPS OF IMPORTANT GEOLOGICAL MARKERS:

Rustler	875'
Tamarisk Anhydrite	960'
Top of Salt	1,255'
Base of Salt	5,061'
Lamar	5,323'
Bell Canyon	5,346'
Cherry Canyon	6,301'
Brushy Canyon	7,887'
Bone Spring Lime	9,298'
Leonard (Avalon) Shale	9,335'
1st Bone Spring Sand	9,606'
2nd Bone Spring Shale	10,317'
2nd Bone Spring Sand	10,836'
3rd Bone Spring Carb	11,372'
3rd Bone Spring Sand	11,904'
Wolfcamp	12,358'
TD	10,352'

3. ESTIMATED DEPTHS OF ANTICIPATED FRESH WATER, OIL OR GAS:

Upper Permian Sands	0- 400'	Fresh Water
Bell Canyon	5,346'	Oil
Cherry Canyon	6,301'	Oil
Brushy Canyon	7,887'	Oil
Leonard (Avalon) Shale	9,335'	Oil
1st Bone Spring Sand	9,606'	Oil
2nd Bone Spring Shale	10,317'	Oil
2nd Bone Spring Sand	10,836'	Oil

Midland

Lea County, NM (NAD 83 NME)

Pistolero 15 Fed

#307H

OH

Plan: Plan #0.2

Standard Planning Report

28 February, 2024

Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #307H
Company:	Midland	TVD Reference:	kb=26' @ 3360.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	kb=26' @ 3360.0usft
Site:	Pistolero 15 Fed	North Reference:	Grid
Well:	#307H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #0.2		

Project	Lea County, NM (NAD 83 NME)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Pistolero 15 Fed				
Site Position:		Northing:	414,055.00 usft	Latitude:	32° 8' 7.059 N
From:	Map	Easting:	812,078.00 usft	Longitude:	103° 27' 31.217 W
Position Uncertainty:		0.0 usft	Slot Radius:	13-3/16 "	

Well	#307H					
Well Position	+N/-S	0.0 usft	Northing:	414,667.00 usft	Latitude:	32° 8' 13.278 N
	+E/-W	0.0 usft	Easting:	810,034.00 usft	Longitude:	103° 27' 54.929 W
Position Uncertainty		0.0 usft	Wellhead Elevation:	usft	Ground Level:	3,334.0 usft
Grid Convergence:		0.46 °				

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2020	8/25/2023	6.23	59.76	47,224.84263250

Design	Plan #0.2				
Audit Notes:					
Version:	Phase:	PLAN	Tie On Depth:	0.0	
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.0	0.0	0.0	176.16	

Plan Survey Tool Program	Date	2/28/2024			
Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks	
1	0.0	25,905.2 Plan #0.2 (OH)	EOG MWD+IFR1		
			MWD + IFR1		

Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #307H
Company:	Midland	TVD Reference:	kb=26' @ 3360.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	kb=26' @ 3360.0usft
Site:	Pistolero 15 Fed	North Reference:	Grid
Well:	#307H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #0.2		

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,267.0	0.00	0.00	1,267.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,699.2	8.64	75.77	1,697.5	8.0	31.5	2.00	2.00	0.00	75.77	
7,547.5	8.64	75.77	7,479.5	224.0	883.5	0.00	0.00	0.00	0.00	
7,979.7	0.00	0.00	7,910.0	232.0	915.0	2.00	-2.00	0.00	180.00	
9,944.2	0.00	0.00	9,874.5	232.0	915.0	0.00	0.00	0.00	0.00	KOP(Pistolero 15 Fed
10,164.6	26.46	180.00	10,087.2	182.0	915.0	12.00	12.00	81.65	180.00	FTP(Pistolero 15 Fed
10,694.2	90.00	179.55	10,351.9	-245.5	917.3	12.00	12.00	-0.09	-0.51	
15,445.9	90.00	179.55	10,352.0	-4,997.0	955.0	0.00	0.00	0.00	0.00	Fed PP1(Pistolero 15
16,764.9	90.00	179.50	10,352.0	-6,316.0	966.0	0.00	0.00	0.00	-88.44	Fed PP2(Pistolero 15
25,905.2	90.00	179.61	10,352.0	-15,456.0	1,037.0	0.00	0.00	0.00	90.66	PBHL(Pistolero 15 Fe

Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #307H
Company:	Midland	TVD Reference:	kb=26' @ 3360.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	kb=26' @ 3360.0usft
Site:	Pistolero 15 Fed	North Reference:	Grid
Well:	#307H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #0.2		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,267.0	0.00	0.00	1,267.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.66	75.77	1,300.0	0.0	0.2	0.0	2.00	2.00	0.00
1,400.0	2.66	75.77	1,400.0	0.8	3.0	-0.6	2.00	2.00	0.00
1,500.0	4.66	75.77	1,499.7	2.3	9.2	-1.7	2.00	2.00	0.00
1,600.0	6.66	75.77	1,599.3	4.8	18.7	-3.5	2.00	2.00	0.00
1,699.2	8.64	75.77	1,697.5	8.0	31.5	-5.9	2.00	2.00	0.00
1,800.0	8.64	75.77	1,797.2	11.7	46.2	-8.6	0.00	0.00	0.00
1,900.0	8.64	75.77	1,896.1	15.4	60.8	-11.3	0.00	0.00	0.00
2,000.0	8.64	75.77	1,994.9	19.1	75.4	-14.0	0.00	0.00	0.00
2,100.0	8.64	75.77	2,093.8	22.8	89.9	-16.7	0.00	0.00	0.00
2,200.0	8.64	75.77	2,192.7	26.5	104.5	-19.4	0.00	0.00	0.00
2,300.0	8.64	75.77	2,291.5	30.2	119.1	-22.1	0.00	0.00	0.00
2,400.0	8.64	75.77	2,390.4	33.9	133.6	-24.9	0.00	0.00	0.00
2,500.0	8.64	75.77	2,489.3	37.6	148.2	-27.6	0.00	0.00	0.00
2,600.0	8.64	75.77	2,588.1	41.3	162.8	-30.3	0.00	0.00	0.00
2,700.0	8.64	75.77	2,687.0	45.0	177.3	-33.0	0.00	0.00	0.00
2,800.0	8.64	75.77	2,785.9	48.7	191.9	-35.7	0.00	0.00	0.00
2,900.0	8.64	75.77	2,884.7	52.3	206.5	-38.4	0.00	0.00	0.00
3,000.0	8.64	75.77	2,983.6	56.0	221.0	-41.1	0.00	0.00	0.00
3,100.0	8.64	75.77	3,082.5	59.7	235.6	-43.8	0.00	0.00	0.00
3,200.0	8.64	75.77	3,181.3	63.4	250.2	-46.5	0.00	0.00	0.00
3,300.0	8.64	75.77	3,280.2	67.1	264.7	-49.3	0.00	0.00	0.00
3,400.0	8.64	75.77	3,379.0	70.8	279.3	-52.0	0.00	0.00	0.00
3,500.0	8.64	75.77	3,477.9	74.5	293.9	-54.7	0.00	0.00	0.00
3,600.0	8.64	75.77	3,576.8	78.2	308.4	-57.4	0.00	0.00	0.00
3,700.0	8.64	75.77	3,675.6	81.9	323.0	-60.1	0.00	0.00	0.00
3,800.0	8.64	75.77	3,774.5	85.6	337.6	-62.8	0.00	0.00	0.00
3,900.0	8.64	75.77	3,873.4	89.3	352.1	-65.5	0.00	0.00	0.00
4,000.0	8.64	75.77	3,972.2	93.0	366.7	-68.2	0.00	0.00	0.00
4,100.0	8.64	75.77	4,071.1	96.7	381.3	-70.9	0.00	0.00	0.00
4,200.0	8.64	75.77	4,170.0	100.4	395.8	-73.6	0.00	0.00	0.00
4,300.0	8.64	75.77	4,268.8	104.1	410.4	-76.4	0.00	0.00	0.00
4,400.0	8.64	75.77	4,367.7	107.8	425.0	-79.1	0.00	0.00	0.00
4,500.0	8.64	75.77	4,466.6	111.4	439.5	-81.8	0.00	0.00	0.00
4,600.0	8.64	75.77	4,565.4	115.1	454.1	-84.5	0.00	0.00	0.00
4,700.0	8.64	75.77	4,664.3	118.8	468.7	-87.2	0.00	0.00	0.00
4,800.0	8.64	75.77	4,763.1	122.5	483.2	-89.9	0.00	0.00	0.00
4,900.0	8.64	75.77	4,862.0	126.2	497.8	-92.6	0.00	0.00	0.00
5,000.0	8.64	75.77	4,960.9	129.9	512.4	-95.3	0.00	0.00	0.00
5,100.0	8.64	75.77	5,059.7	133.6	526.9	-98.0	0.00	0.00	0.00
5,200.0	8.64	75.77	5,158.6	137.3	541.5	-100.7	0.00	0.00	0.00

Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #307H
Company:	Midland	TVD Reference:	kb=26' @ 3360.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	kb=26' @ 3360.0usft
Site:	Pistolero 15 Fed	North Reference:	Grid
Well:	#307H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #0.2		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,300.0	8.64	75.77	5,257.5	141.0	556.1	-103.5	0.00	0.00	0.00
5,400.0	8.64	75.77	5,356.3	144.7	570.6	-106.2	0.00	0.00	0.00
5,500.0	8.64	75.77	5,455.2	148.4	585.2	-108.9	0.00	0.00	0.00
5,600.0	8.64	75.77	5,554.1	152.1	599.8	-111.6	0.00	0.00	0.00
5,700.0	8.64	75.77	5,652.9	155.8	614.3	-114.3	0.00	0.00	0.00
5,800.0	8.64	75.77	5,751.8	159.5	628.9	-117.0	0.00	0.00	0.00
5,900.0	8.64	75.77	5,850.7	163.2	643.5	-119.7	0.00	0.00	0.00
6,000.0	8.64	75.77	5,949.5	166.8	658.0	-122.4	0.00	0.00	0.00
6,100.0	8.64	75.77	6,048.4	170.5	672.6	-125.1	0.00	0.00	0.00
6,200.0	8.64	75.77	6,147.2	174.2	687.2	-127.8	0.00	0.00	0.00
6,300.0	8.64	75.77	6,246.1	177.9	701.7	-130.6	0.00	0.00	0.00
6,400.0	8.64	75.77	6,345.0	181.6	716.3	-133.3	0.00	0.00	0.00
6,500.0	8.64	75.77	6,443.8	185.3	730.9	-136.0	0.00	0.00	0.00
6,600.0	8.64	75.77	6,542.7	189.0	745.4	-138.7	0.00	0.00	0.00
6,700.0	8.64	75.77	6,641.6	192.7	760.0	-141.4	0.00	0.00	0.00
6,800.0	8.64	75.77	6,740.4	196.4	774.6	-144.1	0.00	0.00	0.00
6,900.0	8.64	75.77	6,839.3	200.1	789.1	-146.8	0.00	0.00	0.00
7,000.0	8.64	75.77	6,938.2	203.8	803.7	-149.5	0.00	0.00	0.00
7,100.0	8.64	75.77	7,037.0	207.5	818.3	-152.2	0.00	0.00	0.00
7,200.0	8.64	75.77	7,135.9	211.2	832.8	-154.9	0.00	0.00	0.00
7,300.0	8.64	75.77	7,234.8	214.9	847.4	-157.7	0.00	0.00	0.00
7,400.0	8.64	75.77	7,333.6	218.6	862.0	-160.4	0.00	0.00	0.00
7,500.0	8.64	75.77	7,432.5	222.2	876.5	-163.1	0.00	0.00	0.00
7,547.5	8.64	75.77	7,479.5	224.0	883.5	-164.4	0.00	0.00	0.00
7,600.0	7.59	75.77	7,531.4	225.8	890.6	-165.7	2.00	-2.00	0.00
7,700.0	5.59	75.77	7,630.8	228.6	901.8	-167.8	2.00	-2.00	0.00
7,800.0	3.59	75.77	7,730.4	230.6	909.5	-169.2	2.00	-2.00	0.00
7,900.0	1.59	75.77	7,830.3	231.7	913.9	-170.0	2.00	-2.00	0.00
7,979.7	0.00	0.00	7,910.0	232.0	915.0	-170.2	2.00	-2.00	0.00
8,000.0	0.00	0.00	7,930.3	232.0	915.0	-170.2	0.00	0.00	0.00
8,100.0	0.00	0.00	8,030.3	232.0	915.0	-170.2	0.00	0.00	0.00
8,200.0	0.00	0.00	8,130.3	232.0	915.0	-170.2	0.00	0.00	0.00
8,300.0	0.00	0.00	8,230.3	232.0	915.0	-170.2	0.00	0.00	0.00
8,400.0	0.00	0.00	8,330.3	232.0	915.0	-170.2	0.00	0.00	0.00
8,500.0	0.00	0.00	8,430.3	232.0	915.0	-170.2	0.00	0.00	0.00
8,600.0	0.00	0.00	8,530.3	232.0	915.0	-170.2	0.00	0.00	0.00
8,700.0	0.00	0.00	8,630.3	232.0	915.0	-170.2	0.00	0.00	0.00
8,800.0	0.00	0.00	8,730.3	232.0	915.0	-170.2	0.00	0.00	0.00
8,900.0	0.00	0.00	8,830.3	232.0	915.0	-170.2	0.00	0.00	0.00
9,000.0	0.00	0.00	8,930.3	232.0	915.0	-170.2	0.00	0.00	0.00
9,100.0	0.00	0.00	9,030.3	232.0	915.0	-170.2	0.00	0.00	0.00
9,200.0	0.00	0.00	9,130.3	232.0	915.0	-170.2	0.00	0.00	0.00
9,300.0	0.00	0.00	9,230.3	232.0	915.0	-170.2	0.00	0.00	0.00
9,400.0	0.00	0.00	9,330.3	232.0	915.0	-170.2	0.00	0.00	0.00
9,500.0	0.00	0.00	9,430.3	232.0	915.0	-170.2	0.00	0.00	0.00
9,600.0	0.00	0.00	9,530.3	232.0	915.0	-170.2	0.00	0.00	0.00
9,700.0	0.00	0.00	9,630.3	232.0	915.0	-170.2	0.00	0.00	0.00
9,800.0	0.00	0.00	9,730.3	232.0	915.0	-170.2	0.00	0.00	0.00
9,900.0	0.00	0.00	9,830.3	232.0	915.0	-170.2	0.00	0.00	0.00
9,944.2	0.00	0.00	9,874.5	232.0	915.0	-170.2	0.00	0.00	0.00
9,950.0	0.70	180.00	9,880.3	232.0	915.0	-170.2	12.00	12.00	0.00
9,975.0	3.70	180.00	9,905.3	231.0	915.0	-169.2	12.00	12.00	0.00
10,000.0	6.70	180.00	9,930.2	228.7	915.0	-167.0	12.00	12.00	0.00
10,025.0	9.70	180.00	9,954.9	225.2	915.0	-163.4	12.00	12.00	0.00

Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #307H
Company:	Midland	TVD Reference:	kb=26' @ 3360.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	kb=26' @ 3360.0usft
Site:	Pistolero 15 Fed	North Reference:	Grid
Well:	#307H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #0.2		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
10,050.0	12.70	180.00	9,979.4	220.3	915.0	-158.6	12.00	12.00	0.00	
10,075.0	15.70	180.00	10,003.7	214.2	915.0	-152.5	12.00	12.00	0.00	
10,100.0	18.70	180.00	10,027.6	206.8	915.0	-145.1	12.00	12.00	0.00	
10,125.0	21.70	180.00	10,051.0	198.2	915.0	-136.5	12.00	12.00	0.00	
10,150.0	24.70	180.00	10,074.0	188.3	915.0	-126.6	12.00	12.00	0.00	
10,164.6	26.46	180.00	10,087.2	182.0	915.0	-120.3	12.00	12.00	0.00	
10,175.0	27.70	179.98	10,096.4	177.3	915.0	-115.6	12.00	12.00	-0.23	
10,200.0	30.70	179.93	10,118.2	165.1	915.0	-103.5	12.00	12.00	-0.20	
10,225.0	33.70	179.88	10,139.4	151.8	915.0	-90.2	12.00	12.00	-0.17	
10,250.0	36.70	179.85	10,159.8	137.4	915.1	-75.8	12.00	12.00	-0.14	
10,275.0	39.70	179.82	10,179.5	121.9	915.1	-60.4	12.00	12.00	-0.12	
10,300.0	42.70	179.79	10,198.3	105.4	915.2	-43.9	12.00	12.00	-0.11	
10,325.0	45.70	179.77	10,216.2	88.0	915.2	-26.5	12.00	12.00	-0.10	
10,350.0	48.70	179.74	10,233.2	69.7	915.3	-8.2	12.00	12.00	-0.09	
10,375.0	51.70	179.72	10,249.2	50.5	915.4	10.9	12.00	12.00	-0.08	
10,400.0	54.70	179.71	10,264.2	30.4	915.5	30.9	12.00	12.00	-0.07	
10,425.0	57.70	179.69	10,278.1	9.7	915.6	51.6	12.00	12.00	-0.07	
10,450.0	60.70	179.67	10,290.9	-11.8	915.7	73.1	12.00	12.00	-0.06	
10,475.0	63.70	179.66	10,302.5	-33.9	915.9	95.1	12.00	12.00	-0.06	
10,500.0	66.70	179.64	10,313.0	-56.6	916.0	117.8	12.00	12.00	-0.06	
10,525.0	69.70	179.63	10,322.3	-79.8	916.1	141.0	12.00	12.00	-0.05	
10,550.0	72.70	179.62	10,330.3	-103.5	916.3	164.6	12.00	12.00	-0.05	
10,575.0	75.70	179.60	10,337.2	-127.5	916.5	188.6	12.00	12.00	-0.05	
10,600.0	78.70	179.59	10,342.7	-151.9	916.6	212.9	12.00	12.00	-0.05	
10,625.0	81.70	179.58	10,346.9	-176.5	916.8	237.5	12.00	12.00	-0.05	
10,650.0	84.70	179.57	10,349.9	-201.3	917.0	262.3	12.00	12.00	-0.05	
10,675.0	87.70	179.56	10,351.6	-226.3	917.2	287.2	12.00	12.00	-0.05	
10,694.2	90.00	179.55	10,351.9	-245.5	917.3	306.3	12.00	12.00	-0.05	
10,700.0	90.00	179.55	10,351.9	-251.3	917.4	312.1	0.00	0.00	0.00	
10,800.0	90.00	179.55	10,351.9	-351.3	918.2	412.0	0.00	0.00	0.00	
10,900.0	90.00	179.55	10,351.9	-451.3	919.0	511.8	0.00	0.00	0.00	
11,000.0	90.00	179.55	10,351.9	-551.3	919.8	611.6	0.00	0.00	0.00	
11,100.0	90.00	179.55	10,352.0	-651.3	920.6	711.4	0.00	0.00	0.00	
11,200.0	90.00	179.55	10,352.0	-751.3	921.4	811.3	0.00	0.00	0.00	
11,300.0	90.00	179.55	10,352.0	-851.3	922.1	911.1	0.00	0.00	0.00	
11,400.0	90.00	179.55	10,352.0	-951.3	922.9	1,010.9	0.00	0.00	0.00	
11,500.0	90.00	179.55	10,352.0	-1,051.3	923.7	1,110.7	0.00	0.00	0.00	
11,600.0	90.00	179.55	10,352.0	-1,151.3	924.5	1,210.6	0.00	0.00	0.00	
11,700.0	90.00	179.55	10,352.0	-1,251.3	925.3	1,310.4	0.00	0.00	0.00	
11,800.0	90.00	179.55	10,352.0	-1,351.2	926.1	1,410.2	0.00	0.00	0.00	
11,900.0	90.00	179.55	10,352.0	-1,451.2	926.9	1,510.0	0.00	0.00	0.00	
12,000.0	90.00	179.55	10,352.0	-1,551.2	927.7	1,609.9	0.00	0.00	0.00	
12,100.0	90.00	179.55	10,352.0	-1,651.2	928.5	1,709.7	0.00	0.00	0.00	
12,200.0	90.00	179.55	10,352.0	-1,751.2	929.3	1,809.5	0.00	0.00	0.00	
12,300.0	90.00	179.55	10,352.0	-1,851.2	930.1	1,909.3	0.00	0.00	0.00	
12,400.0	90.00	179.55	10,352.0	-1,951.2	930.9	2,009.2	0.00	0.00	0.00	
12,500.0	90.00	179.55	10,352.0	-2,051.2	931.7	2,109.0	0.00	0.00	0.00	
12,600.0	90.00	179.55	10,352.0	-2,151.2	932.4	2,208.8	0.00	0.00	0.00	
12,700.0	90.00	179.55	10,352.0	-2,251.2	933.2	2,308.6	0.00	0.00	0.00	
12,800.0	90.00	179.55	10,352.0	-2,351.2	934.0	2,408.5	0.00	0.00	0.00	
12,900.0	90.00	179.55	10,352.0	-2,451.2	934.8	2,508.3	0.00	0.00	0.00	
13,000.0	90.00	179.55	10,352.0	-2,551.2	935.6	2,608.1	0.00	0.00	0.00	
13,100.0	90.00	179.55	10,352.0	-2,651.2	936.4	2,707.9	0.00	0.00	0.00	
13,200.0	90.00	179.55	10,352.0	-2,751.2	937.2	2,807.8	0.00	0.00	0.00	

Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #307H
Company:	Midland	TVD Reference:	kb=26' @ 3360.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	kb=26' @ 3360.0usft
Site:	Pistolero 15 Fed	North Reference:	Grid
Well:	#307H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #0.2		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
13,300.0	90.00	179.55	10,352.0	-2,851.2	938.0	2,907.6	0.00	0.00	0.00
13,400.0	90.00	179.55	10,352.0	-2,951.2	938.8	3,007.4	0.00	0.00	0.00
13,500.0	90.00	179.55	10,352.0	-3,051.2	939.6	3,107.2	0.00	0.00	0.00
13,600.0	90.00	179.55	10,352.0	-3,151.2	940.4	3,207.1	0.00	0.00	0.00
13,700.0	90.00	179.55	10,352.0	-3,251.2	941.2	3,306.9	0.00	0.00	0.00
13,800.0	90.00	179.55	10,352.0	-3,351.2	942.0	3,406.7	0.00	0.00	0.00
13,900.0	90.00	179.55	10,352.0	-3,451.2	942.7	3,506.6	0.00	0.00	0.00
14,000.0	90.00	179.55	10,352.0	-3,551.2	943.5	3,606.4	0.00	0.00	0.00
14,100.0	90.00	179.55	10,352.0	-3,651.2	944.3	3,706.2	0.00	0.00	0.00
14,200.0	90.00	179.55	10,352.0	-3,751.2	945.1	3,806.0	0.00	0.00	0.00
14,300.0	90.00	179.55	10,352.0	-3,851.2	945.9	3,905.9	0.00	0.00	0.00
14,400.0	90.00	179.55	10,352.0	-3,951.2	946.7	4,005.7	0.00	0.00	0.00
14,500.0	90.00	179.55	10,352.0	-4,051.2	947.5	4,105.5	0.00	0.00	0.00
14,600.0	90.00	179.55	10,352.0	-4,151.2	948.3	4,205.3	0.00	0.00	0.00
14,700.0	90.00	179.55	10,352.0	-4,251.2	949.1	4,305.2	0.00	0.00	0.00
14,800.0	90.00	179.55	10,352.0	-4,351.2	949.9	4,405.0	0.00	0.00	0.00
14,900.0	90.00	179.55	10,352.0	-4,451.2	950.7	4,504.8	0.00	0.00	0.00
15,000.0	90.00	179.55	10,352.0	-4,551.1	951.5	4,604.6	0.00	0.00	0.00
15,100.0	90.00	179.55	10,352.0	-4,651.1	952.3	4,704.5	0.00	0.00	0.00
15,200.0	90.00	179.55	10,352.0	-4,751.1	953.1	4,804.3	0.00	0.00	0.00
15,300.0	90.00	179.55	10,352.0	-4,851.1	953.8	4,904.1	0.00	0.00	0.00
15,400.0	90.00	179.55	10,352.0	-4,951.1	954.6	5,003.9	0.00	0.00	0.00
15,445.9	90.00	179.55	10,352.0	-4,997.0	955.0	5,049.7	0.00	0.00	0.00
15,500.0	90.00	179.54	10,352.0	-5,051.1	955.4	5,103.8	0.00	0.00	0.00
15,600.0	90.00	179.54	10,352.0	-5,151.1	956.2	5,203.6	0.00	0.00	0.00
15,700.0	90.00	179.54	10,352.0	-5,251.1	957.0	5,303.4	0.00	0.00	0.00
15,800.0	90.00	179.53	10,352.0	-5,351.1	957.8	5,403.2	0.00	0.00	0.00
15,900.0	90.00	179.53	10,352.0	-5,451.1	958.7	5,503.1	0.00	0.00	0.00
16,000.0	90.00	179.53	10,352.0	-5,551.1	959.5	5,602.9	0.00	0.00	0.00
16,100.0	90.00	179.52	10,352.0	-5,651.1	960.3	5,702.7	0.00	0.00	0.00
16,200.0	90.00	179.52	10,352.0	-5,751.1	961.2	5,802.6	0.00	0.00	0.00
16,300.0	90.00	179.52	10,352.0	-5,851.1	962.0	5,902.4	0.00	0.00	0.00
16,400.0	90.00	179.51	10,352.0	-5,951.1	962.8	6,002.2	0.00	0.00	0.00
16,500.0	90.00	179.51	10,352.0	-6,051.1	963.7	6,102.0	0.00	0.00	0.00
16,600.0	90.00	179.50	10,352.0	-6,151.1	964.6	6,201.9	0.00	0.00	0.00
16,700.0	90.00	179.50	10,352.0	-6,251.1	965.4	6,301.7	0.00	0.00	0.00
16,764.9	90.00	179.50	10,352.0	-6,316.0	966.0	6,366.5	0.00	0.00	0.00
16,800.0	90.00	179.50	10,352.0	-6,351.1	966.3	6,401.5	0.00	0.00	0.00
16,900.0	90.00	179.50	10,352.0	-6,451.1	967.2	6,501.4	0.00	0.00	0.00
17,000.0	90.00	179.50	10,352.0	-6,551.1	968.1	6,601.2	0.00	0.00	0.00
17,100.0	90.00	179.50	10,352.0	-6,651.1	968.9	6,701.0	0.00	0.00	0.00
17,200.0	90.00	179.50	10,352.0	-6,751.1	969.8	6,800.8	0.00	0.00	0.00
17,300.0	90.00	179.51	10,352.0	-6,851.1	970.7	6,900.7	0.00	0.00	0.00
17,400.0	90.00	179.51	10,352.0	-6,951.1	971.5	7,000.5	0.00	0.00	0.00
17,500.0	90.00	179.51	10,352.0	-7,051.1	972.4	7,100.3	0.00	0.00	0.00
17,600.0	90.00	179.51	10,352.0	-7,151.1	973.2	7,200.2	0.00	0.00	0.00
17,700.0	90.00	179.51	10,352.0	-7,251.1	974.1	7,300.0	0.00	0.00	0.00
17,800.0	90.00	179.51	10,352.0	-7,351.0	974.9	7,399.8	0.00	0.00	0.00
17,900.0	90.00	179.51	10,352.0	-7,451.0	975.8	7,499.7	0.00	0.00	0.00
18,000.0	90.00	179.51	10,352.0	-7,551.0	976.6	7,599.5	0.00	0.00	0.00
18,100.0	90.00	179.51	10,352.0	-7,651.0	977.5	7,699.3	0.00	0.00	0.00
18,200.0	90.00	179.52	10,352.0	-7,751.0	978.3	7,799.1	0.00	0.00	0.00
18,300.0	90.00	179.52	10,352.0	-7,851.0	979.2	7,899.0	0.00	0.00	0.00
18,400.0	90.00	179.52	10,352.0	-7,951.0	980.0	7,998.8	0.00	0.00	0.00

Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #307H
Company:	Midland	TVD Reference:	kb=26' @ 3360.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	kb=26' @ 3360.0usft
Site:	Pistolero 15 Fed	North Reference:	Grid
Well:	#307H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #0.2		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
18,500.0	90.00	179.52	10,352.0	-8,051.0	980.9	8,098.6	0.00	0.00	0.00
18,600.0	90.00	179.52	10,352.0	-8,151.0	981.7	8,198.5	0.00	0.00	0.00
18,700.0	90.00	179.52	10,352.0	-8,251.0	982.5	8,298.3	0.00	0.00	0.00
18,800.0	90.00	179.52	10,352.0	-8,351.0	983.4	8,398.1	0.00	0.00	0.00
18,900.0	90.00	179.52	10,352.0	-8,451.0	984.2	8,497.9	0.00	0.00	0.00
19,000.0	90.00	179.53	10,352.0	-8,551.0	985.0	8,597.8	0.00	0.00	0.00
19,100.0	90.00	179.53	10,352.0	-8,651.0	985.9	8,697.6	0.00	0.00	0.00
19,200.0	90.00	179.53	10,352.0	-8,751.0	986.7	8,797.4	0.00	0.00	0.00
19,300.0	90.00	179.53	10,352.0	-8,851.0	987.5	8,897.2	0.00	0.00	0.00
19,400.0	90.00	179.53	10,352.0	-8,951.0	988.3	8,997.1	0.00	0.00	0.00
19,500.0	90.00	179.53	10,352.0	-9,051.0	989.1	9,096.9	0.00	0.00	0.00
19,600.0	90.00	179.53	10,352.0	-9,151.0	990.0	9,196.7	0.00	0.00	0.00
19,700.0	90.00	179.53	10,352.0	-9,251.0	990.8	9,296.6	0.00	0.00	0.00
19,800.0	90.00	179.54	10,352.0	-9,351.0	991.6	9,396.4	0.00	0.00	0.00
19,900.0	90.00	179.54	10,352.0	-9,451.0	992.4	9,496.2	0.00	0.00	0.00
20,000.0	90.00	179.54	10,352.0	-9,551.0	993.2	9,596.0	0.00	0.00	0.00
20,100.0	90.00	179.54	10,352.0	-9,651.0	994.0	9,695.9	0.00	0.00	0.00
20,200.0	90.00	179.54	10,352.0	-9,751.0	994.8	9,795.7	0.00	0.00	0.00
20,300.0	90.00	179.54	10,352.0	-9,851.0	995.6	9,895.5	0.00	0.00	0.00
20,400.0	90.00	179.54	10,352.0	-9,951.0	996.4	9,995.3	0.00	0.00	0.00
20,500.0	90.00	179.54	10,352.0	-10,051.0	997.2	10,095.2	0.00	0.00	0.00
20,600.0	90.00	179.55	10,352.0	-10,151.0	998.0	10,195.0	0.00	0.00	0.00
20,700.0	90.00	179.55	10,352.0	-10,251.0	998.8	10,294.8	0.00	0.00	0.00
20,800.0	90.00	179.55	10,352.0	-10,350.9	999.6	10,394.6	0.00	0.00	0.00
20,900.0	90.00	179.55	10,352.0	-10,450.9	1,000.4	10,494.5	0.00	0.00	0.00
21,000.0	90.00	179.55	10,352.0	-10,550.9	1,001.1	10,594.3	0.00	0.00	0.00
21,100.0	90.00	179.55	10,352.0	-10,650.9	1,001.9	10,694.1	0.00	0.00	0.00
21,200.0	90.00	179.55	10,352.0	-10,750.9	1,002.7	10,793.9	0.00	0.00	0.00
21,300.0	90.00	179.55	10,352.0	-10,850.9	1,003.5	10,893.8	0.00	0.00	0.00
21,400.0	90.00	179.56	10,352.0	-10,950.9	1,004.3	10,993.6	0.00	0.00	0.00
21,500.0	90.00	179.56	10,352.0	-11,050.9	1,005.0	11,093.4	0.00	0.00	0.00
21,600.0	90.00	179.56	10,352.0	-11,150.9	1,005.8	11,193.2	0.00	0.00	0.00
21,700.0	90.00	179.56	10,352.0	-11,250.9	1,006.6	11,293.1	0.00	0.00	0.00
21,800.0	90.00	179.56	10,352.0	-11,350.9	1,007.3	11,392.9	0.00	0.00	0.00
21,900.0	90.00	179.56	10,352.0	-11,450.9	1,008.1	11,492.7	0.00	0.00	0.00
22,000.0	90.00	179.56	10,352.0	-11,550.9	1,008.9	11,592.5	0.00	0.00	0.00
22,100.0	90.00	179.56	10,352.0	-11,650.9	1,009.6	11,692.4	0.00	0.00	0.00
22,200.0	90.00	179.57	10,352.0	-11,750.9	1,010.4	11,792.2	0.00	0.00	0.00
22,300.0	90.00	179.57	10,352.0	-11,850.9	1,011.1	11,892.0	0.00	0.00	0.00
22,400.0	90.00	179.57	10,352.0	-11,950.9	1,011.9	11,991.8	0.00	0.00	0.00
22,500.0	90.00	179.57	10,352.0	-12,050.9	1,012.7	12,091.7	0.00	0.00	0.00
22,600.0	90.00	179.57	10,352.0	-12,150.9	1,013.4	12,191.5	0.00	0.00	0.00
22,700.0	90.00	179.57	10,352.0	-12,250.9	1,014.2	12,291.3	0.00	0.00	0.00
22,800.0	90.00	179.57	10,352.0	-12,350.9	1,014.9	12,391.1	0.00	0.00	0.00
22,900.0	90.00	179.57	10,352.0	-12,450.9	1,015.6	12,490.9	0.00	0.00	0.00
23,000.0	90.00	179.58	10,352.0	-12,550.9	1,016.4	12,590.8	0.00	0.00	0.00
23,100.0	90.00	179.58	10,352.0	-12,650.9	1,017.1	12,690.6	0.00	0.00	0.00
23,200.0	90.00	179.58	10,352.0	-12,750.9	1,017.9	12,790.4	0.00	0.00	0.00
23,300.0	90.00	179.58	10,352.0	-12,850.9	1,018.6	12,890.2	0.00	0.00	0.00
23,400.0	90.00	179.58	10,352.0	-12,950.9	1,019.3	12,990.1	0.00	0.00	0.00
23,500.0	90.00	179.58	10,352.0	-13,050.9	1,020.1	13,089.9	0.00	0.00	0.00
23,600.0	90.00	179.58	10,352.0	-13,150.9	1,020.8	13,189.7	0.00	0.00	0.00
23,700.0	90.00	179.58	10,352.0	-13,250.9	1,021.5	13,289.5	0.00	0.00	0.00
23,800.0	90.00	179.59	10,352.0	-13,350.9	1,022.2	13,389.3	0.00	0.00	0.00

Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #307H
Company:	Midland	TVD Reference:	kb=26' @ 3360.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	kb=26' @ 3360.0usft
Site:	Pistolero 15 Fed	North Reference:	Grid
Well:	#307H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #0.2		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
23,900.0	90.00	179.59	10,352.0	-13,450.9	1,023.0	13,489.2	0.00	0.00	0.00	
24,000.0	90.00	179.59	10,352.0	-13,550.9	1,023.7	13,589.0	0.00	0.00	0.00	
24,100.0	90.00	179.59	10,352.0	-13,650.9	1,024.4	13,688.8	0.00	0.00	0.00	
24,200.0	90.00	179.59	10,352.0	-13,750.9	1,025.1	13,788.6	0.00	0.00	0.00	
24,300.0	90.00	179.59	10,352.0	-13,850.8	1,025.8	13,888.5	0.00	0.00	0.00	
24,400.0	90.00	179.59	10,352.0	-13,950.8	1,026.5	13,988.3	0.00	0.00	0.00	
24,500.0	90.00	179.59	10,352.0	-14,050.8	1,027.3	14,088.1	0.00	0.00	0.00	
24,600.0	90.00	179.60	10,352.0	-14,150.8	1,028.0	14,187.9	0.00	0.00	0.00	
24,700.0	90.00	179.60	10,352.0	-14,250.8	1,028.7	14,287.7	0.00	0.00	0.00	
24,800.0	90.00	179.60	10,352.0	-14,350.8	1,029.4	14,387.6	0.00	0.00	0.00	
24,900.0	90.00	179.60	10,352.0	-14,450.8	1,030.1	14,487.4	0.00	0.00	0.00	
25,000.0	90.00	179.60	10,352.0	-14,550.8	1,030.8	14,587.2	0.00	0.00	0.00	
25,100.0	90.00	179.60	10,352.0	-14,650.8	1,031.5	14,687.0	0.00	0.00	0.00	
25,200.0	90.00	179.60	10,352.0	-14,750.8	1,032.2	14,786.8	0.00	0.00	0.00	
25,300.0	90.00	179.60	10,352.0	-14,850.8	1,032.9	14,886.7	0.00	0.00	0.00	
25,400.0	90.00	179.61	10,352.0	-14,950.8	1,033.5	14,986.5	0.00	0.00	0.00	
25,500.0	90.00	179.61	10,352.0	-15,050.8	1,034.2	15,086.3	0.00	0.00	0.00	
25,600.0	90.00	179.61	10,352.0	-15,150.8	1,034.9	15,186.1	0.00	0.00	0.00	
25,700.0	90.00	179.61	10,352.0	-15,250.8	1,035.6	15,285.9	0.00	0.00	0.00	
25,800.0	90.00	179.61	10,352.0	-15,350.8	1,036.3	15,385.8	0.00	0.00	0.00	
25,905.2	90.00	179.61	10,352.0	-15,456.0	1,037.0	15,490.7	0.00	0.00	0.00	

Design Targets										
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude		
- hit/miss target										
- Shape								Longitude		
KOP(Pistolero 15 Fed C - plan hits target center - Point	0.00	0.00	9,874.5	232.0	915.0	414,899.00	810,949.00	32° 8' 15.501 N 103° 27' 44.267 W		
FTP(Pistolero 15 Fed C - plan hits target center - Point	0.00	0.00	10,087.2	182.0	915.0	414,849.00	810,949.00	32° 8' 15.006 N 103° 27' 44.271 W		
Fed PP1(Pistolero 15 Fe - plan hits target center - Point	0.00	0.00	10,352.0	-4,997.0	955.0	409,670.00	810,989.00	32° 7' 23.756 N 103° 27' 44.293 W		
Fed PP2(Pistolero 15 Fe - plan hits target center - Point	0.00	0.00	10,352.0	-6,316.0	966.0	408,351.00	811,000.00	32° 7' 10.704 N 103° 27' 44.289 W		
PBHL(Pistolero 15 Fed - plan hits target center - Point	0.00	0.00	10,352.0	-15,456.0	1,037.0	399,211.00	811,071.00	32° 5' 40.257 N 103° 27' 44.322 W		

Lea County, NM (NAD 83 NME)

Pistolero 15 Fed #307H

Plan #0.2



To convert a Magnetic Direction to a Grid Direction, Add 5.77°
To convert a Magnetic Direction to a True Direction, Add 6.23° East
To convert a True Direction to a Grid Direction, Subtract 0.46°

PROJECT DETAILS: Lea County, NM (NAD 83 NME)

Geodetic System: US State Plane 1983
Datum: North American Datum 1983
Ellipsoid: GRS 1980
Zone: New Mexico Eastern Zone
System Datum: Mean Sea Level

WELL DETAILS: #307H

3334.0
kb=26' @ 3360.0usft
Northing 414667.00 Easting 810034.00 Latitude 32° 8' 13.278 N Longitude 103° 27' 54.929 W

SECTION DETAILS


Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	1267.0	0.00	0.00	1267.0	0.0	0.0	0.00	0.00	0.0	
3	1699.2	8.64	75.77	1697.5	8.0	31.5	2.00	75.77	-5.9	
4	7547.5	8.64	75.77	7479.5	224.0	883.5	0.00	0.00	-164.4	
5	7979.7	0.00	0.00	7910.0	232.0	915.0	2.00	180.00	-170.2	
6	9944.2	0.00	0.00	9874.5	232.0	915.0	0.00	0.00	-170.2	KOP(Pistolero 15 Fed Com #432H)
7	10164.6	26.46	180.00	10087.2	182.0	915.0	12.00	180.00	-120.3	FTP(Pistolero 15 Fed Com #432H)
8	10694.2	90.00	179.55	10351.9	-245.5	917.3	12.00	-0.51	306.3	
9	15445.9	90.00	179.55	10352.0	-4997.0	955.0	0.00	0.00	5049.7	Fed PP1(Pistolero 15 Fed Com #432H)
10	16764.9	90.00	179.50	10352.0	-6316.0	966.0	0.00	-88.44	6366.5	Fed PP2(Pistolero 15 Fed Com #432H)
11	25905.2	90.00	179.61	10352.0	-15456.0	1037.0	0.00	90.66	15490.7	PBHL(Pistolero 15 Fed Com #432H)

CASING DETAILS

No casing data is available

WELLBORE TARGET DETAILS (MAP CO-ORDINATES)

Name	TVD	+N/-S	+E/-W	Northing	Easting
KOP(Pistolero 15 Fed Com #432H)	9874.5	232.0	915.0	414899.00	810949.00
FTP(Pistolero 15 Fed Com #432H)	10087.2	182.0	915.0	414849.00	810949.00
Fed PP1(Pistolero 15 Fed Com #432H)	10352.0	-4997.0	955.0	409670.00	810989.00
Fed PP2(Pistolero 15 Fed Com #432H)	10352.0	-6316.0	966.0	408351.00	811000.00
PBHL(Pistolero 15 Fed Com #432H)	10352.0	-15456.0	1037.0	399211.00	811071.00



Vertical Section at 176.16°



EOG BLANKET CASING DESIGN VARIANCE

EOG respectfully requests the drill plans in the attached document 'EOG Alternate Casing Designs – BLM APPROVED' be added to the COA's for this well. These designs have been approved by the BLM down to the TVDs listed below and will allow EOG to run alternate casing designs for this well if necessary.

The designs and associated details listed are the "worst case scenario" boundaries for design safety factors. Location and lithology have NOT been accounted for in these designs. The specific well details will be based on the APD/Sundry package and the information listed in the COA.

The mud program will not change from the original design for this well. Summary of the mud programs for both shallow and deep targets are listed at the end of this document. If the target is changing, a sundry will be filed to update the casing design and mud/cement programs.

Cement volumes listed in this document are for reference only. The cement volumes for the specific well will be adjusted to ensure cement tops meet BLM requirements as listed in the COA and to allow bradenhead cementing when applicable.

This blanket document only applies to wells with three string designs outside of Potash and Capitan Reef boundaries.

Shallow Design Boundary Conditions				
	Deepest MD (ft)	Deepest TVD (ft)	Max Inc (deg)	Max DLS (°/100usft)
Surface	2030	2030	0	0
Intermediate	7793	5650	40	8
Production	28578	11225	90	25



Shallow Design A

1. CASING PROGRAM

Hole Size	Interval MD		Interval TVD		Csg OD	Weight	Grade	Conn
	From (ft)	To (ft)	From (ft)	To (ft)				
16"	0	2,030	0	2,030	13-3/8"	54.5#	J-55	STC
11"	0	7,793	0	5,650	9-5/8"	40#	J-55	LTC
6-3/4"	0	28,578	0	11,225	5-1/2"	20#	P110-EC	DWC/C IS MS

Hole will be full during casing run for well control and tensile SF factor. Casing will be kept at least half full during run for this design to meet BLM collapse SF requirement. External pressure will be reviewed prior to conducting casing pressure tests to ensure that 70% of the yield is not exceeded.

Variance is requested to waive the centralizer requirements for the 9-5/8" casing in the 11" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 11" hole interval to maximize cement bond and zonal isolation.

Variance is also requested to waive any centralizer requirements for the 5-1/2" casing in the 6-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 6-3/4" hole interval to maximize cement bond and zonal isolation.

EOG requests permission to allow deviation from the 0.422" annulus clearance requirement for the intermediate (salt) section from Title 43 CFR Part 3170 under the following conditions:

- The variance is not applicable within the Potash Boundaries or Capitan Reef areas.
- Operator takes responsibility to get casing to set point in the event that the clearance causes stuck pipe issues.

2. CEMENTING PROGRAM:

Depth	No. Sacks	Wt. ppg	Yld Ft3/sk	Slurry Description
2,030' 13-3/8"	570	13.5	1.73	Lead: Class C + 4.0% Bentonite Gel + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	160	14.8	1.34	Tail: Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate (TOC @ 1830')
7,793' 9-5/8"	770	12.7	2.22	Lead: Class C + 10% NaCl + 6% Bentonite Gel + 3% MagOx (TOC @ Surface)
	250	14.8	1.32	Tail: Class C + 10% NaCl + 3% MagOx (TOC @ 6238')
28,578' 5-1/2"	410	10.5	3.21	Lead: Class H + 0.4% Halad-344 + 0.35% HR-601 + 3% Microbond (TOC @ 7300')
	1110	13.2	1.52	Tail: Class H + 5% NEX-020 + 0.2% NAC-102 + 0.15% NAS-725 + 0.5% NFL-549 + 0.2% NFP-703 + 1% NBE-737 + 0.3% NRT-241 (TOC @ 12730')




Shallow Design A

Proposed Wellbore

KB: 3558'

GL: 3533'




Triaxial Results														
	Depth (MD) (usft)	Axial Force (lbf)		Equivalent Axial Load (lbf)	Bending Stress at OD (psi)	Absolute Safety Factor				Temperature (°F)	Pressure (psi)		Addtl Pickup To Prevent Buck. (lbf)	Buckled Length (usft)
		Apparent (w/Bending)	Actual (w/o Bending)			Triaxial	Burst	Collapse (V)	Axial		Internal	External		
1	0	252987	228954	253140	2098.2	1.69	1.58	N/A	2.82 F	70.00	2500.00	0.00	N/A	N/A
2	100	247735	223702	248466	2098.2	1.69	1.58	N/A	2.88 F	71.10	2543.63	43.63		
3	100	234996	223701	235716	986.2	1.71	1.58	N/A	3.04 F	71.10	2543.64	43.64		
4	1700	341565	139667	352253	17627.2	1.53	1.57	N/A	2.09 F	88.70	3241.64	741.64		
5	1700	312979	139666	323488	15131.5	1.58	1.57	N/A	2.28 F	88.70	3241.65	741.65		
6	1850	336881	132027	348440	17885.2	1.51	1.57	N/A	2.12 F	90.29	3305.05	805.05		
7	1850	318549	132027	329984	16284.8	1.54	1.57	N/A	2.24 F	90.29	3305.06	805.06		
8	1950	320468	127243	332475	16869.9	1.52	1.57	N/A	2.23 F	91.30	3344.87	844.87		
9	1950	312802	127243	324756	16200.7	1.53	1.57	N/A	2.28 F	91.30	3344.87	844.87		
10	2050	307858	122773	320295	16159.3	1.52	1.57	N/A	2.32 F	92.23	3381.89	881.89		
11	2050	303560	122772	315965	15784.1	1.53	1.57	N/A	2.35 F	92.23	3381.89	881.89		
12	2300	151294	112633	163658	3375.4	1.71	1.57	N/A	4.72 F	94.35	3466.13	966.13		
13	2300	132741	112633	144956	1755.6	1.72	1.57	N/A	5.38 F	94.35	3466.14	966.14		
14	2370	129966	109858	142452	1755.6	1.72	1.57	N/A	5.49 F	94.94	3489.28	989.28		
15	2370	127909	107800	140922	1755.6	1.75	1.60	N/A	5.58 F	94.94	3489.29	1036.40		
16	2700	105515	94232	119785	985.1	1.75	1.60	N/A	6.77 F	97.73	3599.97	1152.35		
17	2700	111680	94231	126006	1523.4	1.75	1.60	N/A	6.39 F	97.73	3599.97	1152.35		
18	3100	110766	77783	126839	2879.6	1.71	1.60	N/A	6.44 F	101.11	3734.23	1293.00		
19	3100	97392	77783	113331	1712.1	1.73	1.60	N/A	7.33 F	101.11	3734.23	1293.01		
20	3700	71565	53303	89806	1594.4	1.70	1.61	N/A	9.97 F	106.15	3934.24	1502.54		
21	3700	60887	53302	79004	662.3	1.71	1.61	N/A	11.72 F	106.16	3934.25	1502.55		
22	4650	34671	14219	56495	1785.6	1.64	1.61	N/A	20.59 F	114.20	4253.37	1836.86		
23	4900	44595	4828	67626	3472.0	1.59	1.61	N/A	16.01 F	116.32	4337.37	1924.87		
24	4900	28975	4828	51775	2108.2	1.62	1.61	N/A	24.64 F	116.32	4337.38	1924.87		
25	5029	22103	34	45340	1926.8	1.61	1.61	N/A	32.30 F	117.40	4380.40	1969.94		
26	5029	22102	33	45339	1926.8	1.61	1.61	N/A	32.30 F	117.40	4380.41	1969.95		
27	5600	-45329	-21341	-20805	2094.3	1.57	1.62	N/A	(13.67)	122.23	4572.11	2170.78		
28	5650	-40465	-23210	-15657	1506.5	1.58	1.62	N/A	(15.31)	122.66	4588.87	2188.34		
29														
30		F Conn Fracture												
31		() Compression												
32		(V) Vector Collapse Safety Factor												
33														

9-5/8" Intermediate Casing Pressure Test:

Internal Profile based off Surface Pressure + Hydrostatic: 4589 psi

External Profile based off Pore Pressure: 2188 psi




StressCheck - [String Summary - Shallow 3.0 Mile - Big Hole *]

String Summary

	String	OD/Weight/Grade	Connection	MD Interval (usft)	Drift Dia. (")	Minimum Safety Factor (Abs)				Design Cost (\$)
						Burst	Collapse (V)	Axial	Triaxial	
1	Intermediate Casing	9 5/8", 40.000 ppf, J-55	BTC, J-55	0.0-5650.0	8.750 A	1.57	1.59	1.80 F	1.35	98,141
2										Total = 98,141
3										
4	F Conn Fracture									
5	A Alternate Drift									
6	(V) Vector Collapse Safety Factor									
7										

*Modelling done with 9-5/8" 40# Intermediate Casing. Passes all Burst, Collapse and Tensile design criteria.



StressCheck - [String Summary - Shallow 3.0 Mile]

*Modelling done with 5-1/2" 20# Production Casing with a 125ksi Control Yield. Passes all Burst, Collapse and Tensile design criteria.



Shallow Design B

1. CASING PROGRAM

Hole Size	Interval MD		Interval TVD		Csg OD	Weight	Grade	Conn
	From (ft)	To (ft)	From (ft)	To (ft)				
13-1/2"	0	2,030	0	2,030	10-3/4"	40.5#	J-55	STC
9-7/8"	0	7,793	0	5,650	8-5/8"	32#	J-55	BTC-SC
6-3/4"	0	28,578	0	11,225	5-1/2"	20#	P110-EC	DWC/C IS MS

Hole will be full during casing run for well control and tensile SF factor. Casing will be kept at least half full during run for this design to meet BLM collapse SF requirement. External pressure will be reviewed prior to conducting casing pressure tests to ensure that 70% of the yield is not exceeded.

Variance is requested to waive the centralizer requirements for the 8-5/8" casing in the 9-7/8" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 9-7/8" hole interval to maximize cement bond and zonal isolation.

Variance is also requested to waive any centralizer requirements for the 5-1/2" casing in the 6-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 6-3/4" hole interval to maximize cement bond and zonal isolation.

EOG requests permission to allow deviation from the 0.422" annulus clearance requirement for the intermediate (salt) section from Title 43 CFR Part 3170 under the following conditions:

- The variance is not applicable within the Potash Boundaries or Capitan Reef areas.
- Operator takes responsibility to get casing to set point in the event that the clearance causes stuck pipe issues.

2. CEMENTING PROGRAM:

Depth	No. Sacks	Wt. ppg	Yld Ft3/sk	Slurry Description
2,030' 10-3/4"	530	13.5	1.73	Lead: Class C + 4.0% Bentonite Gel + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	140	14.8	1.34	Tail: Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate (TOC @ 1830')
7,793' 8-5/8"	460	12.7	2.22	Lead: Class C + 10% NaCl + 6% Bentonite Gel + 3% MagOx (TOC @ Surface)
	210	14.8	1.32	Tail: Class C + 10% NaCl + 3% MagOx (TOC @ 6238')
28,578' 5-1/2"	400	10.5	3.21	Lead: Class H + 0.4% Halad-344 + 0.35% HR-601 + 3% Microbond (TOC @ 7300')
	1110	13.2	1.52	Tail: Class H + 5% NEX-020 + 0.2% NAC-102 + 0.15% NAS-725 + 0.5% NFL-549 + 0.2% NFP-703 + 1% NBE-737 + 0.3% NRT-241 (TOC @ 12730')




Shallow Design B

Proposed Wellbore

KB: 3558'

GL: 3533'



StressCheck - [Triaxial Results - Shallow 3.0 Mile *]

File Edit Wellbore Tubular View Composer Tools Window Help

Burst Design 8 5/8" Intermediate Casing

Pressure Test

Triaxial Results

	Depth (MD) (usft)	Axial Force (lbf)		Equivalent Axial Load (lbf)	Bending Stress at OD (psi)	Absolute Safety Factor				Temperature (°F)	Pressure (psi)		Addtl Pickup To Prevent Buck. (lbf)	Buckled Length (usft)
		Apparent (w/Bending)	Actual (w/o Bending)			Triaxial	Burst	Collapse (V)	Axial		Internal	External		
1	0	200426	183224	200546	1880.2	1.68	1.57	N/A	2.89 F	70.00	2500.00	0.00	N/A	N/A
2	100	196229	179028	196812	1880.2	1.69	1.57	N/A	2.95 F	71.10	2543.63	43.63		
3	100	187111	179027	187686	883.7	1.70	1.57	N/A	3.10 F	71.10	2543.64	43.64		
4	1700	256401	111891	264835	15795.8	1.56	1.56	N/A	2.26 F	88.70	3241.64	741.64		
5	1700	235940	111891	244247	13559.4	1.60	1.56	N/A	2.45 F	88.70	3241.65	741.65		
6	1850	252413	105788	261533	16027.0	1.54	1.56	N/A	2.29 F	90.29	3305.05	805.05		
7	1850	239292	105787	248323	14592.9	1.56	1.56	N/A	2.42 F	90.29	3305.06	805.06		
8	1950	240267	101966	249748	15117.2	1.54	1.56	N/A	2.41 F	91.30	3344.87	844.87		
9	1950	234781	101965	244223	14517.5	1.56	1.56	N/A	2.47 F	91.30	3344.87	844.87		
10	2050	230871	98395	240694	14480.4	1.55	1.56	N/A	2.51 F	92.23	3381.89	881.89		
11	2050	227794	98394	237594	14144.2	1.55	1.56	N/A	2.54 F	92.23	3381.89	881.89		
12	2300	117966	90294	127818	3024.7	1.70	1.56	N/A	4.91 F	94.35	3466.13	966.13		
13	2300	104686	90293	114432	1573.2	1.71	1.56	N/A	5.53 F	94.35	3466.14	966.14		
14	2370	102469	88077	112431	1573.2	1.71	1.56	N/A	5.65 F	94.94	3489.28	989.28		
15	2370	100817	86424	111200	1573.2	1.75	1.59	N/A	5.75 F	94.94	3489.29	1036.40		
16	2700	83660	75583	95052	882.8	1.74	1.59	N/A	6.92 F	97.73	3599.97	1152.35		
17	2700	88072	75583	99504	1365.1	1.74	1.59	N/A	6.58 F	97.73	3599.97	1152.35		
18	3100	86049	62442	98863	2580.4	1.71	1.59	N/A	6.73 F	101.11	3734.23	1293.00		
19	3100	76477	62441	89195	1534.2	1.72	1.59	N/A	7.57 F	101.11	3734.23	1293.01		
20	3700	55953	42882	70509	1428.8	1.69	1.60	N/A	10.35 F	106.15	3934.24	1502.54		
21	3700	48311	42881	62778	593.5	1.71	1.60	N/A	11.99 F	106.16	3934.25	1502.55		
22	4000	41458	33043	56865	919.9	1.69	1.60	N/A	13.97 F	108.69	4034.82	1607.91		
23	4650	26293	11655	43706	1600.1	1.63	1.60	N/A	22.03 F	114.20	4253.37	1836.86		
24	4900	32619	4156	50970	3111.2	1.59	1.60	N/A	17.76 F	116.32	4337.37	1924.87		
25	4900	21439	4155	39625	1889.2	1.61	1.60	N/A	27.02 F	116.32	4337.38	1924.87		
26	5039	15822	26	34389	1726.6	1.61	1.61	N/A	36.61 F	117.49	4383.77	1973.48		
27	5039	15822	26	34388	1726.6	1.61	1.61	N/A	36.61 F	117.49	4383.78	1973.49		
28	5600	-33912	-16743	-14286	1876.7	1.57	1.61	N/A	(14.60)	122.23	4572.11	2170.78		
29	5650	-30585	-18235	-10742	1350.0	1.58	1.61	N/A	(16.18)	122.66	4588.87	2188.34		
30														
31		F Conn Fracture												
32		() Compression												
33		(V) Vector Collapse Safety Factor												
34														

Working Config Min SF Load/SF DF Summary VME Wallplot


For Help, press F1

Default Datum @ 0.00 usft API - US Survey Feet jgriffin2

8-5/8" Intermediate Casing Pressure Test:

Internal Profile based off Surface Pressure + Hydrostatic: 4589 psi

External Profile based off Pore Pressure: 2188 psi



StressCheck - [String Summary - Shallow 3.0 Mile *]

String Summary

	String	OD/Weight/Grade	Connection	MD Interval (usft)	Drift Dia. (")	Minimum Safety Factor (Abs)				Design Cost (\$)
						Burst	Collapse (V)	Axial	Triaxial	
1	Intermediate Casing	8 5/8", 32.000 ppg, J-55	BTC, J-55	0.0-5650.0	7.875 A	1.56	1.57	1.81 F	1.34	80,117
2										Total = 80,117
3										
4	F Conn Fracture									
5	A Alternate Drift									
6	(V) Vector Collapse Safety Factor									
7										

*Modelling done with 8-5/8" 32# Intermediate Casing. Passes all Burst, Collapse and Tensile design criteria.



Shallow Design C

1. CASING PROGRAM

Hole Size	Interval MD		Interval TVD		Csg OD	Weight	Grade	Conn
	From (ft)	To (ft)	From (ft)	To (ft)				
16"	0	2,030	0	2,030	13-3/8"	54.5#	J-55	STC
11"	0	7,793	0	5,650	9-5/8"	40#	J-55	LTC
7-7/8"	0	28,578	0	11,225	6"	24.5#	P110-EC	VAM Sprint-SF

Hole will be full during casing run for well control and tensile SF factor. Casing will be kept at least half full during run for this design to meet BLM collapse SF requirement. External pressure will be reviewed prior to conducting casing pressure tests to ensure that 70% of the yield is not exceeded.

Variance is requested to waive the centralizer requirements for the 9-5/8" casing in the 11" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 11" hole interval to maximize cement bond and zonal isolation.

Variance is also requested to waive any centralizer requirements for the 6" casing in the 7-7/8" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 7-7/8" hole interval to maximize cement bond and zonal isolation.

EOG requests permission to allow deviation from the 0.422" annulus clearance requirement for the intermediate (salt) section from Title 43 CFR Part 3170 under the following conditions:

- The variance is not applicable within the Potash Boundaries or Capitan Reef areas.
- Operator takes responsibility to get casing to set point in the event that the clearance causes stuck pipe issues.

2. CEMENTING PROGRAM:

Depth	No. Sacks	Wt. ppg	Yld Ft3/sk	Slurry Description
2,030' 13-3/8"	570	13.5	1.73	Lead: Class C + 4.0% Bentonite Gel + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	160	14.8	1.34	Tail: Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate (TOC @ 1830')
7,793' 9-5/8"	770	12.7	2.22	Lead: Class C + 10% NaCl + 6% Bentonite Gel + 3% MagOx (TOC @ Surface)
	250	14.8	1.32	Tail: Class C + 10% NaCl + 3% MagOx (TOC @ 6238')
28,578' 6"	650	10.5	3.21	Lead: Class H + 0.4% Halad-344 + 0.35% HR-601 + 3% Microbond (TOC @ 7300')
	1870	13.2	1.52	Tail: Class H + 5% NEX-020 + 0.2% NAC-102 + 0.15% NAS-725 + 0.5% NFL-549 + 0.2% NFP-703 + 1% NBE-737 + 0.3% NRT-241 (TOC @ 12730')




Shallow Design C

Proposed Wellbore

KB: 3558'

GL: 3533'



Triaxial Results															
	Depth (MD) (usft)	Axial Force (lbf)		Equivalent Axial Load (lbf)	Bending Stress at OD (psi)	Absolute Safety Factor				Temperature (°F)	Pressure (psi)		Addtl Pickup To Prevent Buck. (lbf)	Buckled Length (usft)	
		Apparent (w/Bending)	Actual (w/o Bending)			Triaxial	Burst	Collapse (V)	Axial		Internal	External			
1	0	252987	228954	253140	2098.2	1.69	1.58	N/A	2.82 F	70.00	2500.00	0.00	N/A	N/A	
2	100	247735	223702	248466	2098.2	1.69	1.58	N/A	2.88 F	71.10	2543.63	43.63			
3	100	234996	223701	235716	986.2	1.71	1.58	N/A	3.04 F	71.10	2543.64	43.64			
4	1700	341565	139667	352253	17627.2	1.53	1.57	N/A	2.09 F	88.70	3241.64	741.64			
5	1700	312979	139666	323488	15131.5	1.58	1.57	N/A	2.28 F	88.70	3241.65	741.65			
6	1850	336881	132027	348440	17885.2	1.51	1.57	N/A	2.12 F	90.29	3305.05	805.05			
7	1850	318549	132027	329984	16284.8	1.54	1.57	N/A	2.24 F	90.29	3305.06	805.06			
8	1950	320468	127243	332475	16869.9	1.52	1.57	N/A	2.23 F	91.30	3344.87	844.87			
9	1950	312802	127243	324756	16200.7	1.53	1.57	N/A	2.28 F	91.30	3344.87	844.87			
10	2050	307858	122773	320295	16159.3	1.52	1.57	N/A	2.32 F	92.23	3381.89	881.89			
11	2050	303560	122772	315965	15784.1	1.53	1.57	N/A	2.35 F	92.23	3381.89	881.89			
12	2300	151294	112633	163658	3375.4	1.71	1.57	N/A	4.72 F	94.35	3466.13	966.13			
13	2300	132741	112633	144956	1755.6	1.72	1.57	N/A	5.38 F	94.35	3466.14	966.14			
14	2370	129966	109858	142452	1755.6	1.72	1.57	N/A	5.49 F	94.94	3489.28	989.28			
15	2370	127909	107800	140922	1755.6	1.75	1.60	N/A	5.58 F	94.94	3489.29	1036.40			
16	2700	105515	94232	119785	985.1	1.75	1.60	N/A	6.77 F	97.73	3599.97	1152.35			
17	2700	111680	94231	126006	1523.4	1.75	1.60	N/A	6.39 F	97.73	3599.97	1152.35			
18	3100	110766	77783	126839	2879.6	1.71	1.60	N/A	6.44 F	101.11	3734.23	1293.00			
19	3100	97392	77783	113331	1712.1	1.73	1.60	N/A	7.33 F	101.11	3734.23	1293.01			
20	3700	71565	53303	89806	1594.4	1.70	1.61	N/A	9.97 F	106.15	3934.24	1502.54			
21	3700	60887	53302	79004	662.3	1.71	1.61	N/A	11.72 F	106.16	3934.25	1502.55			
22	4650	34671	14219	56495	1785.6	1.64	1.61	N/A	20.59 F	114.20	4253.37	1836.86			
23	4900	44595	4828	67626	3472.0	1.59	1.61	N/A	16.01 F	116.32	4337.37	1924.87			
24	4900	28975	4828	51775	2108.2	1.62	1.61	N/A	24.64 F	116.32	4337.38	1924.87			
25	5029	22103	34	45340	1926.8	1.61	1.61	N/A	32.30 F	117.40	4380.40	1969.94			
26	5029	22102	33	45339	1926.8	1.61	1.61	N/A	32.30 F	117.40	4380.41	1969.95			
27	5600	-45329	-21341	-20805	2094.3	1.57	1.62	N/A	(13.67)	122.23	4572.11	2170.78			
28	5650	-40465	-23210	-15657	1506.5	1.58	1.62	N/A	(15.31)	122.66	4588.87	2188.34			
29															
30		F Conn Fracture													
31		() Compression													
32		(V) Vector Collapse Safety Factor													
33															

Working / Config / Min SF / Load/SF / DF Summary / VME / Wallplot


For Help, press F1

Default Datum @ 0.00 usft API - US Survey Feet jgriffin2

9-5/8" Intermediate Casing Pressure Test:

Internal Profile based off Surface Pressure + Hydrostatic: 4589 psi

External Profile based off Pore Pressure: 2188 psi



StressCheck - [String Summary - Shallow 3.0 Mile - Big Hole *]

String Summary

	String	OD/Weight/Grade	Connection	MD Interval (usft)	Drift Dia. (")	Minimum Safety Factor (Abs)				Design Cost (\$)
						Burst	Collapse (V)	Axial	Triaxial	
1	Intermediate Casing	9 5/8", 40.000 ppg, J-55	BTC, J-55	0.0-5650.0	8.750 A	1.57	1.59	1.80 F	1.35	98,141
2										Total = 98,141
3										
4	F Conn Fracture									
5	A Alternate Drift									
6	(V) Vector Collapse Safety Factor									
7										

*Modelling done with 9-5/8" 40# Intermediate Casing. Passes all Burst, Collapse and Tensile design criteria.



StressCheck - [String Summary - Shallow 3.0 Mile - Big Hole]

String Summary

	String	OD/Weight/Grade	Connection	MD Interval (usft)	Drift Dia. (")	Minimum Safety Factor (Abs)				Design Cost (\$)
						Burst	Collapse (V)	Axial (1.75)	Triaxial	
1	Production Casing	6", 24.500 ppf, P110 ICY	BTC, P110 ICY	0.0-28578.0	5.075	1.29	1.52	(1.75)	1.37	541,493
2										
3										
4	() Compression									
5	(V) Vector Collapse Safety Factor									
6										
										Total = 541,493

*Modelling done with 6" Production Casing with a 125ksi Control Yield. Passes all Burst, Collapse and Tensile design criteria.



Shallow Design D

4. CASING PROGRAM

Hole Size	Interval MD		Interval TVD		Csg OD	Weight	Grade	Conn
	From (ft)	To (ft)	From (ft)	To (ft)				
16"	0	2,030	0	2,030	13-3/8"	54.5#	J-55	STC
11"	0	7,793	0	5,650	9-5/8"	40#	J-55	LTC
7-7/8"	0	12,626	0	10,896	6"	22.3#	P110-EC	DWC/C IS
6-3/4"	12,626	28,578	10,896	11,225	5-1/2"	20#	P110-EC	DWC/C IS MS

Hole will be full during casing run for well control and tensile SF factor. Casing will be kept at least half full during run for this design to meet BLM collapse SF requirement. External pressure will be reviewed prior to conducting casing pressure tests to ensure that 70% of the yield is not exceeded.

Variance is requested to waive the centralizer requirements for the 9-5/8" casing in the 11" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 11" hole interval to maximize cement bond and zonal isolation.

Variance is also requested to waive any centralizer requirements for the 6" and 5-1/2" casings in the 7-7/8" and 6-3/4" hole sizes. An expansion additive will be utilized in the cement slurry for the entire length of the 7-7/8" and 6-3/4" hole intervals to maximize cement bond and zonal isolation.

EOG requests permission to allow deviation from the 0.422" annulus clearance requirement for the intermediate (salt) section from Title 43 CFR Part 3170 under the following conditions:

- The variance is not applicable within the Potash Boundaries or Capitan Reef areas.
- Operator takes responsibility to get casing to set point in the event that the clearance causes stuck pipe issues.

5. CEMENTING PROGRAM:

Depth	No. Sacks	Wt. ppg	Yld Ft3/sk	Slurry Description
2,030' 13-3/8"	570	13.5	1.73	Lead: Class C + 4.0% Bentonite Gel + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	160	14.8	1.34	Tail: Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate (TOC @ 1830')
7,793' 9-5/8"	770	12.7	2.22	Lead: Class C + 10% NaCl + 6% Bentonite Gel + 3% MagOx (TOC @ Surface)
	250	14.8	1.32	Tail: Class C + 10% NaCl + 3% MagOx (TOC @ 6238')
28,578' 6"	650	10.5	3.21	Lead: Class H + 0.4% Halad-344 + 0.35% HR-601 + 3% Microbond (TOC @ 7300')
	1870	13.2	1.52	Tail: Class H + 5% NEX-020 + 0.2% NAC-102 + 0.15% NAS-725 + 0.5% NFL-549 + 0.2% NFP-703 + 1% NBE-737 + 0.3% NRT-241 (TOC @ 12730')




Shallow Design D

Proposed Wellbore

KB: 3558'

GL: 3533'




Triaxial Results														
	Depth (MD) (usft)	Axial Force (lbf)		Equivalent Axial Load (lbf)	Bending Stress at OD (psi)	Absolute Safety Factor				Temperature (°F)	Pressure (psi)		Addtl Pickup To Prevent Buck. (lbf)	Buckled Length (usft)
		Apparent (w/Bending)	Actual (w/o Bending)			Triaxial	Burst	Collapse (V)	Axial		Internal	External		
1	0	252987	228954	253140	2098.2	1.69	1.58	N/A	2.82 F	70.00	2500.00	0.00	N/A	N/A
2	100	247735	223702	248466	2098.2	1.69	1.58	N/A	2.88 F	71.10	2543.63	43.63		
3	100	234996	223701	235716	986.2	1.71	1.58	N/A	3.04 F	71.10	2543.64	43.64		
4	1700	341565	139667	352253	17627.2	1.53	1.57	N/A	2.09 F	88.70	3241.64	741.64		
5	1700	312979	139666	323488	15131.5	1.58	1.57	N/A	2.28 F	88.70	3241.65	741.65		
6	1850	336881	132027	348440	17885.2	1.51	1.57	N/A	2.12 F	90.29	3305.05	805.05		
7	1850	318549	132027	329984	16284.8	1.54	1.57	N/A	2.24 F	90.29	3305.06	805.06		
8	1950	320468	127243	332475	16869.9	1.52	1.57	N/A	2.23 F	91.30	3344.87	844.87		
9	1950	312802	127243	324756	16200.7	1.53	1.57	N/A	2.28 F	91.30	3344.87	844.87		
10	2050	307858	122773	320295	16159.3	1.52	1.57	N/A	2.32 F	92.23	3381.89	881.89		
11	2050	303560	122772	315965	15784.1	1.53	1.57	N/A	2.35 F	92.23	3381.89	881.89		
12	2300	151294	112633	163658	3375.4	1.71	1.57	N/A	4.72 F	94.35	3466.13	966.13		
13	2300	132741	112633	144956	1755.6	1.72	1.57	N/A	5.38 F	94.35	3466.14	966.14		
14	2370	129966	109858	142452	1755.6	1.72	1.57	N/A	5.49 F	94.94	3489.28	989.28		
15	2370	127909	107800	140922	1755.6	1.75	1.60	N/A	5.58 F	94.94	3489.29	1036.40		
16	2700	105515	94232	119785	985.1	1.75	1.60	N/A	6.77 F	97.73	3599.97	1152.35		
17	2700	111680	94231	126006	1523.4	1.75	1.60	N/A	6.39 F	97.73	3599.97	1152.35		
18	3100	110766	77783	126839	2879.6	1.71	1.60	N/A	6.44 F	101.11	3734.23	1293.00		
19	3100	97392	77783	113331	1712.1	1.73	1.60	N/A	7.33 F	101.11	3734.23	1293.01		
20	3700	71565	53303	89806	1594.4	1.70	1.61	N/A	9.97 F	106.15	3934.24	1502.54		
21	3700	60887	53302	79004	662.3	1.71	1.61	N/A	11.72 F	106.16	3934.25	1502.55		
22	4650	34671	14219	56495	1785.6	1.64	1.61	N/A	20.59 F	114.20	4253.37	1836.86		
23	4900	44595	4828	67626	3472.0	1.59	1.61	N/A	16.01 F	116.32	4337.37	1924.87		
24	4900	28975	4828	51775	2108.2	1.62	1.61	N/A	24.64 F	116.32	4337.38	1924.87		
25	5029	22103	34	45340	1926.8	1.61	1.61	N/A	32.30 F	117.40	4380.40	1969.94		
26	5029	22102	33	45339	1926.8	1.61	1.61	N/A	32.30 F	117.40	4380.41	1969.95		
27	5600	-45329	-21341	-20805	2094.3	1.57	1.62	N/A	(13.67)	122.23	4572.11	2170.78		
28	5650	-40465	-23210	-15657	1506.5	1.58	1.62	N/A	(15.31)	122.66	4588.87	2188.34		
29														
30		F	Conn Fracture											
31		()	Compression											
32		(V)	Vector Collapse Safety Factor											
33														

9-5/8" Intermediate Casing Pressure Test:

Internal Profile based off Surface Pressure + Hydrostatic: 4589 psi

External Profile based off Pore Pressure: 2188 psi




StressCheck - [String Summary - Shallow 3.0 Mile - Big Hole *]

String Summary

	String	OD/Weight/Grade	Connection	MD Interval (usft)	Drift Dia. (")	Minimum Safety Factor (Abs)				Design Cost (\$)
						Burst	Collapse (V)	Axial	Triaxial	
1	Intermediate Casing	9 5/8", 40.000 ppf, J-55	BTC, J-55	0.0-5650.0	8.750 A	1.57	1.59	1.80 F	1.35	98,141
2										Total = 98,141
3										
4	F Conn Fracture									
5	A Alternate Drift									
6	(V) Vector Collapse Safety Factor									
7										

*Modelling done with 9-5/8" 40# Intermediate Casing. Passes all Burst, Collapse and Tensile design criteria.




StressCheck - [String Summary - Shallow 3.0 Mile - Big Hole]

String Summary

	String	OD/Weight/Grade	Connection	MD Interval (usft)	Drift Dia. (")	Minimum Safety Factor (Abs)				Design Cost (\$)
						Burst	Collapse (V)	Axial (1.75)	Triaxial	
1	Production Casing	6", 24.500 ppf, P110 ICY	BTC, P110 ICY	0.0-28578.0	5.075	1.29	1.52	(1.75)	1.37	541,493
2										
3										
4	() Compression									
5	(V) Vector Collapse Safety Factor									
6										
										Total = 541,493

*Modelling done with 6" Production Casing with a 125ksi Control Yield. Passes all Burst, Collapse and Tensile design criteria.



StressCheck - [String Summary - Shallow 3.0 Mile]

*Modelling done with 5-1/2" 20# Production Casing with a 125ksi Control Yield. Passes all Burst, Collapse and Tensile design criteria.

**MUD PROGRAM:**

During this procedure we plan to use a Closed-Loop System and haul contents to the required disposal. The applicable depths and properties of the drilling fluid systems are as follows:

Measured Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 – 2,030'	Fresh - Gel	8.6-8.8	28-34	N/c
2,030' – 7,793'	Brine	9-10.5	28-34	N/c
5,450' – 28,578' Lateral	Oil Base	8.8-9.5	58-68	N/c - 6

An electronic pit volume totalizer (PVT) will be utilized on the circulating system, to monitor pit volume, flow rate, pump pressure and stroke rate.

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept at the wellsite at all times.

CEMENTING ADDITIVES:

Additive	Purpose
Bentonite Gel	Lightweight/Lost circulation prevention
Calcium Chloride	Accelerator
Cello-flake	Lost circulation prevention
Sodium Metasilicate	Accelerator
MagOx	Expansive agent
Pre-Mag-M	Expansive agent
Sodium Chloride	Accelerator
FL-62	Fluid loss control
Halad-344	Fluid loss control
Halad-9	Fluid loss control
HR-601	Retarder
Microbond	Expansive Agent

Cement integrity tests will be performed immediately following plug bump.

Note: Cement volumes based on bit size plus at least 25% excess in the open hole plus 10% excess in the cased-hole overlap section.

New Search »

« Back to Previous List

6/8/2015 10:04:37 AM

USC ☒ Metric

Mechanical Properties	Pipe	BTC	LTC	STC	
Minimum Yield Strength	55,000	--	--	--	psi
Maximum Yield Strength	80,000	--	--	--	psi
Minimum Tensile Strength	75,000	--	--	--	psi
Dimenstons	Pipe	BTC	LTC	STC	
Outside Diameter	13.375	14.375	--	14.375	in.
Wall Thickness	0.380	--	--	--	in.
Inside Diameter	12.615	12.615	--	12.615	in.
Standard Drift	12.459	12.459	--	12.459	in.
Alternate Drift	--	--	--	--	in.
Nominal Linear Weight, T&C	54.50	--	--	--	lbs/ft
Plain End Weight	52.79	--	--	--	lbs/ft
Performance	Pipe	BTC	LTC	STC	
Minimum Collapse Pressure	1,130	1,130	--	1,130	psi
Minimum Internal Yield Pressure	2,740	2,740	--	2,740	psi
Minimum Pipe Body Yield Strength	853.00	--	--	--	1000 lbs
Joint Strength	--	909	--	514	1000 lbs
Reference Length	--	11,125	--	6,290	ft
Make-Up Data	Pipe	BTC	LTC	STC	
Make-Up Loss	--	4.81	--	3.50	in.
Minimum Make-Up Torque	--	--	--	3,860	ft-lbs
Maximum Make-Up Torque		--	--	6,430	ft-lbs

New Search »

« Back to Previous List

USC ☒ Metric

6/8/2015 10:23:27 AM

Mechanical Properties	Pipe	BTC	LTC	STC	
Minimum Yield Strength	55,000	--	--	--	psi
Maximum Yield Strength	80,000	--	--	--	psi
Minimum Tensile Strength	75,000	--	--	--	psi
Dimenstons	Pipe	BTC	LTC	STC	
Outside Diameter	9.625	10.625	10.625	10.625	in.
Wall Thickness	0.395	--	--	--	in.
Inside Diameter	8.835	8.835	8.835	8.835	in.
Standard Drift	8.679	8.679	8.679	8.679	in.
Alternate Drift	8.750	8.750	8.750	8.750	in.
Nominal Linear Weight, T&C	40.00	--	--	--	lbs/ft
Plain End Weight	38.97	--	--	--	lbs/ft
Performance	Pipe	BTC	LTC	STC	
Minimum Collapse Pressure	2,570	2,570	2,570	2,570	psi
Minimum Internal Yield Pressure	3,950	3,950	3,950	3,950	psi
Minimum Pipe Body Yield Strength	630.00	--	--	--	1000 lbs
Joint Strength	--	714	520	452	1000 lbs
Reference Length	--	11,898	8,665	7,529	ft
Make-Up Data	Pipe	BTC	LTC	STC	
Make-Up Loss	--	4.81	4.75	3.38	in.
Minimum Make-Up Torque	--	--	3,900	3,390	ft-lbs
Maximum Make-Up Torque	--	--	6,500	5,650	ft-lbs



Connection Data Sheet

OD (in.)	WEIGHT (lbs./ft.)	WALL (in.)	GRADE	API DRIFT (in.)	RBW%	CONNECTION
5.500	Nominal: 20.00 Plain End: 19.83	0.361	VST P110EC	4.653	87.5	DWC/C-IS MS

PIPE PROPERTIES			CONNECTION PROPERTIES		
Outside Diameter	5.500	in.	Connection Type	Semi-Premium T&C	
Inside Diameter	4.778	in.	Connection O.D. (nom)	6.115	in.
Nominal Area	5.828	sq.in.	Connection I.D. (nom)	4.778	in.
Grade Type	API 5CT		Make-Up Loss	4.125	in.
Min. Yield Strength	125	ksi	Coupling Length	9.250	in.
Max. Yield Strength	140	ksi	Critical Cross Section	5.828	sq.in.
Min. Tensile Strength	135	ksi	Tension Efficiency	100.0%	of pipe
Yield Strength	729	klb	Compression Efficiency	100.0%	of pipe
Ultimate Strength	787	klb	Internal Pressure Efficiency	100.0%	of pipe
Min. Internal Yield	14,360	psi	External Pressure Efficiency	100.0%	of pipe
Collapse	12,090	psi			

CONNECTION PERFORMANCES			FIELD END TORQUE VALUES		
Yield Strength	729	klb	Min. Make-up torque	16,100	ft.lb
Parting Load	787	klb	Opti. Make-up torque	17,350	ft.lb
Compression Rating	729	klb	Max. Make-up torque	18,600	ft.lb
Min. Internal Yield	14,360	psi	Min. Shoulder Torque	1,610	ft.lb
External Pressure	12,090	psi	Max. Shoulder Torque	12,880	ft.lb
Maximum Uniaxial Bend Rating	104.2	°/100 ft	Min. Delta Turn	-	Turns
Reference String Length w 1.4 Design Factor	26,040	ft	Max. Delta Turn	0.200	Turns
			Maximum Operational Torque	21,100	ft.lb
			Maximum Torsional Value (MTV)	23,210	ft.lb

Need Help? Contact: tech.support@vam-usa.com
Reference Drawing: 8136PP Rev.01 & 8136BP Rev.01
Date: 12/03/2019
Time: 06:19:27 PM

For detailed information on performance properties, refer to DWC Connection Data Notes on following page(s).

Connection specifications within the control of VAM USA were correct as of the date printed. Specifications are subject to change without notice. Certain connection specifications are dependent on the mechanical properties of the pipe. Mechanical properties of mill proprietary pipe grades were obtained from mill publications and are subject to change. Properties of mill proprietary grades should be confirmed with the mill. Users are advised to obtain current connection specifications and verify pipe mechanical properties for each application.

All information is provided by VAM USA or its affiliates at user's sole risk, without liability for loss, damage or injury resulting from the use thereof; and on an "AS IS" basis without warranty or representation of any kind, whether express or implied, including without limitation any warranty of merchantability, fitness for purpose or completeness. This document and its contents are subject to change without notice. In no event shall VAM USA or its affiliates be responsible for any indirect, special, incidental, punitive, exemplary or consequential loss or damage (including without limitation, loss of use, loss of bargain, loss of revenue, profit or anticipated profit) however caused or arising, and whether such losses or damages were foreseeable or VAM USA or its affiliates was advised of the possibility of such damages.

**VAM USA**

2107 CityWest Boulevard Suite 1300

Houston, TX 77042

Phone: 713-479-3200

Fax: 713-479-3234

VAM® USA Sales E-mail: VAMUSAsales@vam-usa.comTech Support Email: tech.support@vam-usa.com**DWC Connection Data Sheet Notes:**

1. DWC connections are available with a seal ring (SR) option.
2. All standard DWC/C connections are interchangeable for a given pipe OD. DWC connections are interchangeable with DWC/C-SR connections of the same OD and wall.
3. Connection performance properties are based on nominal pipe body and connection dimensions.
4. DWC connection internal and external pressure resistance is calculated using the API rating for buttress connections. API Internal pressure resistance is calculated from formulas 31, 32, and 35 in the API Bulletin 5C3.
5. DWC joint strength is the minimum pipe body yield strength multiplied by the connection critical area.
6. API joint strength is for reference only. It is calculated from formulas 42 and 43 in the API Bulletin 5C3.
7. Bending efficiency is equal to the compression efficiency.
8. The torque values listed are recommended. The actual torque required may be affected by field conditions such as temperature, thread compound, speed of make-up, weather conditions, etc.
9. Connection yield torque is not to be exceeded.
10. Reference string length is calculated by dividing the joint strength by both the nominal weight in air and a design factor (DF) of 1.4. These values are offered for reference only and do not include load factors such as bending, buoyancy, temperature, load dynamics, etc.
11. DWC connections will accommodate API standard drift diameters.
12. DWC/C family of connections are compatible with API Buttress BTC connections. Please contact tech.support@vam-usa.com for details on connection ratings and make-up.



Connection specifications within the control of VAM USA were correct as of the date printed. Specifications are subject to change without notice. Certain connection specifications are dependent on the mechanical properties of the pipe. Mechanical properties of mill proprietary pipe grades were obtained from mill publications and are subject to change. Properties of mill proprietary grades should be confirmed with the mill. Users are advised to obtain current connection specifications and verify pipe mechanical properties for each application.

All information is provided by VAM USA or its affiliates at user's sole risk, without liability for loss, damage or injury resulting from the use thereof; and on an "AS IS" basis without warranty or representation of any kind, whether express or implied, including without limitation any warranty of merchantability, fitness for purpose or completeness. This document and its contents are subject to change without notice. In no event shall VAM USA or its affiliates be responsible for any indirect, special, incidental, punitive, exemplary or consequential loss or damage (including without limitation, loss of use, loss of bargain, loss of revenue, profit or anticipated profit) however caused or arising, and whether such losses or damages were foreseeable or VAM USA or its affiliates was advised of the possibility of such damages.

New Search »

« Back to Previous List

USC ☒ Metric

6/8/2015 10:14:05 AM

Mechanical Properties	Pipe	BTC	LTC	STC	
Minimum Yield Strength	55,000	--	--	--	psi
Maximum Yield Strength	80,000	--	--	--	psi
Minimum Tensile Strength	75,000	--	--	--	psi
Dimenstons	Pipe	BTC	LTC	STC	
Outside Diameter	10.750	11.750	--	11.750	in.
Wall Thickness	0.350	--	--	--	in.
Inside Diameter	10.050	10.050	--	10.050	in.
Standard Drift	9.894	9.894	--	9.894	in.
Alternate Drift	--	--	--	--	in.
Nominal Linear Weight, T&C	40.50	--	--	--	lbs/ft
Plain End Weight	38.91	--	--	--	lbs/ft
Performance	Pipe	BTC	LTC	STC	
Minimum Collapse Pressure	1,580	1,580	--	1,580	psi
Minimum Internal Yield Pressure	3,130	3,130	--	3,130	psi
Minimum Pipe Body Yield Strength	629.00	--	--	--	1000 lbs
Joint Strength	--	700	--	420	1000 lbs
Reference Length	--	11,522	--	6,915	ft
Make-Up Data	Pipe	BTC	LTC	STC	
Make-Up Loss	--	4.81	--	3.50	in.
Minimum Make-Up Torque	--	--	--	3,150	ft-lbs
Maximum Make-Up Torque	Page 28 of 32	--	--	5,250	ft-lbs



API 5CT, 10th Ed. Connection Data Sheet

O.D. (in)	WEIGHT (lb/ft)	WALL (in)	GRADE	*API DRIFT (in)	RBW %
8.625	Nominal: 32.00 Plain End: 31.13	0.352	J55	7.796	87.5

Material Properties (PE)

Pipe	
Minimum Yield Strength:	55 ksi
Maximum Yield Strength:	80 ksi
Minimum Tensile Strength:	75 ksi
Coupling	
Minimum Yield Strength:	55 ksi
Maximum Yield Strength:	80 ksi
Minimum Tensile Strength:	75 ksi

Pipe Body Data (PE)

Geometry	
Nominal ID:	7.92 inch
Nominal Area:	9.149 in ²
*Special/Alt. Drift:	7.875 inch
Performance	
Pipe Body Yield Strength:	503 kips
Collapse Resistance:	2,530 psi
Internal Yield Pressure: (API Historical)	3,930 psi

API Connection Data

Coupling OD: 9.625"

STC Performance	
STC Internal Pressure:	3,930 psi
STC Joint Strength:	372 kips
LTC Performance	
LTC Internal Pressure:	3,930 psi
LTC Joint Strength:	417 kips
SC-BTC Performance - Cplg OD = 9.125"	
BTC Internal Pressure:	3,930 psi
BTC Joint Strength:	503 kips

API Connection Torque

STC Torque (ft-lbs)			
Min:	2,793	Opti:	3,724
		Max:	4,655
LTC Torque (ft-lbs)			
Min:	3,130	Opti:	4,174
		Max:	5,217
BTC Torque (ft-lbs)			
follow API guidelines regarding positional make up			

*Alt. Drift will be used unless API Drift is specified on order.

**If above API connections do not suit your needs, VAM® premium connections are available up to 100% of pipe body ratings.

ALL INFORMATION IS PROVIDED BY VALLOUREC OR ITS AFFILIATES AT USER'S SOLE RISK, WITHOUT LIABILITY FOR LOSS, DAMAGE OR INJURY RESULTING FROM THE USE THEREOF; AND ON AN "AS IS" BASIS WITHOUT WARRANTY OR REPRESENTATION OF ANY KIND, WHETHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR PURPOSE, ACCURACY OR COMPLETENESS. THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED FOR INFORMATIONAL PURPOSES ONLY AND IS BASED ON ESTIMATES THAT HAVE NOT BEEN VERIFIED OR TESTED. IN NO EVENT SHALL VALLOUREC OR ITS AFFILIATES BE RESPONSIBLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE, EXEMPLARY OR CONSEQUENTIAL LOSS OR DAMAGE (INCLUDING WITHOUT LIMITATION, LOSS OF USE, LOSS OF BARGAIN, LOSS OF REVENUE, PROFIT OR ANTICIPATED PROFIT) HOWEVER CAUSED OR ARISING, AND WHETHER SUCH LOSSES OR DAMAGES WERE FORESEEABLE OR VALLOUREC OR ITS AFFILIATES WERE ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Rev 3, 7/30/2021

10/21/2022 15:24

VALLOUREC STAR 8.625 32# J55 S S2L2 DA 7.875 W/O# SLN# PO# MADE IN USA FT LB

Issued on: 10 Feb. 2021 by Wesley Ott

VAM® SPRINT-SF
Connection Data Sheet

OD 6 in.	Weight (lb/ft) Nominal: 24.50 Plain End: 23.95	Wall Th. 0.400 in.	Grade P110EC	API Drift: 5.075 in.	Connection VAM® SPRINT-SF
-------------	--	-----------------------	-----------------	-------------------------	------------------------------

PIPE PROPERTIES		
Nominal OD	6.000	in.
Nominal ID	5.200	in.
Nominal Cross Section Area	7.037	sqin.
Grade Type	High Yield	
Min. Yield Strength	125	ksi
Max. Yield Strength	140	ksi
Min. Ultimate Tensile Strength	135	ksi

CONNECTION PROPERTIES		
Connection Type	Integral Semi-Flush	
Connection OD (nom):	6.277	in.
Connection ID (nom):	5.146	in.
Make-Up Loss	5.386	in.
Critical Cross Section	6.417	sqin.
Tension Efficiency	91.0	% of pipe
Compression Efficiency	91.0	% of pipe
Internal Pressure Efficiency	100	% of pipe
External Pressure Efficiency	100	% of pipe

CONNECTION PERFORMANCES		
Tensile Yield Strength	801	klb
Compression Resistance	801	klb
Internal Yield Pressure	14,580	psi
Collapse Resistance	12,500	psi
Max. Structural Bending	83	°/100ft
Max. Bending with ISO/API Sealability	30	°/100ft

* 87.5% RBW

TORQUE VALUES		
Min. Make-up torque	21,750	ft.lb
Opt. Make-up torque	24,250	ft.lb
Max. Make-up torque	26,750	ft.lb
Max. Torque with Sealability (MTS)	53,000	ft.lb

VAM® SPRINT-SF is a semi-flush connection innovatively designed for extreme shale applications. Its high tension rating and ultra high torque capacity make it ideal to run a fill string length as production casing in shale wells with extended horizontal sections and tight clearance requirements.



canada@vamfieldservice.com
usa@vamfieldservice.com
mexico@vamfieldservice.com
brazil@vamfieldservice.com

Do you need help on this product? - Remember no one knows VAM® like VAM®

uk@vamfieldservice.com
dubai@vamfieldservice.com
nigeria@vamfieldservice.com
angola@vamfieldservice.com

china@vamfieldservice.com
baku@vamfieldservice.com
singapore@vamfieldservice.com
australia@vamfieldservice.com

Over 140 VAM® Specialists available worldwide 24/7 for Rig Site Assistance





Connection Data Sheet

OD (in.)	WEIGHT (lbs./ft.)	WALL (in.)	GRADE	API DRIFT (in.)	RBW%	CONNECTION
6.000	Nominal: 22.30 Plain End: 21.70	0.360	VST P110EC	5.155	92.5	DWC/C-IS

PIPE PROPERTIES

Nominal OD	6.000	in.
Nominal ID	5.280	in.
Nominal Area	6.379	sq.in.
Grade Type	API 5CT	
Min. Yield Strength	125	ksi
Max. Yield Strength	140	ksi
Min. Tensile Strength	135	ksi
Yield Strength	797	klb
Ultimate Strength	861	klb
Min. Internal Yield Pressure	13,880	psi
Collapse Pressure	9,800	psi

CONNECTION PERFORMANCES

Yield Strength	797	klb
Parting Load	861	klb
Compression Rating	797	klb
Min. Internal Yield	13,880	psi
External Pressure	9,800	psi
Maximum Uniaxial Bend Rating	47.7	°/100 ft
Reference String Length w 1.4 Design Factor	25,530	ft.

CONNECTION PROPERTIES

Connection Type	Semi-Premium T&C
Connection OD (nom)	6.650 in.
Connection ID (nom)	5.280 in.
Make-Up Loss	4.313 in.
Coupling Length	9.625 in.
Critical Cross Section	6.379 sq.in.
Tension Efficiency	100.0% of pipe
Compression Efficiency	100.0% of pipe
Internal Pressure Efficiency	100.0% of pipe
External Pressure Efficiency	100.0% of pipe

FIELD END TORQUE VALUES

Min. Make-up torque	17,000	ft.lb
Opti. Make-up torque	18,250	ft.lb
Max. Make-up torque	19,500	ft.lb
Min. Shoulder Torque	1,700	ft.lb
Max. Shoulder Torque	13,600	ft.lb
Min. Delta Turn	-	Turns
Max. Delta Turn	0.200	Turns
Maximum Operational Torque	24,200	ft.lb
Maximum Torsional Value (MTV)	26,620	ft.lb

Need Help? Contact: tech.support@vam-usa.com

Reference Drawing: 8135PP Rev.02 & 8135BP Rev.02

Date: 07/30/2020

Time: 07:50:47 PM

For detailed information on performance properties, refer to DWC Connection Data Notes on following page(s).

Connection specifications within the control of VAM USA were correct as of the date printed. Specifications are subject to change without notice. Certain connection specifications are dependent on the mechanical properties of the pipe. Mechanical properties of mill proprietary pipe grades were obtained from mill publications and are subject to change. Properties of mill proprietary grades should be confirmed with the mill. Users are advised to obtain current connection specifications and verify pipe mechanical properties for each application.

All information is provided by VAM USA or its affiliates at user's sole risk, without liability for loss, damage or injury resulting from the use thereof; and on an "AS IS" basis without warranty or representation of any kind, whether express or implied, including without limitation any warranty of merchantability, fitness for purpose or completeness. This document and its contents are subject to change without notice. In no event shall VAM USA or its affiliates be responsible for any indirect, special, incidental, punitive, exemplary or consequential loss or damage (including without limitation, loss of use, loss of bargain, loss of revenue, profit or anticipated profit) however caused or arising, and whether such losses or damages were foreseeable or VAM USA or its affiliates was advised of the possibility of such damages.





VAM USA
2107 CityWest Boulevard Suite 1300
Houston, TX 77042
Phone: 713-479-3200
Fax: 713-479-3234

VAM® USA Sales E-mail: VAMUSAsales@vam-usa.com
Tech Support Email: tech.support@vam-usa.com

DWC Connection Data Sheet Notes:

1. DWC connections are available with a seal ring (SR) option.
2. All standard DWC/C connections are interchangeable for a given pipe OD. DWC connections are interchangeable with DWC/C-SR connections of the same OD and wall.
3. Connection performance properties are based on nominal pipe body and connection dimensions.
4. DWC connection internal and external pressure resistance is calculated using the API rating for buttress connections. API Internal pressure resistance is calculated from formulas 31, 32, and 35 in the API Bulletin 5C3.
5. DWC joint strength is the minimum pipe body yield strength multiplied by the connection critical area.
6. API joint strength is for reference only. It is calculated from formulas 42 and 43 in the API Bulletin 5C3.
7. Bending efficiency is equal to the compression efficiency.
8. The torque values listed are recommended. The actual torque required may be affected by field conditions such as temperature, thread compound, speed of make-up, weather conditions, etc.
9. Connection yield torque is not to be exceeded.
10. Reference string length is calculated by dividing the joint strength by both the nominal weight in air and a design factor (DF) of 1.4. These values are offered for reference only and do not include load factors such as bending, buoyancy, temperature, load dynamics, etc.
11. DWC connections will accommodate API standard drift diameters.
12. DWC/C family of connections are compatible with API Buttress BTC connections. Please contact tech.support@vam-usa.com for details on connection ratings and make-up.

Connection specifications within the control of VAM USA were correct as of the date printed. Specifications are subject to change without notice. Certain connection specifications are dependent on the mechanical properties of the pipe. Mechanical properties of mill proprietary pipe grades were obtained from mill publications and are subject to change. Properties of mill proprietary grades should be confirmed with the mill. Users are advised to obtain current connection specifications and verify pipe mechanical properties for each application.

All information is provided by VAM USA or its affiliates at user's sole risk, without liability for loss, damage or injury resulting from the use thereof; and on an "AS IS" basis without warranty or representation of any kind, whether express or implied, including without limitation any warranty of merchantability, fitness for purpose or completeness. This document and its contents are subject to change without notice. In no event shall VAM USA or its affiliates be responsible for any indirect, special, incidental, punitive, exemplary or consequential loss or damage (including without limitation, loss of use, loss of bargain, loss of revenue, profit or anticipated profit) however caused or arising, and whether such losses or damages were foreseeable or VAM USA or its affiliates was advised of the possibility of such damages.




**Break-test BOP & Offline Cementing:**

EOG Resources Inc. (EOG) respectfully requests a variance from the minimum standards for well control equipment testing of ECFR Title 43 Part 3172.6(b)(9)(iv) to allow a testing schedule of the blow out preventer (BOP) and blow out prevention equipment (BOPE) along with Batch Drilling & Offline cement operations to include the following:

- Full BOPE test at first installation on the pad.
- Full BOPE test every 21 days.
- This test will be conducted for 5M rated hole intervals only.
- Each rig requesting the break-test variance is capable of picking up the BOP without damaging components using winches, following API Standard 53, Well Control Equipment Systems for Drilling Wells (Fifth edition, December 2018, Annex C. Table C.4) which recognizes break testing as an acceptable practice.
- Function tests will be performed on the following BOP elements:
 - Annular ð during each full BOPE test
 - Upper Pipe Rams ð On trip ins where FIT required
 - Blind Rams ð Every trip
 - Lower Pipe Rams ð during each full BOPE test
- Break testing BOP and BOPE coupled with batch drilling operations and option to offline cement and/or remediate (if needed) any surface or intermediate sections, according to attached offline cementing support documentation.
- After the well section is secured, the BOP will be disconnected from the wellhead and walked with the rig to another well on the pad.
- TA cap will also be installed per Wellhead vendor procedure and pressure inside the casing will be monitored via the valve on the TA cap as per standard batch drilling ops.

Break Test Diagram (HCR valve)



Steps

1. Set plug in wellhead (lower barrier)
2. Close Blind Rams (upper barrier)
3. Close roadside kill
4. Open HCR (pressure application)
5. Open wellhead valves below test plug to ensure if leak past test plug, pressure won't be applied to wellbore
6. Tie BOP testers high pressure line to main choke manifold crown valve
7. Pressure up to test break
8. Bleed test pressure from BOP testing unit

Break Test Diagram (Test Joint)



Steps

1. Set plug in with test joint wellhead (lower barrier)
2. Close Upper Pipe Rams (upper barrier)
3. Close roadside kill
4. Close HCR
5. Open wellhead valves below test plug to ensure if leak past test plug, pressure won't be applied to wellbore
6. Tie BOP testers high pressure line to top of test joint
7. Pressure up to test break
8. Bleed test pressure from BOP testing unit



Offline Intermediate Cementing Procedure

2/24/2022

Cement Program

1. No changes to the cement program will take place for offline cementing.

Summarized Operational Procedure for Intermediate Casing

1. Run casing as per normal operations. While running casing, conduct negative pressure test and confirm integrity of the float equipment back pressure valves.
 - a. Float equipment is equipped with two back pressure valves rated to a minimum of 5,000 psi.
2. Land production casing on mandrel hanger through BOP.
 - a. If casing is unable to be landed with a mandrel hanger, then the **casing will be cemented online**.
3. Break circulation and confirm no restrictions.
 - a. Ensure no blockage of float equipment and appropriate annular returns.
 - b. Perform flow check to confirm well is static.
4. Set pack-off
 - a. If utilizing a fluted/ported mandrel hanger, ensure well is static on the annulus and inside the casing by filling the pipe with kill weight fluid, remove landing joint, and set annular packoff through BOP. Pressure test to 5,000 psi for 10 min.
 - b. If utilizing a solid mandrel hanger, ensure well is static on the annulus and inside the casing by filling the pipe with kill weight fluid. Pressure test seals to 5,000 psi for 10 min. Remove landing joint through BOP.
5. After confirmation of both annular barriers and the two casing barriers, install TA plug and pressure test to 5,000 psi for 10 min. Notify the BLM with intent to proceed with nipple down and offline cementing.
 - a. Minimum 4 hrs notice.
6. With the well secured and BLM notified, nipple down BOP and secure on hydraulic carrier or cradle.
 - a. **Note, if any of the barriers fail to test, the BOP stack will not be nipped down until after the cement job has concluded and both lead and tail slurry have reached 500 psi.**
7. Skid/Walk rig off current well.
8. Confirm well is static before removing TA Plug.
 - a. Cementing operations will not proceed until well is under control. (If well is not static, notify BLM and proceed to kill)
 - b. Casing outlet valves will provide access to both the casing ID and annulus. Rig or third party pump truck will kill well prior to cementing.
 - c. Well control plan can be seen in Section B, Well Control Procedures.
 - d. If need be, rig can be moved back over well and BOP nipped back up for any further remediation.



Offline Intermediate Cementing Procedure

2/24/2022

- e. Diagram for rig positioning relative to offline cementing can be seen in Figure 4.
9. Rig up return lines to take returns from wellhead to pits and rig choke.
 - a. Test all connections and lines from wellhead to choke manifold to 5,000 psi high for 10 min.
 - b. If either test fails, perform corrections and retest before proceeding.
 - c. Return line schematics can be seen in Figure 3.
10. Remove TA Plug from the casing.
11. Install offline cement tool.
 - a. Current offline cement tool schematics can be seen in Figure 1 (Cameron) and Figure 2 (Cactus).
12. Rig up cement head and cementing lines.
 - a. Pressure test cement lines against cement head to 80% of casing burst for 10 min.
13. Break circulation on well to confirm no restrictions.
 - a. If gas is present on circulation, well will be shut in and returns rerouted through gas buster.
 - b. Max anticipated time before circulating with cement truck is 6 hrs.
14. Pump cement job as per plan.
 - a. At plug bump, test casing to 0.22 psi/ft or 1500 psi, whichever is greater.
 - b. If plug does not bump on calculated, shut down and wait 8 hrs or 500 psi compressive strength, whichever is greater before testing casing.
15. Confirm well is static and floats are holding after cement job.
 - a. With floats holding and backside static:
 - i. Remove cement head.
 - b. If floats are leaking:
 - i. Shut-in well and WOC (Wait on Cement) until tail slurry reaches 500 psi compressive strength and the casing is static prior to removing cement head.
 - c. If there is flow on the backside:
 - i. Shut in well and WOC until tail slurry reaches 500 psi compressive strength. Ensure that the casing is static prior to removing cement head.
16. Remove offline cement tool.
17. Install night cap with pressure gauge for monitoring.
18. Test night cap to 5,000 psi for 10 min.



Offline Intermediate Cementing Procedure

2/24/2022

Example Well Control Plan Content

A. Well Control Component Table

The table below, which covers the cementing of the **5M MASP (Maximum Allowable Surface Pressure) portion of the well**, outlines the well control component rating in use. This table, combined with the mud program, documents that two barriers to flow can be maintained at all times, independent of the BOP nipped up to the wellhead.

Intermediate hole section, 5M requirement

Component	RWP
Pack-off	10M
Casing Wellhead Valves	10M
Annular Wellhead Valves	5M
TA Plug	10M
Float Valves	5M
2" 1502 Lo-Torque Valves	15M

B. Well Control Procedures

Well control procedures are specific to the rig equipment and the operation at the time the kick occurs. Below are the minimal high-level tasks prescribed to assure a proper shut-in while circulating and cementing through the Offline Cement Adapter.

General Procedure While Circulating

1. Sound alarm (alert crew).
2. Shut down pumps.
3. Shut-in Well (close valves to rig pits and open valve to rig choke line. Rig choke will already be in the closed position).
4. Confirm shut-in.
5. Notify tool pusher/company representative.



Offline Intermediate Cementing Procedure

2/24/2022

6. Read and record the following:
 - a. SICP (Shut in Casing Pressure) and AP (Annular Pressure)
 - b. Pit gain
 - c. Time
 - d. Regroup and identify forward plan to continue circulating out kick via rig choke and mud/gas separator. Circulate and adjust mud density as needed to control well.

General Procedure While Cementing

1. Sound alarm (alert crew).
2. Shut down pumps.
3. Shut-in Well (close valves to rig pits and open valve to rig choke line. Rig choke will already be in the closed position).
4. Confirm shut-in.
5. Notify tool pusher/company representative.
6. Open rig choke and begin pumping again taking returns through choke manifold and mud/gas separator.
7. Continue to place cement until plug bumps.
8. At plug bump close rig choke and cement head.
9. Read and record the following
 - a. SICP and AP
 - b. Pit gain
 - c. Time
 - d. Shut-in annulus valves on wellhead

General Procedure After Cementing

1. Sound alarm (alert crew).
2. Shut-in Well (close valves to rig pits and open valve to rig choke line. Rig choke will already be in the closed position).
3. Confirm shut-in.
4. Notify tool pusher/company representative.
5. Read and record the following:
 - a. SICP and AP
 - b. Pit gain
 - c. Time
 - d. Shut-in annulus valves on wellhead



Offline Intermediate Cementing Procedure

2/24/2022

Figure 1: Cameron TA Plug and Offline Adapter Schematic





Offline Intermediate Cementing Procedure

2/24/2022

Figure 2: Cactus TA Plug and Offline Adapter Schematic






Offline Intermediate Cementing Procedure

2/24/2022

Figure 3: Back Yard Rig Up





Offline Intermediate Cementing Procedure

2/24/2022

Figure 4: Rig Placement Diagram





Salt Section Annular Clearance Variance Request

Daniel Moose

Current Design (Salt Strings)

0.422" Annular clearance requirement

- Casing collars shall have a minimum clearance of 0.422 inches on all sides in the hole/casing annulus, with recognition that variances can be granted for justified exceptions.

- 12.25" Hole x 9.625" 40# J55/HCK55 LTC Casing
 - 1.3125" Clearance to casing OD
 - 0.8125" Clearance to coupling OD
- 9.875" Hole x 8.75" 38.5# P110 Sprint-SF Casing
 - 0.5625" Clearance to casing OD
 - 0.433" Clearance to coupling OD

Annular Clearance Variance Request

EOG request permission to allow deviation from the 0.422" annulus clearance requirement for the intermediate (salt) section from Onshore Order #2 under the following conditions:

- The variance is not applicable within the Potash Boundaries or Capitan Reef areas.
- Operator takes responsibility to get casing to set point in the event that the clearance causes stuck pipe issues


Volumetric Hole Size Calculation

Hole Size Calculations Off Cement Volumes

- Known volume of cement pumped
- Known volume of cement returned to surface
- Must not have had any losses
- Must have bumped plug

Average Hole Size


- 12.25" Hole
 - 12.88" Hole
 - 5.13% diameter increase
 - 10.52% area increase
 - 0.63" Average enlargement
 - 0.58" Median enlargement
 - 179 Well Count
- 9.875" Hole
 - 10.30" Hole
 - 4.24% diameter increase
 - 9.64% area increase
 - 0.42" Average enlargement
 - 0.46" Median enlargement
 - 11 Well Count



Caliper Hole Size (12.25")

Average Hole Size

- 12.25" Bit
 - 12.76" Hole
 - 4.14% diameter increase
 - 8.44% area increase
 - 0.51" Average enlargement
 - 0.52" Median enlargement
 - Brine



Caliper Hole Size (9.875")

Average Hole Size

- 9.875" Hole
 - 11.21" Hole
 - 13.54% diameter increase
 - 28.92% area increase
 - 1.33" Average enlargement
 - 1.30" Median enlargement
 - EnerLite

Whirling Wind 11 Fed Com #744H



Design A

Proposed 11" Hole with 9.625" 40# J55/HCK55 LTC Casing

- 11" Bit + 0.52" Average hole enlargement = 11.52" Hole Size
 - 0.9475" Clearance to casing OD

$$= \frac{11.52 - 9.625}{2}$$
 - 0.4475" Clearance to coupling OD

$$= \frac{11.52 - 10.625}{2}$$
- Previous Shoe – 13.375" 54.5# J55 STC
 - 0.995" Clearance to coupling OD (~1,200' overlap)

$$= \frac{12.615 - 10.625}{2}$$



Design B


Proposed 9.875" Hole with 8.625" 32# J55/P110 BTC-SC Casing

- 9.875" Bit + 0.42" Average hole enlargement = 10.295" Hole Size
 - 0.835" Clearance to casing OD

$$= \frac{10.295 - 8.625}{2}$$
 - 0.585" Clearance to coupling OD

$$= \frac{10.295 - 9.125}{2}$$
- Previous Shoe – 10.75" 40.5# J55 STC
 - 0.4625" Clearance to coupling OD (~1,200' overlap)

$$= \frac{10.05 - 9.125}{2}$$





Index

Casing Spec Sheets

PERFORMANCE DATA

API LTC

Technical Data Sheet

9.625 in

40.00 lbs/ft

K55 HC

Tubular Parameters

Size	9.625	in	Minimum Yield	55	ksi
Nominal Weight	40.00	lbs/ft	Minimum Tensile	95	ksi
Grade	K55 HC		Yield Load	629	kips
PE Weight	38.94	lbs/ft	Tensile Load	1088	kips
Wall Thickness	0.395	in	Min. Internal Yield Pressure	3,950	psi
Nominal ID	8.835	in	Collapse Pressure	3600	psi
Drift Diameter	8.750	in			
Nom. Pipe Body Area	11.454	in²			

Connection Parameters

Connection OD	10.625	in
Coupling Length	10.500	in
Threads Per Inch	8	tpi
Standoff Thread Turns	3.50	turns
Make-Up Loss	4.750	in
Min. Internal Yield Pressure	3,950	psi

Pipe Body and API Connections Performance Data

13.375 54.50/0.380 J55

PDF

New Search »

« Back to Previous List

USC ☒ Metric

6/8/2015 10:04:37 AM

Mechanical Properties	Pipe	BTC	LTC	STC	
Minimum Yield Strength	55,000	--	--	--	psi
Maximum Yield Strength	80,000	--	--	--	psi
Minimum Tensile Strength	75,000	--	--	--	psi
Dimensions	Pipe	BTC	LTC	STC	
Outside Diameter	13.375	14.375	--	14.375	in.
Wall Thickness	0.380	--	--	--	in.
Inside Diameter	12.615	12.615	--	12.615	in.
Standard Drift	12.459	12.459	--	12.459	in.
Alternate Drift	--	--	--	--	in.
Nominal Linear Weight, T&C	54.50	--	--	--	lbs/ft
Plain End Weight	52.79	--	--	--	lbs/ft
Performance	Pipe	BTC	LTC	STC	
Minimum Collapse Pressure	1,130	1,130	--	1,130	psi
Minimum Internal Yield Pressure	2,740	2,740	--	2,740	psi
Minimum Pipe Body Yield Strength	853.00	--	--	--	1000 lbs
Joint Strength	--	909	--	514	1000 lbs
Reference Length	--	11,125	--	6,290	ft
Make-Up Data	Pipe	BTC	LTC	STC	
Make-Up Loss	--	4.81	--	3.50	in.
Minimum Make-Up Torque	--	--	--	3,860	ft-lbs
Maximum Make-Up Torque	--	--	--	6,430	ft-lbs



Casing Spec Sheets

Pipe Body and API Connections Performance Data

10.750 40.50/0.350 J55

PDF

New Search »

« Back to Previous List

USC ☒ Metric

6/8/2015 10:14:05 AM

Mechanical Properties	Pipe	BTC	LTC	STC	
Minimum Yield Strength	55,000	--	--	--	psi
Maximum Yield Strength	80,000	--	--	--	psi
Minimum Tensile Strength	75,000	--	--	--	psi
Dimensions	Pipe	BTC	LTC	STC	
Outside Diameter	10.750	11.750	--	11.750	in.
Wall Thickness	0.350	--	--	--	in.
Inside Diameter	10.050	10.050	--	10.050	in.
Standard Drift	9.894	9.894	--	9.894	in.
Alternate Drift	--	--	--	--	in.
Nominal Linear Weight, T&C	40.50	--	--	--	lbs/ft
Plain End Weight	38.91	--	--	--	lbs/ft
Performance	Pipe	BTC	LTC	STC	
Minimum Collapse Pressure	1,580	1,580	--	1,580	psi
Minimum Internal Yield Pressure	3,130	3,130	--	3,130	psi
Minimum Pipe Body Yield Strength	629.00	--	--	--	1000 lbs
Joint Strength	--	700	--	420	1000 lbs
Reference Length	--	11,522	--	6,915	ft
Make-Up Data	Pipe	BTC	LTC	STC	
Make-Up Loss	--	4.81	--	3.50	in.
Minimum Make-Up Torque	--	--	--	3,150	ft-lbs
Maximum Make-Up Torque	--	--	--	5,250	ft-lbs



API 5CT, 10th Ed. Connection Data Sheet

O.D. (in)	WEIGHT (lb/ft)	WALL (in)	GRADE	*API DRIFT (in)	RBW %
8.625	Nominal: 32.00 Plain End: 31.13	0.352	J55	7.796	87.5

Material Properties (PE)		Pipe Body Data (PE)	
Pipe		Geometry	
Minimum Yield Strength:	55 ksi	Nominal ID:	7.92 inch
Maximum Yield Strength:	80 ksi	Nominal Area:	9.149 in ²
Minimum Tensile Strength:	75 ksi	*Special/Alt. Drift:	7.875 inch
Coupling		Performance	
Minimum Yield Strength:	55 ksi	Pipe Body Yield Strength:	503 kips
Maximum Yield Strength:	80 ksi	Collapse Resistance:	2,530 psi
Minimum Tensile Strength:	75 ksi	Internal Yield Pressure: (API Historical)	3,930 psi

API Connection Data		API Connection Torque	
Coupling OD: 9.625"		STC Torque (ft-lbs)	
STC Performance		Min: 2,793 Opti: 3,724 Max: 4,655	
STC Internal Pressure: 3,930 psi		LTC Torque (ft-lbs)	
STC Joint Strength: 372 kips		Min: 3,130 Opti: 4,174 Max: 5,217	
LTC Performance		BTC Torque (ft-lbs)	
LTC Internal Pressure: 3,930 psi		follow API guidelines regarding positional make up	
LTC Joint Strength: 417 kips			
SC-BTC Performance - Cplg OD = 9.125"			
BTC Internal Pressure: 3,930 psi			
BTC Joint Strength: 503 kips			

*Alt. Drift will be used unless API Drift is specified on order.

**If above API connections do not suit your needs, VAM® premium connections are available up to 100% of pipe body ratings.

ALL INFORMATION IS PROVIDED BY VALLOUREC OR ITS AFFILIATES AT USER'S SOLE RISK, WITHOUT LIABILITY FOR LOSS, DAMAGE OR INJURY RESULTING FROM THE USE THEREOF, AND ON AN "AS IS" BASIS WITHOUT WARRANTY OR REPRESENTATION OF ANY KIND, WHETHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR PURPOSE, ACCURACY OR COMPLETENESS. THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED FOR INFORMATIONAL PURPOSES ONLY AND IS BASED ON ESTIMATES THAT HAVE NOT BEEN VERIFIED OR TESTED. IN NO EVENT SHALL VALLOUREC OR ITS AFFILIATES BE RESPONSIBLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE, EXEMPLARY OR CONSEQUENTIAL LOSS OR DAMAGE (INCLUDING WITHOUT LIMITATION, LOSS OF USE, LOSS OF BARGAIN, LOSS OF REVENUE, PROFIT OR ANTICIPATED PROFIT) HOWEVER CAUSED OR ARISING, AND WHETHER SUCH LOSSES OR DAMAGES WERE FORESEEABLE OR VALLOUREC OR ITS AFFILIATES WERE ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Rev 3, 7/30/2021

10/21/2022 15:24



Annular Clearance Variance

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 349162

CONDITIONS

Operator: EOG RESOURCES INC 5509 Champions Drive Midland, TX 79706	OGRID: 7377
	Action Number: 349162
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
pkautz	None	9/30/2024