Form 3160-3 FORM APPROVED OMB No. 1004-0137 (June 2015) Expires: January 31, 2018 **UNITED STATES** DEPARTMENT OF THE INTERIOR 5. Lease Serial No. BUREAU OF LAND MANAGEMENT APPLICATION FOR PERMIT TO DRILL OR REENTER 6. If Indian, Allotee or Tribe Name 7. If Unit or CA Agreement, Name and No. DRILL REENTER 1a. Type of work: 1b. Type of Well: Oil Well Gas Well Other 8. Lease Name and Well No. 1c. Type of Completion: Hydraulic Fracturing Single Zone Multiple Zone 2. Name of Operator 9. API Well No. 30-015-55690 10. Field and Pool, or Exploratory 3a. Address 3b. Phone No. (include area code) 4. Location of Well (Report location clearly and in accordance with any State requirements.*) 11. Sec., T. R. M. or Blk. and Survey or Area At surface At proposed prod. zone 14. Distance in miles and direction from nearest town or post office* 12. County or Parish 13. State 15. Distance from proposed* 16. No of acres in lease 17. Spacing Unit dedicated to this well location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 18. Distance from proposed location* 19. Proposed Depth 20. BLM/BIA Bond No. in file to nearest well, drilling, completed, applied for, on this lease, ft. 21. Elevations (Show whether DF, KDB, RT, GL, etc.) 22. Approximate date work will start* 23. Estimated duration 24. Attachments The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable) 1. Well plat certified by a registered surveyor. 4. Bond to cover the operations unless covered by an existing bond on file (see 2. A Drilling Plan. Item 20 above). 3. A Surface Use Plan (if the location is on National Forest System Lands, the 5. Operator certification. SUPO must be filed with the appropriate Forest Service Office). 6. Such other site specific information and/or plans as may be requested by the 25. Signature Name (Printed/Typed) Date Title Approved by (Signature) Name (Printed/Typed) Date Title Office Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction APPROVED WITH CONDITIONS

(Continued on page 2)

*(Instructions on page 2)

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM I: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the wen, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionany drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

ITEM 24: If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service wen or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record win be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM conects this information to anow evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Conection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

Additional Operator Remarks

Location of Well

0. SHL: NWNW / 420 FNL / 1176 FWL / TWSP: 20S / RANGE: 30E / SECTION: 11 / LAT: 32.59383 / LONG: -103.94743 (TVD: 0 feet, MD: 0 feet) PPP: SESE / 319 FSL / 0 FEL / TWSP: 20S / RANGE: 30E / SECTION: 5 / LAT: 32.59603 / LONG: -103.98561 (TVD: 9541 feet, MD: 21288 feet) PPP: SESW / 316 FSL / 2632 FEL / TWSP: 20S / RANGE: 30E / SECTION: 4 / LAT: 32.59601 / LONG: -103.97706 (TVD: 9541 feet, MD: 18656 feet) PPP: SESE / 330 FSL / 100 FEL / TWSP: 20S / RANGE: 30E / SECTION: 3 / LAT: 32.59592 / LONG: -103.95155 (TVD: 9541 feet, MD: 10800 feet) PPP: SESE / 314 FSL / 0 FEL / TWSP: 20S / RANGE: 30E / SECTION: 4 / LAT: 32.59598 / LONG: -103.96851 (TVD: 9541 feet, MD: 16024 feet) BHL: SWSE / 330 FSL / 2560 FEL / TWSP: 20S / RANGE: 30E / SECTION: 5 / LAT: 32.59606 / LONG: -103.99392 (TVD: 9541 feet, MD: 23848 feet)

BLM Point of Contact

Name: JANET D ESTES Title: ADJUDICATOR Phone: (575) 234-6233

Email: JESTES@BLM.GOV

Review and Appeal Rights

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.



Michelada 5 FED COM 134H

APD - Geology COAs (Potash or WIPP)

- For at least one well per pad (deepest well within initial development preferred) the record of the drilling rate (ROP) along with the Gamma Ray (GR) and Neutron (CNL) well logs run from TVD to surface in the vertical section of the hole shall be submitted to the BLM office as well as all other logs run on the full borehole 30 days from completion. Any other logs run on the wellbore, excluding cement remediation, should also be sent. Only digital copies of the logs in .TIF or .LAS formats are necessary; paper logs are no longer required. Logs shall be emailed to blm-cfo-geology@doimspp.onmicrosoft.com. Well completion report should have .pdf copies of any CBLs or Temp Logs run on the wellbore.
- Exceptions: In areas where there is extensive log coverage (in particular the salt zone
 adjacent to a pad), Operators are encouraged to contact BLM Geologists to discuss if
 additional GR and N logs are necessary on a pad. Operator may request a waiver of the GR
 and N log requirement due to good well control or other reasons to be approved by BLM
 Geologist prior to well completion. A waiver approved by BLM must be attached to
 completion well report to satisfy COAs.
- The top of the Rustler, top and bottom of the Salt, and the top of the Capitan Reef (if present) are to be recorded on the Completion Report.
- No H2S has been reported within one mile of the proposed project.

Drilling COAs within Known Potash Leasing Area:

Any oil and gas well operator within the KPLA must notify both potash operators as soon as possible if any of the following conditions are encountered during oil and gas operations: (1) Indication of any well collision event, (2) Suspected well fluid flow (oil, gas, or produced water) outside of casing, (3) Sustained annulus pressure between the 1st intermediate and next innermost casing string in excess of 500 psi above the baseline pressure of the well, or above 1500 psi total, (4) Increasing pressure buildup rates (psi/day) across multiple successive bleed-off cycles on the annulus between the 1st intermediate and next innermost casing during well production, or (5) Sustained losses in excess of 50% through the salt interval during drilling.

Questions? Contact Thomas Evans, BLM Geologist at 575-234-5965 or tvevans@blm.gov

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME: Centennial Resource Production LLC

WELL NAME & NO.: Michelada 3 Fed Com 134H

LOCATION: Sec 5-20S-30E-NMP

COUNTY: Eddy County, New Mexico

COA

H_2S	•	No	C	Yes
Potash /	None	Secretary	© R-111-Q	☐ Open Annulus
WIPP	4-String Design: Ope	n 2nd Int x Production Ca Zone)	asing (ICP 2 above Ro	elief
Cave / Karst	• Low	Medium	C High	Critical
Wellhead	Conventional	• Multibowl	O Both	Diverter
Cementing	☐ Primary Squeeze	☐ Cont. Squeeze	☐ EchoMeter	□ DV Tool
Special Req	☐ Capitan Reef	Water Disposal	▼ COM	Unit
Waste Prev.	© Self-Certification	C Waste Min. Plan	APD Submitted pr	rior to 06/10/2024
Additional	▼ Flex Hose	☐ Casing Clearance	☐ Pilot Hole	Break Testing
Language	Four-String	Offline Cementing	☐ Fluid-Filled	

A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet 43 CFR 3176 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

APD is within the R-111-Q defined boundary. Operator must follow all procedures and requirements listed within the updated order.

B. CASING

- 1. The **13-3/8** inch surface casing shall be set at approximately **440** feet (a minimum of 70 feet (Eddy County) into the Rustler Anhydrite, above the salt, and below usable fresh water) and cemented to the surface. *Set depth adjusted per BLM geologist*.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic-type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.

- b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or **500 pounds compressive strength**, whichever is greater. (This is to include the lead cement)
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- d. If cement falls back, remedial cementing will be done prior to drilling out that string.
- 2. The minimum required fill of cement behind the 10-3/4 inch intermediate casing (set at 1740' per BLM geologist) is:
 - Cement to surface. If cement does not circulate see B.1.a, c-d above. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst, Capitan Reef, or potash.
- 3. The minimum required fill of cement behind the 8-5/8 inch intermediate casing (set at 3770' per BLM geologist) is:
 - Cement should tie-back 500 feet into the previous casing but not higher than USGS Marker Bed No. 126. Operator must verify top of cement per R-111-Q requirements. Submit results to the BLM. If cement does not circulate, contact the appropriate BLM office. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst, Capitan Reef, or potash.
- 4. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - Cement should tie-back 500 feet into the previous casing but not higher than USGS Marker Bed No. 126. Operator must verify top of cement per R-111-Q requirements. Submit results to the BLM. If cement does not circulate, contact the appropriate BLM office. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst, Capitan Reef, or potash.

C. PRESSURE CONTROL

- 1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).
- 2. Operator has proposed a multi-bowl wellhead assembly. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.

- d. If the cement does not circulate and one-inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- e. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR 3172 must be followed.

D. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Santa Fe Office, 301 Dinosaur Trail Santa Fe, New Mexico 87508, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- The operator will submit an as-drilled survey well plat of the well completion, but are not limited to, those specified in 43 CFR 3171 and 3172.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

BOPE Break Testing Variance

- BOPE Break Testing is ONLY permitted for intervals utilizing a 5M BOPE or less. (Annular preventer must be tested to a minimum of 70% of BOPE working pressure and shall be higher than the MASP.)
- BOPE Break Testing is NOT permitted to drilling the production hole section.
- Variance only pertains to the intermediate hole-sections and no deeper than the Bone Springs formation.
- While in transfer between wells, the BOPE shall be secured by the hydraulic carrier or cradle.
- Any well control event while drilling require notification to the BLM Petroleum Engineer (575-706-2779) prior to the commencement of any BOPE Break Testing operations.
- A full BOPE test is required prior to drilling the first deep intermediate hole section. If any subsequent hole interval is deeper than the first, a full BOPE test will be required. (200' TVD tolerance between intermediate shoes is allowable).
- The BLM is to be contacted (575-361-2822 Eddy County) 4 hours prior to BOPE tests.
- As a minimum, a full BOPE test shall be performed at 21-day intervals.
- In the event any repairs or replacement of the BOPE is required, the BOPE shall test as per 43 CFR 3172.
- If in the event break testing is not utilized, then a full BOPE test would be conducted.

Offline Cementing

Contact the BLM prior to the commencement of any offline cementing procedure.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Contact Eddy County Petroleum Engineering Inspection Staff:

Email or call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220; **BLM_NM_CFO_DrillingNotifications@BLM.GOV**; (575) 361-2822

- 1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - i. Notify the BLM when moving in and removing the Spudder Rig.
 - ii. Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - iii. BOP/BOPE test to be conducted per **43 CFR 3172** as soon as 2nd Rig is rigged up on well.
- 2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
- 3. For intervals in which cement to surface is required, cement to surface should be verified with a visual check and density or pH check to differentiate cement from spacer and drilling mud. The results should be documented in the driller's log and daily reports.

A. CASING

- 1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
- 2. <u>Wait on cement (WOC) for Potash Areas:</u> After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following

- conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends of both lead and tail cement, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
- 3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
- 4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
- 5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
- 6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
- 7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
- 8. Whenever a casing string is cemented in the R-111-Q potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

- 1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in **43 CFR 3172**.
- 2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.

- 3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
- 4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - i. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - ii. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - iii. Manufacturer representative shall install the test plug for the initial BOP test.
 - iv. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR 3172.6(b)(9) must be followed.
 - v. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- 5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - i. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
 - ii. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (only applies to single stage cement jobs, prior to the cement setting up.)
 - iii. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve open. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to 43 CFR 3172 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for 8 hours or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).

- iv. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- v. The results of the test shall be reported to the appropriate BLM office.
- vi. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- vii. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- viii. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per **43 CFR 3172**.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area. Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.


<u>C-10</u>	_		En	0,5	nerals & Natu	ew Mexico ral Resources Departm TION DIVISION		Revised July 9, 2024						
	Electronically D Permitting	Ý		OIL	CONSERVA	TION DIVISION		C1	☐ Initial Su	bmittal				
								Submittal Type:	X Amende					
						☐ As Drilled								
-			1		WELL LOCA	ATION INFORMATION								
API Nu	30-015		Pool Code		96688	Pool Name GATUNA CANYON;BONE SPRING								
Propert	ty Code 336482	2	Property Na	ame	MICHELAI	DA 3 FED COM								
OGRIE	O No. 3721	.65	Operator Na	9000	88 RMIAN RESOUR	CES OPERATING, LLC	ATUNA CANY	YON;BONE S	SPRINGund Lev	el Elevation 3224.86'				
Surface	e Owner: 🗆 S	State \square Fee \square	Tribal 🛛 Fed	eral		Mineral Owner: □ S	State Fee [□ Tribal 🛛	Federal					
					Sur	face Location								
UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude		Longitude	County				
D	11	20-S 30-E 420' N				1176' W	32.59383	3° N	103.94743° W	EDDY				
	-				Botto	m Hole Location								
UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	[:	Longitude	County				
0	5	20-S	30-E		330' S	2560' E	32.5960	5° N	103.99393° W	EDDY				
Dedica	ted Acres	Infill or Defin	ning Well	Defining	Well API	Overlapping Spacing	Unit (Y/N)	Consolida	tion Code					
4	400 InfilNFILL													
Order N	Order Numbers.					Well setbacks are und	Well setbacks are under Common Ownership: □Yes □No							
					Kick	Off Point (KOP)								
UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude		Longitude	County				
D	11	20-S 30-E 420' N		420' N	1176' W	32.5938	3° N	103.94743° W	EDDY					
			1		First	Гаке Point (FTP)								
UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude		Longitude	County				
P	3	20-S	30-E		330' S	100' E	32.59593	3° N	103.95156° W	EDDY				
	1			1.		Take Point (LTP)	1	1						
UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W		h Day DUX	Longitude	County				
О	5	20-S	30-E		330' S	2540' E	32.5960	10000	Maddala w	EDDY04/18/23				
Unitize	ed Area or Ar	ea of Uniform I	nterest	Spacing	Unit Type ☑ Ho	rizontal Vertical	Astries	n a n Bir Bloor Ele	evation:					
				Spacing		TZORAI — Vertical								
OPER.	ATOR CERT	IFICATIONS				SURVEYOR CERTIFIC		.Brown@pei	rmianres.com					
I hereby	certify that the	information cont	ained herein is	true and com	plete to the best of	I hereby certify that the we	ell location sho	wn on this pi	lat was plotted fro	m field notes of actual				
my know	vledge and beli	ef, and, if the well is a working inter	is a vertical or	directional v	vell, that this	surveys made by me or under my beliefs.								
includin	g the proposed	bottom hole locat	tion or has a rig	ht to drill thi	s well at this	my benefit.								
location pursuant to a contract with an owner of a working interest or unleased mine interest, or to a voluntary pooling agreement or a compulsory pooling order heretofo entered by the division.							PREL	IMINI	ΔRY					
If this well is a horizontal well, I further certify that this organization has received the									CORDED FOR AN	Y				
consent	of at least one	lessee or owner oj	f a working inte	rest or unlea	sed mineral interest	PURPOS	SE AND SHALL	NOT BE USE	D OR VIEWED OR					
		or obtained a con			e well's completed the division.	RELIE	ED UPON AS A	FINAL SURVI	EY DOCUMENT.					
Signature			Date			Signature and Seal of Profess	ional Surveyor							
	Casou	Evano-												
Printed N	Name					Certificate Number	Date of Surve	у						
Email A	ddress					-								
Linaii A							<u> </u>							

Note: No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

ACREAGE DEDICATION PLATS

This grid represents a standard section. You may superimpose a non-standard section, or larger area, over this grid. Operators must outline the dedicated acreage in a red box, clearly show the well surface location and bottom hole location, if it is directionally drilled, with the dimensions from the section lines in the cardinal directions. If this is a horizontal wellbore show on this plat the location of the First Take Point and Last Take Point, and the point within the Completed interval (other than the First Take Point or Last Take Point) that is closest to any outer boundary of the tract.

Surveyors shall use the latest United States government survey or dependent resurvey. Well locations will be in reference to the New Mexico Principal Meridian. If the land is not surveyed, contact the OCD Engineering Bureau. Independent subdivision surveys will not be acceptable.





U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Drilling Plan Data Report

APD ID: 10400091772 **Submission Date:** 04/19/2023

Operator Name: CENTENNIAL RESOURCE PRODUCTION LLC

Well Name: MICHELADA 3 FED COM Well Number: 134H

Well Type: OIL WELL Well Work Type: Drill

Highlighted data reflects the most recent changes

Show Final Text

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical	Measured Depth	Lithologies	Mineral Resources	Producing Formatio
14301132	RUSTLER	2880	375	375	SANDSTONE	USEABLE WATER	N
14301133	TOP SALT	2283	597	597	SALT	POTASH	N
14301134	TANSILL	1125	1755	1755	ANHYDRITE, SHALE	NATURAL GAS, OIL	N
14301135	YATES	1011	1869	1869	ANHYDRITE, SHALE	NATURAL GAS, OIL	N
14301136	CAPITAN REEF	845	2035	2035	LIMESTONE	USEABLE WATER	N
14301138	DELAWARE SAND	-680	3560	3560	SANDSTONE	NATURAL GAS, OIL	N
14301139	BONE SPRING LIME	-3555	6435	6435	OTHER, SHALE : CARBONATE	NATURAL GAS, OIL	N
14301140	BONE SPRING 1ST	-4765	7645	7645	OTHER, SANDSTONE, SHALE : CARBONATE	NATURAL GAS, OIL	N
14301141	BONE SPRING 2ND	-5345	8225	8225	SANDSTONE, SHALE	NATURAL GAS, OIL	Y

Section 2 - Blowout Prevention

Pressure Rating (PSI): 5M Rating Depth: 8241

Equipment: BOPE will meet all requirements for above listed system per 43 CFR 3172. BOPE with working pressure ratings in excess of anticipated maximum surface pressure will be utilized for well control from drill out of surface casing to TMD. The system may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all of the components installed will be functional, tested, and will meet all requirements per 43 CFR 3172. The wellhead will be a multibowl speed head allowing for hangoff of intermediate casing of the surface x intermediate annulus without breaking the connection between the BOP & wellhead. A variance is requested to utilize a flexible choke line (flexhose) from the BOP to choke manifold.

Requesting Variance? YES

Variance request: Multibowl Wellhead, Flexhose, Breaktesting, Offline Cementing Variances. Attachments in Section 8.

Testing Procedure: Operator requests to ONLY test broken pressure seals per API Standard 53 and the attachments in Section 8. The BOP test shall be performed before drilling out of the surface casing shoe and will occur at a minimum: a. when initially installed, b. whenever any seal subject to test pressure is broken, c.

Well Name: MICHELADA 3 FED COM Well Number: 134H

following related repairs, d. at 21-day intervals. Testing of the ram type preventer(s) and annual type preventer(s) shall be tested per 43 CFR 3172. The BOPE configuration, choke manifold layout, and accumulator system will be in compliance with 43 CFR 3172. Bleed lines will discharge 100' from wellhead in non-H2S scenarios and 150' from wellhead in H2S scenarios.

Choke Diagram Attachment:

Michelada_Fed_5MCM_20240730065131.pdf

BOP Diagram Attachment:

Michelada_Fed_5MBOP_20240730065135.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	400	0	400	3225	2825	400	J-55	54.4	BUTT	5.72	3.67	DRY	7.46	DRY	7
2	INTERMED IATE	12.2 5	10.75	NEW	NON API	N	0	1780	0	1780	3226	1445	1780	J-55		OTHER - BTC SCC	10.7 1	4.43	DRY	5.87	DRY	5.75
3	INTERMED IATE	9.87 5	8.625	NEW	NON API	N	0	3510	0	3510	3226	-285	3510	HCL -80		OTHER - MO-FXL	5.97	1.53	DRY	2.38	DRY	3.45
4	PRODUCTI ON	7.87 5	5.5		NON API	N	0	21284	0	8241	3225	-5016	21284	OTH ER		OTHER - GEOCONN	1.75	1.82	DRY	2.27	DRY	2.27

Casing Attachments

Casing ID: 1 String SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Michelada_3_Fed_134H_Csg_20240806044334.pdf

Well Name: MICHELADA 3 FED COM Well Number: 134H

Casing Attachments

Casing ID: 2

String

INTERMEDIATE

Inspection Document:

Spec Document:

Michelada_Fed_Int1_Spec_Sheet_20240806044407.pdf

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Michelada_3_Fed_134H_Csg_20240806044357.pdf

Casing ID: 3

String

INTERMEDIATE

Inspection Document:

Spec Document:

Michelada_Fed_Int2_Spec_Sheet_20240806044414.pdf

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Michelada_3_Fed_134H_Csg_20240806044350.pdf

Casing ID: 4

String

PRODUCTION

Inspection Document:

Spec Document:

Michelada_Fed_Prod_Spec_Sheet_20240806044421.pdf

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Michelada_3_Fed_134H_Csg_20240806044327.pdf

Section 4 - Cement

Well Name: MICHELADA 3 FED COM Well Number: 134H

String Type	Lead/Tail	Stage Tool Depth	Тор МD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	400	680	1.34	14.8	310	50	CLASS C	Accelerator

INTERMEDIATE	Lead		0	1420	790	1.88	12.9	1480	50	CLASS C	EconoCem-HLC + 5% Salt + 5% Kol-Seal
INTERMEDIATE	Tail	1	1420	1780	290	1.34	14.8	380	50	CLASS C	Retarder
INTERMEDIATE	Lead		0	2800	610	1.88	12.9	1130	50	CLASS C	EconoCem-HLC + 5% Salt + 5% Kol-Seal
INTERMEDIATE	Tail	2	2800	3510	220	1.33	14.8	280	25	CLASS C	Salt
PRODUCTION	Lead	2	2100	4010	225	2.41	11.5	542	50	CLASS H	POZ, Extender, Fluid Loss, Dispersant, Retarder
PRODUCTION	Tail	4	4010	2128 4	2412	1.73	12.5	4178	25	CLASS H	POZ, Extender, Fluid Loss, Dispersant, Retarder

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Sufficient quantities of mud materials will be on the well site at all times for the purpose of assuring well control and maintaining wellbore integrity. Surface interval will employ fresh water mud. The intermediate hole will utilize a saturated brine fluid to inhibit salt washout. The production hole will employ brine based and oil base fluid to inhibit formation reactivity and of the appropriate density to maintain well control.

Describe the mud monitoring system utilized: Centrifuge separation system. Open tank monitoring with EDR will be used for drilling fluids and return volumes. Open tank monitoring will be used for cement and cuttings return volumes. Mud properties will be monitored at least every 24 hours using industry accepted mud check practices.

Circulating Medium Table

Well Name: MICHELADA 3 FED COM Well Number: 134H

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	ЬН	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	400	SPUD MUD	8.6	9.5							
400	1780	SALT SATURATED	10	10							
1780	3510	OTHER : Fresh Water	8.6	9.5							
2100	2128 4	OTHER : Brine, OBM	9	10							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

Will utilize MWD/LWD (Gamma ray logging) from intermediate hole to TD of the well.

List of open and cased hole logs run in the well:

GAMMA RAY LOG, DIRECTIONAL SURVEY,

Coring operation description for the well:

N/A

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 4970 Anticipated Surface Pressure: 2870

Anticipated Bottom Hole Temperature(F): 151

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geoharzards description:

Contingency Plans geohazards

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations

H2S_Contingency_Plan_Mezcal_10_Fed_Com_and_Michelada_3_Fed_Com_20230411160402.pdf

Well Name: MICHELADA 3 FED COM Well Number: 134H

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

 $Michelada_3_Fed_134H_DD_20240730065210.pdf$

Michelada_3_Fed_134H_AC_20240730065210.pdf

Other proposed operations facets description:

R-111-Q Process Attached

Other proposed operations facets attachment:

Michelada_Fed_R111Q_Process_ExWBD_20240730065305.pdf

Other Variance attachment:

Michelada_Fed_MBS_20240730065316.pdf

Michelada_Fed_Break_20240730065316.pdf

Michelada_Fed_Batch_20240730065316.pdf


Michelada_Fed_FH_20240730065316.pdf

Michelada_Fed_OLCV_20240730065316.pdf

(Bleed line) To Flare 150' Permian Resources Operating, LLC 5M Choke Manifold Diagram Shaker **Mud Tanks** Separator Mud-Gas Bleed line to burn area (150′) (Not connected to buffer tank) **Buffer Tank** 40'-50' from **Mud Tanks** wellbore To mud gas separator 3" Minimum To mud gas separator 2" Minimum Choke Isolation Valve Isolation Choke Valve Adjustable REMOTELY Adjustable OPERATED Choke Choke min. min. and 150' from WH in H2S scenarios. (Required) HCR. HCR Valve is optional **Drilling Operations Choke Manifold BOP Outlet** 5M Service

Released to Imaging: 11/8/2024 9:15:07 AM

Bleed lines will discharge 100' from WH in non-H2S scenarios




Bleed lines will discharge 100' from WH in non-H2S scenarios and 150' from WH in H2S scenarios.


SOP-12-F05 Performance Data Sheet



API 5CT Casing Performance Data Sheet 10.750" 45.50 lb/ft J55

10.750" 45.50 lb/ft J55							
Manufactured to specificati	ons of API SCT 10th edition and bears the API monogram.						
Grade	155						
	Sizes and Weights						
OD	10.750 in						
Nominal Wall Thickness	0.400 in						
Nominal Weight, T&C	45.50 lb/ft						
Nominal Weight, PE	44.26 lb/ft						
Nominal ID	9.950 in						
Standard Drift	9.794 in						
Alternate Drift	9.875 in						
	Pipe Body Mechanical Properties						
Minimum Yield Strength	55,000 psi						
Maximum Yield Strength	80,000 psi						
Minimum Tensile Strength	75,000 psi						
Maximum Hardness	N/A						
	Minimum Performance						
Collapse Pressure	2,470 psi						
Minimal Internal Pressure Yield	5,210 psi						
Pipe body Tension Yield	1,040,000 lbs						
Joint Strength STC	692,000 lbs						
Joint Strength LTC	N/A						
Joint Strength BTC	1,063,000 lbs						
Internal Pressure Leak Resistance STC/LTC Connections	6.880 lbs						
Internal Pressure Leak Resistance BTC Connections	7,450 lbs						
	Special Clearance Coupling						
ОР	N/A						
Minimum Length (NL)	10.625"						
Diameter at Counterbore	13.515"						
Width of Bearing Face	0.375"						
- The state of the							
	Inspection and Testing						
Visual	OD Longitudinal and independent 3rd party SEA						
NDT	Weldline UT after hydrotest. Calibration notch sensitivity (% of specified wall thickness): 12.5%						
	Color code						
Pipe ends	One green band						
Couplings	Green with one white band (alternate coupling: K55 - green)						
	The state of the s						





Permian Resources Casing Design Criteria

A sundry will be requested if any lesser grade or different size casing is substituted. All casing will be centralized as specified in On Shore Order II. Casing will be tested as specified in On Shore Order II.

Casing Design Assumptions:

Surface

- 1) Burst Design Loads
 - a) Displacement to Gas
 - (1) Internal: Assumes a full column of gas in the casing with a gas gradient of 0.7 psi/ft in the absence of better information. It is limited to the controlling pressure based on the maximum expected pore pressure within the next drilling interval.
 - (2) External: Mud weight to TOC and cement mix water gradient (8.4 ppg) below TOC.
 - b) Casing Pressure Test
 - Internal: Displacement fluid plus surface pressure required to comply with regulatory casing test pressure requirements of Onshore Oil and Gas Order No. 2 and NM NMAC 19.15.16 of NMOCD regulations.
 - (2) External: Mud weight to TOC and cement mix water gradient (8.4 ppg) below TOC.
- 2) Collapse Loads
 - a) Cementing
 - (1) Internal: Displacement fluid density.
 - (2) External: Mud weight from TOC to surface and cement slurry weight from TOC to shoe.
 - b) Lost Returns with Mud Drop
 - Internal: Lost circulation at the TD of the next hole section and the fluid level falls to a depth where the hydrostatic pressure of the mud column equals pore pressure at the depth of the lost circulation zone.
 - (2) External: Mud weight to TOC and cement slurry(s) density below TOC.
- 3) Tension Loads
 - a) Overpull Force
 - Axial: Buoyant weight of the string plus planned 100,000 lbs applied in stuck pipe situation.
 - b) Green Cement Casing Test
 - 1. Axial: Buoyant weight of the string plus cement plug bump pressure load.

Intermediate I

- 1) Burst Design Loads
 - a) Displacement to Gas
 - (1) Internal: Assumes a full column of gas in the casing with a gas gradient of 0.7 psi/ft in the absence of better information. It is limited to the controlling pressure based on the maximum expected pore pressure within the next drilling interval.
 - (2) External: Mud weight to TOC and cement mix water gradient (8.4 ppg) below TOC.
 - b) Casing Pressure Test
 - Internal: Displacement fluid plus surface pressure required to comply with regulatory casing test pressure requirements of Onshore Oil and Gas Order No. 2 and NM NMAC 19.15.16 of NMOCD regulations.

- (2) External: Mud weight to TOC and cement mix water gradient (8.4 ppg) below TOC.
- 2) Collapse Loads
 - a) Cementing
 - (1) Internal: Displacement fluid density.
 - (2) External: Mud weight from TOC to surface and cement slurry weight from TOC to shoe.
 - b) Lost Returns with Mud Drop
 - Internal: Lost circulation at the TD of the next hole section and the fluid level falls to a
 depth where the hydrostatic pressure of the mud column equals pore pressure at the
 depth of the lost circulation zone.
 - (2) External: Mud weight to TOC and cement slurry(s) density below TOC.
- Tension Loads
 - a) Overpull Force
 - 1. Axial: Buoyant weight of the string plus planned 100,000 lbs applied in stuck pipe situation.
 - b) Green Cement Casing Test
 - 1. Axial: Buoyant weight of the string plus cement plug bump pressure load.

Intermediate or Intermediate II

- 1) Burst Design Loads
 - a) Gas Kick Profile
 - Internal: Load profile based on influx encountered in lateral portion of wellbore with a maximum influx volume of 150 bbl and a kick intensity of 1.5 ppg using maximum anticipated MW of 9.9 ppg.
 - (2) External: Mud weight to TOC and cement mix water gradient (8.4 ppg) below TOC.
 - b) Casing Pressure Test
 - Internal: Displacement fluid plus surface pressure required to comply with regulatory casing test pressure requirements of Onshore Oil and Gas Order No. 2 and NM NMAC 19.15.16 of NMOCD regulations.
 - (2) External: Mud weight to TOC and cement mix water gradient (8.4 ppg) below TOC.
- 2) Collapse Loads
 - a) Cementing
 - Internal: Displacement fluid density.
 - (2) External: Mud weight from TOC to surface and cement slurry weight from TOC to shoe.
 - b) Lost Returns with Mud Drop
 - Internal: Lost circulation at the deepest TVD of the next hole section and the fluid level falls
 to a depth where the hydrostatic pressure of the mud column equals pore pressure at the
 depth of the lost circulation zone.
 - (2) External: Mud weight to TOC and cement slurry(s) density below TOC.
- 3) Tension Loads
 - a) Overpull Force
 - 1. Axial: Buoyant weight of the string plus planned 100,000 lbs applied in stuck pipe situation.
 - b) Green Cement Casing Test
 - 1. Axial: Buoyant weight of the string plus cement plug bump pressure load.

Production

- 1) Burst Design Loads
 - a) Injection Down Casing
 - (1) Internal: Surface pressure plus injection fluid gradient.
 - (2) External: Mud base-fluid density to top of cement and cement mix water gradient (8.4 ppg) below TOC.
 - b) Casing Pressure Test (Drilling)
 - Internal: Displacement fluid plus surface pressure required to comply with regulatory casing test pressure requirements of Onshore Oil and Gas Order No. 2 and NM NMAC 19.15.16 of NMOCD regulations.
 - (2) External: Mud weight to TOC and cement mix water gradient (8.4 ppg) below TOC.
 - c) Casing Pressure Test (Production)
 - (1) Internal: The design pressure test should be the greater of the planned test pressure prior to simulation down the casing, the regulatory test pressure, and the expected gas lift system pressure. The design test fluid should be the fluid associated with the pressure test having the greatest pressure.
 - (2) External: Mud base-fluid density to top of cement and cement mix water gradient (8.4 ppg) below TOC.
 - d) Tubing Leak
 - (1) Internal: SITP plus a packer fluid gradient to the top of packer.
 - (2) External: Mud base-fluid density to top of cement and cement mix water gradient (8.4 ppg) below TOC.
- 2) Collapse Loads
 - a) Cementing
 - (1) Internal: Displacement fluid density.
 - (2) External: Mud weight to TOC and cement slurry(s) density below TOC.
 - b) Full Evacuation
 - (1) Internal: Full void pipe.
 - (2) External: Mud weight to TOC and cement slurry(s) density below TOC.
- 3) Tension Loads
 - a) Overpull Force
 - 1. Axial: Buoyant weight of the string plus planned 100,000 lbs applied in stuck pipe situation.
 - b) Green Cement Casing Test
 - 1. Axial: Buoyant weight of the string plus cement plug bump pressure load.

3. Casing

String	Hole Size	Casing Size	Тор	Bottom	Top TVD	Bottom TVD	Length	Grade	Weight	Connection	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
Surface	17.5	13.375	0	400	0	400	400	J55		BTC	5.72	3.67	Dry	7.46		7.00
Intermediate 1	12.25	10.75	0	1780	0	1780	1780	J55	45.5	BTCSCC	10.71	4.43	Dry	5.87	Dry	5.75
Intermediate 2	9.875	8.625	0	3510	0	3510	3510	HCL-80	32	MO-FXL	5.97	1.53	Dry	2.38	Dry	3.45
Production	7.875	5.5	0	21284	0	8241	21284	P110RY	17	GeoConn	1.75	1.82	Dry	2.27	Dry	2.27
								BLM Mi	n Safe	ty Factor	1.125	1		1.6		1.6

Non API casing spec sheets and casing design assumptions attached.

PERMIAN RESOURCES

H₂S CONTINGENCY PLAN

FOR

Permian Resources Corporation Mezcal 10 Fed Com 121H, 131H, 132H, 133H, 134H Michelada 3 Fed Com 123H, 124H, 133H, 134H Eddy County, New Mexico

01-20-2023
This plan is subject to updating

Permian Resources Corporation H₂S Contingency Plan Eddy County, New Mexico Mezcal 10 Fed Com 121H, 131H 132H, 133H, 134H

Table of Contents

Section	1.0 – Introduction
l.	Purpose
II.	Scope & Applicability
Section	2.0 - Plan Implementation3
l.	Activation Requirements
II.	Emergency Evacuation
III.	Emergency Response Activities
	3.0 - Potential Hazardous Conditions4
Section	4.0 - Notification of H2S Release Event6
l.	Local & State Law Enforcement
II.	General Public
III.	New Mexico Oil Conservation Division
IV.	New Mexico Environment Department
V.	Bureau of Land Management
Section	5.0 - Emergency Contact List7
l.	Permian Resources Management Personnel
II.	Eddy County Sheriff
III.	New Mexico State Highway Patrol
IV.	Fire / EMS
V.	Carlsbad Medical Center
VI.	Emergency Response Contractors
VII.	New Mexico Oil Conservation Division
VIII.	New Mexico Environment Department
IX.	Bureau of Land Management
Χ.	Other Agencies
Section	6.0 – Drilling Location Information9-12
l.	Site Safety Information
II.	Directions to Location
III.	Plat of Location including GPS Coordinates
IV.	Routes of Ingress & Egress (MAP)
V.	ROE Map
VI.	Residences in ROE
VII.	Public Roads in ROE
Section	7.0 – Hazard Communication13-15
l.	Physical Characteristics of Hydrogen Sulfide Gas
II.	Human Health Hazards / Toxicological Information
III.	Environmental Hazards
Section	8.0 - Regulatory Information15-17
l.	OSHA Information
II.	New Mexico Oil Conservation Division & Bureau of Land Management
	9.0 - Training Requirements17
	10.0 - Personal Protective Equipment18
Append	dices

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

- I. Appendix A − H₂S SDS
- II. Appendix $B SO_2 SDS$

Section 1.0 - Introduction

I. Purpose

The purpose of this contingency plan (Plan) is to provide Permian Resources Corporation. (Permian Resources) with an organized plan of action for alerting and protecting Permian Resources employees, the general public, and any potential first responders prior to any intentional release or immediately following the accidental / unintentional release of a potentially hazardous volume / concentration of Hydrogen Sulfide Gas (H2S).

II. Scope & Applicability

This Plan applies to all planned, unplanned, uncontrolled and/or unauthorized releases of hazardous concentrations of H_2S or any associated hazardous byproducts of combustion, occurring at any Permian Resources owned or operated facilities including but not limited to: wells, flowlines, pipelines, tank batteries, production facilities, SWD facilities, compressor stations, gas processing plants, drilling / completions / workover operations, and any other applicable company owned property.

Section 2.0 - Plan Implementation

I. Activation Requirements

In accordance with the requirements of Bureau of Land Management Onshore Order #6 and NMAC 19.15.11, this Plan shall be activated in advance of any authorized, planned, unplanned, uncontrolled, or unauthorized release of a hazardous volume / concentration of H₂S gas, or SO², which could potentially adversely impact the workers, general public or the environment.

II. Emergency Evacuation

In the event of an unplanned, uncontrolled, or unauthorized release of a hazardous volume / concentration of H_2S gas, the first priority is to ensure the safety of the workers and general public. Upon discovery and subsequent determination of an applicable release, which cannot be quickly mitigated, immediately by using 911, notify local authorities to begin the process of alerting the general public, evacuate any residents within the Radius of Exposure (ROE), and limit any general public or employee access to any areas within the ROE of the affected facility.

III. Emergency Response Activities

The purpose of emergency response actions is to take steps to quickly mitigate / stop the ongoing release of the hazardous source of H_2S . Upon discovery of any hazardous release, immediately notify Permian Resources management to activate the Emergency Response Team (ERT). Once Permian Resources supervision arrives and assesses the situation, a work plan identifying the proper procedures shall be

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

developed to stop the release.

Section 3.0 - Potential Hazardous Conditions & Response Actions

During a planned or unplanned release of H_2S , there are several hazardous conditions that are presented both to employees, the general public, and emergency responders. These specific hazardous conditions are identified in the tables below.

H2S OPERATING CONDITIONS – RESPONSE ACTIONS TO CONSIDER	✓
H ₂ S CONDITION 1: POTENTIAL DANGER TO LIFE AND HEALTH -> WARNING SIGREEN	GN
H ₂ S concentration <10 ppm detected by location monitors	
General Actions During Condition 1	
Notify Site Supervisor / Permian Resources Person-in-Charge (PIC) of any observed increase in ambient H ₂ S concentrations	
All personnel check safety equipment is in adequate working order & store in accessible location	
Sensitize crews with safety meetings.	
Limit visitors and non-essential personnel on location	
Continuously monitor H ₂ S concentrations and check calibration of sensors	
Ensure H ₂ S scavenger is on location.	
H ₂ S CONDITION 2: MODERATE DANGER TO LIFE AND HEALTH → WARNING SIGN YELLOW	
H ₂ S concentration >10 ppm and < 30 ppm in atmosphere detected by location monitors:	
General Actions During Condition 2	
Sound H ₂ S alarm and/or display yellow flag.	
Account for on-site personnel	
Upon sounding of an area or personal H ₂ S monitor alarm when 10 ppm is reached, proceed to a safe briefing area upwind of the location immediately (see MA-4 , Figure 5-1).	
Don proper respiratory protection.	
Alert other affected personnel	
If trained and safe to do so undertake measures to control source H2S discharge and eliminate possible ignition sources. Initiate Emergency Shutdown procedures as deemed necessary to correct or control the specific situation.	
Account for on-site personnel at safe briefing area.	
Stay in safe briefing area if not working to correct the situation.	
Keep Site Supervisor / Permian Resources PIC informed. Notify applicable government agencies (Appendix A) If off-site impact; notify any neighbors within Radius of Exposure (ROE), Fig 5.11	
Continuously monitor H ₂ S until readings below 10 ppm.	
Evacuated area shall not be re-entered except by trained and authorized personnel utilizing appropriate respiratory protection; or until "all clear" sounded by Permian Resources PIC / Site Supervisor.	

Permian Resources Corporation

Eddy County, New Mexico

Mezcal 10 Fed Com 121H, 131H 132H,	
133H, 134H	
H_2S CONDITION 3: EXTREME DANGER TO LIFE AND HEALTH \rightarrow WARNING SIGN	RED
> 30 ppm H ₂ S concentration in air detected by location monitors: Extreme dange	er to life
General Actions During Condition 3	
Sound H ₂ S alarm and/or display red flag.	
Account for on-site personnel	
Move away from H ₂ S source and get out of the affected area.	
Proceed to designated safe briefing area; alert other affected personnel.	
Account for personnel at safe briefing area.	
If trained and safe to do so undertake measures to control source H2S discharge a eliminate possible ignition sources. Initiate Emergency Shutdown procedures	
necessary to correct or control the specific situation.	s as deemed
Notify vehicles or situation and divert all traffic away from location.	
Permian Resources Peron-in-Charge will make appropriate community notification	
Red warning flag must be on display until the situation has been corrected and the	
Resources Person-in-Charge determines it is safe to resume operations under 1.	
Notify management of the condition and action taken. If H ₂ S concentration is inc	
steps to correct the situation are not successful – or at any time if well contro questionable – alert all responsible parties for possible activation of the H_2S (
Plan. If well control at the surface is lost, determine if situation warrants igni	
well. If uncontrolled flow at the surface occurs, the Permian Resources PIC, with approximately app	oval if
possible, from those coordinating the emergency (as specified in the site-spe	
Contingency Plan) are responsible for determining if the situation warrants	
flow of the uncontrolled well. This decision should be made only as a last resistuation where it is obvious that human life is in danger and there is no hope	
controlling the flow under prevailing conditions.	, O1
If the flow is ignited, burning H ₂ S will be converted to sulphur dioxide (SO ₂), wh	
highly toxic. Do not assume that area is safe after the flow is ignited. If the w	
ignited, evacuation of the area is mandatory, because SO ₂ will remain in low-places under no-wind conditions.	-iying
Keep Site Supervisor / Permian Resources PIC informed.	
Notify applicable government agencies and local law enforcement (Appendix A) If off-site impact; notify any neighbours within the Radius of Exposure (ROE), s	
in Figure 5-11.	

H₂S Contingency Plan

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

Continuously monitor H ₂ S until readings fall below 10 ppm.	
Evacuated area shall not be re-entered except by trained and authorized personnel utilizing appropriate respiratory protection; or until "all clear" sounded by Permian Resources PIC / Site Supervisor.	
IF ABOVE ACTIONS CANNOT BE ACCOMPLISHED IN TIME TO PREVENT EXPOSURE TO THE PUBLIC	
Alert public (directly or through appropriate government agencies) who may be subject to potentially harmful exposure levels.	
Make recommendations to public officials regarding blocking unauthorized access to the unsafe area and assist as appropriate.	
Make recommendations to public officials regarding evacuating the public and assist as appropriate.	
Monitor ambient air in the area of exposure (after following abatement measures) to determine when it is safe for re-entry.	

Section 4.0 - Notification of H₂S Release Event

I. Local & State Law Enforcement

Prior to the planned / controlled release of a hazardous concentration of H_2S gas or any associated byproducts of the combustion of H_2S gas, notify local law enforcement agencies regarding the contents of this plan.

In the event of the discovery of an unplanned/uncontrolled release of a hazardous concentration of H_2S gas or any associated byproducts of combustion, immediately notify local and/or state law enforcement agencies of the situation and ask for their assistance.

II. General Public

In the event of a planned or unplanned release of a hazardous concentration of H_2S gas or any associated byproducts of combustion, notify local law enforcement agencies and ask for their assistance in alerting the general public and limiting access to any public roads that may be impacted by such a release.

III. New Mexico Oil Conservation Division

The Permian Resources HSE Department will make any applicable notification to the New Mexico OCD regarding any release of a hazardous concentration of H₂S Gas or any associated byproducts of combustion.

IV. New Mexico Environment Department

The Permian Resources HSE Department will make any applicable notifications to the NMED regarding any release of a hazardous concentration of H_2S gas or any associated byproducts of combustion.

V. Bureau of Land Management

The Permian Resources Regulatory Department will make any applicable notifications to the BLM

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

regarding any release of a hazardous concentration of H_2S gas or any associated byproducts of combustion.

Section 5.0 - Emergency Contact List

EMERGENCY CONTACT LIST						
PERMIAN RESOURCES CORPORATION.						
POSITION	NAME	OFFICE	CELL	ALT PHONE		
	Operations					
Operations Superintendent	Rick Lawson		432.530.3188			
TX Operations Superintendent	Josh Graham	432.940.3191	432.940.3191			
NM Operations Superintendent	Manual Mata	432.664.0278	575.408.0216			
Drilling Manager	Jason Fitzgerald	432.315.0146	318.347.3916			
Drilling Engineer	Ronny Hise	432.315.0144	432.770.4786			
Production Manager	Levi Harris	432.219.8568	720.261.4633			
SVP Development Ops	Clayton Smith	720.499.1416	361.215.2494			
SVP Production Ops	Casey McCain	432.695.4239	432.664.6140			
	HSE & Ro	egulatory				
H&S Manager	Adam Hicks	720.499.2377	903.426.4556			
Regulatory Manager	Sarah Ferreyros	720.499.1454	720.854.9020			
Environmental Manager	Montgomery Floyd	432-315-0123	432-425-8321			
Environmental Representative	<u> </u>					
HSE Consultant	Blake Wisdom		918-323-2343			
l	ocal, State, & F	ederal Agen	cies			
Eddy County Sheriff		575-887-7551		911		
New Mexico State Highway Patrol		505-757-2297		911		
Eunice Fire / EMS		575-628-5450		911		
Carlsbad Medical Center		575-887-4100				
Secorp – Safety Contractor	Ricky Stephens		(325)-262-0707			
New Mexico Oil Conservation Division – District 1 Office – Hobbs, NM.		575-393-6161				
New Mexico Environment Department – District III Office – Hobbs, NM		575-397-6910				
New Mexico Oil Conservation Division – Hobbs, NM	24 Hour Emergency	575-393-6161				
Bureau of Land Management – Carlsbad, NM		575-234-5972				
U.S. Fish & Wildlife		502-248-6911				

Section 6.0 – Drilling Location Information

I. Site Safety Information

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

1. Safe Briefing Area

a. There shall be two areas that will be designated as "SAFE BRIEFING AREAs". If H₂S is detected in concentrations equal to or in excess of 10 ppm all personnel not assigned emergency duties are to assemble in the designated Safe Briefing area for instructions. These two areas shall be positioned in accessible locations to facilitate the availability of self-contained breathing air devices. The briefing areas shall be positioned no less than 250' from the wellhead and in such locations that at least one briefing area will be upwind from the well at all times.

2. Wind Indicators

a. 4 Windsocks will be installed at strategic points on the facility.

3. Danger Signs

a. A warning sign indicating the possible well conditions will be displayed at the location entrance.

DANGER POISONOUS GAS HYDROGEN SULFIDE DO NOT APPROACH IF AMBER LIGHTS ARE FLASHING

4. H₂S Detectors and Alarms

a. Continuous monitoring type H₂S detectors, capable of sensing a minimum of 5ppm H₂S in air will be located centrally located at the tanks, heater treater, and combustor. Continuous monitoring type SO₂ detector will also be located at the combustor. The automatic H₂S alarm/flashing light will be located at the site entrance and in front of tank battery.

5. Safety Trailer

a. A safety trailer equipped with an emergency cascade breathing air system with 2 ea. Work/escape packs, a stretcher, 2 OSHA approved full body harnesses, and a 20# Class ABC fire extinguisher shall be available at the site in close proximity to the safe briefing area. The cascade system shall be able to be deployed to the drill floor when needed to provide safe breathing air to the workers as needed.

6. Well Control Equipment

- a. The location shall have a flare line to a remote automatic ignitor and back up flare gun, placed 150' from the wellhead.
- b. The location shall be equipped with a remotely operated choke system and a mud gas separator.

7. Mud Program

a. Company shall have a mud program that contains sufficient weight and additives to control H_2S .

8. Metallurgy

a. All drill strings, casing, tubing, wellhead, BOP, spools, kill lines, choke manifold and lines, and valves shall be suitable for anticipated H₂S volume and pressure.

9. Communication

a. The location shall be equipped with a means of effective communication such as a cell

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

phones, intercoms, satellite phones or landlines.

II. Directions to Location


From Intersection of NM 360 & US 180, Go Northeast on NM 360 for 4.4 miles. Turn Right and Go Southeast for 0.54 miles. Turn Right Go South 0.42 Miles, Turn Right Go South 97 Feet, Turn Left onto Crazy Horse Rd and Go Northeast 1.2 Miles to the Southeast Pad Corner for this location.

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

Plat of Location

Permian Resources Corporation H₂S Contingency Plan Mezcal 10 Fed Com 121H, 131H 132H, 133H, 134H

Eddy County, New Mexico



Permian Resources Corporation	H ₂ S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

1. Routes of Ingress & Egress (MAP)



2. Residences in proximity to the 3000' Radius of Exposure (ROE) (MAP)

There are no residences or public gathering places with the 3000' ROE, 100 PPM, 300 PPM, or 500 PPM ROE.

Map of 3000' ROE Perimeter



100 PPM, 300 PPM, & 500 PPM Max ROE under worst case scenario

Enter H₂S in PPM 1500

Enter Gas flow in mcf/day (maximum worst case conditions) 2500

500 ppm radius of exposure (public road) 105 feet

300 ppm radius of exposure (public area) 146 feet

100 ppm radius of exposure (public area) 230 feet

- Location GPS Coordinates Lat: 32.593584, Long: -103.947702
- 3. Public Roads in proximity of the Radius of Exposure (ROE)

There are no public roads that would be within the 500 PPM ROE. The closest public road is New Mexico Crazy Horse Rd, which is 450' from the location.

Section 7.0 - Hazard Communication

I. Physical Characteristics of Hydrogen Sulfide Gas

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

Hydrogen sulfide (H_2S) is a colorless, poisonous gas that is soluble in water. It can be present in crude oils, condensates, natural gas and wastewater streams.

 H_2S is heavier than air with a vapor density of 1.189 (air = 1.0); however, H_2S is most often mixed with other gases. These mixtures of H_2S and other gases can be heavier or lighter than air. If the H_2S -containing mixture is heavier, it can collect in low areas such as ditches, ravines, firewalls, and pits; in storage tanks; and in areas of poor ventilation. Please see physical properties in **Table 7.0.**

With H_2S the sense of smell is rapidly lost allowing lethal concentrations to be accumulated without warning. The toxicity of hydrogen sulfide at varying concentrations is indicated in the **Table 7.1.**

Warning: Do not use the mouth-to-mouth method if a victim ingested or inhaled hydrogen sulfide. Give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Table 7.0. Physical Properties of H₂S

Properties of H2S	Description	
Vapor Density > 1 = 1.189 Air = 1	 H2S gas is slightly heavier than air, which can cause it to settle in low places and build in concentration. Produced as a mixture with other gases associated with oil and gas production. 	
Flammable Range 4.3%-46% 43000 ppm – 460000 ppm	 H2S can be extremely flammable / explosive when these concentrations are reached by volume in air. 	

Although H_2S is primarily a respiratory hazard, it is also flammable and forms an explosive mixture at concentrations of 4.3%–46.0% (40,000ppm – 460,000 ppm) by volume in air.

H₂S can be encountered when:

- Venting and draining equipment.
- Opening equipment (separators, pumps, and tanks).
- Opening piping connections ("line breaking").
- Gauging and sampling storage tanks.
- Entering confined spaces.
- Working around wastewater pits, skimmers, and treatment facilities.
- II. Human Health Hazards Toxicological Information

Table 7.1. Hazards & Toxicity

Concentration	Symptoms/Effects
(ppm)	

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

0.00011-0.00033 ppm	Typical background concentrations
0.01-1.5 ppm	Odor threshold (when rotten egg smell is first noticeable to some). Odor becomes more offensive at 3-5 ppm. Above 30 ppm, odor described as sweet or sickeningly sweet.
2-5 ppm	Prolonged exposure may cause nausea, tearing of the eyes, headaches or loss of sleep. Airway problems (bronchial constriction) in some asthma patients.
20 ppm	Possible fatigue, loss of appetite, headache, irritability, poor memory, dizziness.
50-100 ppm	Slight conjunctivitis ("gas eye") and respiratory tract irritation after 1 hour. May cause digestive upset and loss of appetite.
100 ppm	Coughing, eye irritation, loss of smell after 2-15 minutes (olfactory fatigue). Altered breathing, drowsiness after 15-30 minutes. Throat irritation after 1 hour. Gradual increase in severity of symptoms over several hours. Death may occur after 48 hours.
100-150 ppm	Loss of smell (olfactory fatigue or paralysis).
200-300 ppm	Marked conjunctivitis and respiratory tract irritation after 1 hour. Pulmonary edema may occur from prolonged exposure.
500-700 ppm	Staggering, collapse in 5 minutes. Serious damage to the eyes in 30 minutes. Death after 30-60 minutes.
700-1000 ppm	Rapid unconsciousness, "knockdown" or immediate collapse within 1 to 2 breaths, breathing stops, death within minutes.
1000-2000 ppm	Nearly instant death

III. Environmental Hazards

 H_2S and its associated byproducts from combustion presents a serious environmental hazard. Sulphur Dioxide SO_2 is produced as a constituent of flaring H_2S Gas and can present hazards associated, which are similar to H_2S . Although SO_2 is heavier than air, it will be picked up by a breeze and carried downwind at elevated temperatures. Since Sulfur Dioxide is extremely irritating to the eyes and mucous membranes of the upper respiratory tract, it has exceptionally good warning powers in this respect. The following table indicates the toxic nature of the gas. Please see the attached SDS in Appendix B for reference.

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

SULFUR DIOXIDE TOXICITY		
Conce	entration	Effects
%SO ₂	PPM	
0.0005	3 to 5	Pungent odor-normally a person can detect SO ₂ in this range.
0.0012	12	Throat irritation, coughing, and constriction of the chest tearing and smarting of eyes.
0.15	150	So irritating that it can only be endured for a few minutes.
0.05	500	Causes a sense of suffocation, even with first breath.

Section 8.0 - Regulatory Information

I. OSHA & NIOSH Information

II. Table 8.0. OSHA & NIOSH H₂S Information

PEL, IDLH, TLV	Description	
NIOSH PEL 10 PPM	PEL is the Permissible Exposure Limit that an employee may be exposed up to 8 hr / day.	
OSHA General Industry Ceiling PEL – 20 PPM	The maximum exposure limit, which cannot be exceeded for any length of time.	
IDLH 100 PPM	■ Immediately Dangerous to Life and Health	
Permian Resources PEL 10 PPM	■ Permian Resources Policy Regarding H2S for employee safety	

III. New Mexico OCD & BLM – H₂S Concentration Threshold Requirements

New Mexico NMAC 19.15.11 and Onshore Order #6 identify two Radii of Exposure (ROE) that identify potential danger to the public and require additional compliance measures. Permian Resources is required to install safety devices, establish safety procedures and develop a written H_2S contingency plan for sites where the H_2S concentrations are as follows.

Table 8.1. Calculating H₂S Radius of Exposure

H ₂ S Radius of Exposure	Description	Control and Equipment Requirements
100 ppm	Distance from a release to where the H ₂ S concentration in the air will dilute below 100ppm	ROE > 50-ft and includes any part of a "public area" (residence, school, business, etc., or any area that can be expected to be populated). ROE > 3,000-ft

Permian Resources Corporation	H ₂ S Contingency Plan Mezcal 10 Fed Com 121H, 131H 132H,	Eddy County, New Mexico
	133H, 134H	

500 ppm	Distance from a release to where the H ₂ S concentration in the air will dilute below 500ppm	ROE > 50-ft and includes any part of a public road (public roads are tax supported roads or any road used for public access or use)

Calculating H₂S Radius of Exposure

The ROE of an H_2S release is calculated to determine if a potentially hazardous volume of H_2S gas at 100 or 500 parts per million (ppm) is within a regulated distance requiring further action. If information about the concentration of H_2S and the potential gas release volume is known, the location of the Muster Areas will be set, and safety measures will be implemented based on the calculated radius of exposure (ROE). NMAC 19.15.11 – Hydrogen Sulfide Safety defines the ROE as the radius constructed with the gas's point of escape as its center and its length calculated by the following Pasquill-Gifford equations:

To determine the extent of the **100 ppm ROE**:

 $x = [(1.589) \text{ (mole fraction } H_2S)(Q)]^{(.6258)}.$

To determine the extent of the **500 ppm ROE**:

 $x = [(0.4546) \text{ (mole fraction H}_2S)(Q)]^{(.6258)}.$

Table 8.2. Calculating H2S Radius of Exposure

ROE Variable	Description
X =	ROE in feet
Q =	Max volume of gas released determined to be released in cubic feet per day (ft³/d) normalized to standard temperature and pressure, 60°F and 14.65 psia
Mole fraction H₂S =	Mole fraction of H ₂ S in the gaseous mixture released.

The volume used as the escape rate in determining the ROE is specified in the rule as follows:

- The maximum daily volume rate of gas containing H₂S handled by that system element for which the ROE is calculated.
- For existing gas wells, the current adjusted open-flow rate, or the operator's estimate of the well's capacity to flow against zero back-pressure at the wellhead.

New Mexico Oil Conservation Division & BLM Site Requirements under NMAC 19.15.11 & Onshore Order #6

- Two cleared areas will be designated as Safe Briefing Areas. During an emergency, personnel will assemble in one of these areas for instructions from the Permian Resources Person-in-Charge. Prevailing wind direction should be considered in locating the briefing areas 200' or more on either side of the well head. One area should offset the other at an angle of 45° to 90° with respect to prevailing wind direction to allow for wind shifts during the work period.
- In the event of either an intentional or accidental releases of hydrogen sulfide, safeguards to protect the general public from the harmful effects of hydrogen sulfide must be in place for operations. A summary of the provisions in each of three H₂S ROE cases is included in **Table 8.3**.
 - o **CASE 1** -100 ppm ROE < 50'

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

- CASE 2 100 ppm ROE is 50' or greater, but < 3000' and does not penetrate public area.
- CASE 3 -100 ppm ROE is 50' or greater and penetrates a public area or 500 ppm ROE includes a public road. Also if 100 ppm ROE > 3000' regardless of public area.

Table 8.3. NMAC 19.15.11 Compliance Requirements Drilling & Production

NMAC 19.15.11 & BLM COMPLIANCE REQUIREMENTS - DRILLING & PRODUCTION			
PROVISION	CASE 1	CASE 2	CASE 3
H ₂ S Concentration Test	X	X	X
H-9	X	X	X
Training	X	X	X
District Office Notification	X	X	X
Drill Stem Tests Restricted	X*	X*	X
BOP Test	X*	X*	X
Materials		X	X
Warning and Marker		X	X
Security		X	X
Contingency Plan			X
Control and Equipment Safety			X
Monitors		X**	X**
Mud (ph Control or Scavenger)			X*
Wind Indicators		X**	X
Protective Breathing Equipment		X**	X
Choke Manifold, Secondary Remote Control, and Mud-Gas Separator			X
Flare Stacks			X*

Section 9.0 - Training Requirements

Training

The following elements are considered a minimum level of training for personnel assigned to operations who may encounter H_2S as part of routine or maintenance work.

- The hazards, characteristics, and properties of hydrogen sulfide (H₂S) and (SO₂).
- Sources of H₂S and SO₂.
- Proper use of H₂S and SO₂ detection methods used at the workplace.
- Recognition of, and proper response to, the warning signals initiated by H₂S and SO₂ detection systems in use at the workplace.
- Symptoms of H₂S exposure; symptoms of SO₂ exposure
- Rescue techniques and first aid to victims of H₂S and SO₂ exposure.
- Proper use and maintenance of breathing equipment for working in H₂S and SO₂ atmospheres, as appropriate theory and hands-on practice, with demonstrated proficiency (29 CFR Part 1910.134).
- Workplace practices and relevant maintenance procedures that have been established to protect personnel from the hazards of H₂S and SO₂.
- Wind direction awareness and routes of egress.

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

- Confined space and enclosed facility entry procedures (if applicable).
- Emergency response procedures that have been developed for the facility or operations.
- Locations and use of safety equipment.
- Locations of safe briefing areas.

Refresher training will be conducted annually.

Section 10.0 - Personal Protective Equipment

I. Personal H₂S Monitors

All personnel engaged in planned or unplanned work activity to mitigate the release of a hazardous concentration of H₂S shall have on their person a personal H2S monitor.

- II. Fixed H₂S Detection and Alarms
 - 4 channel H₂S monitor
 - 4 wireless H₂S monitors
 - H₂S alarm system (Audible/Red strobe)
 - Personal gas monitor for each person on location
 - Gas sample tubes

III. Flame Resistant Clothing

All personnel engaged in planned or unplanned work activity associated with this Plan shall have on the appropriate level of FRC clothing.

IV. Respiratory Protection

The following respiratory protection equipment shall be available at each drilling location.

- Working cascade system available on rig floor and pit system & 750' of air line hose
- Four (4) breathing air manifolds
- Four (4) 30-minute rescue packs
- Five (5) work/Escape units
- Five (5) escape units
- One (1) filler hose for the work/escape/rescue units

Supplied air (airline or SCBA) respiratory protection against hydrogen sulfide exposure is required in the following situations:

- When routine or maintenance work tasks involve exposure to H₂S concentrations of 10 ppm or greater.
- When a fixed location area monitor alarms, and re-entry to the work area is required to complete a job.
- When confined spaces are to be entered without knowledge of H₂S levels present, or if initial measurements are to be taken of H₂S levels.
- During rescue of employees suspected of H₂S overexposure.
- For specific tasks identified with significant exposure potential and outlined in local program guidelines.
- All respiratory equipment for hydrogen sulfide must be of the supplied-air type, equipped with pressure-demand regulators and operated in the pressure-demand mode only. This is the only type of respiratory protection recommended for hydrogen sulfide application. Equipment should be approved by NIOSH/MSHA or other recognized national authority as required. If airline units are used, a five-minute egress bottle should also be carried.

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

- Gas masks or other air-purifying respirators MUST NEVER BE USED FOR HYDROGEN SULFIDE due to the poor warning properties of the gas.
- Use of respiratory protection should be accompanied by a written respiratory protection program.

Appendix A H₂S SDS



Hydrogen sulfide

Safety Data Sheet E-4611

according to the Hazardous Products Regulation (February 11, 2015)
Date of issue: 10-15-1979 Revision date: 08-10-2016 Si

Supersedes: 10-15-2013

SECTION 1: Identification

Product form Substance Name Hydrogen sulfide CAS No : 7783-06-4 Formula H2S Other means of identification Hydrogen sulfide Product group Core Products

1.2. Recommended use and restrictions on use

Recommended uses and restrictions Industrial use Use as directed

1.3. Supplier

Praxair Canada inc. 1200 – 1 City Centre Drive Mississauga - Canada L5B 1M2 T 1-905-803-1600 - F 1-905-803-1682 www.praxair.ca

1.4. Emergency telephone number

Emergency number

1-800-363-0042 Call emergency number 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product.

For routine information, contact your supplier or Praxair sales representative.

SECTION 2: Hazard identification

Classification of the substance or mixture

GHS-CA classification

Flam. Gas 1 Liquefied gas H220 H280 H330 Acute Tox. 2 (Inhalation: gas) STOT SE 3 H335

GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms









Signal word : DANGER

Hazard statements

: EXTREMELY FLAMMABLE GAS
CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED
FATAL IF INHALED
MAY CAUSE RESPIRATORY IRRITATION
MAY FORM EXPLOSIVE MIXTURES WITH AIR
SYMPTOMS MAY BE DELAYED
EXTENDED EXPOSURE TO GAS REDUCES THE ABILITY TO SMELL SULFIDES

Precautionary statements

Do not handle until all safety precautions have been read and understood Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website. EN (English) SDS ID : E-4611

1/9



Hydrogen sulfide

Safety Data Sheet E-4611

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-10-2016 Supersedes: 10-15-2013

Do not breathe gas

Use and store only outdoors or in a well-ventilated area

Avoid release to the environment

Wear protective gloves, protective clothing, eye protection, respiratory protection, and/or face

Leaking gas fire: Do not extinguish, unless leak can be stopped safely

In case of leakage, eliminate all ignition sources Store locked up

Dispose of contents/container in accordance with container Supplier/owner instructions

Protect from sunlight when ambient temperature exceeds 52°C (125°F)

Close valve after each use and when empty

Do not open valve until connected to equipment prepared for use

When returning cylinder, install leak tight valve outlet cap or plug

Do not depend on odour to detect the presence of gas

Other hazards

Other hazards not contributing to the classification

: Contact with liquid may cause cold burns/frostbite.

Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

Substances

Name	CAS No.	% (Vol.)	Common Name (synonyms)
Hydrogen sulfide (Main constituent)	(CAS No) 7783-06-4		Hydrogen sulfide (H2S) / Hydrogen sulphide / Sulfur hydride / Sulfureted hydrogen / Dihydrogen sulphide / Hydrogensulfide

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

Description of first aid measures

First-aid measures after inhalation

: Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Call a physician.

First-aid measures after skin contact

The liquid may cause frostbite. For exposure to liquid, immediately warm frostbite area with warm water not to exceed 105°F (41°C). Water temperature should be tolerable to normal skin. Maintain skin warming for at least 15 minutes or until normal coloring and sensation have returned to the affected area. In case of massive exposure, remove clothing while showering with warm water. Seek medical evaluation and treatment as soon as possible.

First-aid measures after eye contact

Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately.

First-aid measures after ingestion

: Ingestion is not considered a potential route of exposure.

Most important symptoms and effects (acute and delayed)

No additional information available

Immediate medical attention and special treatment, if necessary

Other medical advice or treatment

: Obtain medical assistance. Treat with corticosteroid spray as soon as possible after inhalation.

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Suitable extinguishing media

Carbon dioxide, Dry chemical, Water spray or fog. Use extinguishing media appropriate for surrounding fire

Unsuitable extinguishing media

No additional information available

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website

EN (English) SDS ID : E-4611 2/9



Hydrogen sulfide

Safety Data Sheet E-4611

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-10-2016 Supersedes: 10-15-2013

Specific hazards arising from the hazardous product

Fire hazard

: EXTREMELY FLAMMABLE GAS. If venting or leaking gas catches fire, do not extinguish flames. Flammable vapors may spread from leak, creating an explosive reignition hazard. Vapors can be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from product handling point. Explosive atmospheres may linger. Before entering an area, especially a confined area, check the atmosphere with an appropriate device.

Explosion hazard : EXTREMELY FLAMMABLE GAS. Forms explosive mixtures with air and oxidizing agents.

Reactivity : No reactivity hazard other than the effects described in sub-sections below. Reactivity in case of fire : No reactivity hazard other than the effects described in sub-sections below.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions

: DANGER! Toxic, flammable liquefied gas

Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with their provincial and local fire code regulations.

Special protective equipment for fire fighters

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

Other information

Containers are equipped with a pressure relief device. (Exceptions may exist where authorized by TC.).

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedure

General measures

DANGER! Toxic, flammable liquefied gas . Forms explosive mixtures with air and oxidizing agents. Immediately evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Remove all sources of ignition if safe to do so. Reduce vapors with fog or fine water spray, taking care not to spread liquid with water. Shut off flow if safe to do so. Ventilate area or move container to a well-ventilated area. Flammable vapors may spread from leak and could explode if reignited by sparks or flames. Explosive atmospheres may linger. Before entering area, especially confined areas, check atmosphere with an appropriate device.

Methods and materials for containment and cleaning up

Methods for cleaning up

: Try to stop release. Reduce vapour with fog or fine water spray. Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

Reference to other sections

For further information refer to section 8: Exposure controls/personal protection

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling

: Leak-check system with soapy water; never use a flame

All piped systems and associated equipment must be grounded

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Use only explosion-proof equipment

Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g, wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website

EN (English) SDS ID : E-4611 3/9

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	



Hydrogen sulfide

Safety Data Sheet E-4611

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-10-2016 Supersedes: 10-15-2013

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store only where temperature will not exceed 125°F (52°C). Post "No Smoking/No Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g, NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

SECTION 8: Exposure c	ontrols/personal protection		
8.1. Control parameters			
Hydrogen sulfide (7783-06-4)		
USA - ACGIH	ACGIH TLV-TWA (ppm)	1 ppm	
USA - ACGIH	ACGIH TLV-STEL (ppm)	5 ppm	
USA - OSHA	OSHA PEL (Ceiling) (ppm)	20 ppm	
Canada (Quebec)	VECD (mg/m³)	21 mg/m³	
Canada (Quebec)	VECD (ppm)	15 ppm	
Canada (Quebec)	VEMP (mg/m³)	14 mg/m³	
Canada (Quebec)	VEMP (ppm)	10 ppm	
Alberta	OEL Ceiling (mg/m³)	21 mg/m³	
Alberta	OEL Ceiling (ppm)	15 ppm	
Alberta	OEL TWA (mg/m³)	14 mg/m³	
Alberta	OEL TWA (ppm)	10 ppm	
British Columbia	OEL Ceiling (ppm)	10 ppm	
Manitoba	OEL STEL (ppm)	5 ppm	
Manitoba	OEL TWA (ppm)	1 ppm	
New Brunswick	OEL STEL (mg/m³)	21 mg/m³	
New Brunswick	OEL STEL (ppm)	15 ppm	
New Brunswick	OEL TWA (mg/m³)	14 mg/m³	
New Brunswick	OEL TWA (ppm)	10 ppm	
New Foundland & Labrador	OEL STEL (ppm)	5 ppm	
New Foundland & Labrador	OEL TWA (ppm)	1 ppm	
Nova Scotia	OEL STEL (ppm)	5 ppm	
Nova Scotia	OEL TWA (ppm)	1 ppm	
Nunavut	OEL Ceiling (mg/m³)	28 mg/m³	
Nunavut	OEL Ceiling (ppm)	20 ppm	
Nunavut	OEL STEL (mg/m³)	21 mg/m³	
Nunavut	OEL STEL (ppm)	15 ppm	
Nunavut	OEL TWA (mg/m³)	14 mg/m³	
Nunavut	OEL TWA (ppm)	10 ppm	
Northwest Territories	OEL STEL (ppm)	15 ppm	

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

EN (English) SDS ID : E-4611 4/9

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	



Hydrogen sulfide

Safety Data Sheet E-4611

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-10-2016 Supersedes: 10-15-2013

Hydrogen sulfide (7783-06-4)		
Northwest Territories	OEL TWA (ppm)	10 ppm
Ontario	OEL STEL (ppm)	15 ppm
Ontario	OEL TWA (ppm)	10 ppm
Prince Edward Island	OEL STEL (ppm)	5 ppm
Prince Edward Island	OEL TWA (ppm)	1 ppm
Québec	VECD (mg/m³)	21 mg/m³
Québec	VECD (ppm)	15 ppm
Québec	VEMP (mg/m³)	14 mg/m³
Québec	VEMP (ppm)	10 ppm
Saskatchewan	OEL STEL (ppm)	15 ppm
Saskatchewan	OEL TWA (ppm)	10 ppm
Yukon	OEL STEL (mg/m³)	27 mg/m³
Yukon	OEL STEL (ppm)	15 ppm
Yukon	OEL TWA (mg/m³)	15 mg/m³
Yukon	OEL TWA (ppm)	10 ppm

Appropriate engineering controls

Appropriate engineering controls

: Use corrosion-resistant equipment. Use an explosion-proof local exhaust system. Local exhaust and general ventilation must be adequate to meet exposure standards. MECHANICAL (GENERAL): Inadequate - Use only in a closed system. Use explosion proof equipment and lighting.

Individual protection measures/Personal protective equipment

Personal protective equipment

: Safety glasses. Face shield. Gloves.







: Wear work gloves when handling containers. Wear heavy rubber gloves where contact with Hand protection product may occur.

Eye protection

Wear goggles and a face shield when transfilling or breaking transfer connections. Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and

any provincial regulations, local bylaws or guidelines

Respiratory protection Respiratory protection: Use respirable fume respirator or air supplied respirator when working in confined space or where local exhaust or ventilation does not keep exposure below TLV.

Select in accordance with provincial regulations, local bylaws or guidelines. Selection should be based on the current CSA standard Z94.4, "Selection, Care, and Use of Respirators." Respirators should also be approved by NIOSH and MSHA. For emergencies or instances with

unknown exposure levels, use a self-contained breathing apparatus (SCBA).

Wear cold insulating gloves when transfilling or breaking transfer connections. Standard EN Thermal hazard protection

511 - Cold insulating gloves.

Other information Other protection: Safety shoes for general handling at customer sites. Metatarsal shoes and

cuffless trousers for cylinder handling at packaging and filling plants. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines. For working with flammable and oxidizing materials, consider the use of flame resistant anti-static safety clothing

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state

: Gas

Appearance : Colorless gas. Colorless liquid at low temperature or under high pressure.

Molecular mass : 34 g/mol Colour : Colourless.

Odour : Odour can persist. Poor warning properties at low concentrations. Rotten eggs.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

EN (English) SDS ID : E-4611 5/9

PRAXAIR

Hydrogen sulfide

Safety Data Sheet E-4611

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-10-2016 Supersedes: 10-15-2013

рΗ : Not applicable. pH solution : No data available : No data available Relative evaporation rate (butylacetate=1) Relative evaporation rate (ether=1) : Not applicable. Melting point : -86 °C : -82.9 °C Freezing point : -60.3 °C Boiling point Flash point : Not applicable. Critical temperature : 100.4 °C : 260 °C Auto-ignition temperature Decomposition temperature : No data available

Vapour pressure : 1880 kPa Vapour pressure at 50 °C : No data available : 8940 kPa Critical pressure

Relative vapour density at 20 °C : >= Relative density : No data available

Relative density of saturated gas/air mixture : No data available Density : No data available

Relative gas density : 1.2

Solubility : Water: 3980 mg/l : Not applicable. Log Pow : Not applicable. Log Kow Viscosity, kinematic : Not applicable. Viscosity, dynamic : Not applicable. Viscosity, kinematic (calculated value) (40 °C) : No data available : Not applicable. Explosive properties

Oxidizing properties : None.

Flammability (solid, gas)

4.3 - 46 vol %

Other information

: Liquefied gas Gas group

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

SECTION 10: Stability and reactivity

10.1.

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : May react violently with oxidants. Can form explosive mixture with air. Conditions to avoid

: Avoid moisture in installation systems. Keep away from heat/sparks/open flames/hot surfaces. No smoking.

: Ammonia. Bases. Bromine pentafluoride. Chlorine trifluoride. chromium trioxide. (and heat). Incompatible materials Copper, (powdered), Fluorine, Lead, Lead oxide, Mercury, Nitric acid, Nitrogen trifluoride

nitrogen sulfide. Organic compounds. Oxidizing agents. Oxygen difluoride. Rubber. Sodium. (and moisture). Water

Hazardous decomposition products : Thermal decomposition may produce : Sulfur. Hydrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website

EN (English) SDS ID : E-4611 6/9

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	



Hydrogen sulfide

Safety Data Sheet E-4611

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-10-2016 Supersedes: 10-15-2013

Acute toxicity (inhalation) : Inhalation:gas: FATAL IF INHALED.

Hydrogen sulfide (\f)7783-06-4	
LC50 inhalation rat (mg/l)	0.99 mg/l (Exposure time: 1 h)
LC50 inhalation rat (ppm)	356 ppm/4h
ATE CA (gases)	356.00000000 ppmv/4h
ATE CA (vapours)	0.99000000 mg/l/4h
ATE CA (dust,mist)	0.99000000 mg/l/4h

Skin corrosion/irritation : Not classified

pH: Not applicable.

Not classified
pH: Not applicable.

Not classified

Not classified

Not classified

Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : MAY CAUSE RESPIRATORY IRRITATION.

Specific target organ toxicity (repeated

Serious eye damage/irritation

Germ cell mutagenicity
Carcinogenicity

Respiratory or skin sensitization

exposure)

: Not classified

Aspiration hazard : Not classified

SECTION 12:	Ecolo	aioal in	formation
SECTION 12.	ECOIO	uicai III	ioiiiatioii

12.1. Toxicity

Ecology - general : VERY TOXIC TO AQUATIC LIFE.

Hydrogen sulfide (7783-06-4)	
LC50 fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC50 fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

12.2. Persistence and degradability

Hydrogen sulfide (7783-06-4)	
Persistence and degradability	Not applicable for inorganic gases.

12.3. Bioaccumulative potential

Hydrogen sulfide (7783-06-4)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No data available.

12.4. Mobility in soil

Hydrogen sulfide (7783-06-4)		
Mobility in soil	No data available.	
Log Pow	Not applicable.	
Log Kow	Not applicable.	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	

12.5. Other adverse effects

Other adverse effects : May cause pH changes in aqueous ecological systems.

Effect on the ozone layer : None

Effect on global warming : No known effects from this product

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

EN (English) SDS ID : E-4611 7/9



Hydrogen sulfide

Safety Data Sheet E-4611

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-10-2016 Supersedes: 10-15-2013

SECTION 13: Disposal considerations

Disposal methods

Waste disposal recommendations : Do not attempt to dispose of residual or unused quantities. Return container to supplier.

SECTION 14: Transport information

Basic shipping description

In accordance with TDG

TDG

UN-No. (TDG) : UN1053

TDG Primary Hazard Classes : 2.3 - Class 2.3 - Toxic Gas.

: 2.1 TDG Subsidiary Classes

: HYDROGEN SULPHIDE Proper shipping name

ERAP Index : 500 Explosive Limit and Limited Quantity Index : 0 Passenger Carrying Ship Index : Forbidden

Passenger Carrying Road Vehicle or Passenger : Forbidden

Carrying Railway Vehicle Index

14.3. Air and sea transport

IMDG

UN-No. (IMDG) : 1053

Proper Shipping Name (IMDG) : HYDROGEN SULPHIDE

Class (IMDG) : 2 - Gases MFAG-No : 117 IATA

UN-No. (IATA) : 1053

Proper Shipping Name (IATA) : Hydrogen sulphide Class (IATA) : 2

SECTION 15: Regulatory information

15.1. National regulations

Hydrogen sulfide (7783-06-4)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Hydrogen sulfide (7783-06-4)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican national Inventory of Chemical Substances)

SECTION 16: Other information

Date of issue : 15/10/1979 Revision date : 10/08/2016 Supersedes : 15/10/2013

Indication of changes:

Training advice : Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard. Ensure operators understand the flammability hazard.

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

EN (English) SDS ID : E-4611 8/9

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

PRAXAIR Safety Data Sheet E-4611

Hydrogen sulfide

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-10-2016 Supersedes: 10-15-2013

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair Canada Inc. it is the user's obligation to determine the conditions of safe use of the product. Praxair Canada Inc, SDSs are furnished on sale or delivery by Praxair Canada Inc, or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.ca. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write Praxair Canada Inc, (Phone: 1-888-257-5149; Address: Praxair Canada Inc, 1 City Centre Drive, Suite 1200, Mississauga, Ontario, L5B 1M2).

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

NFPA health hazard

: 4 - Very short exposure could cause death or serious residual injury even though prompt medical attention was

NFPA fire hazard

: 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn

readily.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

Flammability

Physical

: 2 Moderate Hazard - Temporary or minor injury may occur

: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)

: 2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at normal temperature and pressure with low risk for explosion. Materials may react violently with water or form peroxides upon exposure to air.

SDS Canada (GHS) - Praxair

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	

Appendix B SO₂ SDS



Safety Data Sheet

Material Name: SULFUR DIOXIDE SDS ID: MAT22290

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

SULFUR DIOXIDE

Synonyms

MTG MSDS 80; SULFUROUS ACID ANHYDRIDE; SULFUROUS OXIDE; SULPHUR DIOXIDE; SULFUROUS ANHYDRIDE; FERMENTICIDE LIQUID; SULFUR DIOXIDE(SO2); SULFUR OXIDE; SULFUR OXIDE(SO2)

Chemical Family

inorganic, gas

Product Description

Classification determined in accordance with Compressed Gas Association standards.

Product Use

Industrial and Specialty Gas Applications.

Restrictions on Use

None known.

Details of the supplier of the safety data sheet

MATHESON TRI-GAS, INC.

3 Mountainview Road

Warren, NJ 07059

General Information: 1-800-416-2505 Emergency #: 1-800-424-9300 (CHEMTREC) Outside the US: 703-527-3887 (Call collect)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Gases Under Pressure - Liquefied gas

Acute Toxicity - Inhalation - Gas - Category 3

Skin Corrosion/Irritation - Category 1B

Serious Eye Damage/Eye Irritation - Category 1

Simple Asphyxiant GHS Label Elements

GHS Label Elemen Symbol(s)







Signal Word

Danger

Hazard Statement(s)

Contains gas under pressure; may explode if heated.

Toxic if inhaled.

Causes severe skin burns and eye damage.

May displace oxygen and cause rapid suffocation.

Precautionary Statement(s)

Prevention

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Page 1 of 9 Issue date: 2021-01-30 Revision 8.0 Print date: 2021-01-30

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	



Safety Data Sheet

Material Name: SULFUR DIOXIDE SDS ID: MAT22290

Wash thoroughly after handling. Do not breathe dusts or mists.

Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Immediately call a POISON CENTER or doctor.

Specific treatment (see label).

Storage

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other Hazards

Contact with liquified gas may cause frostbite.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS		
CAS Component Name Percent		
7446-09-5	Sulfur dioxide	100.0
Section 4 - FIRST AID MEASURES		

Inhalation

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical attention.

Skir

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115°F; 41-46°C). If warm water is not available, gently wrap affected parts in blankets. DO NOT induce vomiting. Get immediate medical attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention.

Ingestion

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get immediate medical attention.

Most Important Symptoms/Effects

Acute

Toxic if inhaled, frostbite, suffocation, respiratory tract burns, skin burns, eye burns

Delayed

No information on significant adverse effects.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Note to Physicians

For inhalation, consider oxygen.

Page 2 of 9 Issue date: 2021-01-30 Revision 8.0 Print date: 2021-01-30

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	



Safety Data Sheet

Material Name: SULFUR DIOXIDE SDS ID: MAT22290

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

carbon dioxide, regular dry chemical, Large fires: Use regular foam or flood with fine water spray.

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical

Negligible fire hazard.

Hazardous Combustion Products

sulfur oxides

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Keep unnecessary people away, isolate hazard area and deny entry.

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Ventilate closed spaces before entering. Evacuation radius: 150 feet. Stop leak if possible without personal risk. Reduce vapors with water spray. Do not get water directly on material.

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Do not get in eyes, on skin, or on clothing. Do not breathe gas, fumes, vapor, or spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Keep only in original container. Avoid release to the environment.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight.

Store and handle in accordance with all current regulations and standards. Protect from physical damage. Store outside or in a detached building. Keep separated from incompatible substances.

Incompatible Materials

bases, combustible materials, halogens, metal carbide, metal oxides, metals, oxidizing materials, peroxides, reducing agents

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits Sulfur dioxide 7446-09-5 ACGIH: 0.25 ppm STEL

Page 3 of 9 Issue date: 2021-01-30 Revision 8.0 Print date: 2021-01-30

SDS ID: MAT22290

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	



Safety Data Sheet

Material Name: SULFUR DIOXIDE

NIOSH:	2 ppm TWA; 5 mg/m3 TWA
	5 ppm STEL; 13 mg/m3 STEL
	100 ppm IDLH
OSHA (US):	5 ppm TWA; 13 mg/m3 TWA
Mexico:	0.25 ppm STEL [PPT-CT]

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)
There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles with a faceshield. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing. Wear chemical resistant clothing to prevent skin contact.

Respiratory Protection

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES				
Appearance	colorless gas	Physical State	gas	
Odor	irritating odor	Color	colorless	
Odor Threshold	3 - 5 ppm	pН	(Acidic in solution)	
Melting Point	-73 °C (-99 °F)	Boiling Point	-10 °C (14 °F)	
Boiling Point Range	Not available	Freezing point	Not available	
Evaporation Rate	>1 (Butyl acetate = 1)	Flammability (solid, gas)	Not available	
Autoignition Temperature	Not available	Flash Point (Not flammable		
Lower Explosive Limit	Not available	Decomposition temperature	Not available	
Upper Explosive Limit	Not available	Vapor Pressure	2432 mmHg @ 20 °C	
Vapor Density (air=1)	2.26	Specific Gravity (water=1)	1.462 at -10 °C	

Page 4 of 9 Issue date: 2021-01-30 Revision 8.0 Print date: 2021-01-30

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	



Safety Data Sheet

Material Name: SULFUR DIOXIDE SDS ID: MAT22290

Water Solubility	22.8 % (@ 0 °C)	.8 % (@ 0 °C) Partition coefficient: n- octanol/water	
Viscosity	Not available	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	Not available
Physical Form	liquified gas	Molecular Formula	S-O2
Molecular Weight	64.06		

Solvent Solubility

Soluble

alcohol, acetic acid, sulfuric acid, ether, chloroform, Benzene, sulfuryl chloride, nitrobenzenes, Toluene, acetone

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable at normal temperatures and pressure.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Minimize contact with material. Containers may rupture or explode if exposed to heat.

Incompatible Materials

bases, combustible materials, halogens, metal carbide, metal oxides, metals, oxidizing materials, peroxides, reducing agents

Hazardous decomposition products

oxides of sulfur

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

Toxic if inhaled. Causes damage to respiratory system, burns, difficulty breathing

Skin Contact

skin burns

Eye Contact

eye burns

Ingestion

burns, nausea, vomiting, diarrhea, stomach pain

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Sulfur dioxide (7446-09-5)

Inhalation LC50 Rat 965 - 1168 ppm 4 h

Product Toxicity Data

Acute Toxicity Estimate

No data available.

Immediate Effects

Page 5 of 9 Issue date: 2021-01-30 Revision 8.0 Print date: 2021-01-30

SDS ID: MAT22290

Permian Resources Corporation	H ₂ S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	



Safety Data Sheet

Material Name: SULFUR DIOXIDE

Toxic if inhaled, frostbite, suffocation, respiratory tract burns, skin burns, eye burns

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

respiratory tract burns, skin burns, eye burns

Respiratory Sensitization

No data available.

Dermal Sensitization

No data available.

Sulfur dioxide	7446-09-5	
ACGIH:	A4 - Not Classifiable as a Human Carcinogen	
IARC:	Monograph 54 [1992] (Group 3 (not classifiable))	

Germ Cell Mutagenicity

No data available.

Tumorigenic Data

No data available

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

Not applicable.

Medical Conditions Aggravated by Exposure

respiratory disorders

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

No LOLI ecotoxicity data are available for this product's components.

Persistence and Degradability

No data available.

Bioaccumulative Potential

No data available.

Mobility

No data available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name: SULFUR DIOXIDE

Page 6 of 9 Issue date: 2021-01-30 Revision 8.0 Print date: 2021-01-30

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	



Safety Data Sheet

Material Name: SULFUR DIOXIDE SDS ID: MAT22290

Hazard Class: 2.3 UN/NA #: UN1079 Required Label(s): 2.3

IMDG Information:

Shipping Name: SULPHUR DIOXIDE

Hazard Class: 2.3 UN#: UN1079 Required Label(s): 2.3

TDG Information:

Shipping Name: SULFUR DIOXIDE

Hazard Class: 2.3 UN#: UN1079 Required Label(s): 2.3

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Sulfur dioxide	7446-09-5	
SARA 302:	500 lb TPQ	
OSHA (safety):	1000 lb TQ (Liquid)	
SARA 304:	500 lb EPCRA RQ	

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Gas Under Pressure; Acute toxicity; Skin Corrosion/Irritation; Serious Eye Damage/Eye Irritation; Simple Asphyxiant

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Sulfur dioxide	7446-09-5	Yes	Yes	Yes	Yes	Yes

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)



WARNING

This product can expose you to chemicals including Sulfur dioxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Page 7 of 9 Issue date: 2021-01-30 Revision 8.0 Print date: 2021-01-30

Permian Resources Corporation	H₂S Contingency Plan	Eddy County, New Mexico
	Mezcal 10 Fed Com 121H, 131H 132H,	
	133H, 134H	



Safety Data Sheet

Material Name: SULFUR DIOXIDE SDS ID: MAT22290

Sulfur dioxide	7446-09-5
Repro/Dev. Tox	developmental toxicity, 7/29/2011

Component Analysis - Inventory Sulfur dioxide (7446-09-5)

1							
	US	CA	AU	CN	EU	JP - ENCS	JP - ISHI

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No

KR - REACH CCA	MX NZ PH		TH-TECI	TW, CN	VN (Draft)	
No	Yes	Yes	Yes	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 3 Fire: 0 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes SDS update: 02/10/2016

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU -Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA -California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA -Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG -Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN -European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH -Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; KR REACH CCA Korea Registration and Evaluation of Chemical Substances Chemical Control Act; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; Ne- Non-specific; NFPA National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL - Non-Domestic Substance List (Canada); NTP -National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL-Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH-Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA -Superfund Amendments and Reauthorization Act; Sc - Semi-quantitative; STEL - Short-term Exposure Limit;

Page 8 of 9 Issue date: 2021-01-30 Revision 8.0 Print date: 2021-01-30

NEW MEXICO

(SP) EDDY MICHELADA FED COM MICHELADA 3 FED COM 134H

OWB

Plan: PWP0

Standard Planning Report - Geographic

26 June, 2024

Planning Report - Geographic

Database: Company: Project:

Compass **NEW MEXICO** (SP) EDDY

MICHELADA FED COM MICHELADA 3 FED COM 134H

Wellbore: **OWB** PWP0 Design:

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well MICHELADA 3 FED COM 134H

GL @ 3225.0usft GL @ 3225.0usft

Grid

Minimum Curvature

Project

Site

Site:

Well:

(SP) EDDY

Map System: Geo Datum: Map Zone:

US State Plane 1983 North American Datum 1983 New Mexico Eastern Zone

System Datum:

Mean Sea Level

MICHELADA FED COM

Site Position: From:

Мар

Northing: Easting:

585,277.78 usft 644,676.60 usft 13-3/16 "

Latitude: Longitude:

579,981.05 usft

7.95

32° 36' 30.715 N 103° 59' 51.842 W

Position Uncertainty: 0.0 usft Slot Radius:

MICHELADA 3 FED COM 134H Well

Well Position +N/-S +E/-W

0.0 usft 0.0 usft 0.0 usft Northing: Easting:

660,189.09 usft Wellhead Elevation: usft

Latitude: Longitude: **Ground Level:**

32° 35' 37.782 N 103° 56' 50.711 W

3,225.0 usft

0.21 ° **Grid Convergence:**

PWP0

OWB Wellbore

Position Uncertainty

Model Name Magnetics Sample Date IGRF200510 12/31/2009 Declination (°)

Dip Angle (°)

Field Strength (nT)

48.975.43628785

Design

Audit Notes:

Version:

Phase:

PROTOTYPE

Tie On Depth:

0.0

60.52

Vertical Section: Depth From (TVD) +N/-S +E/-W Direction (usft) (usft) (usft) (°) 0.0 0.0 0.0 273.05

Plan Survey Tool Program

Date 6/26/2024

Depth From Depth To (usft)

(usft)

Survey (Wellbore)

Tool Name

Remarks

0.0 21,283.3 PWP0 (OWB) MWD+IFR1+MS OWSG Rev2 MWD + IFR1 +

Plan Sections Vertical Build Measured Dogleg Turn Depth Inclination Azimuth Depth +N/-S +E/-W Rate Rate Rate **TFO** (°/100usft) (usft) (usft) (usft) (usft) (°/100usft) (°/100usft) (°) (°) Target (°) 0.0 0.00 0.00 0.0 0.0 0.00 0.00 0.00 0.0 0.00 1,750.0 0.00 0.00 1,750.0 0.0 0.0 0.00 0.00 0.00 0.00 2,556.0 16.12 300.75 2,545.4 57.6 -96.8 2.00 2.00 0.00 300.75 7,097.2 16.12 300.75 6,908.1 702.3 -1,180.4 0.00 0.00 0.00 0.00 7.903.2 0.00 0.00 7.703.5 759.9 -1.277.1 2.00 -2.00 0.00 180.00 759 9 0.00 0.00 7.963.2 0.00 0.00 7,763.5 -1.277.10.00 0.00 8,713.2 90.00 270.02 8,241.0 760.0 -1.754.612.00 12.00 -12.00270.02 21,284.2 90.00 270.02 8,241.0 763.7 -14,325.6 0.00 0.00 0.00 0.00 MICHELADA 3 FED (

Planning Report - Geographic

Database: Compass
Company: NEW MEXICO

 Project:
 (SP) EDDY

 Site:
 MICHELADA FED COM

 Well:
 MICHELADA 3 FED COM 134H

Wellbore: OWB
Design: PWP0

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well MICHELADA 3 FED COM 134H

GL @ 3225.0usft GL @ 3225.0usft

Grid

esigii.	FVVF								
lanned Survey	1								
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.0	0.00	0.00	0.0	0.0	0.0	579,981.05	660,189.09	32° 35' 37.782 N	103° 56' 50.711
100.0	0.00	0.00	100.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
200.0	0.00	0.00	200.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
300.0	0.00	0.00	300.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
400.0	0.00	0.00	400.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
500.0	0.00	0.00	500.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
600.0	0.00	0.00	600.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
700.0	0.00	0.00	700.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
800.0	0.00	0.00	800.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
900.0	0.00	0.00	900.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
1,000.0	0.00	0.00	1,000.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
1,100.0	0.00	0.00	1,100.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
1,200.0	0.00	0.00	1,200.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.711
1,300.0	0.00	0.00	1,300.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.71
1,400.0	0.00	0.00	1,400.0	0.0	0.0	579,981.05	660,189.09	32° 35′ 37.782 N	103° 56' 50.71
1,500.0	0.00	0.00	1,500.0	0.0	0.0	579,981.05	660,189.09	32° 35' 37.782 N	103° 56' 50.71
1,600.0	0.00	0.00	1,600.0	0.0	0.0	579,981.05	660,189.09	32° 35' 37.782 N	103° 56' 50.71
1,700.0	0.00	0.00	1,700.0	0.0	0.0	579,981.05	660,189.09	32° 35' 37.782 N	103° 56' 50.71
1,750.0	0.00	0.00	1,750.0	0.0	0.0	579,981.05	660,189.09	32° 35' 37.782 N	103° 56' 50.71
Start Bu	ild 2.00								
1,800.0	1.00	300.75	1,800.0	0.2	-0.4	579,981.28	660,188.72	32° 35' 37.784 N	103° 56' 50.71
1,900.0	3.00	300.75	1,899.9	2.0	-3.4	579,983.06	660,185.72	32° 35' 37.802 N	103° 56' 50.75
2,000.0	5.00	300.75	1,999.7	5.6	-9.4	579,986.63	660,179.73	32° 35' 37.837 N	103° 56' 50.82
2,100.0	7.00	300.75	2,099.1	10.9	-18.4	579,991.97	660,170.74	32° 35' 37.890 N	103° 56' 50.92
2,200.0	9.00	300.75	2,198.2	18.0	-30.3	579,999.09	660,158.78	32° 35' 37.961 N	103° 56' 51.06
2,300.0	11.00	300.75	2,296.6	26.9	-45.2	580,007.97	660,143.86	32° 35' 38.050 N	103° 56' 51.23
2,400.0	13.00	300.75	2,394.4	37.5	-63.1	580,018.60	660,125.99	32° 35' 38.155 N	103° 56' 51.44
2,500.0	15.00	300.75	2,491.5	49.9	-83.9	580,030.96	660,105.20	32° 35' 38.279 N	103° 56' 51.689
2,556.0	16.12	300.75	2,545.4	57.6	-96.8	580,038.64	660,092.30	32° 35' 38.355 N	103° 56' 51.84
	11.3 hold at 25		2,0 .0	00	00.0	000,000.0	000,002.00	02 00 00.000	
2,600.0	16.12	300.75	2,587.7	63.8	-107.3	580,044.89	660,081.80	32° 35' 38.417 N	103° 56' 51.96
2,700.0	16.12	300.75	2,683.7	78.0	-131.2	580,059.09	660,057.94	32° 35' 38.559 N	103° 56' 52.24
2,800.0	16.12	300.75	2,779.8	92.2	-155.0	580,073.28	660,034.08	32° 35' 38.700 N	103° 56' 52.51
2,900.0	16.12	300.75	2,875.9	106.4	-178.9	580,087.48	660,010.22	32° 35' 38.841 N	103° 56' 52.79
3,000.0	16.12	300.75	2,972.0	120.6	-202.7	580,101.68	659,986.36	32° 35' 38.982 N	103° 56' 53.07
3,100.0	16.12	300.75	3,068.0	134.8	-226.6	580,115.87	659,962.49	32° 35' 39.124 N	103° 56' 53.35
3,200.0	16.12	300.75	3,164.1	149.0	-250.5	580,130.07	659,938.63	32° 35' 39.265 N	103° 56' 53.63
3,300.0	16.12	300.75	3,260.2	163.2	-274.3	580,144.26	659,914.77	32° 35' 39.406 N	103° 56' 53.91
3,400.0	16.12	300.75	3,356.2	177.4	-274.3	580,158.46	659,890.91	32° 35' 39.548 N	103° 56' 54.18
3,500.0	16.12	300.75	3,452.3	191.6	-322.0	580,172.66	659,867.05	32° 35' 39.689 N	103° 56' 54.46
3,600.0	16.12	300.75	3,548.4	205.8	-345.9	580,186.85	659,843.19	32° 35' 39.830 N	103° 56' 54.74
3,700.0	16.12	300.75	3,644.4	220.0	-369.8	580,201.05	659,819.33	32° 35' 39.972 N	103° 56' 55.02
3,800.0	16.12	300.75	3,740.5	234.2	-393.6	580,215.24	659,795.47	32° 35' 40.113 N	103° 56' 55.30
3,900.0	16.12	300.75	3,836.6	248.4	-417.5	580,229.44	659,771.61	32° 35' 40.254 N	103° 56' 55.58
4,000.0	16.12	300.75	3,932.6	262.6	-441.3	580,243.64	659,747.75	32° 35' 40.396 N	103° 56' 55.85
4,000.0	16.12	300.75	4,028.7	276.8	-441.3 -465.2	580,257.83	659,723.89	32° 35' 40.537 N	103° 56' 56.13'
4,100.0	16.12	300.75	4,026.7	270.8	-405.2 -489.1	580,272.03	659,700.03	32° 35' 40.678 N	103° 56' 56.41
4,200.0	16.12	300.75	4,124.6	305.2	-409.1 -512.9	580,286.22	659,676.17	32° 35' 40.820 N	103 56 56.413 103° 56' 56.69
4,400.0		300.75		305.2 319.4	-512.9 -536.8	580,300.42	659,652.31	32° 35' 40.961 N	103° 56' 56.97
4,400.0	16.12 16.12	300.75	4,316.9 4,413.0	333.6	-536.6 -560.6		659,628.45	32° 35' 41.102 N	103° 56' 57.25
						580,314.62 580,328,81	659,628.45		
4,600.0	16.12 16.12	300.75	4,509.0 4,605.1	347.8 362.0	-584.5	580,328.81 580,343.01	,	32° 35' 41.244 N	103° 56' 57.52
4,700.0	16.12	300.75	4,605.1	362.0	-608.4	580,343.01	659,580.73	32° 35' 41.385 N	103° 56' 57.80'
4,800.0	16.12	300.75	4,701.2	376.2	-632.2	580,357.21	659,556.87	32° 35' 41.526 N	103° 56' 58.08
4,900.0	16.12	300.75	4,797.3	390.3	-656.1	580,371.40	659,533.01	32° 35' 41.668 N	103° 56' 58.363

Planning Report - Geographic

Database: Compass
Company: NEW MEXICO
Project: (SP) EDDY

Site: MICHELADA FED COM
Well: MICHELADA 3 FED COM 134H

Wellbore: OWB
Design: PWP0

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well MICHELADA 3 FED COM 134H

GL @ 3225.0usft GL @ 3225.0usft

Grid

ned Survey									
Measured Depth (usft)	Inclination	Azimuth	Vertical Depth (usft)	+N/-S	+E/-W	Map Northing (usft)	Map Easting (usft)	l stands	1
(usit)	(°)	(°)	(usit)	(usft)	(usft)	(usit)		Latitude	Longitude
5,000.0	16.12	300.75	4,893.3	404.5	-679.9	580,385.60	659,509.15	32° 35′ 41.809 N	103° 56' 58.642
5,100.0	16.12	300.75	4,989.4	418.7	-703.8	580,399.79	659,485.29	32° 35′ 41.950 N	103° 56' 58.920
5,200.0	16.12	300.75	5,085.5	432.9	-727.7	580,413.99	659,461.43	32° 35′ 42.092 N	103° 56' 59.198
5,300.0	16.12	300.75	5,181.5	447.1	-751.5	580,428.19	659,437.57	32° 35′ 42.233 N	103° 56' 59.476
5,400.0	16.12	300.75	5,277.6	461.3	-775.4	580,442.38	659,413.71	32° 35′ 42.374 N	103° 56' 59.755
5,500.0	16.12	300.75	5,373.7	475.5	-799.2	580,456.58	659,389.85	32° 35′ 42.516 N	103° 57' 0.03
5,600.0	16.12	300.75	5,469.7	489.7	-823.1	580,470.77	659,365.99	32° 35′ 42.657 N	103° 57' 0.31
5,700.0	16.12	300.75	5,565.8	503.9	-847.0	580,484.97	659,342.13	32° 35′ 42.798 N	103° 57' 0.59
5,800.0	16.12	300.75	5,661.9	518.1	-870.8	580,499.17	659,318.27	32° 35′ 42.940 N	103° 57' 0.86
5,900.0	16.12	300.75	5,757.9	532.3	-894.7	580,513.36	659,294.41	32° 35′ 43.081 N	103° 57' 1.14
6,000.0	16.12	300.75	5,854.0	546.5	-918.5	580,527.56	659,270.55	32° 35′ 43.222 N	103° 57' 1.42
6,100.0	16.12	300.75	5,950.1	560.7	-942.4	580,541.75	659,246.68	32° 35′ 43.364 N	103° 57' 1.70
6,200.0	16.12	300.75	6,046.1	574.9	-966.3	580,555.95	659,222.82	32° 35' 43.505 N	103° 57' 1.98
6,300.0	16.12	300.75	6,142.2	589.1	-990.1	580,570.15	659,198.96	32° 35' 43.646 N	103° 57' 2.26
6,400.0	16.12	300.75	6,238.3	603.3	-1,014.0	580,584.34	659,175.10	32° 35' 43.788 N	103° 57' 2.53
6,500.0	16.12	300.75	6,334.4	617.5	-1,037.9	580,598.54	659,151.24	32° 35' 43.929 N	103° 57' 2.81
6,600.0	16.12	300.75	6,430.4	631.7	-1,061.7	580,612.73	659,127.38	32° 35' 44.070 N	103° 57' 3.09
6,700.0	16.12	300.75	6,526.5	645.9	-1,085.6	580,626.93	659,103.52	32° 35' 44.212 N	103° 57' 3.37
6,800.0	16.12	300.75	6,622.6	660.1	-1,109.4	580,641.13	659,079.66	32° 35' 44.353 N	103° 57' 3.65
6,900.0	16.12	300.75	6,718.6	674.3	-1,133.3	580,655.32	659,055.80	32° 35' 44.494 N	103° 57' 3.92
7,000.0	16.12	300.75	6,814.7	688.5	-1,157.2	580,669.52	659,031.94	32° 35' 44.636 N	103° 57' 4.20
7,097.2	16.12	300.75	6,908.1	702.3	-1,180.4	580,683.32	659,008.74	32° 35' 44.773 N	103° 57' 4.47
Start Dro			-,		,	,	,		
7,100.0	16.06	300.75	6,910.8	702.7	-1,181.0	580,683.71	659,008.08	32° 35' 44.777 N	103° 57' 4.48
7,200.0	14.06	300.75	7,007.3	715.9	-1,203.3	580,697.00	658,985.75	32° 35' 44.909 N	103° 57' 4.74
7,300.0	12.06	300.75	7,104.7	727.5	-1,222.8	580,708.56	658,966.32	32° 35' 45.024 N	103° 57' 4.97
7,400.0	10.06	300.75	7,202.9	737.3	-1,239.3	580,718.37	658,949.83	32° 35' 45.122 N	103° 57' 5.16
7,500.0	8.06	300.75	7,301.6	745.4	-1,252.8	580,726.43	658,936.29	32° 35' 45.202 N	103° 57' 5.32
7,600.0	6.06	300.75	7,400.8	751.7	-1,263.4	580,732.72	658,925.72	32° 35' 45.265 N	103° 57' 5.44
7,700.0	4.06	300.75	7,500.4	756.2	-1,271.0	580,737.23	658,918.14	32° 35' 45.310 N	103° 57' 5.53
7,800.0	2.06	300.75	7,600.3	758.9	-1,275.6	580,739.96	658,913.54	32° 35' 45.337 N	103° 57' 5.58
7,903.2	0.00	0.00	7,703.5	759.9	-1,277.1	580,740.91	658,911.94	32° 35' 45.346 N	103° 57' 5.60
) hold at 7903		7,700.0	700.0	1,2,7,1	000,1 10.01	000,011.01	02 00 10.01011	100 01 0.00
7,963.2	0.00	0.00	7,763.5	759.9	-1,277.1	580,740.91	658,911.94	32° 35' 45.346 N	103° 57' 5.60
	12.00 TFO 2								
7,975.0	1.41	270.02	7,775.3	759.9	-1,277.3	580,740.91	658,911.80	32° 35' 45.346 N	103° 57' 5.60
8,000.0	4.41	270.02	7,800.2	759.9	-1,278.6	580,740.91	658,910.53	32° 35' 45.346 N	103° 57' 5.62
8,025.0	7.41	270.02	7,825.1	759.9	-1,281.1	580,740.91	658,907.95	32° 35' 45.346 N	103° 57' 5.65
8,050.0	10.41	270.02	7,849.8	759.9	-1,285.0	580,740.92	658,904.08	32° 35' 45.347 N	103° 57' 5.69
8,075.0	13.41	270.02	7,874.3	759.9	-1,290.2	580,740.92	658,898.92	32° 35' 45.347 N	103° 57' 5.76
8,100.0	16.41	270.02	7,898.4	759.9	-1,296.6	580,740.92	658,892.49	32° 35' 45.347 N	103° 57' 5.83
8,125.0	19.41	270.02	7,922.2	759.9	-1,304.3	580,740.92	658,884.80	32° 35' 45.347 N	103° 57' 5.92
8,150.0	22.41	270.02	7,945.6	759.9	-1,313.2	580,740.92	658,875.88	32° 35' 45.348 N	103° 57' 6.02
8,175.0	25.41	270.02	7,968.4	759.9	-1,323.4	580,740.93	658,865.74	32° 35' 45.348 N	103° 57' 6.14
8,200.0	28.41	270.02	7,990.7	759.9	-1,334.7	580,740.93	658,854.43	32° 35' 45.348 N	103° 57' 6.28
8,225.0	31.41	270.02	8,012.4	759.9	-1,347.1	580,740.93	658,841.96	32° 35' 45.349 N	103° 57' 6.42
8,250.0	34.41	270.02	8,033.3	759.9	-1,360.7	580,740.94	658,828.38	32° 35' 45.349 N	103° 57' 6.58
8,275.0	37.41	270.02	8,053.6	759.9	-1,375.4	580,740.94	658,813.72	32° 35' 45.350 N	103° 57' 6.75
8,300.0	40.41	270.02	8,073.0	759.9	-1,391.1	580,740.95	658,798.01	32° 35' 45.351 N	103° 57' 6.93
8,325.0	43.41	270.02	8,091.6	759.9	-1,407.8	580,740.95	658,781.32	32° 35' 45.351 N	103° 57' 7.13
8,350.0	46.41	270.02	8,109.3	759.9	-1,425.4	580,740.96	658,763.67	32° 35' 45.352 N	103° 57' 7.34
	49.41	270.02	8,126.1	759.9	-1,444.0	580,740.96	658,745.12	32° 35' 45.353 N	103° 57' 7.55
8,3/50		-10.02	0,120.1	. 00.0	1, 177.0	555,175.50	555,175.12	02 00 TO.000 N	100 01 1.00
8,375.0 8,400.0	52.41	270.02	8,141.9	759.9	-1,463.4	580,740.97	658,725.71	32° 35' 45.353 N	103° 57' 7.78

Planning Report - Geographic

Database: Compass
Company: NEW MEXICO
Project: (SP) EDDY

Site: MICHELADA FED COM
Well: MICHELADA 3 FED COM 134H

Wellbore: OWB
Design: PWP0

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well MICHELADA 3 FED COM 134H

GL @ 3225.0usft GL @ 3225.0usft

Grid

Design.	FVVF								
Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
8,450.0	58.41	270.02	8,170.2	759.9	-1,504.5	580,740.98	658,684.57	32° 35' 45.355 N	103° 57' 8.265 V
8,475.0	61.41	270.02	8,182.8	759.9	-1,526.2	580,740.99	658,662.94	32° 35' 45.356 N	103° 57' 8.518 V
8,500.0	64.41	270.02	8,194.1	759.9	-1,548.4	580,740.99	658,640.68	32° 35′ 45.357 N	103° 57' 8.778 \
8,525.0	67.41	270.02	8,204.3	759.9	-1,571.2	580,741.00	658,617.86	32° 35′ 45.358 N	103° 57' 9.045 \
8,550.0	70.41	270.02	8,213.3	760.0	-1,594.6	580,741.01	658,594.54	32° 35′ 45.358 N	103° 57' 9.318 \
8,575.0	73.41	270.02	8,221.1	760.0	-1,618.3	580,741.01	658,570.78	32° 35′ 45.359 N	103° 57' 9.595 '
8,600.0	76.41	270.02	8,227.6	760.0	-1,642.5	580,741.02	658,546.64	32° 35′ 45.360 N	103° 57' 9.878 '
8,625.0	79.41	270.02	8,232.8	760.0	-1,666.9	580,741.03	658,522.20	32° 35′ 45.361 N	103° 57' 10.163
8,650.0	82.41	270.02	8,236.8	760.0	-1,691.6	580,741.04	658,497.52	32° 35′ 45.362 N	103° 57' 10.452
8,675.0	85.41	270.02	8,239.4	760.0	-1,716.4	580,741.04	658,472.66	32° 35′ 45.363 N	103° 57' 10.742 '
8,700.0	88.41	270.02	8,240.8	760.0	-1,741.4	580,741.05	658,447.70	32° 35′ 45.364 N	103° 57' 11.034
8,713.2	90.00	270.02	8,241.0	760.0	-1,754.6	580,741.05	658,434.48	32° 35′ 45.365 N	103° 57' 11.189 '
Start 125	71.0 hold at 8	3713.2 MD							
8,800.0	90.00	270.02	8,241.0	760.0	-1,841.4	580,741.08	658,347.70	32° 35′ 45.368 N	103° 57' 12.203
8,900.0	90.00	270.02	8,241.0	760.1	-1,941.4	580,741.11	658,247.70	32° 35′ 45.372 N	103° 57' 13.372
9,000.0	90.00	270.02	8,241.0	760.1	-2,041.4	580,741.14	658,147.70	32° 35′ 45.376 N	103° 57' 14.541
9,100.0	90.00	270.02	8,241.0	760.1	-2,141.4	580,741.17	658,047.70	32° 35′ 45.379 N	103° 57' 15.710
9,200.0	90.00	270.02	8,241.0	760.1	-2,241.4	580,741.20	657,947.70	32° 35′ 45.383 N	103° 57' 16.879
9,300.0	90.00	270.02	8,241.0	760.2	-2,341.4	580,741.23	657,847.70	32° 35′ 45.387 N	103° 57' 18.048
9,400.0	90.00	270.02	8,241.0	760.2	-2,441.4	580,741.26	657,747.70	32° 35′ 45.391 N	103° 57' 19.217
9,500.0	90.00	270.02	8,241.0	760.2	-2,541.4	580,741.29	657,647.70	32° 35′ 45.395 N	103° 57' 20.386
9,600.0	90.00	270.02	8,241.0	760.3	-2,641.4	580,741.32	657,547.70	32° 35′ 45.398 N	103° 57' 21.555
9,700.0	90.00	270.02	8,241.0	760.3	-2,741.4	580,741.35	657,447.70	32° 35′ 45.402 N	103° 57' 22.723
9,800.0	90.00	270.02	8,241.0	760.3	-2,841.4	580,741.38	657,347.70	32° 35′ 45.406 N	103° 57' 23.892
9,900.0	90.00	270.02	8,241.0	760.4	-2,941.4	580,741.41	657,247.70	32° 35′ 45.410 N	103° 57' 25.061
10,000.0	90.00	270.02	8,241.0	760.4	-3,041.4	580,741.44	657,147.70	32° 35′ 45.414 N	103° 57' 26.230
10,100.0	90.00	270.02	8,241.0	760.4	-3,141.4	580,741.47	657,047.70	32° 35′ 45.417 N	103° 57' 27.399
10,200.0	90.00	270.02	8,241.0	760.4	-3,241.4	580,741.50	656,947.70	32° 35′ 45.421 N	103° 57' 28.568
10,300.0	90.00	270.02	8,241.0	760.5	-3,341.4	580,741.53	656,847.70	32° 35′ 45.425 N	103° 57' 29.737
10,400.0	90.00	270.02	8,241.0	760.5	-3,441.4	580,741.56	656,747.70	32° 35′ 45.429 N	103° 57' 30.906
10,500.0	90.00	270.02	8,241.0	760.5	-3,541.4	580,741.59	656,647.70	32° 35′ 45.433 N	103° 57' 32.075
10,600.0	90.00	270.02	8,241.0	760.6	-3,641.4	580,741.62	656,547.70	32° 35′ 45.436 N	103° 57' 33.244 '
10,700.0	90.00	270.02	8,241.0	760.6	-3,741.4	580,741.65	656,447.70	32° 35′ 45.440 N	103° 57' 34.413
10,800.0	90.00	270.02	8,241.0	760.6	-3,841.4	580,741.68	656,347.70	32° 35′ 45.444 N	103° 57' 35.582
10,900.0	90.00	270.02	8,241.0	760.7	-3,941.4	580,741.71	656,247.70	32° 35′ 45.448 N	103° 57' 36.751
11,000.0	90.00	270.02	8,241.0	760.7	-4,041.4	580,741.73	656,147.70	32° 35' 45.451 N	103° 57' 37.920
11,100.0	90.00	270.02	8,241.0	760.7	-4,141.4	580,741.76	656,047.70	32° 35' 45.455 N	103° 57' 39.089
11,200.0	90.00	270.02	8,241.0	760.7	-4,241.4	580,741.79	655,947.70	32° 35' 45.459 N	103° 57' 40.257
11,300.0	90.00	270.02	8,241.0	760.8	-4,341.4	580,741.82	655,847.70	32° 35' 45.463 N	103° 57' 41.426
11,400.0	90.00	270.02	8,241.0	760.8	-4,441.4	580,741.85	655,747.70	32° 35' 45.466 N	103° 57' 42.595
11,500.0	90.00	270.02	8,241.0	760.8	-4,541.4	580,741.88	655,647.70	32° 35' 45.470 N	103° 57' 43.764
11,600.0	90.00	270.02	8,241.0	760.9	-4,641.4	580,741.91	655,547.70	32° 35' 45.474 N	103° 57' 44.933
11,700.0	90.00	270.02	8,241.0	760.9	-4,741.4	580,741.94	655,447.70	32° 35' 45.478 N	103° 57' 46.102
11,800.0	90.00	270.02	8,241.0	760.9	-4,841.4	580,741.97	655,347.70	32° 35' 45.481 N	103° 57' 47.271
11,900.0	90.00	270.02	8,241.0	760.9	-4,941.4	580,742.00	655,247.70	32° 35' 45.485 N	103° 57' 48.440
12,000.0	90.00	270.02	8,241.0	761.0	-5,041.4	580,742.03	655,147.70	32° 35' 45.489 N	103° 57' 49.609
12,100.0	90.00	270.02	8,241.0	761.0	-5,141.4	580,742.06	655,047.70	32° 35' 45.493 N	103° 57' 50.778
12,200.0	90.00	270.02	8,241.0	761.0	-5,241.4	580,742.09	654,947.70	32° 35' 45.496 N	103° 57' 51.947
12,300.0	90.00	270.02	8,241.0	761.1	-5,341.4	580,742.12	654,847.70	32° 35' 45.500 N	103° 57' 53.116
12,400.0	90.00	270.02	8,241.0	761.1	-5,441.4	580,742.15	654,747.70	32° 35' 45.504 N	103° 57' 54.285
12,500.0	90.00	270.02	8,241.0	761.1	-5,541.4	580,742.18	654,647.70	32° 35' 45.508 N	103° 57' 55.454
12,600.0	90.00	270.02	8,241.0	761.2	-5,641.4	580,742.21	654,547.70	32° 35' 45.511 N	103° 57' 56.623
12,700.0	90.00	270.02	8,241.0	761.2	-5,741.4	580,742.24	654,447.70	32° 35' 45.515 N	103° 57' 57.791
12,800.0	90.00	270.02	8,241.0	761.2	-5,841.4	580,742.27	654,347.70	32° 35' 45.519 N	103° 57' 58.960 \

Planning Report - Geographic

Database: Compass
Company: NEW MEXICO

Project:

Site: MICHELADA FED COM
Well: MICHELADA 3 FED COM 134H

(SP) EDDY

Wellbore: OWB
Design: PWP0

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well MICHELADA 3 FED COM 134H

GL @ 3225.0usft GL @ 3225.0usft

Grid

13,000.0 90.00 270.02 8,241.0 761.3 6,041.4 \$80,742.33 665,41,770 92*354.55.80 103*68*1.43.00 100.00	Design:	PWP								
Measured Depth Inclination Azimuth Depth (usft) (usf	Planned Survey									
13,000.0 90.00 270.02 8,241.0 761.3 -6,041.4 880,742.33 863,447.70 32° 35° 45.550 N 103° 58° 1.4 13,200.0 90.00 270.02 8,241.0 761.3 -6,241.4 880,742.39 853,447.70 32° 35° 45.550 N 103° 58° 1.4 13,400.0 90.00 270.02 8,241.0 761.4 -6,441.4 880,742.45 853,447.70 32° 35° 45.553 N 103° 58° 1.4 13,800.0 90.00 270.02 8,241.0 761.4 -6,441.4 880,742.45 853,447.70 32° 35° 45.551 N 103° 58° 1.4 13,800.0 90.00 270.02 8,241.0 761.5 -6,641.4 880,742.45 853,447.70 32° 35° 45.551 N 103° 58° 1.4 13,800.0 90.00 270.02 8,241.0 761.5 -6,641.4 880,742.51 853,447.70 32° 35° 45.554 N 103° 58° 1.4 13,800.0 90.00 270.02 8,241.0 761.5 -6,641.4 880,742.51 853,447.70 32° 35° 45.558 N 103° 58° 1.4 13,800.0 90.00 270.02 8,241.0 761.5 -6,641.4 880,742.51 853,447.70 32° 35° 45.558 N 103° 58° 1.4 13,800.0 90.00 270.02 8,241.0 761.5 -6,641.4 880,742.57 853,447.70 32° 35° 45.558 N 103° 58° 1.4 13,800.0 90.00 270.02 8,241.0 761.5 -6,641.4 880,742.57 853,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0 90.00 270.02 8,241.0 761.5 -7,041.4 880,742.63 853,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0 90.00 270.02 8,241.0 761.6 -7,041.4 880,742.63 853,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0 90.00 270.02 8,241.0 761.6 -7,041.4 880,742.69 852,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0 90.00 270.02 8,241.0 761.6 -7,241.4 880,742.69 852,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0 90.00 270.02 8,241.0 761.6 -7,241.4 880,742.69 852,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0 90.00 270.02 8,241.0 761.6 -7,241.4 880,742.69 852,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0 90.00 270.02 8,241.0 761.8 -7,241.4 880,742.69 852,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0 90.00 270.02 8,241.0 761.8 -7,441.4 880,742.69 852,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0 90.00 270.02 8,241.0 761.8 -7,441.4 880,742.89 852,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0 90.00 270.02 8,241.0 761.8 -7,441.4 880,742.89 852,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0 90.00 270.02 8,241.0 761.8 -7,441.4 880,742.89 852,447.70 32° 35° 45.558 N 103° 58° 1.4 14,000.0	Measured Depth			Depth			Northing	Easting	Latitude	Longitude
13,100.0 90.00 270.02 8,241.0 761.3 6,141.4 860,742.36 683,447.70 82°39′45.530 N 103°58′36.313.00.0 90.00 270.02 8,241.0 761.4 6,841.4 860,742.42 683,847.70 82°39′45.533 N 103°58′36.313.00.0 90.00 270.02 8,241.0 761.4 -8,841.4 860,742.42 683,847.70 82°39′45.533 N 103°58′36.313.00.0 90.00 270.02 8,241.0 761.4 -8,841.4 860,742.48 683,847.70 32°39′45.545 N 103°58′16.313.00.0 90.00 270.02 8,241.0 761.5 -8,641.4 860,742.48 683,847.70 32°39′45.545 N 103°58′16.313.00.0 90.00 270.02 8,241.0 761.5 -8,741.4 860,742.54 683,847.70 32°39′45.545 N 103°58′16.313.00.0 90.00 270.02 8,241.0 761.5 -8,741.4 860,742.54 683,847.70 32°39′45.545 N 103°58′16.313.00.0 90.00 270.02 8,241.0 761.5 -8,741.4 860,742.54 683,447.70 32°39′45.555 N 103°58′16.313.00.0 90.00 270.02 8,241.0 761.5 -8,741.4 860,742.54 683,447.70 32°39′45.555 N 103°58′16.313.00.0 90.00 270.02 8,241.0 761.5 -8,741.4 860,742.54 683,447.70 32°39′45.555 N 103°58′16.9 14.00.0 90.00 270.02 8,241.0 761.6 -7,741.4 860,742.56 683,447.70 32°39′45.555 N 103°58′16.9 14.00.0 90.00 270.02 8,241.0 761.6 -7,741.4 860,742.56 853,447.70 32°39′45.555 N 103°58′16.9 14.200.0 90.00 270.02 8,241.0 761.6 -7,741.4 860,742.56 853,447.70 32°39′45.555 N 103°58′16.9 14.200.0 90.00 270.02 8,241.0 761.6 -7,741.4 860,742.56 853,447.70 32°39′45.555 N 103°58′16.9 14.200.0 90.00 270.02 8,241.0 761.6 -7,741.4 860,742.56 853,447.70 32°39′45.555 N 103°58′17.6 14.200.0 90.00 270.02 8,241.0 761.6 -7,741.4 860,742.56 853,447.70 32°39′45.555 N 103°58′17.6 14.200.0 90.00 270.02 8,241.0 761.7 -7,741.4 860,742.56 853,447.70 32°39′45.555 N 103°58′17.6 14.200.0 90.00 270.02 8,241.0 761.8 -7,741.4 860,742.56 852,747.70 32°39′45.555 N 103°58′17.6 14.200.0 90.00 270.02 8,241.0 761.8 -7,741.4 860,742.56 852,747.70 32°39′45.555 N 103°58′17.6 14.200.0 90.00 270.02 8,241.0 761.8 -7,741.4 860,742.56 850,742.75 852,747.70 32°39′45.555 N 103°58′17.6 14.200.0 90.00 270.02 8,241.0 761.8 -7,741.4 860,742.56 850,742.75 852,747.70 32°39′45.555 N 103°58′17.6 14.200.0 90.00 270.02 8,241.0 761.8 -7,741.4 860,742.56 850,742.75 852,7	12,900.0	90.00	270.02	8,241.0	761.2	-5,941.4	580,742.30	654,247.70	32° 35' 45.522 N	103° 58' 0.129 W
13,200.0 90.00 270.02 8,241.0 761.3 -6,241.4 580,742.39 683,947.70 32° 35° 45.537 N 103° 58° 1.6 13.400.0 90.00 270.02 8,241.0 761.4 -6,441.4 580,742.45 683,947.70 32° 35° 45.537 N 103° 58° 1.6 13.500.0 90.00 270.02 8,241.0 761.5 -6,641.4 580,742.45 683,947.70 32° 35° 45.545 N 103° 58° 1.6 13.700.0 90.00 270.02 8,241.0 761.5 -6,641.4 580,742.51 683,947.70 32° 35° 45.545 N 103° 58° 1.6 13.700.0 90.00 270.02 8,241.0 761.5 -6,641.4 580,742.51 683,947.70 32° 35° 45.558 N 103° 58° 1.6 13.800.0 90.00 270.02 8,241.0 761.5 -6,641.4 580,742.57 683,947.70 32° 35° 45.558 N 103° 58° 1.6 13.800.0 90.00 270.02 8,241.0 761.5 -6,641.4 580,742.57 683,947.70 32° 35° 45.558 N 103° 58° 1.6 13.800.0 90.00 270.02 8,241.0 761.5 -6,641.4 580,742.65 683,947.70 32° 35° 45.558 N 103° 58° 1.6 14.000.0 90.00 270.02 8,241.0 761.6 -7,041.4 580,742.63 683,447.70 32° 35° 45.558 N 103° 58° 1.6 14.000.0 90.00 270.02 8,241.0 761.6 -7,041.4 580,742.63 683,447.70 32° 35° 45.558 N 103° 58° 1.4 14.000.0 90.00 270.02 8,241.0 761.6 -7,441.4 580,742.69 682,947.70 32° 35° 45.558 N 103° 58° 1.4 14.000.0 90.00 270.02 8,241.0 761.6 -7,241.4 580,742.69 682,947.70 32° 35° 45.558 N 103° 58° 1.4 14.000.0 90.00 270.02 8,241.0 761.6 -7,241.4 580,742.69 682,947.70 32° 35° 45.578 N 103° 58° 1.4 14.000.0 90.00 270.02 8,241.0 761.7 -7,441.4 580,742.69 682,947.70 32° 35° 45.578 N 103° 58° 1.4 14.000.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.69 682,947.70 32° 35° 45.578 N 103° 58° 1.8 14.000.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.78 682,747.70 32° 35° 45.588 N 103° 58° 1.8 14.000.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.78 682,747.70 32° 35° 45.588 N 103° 58° 1.8 14.000.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.89 682,747.70 32° 35° 45.588 N 103° 58° 1.8 14.000.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.98 682,447.70 32° 35° 45.588 N 103° 58° 1.8 14.000.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.89 682,447.70 32° 35° 45.588 N 103° 58° 1.8 14.000.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.99 682,447.70 32° 35° 45.588 N 103° 58° 1.8 14.000.0	13,000.0	90.00	270.02	8,241.0	761.3	-6,041.4	580,742.33	654,147.70	32° 35′ 45.526 N	103° 58' 1.298 W
13,300.0 90.00 270.02 8,241.0 761.4 -6,341.4 \$50,742.42 \$65,847.70 32 35 45,557 N 102 58 4.6 13,400.0 90.00 270.02 8,241.0 761.5 -6,841.4 \$50,742.46 \$65,847.70 32 35 45,545 N 102 58 7.6 13,500.0 90.00 270.02 8,241.0 761.5 -6,841.4 \$50,742.56 \$65,347.70 32 35 45,545 N 102 58 7.4 13,500.0 90.00 270.02 8,241.0 761.5 -6,841.4 \$50,742.56 \$65,347.70 32 35 45,545 N 102 58 7.4 13,500.0 90.00 270.02 8,241.0 761.5 -6,841.4 \$50,742.56 \$65,347.70 32 35 45,556 N 103 58 14.0 13,500.0 90.00 270.02 8,241.0 761.5 -6,841.4 \$50,742.56 \$63,347.70 32 35 45,556 N 103 58 14.0 14,000.0 90.00 270.02 8,241.0 761.5 -7,041.4 \$50,742.50 \$63,347.70 32 35 45,556 N 103 58 11.8 14,000.0 90.00 270.02 8,241.0 761.6 -7,041.4 \$50,742.50 \$63,347.70 32 35 45,556 N 103 58 11.8 14,000.0 90.00 270.02 8,241.0 761.6 -7,041.4 \$50,742.50 \$63,347.70 32 35 45,556 N 103 58 11.4 14,000.0 90.00 270.02 8,241.0 761.6 -7,041.4 \$50,742.50 \$63,347.70 32 35 45,557 N 103 58 11.4 14,000.0 90.00 270.02 8,241.0 761.6 -7,241.4 \$50,742.50 \$65,247.70 32 35 45,557 N 103 58 11.4 14,000.0 90.00 270.02 8,241.0 761.6 -7,241.4 \$50,742.50 \$62,947.70 32 35 45,557 N 103 58 11.4 14,000.0 90.00 270.02 8,241.0 761.6 -7,241.4 \$50,742.76 \$65,247.70 32 35 45,557 N 103 58 11.4 14,000.0 90.00 270.02 8,241.0 761.6 -7,441.4 \$50,742.76 \$65,247.70 32 35 45,557 N 103 58 11.4 14,000.0 90.00 270.02 8,241.0 761.8 -7,641.4 \$50,742.76 \$65,247.70 32 35 45,557 N 103 58 11.4 14,000.0 90.00 270.02 8,241.0 761.8 -7,641.4 \$50,742.76 \$65,247.70 32 35 45,556 N 103 58 11.8 14,000.0 90.00 270.02 8,241.0 761.8 -7,641.4 \$50,742.76 \$65,247.70 32 35 45,556 N 103 58 11.8 14,000.0 90.00 270.02 8,241.0 761.8 -7,641.4 \$50,742.78 \$65,247.70 32 35 45,556 N 103 58 11.8 14,000.0 90.00 270.02 8,241.0 761.8 -7,641.4 \$50,742.89 \$65,247.70 32 35 45,561 N 103 58 11.8 14,000.0 90.00 270.02 8,241.0 761.8 -7,641.4 \$50,742.89 \$65,247.70 32 35 45,561 N 103 58 11.8 15,000.0 90.00 270.02 8,241.0 761.8 -7,641.4 \$50,742.89 \$65,247.70 32 35 45,561 N 103 58 11.8 15,000.0 90.00 270.02 8,241.0 761.8 -7,641.4 \$50,742.89 \$65,247.70 32 35 45,	13,100.0	90.00	270.02	8,241.0	761.3	-6,141.4	580,742.36	654,047.70	32° 35′ 45.530 N	103° 58' 2.467 W
13,800 90,00 270,02 8,2410 761,4 -6,641,4 580,742,45 653,747,70 32 35 45,654 N 103 56 71,71 13,600 90,00 270,02 8,2410 761,5 -6,641,4 580,742,51 633,647,70 32 35 45,654 N 103 56 71,71 13,600 90,00 270,02 8,2410 761,5 -6,641,4 580,742,51 633,647,70 32 35 45,554 N 103 56 71,6 13,800 90,00 270,02 8,2410 761,5 -6,641,4 580,742,5 N 63,247,5 N 32 35 45,554 N 103 56 71,8 N 13,8 N 14,0	13,200.0	90.00	270.02	8,241.0	761.3	-6,241.4	580,742.39	653,947.70	32° 35′ 45.533 N	103° 58' 3.636 W
13,500.0 90.00 970.02 8,241.0 761.5 -6,641.4 580,742.5 63,547.7 32° 35° 45,548 N 103° 58° 13.6 13700.0 90.00 270.02 8,241.0 761.5 -6,641.4 580,742.5 64 633,447.7 32° 35° 45,548 N 103° 58° 34.6 13.8 00.0 90.0 270.02 8,241.0 761.5 -6,841.4 580,742.5 66 63,247.70 32° 35° 45,568 N 103° 58° 14.8 14,000.0 90.00 270.02 8,241.0 761.6 -7,641.4 580,742.5 65 63,247.70 32° 35° 45,569 N 103° 58° 14.8 14,000.0 90.00 270.02 8,241.0 761.6 -7,641.4 580,742.6 65,347.70 32° 35° 45,569 N 103° 58° 18.8 14,000.0 90.00 270.02 8,241.0 761.6 -7,141.4 580,742.8 653,447.70 32° 35° 45,569 N 103° 58° 18.8 14,000.0 90.00 270.02 8,241.0 761.6 -7,141.4 580,742.8 653,447.70 32° 35° 45,569 N 103° 58° 18.8 14,000.0 90.00 270.02 8,241.0 761.6 -7,141.4 580,742.8 652,477.0 32° 35° 45,570 N 103° 58° 14.8 14,000.0 90.00 270.02 8,241.0 761.7 -7,341.4 580,742.8 652,477.0 32° 35° 45,570 N 103° 58° 14.8 14,000.0 90.00 270.02 8,241.0 761.7 -7,341.4 580,742.7 662,747.70 32° 35° 45,570 N 103° 58° 14.8 14,000.0 90.00 270.02 8,241.0 761.7 -7,541.4 580,742.7 662,747.70 32° 35° 45,570 N 103° 58° 17.6 14,000.0 90.00 270.02 8,241.0 761.8 -7,741.4 580,742.7 662,747.70 32° 35° 45,570 N 103° 58° 17.6 14,000.0 90.00 270.02 8,241.0 761.8 -7,741.4 580,742.8 652,477.70 32° 35° 45,558 N 103° 58° 17.6 14,000.0 90.00 270.02 8,241.0 761.8 -7,741.4 580,742.8 652,477.7 32° 35° 45,558 N 103° 58° 17.6 14,000.0 90.00 270.02 8,241.0 761.8 -7,741.4 580,742.8 652,477.7 32° 35° 45,558 N 103° 58° 17.6 14,000.0 90.00 270.02 8,241.0 761.8 -7,741.4 580,742.8 652,477.7 32° 35° 45,558 N 103° 58° 17.6 14,000.0 90.00 270.02 8,241.0 761.8 -7,741.4 580,742.8 652,477.7 32° 35° 45,558 N 103° 58° 17.6 14,000.0 90.00 270.02 8,241.0 761.9 -8,141.4 580,742.8 652,477.7 32° 35° 45,558 N 103° 58° 12.3 15,000.0 90.00 270.02 8,241.0 761.9 -8,141.4 580,742.9 652,447.70 32° 35° 45,580 N 103° 58° 23.5 15,000.0 90.00 270.02 8,241.0 762.9 -8,441.4 580,742.9 652,447.7 32° 35° 45,580 N 103° 58° 23.5 15,000.0 90.00 270.02 8,241.0 762.9 -8,441.4 580,742.9 652,447.7 32° 35° 45,658 N 103° 58° 23.5 15,000.0 90.00 2	13,300.0	90.00	270.02	8,241.0	761.4	-6,341.4	580,742.42	653,847.70		103° 58' 4.805 W
13,000 90,00 270,02 8,241,0 761,5 -6,641,4 580,742,51 635,547,70 32° 35° 45,558 N 103° 58° 42. 13,000 90,00 270,02 8,241,0 761,5 -6,841,4 580,742,57 633,347,70 32° 35° 45,558 N 103° 58° 10. 13,000 90,00 270,02 8,241,0 761,5 -6,841,4 580,742,67 633,347,70 32° 35° 45,558 N 103° 58° 10. 14,000 90,00 270,02 8,241,0 761,6 -7,141,4 580,742,68 63,247,70 32° 35° 45,558 N 103° 58° 12.9 14,100 90,00 270,02 8,241,0 761,6 -7,141,4 580,742,68 63,247,70 32° 35° 45,558 N 103° 58° 12.9 14,100 90,00 270,02 8,241,0 761,6 -7,741,4 580,742,68 65,247,70 32° 35° 45,558 N 103° 58° 13.9 14,300 90,00 270,02 8,241,0 761,7 -7,341,4 580,742,69 65,247,70 32° 35° 45,558 N 103° 58° 13.9 14,300 90,00 270,02 8,241,0 761,7 -7,341,4 580,742,76 652,747,70 32° 35° 45,558 N 103° 58° 13.8 14,300 90,00 270,02 8,241,0 761,8 -7,641,4 580,742,76 652,747,70 32° 35° 45,558 N 103° 58° 13.8 14,300 90,00 270,02 8,241,0 761,8 -7,641,4 580,742,76 652,747,70 32° 35° 45,558 N 103° 58° 13.8 14,600,0 90,00 270,02 8,241,0 761,8 -7,641,4 580,742,76 652,747,70 32° 35° 45,558 N 103° 58° 13.8 14,600,0 90,00 270,02 8,241,0 761,8 -7,641,4 580,742,76 652,747,70 32° 35° 45,568 N 103° 58° 13.8 14,800,0 90,00 270,02 8,241,0 761,8 -7,841,4 580,742,78 652,647,70 32° 35° 45,568 N 103° 58° 13.8 14,800,0 90,00 270,02 8,241,0 761,8 -7,841,4 580,742,86 652,347,70 32° 35° 45,569 N 103° 58° 23.8 14,900,0 90,00 270,02 8,241,0 761,8 -7,841,4 580,742,86 652,347,70 32° 35° 45,569 N 103° 58° 23.8 15,500,0 90,00 270,02 8,241,0 761,8 -7,841,4 580,742,86 652,347,70 32° 35° 45,569 N 103° 58° 23.8 15,500,0 90,00 270,02 8,241,0 761,8 -7,841,4 580,742,86 652,347,70 32° 35° 45,569 N 103° 58° 23.8 15,500,0 90,00 270,02 8,241,0 761,8 -7,841,4 580,742,86 652,347,70 32° 35° 45,569 N 103° 58° 23.8 15,500,0 90,00 270,02 8,241,0 761,8 -7,841,4 580,742,86 652,347,70 32° 35° 45,569 N 103° 58° 23.8 15,500,0 90,00 270,02 8,241,0 761,8 -7,841,4 580,742,86 652,347,70 32° 35° 45,569 N 103° 58° 23.8 15,500,0 90,00 270,02 8,241,0 762,0 -8,841,4 580,742,96 652,447,70 32° 35° 45,569 N 103° 58°	13,400.0	90.00	270.02	8,241.0	761.4	-6,441.4	580,742.45	653,747.70	32° 35′ 45.541 N	103° 58' 5.974 W
13,700.0 90.00 270.02 8,241.0 761.5 -6,741.4 580.742.54 653.447.70 32° 35′ 45.552.N 103° 58′ 24.6 13.000.0 90.00 270.02 8,241.0 761.5 -6,841.4 580.742.60 653.247.70 32° 35′ 45.558.N 103° 58′ 12.6 14.1 4.000.0 90.00 270.02 8,241.0 761.6 -7,741.4 580.742.66 653.047.70 32° 35′ 45.558.N 103° 58′ 12.6 14.1 4.000.0 90.00 270.02 8,241.0 761.6 -7,741.4 580.742.66 653.047.70 32° 35′ 45.558.N 103° 58′ 12.6 14.1 4.000.0 90.00 270.02 8,241.0 761.6 -7,241.4 580.742.66 653.047.70 32° 35′ 45.558 N 103° 58′ 12.6 14.1 4.000.0 90.00 270.02 8,241.0 761.6 -7,241.4 580.742.66 653.047.70 32° 35′ 45.574 N 103° 58′ 12.6 14.1 4.000.0 90.00 270.02 8,241.0 761.7 -7,341.4 580.742.72 582.847.70 32° 35′ 45.574 N 103° 58′ 14.5 14.4 4.000.0 90.00 270.02 8,241.0 761.7 -7,341.4 580.742.72 582.847.70 32° 35′ 45.574 N 103° 58′ 14.5 14.4 580.742.73 580.742.73 580.742.73 580.742.73 580.742.73 580.742.73 580.742.74 5		90.00		8,241.0	761.4	-6,541.4		653,647.70		103° 58' 7.143 W
13,800.0 90.00 270.02 8,241.0 761.5 -6,841.4 580.742.57 653.347.70 32° 35′ 45.565 N 103° 58′ 11.6 14,000.0 90.00 270.02 8,241.0 761.6 -7,041.4 580.742.83 653.447.70 32° 35′ 45.565 N 103° 58′ 12.9 14,100.0 90.00 270.02 8,241.0 761.6 -7,041.4 580.742.89 652.947.70 32° 35′ 45.565 N 103° 58′ 12.9 14,100.0 90.00 270.02 8,241.0 761.6 -7,241.4 580.742.89 652.947.70 32° 35′ 45.567 N 103° 58′ 12.9 14,100.0 90.00 270.02 8,241.0 761.6 -7,241.4 580.742.89 652.947.70 32° 35′ 45.576 N 103° 58′ 13.1 14,400.0 90.00 270.02 8,241.0 761.7 -7,441.4 580.742.89 652.947.70 32° 35′ 45.576 N 103° 58′ 13.6 14,400.0 90.00 270.02 8,241.0 761.7 -7,441.4 580.742.75 652.747.70 32° 35′ 45.576 N 103° 58′ 13.6 14,600.0 90.00 270.02 8,241.0 761.8 -7,641.4 580.742.75 652.747.70 32° 35′ 45.587 N 103° 58′ 13.6 14,600.0 90.00 270.02 8,241.0 761.8 -7,641.4 580.742.81 652.647.70 32° 35′ 45.586 N 103° 58′ 12.9 14,700.0 90.00 270.02 8,241.0 761.8 -7,741.4 580.742.81 652.547.70 32° 35′ 45.586 N 103° 58′ 20.0 14,700.0 90.00 270.02 8,241.0 761.8 -7,741.4 580.742.81 652.547.70 32° 35′ 45.586 N 103° 58′ 20.0 14,700.0 90.00 270.02 8,241.0 761.8 -7,641.4 580.742.81 652.547.70 32° 35′ 45.589 N 103° 58′ 20.0 14,800.0 90.00 270.02 8,241.0 761.8 -7,641.4 580.742.81 652.547.70 32° 35′ 45.589 N 103° 58′ 20.0 14,800.0 90.00 270.02 8,241.0 761.8 -7,641.4 580.742.92 652.447.70 32° 35′ 45.589 N 103° 58′ 20.0 15,500.0 90.00 270.02 8,241.0 761.9 8,041.4 580.742.92 652.447.70 32° 35′ 45.589 N 103° 58′ 20.0 15,500.0 90.00 270.02 8,241.0 761.9 8,041.4 580.742.92 652.447.70 32° 35′ 45.589 N 103° 58′ 24.0 15,500.0 90.00 270.02 8,241.0 761.9 8,041.4 580.742.92 652.447.70 32° 35′ 45.580 N 103° 58′ 24.0 15,500.0 90.00 270.02 8,241.0 762.0 8,341.4 580.743.91 651.447.70 32° 35′ 45.580 N 103° 58′ 24.0 15,500.0 90.00 270.02 8,241.0 762.0 8,341.4 580.743.91 651.447.70 32° 35′ 45.580 N 103° 58′ 24.0 15,500.0 90.00 270.02 8,241.0 762.0 8,541.4 580.743.91 651.447.70 32° 35′ 45.580 N 103° 58′ 24.0 15,500.0 90.00 270.02 8,241.0 762.0 8,541.4 580.743.1 651.447.70 32° 35′ 45.580 N 103° 58′ 3						,	,			103° 58' 8.312 W
13,000.0 90.00 270.02 8,241.0 761.5 -6,941.4 580.742.60 653.447.70 32° 35′ 45.559 N 103° 58′ 11.8 14.100.0 90.00 270.02 8,241.0 761.6 -7,141.4 580.742.66 653.047.70 32° 35′ 45.569 N 103° 58′ 12.9 14.100.0 90.00 270.02 8,241.0 761.6 -7,241.4 580.742.66 653.047.70 32° 35′ 45.570 N 103° 58′ 12.9 14.400.0 90.00 270.02 8,241.0 761.7 -7,341.4 580.742.72 652.847.70 32° 35′ 45.570 N 103° 58′ 12.9 14.400.0 90.00 270.02 8,241.0 761.7 -7,341.4 580.742.72 652.847.70 32° 35′ 45.570 N 103° 58′ 15.8 14.1 4.00.0 90.00 270.02 8,241.0 761.7 -7,341.4 580.742.72 652.847.70 32° 35′ 45.570 N 103° 58′ 15.8 14.1 4.00.0 90.00 270.02 8,241.0 761.7 -7,541.4 580.742.78 652.647.70 32° 35′ 45.580 N 103° 58′ 15.8 14.1 4.00.0 90.00 270.02 8,241.0 761.8 -7,641.4 580.742.78 652.647.70 32° 35′ 45.580 N 103° 58′ 12.8 14.1 4.00.0 90.00 270.02 8,241.0 761.8 -7,641.4 580.742.84 652.447.70 32° 35′ 45.580 N 103° 58′ 12.1 14.800.0 90.00 270.02 8,241.0 761.8 -7,641.4 580.742.84 652.447.70 32° 35′ 45.580 N 103° 58′ 12.1 14.800.0 90.00 270.02 8,241.0 761.8 -7,641.4 580.742.84 652.447.70 32° 35′ 45.590 N 103° 58′ 21.8 14.1 4.1 4.1 4.1 4.1 4.1 4.1 4.1 4.1 4.										103° 58' 9.481 W
14,000.0 90.00 270.02 8,241.0 761.6 -7,041.4 580,742.63 683,147.70 32° 35° 45.568 N 103° 58° 12.9 14,000.0 90.00 270.02 8,241.0 761.6 -7,241.4 580,742.66 683,047.70 32° 35° 45.567 N 103° 58° 14.1 14,000.0 90.00 270.02 8,241.0 761.7 -7,341.4 580,742.69 683,047.70 32° 35° 45.574 N 103° 58° 16.1 14,000.0 90.00 270.02 8,241.0 761.7 -7,341.4 580,742.75 682,847.70 32° 35° 45.574 N 103° 58° 16.8 14,000.0 90.00 270.02 8,241.0 761.7 -7,541.4 580,742.75 682,847.70 32° 35° 45.578 N 103° 58° 16.8 14,000.0 90.00 270.02 8,241.0 761.7 -7,541.4 580,742.78 682,847.70 32° 35° 45.587 N 103° 58° 17.6 14,000.0 90.00 270.02 8,241.0 761.8 -7,541.4 580,742.78 682,847.70 32° 35° 45.586 N 103° 58° 12.6 14,000.0 90.00 270.02 8,241.0 761.8 -7,541.4 580,742.81 682,847.70 32° 35° 45.586 N 103° 58° 12.0 14,700.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.81 682,447.70 32° 35° 45.589 N 103° 58° 22.0 14,000.0 90.00 270.02 8,241.0 761.8 -7,941.4 580,742.86 682,447.70 32° 35° 45.590 N 103° 58° 22.3 14,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.89 682,247.70 32° 35° 45.590 N 103° 58° 22.8 15,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.95 682,047.70 32° 35° 45.590 N 103° 58° 22.8 15,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.95 682,047.70 32° 35° 45.600 N 103° 58° 22.6 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,742.95 682,047.70 32° 35° 45.600 N 103° 58° 22.6 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.01 661,847.70 32° 35° 45.610 N 103° 58° 23.6 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.01 661,847.70 32° 35° 45.610 N 103° 58° 23.6 15,000.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.01 661,847.70 32° 35° 45.610 N 103° 58° 23.6 15,000.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.01 661,847.70 32° 35° 45.610 N 103° 58° 33.6 15,000.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.10 651,847.70 32° 35° 45.610 N 103° 58° 33.6 15,000.0 90.00 270.02 8,241.0 762.1 -8,641.4 580,743.30 651,847.70 32° 35° 45.610 N 103° 58° 33.6 15,000.0 90.00 270.02 8,241.0 762.1 -8,641.4 580,743.30 651,847.70 32° 35° 45.650 N 10										103° 58' 10.650 W
14,100.0 90.00 270.02 8,241.0 761.6 -7,141.4 580,742.69 653,047.70 32° 35° 45.567 N 103° 58° 18.1 14,300.0 90.00 270.02 8,241.0 761.7 -7,341.4 580,742.75 652,847.70 32° 35° 45.570 N 103° 58° 16.4 14,400.0 90.00 270.02 8,241.0 761.7 -7,341.4 580,742.75 652,847.70 32° 35° 45.576 N 103° 58° 16.4 14,400.0 90.00 270.02 8,241.0 761.7 -7,541.4 580,742.75 652,747.70 32° 35° 45.576 N 103° 58° 16.4 14,600.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.78 652,847.70 32° 35° 45.588 N 103° 58° 18.8 14,600.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.81 652,647.70 32° 35° 45.589 N 103° 58° 12.8 14,600.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.81 652,647.70 32° 35° 45.598 N 103° 58° 12.1 14,800.0 90.00 270.02 8,241.0 761.8 -7,841.4 580,742.81 652,647.70 32° 35° 45.598 N 103° 58° 22.1 14,800.0 90.00 270.02 8,241.0 761.8 -7,841.4 580,742.86 652,447.70 32° 35° 45.598 N 103° 58° 22.1 15,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.98 652,447.70 32° 35° 45.599 N 103° 58° 22.5 15,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.92 652,447.70 32° 35° 45.600 N 103° 58° 22.5 15,000.0 90.00 270.02 8,241.0 761.9 -8,241.4 580,742.92 652,447.70 32° 35° 45.600 N 103° 58° 22.5 15,000.0 90.00 270.02 8,241.0 761.9 -8,241.4 580,742.92 652,447.70 32° 35° 45.600 N 103° 58° 22.5 15,000.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,743.01 651,847.70 32° 35° 45.600 N 103° 58° 22.5 15,000.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.01 651,847.70 32° 35° 45.600 N 103° 58° 23.5 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.01 651,847.70 32° 35° 45.614 N 103° 58° 23.5 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.01 651,847.70 32° 35° 45.614 N 103° 58° 23.5 15,000.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.10 651,847.70 32° 35° 45.614 N 103° 58° 23.5 15,000.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.10 651,847.70 32° 35° 45.614 N 103° 58° 31.5 15,000.0 90.00 270.02 8,241.0 762.2 -9,414.4 580,743.26 651,447.70 32° 35° 45.620 N 103° 58° 31.5 15,000.0 90.00 270.02 8,241.0 762.2 -9,414.4 580,743.26 651,447.70 32° 35° 45.620 N 10										103° 58' 11.819 W
14,200.0 90.00 270.02 8,241.0 761.6 -7,241.4 580,742.96 652,947.70 32° 35° 45,570 N 103° 58° 15.6 14.400.0 90.00 270.02 8,241.0 761.7 -7,441.4 580,742.75 662,847.70 32° 35° 45,578 N 103° 58° 15.6 14.400.0 90.00 270.02 8,241.0 761.7 -7,441.4 580,742.75 662,847.70 32° 35° 45,578 N 103° 58° 17.6 14.500.0 90.00 270.02 8,241.0 761.7 -7,441.4 580,742.78 652,647.70 32° 35° 45,581 N 103° 58° 17.6 14.500.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.78 652,647.70 32° 35° 45,585 N 103° 58° 12.6 14.700.0 90.00 270.02 8,241.0 761.8 -7,741.4 580,742.81 652,447.70 32° 35° 45,589 N 103° 58° 12.6 14.700.0 90.00 270.02 8,241.0 761.8 -7,741.4 580,742.84 652,447.70 32° 35° 45,589 N 103° 58° 12.6 14.900.0 90.00 270.02 8,241.0 761.8 -7,941.4 580,742.86 652,447.70 32° 35° 45,590 N 103° 58° 22.6 15.000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.89 652,247.70 32° 35° 45,590 N 103° 58° 22.6 15.000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.95 662,047.70 32° 35° 45,600 N 103° 58° 22.8 15.200.0 90.00 270.02 8,241.0 761.9 -8,241.4 580,742.95 662,047.70 32° 35° 45,600 N 103° 58° 22.6 15.000.0 90.00 270.02 8,241.0 761.9 -8,241.4 580,742.98 651,947.70 32° 35° 45,600 N 103° 58° 22.6 15.000.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,742.98 651,947.70 32° 35° 45,600 N 103° 58° 22.6 15.000.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,743.01 651,477.0 32° 35° 45,600 N 103° 58° 22.6 15.600.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.01 651,477.0 32° 35° 45,610 N 103° 58° 23.6 15.600.0 90.00 270.02 8,241.0 762.0 -8,841.4 580,743.10 651,477.0 32° 35° 45,610 N 103° 58° 32.6 15.600.0 90.00 270.02 8,241.0 762.0 -8,841.4 580,743.10 651,477.0 32° 35° 45,610 N 103° 58° 32.6 15,600.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.10 651,477.0 32° 35° 45,610 N 103° 58° 33.6 15,600.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.10 651,477.0 32° 35° 45,620 N 103° 58° 33.6 15,600.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.13 651,477.0 32° 35° 45,620 N 103° 58° 33.6 15,600.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.3 651,477.0 32° 35° 45,620 N 103° 58° 32										103° 58' 12.988 W
14,300 0 90.00 270.02 8,241.0 761.7 -7,341.4 580,742.75 652,847.70 32° 35′ 45,574 N 103° 58′ 17.6 14,000 90.00 270.02 8,241.0 761.7 -7,441.4 580,742.75 652,747.70 32° 35′ 45,574 N 103° 58′ 17.6 14,000 90.00 270.02 8,241.0 761.8 -7,541.4 580,742.75 652,647.70 32° 35′ 45,555 N 103° 58′ 17.6 14,000 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.81 652,547.70 32° 35′ 45,555 N 103° 58′ 20.0 14,700 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.81 652,547.70 32° 35′ 45,555 N 103° 58′ 20.0 14,700 90.00 270.02 8,241.0 761.8 -7,841.4 580,742.86 652,347.70 32° 35′ 45,550 N 103° 58′ 21.0 14,800.0 90.00 270.02 8,241.0 761.8 -7,941.4 580,742.86 652,347.70 32° 35′ 45,550 N 103° 58′ 21.0 15,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.92 652,147.70 32° 35′ 45,500 N 103° 58′ 24.6 15,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.95 652,047.70 32° 35′ 45,600 N 103° 58′ 24.6 15,000.0 90.00 270.02 8,241.0 761.9 -8,141.4 580,742.95 652,047.70 32° 35′ 45,600 N 103° 58′ 24.6 15,000.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,743.91 651,847.70 32° 35′ 45,600 N 103° 58′ 24.0 15,000.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,743.01 651,847.70 32° 35′ 45,610 N 103° 58′ 24.0 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.01 651,847.70 32° 35′ 45,610 N 103° 58′ 24.0 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35′ 45,610 N 103° 58′ 24.0 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35′ 45,610 N 103° 58′ 24.0 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35′ 45,650 N 103° 58′ 30.5 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.10 651,547.70 32° 35′ 45,600 N 103° 58′ 30.5 15,000.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.10 651,547.70 32° 35′ 45,600 N 103° 58′ 30.5 15,000.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.10 651,547.70 32° 35′ 45,600 N 103° 58′ 30.5 15,000.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.10 651,547.70 32° 35′ 45,600 N 103° 58′ 30.5 15,000.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.31 651,447.70 32° 35′ 45,600 N 103° 58′ 30.										103° 58' 14.157 W
14,400.0 90.00 270.02 8,241.0 761.7 -7,441.4 580,742.75 652,747.70 32° 35′ 45,578 N 103° 58′ 18.6 14,600.0 90.00 270.02 8,241.0 761.8 -7,541.4 580,742.78 652,647.70 32° 35′ 45,585 N 103° 58′ 18.6 14,600.0 90.00 270.02 8,241.0 761.8 -7,541.4 580,742.81 652,547.70 32° 35′ 45,585 N 103° 58′ 20.0 14,700.0 90.00 270.02 8,241.0 761.8 -7,541.4 580,742.84 652,447.70 32° 35′ 45,585 N 103° 58′ 22.3 14,900.0 90.00 270.02 8,241.0 761.8 -7,841.4 580,742.84 652,447.70 32° 35′ 45,589 N 103° 58′ 22.3 14,900.0 90.00 270.02 8,241.0 761.8 -7,841.4 580,742.86 652,447.70 32° 35′ 45,596 N 103° 58′ 22.3 14,900.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.96 652,247.70 32° 35′ 45,596 N 103° 58′ 22.3 14,900.0 90.00 270.02 8,241.0 761.9 -8,141.4 580,742.96 652,447.70 32° 35′ 45,506 N 103° 58′ 22.5 15,500.0 90.00 270.02 8,241.0 761.9 -8,141.4 580,742.95 652,047.70 32° 35′ 45,500 N 103° 58′ 22.5 15,500.0 90.00 270.02 8,241.0 761.9 -8,341.4 580,742.95 652,047.70 32° 35′ 45,500 N 103° 58′ 24.1 15,400.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,742.98 651,947.70 32° 35′ 45,610 N 103° 58′ 22.5 15,500.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.01 651,847.70 32° 35′ 45,610 N 103° 58′ 22.3 15,500.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.01 651,847.70 32° 35′ 45,610 N 103° 58′ 22.3 15,500.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.10 651,847.70 32° 35′ 45,610 N 103° 58′ 23.5 15,500.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.10 651,847.70 32° 35′ 45,610 N 103° 58′ 31.6 15,500.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.13 651,447.70 32° 35′ 45,620 N 103° 58′ 31.6 15,500.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.13 651,447.70 32° 35′ 45,620 N 103° 58′ 33.6 15,600 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.13 651,447.70 32° 35′ 45,620 N 103° 58′ 33.6 15,600 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.12 651,447.70 32° 35′ 45,660 N 103° 58′ 33.6 16,000 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.35 651,447.70 32° 35′ 45,660 N 103° 58′ 33.6 16,000 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.35 651,447.70 32° 35′ 45,660 N 103° 58′ 4								,-		103° 58' 15.326 W
14,500.0 90.00 270.02 8,241.0 761.7 -7,541.4 580,742.78 652,647.70 32° 35′ 45,581 N 103° 58′ 12.8 14,600.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.81 652,547.70 32° 35′ 45,585 N 103° 58′ 20.0 14,700.0 90.00 270.02 8,241.0 761.8 -7,641.4 580,742.86 652,447.70 32° 35′ 45,585 N 103° 58′ 21.1 14,800.0 90.00 270.02 8,241.0 761.8 -7,841.4 580,742.86 652,347.70 32° 35′ 45,596 N 103° 58′ 22.3 14,900.0 90.00 270.02 8,241.0 761.8 -7,941.4 580,742.86 652,347.70 32° 35′ 45,596 N 103° 58′ 22.3 15,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.92 652,147.70 32° 35′ 45,600 N 103° 58′ 22.3 15,000.0 90.00 270.02 8,241.0 761.9 -8,141.4 580,742.92 652,147.70 32° 35′ 45,600 N 103° 58′ 22.5 15,000.0 90.00 270.02 8,241.0 761.9 -8,241.4 580,742.99 652,047.70 32° 35′ 45,600 N 103° 58′ 22.6 15,100.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,742.98 652,047.70 32° 35′ 45,600 N 103° 58′ 22.8 15,500.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,743.01 651,847.70 32° 35′ 45,610 N 103° 58′ 22.8 15,500.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.01 651,647.70 32° 35′ 45,614 N 103° 58′ 28.1 15,500.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35′ 45,614 N 103° 58′ 28.1 15,500.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35′ 45,614 N 103° 58′ 28.1 15,500.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35′ 45,614 N 103° 58′ 30.5 15,500.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35′ 45,625 N 103° 58′ 30.5 15,500.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.13 651,447.70 32° 35′ 45,625 N 103° 58′ 33.5 16,000.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.13 651,447.70 32° 35′ 45,625 N 103° 58′ 33.5 16,000.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.26 651,447.70 32° 35′ 45,636 N 103° 58′ 33.5 16,000.0 90.00 270.02 8,241.0 762.2 -9,941.4 580,743.26 651,447.70 32° 35′ 45,636 N 103° 58′ 33.5 16,000.0 90.00 270.02 8,241.0 762.2 -9,941.4 580,743.26 650,447.70 32° 35′ 45,636 N 103° 58′ 33.5 16,000.0 90.00 270.02 8,241.0 762.5 -10,441.4				,						103° 58' 16.494 W
14,600 0 90.00 270.02 8,241.0 761.8 7,641.4 580,742.81 652,547.70 32° 35′ 45.865 N 103° 58′ 20.0 14,700.0 90.00 270.02 8,241.0 761.8 7,841.4 580,742.84 652,447.70 32° 35′ 45.569 N 103° 58′ 20.1 14,800.0 90.00 270.02 8,241.0 761.8 7,841.4 580,742.89 652,247.70 32° 35′ 45.569 N 103° 58′ 22.3 14,900.0 90.00 270.02 8,241.0 761.8 7,941.4 580,742.89 652,247.70 32° 35′ 45.560 N 103° 58′ 22.3 15,500.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.95 652,047.70 32° 35′ 45.600 N 103° 58′ 22.5 15,500.0 90.00 270.02 8,241.0 761.9 -8,141.4 580,742.95 652,047.70 32° 35′ 45.601 N 103° 58′ 22.5 15,500.0 90.00 270.02 8,241.0 761.9 -8,241.4 580,742.95 652,047.70 32° 35′ 45.601 N 103° 58′ 22.5 15,500.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,742.95 652,047.70 32° 35′ 45.601 N 103° 58′ 22.5 15,500.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,742.95 652,047.70 32° 35′ 45.610 N 103° 58′ 22.5 15,500.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.04 651,747.70 32° 35′ 45.610 N 103° 58′ 22.5 15,500.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.04 651,747.70 32° 35′ 45.614 N 103° 58′ 23.5 15,500.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.10 651,547.70 32° 35′ 45.625 N 103° 58′ 23.8 15,500.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.10 651,547.70 32° 35′ 45.625 N 103° 58′ 32.6 15,500.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35′ 45.625 N 103° 58′ 32.6 15,500.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35′ 45.625 N 103° 58′ 32.6 15,500.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.19 651,247.70 32° 35′ 45.625 N 103° 58′ 33.6 15,500.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.19 651,247.70 32° 35′ 45.625 N 103° 58′ 33.6 15,000.0 90.00 270.02 8,241.0 762.2 -9,414.4 580,743.19 651,247.70 32° 35′ 45.625 N 103° 58′ 33.6 16,000.0 90.00 270.02 8,241.0 762.2 -9,414.4 580,743.25 651,047.70 32° 35′ 45.625 N 103° 58′ 33.6 16,000.0 90.00 270.02 8,241.0 762.2 -9,441.4 580,743.25 651,047.70 32° 35′ 45.630 N 103° 58′ 33.5 16,000.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.25 651,447.70 32° 35′ 45.630 N 103° 5										103° 58' 17.663 W
14,700 0 90.00 270.02 8,241.0 761.8 -7,741.4 580,742.86 652,447.70 32° 35′ 45.589 N 103° 58′ 21.1 14,900.0 90.00 270.02 8,241.0 761.8 -7,841.4 580,742.86 652,247.70 32° 35′ 45.596 N 103° 58′ 22.3 14,900.0 90.00 270.02 8,241.0 761.8 -7,941.4 580,742.99 652,147.70 32° 35′ 45.596 N 103° 58′ 22.3 15,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.99 652,147.70 32° 35′ 45.600 N 103° 58′ 24.5 15,100.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.99 652,147.70 32° 35′ 45.600 N 103° 58′ 24.5 15,200.0 90.00 270.02 8,241.0 761.9 -8,241.4 580,742.99 651,947.70 32° 35′ 45.601 N 103° 58′ 24.5 15,200.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,742.99 651,947.70 32° 35′ 45.610 N 103° 58′ 24.5 15,400.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,743.01 651,447.70 32° 35′ 45.610 N 103° 58′ 23.5 15,600.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,743.01 651,447.70 32° 35′ 45.614 N 103° 58′ 23.5 15,600.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35′ 45.614 N 103° 58′ 23.5 15,600.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35′ 45.618 N 103° 58′ 33.6 15,700.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35′ 45.625 N 103° 58′ 32.8 15,800.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.13 651,447.70 32° 35′ 45.625 N 103° 58′ 32.8 15,800.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.13 651,447.70 32° 35′ 45.625 N 103° 58′ 33.6 16,100.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.13 651,447.70 32° 35′ 45.636 N 103° 58′ 33.5 16,000.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.13 651,447.70 32° 35′ 45.636 N 103° 58′ 33.5 16,000.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.25 651,147.70 32° 35′ 45.636 N 103° 58′ 33.5 16,000.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.31 650,447.70 32° 35′ 45.636 N 103° 58′ 33.5 16,000.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.34 650,447.70 32° 35′ 45.665 N 103° 58′ 35.5 16,000.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.34 650,447.70 32° 35′ 45.666 N 103° 58′ 35.5 16,000.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.34 650,447.70 32° 35′ 45.667 N 10										103° 58' 18.832 W
14,800.0 90.00 270.02 8,241.0 761.8 -7,841.4 580,742.86 652,347.70 32° 35° 45.592 N 103° 58° 23.5 15,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.89 652,447.70 32° 35° 45.596 N 103° 58° 23.5 15,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.92 652,147.70 32° 35° 45.600 N 103° 58° 23.6 15,000.0 90.00 270.02 8,241.0 761.9 -8,141.4 580,742.95 652,047.70 32° 35° 45.600 N 103° 58° 23.6 15,000.0 90.00 270.02 8,241.0 761.9 -8,241.4 580,742.95 652,047.70 32° 35° 45.600 N 103° 58° 23.6 15,000.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,743.01 651,847.70 32° 35° 45.610 N 103° 58° 23.6 15,000.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.01 651,847.70 32° 35° 45.610 N 103° 58° 23.6 15,000.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.01 651,847.70 32° 35° 45.618 N 103° 58° 30.5 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.01 651,647.70 32° 35° 45.618 N 103° 58° 30.5 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.10 651,547.70 32° 35° 45.621 N 103° 58° 30.5 15,000.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.10 651,547.70 32° 35° 45.621 N 103° 58° 33.5 15,000.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.10 651,547.70 32° 35° 45.622 N 103° 58° 33.5 15,000.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.10 651,547.70 32° 35° 45.628 N 103° 58° 33.5 16,000.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.10 651,477.70 32° 35° 45.628 N 103° 58° 33.5 16,000.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.10 651,477.70 32° 35° 45.630 N 103° 58° 33.6 16,000.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.10 651,477.70 32° 35° 45.647 N 103° 58° 33.6 16,000.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.25 651,477.0 32° 35° 45.647 N 103° 58° 38.8 16,000.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.26 651,477.0 32° 35° 45.668 N 103° 58° 36.8 16,000.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.26 651,477.0 32° 35° 45.668 N 103° 58° 36.8 16,000.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.26 651,477.0 32° 35° 45.668 N 103° 58° 36.8 16,000.0 90.00 270.02 8,241.0 762.5 -10,441.4 580,743.26 651,477.0 32° 35° 45.668 N 103° 5										103° 58' 20.001 W
14,900.0 90.00 270.02 8,241.0 761.8 -7,941.4 580,742.89 652,247.70 32° 35° 45.596 N 103° 58° 23.6 15,000.0 90.00 270.02 8,241.0 761.9 -8,141.4 580,742.92 652,147.70 32° 35° 45.600 N 103° 58° 24.6 15,100.0 90.00 270.02 8,241.0 761.9 -8,141.4 580,742.93 652,047.70 32° 35° 45.600 N 103° 58° 25.8 15,200.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,742.98 651,947.70 32° 35° 45.600 N 103° 58° 25.8 15,200.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,742.98 651,947.70 32° 35° 45.600 N 103° 58° 25.8 15,500.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.04 651,747.70 32° 35° 45.610 N 103° 58° 25.8 15,500.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.04 651,747.70 32° 35° 45.610 N 103° 58° 30.5 15,500.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35° 45.621 N 103° 58° 30.5 15,500.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35° 45.621 N 103° 58° 30.5 15,500.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35° 45.625 N 103° 58° 31.6 15,700.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35° 45.625 N 103° 58° 35.5 16,000.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.16 651,347.70 32° 35° 45.632 N 103° 58° 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.25 651,047.70 32° 35° 45.632 N 103° 58° 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.25 651,047.70 32° 35° 45.643 N 103° 58° 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.25 651,047.70 32° 35° 45.643 N 103° 58° 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.25 651,047.70 32° 35° 45.643 N 103° 58° 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.31 650,847.70 32° 35° 45.665 N 103° 58° 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.31 650,847.70 32° 35° 45.668 N 103° 58° 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.31 650,847.70 32° 35° 45.668 N 103° 58° 45.6 16,000.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.31 650,847.70 32° 35° 45.668 N 103° 58° 45.6 16,000.0 90.00 270.02 8,241.0 762.5 -10,341.4 580,743.31 650,447.70 32° 35° 45.668 N 1										103° 58' 21.170 W
15,000.0 90.00 270.02 8,241.0 761.9 -8,041.4 580,742.92 652,147.70 32° 35′ 45.600 N 103° 58′ 25.8							,			103° 58' 22.339 W
15,100.0 90.00 270.02 8,241.0 761.9 -8,141.4 580,742.95 652,047.70 32° 35′ 45.603 N 103° 58′ 27.0 15,300.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,742.98 651,947.70 32° 35′ 45.607 N 103° 58′ 27.0 15,300.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.04 651,747.70 32° 35′ 45.610 N 103° 58′ 27.0 15,500.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.04 651,747.70 32° 35′ 45.610 N 103° 58′ 28.1 15,500.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.04 651,747.70 32° 35′ 45.610 N 103° 58′ 29.3 15,500.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.10 651,647.70 32° 35′ 45.621 N 103° 58′ 30.5 15,600.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.10 651,547.70 32° 35′ 45.621 N 103° 58′ 30.5 15,800.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35′ 45.625 N 103° 58′ 32.8 15,800.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.13 651,447.70 32° 35′ 45.622 N 103° 58′ 35.1 16,000.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.19 651,247.70 32° 35′ 45.632 N 103° 58′ 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.22 651,147.70 32° 35′ 45.632 N 103° 58′ 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.22 651,147.70 32° 35′ 45.639 N 103° 58′ 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,441.4 580,743.22 651,447.70 32° 35′ 45.639 N 103° 58′ 36.3 16,100.0 90.00 270.02 8,241.0 762.2 -9,441.4 580,743.28 650,947.70 32° 35′ 45.643 N 103° 58′ 36.1 16,000.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.643 N 103° 58′ 38.7 16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.664 N 103° 58′ 38.7 16,500.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.31 650,847.70 32° 35′ 45.665 N 103° 58′ 38.7 16,500.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.31 650,847.70 32° 35′ 45.665 N 103° 58′ 38.7 16,500.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.40 650,747.70 32° 35′ 45.666 N 103° 58′ 38.3 16,700.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.40 650,747.70 32° 35′ 45.665 N 103° 58′ 4										103° 58' 23.508 W
15,200.0 90.00 270.02 8,241.0 761.9 -8,241.4 580,742.98 651,947.70 32° 35′ 45,607 N 103° 68′ 27.0 15,300.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.01 651,847.70 32° 35′ 45,610 N 103° 68′ 27.0 15,500.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.01 651,847.70 32° 35′ 45,610 N 103° 68′ 28.3 15,500.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35′ 45,618 N 103° 68′ 30.5 15,600.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.10 651,647.70 32° 35′ 45,621 N 103° 68′ 30.5 15,700.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35′ 45,621 N 103° 68′ 32.8 15,800.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.16 651,347.70 32° 35′ 45,621 N 103° 68′ 32.8 15,800.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.16 651,347.70 32° 35′ 45,629 N 103° 68′ 32.8 15,800.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.16 651,347.70 32° 35′ 45,632 N 103° 68′ 32.8 16,900.0 90.00 270.02 8,241.0 762.1 -9,941.4 580,743.19 651,247.70 32° 35′ 45,632 N 103° 68′ 36.3 16,100.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.25 651,047.70 32° 35′ 45,632 N 103° 68′ 36.3 16,100.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.25 651,047.70 32° 35′ 45,639 N 103° 68′ 36.3 16,100.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.26 650,947.70 32° 35′ 45,643 N 103° 68′ 35.3 16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45,664 N 103° 68′ 38.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.34 650,747.70 32° 35′ 45,664 N 103° 68′ 38.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.34 650,747.70 32° 35′ 45,664 N 103° 68′ 38.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.45 650,747.70 32° 35′ 45,661 N 103° 68′ 38.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.45 650,747.70 32° 35′ 45,661 N 103° 68′ 43.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.46 650,747.70 32° 35′ 45,661 N 103° 68′ 43.8 16,400.0 90.00 270.02 8,241.0 762.4 -9,441.4 580,743.46 650,747.70 32° 35′ 45,661 N 103° 68′ 43.8 16,400.0 90.00 270.02 8,241.0 762.4 -9,441.4 580,743.46 650,747.70 32° 35′ 45,661 N 10				,						103° 58' 24.677 W
15,300.0 90.00 270.02 8,241.0 762.0 -8,341.4 580,743.01 651,847.70 32° 35′ 45.610 N 103° 58′ 28.1 15,000.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35′ 45.614 N 103° 58′ 29.3 15,500.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.07 651,647.70 32° 35′ 45.618 N 103° 58′ 30.5 15,600.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.10 651,547.70 32° 35′ 45.621 N 103° 58′ 30.5 15,600.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.10 651,547.70 32° 35′ 45.625 N 103° 58′ 32.6 15,800.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35′ 45.625 N 103° 58′ 34.6 15,900.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.19 651,247.70 32° 35′ 45.625 N 103° 58′ 34.6 16,000.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.22 651,147.70 32° 35′ 45.632 N 103° 58′ 35.3 16,000.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.22 651,147.70 32° 35′ 45.633 N 103° 58′ 35.3 16,000.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.25 651,047.70 32° 35′ 45.633 N 103° 58′ 35.3 16,000.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.26 650,947.70 32° 35′ 45.634 N 103° 58′ 35.3 16,000.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.28 650,947.70 32° 35′ 45.643 N 103° 58′ 38.7 16,000.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.654 N 103° 58′ 38.7 16,000.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.31 650,847.70 32° 35′ 45.654 N 103° 58′ 40.2 16,000.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.37 650,647.70 32° 35′ 45.654 N 103° 58′ 40.2 16,000.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.34 650,477.70 32° 35′ 45.654 N 103° 58′ 40.2 16,000.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.40 650,547.70 32° 35′ 45.654 N 103° 58′ 40.2 16,000.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.40 650,547.70 32° 35′ 45.654 N 103° 58′ 40.2 16,000.0 90.00 270.02 8,241.0 762.4 -9,441.4 580,743.40 650,547.70 32° 35′ 45.656 N 103° 58′ 40.2 16,000.0 90.00 270.02 8,241.0 762.5 -10,441.4 580,743.40 650,547.70 32° 35′ 45.666 N 103° 58′ 40.2 16,000.0 90.00 270.02 8,241.0 762.5 -10,441.4 580,743.40 650,547.70 32° 35′ 45.668 N										103° 58' 25.846 W
15,400.0 90.00 270.02 8,241.0 762.0 -8,441.4 580,743.04 651,747.70 32° 35° 45.614 N 103° 58′ 29.3 15,500.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.07 651,647.70 32° 35° 45.618 N 103° 58′ 30.5 15,600.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,647.70 32° 35° 45.625 N 103° 58′ 31.6 15,700.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35° 45.625 N 103° 58′ 31.6 15,800.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.13 651,447.70 32° 35′ 45.625 N 103° 58′ 32.8 15,800.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.13 651,447.70 32° 35′ 45.625 N 103° 58′ 35.0 15,900.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.13 651,447.70 32° 35′ 45.632 N 103° 58′ 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.22 651,147.70 32° 35′ 45.632 N 103° 58′ 35.1 16,100.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.25 651,047.70 32° 35′ 45.633 N 103° 58′ 35.1 16,200.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.25 651,047.70 32° 35′ 45.643 N 103° 58′ 35.7 16,200.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.643 N 103° 58′ 35.7 16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.654 N 103° 58′ 36.3 16,500.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.31 650,847.70 32° 35′ 45.655 N 103° 58′ 43.5 16,600.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.40 650,547.70 32° 35′ 45.655 N 103° 58′ 42.2 16,600.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.40 650,547.70 32° 35′ 45.656 N 103° 58′ 42.2 16,600.0 90.00 270.02 8,241.0 762.4 -9,441.4 580,743.40 650,547.70 32° 35′ 45.656 N 103° 58′ 42.2 16,600.0 90.00 270.02 8,241.0 762.4 -9,441.4 580,743.40 650,547.70 32° 35′ 45.656 N 103° 58′ 45.650 N 103° 58′ 45.0 16,000.0 90.00 270.02 8,241.0 762.4 -9,441.4 580,743.40 650,547.70 32° 35′ 45.666 N 103° 58′ 45.2 16,600.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.40 650,547.70 32° 35′ 45.668 N 103° 58′ 45.8 16,600.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.56 650,447.70 32° 35′ 45.668 N 103° 58′ 45.8 17,000.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.56 650,447.7						,	,			103° 58' 27.015 W
15,500.0 90.00 270.02 8,241.0 762.0 -8,541.4 580,743.07 651,647.70 32° 35′ 45,632 N 103° 58′ 30.5 15,500.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35′ 45,622 N 103° 58′ 31.6 15,800.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.16 651,347.70 32° 35′ 45,629 N 103° 58′ 33.5 15,800.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.16 651,347.70 32° 35′ 45,629 N 103° 58′ 34.0 15,900.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.16 651,347.70 32° 35′ 45,632 N 103° 58′ 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.19 651,247.70 32° 35′ 45,632 N 103° 58′ 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.22 651,147.70 32° 35′ 45,639 N 103° 58′ 36.3 16,100.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.25 651,047.70 32° 35′ 45,639 N 103° 58′ 35.3 16,200.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.26 651,047.70 32° 35′ 45,643 N 103° 58′ 36.3 16,200.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.28 650,947.70 32° 35′ 45,647 N 103° 58′ 38.7 16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45,664 N 103° 58′ 39.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.34 650,747.70 32° 35′ 45,650 N 103° 58′ 49.2 16,600.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.34 650,747.70 32° 35′ 45,665 N 103° 58′ 43.5 16,600.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.34 650,747.70 32° 35′ 45,665 N 103° 58′ 43.5 16,600.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.40 650,477.0 32° 35′ 45,665 N 103° 58′ 43.3 16,700.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.49 650,477.70 32° 35′ 45,665 N 103° 58′ 45.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.49 650,477.70 32° 35′ 45,665 N 103° 58′ 45.6 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.49 650,477.70 32° 35′ 45,665 N 103° 58′ 45.6 17,100.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.49 650,477.70 32° 35′ 45,665 N 103° 58′ 45.6 17,100.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.50 650,477.70 32° 35′ 45,668 N 103° 58′ 45.6 17,100.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.50 640,477.70 32° 35′ 45,669 N										103° 58' 28.184 W
15,600.0 90.00 270.02 8,241.0 762.0 -8,641.4 580,743.10 651,547.70 32° 35′ 45.621 N 103° 58′ 31.6 15,700.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35′ 45.629 N 103° 58′ 32.8 15,800.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.16 651,347.70 32° 35′ 45.629 N 103° 58′ 32.8 16,000.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.19 651,247.70 32° 35′ 45.632 N 103° 58′ 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.25 651,147.70 32° 35′ 45.639 N 103° 58′ 35.3 16,100.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.25 651,047.70 32° 35′ 45.639 N 103° 58′ 35.3 16,200.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.25 651,047.70 32° 35′ 45.639 N 103° 58′ 35.3 16,200.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.25 651,047.70 32° 35′ 45.643 N 103° 58′ 35.3 16,400.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,447.70 32° 35′ 45.647 N 103° 58′ 39.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,447.70 32° 35′ 45.650 N 103° 58′ 39.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.31 650,747.70 32° 35′ 45.650 N 103° 58′ 41.0 16,500.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.34 650,747.0 32° 35′ 45.651 N 103° 58′ 43.2 16,600.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.37 650,647.70 32° 35′ 45.661 N 103° 58′ 43.3 16,700.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.43 650,447.70 32° 35′ 45.661 N 103° 58′ 43.3 16,700.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.43 650,447.70 32° 35′ 45.661 N 103° 58′ 43.3 16,700.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.43 650,447.70 32° 35′ 45.666 N 103° 58′ 45.8 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.49 650,247.70 32° 35′ 45.666 N 103° 58′ 45.8 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.55 650,047.70 32° 35′ 45.668 N 103° 58′ 45.0 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.56 650,047.70 32° 35′ 45.668 N 103° 58′ 45.0 17,000.0 90.00 270.02 8,241.0 762.6 -10,641.4 580,743.56 649,447.70 32° 35′ 45.668 N 103° 58′ 45.5 17,000.0 90.00 270.02 8,241.0 762.6 -10,641.4 580,743.56 649,447.70 32° 35′ 45.608							,			103° 58' 29.353 W
15,700.0 90.00 270.02 8,241.0 762.1 -8,741.4 580,743.13 651,447.70 32° 35′ 45.625 N 103° 58′ 32.8 15,800.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.16 651,347.70 32° 35′ 45.622 N 103° 58′ 34.0 15,900.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.19 651,247.70 32° 35′ 45.632 N 103° 58′ 36.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.25 651,147.70 32° 35′ 45.632 N 103° 58′ 36.3 16,100.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.25 651,047.70 32° 35′ 45.639 N 103° 58′ 36.3 16,200.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.25 651,047.70 32° 35′ 45.639 N 103° 58′ 38.3 16,300.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.28 650,947.70 32° 35′ 45.643 N 103° 58′ 38.3 16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.28 650,947.70 32° 35′ 45.664 N 103° 58′ 38.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.650 N 103° 58′ 38.9 16,500.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.34 650,747.70 32° 35′ 45.650 N 103° 58′ 38.9 16,500.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.34 650,747.70 32° 35′ 45.650 N 103° 58′ 43.5 16,500.0 90.00 270.02 8,241.0 762.3 -9,641.4 580,743.40 650,547.70 32° 35′ 45.661 N 103° 58′ 44.5 16,600.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.40 650,547.70 32° 35′ 45.661 N 103° 58′ 44.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.40 650,447.70 32° 35′ 45.661 N 103° 58′ 44.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,441.4 580,743.40 650,447.70 32° 35′ 45.661 N 103° 58′ 44.5 17,000.0 90.00 270.02 8,241.0 762.4 -9,441.4 580,743.49 650,447.70 32° 35′ 45.661 N 103° 58′ 44.5 17,000.0 90.00 270.02 8,241.0 762.4 -9,441.4 580,743.49 650,447.70 32° 35′ 45.661 N 103° 58′ 44.5 17,000.0 90.00 270.02 8,241.0 762.5 -10,441.4 580,743.55 650,447.70 32° 35′ 45.661 N 103° 58′ 45.6 17,000.0 90.00 270.02 8,241.0 762.5 -10,441.4 580,743.56 649,447.70 32° 35′ 45.665 N 103° 58′ 45.0 17,700.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.56 649,447.70 32° 35′ 45.669 N 103° 58′ 55.0 17,700.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.60 649,447.70 32° 35′ 45.669										103° 58' 30.522 W
15,800.0 90.00 270.02 8,241.0 762.1 -8,841.4 580,743.16 651,347.70 32° 35′ 45.629 N 103° 58′ 34.0 15,900.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.19 651,247.70 32° 35′ 45.632 N 103° 58′ 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.22 651,147.70 32° 35′ 45.636 N 103° 58′ 35.1 16,100.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.25 651,047.70 32° 35′ 45.639 N 103° 58′ 35.1 16,200.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.25 651,047.70 32° 35′ 45.639 N 103° 58′ 38.7 16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.643 N 103° 58′ 39.8 16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.650 N 103° 58′ 39.8 16,500.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.31 650,647.70 32° 35′ 45.650 N 103° 58′ 39.8 16,500.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.34 650,747.70 32° 35′ 45.650 N 103° 58′ 49.8 16,500.0 90.00 270.02 8,241.0 762.3 -9,641.4 580,743.34 650,647.70 32° 35′ 45.655 N 103° 58′ 43.3 16,700.0 90.00 270.02 8,241.0 762.3 -9,641.4 580,743.43 650,447.70 32° 35′ 45.661 N 103° 58′ 43.3 16,700.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.43 650,447.70 32° 35′ 45.661 N 103° 58′ 45.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.46 650,347.70 32° 35′ 45.665 N 103° 58′ 45.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,941.4 580,743.46 650,347.70 32° 35′ 45.665 N 103° 58′ 45.6 17,000.0 90.00 270.02 8,241.0 762.4 -9,941.4 580,743.46 650,347.70 32° 35′ 45.665 N 103° 58′ 45.5 11,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.55 650,047.70 32° 35′ 45.665 N 103° 58′ 45.6 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.55 650,047.70 32° 35′ 45.675 N 103° 58′ 45.6 17,000.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.55 650,047.70 32° 35′ 45.675 N 103° 58′ 45.5 17,000.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.56 649,947.70 32° 35′ 45.686 N 103° 58′ 45.5 17,000.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.6 649,847.70 32° 35′ 45.680 N 103° 58′ 58.5 17,000.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.76 649,847.70 32° 35′ 45.680										103° 58' 31.691 W
15,900.0 90.00 270.02 8,241.0 762.1 -8,941.4 580,743.19 651,247.70 32° 35′ 45.632 N 103° 58′ 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.22 651,147.70 32° 35′ 45.632 N 103° 58′ 35.1 16,000.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.25 651,047.70 32° 35′ 45.633 N 103° 58′ 37.5 16,200.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.28 650,947.70 32° 35′ 45.643 N 103° 58′ 37.5 16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.647 N 103° 58′ 39.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.31 650,847.70 32° 35′ 45.650 N 103° 58′ 39.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.37 650,647.70 32° 35′ 45.650 N 103° 58′ 41.0 16,500.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.37 650,647.70 32° 35′ 45.665 N 103° 58′ 43.5 16,600.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.40 650,547.70 32° 35′ 45.665 N 103° 58′ 43.5 16,700.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.40 650,547.70 32° 35′ 45.661 N 103° 58′ 44.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.43 650,447.70 32° 35′ 45.665 N 103° 58′ 45.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.49 650,247.70 32° 35′ 45.665 N 103° 58′ 45.65 17,000.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.49 650,247.70 32° 35′ 45.665 N 103° 58′ 45.65 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.49 650,247.70 32° 35′ 45.668 N 103° 58′ 45.65 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.55 650,047.70 32° 35′ 45.668 N 103° 58′ 48.0 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.55 650,047.70 32° 35′ 45.682 N 103° 58′ 45.0 17,000.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.55 650,047.70 32° 35′ 45.686 N 103° 58′ 49.2 17,000.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.61 649,847.70 32° 35′ 45.682 N 103° 58′ 50.3 17,300.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.61 649,847.70 32° 35′ 45.680 N 103° 58′ 50.3 17,300.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.61 649,847.70 32° 35′ 45.680 N 103° 58′ 50.3 17,000.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.61 649,847.70 32° 35′										
16,000.0 90.00 270.02 8,241.0 762.2 -9,041.4 580,743.22 651,147.70 32° 35′ 45.636 N 103° 58′ 36.3 16,100.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.25 651,047.70 32° 35′ 45.639 N 103° 58′ 37.5 16,200.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.28 650,947.70 32° 35′ 45.643 N 103° 58′ 38.3 16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.647 N 103° 58′ 39.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.31 650,847.70 32° 35′ 45.650 N 103° 58′ 39.8 16,500.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.34 650,747.70 32° 35′ 45.654 N 103° 58′ 44.0 16,500.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.37 650,647.70 32° 35′ 45.657 N 103° 58′ 42.2 16,600.0 90.00 270.02 8,241.0 762.3 -9,641.4 580,743.40 650,547.70 32° 35′ 45.661 N 103° 58′ 43.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.43 650,447.70 32° 35′ 45.661 N 103° 58′ 43.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.46 650,347.70 32° 35′ 45.665 N 103° 58′ 45.5 16,900.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.46 650,347.70 32° 35′ 45.668 N 103° 58′ 45.8 16,900.0 90.00 270.02 8,241.0 762.4 -9,941.4 580,743.49 650,247.70 32° 35′ 45.668 N 103° 58′ 45.8 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.55 650,047.70 32° 35′ 45.675 N 103° 58′ 48.0 17,000.0 90.00 270.02 8,241.0 762.5 -10,141.4 580,743.55 650,047.70 32° 35′ 45.675 N 103° 58′ 45.0 17,200.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.55 650,047.70 32° 35′ 45.675 N 103° 58′ 45.0 17,200.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.56 649,947.70 32° 35′ 45.690 N 103° 58′ 50.3 17,300.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.61 649,847.70 32° 35′ 45.690 N 103° 58′ 50.3 17,500.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.61 649,847.70 32° 35′ 45.690 N 103° 58′ 50.3 17,500.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.61 649,847.70 32° 35′ 45.690 N 103° 58′ 50.3 17,500.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.61 649,847.70 32° 35′ 45.690 N 103° 58′ 55.5 17,400.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.70 649,647.70 32° 35′ 45							,			
16,100.0 90.00 270.02 8,241.0 762.2 -9,141.4 580,743.25 651,047.70 32° 35′ 45.639 N 103° 58′ 37.5 16,200.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.28 650,947.70 32° 35′ 45.643 N 103° 58′ 39.87 16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.647 N 103° 58′ 39.8 16,500.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.34 650,647.70 32° 35′ 45.665 N 103° 58′ 44.2 16,600.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.37 650,647.70 32° 35′ 45.665 N 103° 58′ 44.2 16,600.0 90.00 270.02 8,241.0 762.3 -9,641.4 580,743.40 650,547.70 32° 35′ 45.661 N 103° 58′ 44.5 16,700.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.43 650,447.70 32° 35′ 45.661 N 103° 58′ 445.6 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.4										
16,200.0 90.00 270.02 8,241.0 762.2 -9,241.4 580,743.28 650,947.70 32° 35′ 45.643 N 103° 58′ 38.7 16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.667 N 103° 58′ 39.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.34 650,747.70 32° 35′ 45.650 N 103° 58′ 41.0 16,500.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.37 650,647.70 32° 35′ 45.657 N 103° 58′ 42.2 16,600.0 90.00 270.02 8,241.0 762.3 -9,641.4 580,743.40 650,547.70 32° 35′ 45.657 N 103° 58′ 44.5 16,700.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.43 650,447.70 32° 35′ 45.661 N 103° 58′ 44.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.46 650,347.70 32° 35′ 45.666 N 103° 58′ 45.7 16,900.0 90.00 270.02 8,241.0 762.4 -9,941.4 580,743.46 650,347.70 32° 35′ 45.666 N 103° 58′ 45.7 16,900.0 90.00 270.02 8,241.0 762.4 -9,941.4 580,743.49 650,247.70 32° 35′ 45.668 N 103° 58′ 46.8 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.52 650,147.70 32° 35′ 45.672 N 103° 58′ 48.0 17,100.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.58 649,947.70 32° 35′ 45.675 N 103° 58′ 49.5 17,200.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.58 649,947.70 32° 35′ 45.679 N 103° 58′ 49.5 17,300.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.66 649,847.70 32° 35′ 45.686 N 103° 58′ 45.7 17,500.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.66 649,847.70 32° 35′ 45.680 N 103° 58′ 50.3 17,600.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.66 649,847.70 32° 35′ 45.690 N 103° 58′ 55.0 17,500.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.67 649,647.70 32° 35′ 45.690 N 103° 58′ 55.0 17,500.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.70 649,547.70 32° 35′ 45.690 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.70 649,547.70 32° 35′ 45.690 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.70 649,547.70 32° 35′ 45.690 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.70 649,547.70 32° 35′ 45.690 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.70 649,547.70 32° 35′						,	,			
16,300.0 90.00 270.02 8,241.0 762.3 -9,341.4 580,743.31 650,847.70 32° 35′ 45.647 N 103° 58′ 39.8 16,400.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.34 650,747.70 32° 35′ 45.650 N 103° 58′ 41.0 16,500.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.37 650,647.70 32° 35′ 45.654 N 103° 58′ 42.2 16,600.0 90.00 270.02 8,241.0 762.3 -9,641.4 580,743.40 650,547.70 32° 35′ 45.665 N 103° 58′ 43.5 16,700.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.43 650,447.70 32° 35′ 45.666 N 103° 58′ 44.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.43 650,347.70 32° 35′ 45.666 N 103° 58′ 45.6 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.49 650,247.70 32° 35′ 45.666 N 103° 58′ 46.8 17,000.0 90.00 270.02 8,241.0 762.4 -9,941.4 580,743.49 650,247.70 32° 35′ 45.666 N 103° 58′ 46.8 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.52 650,147.70 32° 35′ 45.675 N 103° 58′ 48.0 17,100.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.55 650,047.70 32° 35′ 45.675 N 103° 58′ 49.2 17,200.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.56 650,047.70 32° 35′ 45.679 N 103° 58′ 55.0 17,300.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.58 649,947.70 32° 35′ 45.680 N 103° 58′ 55.0 17,500.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.56 649,947.70 32° 35′ 45.680 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.56 649,947.70 32° 35′ 45.680 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.56 649,947.70 32° 35′ 45.690 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.76 649,647.70 32° 35′ 45.690 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.76 649,647.70 32° 35′ 45.690 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.76 649,647.70 32° 35′ 45.690 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.76 649,647.70 32° 35′ 45.690 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.76 649,647.70 32° 35′ 45.690 N 103° 58′ 55.0 17,600.0 90.00 270.02 8,241.0 762.8 -11,641.4 580,743.76 649,647.70 32° 35										
16,400.0 90.00 270.02 8,241.0 762.3 -9,441.4 580,743.34 650,747.70 32° 35' 45.650 N 103° 58' 41.0 16,500.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.37 650,647.70 32° 35' 45.654 N 103° 58' 42.2 16,600.0 90.00 270.02 8,241.0 762.3 -9,641.4 580,743.40 650,547.70 32° 35' 45.661 N 103° 58' 43.3 16,700.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.40 650,447.70 32° 35' 45.661 N 103° 58' 44.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.46 650,447.70 32° 35' 45.665 N 103° 58' 45.67 16,900.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.49 650,447.70 32° 35' 45.665 N 103° 58' 46.8 17,000.0 90.00 270.02 8,241.0 762.5 -10,41.4 580,743.52 650,147.70 32° 35' 45.675 N 103° 58' 48.0 17,200.0 90.00 270.02 8,241.0 762.5 -10,41.4 580,743.55										
16,500.0 90.00 270.02 8,241.0 762.3 -9,541.4 580,743.37 650,647.70 32° 35' 45.654 N 103° 58' 42.2 16,600.0 90.00 270.02 8,241.0 762.3 -9,641.4 580,743.40 650,547.70 32° 35' 45.657 N 103° 58' 44.3 16,700.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.43 650,447.70 32° 35' 45.661 N 103° 58' 44.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.46 650,347.70 32° 35' 45.665 N 103° 58' 45.7 16,900.0 90.00 270.02 8,241.0 762.4 -9,941.4 580,743.49 650,247.70 32° 35' 45.666 N 103° 58' 46.8 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.52 650,147.70 32° 35' 45.668 N 103° 58' 48.0 17,200.0 90.00 270.02 8,241.0 762.5 -10,411.4 580,743.55 650,047.70 32° 35' 45.675 N 103° 58' 48.0 17,300.0 90.00 270.02 8,241.0 762.6 -10,241.4 580,743.										
16,600.0 90.00 270.02 8,241.0 762.3 -9,641.4 580,743.40 650,547.70 32° 35′ 45.657 N 103° 58′ 43.3 16,700.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.43 650,447.70 32° 35′ 45.661 N 103° 58′ 44.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.46 650,347.70 32° 35′ 45.665 N 103° 58′ 45.7 16,900.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.49 650,247.70 32° 35′ 45.668 N 103° 58′ 46.8 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.52 650,147.70 32° 35′ 45.672 N 103° 58′ 48.0 17,100.0 90.00 270.02 8,241.0 762.5 -10,141.4 580,743.55 650,047.70 32° 35′ 45.675 N 103° 58′ 49.2 17,200.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.58 649,947.70 32° 35′ 45.662 N 103° 58′ 50.3 17,300.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743										
16,700.0 90.00 270.02 8,241.0 762.4 -9,741.4 580,743.43 650,447.70 32° 35' 45.661 N 103° 58' 44.5 16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.46 650,347.70 32° 35' 45.665 N 103° 58' 45.7 16,900.0 90.00 270.02 8,241.0 762.4 -9,941.4 580,743.49 650,247.70 32° 35' 45.668 N 103° 58' 46.8 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.52 650,147.70 32° 35' 45.672 N 103° 58' 48.0 17,100.0 90.00 270.02 8,241.0 762.5 -10,141.4 580,743.55 650,047.70 32° 35' 45.675 N 103° 58' 49.2 17,200.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.58 649,947.70 32° 35' 45.675 N 103° 58' 58' 59.3 17,300.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.58 649,947.70 32° 35' 45.682 N 103° 58' 55.5 17,400.0 90.00 270.02 8,241.0 762.6 -10,341.4 58										
16,800.0 90.00 270.02 8,241.0 762.4 -9,841.4 580,743.46 650,347.70 32° 35' 45.665 N 103° 58' 45.7 16,900.0 90.00 270.02 8,241.0 762.4 -9,941.4 580,743.49 650,247.70 32° 35' 45.668 N 103° 58' 46.8 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.52 650,147.70 32° 35' 45.672 N 103° 58' 48.0 17,100.0 90.00 270.02 8,241.0 762.5 -10,141.4 580,743.55 650,047.70 32° 35' 45.675 N 103° 58' 49.2 17,200.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.58 649,947.70 32° 35' 45.675 N 103° 58' 49.2 17,300.0 90.00 270.02 8,241.0 762.6 -10,241.4 580,743.61 649,847.70 32° 35' 45.682 N 103° 58' 59.5 17,400.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.64 649,747.70 32° 35' 45.686 N 103° 58' 59.5 17,500.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,7							,			
16,900.0 90.00 270.02 8,241.0 762.4 -9,941.4 580,743.49 650,247.70 32° 35' 45.668 N 103° 58' 46.88 17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.52 650,147.70 32° 35' 45.672 N 103° 58' 48.0 17,100.0 90.00 270.02 8,241.0 762.5 -10,141.4 580,743.55 650,047.70 32° 35' 45.675 N 103° 58' 49.2 17,200.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.58 649,947.70 32° 35' 45.679 N 103° 58' 49.2 17,300.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.61 649,847.70 32° 35' 45.682 N 103° 58' 59.5 17,400.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.64 649,747.70 32° 35' 45.686 N 103° 58' 59.5 17,500.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.67 649,647.70 32° 35' 45.690 N 103° 58' 59.5 17,600.0 90.00 270.02 8,241.0 762.6 -10,541.4 580										
17,000.0 90.00 270.02 8,241.0 762.5 -10,041.4 580,743.52 650,147.70 32° 35' 45.672 N 103° 58' 48.0 17,100.0 90.00 270.02 8,241.0 762.5 -10,141.4 580,743.55 650,047.70 32° 35' 45.675 N 103° 58' 49.2 17,200.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.58 649,947.70 32° 35' 45.679 N 103° 58' 59.3 17,300.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.61 649,847.70 32° 35' 45.682 N 103° 58' 59.5 17,400.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.64 649,747.70 32° 35' 45.686 N 103° 58' 59.5 17,500.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.67 649,647.70 32° 35' 45.690 N 103° 58' 53.9 17,600.0 90.00 270.02 8,241.0 762.6 -10,641.4 580,743.67 649,647.70 32° 35' 45.690 N 103° 58' 55.0 17,700.0 90.00 270.02 8,241.0 762.7 -10,741.4 580										
17,100.0 90.00 270.02 8,241.0 762.5 -10,141.4 580,743.55 650,047.70 32° 35' 45.675 N 103° 58' 49.2 17,200.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.58 649,947.70 32° 35' 45.679 N 103° 58' 59.3 17,300.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.61 649,847.70 32° 35' 45.682 N 103° 58' 59.5 17,400.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.64 649,747.70 32° 35' 45.686 N 103° 58' 59.7 17,500.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.67 649,647.70 32° 35' 45.690 N 103° 58' 59.5 17,600.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.67 649,647.70 32° 35' 45.690 N 103° 58' 59.50 17,700.0 90.00 270.02 8,241.0 762.6 -10,641.4 580,743.70 649,547.70 32° 35' 45.693 N 103° 58' 55.0 17,800.0 90.00 270.02 8,241.0 762.7 -10,741.4 58										
17,200.0 90.00 270.02 8,241.0 762.5 -10,241.4 580,743.58 649,947.70 32° 35' 45.679 N 103° 58' 50.3 17,300.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.61 649,847.70 32° 35' 45.682 N 103° 58' 51.5 17,400.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.64 649,747.70 32° 35' 45.686 N 103° 58' 52.7 17,500.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.67 649,647.70 32° 35' 45.690 N 103° 58' 53.9 17,600.0 90.00 270.02 8,241.0 762.6 -10,641.4 580,743.70 649,547.70 32° 35' 45.693 N 103° 58' 55.0 17,700.0 90.00 270.02 8,241.0 762.7 -10,741.4 580,743.73 649,447.70 32° 35' 45.697 N 103° 58' 56.2 17,800.0 90.00 270.02 8,241.0 762.7 -10,741.4 580,743.76 649,347.70 32° 35' 45.697 N 103° 58' 56.2 17,900.0 90.00 270.02 8,241.0 762.7 -10,841.4 580	,						•			
17,300.0 90.00 270.02 8,241.0 762.6 -10,341.4 580,743.61 649,847.70 32° 35' 45.682 N 103° 58' 51.5 17,400.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.64 649,747.70 32° 35' 45.686 N 103° 58' 52.7 17,500.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.67 649,647.70 32° 35' 45.690 N 103° 58' 53.9 17,600.0 90.00 270.02 8,241.0 762.6 -10,641.4 580,743.70 649,547.70 32° 35' 45.693 N 103° 58' 55.0 17,700.0 90.00 270.02 8,241.0 762.7 -10,741.4 580,743.73 649,447.70 32° 35' 45.697 N 103° 58' 56.2 17,800.0 90.00 270.02 8,241.0 762.7 -10,841.4 580,743.76 649,347.70 32° 35' 45.697 N 103° 58' 57.4 17,900.0 90.00 270.02 8,241.0 762.7 -10,841.4 580,743.76 649,347.70 32° 35' 45.700 N 103° 58' 58.5 18,000.0 90.00 270.02 8,241.0 762.7 -10,941.4 580								*		
17,400.0 90.00 270.02 8,241.0 762.6 -10,441.4 580,743.64 649,747.70 32° 35' 45.686 N 103° 58' 52.7 17,500.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.67 649,647.70 32° 35' 45.690 N 103° 58' 53.9 17,600.0 90.00 270.02 8,241.0 762.6 -10,641.4 580,743.70 649,547.70 32° 35' 45.693 N 103° 58' 55.0 17,700.0 90.00 270.02 8,241.0 762.7 -10,741.4 580,743.73 649,447.70 32° 35' 45.697 N 103° 58' 56.2 17,800.0 90.00 270.02 8,241.0 762.7 -10,841.4 580,743.76 649,347.70 32° 35' 45.697 N 103° 58' 57.4 17,900.0 90.00 270.02 8,241.0 762.7 -10,841.4 580,743.76 649,347.70 32° 35' 45.700 N 103° 58' 58.5 18,000.0 90.00 270.02 8,241.0 762.7 -10,941.4 580,743.79 649,247.70 32° 35' 45.704 N 103° 58' 58.5 18,000.0 90.00 270.02 8,241.0 762.8 -11,041.4 580										
17,500.0 90.00 270.02 8,241.0 762.6 -10,541.4 580,743.67 649,647.70 32° 35' 45.690 N 103° 58' 53.9 17,600.0 90.00 270.02 8,241.0 762.6 -10,641.4 580,743.70 649,547.70 32° 35' 45.693 N 103° 58' 55.0 17,700.0 90.00 270.02 8,241.0 762.7 -10,741.4 580,743.73 649,447.70 32° 35' 45.697 N 103° 58' 56.2 17,800.0 90.00 270.02 8,241.0 762.7 -10,841.4 580,743.76 649,347.70 32° 35' 45.700 N 103° 58' 57.4 17,900.0 90.00 270.02 8,241.0 762.7 -10,941.4 580,743.79 649,247.70 32° 35' 45.704 N 103° 58' 58.5 18,000.0 90.00 270.02 8,241.0 762.8 -11,041.4 580,743.82 649,147.70 32° 35' 45.707 N 103° 58' 59.7 18,100.0 90.00 270.02 8,241.0 762.8 -11,041.4 580,743.82 649,147.70 32° 35' 45.707 N 103° 58' 59.7 18,100.0 90.00 270.02 8,241.0 762.8 -11,141.4 580								*		103° 58' 52.731 W
17,600.0 90.00 270.02 8,241.0 762.6 -10,641.4 580,743.70 649,547.70 32° 35' 45.693 N 103° 58' 55.0 17,700.0 90.00 270.02 8,241.0 762.7 -10,741.4 580,743.73 649,447.70 32° 35' 45.697 N 103° 58' 56.2 17,800.0 90.00 270.02 8,241.0 762.7 -10,841.4 580,743.76 649,347.70 32° 35' 45.700 N 103° 58' 57.4 17,900.0 90.00 270.02 8,241.0 762.7 -10,941.4 580,743.79 649,247.70 32° 35' 45.704 N 103° 58' 58.5 18,000.0 90.00 270.02 8,241.0 762.8 -11,041.4 580,743.82 649,147.70 32° 35' 45.707 N 103° 58' 59.7 18,100.0 90.00 270.02 8,241.0 762.8 -11,041.4 580,743.82 649,147.70 32° 35' 45.707 N 103° 58' 59.7 18,100.0 90.00 270.02 8,241.0 762.8 -11,141.4 580,743.85 649,047.70 32° 35' 45.711 N 103° 59' 0.9							•			103° 58' 53.900 W
17,700.0 90.00 270.02 8,241.0 762.7 -10,741.4 580,743.73 649,447.70 32° 35' 45.697 N 103° 58' 56.2 17,800.0 90.00 270.02 8,241.0 762.7 -10,841.4 580,743.76 649,347.70 32° 35' 45.700 N 103° 58' 57.4 17,900.0 90.00 270.02 8,241.0 762.7 -10,941.4 580,743.79 649,247.70 32° 35' 45.704 N 103° 58' 58.5 18,000.0 90.00 270.02 8,241.0 762.8 -11,041.4 580,743.82 649,147.70 32° 35' 45.707 N 103° 58' 59.7 18,100.0 90.00 270.02 8,241.0 762.8 -11,141.4 580,743.85 649,047.70 32° 35' 45.711 N 103° 59' 0.9										103° 58' 55.069 W
17,800.0 90.00 270.02 8,241.0 762.7 -10,841.4 580,743.76 649,347.70 32° 35' 45.700 N 103° 58' 57.4 17,900.0 90.00 270.02 8,241.0 762.7 -10,941.4 580,743.79 649,247.70 32° 35' 45.704 N 103° 58' 58.5 18,000.0 90.00 270.02 8,241.0 762.8 -11,041.4 580,743.82 649,147.70 32° 35' 45.707 N 103° 58' 59.7 18,100.0 90.00 270.02 8,241.0 762.8 -11,141.4 580,743.85 649,047.70 32° 35' 45.711 N 103° 59' 0.9								*		103° 58' 56.238 W
17,900.0 90.00 270.02 8,241.0 762.7 -10,941.4 580,743.79 649,247.70 32° 35' 45.704 N 103° 58' 58.5 18,000.0 90.00 270.02 8,241.0 762.8 -11,041.4 580,743.82 649,147.70 32° 35' 45.707 N 103° 58' 59.7 18,100.0 90.00 270.02 8,241.0 762.8 -11,141.4 580,743.85 649,047.70 32° 35' 45.711 N 103° 59' 0.9										103° 58' 57.407 W
18,000.0 90.00 270.02 8,241.0 762.8 -11,041.4 580,743.82 649,147.70 32° 35′ 45.707 N 103° 58′ 59.7 18,100.0 90.00 270.02 8,241.0 762.8 -11,141.4 580,743.85 649,047.70 32° 35′ 45.711 N 103° 59′ 0.9						,	•			103° 58' 58.576 W
18,100.0 90.00 270.02 8,241.0 762.8 -11,141.4 580,743.85 649,047.70 32° 35' 45.711 N 103° 59' 0.9										103° 58' 59.745 W
							•	*		103° 59' 0.914 W
,										103° 59' 2.083 W
										103° 59' 3.252 W

Planning Report - Geographic

Database: Compass
Company: NEW MEXICO
Project: (SP) EDDY

Site:MICHELADA FED COMWell:MICHELADA 3 FED COM 134H

Wellbore: OWB
Design: PWP0

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well MICHELADA 3 FED COM 134H

GL @ 3225.0usft GL @ 3225.0usft Grid

Minimum Curvature

ned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
18,400.0	90.00	270.02	8,241.0	762.9	-11,441.4	580,743.94	648,747.70	32° 35' 45.722 N	103° 59' 4.421
18,500.0	90.00	270.02	8,241.0	762.9	-11,541.4	580,743.97	648,647.70	32° 35' 45.725 N	103° 59' 5.590
18,600.0	90.00	270.02	8,241.0	762.9	-11,641.4	580,743.99	648,547.70	32° 35' 45.729 N	103° 59' 6.759
18,700.0	90.00	270.02	8,241.0	763.0	-11,741.4	580,744.02	648,447.70	32° 35' 45.732 N	103° 59' 7.928
18,800.0	90.00	270.02	8,241.0	763.0	-11,841.4	580,744.05	648,347.70	32° 35' 45.736 N	103° 59' 9.097
18,900.0	90.00	270.02	8,241.0	763.0	-11,941.4	580,744.08	648,247.70	32° 35' 45.739 N	103° 59' 10.266
19,000.0	90.00	270.02	8,241.0	763.1	-12,041.4	580,744.11	648,147.70	32° 35' 45.743 N	103° 59' 11.434
19,100.0	90.00	270.02	8,241.0	763.1	-12,141.4	580,744.14	648,047.70	32° 35' 45.746 N	103° 59' 12.603
19,200.0	90.00	270.02	8,241.0	763.1	-12,241.4	580,744.17	647,947.70	32° 35' 45.750 N	103° 59' 13.772
19,300.0	90.00	270.02	8,241.0	763.1	-12,341.4	580,744.20	647,847.70	32° 35' 45.753 N	103° 59' 14.941
19,400.0	90.00	270.02	8,241.0	763.2	-12,441.4	580,744.23	647,747.70	32° 35' 45.757 N	103° 59' 16.110
19,500.0	90.00	270.02	8,241.0	763.2	-12,541.4	580,744.26	647,647.70	32° 35' 45.760 N	103° 59' 17.27
19,600.0	90.00	270.02	8,241.0	763.2	-12,641.4	580,744.29	647,547.70	32° 35' 45.764 N	103° 59' 18.448
19,700.0	90.00	270.02	8,241.0	763.3	-12,741.4	580,744.32	647,447.70	32° 35' 45.767 N	103° 59' 19.61
19,800.0	90.00	270.02	8,241.0	763.3	-12,841.4	580,744.35	647,347.70	32° 35' 45.771 N	103° 59' 20.78
19,900.0	90.00	270.02	8,241.0	763.3	-12,941.4	580,744.38	647,247.70	32° 35' 45.774 N	103° 59' 21.95
20,000.0	90.00	270.02	8,241.0	763.4	-13,041.4	580,744.41	647,147.70	32° 35' 45.778 N	103° 59' 23.12
20,100.0	90.00	270.02	8,241.0	763.4	-13,141.4	580,744.44	647,047.70	32° 35' 45.781 N	103° 59' 24.29
20,200.0	90.00	270.02	8,241.0	763.4	-13,241.4	580,744.47	646,947.70	32° 35' 45.785 N	103° 59' 25.46
20,300.0	90.00	270.02	8,241.0	763.4	-13,341.4	580,744.50	646,847.70	32° 35' 45.788 N	103° 59' 26.63
20,400.0	90.00	270.02	8,241.0	763.5	-13,441.4	580,744.53	646,747.70	32° 35' 45.792 N	103° 59' 27.80
20,500.0	90.00	270.02	8,241.0	763.5	-13,541.4	580,744.56	646,647.70	32° 35' 45.795 N	103° 59' 28.96
20,600.0	90.00	270.02	8,241.0	763.5	-13,641.4	580,744.59	646,547.70	32° 35' 45.799 N	103° 59' 30.13
20,700.0	90.00	270.02	8,241.0	763.6	-13,741.4	580,744.62	646,447.70	32° 35' 45.802 N	103° 59' 31.30
20,800.0	90.00	270.02	8,241.0	763.6	-13,841.4	580,744.65	646,347.70	32° 35′ 45.806 N	103° 59' 32.47
20,900.0	90.00	270.02	8,241.0	763.6	-13,941.4	580,744.68	646,247.70	32° 35′ 45.809 N	103° 59' 33.64
21,000.0	90.00	270.02	8,241.0	763.7	-14,041.4	580,744.71	646,147.70	32° 35' 45.813 N	103° 59' 34.81
21,100.0	90.00	270.02	8,241.0	763.7	-14,141.4	580,744.74	646,047.70	32° 35' 45.816 N	103° 59' 35.98
21,200.0	90.00	270.02	8,241.0	763.7	-14,241.4	580,744.77	645,947.70	32° 35' 45.819 N	103° 59' 37.15
21,284.2	90.00	270.02	8,241.0	763.7	-14,325.6	580,744.79	645,863.48	32° 35' 45.822 N	103° 59' 38.13

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
MICHELADA 3 FED CO - plan misses target - Point		0.00 usft at 21264	8,241.0 .2usft MD (8	763.8 241.0 TVD, 7	-14,305.6 63.7 N, -14305	580,744.87 5.6 E)	645,883.48	32° 35' 45.823 N	103° 59' 37.902 W
MICHELADA 3 FED CO - plan hits target cer - Point		0.00	8,241.0	763.7	-14,325.6	580,744.79	645,863.48	32° 35' 45.822 N	103° 59' 38.136 W
MICHELADA 3 FED CO - plan misses target - Point		0.00 .8usft at 833	8,241.0 8.5usft MD (759.9 8101.3 TVD,	-1,277.1 759.9 N, -1417	580,740.91 7.2 E)	658,911.94	32° 35' 45.346 N	103° 57' 5.607 W

Planning Report - Geographic

Database: Compass
Company: NEW MEXICO
Project: (SP) EDDY

Site: MICHELADA FED COM
Well: MICHELADA 3 FED COM 134H

Wellbore: OWB
Design: PWP0

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well MICHELADA 3 FED COM 134H

GL @ 3225.0usft GL @ 3225.0usft

Grid

Minimum Curvature

Annotations				
Measured	Vertical	Local Coor	dinates	
Depth	Depth	+N/-S	+E/-W	
(usft)	(usft)	(usft)	(usft)	Comment
1,750.0	1,750.0	0.0	0.0	Start Build 2.00
2,556.0	2,545.4	57.6	-96.8	Start 4541.3 hold at 2556.0 MD
7,097.2	6,908.1	702.3	-1,180.4	Start Drop -2.00
7,903.2	7,703.5	759.9	-1,277.1	Start 60.0 hold at 7903.2 MD
7,963.2	7,763.5	759.9	-1,277.1	Start DLS 12.00 TFO 270.02
8,713.2	8,241.0	760.0	-1,754.6	Start 12571.0 hold at 8713.2 MD
21,284.2	8,241.0	763.7	-14,325.6	TD at 21284.2

NEW MEXICO

(SP) EDDY
MICHELADA FED COM
MICHELADA 3 FED COM 134H

OWB PWP0

Anticollision Report

26 June, 2024

Anticollision Report

Company: **NEW MEXICO** Project: (SP) EDDY

Reference Site: MICHELADA FED COM

Site Error: 0.0 usft

Reference Well: MICHELADA 3 FED COM 134H

Well Error: 0.0 usft Reference Wellbore **OWB** Reference Design: PWP0

Local Co-ordinate Reference:

Well MICHELADA 3 FED COM 134H **TVD Reference:** GL @ 3225.0usft

GL @ 3225.0usft MD Reference:

North Reference: Grid **Survey Calculation Method:** Minimum Curvature

Output errors are at 2.00 sigma Database: Compass Offset TVD Reference: Reference Datum

Reference PWP0

NO GLOBAL FILTER: Using user defined selection & filtering criteria Filter type:

Interpolation Method: Stations Error Model: **ISCWSA**

Depth Range: Unlimited Scan Method: Closest Approach 3D Results Limited by: Maximum centre distance of 1,000.0usft Error Surface: Pedal Curve Warning Levels Evaluated at: 2.00 Sigma Casing Method: Not applied

6/26/2024 Survey Tool Program Date

> From То

(usft)

(usft) Survey (Wellbore) **Tool Name** Description

21,283.3 PWP0 (OWB) MWD+IFR1+MS 0.0 OWSG_Rev2_ MWD + IFR1 + Multi-Station Correction

Summary						
Site Name Offset Well - Wellbore - Design	Reference Measured Depth (usft)	Offset Measured Depth (usft)	Dista Between Centres (usft)	nce Between Ellipses (usft)	Separation Factor	Warning
MEZCAL 10 FED COM						
MEZCAL 10 FED COM 131H - OWB - PWP0 MEZCAL 10 FED COM 131H - OWB - PWP0 MEZCAL 10 FED COM 131H - OWB - PWP0 MEZCAL 10 FED COM 132H - OWB - PWP0 MEZCAL 10 FED COM 132H - OWB - PWP0 MEZCAL 10 FED COM 132H - OWB - PWP0 MEZCAL 10 FED COM 133H - OWB - PWP0 MEZCAL 10 FED COM 133H - OWB - PWP0 MEZCAL 10 FED COM 133H - OWB - PWP0 MEZCAL 10 FED COM 134H - OWB - PWP0 MEZCAL 10 FED COM 134H - OWB - PWP0 MEZCAL 10 FED COM 134H - OWB - PWP0 MEZCAL 10 FED COM 134H - OWB - PWP0	2,066.9 2,100.0 2,200.0 1,466.0 1,500.0 1,600.0 1,707.3 1,750.0 1,800.0 1,750.0	2,065.1 2,097.0 2,193.0 1,468.0 1,500.0 1,594.9 1,710.1 1,752.6 1,800.0 1,753.5 1,803.5 2,000.0	112.6 112.8 115.6 104.3 107.7 100.1 100.1 101.1 104.1 104.3 109.8	97.8 97.8 100.0 93.8 93.6 96.3 87.8 87.5 88.2 91.4	7.619 CC 7.517 ES 7.381 SF 9.917 CC 9.702 ES 9.431 SF 8.168 CC 7.970 ES 7.841 SF 8.285 CC 8.073 ES 7.671 SF	
MICHELADA FED COM	2,000.0	2,000.0	103.0	30.0	7.071 01	
MICHELADA 3 FED COM 133H - OWB - PWP0 MICHELADA 3 FED COM 133H - OWB - PWP0 MICHELADA 5 FED COM 131H - OWB - PWP0 MICHELADA 5 FED COM 132H - OWB - PWP0	1,750.0 1,800.0	1,750.0 1,800.0	29.3 29.7	16.7 16.8	2.333 CC, ES 2.301 SF Out of	range

Offset Des	sign: ME	ZCAL 10 F	ED COM	- MEZCAL	10 FED 0	COM 131H -	OWB - PWP0						Offset Site Error:	0.0 usft
Survey Progr Refer Measured		MWD Off Measured	set Vertical	Semi M Reference	Major Axis Offset	Highside	Offset Wellbo		Dis Between	Rule Assi tance Between	gned: Minimum	Separation	Offset Well Error: Warning	0.0 usft
Depth	Depth	Depth	Depth			Toolface	+N/-S	+E/-W (usft)	Centres	Ellipses	Separation	Factor		
(usft)	(usft)	(usft)	(usft)	(usft)	(usft)	(°)	(usft)	(usit)	(usft)	(usft)	(usft)			
0.0	0.0	1.2	0.0	0.0	0.0	-130.36	-75.3	-88.7	116.4	116.4	0.00	N/A		
100.0	100.0	101.2	100.0	0.4	0.4	-130.36	-75.3	-88.7	116.4	115.6	0.72	161.334		
200.0	200.0	201.2	200.0	0.7	0.7	-130.36	-75.3	-88.7	116.4	114.9	1.44	80.908		
300.0	300.0	301.2	300.0	1.1	1.1	-130.36	-75.3	-88.7	116.4	114.2	2.16	53.993		
400.0	400.0	401.2	400.0	1.4	1.4	-130.36	-75.3	-88.7	116.4	113.5	2.87	40.515		
500.0	500.0	501.2	500.0	1.8	1.8	-130.36	-75.3	-88.7	116.4	112.8	3.59	32.422		
600.0	600.0	601.2	600.0	2.2	2.2	-130.36	-75.3	-88.7	116.4	112.1	4.31	27.023		
700.0	700.0	701.2	700.0	2.5	2.5	-130.36	-75.3	-88.7	116.4	111.3	5.02	23.166		
800.0	800.0	801.2	800.0	2.9	2.9	-130.36	-75.3	-88.7	116.4	110.6	5.74	20.273		
900.0	900.0	901.2	900.0	3.2	3.2	-130.36	-75.3	-88.7	116.4	109.9	6.46	18.022		

Anticollision Report

Company: NEW MEXICO Project: (SP) EDDY

Reference Site: MICHELADA FED COM

Site Error: 0.0 usft

Reference Well: MICHELADA 3 FED COM 134H

Well Error: 0.0 usft
Reference Wellbore OWB
Reference Design: PWP0

Local Co-ordinate Reference:

TVD Reference: GL @ 3225.0usft MD Reference: GL @ 3225.0usft

North Reference: Grid

Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma

Well MICHELADA 3 FED COM 134H

	,.g		-ED COM	- MEZCAL	10 FED (COM 131H -	OWB - PWP0						Offset Site Error:	0.0 usft
Survey Progra Refere		MWD Off	fset	Semi I	Major Axis		Offset Wellbo	re Centre	Dist	Rule Assi	gned:		Offset Well Error:	0.0 usft
Measured Depth	Vertical Depth	Measured Depth	Vertical Depth	Reference	Offset	Highside Toolface	+N/-S	+E/-W	Between Centres	Between Ellipses	Minimum Separation	Separation Factor	Warning	
(usft)	(usft)	(usft)	(usft)	(usft)	(usft)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)	i uctoi		
1,000.0	1,000.0	1,001.2	1,000.0	3.6	3.6	-130.36	-75.3	-88.7	116.4	109.2	7.17	16.220		
1,100.0	1,100.0	1,101.2	1,100.0	3.9	3.9	-130.36	-75.3	-88.7	116.4	108.5	7.89	14.747		
1,200.0	1,200.0	1,201.2	1,200.0	4.3	4.3	-130.36	-75.3	-88.7	116.4	107.8	8.61	13.518		
1,300.0	1,300.0	1,301.2	1,300.0	4.7	4.7	-130.36	-75.3	-88.7	116.4	107.0	9.32	12.479		
1,400.0	1,400.0	1,401.2	1,400.0	5.0	5.0	-130.36	-75.3	-88.7	116.4	106.3	10.04	11.588		
1,500.0	1,500.0	1,501.2	1,500.0	5.4	5.4	-130.36	-75.3	-88.7	116.4	105.6	10.76	10.816		
1,600.0	1,600.0	1,601.2	1,600.0	5.7	5.7	-130.36	-75.3	-88.7	116.4	104.9	11.48	10.140		
1,700.0	1,700.0	1,701.2	1,700.0	6.1	6.1	-130.36	-75.3	-88.7	116.4	104.2	12.19	9.544		
1,750.0	1,750.0	1,751.2	1,750.0	6.3	6.3	-130.36	-75.3	-88.7	116.4	103.8	12.55	9.271		
1,800.0	1,800.0	1,801.2	1,800.0	6.5	6.5	-71.31	-75.3	-88.7	116.2	103.3	12.91	9.004		
1,900.0	1,899.9	1,901.1	1,899.9	6.8	6.8	-72.98	-75.3	-88.7	115.2	101.5	13.62	8.457		
2,000.0	1,999.7	2,000.0	1,998.8	7.2	7.2	-76.34	-75.3	-88.7	113.3	99.0	14.32	7.912		
2,066.9	2,066.2	2,065.1	2,063.9	7.4	7.4	-79.39	-75.6	-89.4	112.6	97.8	14.78	7.619 CC		
2,100.0	2,099.1	2,097.0	2,095.8	7.5	7.5	-81.03	-76.0	-90.2	112.8	97.8	15.00	7.517 ES		
2,200.0	2,198.2	2,193.0	2,191.7	7.9	7.8	-86.39	-77.8	-94.7	115.6	100.0	15.67	7.381 SF		
2,300.0	2,296.6	2,288.9	2,287.2	8.2	8.2	-92.00	-80.8	-102.2	122.2	105.9	16.33	7.486		
2,400.0	2,394.4	2,384.4	2,382.0	8.6	8.5	-97.37	-85.0	-112.5	132.7	115.8	16.99	7.813		
2,500.0	2,491.5	2,479.4	2,476.0	8.9	8.8	-102.14	-90.4	-125.8	147.2	129.6	17.66	8.336		
2,556.0	2,545.4	2,532.4	2,528.1	9.1	9.0	-104.48	-93.9	-134.4	157.0	139.0	18.04	8.703		
2,600.0	2,587.7	2,573.9	2,568.9	9.3	9.2	-106.21	-96.9	-141.8	165.5	147.1	18.35	9.019		
2,700.0	2,683.7	2,668.2	2,661.0	9.7	9.5	-108.97	-104.5	-160.5	186.3	167.3	19.04	9.787		
2,800.0	2,779.8	2,762.1	2,751.9	10.0	9.9	-110.42	-113.3	-182.0	209.1	189.4	19.74	10.596		
2,900.0	2,875.9	2,857.7	2,843.9	10.4	10.3	-111.05	-123.1	-206.2	233.3	212.9	20.47	11.398		
3,000.0	2,972.0	2,954.6	2,937.1	10.8	10.7	-111.51	-133.1	-231.0	257.7	236.4	21.24	12.131		
3,100.0	3,068.0	3,051.6	3,030.3	11.2	11.1	-111.90	-143.2	-255.8	282.1	260.0	22.03	12.806		
3,200.0	3,164.1	3,148.6	3,123.5	11.5	11.6	-112.22	-153.2	-280.5	306.4	283.6	22.82	13.428		
3,300.0	3,260.2	3,245.5	3,216.7	11.9	12.0	-112.50	-163.3	-305.3	330.8	307.2	23.63	14.003		
3,400.0	3,356.2	3,342.5	3,309.9	12.3	12.5	-112.73	-173.3	-330.0	355.2	330.8	24.44	14.534		
3,500.0	3,452.3	3,439.5	3,403.1	12.7	13.0	-112.94	-183.4	-354.8	379.6	354.4	25.26	15.026		
3,600.0	3,548.4	3,536.4	3,496.4	13.1	13.5	-113.12	-193.5	-379.6	404.0	377.9	26.10	15.483		
3,700.0	3,644.4	3,633.4	3,589.6	13.4	13.9	-113.29	-203.5	-404.3	428.4	401.5	26.93	15.907		
3,800.0	3,740.5	3,730.4	3,682.8	13.8	14.4	-113.43	-213.6	-429.1	452.9	425.1	27.78	16.303		
3,900.0	3,836.6	3,827.3	3,776.0	14.2	14.9	-113.56	-223.6	-453.9	477.3	448.6	28.63	16.671		
4,000.0	3,932.6	3,924.3	3,869.2	14.6	15.4	-113.68	-233.7	-478.6	501.7	472.2	29.48	17.016		
4,100.0	4,028.7	4,021.3	3,962.4	15.0	15.9	-113.78	-243.7	-503.4	526.1	495.8	30.34	17.338		
4,200.0	4,124.8	4,118.3	4,055.6	15.4	16.4	-113.88	-253.8	-528.2	550.5	519.3	31.21	17.640		
4,300.0	4,220.8	4,215.2	4,148.8	15.8	16.9	-113.97	-263.8	-552.9	574.9	542.9	32.08	17.924		
4,400.0	4,316.9	4,312.2	4,242.1	16.2	17.5	-114.05	-273.9	-577.7	599.4	566.4	32.95	18.190		
4,500.0	4,413.0	4,409.2	4,335.3	16.6	18.0	-114.12	-283.9	-602.5	623.8	590.0	33.83	18.441		
4,600.0	4,509.0	4,506.1	4,428.5	17.0	18.5	-114.19	-294.0	-627.2	648.2	613.5	34.70	18.678		
4,700.0	4,605.1	4,603.1	4,521.7	17.4	19.0	-114.26	-304.0	-652.0	672.6	637.0	35.59	18.901		
4,800.0	4,701.2	4,700.1	4,614.9	17.7	19.5	-114.32	-314.1	-676.8	697.1	660.6	36.47	19.113		
4,900.0	4,797.3	4,797.0	4,708.1	18.1	20.1	-114.37	-324.2	-701.5	721.5	684.1	37.36	19.312		
5,000.0	4,893.3	4,894.0	4,801.3	18.5	20.6	-114.42	-334.2	-726.3	745.9	707.7	38.25	19.502		
5,100.0	4,989.4	4,991.0	4,894.5	18.9	21.1	-114.47	-344.3	-751.1	770.3	731.2	39.14	19.682		
5,200.0	5,085.5	5,087.9	4,987.8	19.3	21.7	-114.52	-354.3	-775.8	794.8	754.7	40.03	19.853		
5,300.0	5,181.5	5,184.9	5,081.0	19.7	22.2	-114.56	-364.4	-800.6	819.2	778.3	40.93	20.015		
5,400.0	5,277.6	5,281.9	5,174.2	20.1	22.7	-114.60	-374.4	-825.3	843.6	801.8	41.83	20.170		
5,500.0	5,373.7	5,378.8	5,267.4	20.5	23.3	-114.64	-384.5	-850.1	868.0	825.3	42.72	20.317		
5,600.0	5,469.7	5,475.8	5,360.6	20.9	23.8	-114.68	-394.5	-874.9	892.5	848.8	43.63	20.458		
5,700.0	5,565.8	5,572.8	5,453.8	21.3	24.3	-114.71	-404.6	-899.6	916.9	872.4	44.53	20.592		
5,800.0	5,661.9	5,669.8	5,547.0	21.7	24.9	-114.74	-414.6	-924.4	941.3	895.9	45.43	20.720		

Anticollision Report

Company: NEW MEXICO Project: (SP) EDDY

Reference Site: MICHELADA FED COM

Site Error: 0.0 usft

Reference Well: MICHELADA 3 FED COM 134H

Well Error: 0.0 usft
Reference Wellbore OWB
Reference Design: PWP0

Local Co-ordinate Reference:

TVD Reference: GL @ 3225.0usft MD Reference: GL @ 3225.0usft

North Reference: Grid

Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma

Well MICHELADA 3 FED COM 134H

Database: Compass
Offset TVD Reference: Reference Datum

Offset De	sign: ME	ZCAL 10 F	ED COM	- MEZCAL	10 FED (COM 131H -	OWB - PWP0						Offset Site Error:	0.0 usft
Survey Prog Refe Measured Depth	Reference Offset Semi Major A) asured Vertical Measured Vertical Reference Offse epth Depth Depth				Major Axis Offset	Highside Toolface	Offset Wellbo	+E/-W	Dis Between Centres	Rule Assi tance Between Ellipses	gned: Minimum Separation	Separation Factor	Offset Well Error: Warning	0.0 usft
(usft)	(usft)	(usft)	(usft)	(usft)	(usft)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)			
5,900.0	5,757.9	5,766.7	5,640.2	22.1	25.4	-114.77	-424.7	-949.2	965.8	919.4	46.34	20.843		
6,000.0	5,854.0	5,863.7	5,733.4	22.5	26.0	-114.80	-434.8	-973.9	990.2	942.9	47.24	20.960		

Anticollision Report

NEW MEXICO Company: Project: (SP) EDDY

MICHELADA FED COM Reference Site:

0.0 usft Site Error:

Reference Well: MICHELADA 3 FED COM 134H

Well Error: 0.0 usft OWB Reference Wellbore Reference Design: PWP0

Local Co-ordinate Reference:

Well MICHELADA 3 FED COM 134H TVD Reference: GL @ 3225.0usft GL @ 3225.0usft MD Reference:

Grid North Reference:

Survey Calculation Method: Minimum Curvature

Output errors are at 2.00 sigma Compass Database: Offset TVD Reference: Reference Datum

Offset De	sign: ME	ZCAL 10 F	ED COM -	MEZCAL	10 FED (COM 132H -	OWB - PWP0						Offset Site Error:	0.0 usft
Survey Prog	ram: 0-1	MWD Off s	eat	Sami N	lajor Axis		Offset Wellbo	ore Centre	Diet	Rule Assi	gned:		Offset Well Error:	0.0 usft
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
0.0	0.0	2.0	0.0	0.0	0.0	-145.14	-85.6	-59.6	104.3	104.3	0.01	N/A		
100.0	100.0	102.0	100.0	0.4	0.4	-145.14	-85.6	-59.6	104.3	103.6	0.72	144.038		
200.0	200.0	202.0	200.0	0.7	0.7	-145.14	-85.6	-59.6	104.3	102.9	1.44	72.377		
300.0	300.0	302.0	300.0	1.1	1.1	-145.14	-85.6	-59.6	104.3	102.1	2.16	48.332		
400.0	400.0	402.0	400.0	1.4	1.4	-145.14	-85.6	-59.6	104.3	101.4	2.87	36.279		
500.0	500.0	502.0	500.0	1.8	1.8	-145.14	-85.6	-59.6	104.3	100.7	3.59	29.038		
600.0	600.0	602.0	600.0	2.2	2.2	-145.14	-85.6	-59.6	104.3	100.0	4.31	24.206		
700.0	700.0	702.0	700.0	2.5	2.5	-145.14	-85.6	-59.6	104.3	99.3	5.03	20.753		
800.0	800.0	802.0	800.0	2.9	2.9	-145.14	-85.6	-59.6	104.3	98.6	5.74	18.162		
900.0	900.0	902.0	900.0	3.2	3.2	-145.14	-85.6	-59.6	104.3	97.8	6.46	16.146		
1,000.0	1,000.0	1,002.0	1,000.0	3.6	3.6	-145.14	-85.6	-59.6	104.3	97.1	7.18	14.533		
1,100.0	1,100.0	1,102.0	1,100.0	3.9	4.0	-145.14	-85.6	-59.6	104.3	96.4	7.89	13.213		
1,200.0	1,200.0	1,202.0	1,200.0	4.3	4.3	-145.14	-85.6	-59.6	104.3	95.7	8.61	12.113		
1,300.0	1,300.0	1,302.0	1,300.0	4.7	4.7	-145.14	-85.6	-59.6	104.3	95.0	9.33	11.182		
1,400.0	1,400.0	1,402.0	1,400.0	5.0	5.0	-145.14	-85.6	-59.6	104.3	94.3	10.04	10.384		
1,466.0	1,466.0	1,468.0	1,466.0	5.3	5.3	-145.14	-85.6	-59.6	104.3	93.8	10.52	9.917 CC		
1,500.0	1,500.0	1,500.0	1,498.0	5.4	5.4	-145.14	-85.6	-59.6	104.3	93.6	10.75	9.702 ES		
1,600.0	1,600.0	1,594.9	1,592.9	5.7	5.7	-145.15	-88.2	-61.4	107.7	96.3	11.42	9.431 SF		
1,700.0	1,700.0	1,687.2	1,684.7	6.1	6.0	-145.18	-95.7	-66.5	117.5	105.5	12.02	9.778		
1,750.0	1,750.0	1,732.8	1,729.8	6.3	6.2	-145.19	-101.1	-70.3	124.8	112.5	12.30	10.147		
1,800.0	1,800.0	1,778.0	1,774.2	6.5	6.3	-85.96	-107.7	-74.8	133.7	121.1	12.57	10.633		
1,900.0	1,899.9	1,866.5	1,860.5	6.8	6.6	-86.71	-124.0	-86.0	155.8	142.7	13.07	11.923		
2,000.0	1,999.7	1,952.2	1,942.7	7.2	7.0	-87.98	-143.9	-99.7	183.7	170.2	13.51	13.601		
2,100.0	2,099.1	2,036.1	2,021.7	7.5	7.3	-89.41	-167.3	-115.7	217.3	203.4	13.95	15.583		
2,200.0	2,198.2	2,128.9	2,108.4	7.9	7.7	-91.19	-194.6	-134.5	253.3	238.7	14.61	17.333		
2,300.0	2,296.6	2,221.3	2,194.6	8.2	8.2	-93.04	-221.9	-153.3	289.8	274.5	15.29	18.947		
2,400.0	2,394.4	2,313.1	2,280.4	8.6	8.7	-94.93	-249.0	-171.9	327.0	311.0	15.99	20.450		
2,500.0	2,491.5	2,404.3	2,365.5	8.9	9.1	-96.81	-275.8	-190.3	365.1	348.4	16.70	21.861		
2,556.0	2,545.4	2,455.0	2,412.8	9.1	9.4	-97.86	-290.8	-200.6	386.9	369.8	17.11	22.617		
2,600.0	2,587.7	2,494.8	2,450.0	9.3	9.6	-99.00	-302.5	-208.7	404.3	386.9	17.43	23.196		
2,700.0	2,683.7	2,585.1	2,534.4	9.7	10.2	-101.26	-329.2	-227.0	444.2	426.0	18.17	24.447		
2,800.0	2,779.8	2,675.5	2,618.7	10.0	10.7	-103.17	-355.8	-245.3	484.6	465.7	18.92	25.611		
2,900.0	2,875.9	2,765.8	2,703.1	10.4	11.2	-103.17	-382.5	-243.5	525.4	505.7	19.68	26.693		
3,000.0	2,972.0	2,765.6	2,703.1	10.4	11.7	-104.76	-362.5 -409.1	-203.0 -281.9	566.5	546.0	20.45	27.697		
3,100.0	3,068.0	2,946.5	2,767.5	11.2	12.3	-100.10	-435.8	-300.2	607.8	586.6	21.23	28.629		
3,200.0	3,164.1	3,036.9	2,956.2	11.5	12.9	-107.30	-462.4	-318.5	649.4	627.3	22.02	29.494		
3,300.0	3,260.2	3,127.3	3,040.6	11.9	13.4	-109.33	-489.1	-336.8	691.0	668.2	22.81	30.298		
3,400.0	3,356.2	3,217.6	3,125.0	12.3	14.0	-110.15	-515.7	-355.1	732.9	709.3	23.61	31.046		
3,500.0	3,452.3	3,308.0	3,209.4	12.7	14.5	-110.88	-542.3	-373.4	774.8	750.4	24.41	31.743		
3,600.0	3,548.4	3,398.3	3,293.7	13.1	15.1	-111.54 112.13	-569.0	-391.7	816.8	791.6	25.22	32.393		
3,700.0	3,644.4	3,488.7	3,378.1	13.4	15.7	-112.13	-595.6	-410.0	859.0	832.9	26.03	32.999		
3,800.0	3,740.5	3,579.0	3,462.5	13.8	16.3	-112.67	-622.3	-428.3	901.1	874.3	26.85	33.567		
3,900.0	3,836.6	3,669.4	3,546.9	14.2	16.9	-113.16	-648.9	-446.6	943.4	915.7	27.67	34.099		
4,000.0	3,932.6	3,759.8	3,631.3	14.6	17.4	-113.61	-675.6	-464.9	985.7	957.2	28.49	34.597		

Anticollision Report

Company: NEW MEXICO Project: (SP) EDDY

Reference Site: MICHELADA FED COM

Site Error: 0.0 usft

Reference Well: MICHELADA 3 FED COM 134H

Well Error: 0.0 usft
Reference Wellbore OWB
Reference Design: PWP0

Local Co-ordinate Reference:

TVD Reference: GL @ 3225.0usft MD Reference: GL @ 3225.0usft

North Reference: Grid

Survey Calculation Method: Minimum Curvature

Well MICHELADA 3 FED COM 134H

		AMD											Offset Site Error:	0.0 us
urvey Prog Refe	ram: 0-l rence	MWD Off	set	Semi N	lajor Axis		Offset Wellbe	ore Centre	Dis	Rule Assi	gned:		Offset Well Error:	0.0 us
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
0.0	0.0	2.8	0.0	0.0	0.0	-161.46	-94.9	-31.8	100.1	100.1	0.01	9,779.597		
100.0	100.0	102.8	100.0	0.4	0.4	-161.46	-94.9	-31.8	100.1	99.3	0.73	137.639		
200.0	200.0	202.8	200.0	0.7	0.7	-161.46	-94.9	-31.8	100.1	98.6	1.44	69.298		
300.0	300.0	302.8	300.0	1.1	1.1	-161.46	-94.9	-31.8	100.1	97.9	2.16	46.306		
400.0	400.0	402.8	400.0	1.4	1.4	-161.46	-94.9	-31.8	100.1	97.2	2.88	34.770		
500.0	500.0	502.8	500.0	1.8	1.8	-161.46	-94.9	-31.8	100.1	96.5	3.59	27.835		
600.0	600.0	602.8	600.0	2.2	2.2	-161.46	-94.9	-31.8	100.1	95.7	4.31	23.207		
700.0	700.0	702.8	700.0	2.5	2.5	-161.46	-94.9	-31.8	100.1	95.0	5.03	19.898		
800.0	800.0	802.8	800.0	2.9	2.9	-161.46	-94.9	-31.8	100.1	94.3	5.75	17.415		
900.0	900.0	902.8	900.0	3.2	3.2	-161.46	-94.9	-31.8	100.1	93.6	6.46	15.483		
1,000.0	1,000.0	1,002.8	1,000.0	3.6	3.6	-161.46	-94.9	-31.8	100.1	92.9	7.18	13.937		
1,100.0	1,100.0	1,102.8	1,100.0	3.9	4.0	-161.46	-94.9	-31.8	100.1	92.2	7.90	12.672		
1,200.0	1,200.0	1,202.8	1,200.0	4.3	4.3	-161.46	-94.9	-31.8	100.1	91.4	8.61	11.617		
1,300.0	1,300.0	1,302.8	1,300.0	4.7	4.7	-161.46	-94.9	-31.8	100.1	90.7	9.33	10.724		
1,400.0	1,400.0	1,402.8	1,400.0	5.0	5.0	-161.46	-94.9	-31.8	100.1	90.0	10.05	9.959		
1,500.0	1,500.0	1,502.8	1,500.0	5.4	5.4	-161.46	-94.9	-31.8	100.1	89.3	10.76	9.296		
1,600.0	1,600.0	1,602.8	1,600.0	5.7	5.7	-161.46	-94.9	-31.8	100.1	88.6	11.48	8.715		
1,700.0	1,700.0	1,702.8	1,700.0	6.1	6.1	-161.46	-94.9	-31.8	100.1	87.9	12.20	8.203		
1,707.3	1,707.3	1,710.1	1,707.3	6.1	6.1	-161.46	-94.9	-31.8	100.1	87.8	12.25	8.168 CC		
1,750.0	1,750.0	1,752.6	1,749.8	6.3	6.3	-161.46	-94.9	-31.8	100.1	87.5	12.56	7.970 ES		
1,800.0	1,800.0	1,800.0	1,797.2	6.5	6.4	-102.41	-95.7	-32.1	101.1	88.2	12.89	7.841 SF		
1,900.0	1,899.9	1,892.2	1,889.2	6.8	6.7	-103.82	-101.5	-34.3	108.5	95.0	13.49	8.045		
2,000.0	1,999.7	1,983.6	1,979.8	7.2	7.0	-106.09	-112.7	-38.5	123.4	109.3	14.05	8.784		
2,100.0	2,099.1	2,072.6	2,067.1	7.5	7.3	-108.53	-128.8	-44.5	145.7	131.1	14.55	10.009		
2,200.0	2,198.2	2,158.4	2,150.1	7.9	7.7	-110.69	-149.0	-52.0	175.2	160.2	15.01	11.674		
2,300.0	2,296.6	2,240.3	2,228.0	8.2	8.0	-112.38	-172.7	-60.9	211.7	196.3	15.42	13.724		
2,400.0	2,394.4	2,318.1	2,300.5	8.6	8.3	-113.57	-199.0	-70.7	254.7	238.9	15.81	16.112		
2,500.0	2,491.5	2,391.3	2,367.3	8.9	8.6	-114.32	-227.1	-81.1	303.6	287.5	16.16	18.793		
2,556.0	2,545.4	2,430.2	2,402.1	9.1	8.8	-114.56	-243.4	-87.2	333.4	317.1	16.34	20.402		
2,600.0	2,587.7	2,459.9	2,428.4	9.3	9.0	-115.17	-256.3	-92.0	357.9	341.5	16.48	21.713		
2,700.0	2,683.7	2,524.6	2,484.6	9.7	9.3	-116.15	-286.4	-103.2	416.2	399.4	16.78	24.799		
2,800.0	2,779.8	2,590.4	2,540.3	10.0	9.7	-116.78	-319.2	-115.5	477.7	460.6	17.15	27.852		
2,900.0	2,875.9	2,668.4	2,605.9	10.4	10.2	-117.32	-358.8	-130.3	540.1	522.3	17.79	30.352		
3,000.0	2,972.0	2,746.5	2,671.5	10.8	10.8	-117.75	-398.4	-145.0	602.5	584.1	18.45	32.655		
3,100.0	3,068.0	2,824.5	2,737.1	11.2	11.3	-118.10	-438.0	-159.8	664.9	645.8	19.12	34.778		
3,200.0	3,164.1	2,902.6	2,802.7	11.5	11.9	-118.39	-477.7	-174.6	727.4	707.6	19.80	36.737		
3,300.0	3,260.2	2,980.7	2,868.3	11.9	12.5	-118.63	-517.3	-189.4	789.8	769.4	20.49	38.543		
3,400.0	3,356.2	3,058.7	2,933.9	12.3	13.1	-118.84	-556.9	-204.2	852.3	831.1	21.19	40.214		
3,500.0	3,452.3	3,136.8	2,933.9	12.3	13.1	-110.04	-596.5	-204.2	914.8	892.9	21.19	41.761		
3,600.0	3,548.4	3,214.8	3,065.1	13.1	14.3	-119.02	-636.2	-219.0	914.6	954.6	22.62	43.196		

Anticollision Report

Company: NEW MEXICO Project: (SP) EDDY

Reference Site: MICHELADA FED COM

Site Error: 0.0 usft

Reference Well: MICHELADA 3 FED COM 134H

Well Error: 0.0 usft
Reference Wellbore OWB
Reference Design: PWP0

Local Co-ordinate Reference:

TVD Reference:
MD Reference:

North Reference: Grid

Survey Calculation Method: Minimum Curvature

Well MICHELADA 3 FED COM 134H

GL @ 3225.0usft

GL @ 3225.0usft

Survey Prog	ram: 0-l	MWD								Rule Assi	gned:		Offset Well Error:	0.0 ust
Refe Measured	rence Vertical	Offs Measured	Vertical	Semi M Reference	lajor Axis Offset	Highside	Offset Wellb		Between	tance Between	Minimum	Separation	Warning	
Depth (usft)	Depth (usft)	Depth (usft)	Depth (usft)	(usft)	(usft)	Toolface (°)	+N/-S (usft)	+E/-W (usft)	Centres (usft)	Ellipses (usft)	Separation (usft)	Factor		
0.0	0.0	3.5	0.0	0.0	0.0	-178.45	-104.0	-2.8	104.1	104.0	0.01	8,168.132		
100.0	100.0	103.5	100.0	0.4	0.4	-178.45	-104.0	-2.8	104.1	103.3	0.73	142.645		
200.0	200.0	203.5	200.0	0.7	0.7	-178.45	-104.0	-2.8	104.1	102.6	1.45	71.941		
300.0	300.0	303.5	300.0	1.1	1.1	-178.45	-104.0	-2.8	104.1	101.9	2.16	48.100		
400.0	400.0	403.5	400.0	1.4	1.4	-178.45	-104.0	-2.8	104.1	101.2	2.88	36.127		
500.0	500.0	503.5	500.0	1.8	1.8	-178.45	-104.0	-2.8	104.1	100.5	3.60	28.927		
600.0	600.0	603.5	600.0	2.2	2.2	-178.45	-104.0	-2.8	104.1	99.7	4.31	24.120		
700.0	700.0	703.5	700.0	2.5	2.5	-178.45	-104.0	-2.8	104.1	99.0	5.03	20.683		
800.0	800.0	803.5	800.0	2.9	2.9	-178.45	-104.0	-2.8	104.1	98.3	5.75	18.103		
900.0	900.0	903.5	900.0	3.2	3.2	-178.45	-104.0	-2.8	104.1	97.6	6.47	16.095		
1,000.0	1,000.0	1,003.5	1,000.0	3.6	3.6	-178.45	-104.0	-2.8	104.1	96.9	7.18	14.489		
1,100.0	1,100.0	1,103.5	1,100.0	3.9	4.0	-178.45	-104.0	-2.8	104.1	96.2	7.90	13.174		
1,200.0	1,200.0	1,203.5	1,200.0	4.3	4.3	-178.45	-104.0	-2.8	104.1	95.4	8.62	12.077		
1,300.0	1,300.0	1,303.5	1,300.0	4.7	4.7	-178.45	-104.0	-2.8	104.1	94.7	9.33	11.150		
1,400.0	1,400.0	1,403.5	1,400.0	5.0	5.0	-178.45	-104.0	-2.8	104.1	94.0	10.05	10.354		
1,500.0	1,500.0	1,503.5	1,500.0	5.4	5.4	-178.45	-104.0	-2.8	104.1	93.3	10.77	9.665		
1,600.0	1,600.0	1,603.5	1,600.0	5.7	5.7	-178.45	-104.0	-2.8	104.1	92.6	11.48	9.061		
1,700.0	1,700.0	1,703.5	1,700.0	6.1	6.1	-178.45	-104.0	-2.8	104.1	91.9	12.20	8.529		
1,750.0	1,750.0	1,753.5	1,750.0	6.3	6.3	-178.45	-104.0	-2.8	104.1	91.5	12.56	8.285 CC		
1,800.0	1,800.0	1,803.5	1,800.0	6.5	6.5	-119.41	-104.0	-2.8	104.3	91.4	12.92	8.073 ES		
1,900.0	1,899.9	1,903.4	1,899.9	6.8	6.8	-121.02	-104.0	-2.8	106.0	92.4	13.62	7.782		
2,000.0	1,999.7	2,000.0	1,996.5	7.2	7.2	-123.95	-104.0	-2.8	109.8	95.5	14.32	7.671 SF		
2,100.0	2,099.1	2,095.4	2,091.9	7.5	7.5	-127.27	-107.1	-3.7	119.1	104.1	14.98	7.952		
2,200.0	2,198.2	2,186.3	2,182.3	7.9	7.8	-129.79	-115.6	-6.3	136.7	121.2	15.56	8.785		
2,300.0	2,296.6	2,274.7	2,269.5	8.2	8.1	-131.44	-129.2	-10.3	162.2	146.1	16.10	10.076		
2,400.0	2,394.4	2,359.8	2,352.5	8.6	8.4	-132.31	-147.1	-15.6	195.2	178.6	16.60	11.761		
2,500.0	2,491.5	2,440.9	2,430.5	8.9	8.7	-132.59	-168.6	-22.0	235.1	218.1	17.05	13.789		
2,556.0	2,545.4	2,440.9	2,430.3	9.1	8.8	-132.59	-181.8	-25.9	260.3	243.0	17.03	15.769		
2,600.0	2,587.7	2,517.8	2,503.1	9.3	9.0	-132.77	-192.8	-29.2	281.2	263.8	17.47	16.102		
2,700.0	2,683.7	2,590.9	2,570.8	9.7	9.3	-132.85	-219.2	-37.0	331.6	313.8	17.84	18.590		
2,800.0	2,779.8	2,660.3	2,633.7	10.0	9.6	-132.59	-247.3	-45.4	385.6	367.4	18.17	21.216		
2,900.0	2,875.9	2,726.0	2,691.8	10.4	9.9	-132.13	-276.6	-54.1	442.9	424.5	18.48	23.973		
3,000.0	2,972.0	2,720.0	2,745.3	10.4	10.2	-132.13	-306.6	-63.0	503.4	484.6	18.75	26.851		
3,100.0	3,068.0	2,767.9	2,745.3	11.2	10.2	-131.57	-336.8	-63.0 -72.0	566.7	547.7	18.99	29.840		
3,200.0	3,164.1	2,900.0	2,794.4	11.5	10.6	-130.96	-366.2	-72.0 -80.7	632.7	613.5	19.19	32.973		
3,300.0	3,260.2	2,952.7	2,880.5	11.9	11.3	-130.36	-396.7	-89.8	701.2	681.8	19.19	36.122		
2 400 0	2 050 0	2 000 0	2.047.0	40.0	44.0	100.04	405.0	00.0	774.0	750.4	40.57	20.440		
3,400.0	3,356.2	3,000.0	2,917.2	12.3	11.6	-129.21	-425.3	-98.3	771.9 844.7	752.4 825.0	19.57	39.440		
3,500.0	3,452.3	3,046.5	2,952.3	12.7	12.0	-128.65	-454.4	-107.0			19.76	42.749		
3,600.0	3,548.4	3,100.0	2,991.5	13.1	12.4	-128.01	-489.4	-117.3	919.6	899.5	20.10	45.755		
3,700.0	3,644.4	3,129.1	3,012.3	13.4	12.6	-127.66	-509.0	-123.2	995.9	975.9	20.06	49.657		

Anticollision Report

Company: NEW MEXICO Project: (SP) EDDY

Reference Site: MICHELADA FED COM

Site Error: 0.0 usft

Reference Well: MICHELADA 3 FED COM 134H

Well Error: 0.0 usft
Reference Wellbore OWB
Reference Design: PWP0

Local Co-ordinate Reference:

TVD Reference: GL @ 3225.0usft MD Reference: GL @ 3225.0usft

North Reference: Grid

Survey Calculation Method: Minimum Curvature

Well MICHELADA 3 FED COM 134H

rvey Progr	am: 0	MWD+IFR1+M	S							Rule Assi	anod:		Offset Well Error:	0.0 usf
Refer	rence	Offs	set		lajor Axis		Offset Wellbe	ore Centre		ance	_			0.0 us
leasured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
0.0	0.0	0.0	0.0	0.0	0.0	108.09	-9.1	27.8	29.3					
100.0	100.0	100.0	100.0	0.4	0.4	108.09	-9.1	27.8	29.3	28.6	0.72	40.822		
200.0	200.0	200.0	200.0	0.7	0.7	108.09	-9.1	27.8	29.3	27.8	1.43	20.411		
300.0	300.0	300.0	300.0	1.1	1.1	108.09	-9.1	27.8	29.3	27.1	2.15	13.607		
400.0	400.0	400.0	400.0	1.4	1.4	108.09	-9.1	27.8	29.3	26.4	2.87	10.206		
500.0	500.0	500.0	500.0	1.8	1.8	108.09	-9.1	27.8	29.3	25.7	3.58	8.164		
600.0	600.0	600.0	600.0	2.2	2.2	108.09	-9.1	27.8	29.3	25.0	4.30	6.804		
700.0	700.0	700.0	700.0	2.5	2.5	108.09	-9.1	27.8	29.3	24.2	5.02	5.832		
0.008	800.0	800.0	800.0	2.9	2.9	108.09	-9.1	27.8	29.3	23.5	5.74	5.103		
900.0	900.0	900.0	900.0	3.2	3.2	108.09	-9.1	27.8	29.3	22.8	6.45	4.536		
1,000.0	1,000.0	1,000.0	1,000.0	3.6	3.6	108.09	-9.1	27.8	29.3	22.1	7.17	4.082		
1,100.0	1,100.0	1,100.0	1,100.0	3.9	3.9	108.09	-9.1	27.8	29.3	21.4	7.89	3.711		
1,200.0	1,200.0	1,200.0	1,200.0	4.3	4.3	108.09	-9.1	27.8	29.3	20.7	8.60	3.402		
1,300.0	1,300.0	1,300.0	1,300.0	4.7	4.7	108.09	-9.1	27.8	29.3	19.9	9.32	3.140		
1,400.0 1,500.0	1,400.0 1,500.0	1,400.0 1,500.0	1,400.0 1,500.0	5.0 5.4	5.0 5.4	108.09 108.09	-9.1 -9.1	27.8 27.8	29.3 29.3	19.2 18.5	10.04 10.75	2.916 2.721		
1,600.0	1,600.0	1,600.0	1,600.0	5.7	5.7	108.09	-9.1	27.8	29.3	17.8	11.47	2.551		
1,700.0	1,700.0	1,700.0	1,700.0	6.1	6.1	108.09	-9.1	27.8	29.3	17.1	12.19	2.401		
1,750.0	1,750.0	1,750.0	1,750.0	6.3	6.3	108.09	-9.1	27.8	29.3	16.7	12.55	2.333 CC, E	S	
1,800.0	1,800.0	1,800.0	1,800.0	6.5	6.5	167.53	-9.1	27.8	29.7	16.8	12.90	2.301 SF		
1,900.0	1,899.9	1,899.9	1,899.9	6.8	6.8	168.82	-9.1	27.8	33.1	19.5	13.61	2.433		
2,000.0	1,999.7	1,999.7	1,999.7	7.2	7.2	170.73	-9.1	27.8	40.0	25.7	14.32	2.792		
2,100.0	2,099.1	2,100.5	2,100.5	7.5	7.5	171.47	-7.6	26.9	48.9	33.9	15.03	3.254		
2,200.0	2,198.2	2,201.6	2,201.4	7.9	7.9	170.44	-3.1	24.1	58.4	42.7	15.72	3.716		
2,300.0	2,296.6	2,302.8	2,302.3	8.2	8.3	168.40	4.5	19.3	68.6	52.2	16.41	4.180		
2,400.0	2,394.4	2,404.2	2,402.9	8.6	8.6	165.78	15.0	12.7	79.5	62.4	17.09	4.653		
2,500.0	2,491.5	2,505.6	2,503.0	8.9	9.0	162.85	28.6	4.2	91.3	73.6	17.77	5.141		
2,556.0	2,545.4	2,562.4	2,558.8	9.1	9.2	161.14	37.5	-1.4	98.4	80.2	18.15	5.422		
2,600.0	2,587.7	2,607.2	2,602.6	9.3	9.3	159.76	45.2	-6.2	103.9	85.4	18.45	5.630		
2,700.0	2,683.7	2,708.9	2,701.7	9.7	9.7	156.11	64.8	-18.5	114.8	95.7	19.14	5.999		
2,800.0	2,779.8	2,810.7	2,799.9	10.0	10.1	151.79	87.4	-32.7	124.1	104.2	19.84	6.251		
2,900.0	2,875.9	2,912.2	2,896.9	10.4	10.4	146.77	112.9	-48.7	132.0	111.5	20.57	6.419		
3,000.0	2,972.0	3,013.3	2,992.3	10.8	10.8	141.06	141.2	-66.4	139.4	118.1	21.33	6.536		
3,100.0	3,068.0	3,113.6	3,085.8	11.2	11.2	134.72	172.0	-85.7	146.8	124.7	22.11	6.640		
3,200.0	3,164.1	3,213.0	3,177.1	11.5	11.5	127.87	205.3	-106.6	155.1	132.2	22.90	6.771		
3,300.0	3,260.2	3,311.2	3,265.9	11.9	11.9	120.68	240.7	-128.8	165.0	141.3	23.68	6.966		
3,400.0	3,356.2	3,408.0	3,352.0	12.3	12.2	113.40	278.2	-152.3	177.4	152.9	24.43	7.259		
3,500.0	3,452.3	3,503.2	3,435.2	12.7	12.6	106.28	317.5	-176.9	192.9	167.8	25.13	7.676		
3,600.0	3,548.4	3,598.1	3,516.9	13.1	13.0	99.64	358.3	-202.5	211.7	185.9	25.77	8.215		
3,700.0	3,644.4	3,693.4	3,598.9	13.4	13.4	94.04	399.5	-228.3	233.0	206.6	26.41	8.822		
3,800.0	3,740.5	3,788.6	3,680.8	13.8	13.7	89.37	440.6	-254.1	256.2	229.1	27.07	9.465		
3,900.0	3,836.6	3,883.9	3,762.8	14.2	14.1	85.47	481.7	-279.9	280.8	253.0	27.73	10.124		
4,000.0	3,932.6	3,979.1	3,844.7	14.6	14.5	82.19	522.8	-305.6	306.4	278.0	28.42	10.781		
4,100.0	4,028.7	4,074.4	3,926.7	15.0	14.9	79.41	564.0	-331.4	332.8	303.7	29.12	11.429		
4,200.0 4,300.0	4,124.8 4,220.8	4,169.6 4,264.9	4,008.6 4,090.6	15.4 15.8	15.3 15.8	77.04 74.99	605.1 646.2	-357.2 -383.0	359.9 387.5	330.1 356.9	29.84 30.58	12.060 12.672		
4,400.0	4,316.9	4,360.1	4,172.6	16.2	16.2	73.22	687.3	-408.8	415.5	384.1	31.33	13.263		
4,500.0	4,413.0	4,455.4	4,254.5	16.6	16.6	71.66	728.4	-434.5	443.8	411.7	32.09	13.831		
4,600.0	4,509.0	4,550.6	4,336.5	17.0	17.0	70.29	769.6	-460.3	472.4	439.5	32.86	14.377		
4,700.0	4,605.1	4,645.9	4,418.4	17.4	17.4	69.08	810.7	-486.1	501.2	467.5	33.63	14.900		
4,800.0	4,701.2	4,741.1	4,500.4	17.7	17.9	68.00	851.8	-511.9	530.2	495.7	34.42	15.402		
4,900.0	4,797.3	4,836.4	4,582.3	18.1	18.3	67.03	892.9	-537.6	559.3	524.1	35.22	15.882		

Anticollision Report

NEW MEXICO Company: Project: (SP) EDDY

Reference Site: MICHELADA FED COM

Site Error: 0.0 usft

Reference Well: MICHELADA 3 FED COM 134H

Well Error: 0.0 usft OWB Reference Wellbore Reference Design: PWP0

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

GL @ 3225.0usft

GL @ 3225.0usft

Well MICHELADA 3 FED COM 134H

Grid

Survey Calculation Method: Minimum Curvature 2.00 sigma

Output errors are at Database:

Compass Offset TVD Reference: Reference Datum

Offset Des	sign: MIC	CHELADA I	FED COM	- MICHEL	ADA 3 FE	D COM 133I	H - OWB - PW	'P0					Offset Site Error:	0.0 usf
Survey Progra		MWD+IFR1+M: Offs		Semi N	laior Axis		Offset Wellbo	ore Centre	Dis	Rule Assig	gned:		Offset Well Error:	0.0 usf
Measured Depth	Vertical Depth	Measured Depth	Vertical Depth	Reference	Offset	Highside Toolface	+N/-S (usft)	+E/-W (usft)	Between Centres	Between Ellipses	Minimum Separation	Separation Factor	Warning	
(usft)	(usft)	(usft)	(usft)	(usft)	(usft)	(°)		, ,	(usft)	(usft)	(usft)			
5,000.0	4,893.3	4,931.6	4,664.3	18.5	18.7	66.15	934.1	-563.4	588.6	552.6	36.02	16.342		
5,100.0	4,989.4	5,026.8	4,746.2	18.9	19.2	65.36	975.2	-589.2	618.0	581.1	36.82	16.783		
5,200.0	5,085.5	5,122.1	4,828.2	19.3	19.6	64.64	1,016.3	-615.0	647.5	609.8	37.63	17.205		
5,300.0	5,181.5	5,217.3	4,910.1	19.7	20.0	63.98	1,057.4	-640.8	677.0	638.6	38.45	17.609		
5,400.0	5,277.6	5,312.6	4,992.1	20.1	20.5	63.38	1,098.5	-666.5	706.7	667.4	39.27	17.997		
5,500.0	5,373.7	5,407.8	5,074.1	20.5	20.9	62.82	1,139.7	-692.3	736.4	696.3	40.09	18.369		
5,600.0	5,469.7	5,503.1	5,156.0	20.9	21.4	62.31	1,180.8	-718.1	766.2	725.3	40.92	18.726		
5,700.0	5,565.8	5,598.3	5,238.0	21.3	21.8	61.83	1,221.9	-743.9	796.0	754.3	41.75	19.068		
5,800.0	5,661.9	5,693.6	5,319.9	21.7	22.3	61.39	1,263.0	-769.7	825.9	783.3	42.58	19.397		
5,900.0	5,757.9	5,788.8	5,401.9	22.1	22.7	60.99	1,304.2	-795.4	855.8	812.4	43.41	19.713		
6,000.0	5,854.0	5,884.1	5,483.8	22.5	23.2	60.60	1,345.3	-821.2	885.7	841.5	44.25	20.016		
6,100.0	5,950.1	5,979.3	5,565.8	22.9	23.6	60.25	1,386.4	-847.0	915.7	870.6	45.09	20.309		
6,200.0	6,046.1	6,074.6	5,647.7	23.3	24.1	59.91	1,427.5	-872.8	945.7	899.8	45.93	20.590		
6,300.0	6,142.2	6,169.8	5,729.7	23.7	24.5	59.60	1,468.6	-898.6	975.8	929.0	46.78	20.860		

Anticollision Report

Company: NEW MEXICO Project: (SP) EDDY

Reference Site: MICHELADA FED COM

Site Error: 0.0 usft

Reference Well: MICHELADA 3 FED COM 134H

Well Error: 0.0 usft
Reference Wellbore OWB
Reference Design: PWP0

Local Co-ordinate Reference:

 TVD Reference:
 GL @ 3225.0usft

 MD Reference:
 GL @ 3225.0usft

North Reference: Grid

 Survey Calculation Method:
 Minimum Curvature

 Output errors are at
 2.00 sigma

 Database:
 Compass


 Offset TVD Reference:
 Reference Datum

Reference Depths are relative to GL @ 3225.0usft
Offset Depths are relative to Offset Datum
Central Meridian is 104° 20' 0.000 W

Coordinates are relative to: MICHELADA 3 FED COM 134H Coordinate System is US State Plane 1983, New Mexico Eastern Zone

Well MICHELADA 3 FED COM 134H

Grid Convergence at Surface is: 0.21°



Anticollision Report

Company: NEW MEXICO Project: (SP) EDDY

Reference Site: MICHELADA FED COM

Site Error: 0.0 usft

Reference Well: MICHELADA 3 FED COM 134H

Well Error: 0.0 usft
Reference Wellbore OWB
Reference Design: PWP0

Local Co-ordinate Reference:

TVD Reference: GL @ 3225.0usft MD Reference: GL @ 3225.0usft

North Reference: Grid

Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma


Database: Offset TVD Reference: 2.00 sigma Compass

Well MICHELADA 3 FED COM 134H

Offset TVD Reference: Reference Datum

Reference Depths are relative to GL @ 3225.0usft
Offset Depths are relative to Offset Datum
Central Meridian is 104° 20' 0.000 W

Coordinates are relative to: MICHELADA 3 FED COM 134H Coordinate System is US State Plane 1983, New Mexico Eastern Zone



R-111-Q Program Being Utilized for Michelada & Mezcal


The WBD below depicts the cement design required for R111Q.

The annulus between the production and intermediate casing strings shall be actively monitored for pressure during hydraulic fracturing operations. If pressure communication is observed, indicating a possible production casing failure, hydraulic fracturing operations must immediately cease, and source of the pressure increase shall be investigated. During hydraulic fracturing operations, a pressure relief valve or appropriate venting system shall be installed to relieve pressure in the event of a production casing failure. The opening pressure of any pressure relief valves must be set below 50% of the intermediate casing burst rating. If the well design features an uncemented intermediate casing shoe (for example as shown in Exhibit B, Figure B) and the well approaches to within ¼ mile of an offset well drilling, completing or producing from the Delaware Mountain Group, then the pressure relief valve opening pressure shall be set no more than 1000 psi and at no time shall the pressure on the annulus be allowed to exceed 1000 psi. This requirement can be waived by the offset well operator.


Production cement will be 500' below the 2nd intermediate shoe with 0% excess leaving the DMG un-cemented as a pressure relief zone.

Bradenhead operations will be performed within 180 days of completing hydraulic fracturing operations, tying back cement at least 500' inside the 2nd intermediate shoe but below Marker Bed 126.

R-111-Q Example Program Being Utilized for Michelada & Mezcal



[Figure E] 4 String – Uncemented Annulus between 2nd Intermediate and Production Casing Strings



Permian Resources BOP Break Testing Variance Procedure

Subject: Request for a Variance Allowing break Testing of the Blowout Preventer Equipment (BOPE). Permian Resources requests a variance to ONLY test broken pressure seals on the BOPE and function test BOP when skidding a drilling rig between multiple wells on a pad.

Background

Title 43 CFR 3172, Drilling Operations, Sections 6.b.9.iv states that the BOP test must be performed whenever any seal subject to test pressure is broken. The current interpretation of the Bureau of Land Management (BLM) requires a complete BOP test and not just a test of the affected component. 43 CFR 3172.13, Variances from minimum standards states, "An operator may request the authorized officer to approve a variance from any of the minimum standards prescribed in §§ 3172.6 through 3172.12. All such requests shall be submitted in writing to the appropriate authorized officer and provide information as to the circumstances which warrant approval of the variance(s) requested and the proposed alternative methods by which the related minimum standard(s) are to be satisfied. The authorized officer, after considering all relevant factors, if appropriate, may approve the requested variance(s) if it is determined that the proposed alternative(s) meet or exceed the objectives of the applicable minimum standard(s).". Permian Resources feels the break testing the BOPE is such a situation. Therefore, as per 43 CFR 3172.13, Permian Resources submits this request for the variance.

Supporting Documentation

The language used in 43 CFR 3172 became effective on December 19, 1988 and has remained the standard for regulating BLM onshore drilling operations for over 30 years. During this time, there have been significant changes in drilling technology. The BLM continues to use the variance request process to allow for the use of modern technology and acceptable engineering practices that have arisen since 43 CFR 3172 was originally released. The Permian Resources drilling rig fleet has many modern upgrades that allow the intact BOP stack to be moved between well slots on a multi-well pad, as well as, wellhead designs that incorporate quick connects facilitating release of the BOP from the wellhead without breaking any BOP stack components apart. These technologies have been used extensively offshore, and other regulators, API, and many operators around the world have endorsed break testing as safe and reliable.

Figure 1: Winch System attached to BOP Stack



Figure 2: BOP Winch System



American Petroleum Institute (API) standards, specification and recommended practices are considered the industry standard and are consistently utilized and referenced by the industry. 43 CFR 3172 recognizes API recommended Practices (RP) 53 in its original development. API Standard 53, Well Control Equipment Systems for Drilling Wells (Fifth Edition, December 2018, Annex C, Table C.4) recognizes break testing as an acceptable practice. Specifically, API Standard 53, Section 5.3.7.1 states "A pressure test of the pressure containing component shall be performed following the disconnection or repair, limited to the affected component." See Table C.4 below for reference.

52	API STANDARD	53			
Ta	ble C.4—Initial Pressure Te	esting, Surface BOP Stacks			
	Pressure Test—Low	Pressure Test—High Pressure**			
Component to be Pressure Tested	Pressure** psig (MPa)	Change Out of Component, Elastomer, or Ring Gasket	No Change Out of Component, Elastomer, or Ring Gasket		
Annular preventer	250 to 350 (1.72 to 2.41)	RWP of annular preventer	MASP or 70% annular RWP, whichever is lower.		
Fixed pipe, variable bore, blind, and BSR preventers∞	250 to 350 (1.72 to 2.41)	RWP of ram preventer or wellhead system, whichever is lower	ІТР		
Choke and kill line and BOP side outlet valves below ram preventers (both sides)	250 to 350 (1.72 to 2 41)	RWP of side outlet valve or wellhead system, whichever is lower	ІТР		
Choke manifold—upstream of chokes*	250 to 350 (1.72 to 2.41)	RWP of ram preventers or wellhead system, whichever is lower	ITP		
Choke manifold—downstream of chokes*	250 to 350 (1.72 to 2.41)	RWP of valve(s), line(s), or N whichever is lower	MASP for the well program,		
Kelly, kelly valves, drill pipe safety valves, IBOPs	250 to 350 (1.72 to 2.41)	MASP for the well program			
No visible leaks. The pressure shall remain stable		ressure shall not decrease below the allest OD drill pipe to be used in well p			
	from one wellhead to another within when the integrity of a pressure sea	the 21 days, pressure testing is required is broken.	uired for pressure-containing and		
For surface offshore operations, the	e rom BOPs shall be pressure test land operations, the ram BOPs sha	led with the ram locks engaged and ill be pressure tested with the ram loc	the closing and locking pressure cks engaged and the closing and		

The Bureau of Safety and Environmental Enforcement (BSEE), Department of Interior, has also utilized the API standards, specification and best practices in the development of its offshore oil and gas regulations and incorporates them by reference within its regulations.


Break testing has been approved by the BLM in the past with other operators based on the detailed information provided in this document.

Permian Resources feels break testing and our current procedures meet the intent of 43 CFR 3172 and often exceed it. There has been no evidence that break testing results in more components failing than seen on full BOP tests. Permian Resources internal standards require complete BOPE tests more often than that of 43 CFR 3172 (every 21 days). In addition to function testing the annular, pipe rams and blind rams after each BOP nipple up, Permian Resources performs a choke drill with the rig crew prior to drilling out every casing shoe. This is additional training for the rig crew that exceeds the requirements of 43 CFR 3172.

Procedures

- 1) Permian Resources will use this document for our break testing plan for New Mexico Delaware Basin. The summary below will be referenced in the APD or Sundry Notice and receive approval prior to implementing this variance.
- 2) Permian Resources will perform BOP break testing on multi-wells pads where multiple intermediate sections can be drilled and cased within the 21-day BOP test window.
 - a)A full BOP test will be conducted on the first well on the pad.
- b) The first intermediate hole section drilled on the pad will be the deepest. All the remaining hole sections will be the same formation depth or shallower.
- c) A full BOP test will be required if the intermediate hole section being drilled has a MASP over 5M.
 - d) A full BOP test will be required prior to drilling any production hole.
- 3) After performing a complete BOP test on the first well, the intermediate hole section will be drilled and cased, two breaks would be made on the BOP equipment.
 - a) Between the HCV valve and choke line connection
 - b)Between the BOP quick connect and the wellhead
- 4) The BOP is then lifted and removed from the wellhead by a hydraulic system.
- 5) After skidding to the next well, the BOP is moved to the wellhead by the same hydraulic system and installed.
- 6) The connections mentioned in 3a and 3b will then be reconnected.
- 7) Install test plug into the wellhead using test joint or drill pipe.
- 8) A shell test is performed against the upper pipe rams testing the two breaks.
- 9) The shell test will consist of a 250 psi low test and a high test to the value submitted in the APD or Sundry (e.g. 5,000 psi or 10,000psi).
- 10) Function tests will be performed on the following components: lower pipe rams, blind rams, and annular.
- 11) For a multi-well pad the same two breaks on the BOP would be made and on the next wells and steps 4 through 10 would be repeated.
- 12) A second break test would only be done if the intermediate hole section being drilled could not be completed within the 21 day BOP test window.

Note: Picture below highlights BOP components that will be tested during batch operations



Summary


A variance is requested to ONLY test broken pressure seals on the BOP equipment when moving from wellhead to wellhead which is in compliance with API Standard 53. API Standard 53 states, that for pad drilling operations, moving from one wellhead to another within 21 days, pressure testing is required for pressure-containing and pressure-controlling connections when the integrity of a pressure seal is broken.

The BOP will be secured by a hydraulic carrier or cradle. The BLM will be contacted if a Well Control

event occurs prior to the commencement of a BOPE Break Testing operation.

Based on public data and the supporting documentation submitted herein to the BLM, we will request permission to ONLY retest broken pressure seals if the following conditions are met:

- 1) After a full BOP test is conducted on the first well on the pad.
- 2) The first intermediate hole section drilled on the pad will be the deepest. All the remaining hole sections will be the same depth or shallower.
- 3) A full BOP test will be required if the intermediate hole section being drilled has a MASP over 5M.
- 4) A full BOP test will be required prior to drilling the production hole.



Permian Resources Multi-Well Pad Batch Drilling Procedure

<u>Surface Casing</u> - PR intends to Batch set all surface casing to a depth approved in the APD. Surface Holes will be batch drilled by a rig. Appropriate notifications will be made prior to spudding the well, running and cementing casing and prior to skidding to the rig to the next well on pad.

- 1. Drill Surface hole to Approved Depth with Rig and perform wellbore cleanup cycles. Trip out and rack back drilling BHA.
- 2. Run and land planned surface casing see Illustration 1-1 Below to depth approved in APD.
- 3. Set packoff and test to 5k psi
- 4. Offline Cement
- 5. Install wellhead with pressure gauge and nightcap. Nightcap is shown on final wellhead Stack up Illustration #2-2.
- 6. Skid Rig to adjacent well to drill Surface hole.
- 7. Surface casing test will be performed by the rig in order to allow ample time for Cement to develop 500psi compressive strength. Casing test to 0.22 psi/ft or 1500 psi whichever is greater not to exceed 70% casing burst.




Illustration 1-1

<u>Intermediate Casing</u> – PR intends to Batch set all intermediate casing strings to a depth approved in the APD. Intermediate Holes will be batch drilled by the rig. Appropriate notifications will be made prior to testing BOPE, and prior to running/cementing all casing strings.

- 1. Rig will remove the nightcap and install and test BOPE.
- 2. Test Surface casing per COA WOC timing (.22 psi/ft or 1500 psi whichever is greater) not to exceed 70% casing burst. Cement must have achieved 500psi compressive strength prior to test.
- 3. Install wear bushing then drill out surface casing shoe-track plus 20' and conduct FIT to minimum of the MW equivalent anticipated to control the formation pressure to the next casing point.
- 4. Drill Intermediate hole to approved casing point. Trip out of hole with BHA to run Casing.
- 5. Remove wear bushing then run and land Intermediate Casing with mandrel hanger in wellhead.
- 6. Cement casing to surface with floats holding.
- 7. Washout stack then run wash tool in wellhead and wash hanger and pack-off setting area.
- 8. Install pack-off and test void to 5,000 psi for 15 minutes. Nightcap shown on final wellhead stack up illustration 2-2 on page 3.
- 9. Test casing per COA WOC timing (.22 psi/ft or 1500 psi whichever is greater) not to exceed 70% casing burst. Cement must have achieved 500psi compressive strength prior to test.
- 10. Install nightcap skid rig to adjacent well to drill Intermediate hole.




Illustration 2-2

<u>Production Casing</u> – PR intends to Batch set all Production casings with Rig. Appropriate notifications will be made prior Testing BOPE, and prior to running/cementing all casing strings.

- 1. Drilling Rig will remove the nightcap and install and test BOPE.
- 2. Install wear bushing then drill Intermediate shoe-track plus 20' and conduct FIT to minimum MW equivalent to control the formation pressure to TD of well.
- 3. Drill Vertical hole to KOP Trip out for Curve BHA.
- 4. Drill Curve, landing in production interval Trip for Lateral BHA.
- 5. Drill Lateral / Production hole to Permitted BHL, perform cleanup cycles and trip out to run Production Casing.
- 6. Remove wear bushing then run Production casing to TD landing casing mandrel in wellhead.
- 7. Cement Production string with floats holding.
- 8. Run in with wash tool and wash wellhead area install pack-off and test void to 5,000psi for 15 minutes.
- 9. Install BPV in Production mandrel hanger Nipple down BOPE and install nightcap.
- 10. Test nightcap void to 5,000 psi for 30 minutes per illustration 2-2
- 11. Skid rig to adjacent well on pad to drill production hole.

@ntinental<u>⅓</u>

ContiTech Fluid Technology

ContiTech	Oil & Marine Corp. # 11535 Brittmoore Park Dr., Houston, TX	Packing list / Delivery note
77041-69		Document No. 71461553
		Document Date 28.01.2022
CONSI	GNEE / Ship-to address:	Customer Number 11697
	EDICULA DAVALE INITII DDIILLING CO	Customer VAT No.
HELMERICH & PAYNE INT'L DRILLING CO		Supplier Number
	FLEX RIG WHSE - B-BAY AGNOLIA DRIVE	Purchase Order No. /740362040
	JA PARK TX 77547	Purchase Order Date 18.01.2022
20.200	ATAIN IN 11041	Sales Order Number 1388153
Buyer:		Sales Order Date 18.01.2022
HEI ME	ERICH & PAYNE INT'L DRILLING CO	
	OUTH BOULDER	Unloading Point
	TULSA	RAN-No.
Conditi	ons	
y man-	EVIII I	Page 1 of 2
Incoter		Weights (Gross / Net)
	Ex Works	Total Gross Weight 2,507.000 LB Total Net Weight 2,507.000 LB
Item	Material/Description	Quantity Net Weight Gross Weight
	Buyer: Jack Peebles	
	E-mail: Jackie.Peebles@hpinc.com	
	Tel: 832-782-6000	
	Rig/Whse: HOW	
20	00RECERTIFY	1 PC) 2,507.000 LB 2,507.000 LB
20	Recert of HP Hoses Serial# 67094	
	Commodity Code:	\bigcirc
	3" X 35 FT 10K Choke & Kill Hoses API 16C	
	5 X 55 T T TORK STIGHT ST THE TOTAL ST THE THE THE TOTAL ST THE THE THE THE THE THE THE THE THE TH	
	End 1: 4 - 1/16" 10Kpsi API Spec 6A Type 6BX Flange	
	End 2: 4 - 1/16" 10Kpsi API Spec 6A Type 6BX Flange c/w BX155	ring groove each end
	Standard: API Spec 16C - Monogrammed	
		, (()
	Working Pressure: 10,000psi	190-
	Test Pressure: 15,000psi	100
	Inspection & Certification includes:	
	External inspection of the hose & couplings	470
	Internal boroscopic inspection of hose liner	00
	Hydrostatic pressure test of hose assembly	$ \begin{array}{c} 880007401 \\ 880007401 \end{array} $ Solimited ion
	Repair of any external damage to hose body and end connections	(limited
	to minor repairs).	1100
	Clean & protect end connections Inspection Report	1710
	Disposal of hose assembly if hose fails inspection and recertificati	ion
	process.	\ \&\'

ContiTech Rubber Industrial Kft Contriech Rubber Indoorsial Nt. H-6728 Szeged Budapesti út 10. P. O. Box 152 Szeged H-6701 Phone:(62)566-700, Fax:(62)566-713 Tax Number: 11087209-2-06 EU Community VAT: HU11087209 Registration No.: Cg. 0609-002502 Registry Court: Csongråd Megyei Cégbíróság

Please Flush Hoses before sending them to our Facility

COMMERZBANK ZRT (HUF) H-1054 Budapest, Széchenyi rakpart 8. H-1245 Budapest P.O. Box 1070 Account No.: 14220108-26830003 IBAN: HU83 1422 0108 2683 0003 0000 0000 SWIFT: COBA HU HXXXX

COMMERZBANK AG Hannover (EUR) 30159 Hannover, Theaterstr. 11-12. Account No.: 3 066 156 00 Sort Code: 250 400 66 BIC: COBADEFF250 IBAN: DE41250400660306615600

Hydrostatic Test Certificate



ContiTech

Certificate Number H100122	COM Order Reference 1388153	Customer Name & Address HELMERICH & PAYNE DRILLING CO
Customer Purchase Order No: 740362040		1434 SOUTH BOULDER AVE TULSA, OK 74119
Project:		USA
Test Center Address	Accepted by COM Inspection	Accepted by Client Inspection
ContiTech Oil & Marine Corp. 11535 Brittmoore Park Drive Houston, TX 77041 USA	Signed: Gerson Mejia-Lazo Date: 02/09/22	

We certify that the goods detailed hereon have been inspected as described below by our Quality Management System, and to the best of our knowledge are found to conform the requirements of the above referenced purchase order as issued to ContiTech Oil & Marine Corporation.

Item	Part No.	Description	Qnty	Serial Number	Work. Press. (psi)	Test Press. (psi)	Test Time (minutes)

20 RECERTIFICATION

3" ID 10K Choke and Kill Hose x 35ft OAL

67094


10,000

15,000

60

Record Information				
Start Time	1/27/2022 13:21:21			
End Time	1/27/2022 14:38:28			
Interval	00:01:00			
Number	78			
MaxValue	15849			
MinValue	-3			
AvgValue	14240			
RecordName	67094-sh			
RecordNumber	199			

Gauge Information				
Model	ADT680			
SN	21817380014			
Range	(0-40000)psi			
Unit	psi			




Permian Resources Offline Cementing Procedure Surface & Intermediate Casing


- 1. Drill hole to Total Depth with Rig and perform wellbore cleanup cycles.
- 2. Run and casing to Depth.
- 3. Land casing with mandrel.
- 4. Circulate 1.5 csg capacity.
- 5. Flow test Confirm well is static and floats are holding.
- 6. Set Annular packoff and pressure test. Test to 5k.
- 7. Nipple down BOP and install cap flange.
- 8. Skid rig to next well on pad
- 9. Remove cap flange (confirm well is static before removal)
 - a) If well is not static use the casing outlet valves to kill well
 - b) Drillers method will be used in well control event
 - c) High pressure return line will be rigged up to lower casing valve and run to choke manifold to control annular pressure
 - d) Kill mud will be circulated once influx is circulated out of hole
 - e) Confirm well is static and remove cap flange to start offline cement operations
- 10. Install offline cement tool.
- 11. Rig up cementers.
- 12. Circulate bottoms up with cement truck
- 13. Commence planned cement job, take returns through the annulus wellhead valve
- 14. After plug is bumped confirm floats hold and well is static
- 15. Rig down cementers and equipment
- 16. Install night cap with pressure gauge to monitor.

13 3/8" Surface


CFL Off-Line Cementing Tool




Intermediate



Run 7 5/8" Casing Land Casing on 7 5/8" Mandrel Hanger Cement 7 5/8" Casing Retrieve Running Tool



Run 9 5/8" Packoff
Test Upper and Lower Seals
Engage Lockring
Retrieve Running Tool



Operator Name: CENTENNIAL RESOURCE PRODUCTION LLC

Well Name: MICHELADA 3 FED COM Well Number: 134H

Safe containment description: Steel tanks with plastic-lined containment berms.

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: Contents (drill cuttings, mud, salts, and other chemicals) of the mud tanks will be hauled to

R360s state approved (NM-01-0006) disposal site at Halfway.

Waste type: SEWAGE

Waste content description: Grey Water/Human waste.

Amount of waste: 5000 gallons

Waste disposal frequency: Weekly

Safe containment description: Approved waste storage tanks with containment.

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: Human waste will be disposed of in chemical toilets and hauled to the Carlsbad wastewater

treatment plant.

Waste type: GARBAGE

Waste content description: General trash/garbage.

Amount of waste: 5000 pounds

Waste disposal frequency: Weekly

Safe containment description: Enclosed trash trailer.

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: Haul to the Eddy County landfill.

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit? NO

Reserve pit length (ft.) Reserve pit width (ft.)

Reserve pit depth (ft.) Reserve pit volume (cu. yd.)

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Operator Name: CENTENNIAL RESOURCE PRODUCTION LLC

Well Name: MICHELADA 3 FED COM Well Number: 134H

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? Y

Description of cuttings location 12580 cubic feet of waste, stored in steel tanks. Hauled off to a commercial State approved facility.

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary

Are you requesting any Ancillary Facilities?: N

Ancillary Facilities

Comments:

Section 9 - Well Site

Well Site Layout Diagram:

Michelada_3_Fed_WSL_N_Pad_20240806053245.pdf

Comments: See rig layout diagram for depictions of the well pad, trash cage, access onto the location, parking, living facilities, and rig orientation.

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance Multiple Well Pad Name: MEZCAL 10 NWNW 1

Multiple Well Pad Number: 9

Recontouring

Michelada_3_Fed_IR_S_Pad_20240806053346.pdf

Michelada_3_Fed_IR_N_Pad_20240806053346.pdf

Michelada_3_Fed_IR_CTB_20240806055206.pdf

Drainage/Erosion control construction: All compacted areas to be seeded will be ripped to a minimum depth of 18 inches with a minimum furrow spacing of 2 feet, followed by recontouring the surface and then evenly spreading the stockpiled topsoil. Prior to seeding, the seedbed will be scarified to a depth of no less than 4-6 inches.

Date: <u>10/14/2024</u>

State of New Mexico Energy, Minerals and Natural Resources Department

Oil Conservation Division 1220 South St. Francis Dr Santa Fe, NM 87505

NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

Section 1 – Plan Description Effective May 25, 2021

I. Operator: Permian Resources Operating, LLC OGRID: 372165

I. Type: □ Original □ Amendment due to □ 19.15.27.9.D(6)(a) NMAC □ 19.15.27.9.D(6)(b) NMAC □ Other. f Other, please describe:								
III. Well(s): Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.								
Well Name	API	ULSIR	Footages	Anticipated Oil	Anticipated Gas	Anticipated Prod Water		
Mezcal 10 Fed Com 121H		D-11-T20S-R30E	488' FNL-1062' FWL	1300 BOPD	1500 MCFD	2600 BWPD		
Mezcal 10 Fed Com 122H		N-11-T20S-R30E	1128' FSL – 1302' FWL	1300 BOPD	1500 MCFD	2600 BWPD		
Mezcal 10 Fed Com 123H M-11-T20S-R30E 1111' FSL – 1277' FWL 1300 BOPD 1500 MCFD 2600 BWPD								
Mezcal 10 Fed Com 124H		M-11-T20S-R30E	1094' FSL – 1253' FWL	1300 BOPD	1500 MCFD	2600 BWPD		
Mezcal 10 Fed Com 131H		D-11-T20S-R30E	497' FNL-1091' FWL	1200 BOPD	3000 MCFD	3000 BWPD		
Mezcal 10 Fed Com 132H		D-11-T20S-R30E	507' FNL-1120' FWL	1200 BOPD	3000 MCFD	3000 BWPD		
Mezcal 10 Fed Com 133H		D-11-T20S-R30E	516' FNL-1148' FWL	1200 BOPD	3000 MCFD	3000 BWPD		
Mezcal 10 Fed Com 134H		D-11-T20S-R30E	525' FNL-1177' FWL	1200 BOPD	3000 MCFD	3000 BWPD		
Michelada 3 Fed Com 123H		D-11-T20S-R30E	412' FNL-1150' FWL	1300 BOPD	1500 MCFD	2600 BWPD		
Michelada 3 Fed Com 124H		D-11-T20S-R30E	402' FNL-1122' FWL	1300 BOPD	1500 MCFD	2600 BWPD		
Michelada 3 Fed Com 133H D-11-T20S-R30E 430' FNL – 1207' FWL 1200 BOPD 3000 MCFD 3000 BWPD								
Michelada 3 Fed Com 134H D-11-T20S-R30E 421' FNL - 1179' FWL 1200 BOPD 3000 MCFD 3000 BWPD								
Michelada 5 Fed Com 121H		3-5-T20S-R30E	427' FNL-1613' FWL	1200 BOPD	3000 MCFD	3000 BWPD		
Michelada 5 Fed Com 122H		3-5-T20S-R30E	435' FNL-1645' FWL	1200 BOPD	3000 MCFD	3000 BWPD		
Michelada 5 Fed Com 131H		3-5-T20S-R30E	411' FNL – 1549' FWL	1200 BOPD	3000 MCFD	3000 BWPD		

IV. Central Delivery Point Name: Mezcal/Michelada 10 CTB [See 19.15.27.9(D)(1) NMAC]

419' FNL – 1581' FWL

1200 BOPD

3000 MCFD

3000 BWPD

3-5-T20S-R30E

V. Anticipated Schedule: Provide the following information for each new or recompleted well or set of wells proposed to be drilled or recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
Mezcal 10 Fed Com 121H		TBD	TBD	TBD	TBD	TBD
Mezcal 10 Fed Com 122H		TBD	TBD	TBD	TBD	TBD
Mezcal 10 Fed Com 123H		TBD	TBD	TBD	TBD	TBD
Mezcal 10 Fed Com 124H	15.07	TBD	TBD	TBD	TBD	TBD

Released to Imaging: 11/8/2024 9:15:07\AM

Michelada 5 Fed Com 132H

ceived by OCD: 10/20/2024 3:21:	20 PM				Page 104 o
Mezcal 10 Fed Com 131H	TBD	TBD	TBD	TBD	TBD
Mezcal 10 Fed Com 132H	TBD	TBD	TBD	TBD	TBD
Mezcal 10 Fed Com 133H	TBD	TBD	TBD	TBD	TBD
Mezcal 10 Fed Com 134H	TBD	TBD	TBD	TBD	TBD .
Michelada 3 Fed Com 123H	TBD	TBD	TBD	TBD	TBD
Michelada 3 Fed Com 124H	TBD	TBD	TBD	TBD	TBD
Michelada 3 Fed Com 133H	TBD	TBD	TBD	TBD	TBD
Michelada 3 Fed Com 134H	TBD	TBD	TBD	TBD	TBD
Michelada 5 Fed Com 121H	TBD	TBD	TBD	TBD	TBD
Michelada 5 Fed Com 122H	TBD	TBD	TBD	TBD	TBD
Michelada 5 Fed Com 131H	TBD	TBD	TBD	TBD	TBD

TBD

TBD

TBD

VI. Separation Equipment: \Box Attach a complete description of how Operator will seize separation equipment to optimize gas capture.

TBD

TBD

VII. Operations Practices: □ Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

VIII. Best Management Practices:

Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

Section 2 – Enhanced Plan

Effective April 1, 2022

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

□ Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

IX. Anticipated Natural Gas Production:

Michelada 5 Fed Com 132H

Well Name	API	Anticipated Average Natural Gas Rate	Anticipated Volume of Natural Gas for the First Year
Mezcal 10 Fed Com 121H	TBD	1000 MCFD	350,000 MCF
Mezcal 10 Fed Com 122H	TBD	1000 MCFD	350,000 MCF
Mezcal 10 Fed Com 123H	TBD	1000 MCFD	350,000 MCF
Mezcal 10 Fed Com 124H	TBD	1000 MCFD	350,000 MCF
Mezcal 10 Fed Com 131H	TBD	2000 MCFD	750,000 MCF
Mezcal 10 Fed Com 132H	TBD	2000 MCFD	750,000 MCF
Mezcal 10 Fed Com 133H	TBD	2000 MCFD	750,000 MCF
Mezcal 10 Fed Com 134H	TBD	2000 MCFD	750,000 MCF
Michelada 3 Fed Com 123H	TBD	1000 MCFD	350,000 MCF
Michelada 3 Fed Com 124H	TBD	1000 MCFD	350,000 MCF
Michelada 3 Fed Com 133H	TBD	2000 MCFD	750,000 MCF
Michelada 3 Fed Com 134H	TBD	2000 MCFD	750,000 MCF
Michelada 5 Fed Com 121H	TBD	2000 MCFD	750,000 MCF
Michelada 5 Fed Com 122H	TBD	2000 MCFD	750,000 MCF
Michelada 5 Fed Com 131H	TBD	2000 MCFD	750,000 MCF
Michelada 5 Fed Com 132H	TBD	2000 MCFD	750,000 MCF

Received by OCD: 10/20/2024 3:21:20 PM X. Natural Gas Gathering System (NGGS):

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Volume of Natural Gas for the First Year

XI. Map. □ Attach an accurate and legible map depicting the location of the well(s), the anticipated pipe connecting the production operations to the existing or planned interconnect of the natural gas gathering the maximum daily capacity of the segment or portion of the natural gas system(s) to which the well(s) wi	system(s), and						
XII. Line Capacity. Operator \Box does \Box does not anticipate that its existing well(s) connected to the same portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases caused by the new well(s).	e segment, or						
☐ Attach Operator's plan to manage production in response to the increased line pressure.							
XIV. Confidentiality: □ Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attached a full description of the specific information for which confidentiality is asserted and the basis for such assertion.							

Section 3 – Certifications

Effective May 25, 2021

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

☐ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient
capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on
the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or
□ Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to

transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

If Operator checks this box, Operator will select one of the following:

Well Shut-In.
Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

Venting and Flaring Plan. □ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) Power generation on lease;
- **(b)** power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- **(f)** reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

Section 4 – Notices

- If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:
 - (a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or
 - (b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, not later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file and update for each Natural Gas Management Plan until the Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.
 - (c) OCD may deny or conditionally approve and APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

Released to Imaging: 11/8/2024 9:15:07 AM

I certify, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature: Cooci Wans-		
Printed Name: Cassie Evans		
Title: Regulatory Specialist		
E-mail Address: Cassie.Evans@permianres.com		
Date: 10/14/24		
Phone: 432-313-1732		
OIL CONSERVATION DIVISION		
(Only applicable when submitted as a standalone form)		
Approved By:		
Title:		
Approval Date:		
Conditions of Approval:		

Permian Resources Operating, LLC (372165)

Natural Gas Management Plan Descriptions

VI. Separation Equipment:

Permian Resources Operating, LLC (Permian) utilizes a production forecast from our Reservoir Engineering team to appropriately size each permanent, 3-phase separator and heater treater utilized for production operations. Our goal is to maintain 5 minutes of retention time in the test vessel and 20 minutes in the heater treater at peak production rates. The gas produced is routed from the separator to the gas sales line.

VII. Operational Practices:

Drilling

During Permian's drilling operations it is uncommon for venting or flaring to occur. If flaring is needed due to safety concerns, gas will be routed to a flare and volumes will be estimated.

Flowback

During completion/recompletion flowback operations, after separation flowback begins and as soon as it is technically feasible, Permian routes gas though a permanent separator and the controlled facility where the gas is either sold or flared through a high-pressure flare if needed.

Production

Per 19.15.27.8.D, Permian's facilities are designed to minimize waste. Our produced gas will only be vented or flared in an emergency or malfunction situation, except as allowed for normal operations noted in 19.15.27.8.D(2) & (4). All gas that is flared is metered. All gas that may be vented will be estimated.

Performance Standards

Permian utilizes a production forecast from our Reservoir Engineering team to appropriately size each permanent, 3-phase separator and heater treater utilized for production operations.

All of Permian's permanent storage tanks associated with production operations which are routed to a flare or control device are equipped with an automatic gauging system.

All of Permian's flare stacks, both currently installed and for future installation, are:

- 1) Appropriately sized and designed to ensure proper combustion effciency.
- 2) Equipped with an automatic ignitor or continuous pilot.

Released to Imaging: 11/8/2024 9:15:07 AM

3) Anchored and located at least 100 feet from the well and storage tanks.

Permian Resources Operating, LLC (372165)

- Vapor recovery units to maximize recovery of low-pressure gas streams and potential unauthorized emissions
- Low-emitting or electric engines whenever practical
- Combustors and flare stacks in the event of a malfunction or emergency
- Routine facility inspections to identify leaking components, functioning control devices, such as flares and combustors, and repair / replacement of malfunctioning components where applicable

Measurement or estimation

Permian measures or estimates the volumes of natural gas vented, flared and/or beneficially used for all of our drilling, completing and producing wells. We utilize accepted industry standards and methodology which can be independently verified. Annual GOR testing is completed on our wells and will be submitted as required by the OCD. None of our equipment is designed to allow diversion around metering elements except during inspection, maintenance and repair operations.

VIII. Best Management Practices:


Permian Resources utilizes the following BMPs to minimize venting during active and planned maintenance activities:

- Use a closed-loop process wherever possible during planned maintenance activities, such as blowdowns, liquid removal, and work over operations.
- Employ low-emitting or electric engines for equipment, such as compressors
- Adhere to a strict preventative maintenance program which includes routine facility inspections, identification of component malfunctions, and repairing or replacing components such as hatches, seals, valves, etc. where applicable
- Utilize vapor recovery units (VRU's) to maximize recovery of volumes of low-pressure gas streams and potential unauthorized emissions
- Route low pressure gas and emissions streams to a combustion device to prevent venting where necessary

Enhanced Natural Gas Management Plan

Operator's Plan to Manage Production in Response to Increased Line Pressure

Permian Resources Operating, LLC (Permian) anticipates that its existing wells connected to the same portion of the natural gas gathering system will continue to meet anticipated increases in line pressure caused by the new wells. Permian will actively monitor line pressure throughout the field and will make necessary adjustments to existing production separators' pressures to send gas to sales. Permian also plans to implement automated alarms on all flare meters to alert of flaring events as they occur. The alarms will send notifications to field operations and engineering staff via text message and email at every occurrence of flaring. In addition, Permian plans to implement automated alarms on all flare meters to alert of any continuous flaring event that has continued for at least 4 hours. The alarms will send notifications to field operations and engineering management. Permian personnel will promptly respond to these alarms, communicate with midstream partners, and take the appropriate action to reduce flaring caused by high line pressure from new well production.



District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 393937

CONDITIONS

Operator:	OGRID:
Permian Resources Operating, LLC	372165
300 N. Marienfeld St Ste 1000	Action Number:
Midland, TX 79701	393937
	Action Type:
	[C-101] BLM - Federal/Indian Land Lease (Form 3160-3)

CONDITIONS

Created By	Condition	Condition Date
ward.rikala	Notify the OCD 24 hours prior to casing & cement.	11/8/2024
ward.rikala	File As Drilled C-102 and a directional Survey with C-104 completion packet.	11/8/2024
ward.rikala	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string.	11/8/2024
ward.rikala	Cement is required to circulate on both surface and intermediate1 strings of casing.	11/8/2024
ward.rikala	If cement does not circulate on any string, a Cement Bond Log (CBL) is required for that string of casing.	11/8/2024
ward.rikala	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.	11/8/2024
ward.rikala	This well is within the Capitan Reef. The 1st intermediate string shall be sat and cemented back to surface immediately on top of the Capitan Reef. The 2nd intermediate string shall be sat and cemented back to surface immediately below the base of the Capitan Reef.	11/8/2024
ward.rikala	Operator must comply with all of the R-111-Q requirements.	11/8/2024