cewer by OCD: 2/16/2025 8:40:31 AM U.S. Department of the Interior BUREAU OF LAND MANAGEMENT		Sundry Print Repo	
Well Name: LINDRITH B UNIT	Well Location: T24N / R3W / SEC 16 / NENE / 36.314618 / -107.155315	County or Parish/State: RIO ARRIBA / NM	
Well Number: 41	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:	
Lease Number: NMSF078913	Unit or CA Name: LINDRITH UNIT GALLUP/DAKOTA	Unit or CA Number: NMNM78399B	
US Well Number: 3003923840	Operator: HILCORP ENERGY COMPANY		

Notice of Intent

Sundry ID: 2847523

Type of Submission: Notice of Intent

Date Sundry Submitted: 04/16/2025

Date proposed operation will begin: 04/30/2025

Type of Action: Workover Operations Time Sundry Submitted: 07:18

Procedure Description: Hilcorp Energy Company requests permission to add pay to the existing Lindrith Gallup-Dakota, West formation in the subject well. Please see the attached procedure, current and proposed wellbore diagram, plat and natural gas management plan. A closed loop system will be used. There will not be any additional surface disturb-ance to this location.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Lindrith_B_Unit_41_RC_NOI_20250416071816.pdf

Received by OCD: 4/16/2025 8:40:31 AM Well Name: LINDRITH B UNIT	Well Location: T24N / R3W / SEC 16 / NENE / 36.314618 / -107.155315	County or Parish/State: Rigge 2 of 16 ARRIBA / NM
Well Number: 41	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:
Lease Number: NMSF078913	Unit or CA Name: LINDRITH UNIT GALLUP/DAKOTA	Unit or CA Number: NMNM78399B
US Well Number: 3003923840	Operator: HILCORP ENERGY COMPANY	

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: DAWN NASH-DEAL

Name: HILCORP ENERGY COMPANY

Title: Operations Regulatory Tech

Street Address: 1111 TRAVIS ST

City: HOUSTON

State: TX

Phone: (505) 324-5132

Email address: DNASH@HILCORP.COM

Field

Representative Name: Street Address: City: State: Phone: Email address:

BLM Point of Contact

BLM POC Name: KENNETH G RENNICK BLM POC Phone: 5055647742 Disposition: Approved Signature: Kenneth Rennick Signed on: APR 16, 2025 07:18 AM

BLM POC Title: Petroleum Engineer BLM POC Email Address: krennick@blm.gov

Zip:

Disposition Date: 04/16/2025

Received by OCD: 4/16/2025 8:40:31 AM

	10/2020 0.				I uge o oj	
Form 3160-5 (June 2019)		UNITED STATE ARTMENT OF THE I EAU OF LAND MAN	NTERIOR	Ol	DRM APPROVED MB No. 1004-0137 res: October 31, 2021	
Do not	use this f		DRTS ON WELLS to drill or to re-enter an PD) for such proposals.	6. If Indian, Allottee or Tribe Name		
	SUBMIT IN	TRIPLICATE - Other instr	uctions on page 2	7. If Unit of CA/Agreement, N	ame and/or No.	
1. Type of Well	Gas W	Jell Other	8. Well Name and No.			
2. Name of Operator			9. API Well No.			
3a. Address			3b. Phone No. (include area code)	10. Field and Pool or Exploratory Area		
4. Location of Well (Foo	tage, Sec., T.,K	,M., or Survey Description,)	11. Country or Parish, State		
	12. CHE	CK THE APPROPRIATE B	OX(ES) TO INDICATE NATURE	OF NOTICE, REPORT OR OTH	ER DATA	
TYPE OF SUBM	SSION		TYP	E OF ACTION		
Notice of Intent		Acidize	Deepen Hydraulic Fracturing	Production (Start/Resume) Reclamation	Water Shut-Off Well Integrity	
Subsequent Report	t	Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete	Other	
Final Abandonme	nt Notice	Convert to Injection	Plug Back	Water Disposal		
the proposal is to dee the Bond under whic completion of the inv	pen directiona h the work wil volved operation andonment No	Ily or recomplete horizontal l be perfonned or provide th ons. If the operation results in	ly, give subsurface locations and me e Bond No. on file with BLM/BIA. n a multiple completion or recompletion of the subscription of the subscript	easured and true vertical depths of Required subsequent reports mus etion in a new interval, a Form 31	k and approximate duration thereof. If f all pertinent markers and zones. Attach t be filed within 30 days following 60-4 must be filed once testing has been he operator has detennined that the site	

14. I hereby certify that the foregoing is true and correct. Name (<i>Printed/Typed</i>)				
	Fitle			
Signature	Date			
THE SPACE FOR FEDE	RAL OR STATE OF	FICE USE		
Approved by				
	Title	Date		
Conditions of approval, if any, are attached. Approval of this notice does not warrant of certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.				
Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any any false, fictitious or fraudulent statements or representations as to any matter within		Ifully to make to any department or agency of the United S		

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

0. SHL: NENE / 1105 FNL / 660 FEL / TWSP: 24N / RANGE: 3W / SECTION: 16 / LAT: 36.314618 / LONG: -107.155315 (TVD: 0 feet, MD: 0 feet) BHL: NENE / 1105 FNL / 660 FEL / TWSP: 24N / SECTION: / LAT: 36.314618 / LONG: 107.155315 (TVD: 0 feet, MD: 0 feet)



HILCORP ENERGY COMPANY Lindrith B Unit 41 RECOMPLETION SUNDRY

Prepared by:	Matthew Esz	
Preparation Date:	April 15, 2025	

WELL INFORMATION							
Well Name:	Lindrith B Unit 41	State:	NM				
API #:	3003923840	County:					
Area:	14	Location:					
Route:	1413	Latitude:					
Spud Date:	December 1, 1985	Longitude:					

PROJECT DESCRIPTION

Perforate and fracture the Lindrith Gallup-Dakota interval.

CONTACTS								
Title	Name	Office Phone #	Cell Phone #					
Engineer	Matthew Esz		770-843-9226					
Area Foreman								
Lead								
Artificial Lift Tech								
Operator								



HILCORP ENERGY COMPANY Lindrith B Unit 41 RECOMPLETION SUNDRY

JOB PROCEDURES

- 1. MIRU service rig and associated equipment; test BOP.
- 2. TOOH with 2-3/8" tubing set at 7,612'.
- 3. Set a 5-1/2" plug at +/- 7,339' to isolate the Lindrith Gallup-Dakota.
- 4. RU Wireline. Run CBL. Record Top of Cement.
- 5. Load the hole and pressure test the casing.
- 6. N/D BOP, N/U frac stack and pressure test frac stack.
- 7. Perforate and frac the Lindrith Gallup-Dakota interval from 6,390'-7,278'.
- 8. Nipple down frac stack, nipple up BOP and test.
- 9. TIH with a mill and drill out top isolation plug and Lindrith Gallup-Dakota frac plugs.
- 10. Clean out to Lindrith Gallup-Dakota isolation plug.
- 11. Drill out Lindrith Gallup-Dakota isolation plug and cleanout to PBTD of 7,690'. TOOH.
- 12. TIH and land production tubing. RTP.

HILCORP ENERGY COMPANY Lindrith B Unit 41 RECOMPLETION SUNDRY

md Elevation (ft 20.00 bing String: Date D/2019 12:0 MD TV (KB) (ftK 13.1 16.4 885 209 100.1 113.8 503.9 770.0 503.9	/D //D (B) (B) (C) (C) (C) (C) (C) (C) (C) (C) (C) (C	JO_ALAMO_TOP * (OJO_F RTLAND * (KIRTLAND * (fi CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2	1/16 in; 4.70 lb/ft; materian 00 ftKB; 14.00 ftKB ALAMO_TOP nal))	RKB to GL (ft) 13.00 String Min Nominal ID (in) 2.00 Hole [Vertical] Vertical schematic (actual)	7/8in Pony Rod; 2 Surface Casing Ce 00:00; 13:00-422.0 with 400 sx Class F to surface. 1; Surface, 422.00 lb/ft; 13:00 ftKB; 4 7/8in Sucker Rod;	Original Spud Date 12/1/1985 00:00 tod; 22.00 ft energy 22.00 ft energ
Date DJ/2019 12:0 MD TV (ftK 13.1 16.4 88.5 20.9 100.1 113.8 503.9 770.0 279.9	/D (B) (B) (C) (C) (C) (C) (C) (C) (C) (C) (C) (C	7,612.57 1/16in, Tubing Hanger; 7 J-55; 13.0 JO_ALAMO_TOP * (OJO_A RTLAND * (KIRTLAND * (fi CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACKA (CHACKA (final))	2 3/8 Original I 1/16 in: 4.70 lb/ft, 00 ftKB; 14.00 ftKB	I 2.00 Hole [Vertical]	4.70 7/8in Polished R 7/8in Pony Rod; 2 Surface Casing Ce 0:00; 13.00-422.0 with 400 sx Class F to surface. 1; Surface, 422.00 Ib/ft; 13.00 ftKB; 4 7/8in Sucker Rod;	12/1/1985 00:00 tod; 22.00 ft ment, Casing, 12/2/1985 00; 1985-12-02; Cemented B cement, Circulated 60 sx ftKB; 9 5/8 in; 8.68 in; 47.00 22.00 ftKB
AD TV (KB) (ftK 13.1 16.4 88.5 20.9 100.1 113.8 503.9 770.0 279.9	/D (B) 7 	7,612.57 1/16in, Tubing Hanger; 7 J-55; 13.0 JO_ALAMO_TOP * (OJO_A RTLAND * (KIRTLAND * (fi CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACKA (CHACKA (final))	2 3/8 Original I 1/16 in: 4.70 lb/ft, 00 ftKB; 14.00 ftKB	I 2.00 Hole [Vertical]	4.70 7/8in Polished R 7/8in Pony Rod; 2 Surface Casing Ce 0:00; 13.00-422.0 with 400 sx Class F to surface. 1; Surface, 422.00 Ib/ft; 13.00 ftKB; 4 7/8in Sucker Rod;	12/1/1985 00:00 tod; 22.00 ft ment, Casing, 12/2/1985 00; 1985-12-02; Cemented B cement, Circulated 60 sx ftKB; 9 5/8 in; 8.68 in; 47.00 22.00 ftKB
KB) (ftK 13.1 - 164 - 885 - 100.1 - 832.0 - 113.8 - 503.9 - 279.9 -	(B) 7 0 -0 -0 -0 -0 -0 -0 -0 -0 -0	J-55; 13.0 JO_ALAMO_TOP * (OJO_A RTLAND * (KIRTLAND * (fii CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACRA (CHACRA (final))	1/16 in; 4.70 lb/ft; materian 00 ftKB; 14.00 ftKB ALAMO_TOP nal))		7/8in Pony Rod; 2 Surface Casing Ce 00:00; 13:00-422.0 with 400 sx Class F to surface. 1; Surface, 422.00 lb/ft; 13:00 ftKB; 4 7/8in Sucker Rod;	200 ft ement, Casing, 12/2/1985 30; 1985-12-02; Cemented B cement, Circulated 60 sx ftKB; 9 5/8 in; 8.68 in; 47.00 22.00 ftKB
KB) (ftK 13.1 - 164 - 885 - 100.1 - 832.0 - 113.8 - 503.9 - 279.9 -	(B) 7 0 -0 -0 -0 -0 -0 -0 -0 -0 -0	J-55; 13.0 JO_ALAMO_TOP * (OJO_A RTLAND * (KIRTLAND * (fii CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACRA (CHACRA (final))	1/16 in; 4.70 lb/ft; additioner 00 ftKB; 14.00 ftKB ALAMO_TOP nal))	Vertical schematic (actual)	7/8in Pony Rod; 2 Surface Casing Ce 00:00; 13:00-422.0 with 400 sx Class F to surface. 1; Surface, 422.00 lb/ft; 13:00 ftKB; 4 7/8in Sucker Rod;	200 ft ement, Casing, 12/2/1985 30; 1985-12-02; Cemented B cement, Circulated 60 sx ftKB; 9 5/8 in; 8.68 in; 47.00 22.00 ftKB
13.1 16.4 20.9 100.1 100.1 113.8 503.9 770.0 279.9		J-55; 13.0 JO_ALAMO_TOP * (OJO_A RTLAND * (KIRTLAND * (fii CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACRA (CHACRA (final))	ALAMO_TOP RED_CLIFFS *		7/8in Pony Rod; 2 Surface Casing Ce 00:00; 13:00-422.0 with 400 sx Class F to surface. 1; Surface, 422.00 lb/ft; 13:00 ftKB; 4 7/8in Sucker Rod;	200 ft ement, Casing, 12/2/1985 30; 1985-12-02; Cemented B cement, Circulated 60 sx ftKB; 9 5/8 in; 8.68 in; 47.00 22.00 ftKB
16.4 888.5 20.9 100.1 832.0 113.8 503.9 770.0 2279.9	0 - Ki - Pi	J-55; 13.0 JO_ALAMO_TOP * (OJO_A RTLAND * (KIRTLAND * (fii CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACRA (CHACRA (final))	ALAMO_TOP RED_CLIFFS *		7/8in Pony Rod; 2 Surface Casing Ce 00:00; 13:00-422.0 with 400 sx Class F to surface. 1; Surface, 422.00 lb/ft; 13:00 ftKB; 4 7/8in Sucker Rod;	200 ft ement, Casing, 12/2/1985 20; 1985-12-02; Cemented B cement, Circulated 60 sx ftKB; 9 5/8 in; 8.68 in; 47.00 22.00 ftKB
885		JO_ALAMO_TOP * (OJO_A RTLAND * (KIRTLAND * (fi CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACRA (CHACRA (Inai))	ALAMO_TOP nal)) RED_CLIFFS *		Surface Casing Ce 00:00; 13:00-422.0 with 400 sx Class I to surface. 1; Surface, 422:00 lb/ft; 13:00 ftKB; 4 7/8in Sucker Rod;	ement, Casing, 12/2/1985 00; 1985-12-02; Cemented B cement. Circulated 60 sx ftKB; 9 5/8 in; 8.68 in; 47.00 22.00 ftKB
209		RTLAND * (KIRTLAND * (fi CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACRA (CHACRA (final))	nal))		with 400 sx Class I to surface. 1; Surface, 422.000 Ib/ft; 13.00 ftKB; 4 7/8in Sucker Rod;	B cement. Circulated 60 sx ftKB; 9 5/8 in; 8.68 in; 47.00 i22.00 ftKB
209		RTLAND * (KIRTLAND * (fi CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACRA (CHACRA (final))	nal))		to surface. 1; Surface, 422.000 lb/ft; 13.00 ftKB; 4 7/8in Sucker Rod;	ftKB; 9 5/8 in; 8.68 in; 47.00 22.00 ftKB
100.1		RTLAND * (KIRTLAND * (fi CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACRA (CHACRA (final))	nal))		Ib/ft; 13.00 ftKB; 4 	22.00 ftKB
8320		RTLAND * (KIRTLAND * (fi CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACRA (CHACRA (final))	nal))		7/8in Sucker Rod;	
113.8 503.9 770.0		RTLAND * (KIRTLAND * (fi CTURED_CLIFFS * (PICTUF 3/8in, Tubing YELLOW; 2 -55; 14.00 f HACRA (CHACRA (final))	nal))		I	
503.9 770.0 279.9		3/8in, Tubing YELLOW; 2 -55; 14.00 f HACKA (CHACKA (final))				
503.9 770.0 279.9		3/8in, Tubing YELLOW; 2 -55; 14.00 f HACKA (CHACKA (final))				
279.9	- a	HACKA (CHACKA (final)) -		9888 STOL	Production Casing	3 Cement, Casing, ; 1,100.00-7,750.00; 1985-12
279.9		IEE HOUSE ICHEE HOUSE	ftKB; 6,850.14 ftKB		-22; Cemented wit	th 1800 sx Tridently Light
			E (final))			nd tailed with 200 sx 1-1 per CBL dated 1/12/1986.
518.1	- P(IENEFEE (MENEFEE (final)) DINT_LOOKOUT (POINT_L			3/4in Sucker Rod;	4,425.00 ft
		3/8in, Tubing YELLOW; 2				
		And the second	tKB; 7,271.57 ftKB			
966.9		2 3/8in, Tubing Pup Joint; 2 L-80; 7,271.57 f	tkB; 7,273.57 ftkB			
273.6	2	3/8in, Tubing YELLOW; 2 3				
337.3		-80; 7,273.57 f 4.95in, Anchor/catcher; 4.9	ftKB; 7,337.32 ftKB 95 in; 4.70 lb/ft; L-			
341.9		80; 7,337.32 f RANEROS (GRANEROS (fin	ftKB; 7,340.04 ftKB			
10.000		WO_WELLS (TWO_WELLS (3105 A			2/2/1986 00:00 (PERF -
368.4	2	3/8in, Tubing YELLOW; 2	3/8 in; 4.70 lb/ft; J		DAKOTA); 1986-02	
478.0			КВ, 7,527.10 ККВ			
527.2	- a	UBERO (CUBERO (final)) -				
		UBERO_LWR (CUBERO_LW			7548-7578ftKB on	1/29/1986 00:00 (PERF -
5479	2	3/8in, Tubing YELLOW; 2 - -80; 7,527.10 f	3/8 in; 4.70 lb/ft; L ftKB; 7,591.05 ftKB		DAKOTA); 1986-01 3/4in Shear Coupl	
568.9					3/4in Guided Rod;	
578.1	2	3/8in, SEAT NIPPLE 1.78; 2	2 3/8 in; 4.70 lb/ft; M. ftKB; 7,592.15 ftKB			Pump 2" X 1 1/4" X 10' X
592.2	12	2 3/8in, PRICE TYPE MUD A			14' RHBC-Z HVR; 1.315in Strainer N	
	-	4.70 lb/ft; J-55; 7,592.15 f 2 3/8in, Mule Shoe; 2 3/8	NUMBER OF A DESCRIPTION		Production Casing	and the second
512.2			ftKB; 7,612.57 ftKB		12/22/1985 00:00	(plug); 7,690.00-7,750.00; ented with 1800 sx Tridently
590.0		Float Colla	ar (PBTD); 7,690.00		Light Weight cem	ent, and tailed with 200 sx
702.4					-1 Talc. TOC at 110 1/12/1986.)0' per CBL dated
734.9					bed and a second s	735.00ftKB; 5 1/2 in; 4.95 in
				NEW NAME AND A DESCRIPTION OF A A DESCRIPTION OF A DESCRI	15.50 lb/ft; 13.00 f	ftKB; 7,735.00 ftKB
						<u></u>

•

HILCORP ENERGY COMPANY Lindrith B Unit 41 RECOMPLETION SUNDRY

Woll Na	mor		NTH B UNIT #41	Lindrith B Unit 41	- Proposed Schematic		
API/UWI	me.	LINDR	Surface Legal Location	Field Name	Route	State/Province	Well Configuration Type
300392384 Ground Elevati			016-024N-003W-A Original KB/RT Elevation (ft)	DK Tubing Hanger Elevation (ft)	1413 RKB to GL (ft)	NEW MEXICO KB-Casing Flange Distance (ft)	Vertical KB-Tubing Hanger Distance (ft)
6,920.00			6,933.00	Tabely Harger Elevatori (ii)	13.00	No-Casing Hamge Distance (ii)	Rentancy Hanger Desance (n)
Tubing Str Run Date	médern		Set Depth (ftKB)	String Max Nominal OD (in)	String Min Nominal ID (in)	Weight/Length (Ib/ft)	Original Spud Date
9/30/2019	12:00		7,612.57	2 3/8	2.00	4.70	12/1/1985 00:00
				Original H	ole [Vertical]		
MD (ftKB)	TVD (ftKB)			V	ertical schematic (actual)		
			- 117 - 117 - 117 - 117				
13.1		7 1	/16in, Tubing Hanger; 7 1/ J-55; 13.00	16 in; 4.70 lb/ft; material and ftKB; 14.00 ftKB		7/8in Pony Rod; 2.00	22.00 ft advertssädentudetentistelt ft
16.4							nt, Casing, 12/2/1985 1985-12-02; Cemented
388.5							ement. Circulated 60 sx
420.9						1; Surface, 422.00ftKE	3; 9 5/8 in; 8.68 in; 47.00
1,100.1				8		Ib/ft; 13.00 ftKB; 422.0 7/8in Sucker Rod; 2,9	
2,832.0		1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.	D_ALAMO_TOP * (OJO_AL TLAND * (KIRTLAND * (fina				
3,113.8		PIC	TURED_CLIFFS * (PICTURE	D_CLIFFS *		Production Casing Ce	most Casing
3,503.9		23	/8in, Tubing YELLOW; 2 3/	8 in; 4.70 lb/ft; J 8; 6,850.14 ftKB		12/22/1985 00:00; 1,1	100.00-7,750.00; 1985-12
4,770.0			ACRA (CHACRA (final)) FF_HOUSE (CLIFF_HOUSE (8		Weight cement, and t	The second s
5,279.9		-ME	NEFEE (MENEFEE (final)) - NT LOOKOUT (POINT LO			Talc. TOC at 1100' per 3/4in Sucker Rod: 4.4	r CBL dated 1/12/1986.
		AAA	/8in, Tubing YELLOW; 2 3/	(R (6nal))			
6,618.1			-80; 6,850.14 ftK	B; 7,271.57 ftKB			
6,966.9		2.	3/8in, Tubing Pup Joint; 2 3 L-80; 7,271.57 ftK				
7,273.6		2.3	/8in, Tubing YELLOW; 2 3/ -80; 7,273.57 ftK	B 2			
7,337.3		4.	95in, Anchor/catcher; 4.95	in; 4.70 lb/ft; L-			
7,341.9			ANEROS (GRANEROS (final			7364-7478ftKB on 2/	2/1986 00:00 (PEPE -
7,368.4		-	O_WELLS (TWO_WELLS (fir //8in, Tubing YELLOW; 2 3/			DAKOTA); 1986-02-02	
7,478.0		H_	-55; 7,340.04 ftK	B; 7,527.10 ftKB		1 1/4in Sinker Bar; 20	0.00 ft
7,527.2		- CUE	SERO (CUBERO (final))				
		_	BERO_LWR (CUBERO_LWR	73		7548-7578ftKB on 1/2	29/1986 00:00 (PERF -
7,5479		23	/8in, Tubing YELLOW; 2 3/4 -80; 7,527.10 ftK	B-7 591 05 EKB		DAKOTA); 1986-01-29 3/4in Shear Coupling	
7,568.9				1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		- 3/4in Guided Rod; 8.0	
7,578.1		23	/8in, SEAT NIPPLE 1.78; 2 3 J-55; 7,591.05 ftK	E State Stat			mp 2" X 1 1/4" X 10' X
7,592.2			3/8in, PRICE TYPE MUD AN	ICHOR; 2 3/8 in;		14' RHBC-Z HVR; 14.	
7,612.2		1	1.70 lb/ft; J-55; 7,592.15 ftK 3/8in, Mule Shoe; 2 3/8 in;	Next In the International Property i		Production Casing Ce	
7,690.0				B; 7,612.57 ftKB PBTD); 7,690.00		1985-12-22; Cemente	ug); 7,690.00-7,750.00; ed with 1800 sx Tridently
7,702.4			L'IOR CONT			Light Weight cement -1 Talc. TOC at 1100	, and tailed with 200 sx 1 per CBL dated
7,702.4						1/12/1986.	.00ftKB; 5 1/2 in; 4.95 in;
7,734,9				8		15.50 lb/ft; 13.00 ftKE	
L				_			

•

Received by OCD: 4/16/2025 8:40:31 AM

Page 9 of 16

`					ATION COM			Form C-102 Supersedes C-128 Effective 1-1-65
		All distan	ces must be	from the oute	r boundaries of t	the Sectio	on.	<u> </u>
erator MOBIL P	RODUCING	TEXAS	B. N.M.	Lease /	induit	-1. 7	3 Ilnit	Well No. 41
.t Letter Sectio		Township	. 24 N.	Pange		Cour.ty	RIO ARRI	BA
tus. Footage Location of								
		ORTH	line and	66	0 feet	t from the	EAST	line
and Level Elev. 6941	Producing Form Dakota			Pool Wes	t Lindri	th		Dedicated Acreage:
1. Outline the acre	eage dedica	ed to the	subject w	ell by col	ored pencil o	r hachu	re marks on th	ne plat below.
2. If more than on interest and roy	e lease is alty).	dedicated	to the we	ll, outline	each and ide	ntify th	e ownership t	hereof (both as to working f all owners been consoli-
dated by commu	nitization, u	nitization,	force-pool	ing. etc?				all owners been consoll-
X Yes	No Ifar	iswer is "	ves." type	of consoli	dation <u> </u>	itiza	ation	<u></u>
		owners and	d tract des	criptions v	which have a	ctually "	been consolid	ated. (Use reverse side of
this form if nece	-	11		11 •	······			
	-							nmunitization, unitization. n approved by the Commis-
sion.		-		,	0		,	
	1				1		T	CERTIFICATION
	1					/		
				/			tained h	certify that the information con- erein is true and complete to the ny knowledge and belief.
	1				B-41	660'	- C.	a. Stone for
	+ I			/-	·			E. TATE
	1				1	/	ENV.	8 REG. MANAGER
	1				1		Company	
	1					113	Mobil Date	Producing TX, &N.M.
	1			DEC	EX S			y 25, 1985
	!	/	6 1	AEU	1.2.19 -	N.J		• • • •
					CON. D)/V .	shown a notes s under m is true	y certify that the well location on this plat was plotted from field f octual surveys made by me or y supervision, and that the some and correct to the best of my lge ond belief.
							Date Surv	
	Ta	4 N	R	3 W	† ! [JULY 19, 1985 d Professional Engineer md Surveyor
					1			6256

1320 1640 1010 7310 1110

Released to Imaging: 4/30/2025 3:23:05 PM

Received by	• OCD:	4/16/2025	8:40:31	AM
-------------	--------	-----------	---------	----

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Electronically Via E-permitting

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

<u>Section 1 – Plan Description</u> <u>Effective May 25, 2021</u>

I. Operator: <u>Hilcorp Energy Company</u>

OGRID: <u>372171</u> Date: <u>04/12/2025</u>

II. Type: ⊠ Original □ Amendment due to □ 19.15.27.9.D(6)(a) NMAC □ 19.15.27.9.D(6)(b) NMAC □ Other.

If Other, please describe: _____

III. Well(s): Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water
LINDRITH B UNIT 41	3003923840	A,16,24N,03W	1105' FNL & 660' FEL	4 BBL	300 MCF	0.5 BBL

IV. Central Delivery Point Name: [See 19.15.27.9(D)(1) NMAC]

V. Anticipated Schedule: Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
LINDRITH B UNIT 41	3003923840					

VI. Separation Equipment: 🛛 Attach a complete description of how Operator will size separation equipment to optimize gas capture.

VII. Operational Practices: \boxtimes Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

VIII. Best Management Practices: 🖂 Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

Section 2 – Enhanced Plan EFFECTIVE APRIL 1, 2022

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

 \boxtimes Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

IX. Anticipated Natural Gas Production:

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF	

X. Natural Gas Gathering System (NGGS):

Operator	System	ULSTR of Tie-in	Anticipated Gathering	Available Maximum Daily Capacity
			Start Date	of System Segment Tie-in

XI. Map. \Box Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

XII. Line Capacity. The natural gas gathering system \Box will \Box will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

XIII. Line Pressure. Operator \Box does \Box does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

 \Box Attach Operator's plan to manage production in response to the increased line pressure.

XIV. Confidentiality: \Box Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

Section 3 - Certifications Effective May 25, 2021

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

 \boxtimes Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

 \Box Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system. *If Operator checks this box, Operator will select one of the following:*

Well Shut-In. \Box Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

Venting and Flaring Plan. \Box Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

Section 4 - Notices

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature: DUWNNOCH DEQO					
Printed Name: DAWN NASH-DEAL					
Title: REGULATORY TECHNICIAN					
E-mail Address: DNASH@HILCORP.COM					
Date: 04/12/2025					
Phone: 505-324-5132					
OIL CONSERVATION DIVISION					
(Only applicable when submitted as a standalone form)					
Approved By:					
Title:					
Approval Date:					
Conditions of Approval:					

VI. Separation Equipment:

Hilcorp Energy Company (HEC or Operator) production facilities include separation equipment designed to efficiently separate gas from liquid phases to optimize gas capture based on projected and estimated volumes from the targeted pool of our recomplete project. HEC will utilize flowback separation equipment and production separation equipment designed and built to industry specifications after the recomplete to optimize gas capture and send gas to sales or flare based on analytical composition. HEC operates facilities that are typically one-well facilities. Production separation equipment is upgraded prior to well being completed, if determined to be undersized or inadequate. This equipment is already on-site and tied into our sales gas lines prior to the recomplete operations.

VII. Operational Practices:

- 1. Subsection (A) Venting and Flaring of Natural Gas
 - HEC understands the requirements of NMAC 19.15.27.8 which outlines that the venting and flaring of natural gas during drilling, completion or production operations that constitutes waste as defined in 19.15.2 are prohibited.
- 2. Subsection (B) Venting and Flaring during drilling operations
 - This gas capture plan isn't for a well being drilled.
- 3. Subsection (C) Venting and flaring during completion or recompletion
 - Flowlines will be routed for flowback fluids into a completion or storage tank and if feasible under well conditions, flare rather than vent and commence operation of a separator as soon as it is technically feasible for a separator to function.
 - At any point in the well life (completion, production, inactive) an audio, visual and olfactory inspection be performed at prescribed intervals (weekly or monthly) pursuant to Subsection D of 19.15.27.8 NMAC, to confirm that all production equipment is operating properly and there are no leaks or releases.
- 4. Subsection (D) Venting and flaring during production operations
 - At any point in the well life (completion, production, inactive) an audio, visual and olfactory inspection be performed at prescribed intervals (weekly or monthly) pursuant to Subsection D of 19.15.27.8 NMAC, to confirm that all production equipment is operating properly and there are no leaks or releases.
 - Monitor manual liquid unloading for wells on-site or in close proximity (<30 minutes' drive time), take reasonable actions to achieve a stabilized rate and pressure at the earliest practical time, and take reasonable actions to minimize venting to the maximum extent practicable.
 - HEC will not vent or flare except during the approved activities listed in NMAC 19.15.27.8 (D) 1 4.
- 5. Subsection (E) Performance standards
 - All tanks and separation equipment are designed for maximum throughput and pressure to minimize waste.
 - If a flare is utilized during production operations it will have a continuous pilot and is located more than 100 feet from any known well or storage tanks.
 - At any point in the well life (completion, production, inactive) an audio, visual and olfactory inspection be performed at prescribed intervals (weekly or monthly) pursuant to Subsection D of 19.15.27.8 NMAC, to confirm that all production equipment is operating properly and there are no leaks or releases.

- 6. Subsection (F) Measurement or estimation of vented and flared natural gas
 - Measurement equipment is installed to measure the volume of natural gas flared from process piping.
 - When measurement isn't practicable, estimation of vented and flared natural gas will be completed as noted in 19.15.27.8 (F) 5-6.

VIII. Best Management Practices:

- 1. Operator has adequate storage and takeaway capacity for wells it chooses to recomplete as the flowlines at the sites are already in place and tied into a gathering system.
- 2. Operator will flare rather than vent vessel blowdown gas when technically feasible during active and/or planned maintenance to equipment on-site.
- 3. Operator combusts natural gas that would otherwise be vented or flared, when technically feasible.
- 4. Operator will shut in wells in the event of a takeaway disruption, emergency situation, or other operations where venting or flaring may occur due to equipment failures.

Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:	
HILCORP ENERGY COMPANY	372171	
1111 Travis Street	Action Number:	
Houston, TX 77002	452619	
	Action Type:	
	[C-103] NOI Recompletion (C-103E)	

CONDITIONS

Created By	Condition	Condition Date
ward.rikala	Notify the OCD inspection supervisor via email 24 Hours Prior to beginning operations.	4/30/2025
ward.rikala	All conducted logs shall be submitted to the OCD as a [UF-WL] EP Well Log Submission (WellLog).	4/30/2025
ward.rikala	If Cement is not adequate to protect casing and isolate strata: (a) the uppermost perforation in each additional pool to at least 150 feet above that perforation; and (b) the lowermost perforation in each added pool to at least 100 feet below that perforation, the appropriate Inspection supervisor shall be consulted and remedial action conducted as directed.	4/30/2025
ward.rikala	A C-104 packet is required if, a pool is added, or perforations are added above or below existing perfs.	4/30/2025

CONDITIONS

Page 16 of 16

Action 452619