State of New Mexico Energy, Minerals and Natural Resources Department

Submit Electronically Via E-permitting

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

Section 1 – Plan Description Effective May 25, 2021

I. Operator: 3R Opera	ating, LLC		OGRID: _33	1569		Date:	1 / 22 / 25
II. Type: ☐ Original ☐	Amendment	due to □ 19.15.27.	9.D(6)(a) NMA	C □ 19.15.27.9.D(6)(b) N	МАС □ О	ther.
If Other, please describe	:						
III. Well(s): Provide the be recompleted from a si					wells pro	oposed to l	be drilled or proposed to
Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	1	cipated MCF/D	Anticipated Produced Water BBL/D
See attachment							
V. Anticipated Schedul proposed to be recomple Well Name						Initial Fl Back Da	
See attachment							
Subsection A through F	ices: Attacling 19.15.27.8 In the Practices:	h a complete descr NMAC. Attach a complet	ription of the ac	tions Operator will	l take to	comply v	to optimize gas capture. with the requirements of ces to minimize venting

Section 2 Enhanced Plan

			E APRIL 1, 2022		
Beginning April 1, 2 reporting area must c			with its statewide natural ga	as capture requiren	nent for the applicable
☐ Operator certifies capture requirement		-	tion because Operator is in	compliance with its	s statewide natural gas
IX. Anticipated Nat	ural Gas Producti	on:			
We	sl1	API	Anticipated Average Natural Gas Rate MCF/D		l Volume of Natural ne First Year MCF
X. Natural Gas Gat	hering System (NC	GGS):			
Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date		num Daily Capacity Segment Tie-in
production operations the segment or portion the segment or portion in the segment or portion in the segment or portion in the segment or portion volume from the segment of the segment o	s to the existing or point of the natural gas gas. The natural gas gas from the well prior to the operator does system(s) describe a plan to manage program of the paragraph (2) of the prior of the paragraph (2) of the prior of the paragraph (2) of the paragraph (2) of the paragraph (2) of the paragraph (2) of the paragraph (3) of the paragraph (4) of the paragraph (5) of the paragraph (6) of the paragraph (7) of the paragraph	planned interconnect of to gathering system(s) to we thering system will to the date of first product does not anticipate that above will continue to enduction in response to the terts confidentiality pursuant to the system of the confidentiality pursuant to the confidentiali	at its existing well(s) connect meet anticipated increases in the increased line pressure. The uant to Section 71-2-8 NMS 27.9 NMAC, and attaches a financial section of the connection of the c	em(s), and the maximected. ather 100% of the seed to the same segral line pressure cause	anticipated natural gas ment, or portion, of the ed by the new well(s).

(i)

Section 3 - Certifications Effective May 25, 2021 Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal: ☐ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or ☐ Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system. If Operator checks this box, Operator will select one of the following: Well Shut-In. ☐ Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or Venting and Flaring Plan.

Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including: power generation on lease; (a) (b) power generation for grid; (c) compression on lease; (d) liquids removal on lease; (e) reinjection for underground storage; (f) reinjection for temporary storage; reinjection for enhanced oil recovery; (g) (h) fuel cell production; and

Section 4 - Notices

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

other alternative beneficial uses approved by the division.

- (a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or
- (b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.
- 2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature:	Kalen Melton
Printed Name:	Kalen Melton
Title:	Permitting Agent
E-mail Address	kmelton@reagansmith.com
Date:	1/22/25
Phone:	405-286-9326
	OIL CONSERVATION DIVISION
	(Only applicable when submitted as a standalone form)
Approved By:	
Title:	
Approval Date:	
Conditions of A	pproval:


Received by OCD: 5/22/2025 2:29:43 PM

XIV. Confidentiality

Uniqueness and variability of the formation encountered for this well is such that the Operator requests confidentiality in order to protect its proprietary data. After the responsible agency has conducted its review, the Operator requests the following information be REDACTED from the approved and posted permit(s), including anticipated production volumes and the Operator's planned development schedule. This information is expected to remain private between the submitting operator and the reviewing agency only.


III. Wells

	Water BE	Anticipated Initial Gas Production MCF/D		on BBL/D	Anticipate Production	Footages	JLSTR		API	ell Name	



V. Anticipated Schedule

Well Name	API	Spud date	TD Reached Date	Completion	Initial Flow Back Date	First Production Date
				Commencement Date		
MONGO 25 FED COM 502H	30-015-56625	7/15/2025	8/2/2025	9/1/2025	10/15/2025	10/29/2025
MONGO 25 FED COM 503H	30-015-56624	7/27/2025	8/14/2025	9/1/2025	10/15/2025	10/29/2025
MONGO 25 FED COM 702H	30-015-56623	8/8/2025	8/26/2025	9/1/2025	10/15/2025	10/29/2025
MONGO 25 FED COM 703H	30-015-56622	8/21/2025	9/8/2025	9/1/2025	10/15/2025	10/29/2025



VI. Separation Equipment

Separation equipment will be sized by construction engineering staff based on stated manufacturer daily throughput capacities and anticipated daily production rates to ensure adequate capacity. Closed vent system piping, compression needs, and VRUs will be sized utilizing modeling software to ensure adequate capacity for anticipated production volumes and conditions. Production composition and the volumes will be utilized as inputs to a process model which predicts relative amounts of gas, oil and water throughout the process. The high-volume case will be used to size equipment, piping and instrumentation.

Each well has a dedicated 3-phase separator and gas from that separator is taken directly to gas sales. Facility piping and pipeline will be sized to allow peak volumes to flow with minimal pressure loss and deliver to the midstream gatherer at an acceptable pressure. Water will be conveyed directly to tankage. Oil from 3-phase separators will be conveyed to a heated separator for enhanced liquid-liquid separation and degassing. Vapors from the heater treater are routed to flare. Oil and water storage tanks vapor outlets utilize a closed vent vapor system to ensure all working & breathing and flashing losses are routed to the flare which is sized to accommodate peak expected production volume. Flash volumes are estimated using the high-volume case.

VII. Operational Practices

The operator will ensure pipeline connectivity before producing hydrocarbons and will operate a closed vent vapor capture system that is designed to capture all associated and evolved gas during normal operation. Venting will only occur during maintenance activities or equipment failure. The operator may utilize the following from Section 3 for its operations to minimize flaring:

- A. The operator will maximize the recovery of natural gas by minimizing the waste, as defined by 19.15.2 NMAC, of natural gas through venting and flaring. The operator will ensure that well(s) will be connected to a natural gas gathering system with sufficient capacity to transport natural gas. If there is no adequate takeaway for the gas, compression will be added to deliver volumes that are produced. Well production may also be curtailed to manage the flow of gas and not overrun compression.
- B. All drilling operations will be equipped with a rig flare located at least 100' from the nearest surface hole. Rig flare will be utilized to combust any natural gas that is brought to surface during normal drilling operations.
- C. During completion operations any natural gas brought to surface will be flared. Immediately following the finish of completion operations, all well flowback will be directed to permanent separation equipment. Produced natural gas from separation equipment will be sent to sales. It is not anticipated that gas will not meet pipeline standards; however, if natural gas does not meet gathering pipeline quality specifications, the operator will flare the natural gas for up to 60 days or until the natural gas meets the pipeline quality specifications, whichever is sooner. The operator will ensure that the flare is sized properly and is equipped with automatic igniter or continuous pilot. The gas sample will be analyzed twice per week and the gas will be routed into a gathering system as soon as pipeline specifications are met.
- D. Natural gas will not be flared with the exceptions and provisions listed in the 19.15.27.8 D.(I) through (4). If there is no adequate takeaway for the separator gas, well(s) will be curtailed until the natural gas gathering system is available with exception of emergency or malfunction situations. Venting and/or flaring volumes will be measured using a total flow meter and reported appropriately.
- E. The operator will comply with the performance standards requirements and provisions listed in 19.15.27.8 E.(I) through (8). All equipment will be designed and sized to handle maximum anticipated pressures and throughputs to minimize the waste. Production storage tanks constructed after May 25, 2021, will be equipped with automatic gauging system. Flares constructed after May 25, 2021, will be equipped with automatic igniter or continuous pilot. Flares will be located at least 100' from the well and storage tanks unless otherwise approved by the division. The operator will conduct AVO inspections as described in 19.15.27.8 E (5) (a) with frequencies specified in 19.15.27.8 E (5) (b) and (c). All emergencies will be resolved as quickly and safely as feasible to minimize waste.
- F. The volume of natural gas that is vented or flared as the result of malfunction or emergency during drilling and completions operations will be estimated. The volume of natural gas that is vented, flared, or beneficially used during production operations, will be measured, or estimated. The operator will install equipment to measure the volume of natural gas flared from existing process piping, or a flowline piped from equipment such as high-

pressure separators, heater treaters, or vapor recovery units associated with a well or facility associated with a well authorized by an APD issued after May 25, 2021, that has an average daily production greater than 60 Mcf/day. If metering is not practicable due to circumstances such as low flow rate or low pressure venting and flaring, the operator will estimate the volume of vented or flared natural gas. Measuring equipment will conform to industry standards and will not be designed or equipped with a manifold that allows the diversion of natural gas around the metering element except for the sole purpose of inspecting and servicing the measurement equipment.

VIII. Best Management Practices

The operator utilizes automated engineering controls included in facility design to minimize venting and flaring. Additionally, operator's SOP support the minimization of flare and venting.

If the main gas outlet becomes unavailable and pressure increases on the outlet sales line, produced gas will be routed directly to the facility flare. The facility control system will alert personnel to the need for maintenance and appropriate response to the temporary flaring event. The facility design includes a closed vent vapor capture system to route flash from the heater treater and tanks to the flare. For maintenance activities, the operator will utilize the facility flare to blowdown equipment and piping whenever practical to minimize venting.

Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Action 466587

CONDITIONS

Operator:	OGRID:
3R Operating, LLC	331569
20405 State Highway 249	Action Number:
Houston, TX 77070	466587
	Action Type:
	[C-101] BLM - Federal/Indian Land Lease (Form 3160-3)

CONDITIONS

Created By	Condition	Condition Date
ward.rikala	None	5/22/2025