

Well Name: POKER LAKE UNIT 13-24 PC	Well Location: T24S / R29E / SEC 13 / SENE / 32.218561 / -103.932815	County or Parish/State: EDDY / NM
Well Number: 707H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM05912	Unit or CA Name: POKER LAKE UNIT	Unit or CA Number: NMNM71016X
US Well Number:	Operator: XTO PERMIAN OPERATING LLC	

Notice of Intent

Sundry ID: 2855396

Type of Submission: Notice of Intent

Type of Action: APD Change

Date Sundry Submitted: 05/30/2025

Time Sundry Submitted: 10:46

Date proposed operation will begin: 06/13/2025

Procedure Description: XTO Permian Operating, LLC. respectfully requests approval to make the following changes to the approved APD. Changes to include KOP, FTP, proposed total depth, pool, and dedicated acreage. FROM: TO: KOP: 2270' FNL & 1025' FEL OF SECTION 13-T24S-R29E 2636' FSL & 1031' FEL OF SECTION 13-T24S-R29E FTP: 1959' FNL & 1229' FEL OF SECTION 13-T24S-R29E 2504' FNL & 1027' FEL OF SECTION 13-T24S-R29E The proposed total depth is changing FROM 22021' MD; 9051' TVD TO 21980' MD; 8992' TVD. Pool code is changing FROM PIERCE CROSSING; BONE SPRING, EAST(96473) TO CEDAR CANYON; BONE SPRING(11520); PIERCE CROSSING; BONE SPRING(96473); WILDCAT S243006B; LWR BONE SPRING(97753) Dedicated acreage is changing FROM 719.94 ac TO 439.94 ac There is no new surface disturbance.

NOI Attachments

Procedure Description

POKER_LAKE_UNIT_13_24_PC_707H_Sundry_Docs_20250530104524.pdf

Well Name: POKER LAKE UNIT 13-24
PC

Well Location: T24S / R29E / SEC 13 /
SENE / 32.218561 / -103.932815

County or Parish/State: EDDY /
NM

Well Number: 707H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM05912

Unit or CA Name: POKER LAKE UNIT

Unit or CA Number:
NMNM71016X

US Well Number:

Operator: XTO PERMIAN OPERATING
LLC

Conditions of Approval

Additional

242913_Poker_Lake_Unit_13_24_PC_707H_06_09_2025_COAs_20250609085001.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: MANOJ VENKATESH

Signed on: MAY 30, 2025 10:45 AM

Name: XTO PERMIAN OPERATING LLC

Title: Regulatory Analyst

Street Address: 22777 SPRINGWOODS VILLAGE PARKWAY

City: SPRING

State: TX

Phone: (720) 539-1673

Email address: MANOJ.VENKATESH@EXXONMOBIL.COM

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: CHRISTOPHER WALLS

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752342234

BLM POC Email Address: cwalls@blm.gov

Disposition: Approved

Disposition Date: 06/09/2025

Signature: Chris Walls

Form 3160-5
(June 2019)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 2021

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.	NMNM05912
6. If Indian, Allottee or Tribe Name	

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other	7. If Unit of CA/Agreement, Name and/or No. POKER LAKE UNIT/NMNM71016X
2. Name of Operator XTO PERMIAN OPERATING LLC	8. Well Name and No. POKER LAKE UNIT 13-24 PC/707H
3a. Address 6401 HOLIDAY HILL ROAD BLDG 5, MIDLAND,	9. API Well No.
3b. Phone No. (include area code) (432) 683-2277	10. Field and Pool or Exploratory Area PIERCE CROSSING/BONE SPRING, EAST
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) SEC 13/T24S/R29E/NMP	11. Country or Parish, State EDDY/NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input checked="" type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

XTO Permian Operating, LLC. respectfully requests approval to make the following changes to the approved APD. Changes to include KOP, FTP, proposed total depth, pool, and dedicated acreage.

FROM: TO:

KOP: 2270' FNL & 1025 FEL OF SECTION 13-T24S-R29E 2636' FSL & 1031 FEL OF SECTION 13-T24S-R29E

FTP: 1959' FNL & 1229' FEL OF SECTION 13-T24S-R29E 2504' FNL & 1027' FEL OF SECTION 13-T24S-R29E

The proposed total depth is changing FROM 22021 MD; 9051 TVD TO 21980 MD; 8992 TVD.

Pool code is changing FROM PIERCE CROSSING; BONE SPRING, EAST(96473) TO CEDAR CANYON; BONE SPRING(11520); PIERCE CROSSING; BONE SPRING(96473); WILDCAT S243006B; LWR BONE SPRING(97753)

Continued on page 3 additional information

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) MANOJ VENKATESH / Ph: (720) 539-1673	Regulatory Analyst Title
Signature (Electronic Submission)	Date 05/30/2025

THE SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by CHRISTOPHER WALLS / Ph: (575) 234-2234 / Approved	Petroleum Engineer Title	06/09/2025 Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office CARLSBAD	

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Additional Remarks

Dedicated acreage is changing FROM 719.94 ac TO 439.94 ac

There is no new surface disturbance.

Location of Well

0. SHL: SENE / 2270 FNL / 1025 FEL / TWSP: 24S / RANGE: 29E / SECTION: 13 / LAT: 32.218561 / LONG: -103.932815 (TVD: 0 feet, MD: 0 feet)

PPP: SENE / 1959 FNL / 1229 FEL / TWSP: 24S / RANGE: 29E / SECTION: 13 / LAT: 32.219418 / LONG: -103.933473 (TVD: 9050 feet, MD: 9500 feet)

BHL: LOT 1 / 50 FNL / 940 FEL / TWSP: 24S / RANGE: 29E / SECTION: 1 / LAT: 32.253811 / LONG: -103.932606 (TVD: 9051 feet, MD: 22021 feet)

CONFIDENTIAL

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	XTO Permian Operating LLC
WELL NAME & NO.:	Poker Lake Unit 13-24 PC 707H
LOCATION:	Section 13, T.24S., R.29E.
COUNTY:	Eddy County

COA

H2S	<input checked="" type="radio"/> Yes	<input type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Wellhead Variance	<input type="radio"/> Diverter		
Other	<input type="checkbox"/> 4 String	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input checked="" type="checkbox"/> Fluid Filled	<input type="checkbox"/> Pilot Hole	<input type="checkbox"/> Open Annulus
Cementing	<input checked="" type="checkbox"/> Contingency Cement Squeeze	<input type="checkbox"/> EchoMeter	<input type="checkbox"/> Primary Cement Squeeze
Special Requirements	<input type="checkbox"/> Water Disposal	<input type="checkbox"/> COM	<input checked="" type="checkbox"/> Unit
Special Requirements	<input type="checkbox"/> Batch Sundry		
Special Requirements Variance	<input checked="" type="checkbox"/> Break Testing	<input checked="" type="checkbox"/> Offline Cementing	<input type="checkbox"/> Casing Clearance

Possibility of water flows in the Rustler
Possibility of lost circulation in the Salado, Castile, and Delaware
Abnormal pressures may be encountered upon penetrating the 3rd Bone Spring Sandstone and all subsequent formations.

A. HYDROGEN SULFIDE

A Hydrogen Sulfide (H2S) Drilling Plan shall be activated AT SPUD. As a result, the Hydrogen Sulfide area must meet 43 CFR part 3170 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.

B. CASING

1. The **9-5/8** inch surface casing shall be set at approximately **400** feet (a minimum of 70 feet (Eddy County) into the Rustler Anhydrite, above the salt, and below usable fresh water) and cemented to the surface. The surface hole shall be **12-1/4** inch in diameter.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the **7-5/8** inch intermediate casing is:
 - Cement to surface. If cement does not circulate see B.1.a, c-d above.

Operator has proposed to pump down 9-5/8" X 7-5/8" annulus after primary cementing stage. Operator must run Echo-meter to verify Cement Slurry/Fluid top in the annulus Or operator shall run a CBL from TD of the 7-5/8" casing to surface after the second stage BH to verify TOC.

Submit results to the BLM. No displacement fluid/wash out shall be utilized at the top of the cement slurry between second stage BH and top out. Operator must run one CBL per Well Pad.

If cement does not reach surface, the next casing string must come to surface.

Operator must use a limited flush fluid volume of 1 bbl following backside cementing procedures.

3. The minimum required fill of cement behind the **5-1/2** inch production casing is:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification. **Cement excess calculates to 21% - more cement may be needed.**

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the **9-5/8** inch surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in **43 CFR 3172** i must be followed.

D. SPECIAL REQUIREMENT (S)

Unit Wells

The well sign for a unit well shall include the unit number in addition to the surface and bottom hole lease numbers. This also applies to participating area numbers. If a participating area has not been established, the operator can use the general unit designation, but will replace the unit number with the participating area number when the sign is replaced.

Commercial Well Determination

A commercial well determination shall be submitted after production has been established for at least six months.

E. SPECIAL REQUIREMENT (S)

BOPE Break Testing Variance

- BOPE Break Testing is ONLY permitted for 5M BOPE or less. (**Annular preventer must be tested to a minimum of 70% of BOPE working pressure and shall be higher than the MASP**)
- BOPE Break Testing is NOT permitted to drilling the production hole section.
- Variance only pertains to the intermediate hole-sections and no deeper than the Bone Springs formation.
- While in transfer between wells, the BOPE shall be secured by the hydraulic carrier or cradle.
- Any well control event while drilling require notification to the BLM Petroleum Engineer (**575-706-2779**) prior to the commencement of any BOPE Break Testing operations.
- A full BOPE test is required prior to drilling the first deep intermediate hole section. If any subsequent hole interval is deeper than the first, a full BOPE test will be required. (200' TVD tolerance between intermediate shoes is allowable).
- The BLM is to be contacted (575-361-2822 Eddy County) 4 hours prior to BOPE tests.
- As a minimum, a full BOPE test shall be performed at 21-day intervals.
- In the event any repairs or replacement of the BOPE is required, the BOPE shall test as per **43 CFR 3172**.
- If in the event break testing is not utilized, then a full BOPE test would be conducted.

Offline Cementing

Contact the BLM prior to the commencement of any offline cementing procedure.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County
EMAIL or call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
BLM_NM_CFO_DrillingNotifications@BLM.GOV
 (575) 361-2822

Lea County
 Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240,
 (575) 689-5981

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - i. Notify the BLM when moving in and removing the Spudder Rig.
 - ii. Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - iii. BOP/BOPE test to be conducted per **43 CFR 3172** as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. For intervals in which cement to surface is required, cement to surface should be verified with a visual check and density or pH check to differentiate cement from spacer and drilling mud. The results should be documented in the driller's log and daily reports.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends of both lead and tail cement, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-Q potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in **43 CFR 3172**.

2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - i. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - ii. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - iii. Manufacturer representative shall install the test plug for the initial BOP test.
 - iv. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR 3172.6(b)(9) must be followed.
 - v. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - i. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However,

- if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
- ii. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (only applies to single stage cement jobs, prior to the cement setting up.)
 - iii. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve open. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to **43 CFR 3172** with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for 8 hours or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
 - iv. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
 - v. The results of the test shall be reported to the appropriate BLM office.
 - vi. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
 - vii. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
 - viii. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per **43 CFR 3172**.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area. Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

JS 6/9/2025

C-102 Submit electronically Via OCD Permitting	State of New Mexico Energy, Minerals & Natural Resources Department OIL CONVERSION DIVISION		Revised July, 09 2024
	Submittal Type:	<input type="checkbox"/> Initial Submittal	
		<input checked="" type="checkbox"/> Amended Report	
		<input type="checkbox"/> As Drilled	

WELL LOCATION INFORMATION

API Number 30-015-	Pool Code 11520	Pool Name CEDAR CANYON; BONE SPRING
Property Code	Property Name POKER LAKE UNIT 13-24 PC	Well Number 707H
OGRID No. 373075	Operator Name XTO PERMIAN OPERATING, LLC.	Ground Level Elevation 3,114'
Surface Owner: <input type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input checked="" type="checkbox"/> Federal		Mineral Owner: <input type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input checked="" type="checkbox"/> Federal

Surface Hole Location

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
H	13	24S	29E		2,270 FNL	1,025 FEL	32.218561	-103.932815	EDDY

Bottom Hole Location

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
	1	24S	29E	1	50 FNL	940 FEL	32.253811	-103.932606	EDDY

Dedicated Acres 159.94	Infill or Defining Well INFILL	Defining Well API	Overlapping Spacing Unit (Y/N) Y	Consolidation Code U
Order Numbers.			Well Setbacks are under Common Ownership: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
I	13	24S	29E		2,636 FSL	1,031 FEL	32.217440	-103.932836	EDDY

First Take Point (FTP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
H	13	24S	29E		2,504 FNL	1,027 FEL	32.217916	-103.932823	EDDY

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
	1	24S	29E	1	100 FNL	940 FEL	32.253673	-103.932606	EDDY

Unitized Area or Area of Interest NMNM105422429	Spacing Unit Type: <input checked="" type="checkbox"/> Horizontal <input type="checkbox"/> Vertical	Ground Elevation 3,114'
---	---	-----------------------------------

<p>OPERATOR CERTIFICATIONS</p> <p><i>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and, if the well is vertical or directional well, that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this at this location pursuant to a contract with an owner of a working interest or unleased mineral interest, or a voluntary pooling agreement or a compulsory pooling order of heretofore entered by the division.</i></p> <p><i>If this well is a horizontal well, I further certify that this organization has received the consent of at least one lessee or owner of a working interest or unleased mineral interest in each tract (in the target pool or information) in which any part of the well's completed interval will be located or obtained a compulsory pooling order from the division.</i></p> <p> Signature _____ Date 05/29/2025</p> <p>Manoj Venkatesh Printed Name _____</p> <p>manoj.venkatesh@exxonmobil.com Email Address _____</p>	<p>SURVEYOR CERTIFICATIONS</p> <p><i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief</i></p> <p style="text-align: right;"></p> <p> Signature and Seal of Professional Surveyor _____</p> <p>MARK DILLON HARP 23786 5/22/2025 Certificate Number Date of Survey</p> <p style="text-align: center;">YH 618.013003.04-26</p>
---	--


Note: No allowable will be assigned to this completion until all interest have been consolidated or a non-standard unit has been approved by the division.

P:\618.013 XTO Energy - NM\003 POKER LAKE Unit\04 - 13-1,13-24 PC - EDDY\Wells\26 - PLU Pierce Canyon 13-24 707H\DWG\13-24 PC 707H.dwg

ACREAGE DEDICATION PLATS

This grid represents a standard section. You may superimpose a non-standard section, or larger area, over this grid. Operators must outline the dedicated areage in a red box, clearly show the well surface location and bottom hole location, if it is directionally drilled, with the dimensions from the section lines in the cardinal directions. If this is a horizontal wellbore show on this plat the location of the First Take Point and Last Take Point, and the point within the completed interval (other than the First Take Point or Last Take Point) that is closest to any outer boundary of the tract.

Surveyors shall use the latest United States government survey or dependent resurvey. Well Locations will be in reference to the New Mexico Principal Meridian. If the land is not surveyed, contact the OCD Engineering Bureau. Independent subdivision surveys will not be accepted.



LEGEND

- SECTION LINE
- 330' BUFFER
- TOWNSHIP LINE
- MINERAL LEASE
- DEDICATED ACREAGE
- WELL BORE
- ▲ PPP
- WELL

WELL COORDINATE TABLE								
WELL	NAD 83 NME X	NAD 83 NME Y	NAD 83 LAT	NAD 83 LON	NAD 27 NME X	NAD 27 NME Y	NAD 27 LAT	NAD 27 LON
SHL	665,198.4	443,477.2	32.218561	-103.932815	624,014.9	443,417.9	32.218437	-103.932326
KOP	665,193.4	443,069.2	32.217440	-103.932836	624,009.9	443,009.9	32.217315	-103.932347
FTP	665,196.7	443,242.7	32.217916	-103.932823	624,013.2	443,183.3	32.217792	-103.932335
LTP	665,215.5	456,250.8	32.253673	-103.932606	624,032.4	456,191.1	32.253549	-103.932115
BHL	665,215.1	456,300.8	32.253811	-103.932606	624,032.0	456,241.1	32.253687	-103.932116
PPP #1	664,993.7	448,398.3	32.232090	-103.933418	623,810.3	448,338.8	32.231966	-103.932928

CORNER COORDINATE TABLE				
CORNER	NAD 83 NME X	NAD 83 NME Y	NAD 27 NME X	NAD 27 NME Y
A	663,576.0	443,093.9	622,392.5	443,034.6
B	663,570.2	445,748.2	622,386.8	445,688.8
C	663,559.1	448,399.9	622,375.8	448,340.4
D	663,547.9	451,051.0	622,364.7	450,991.4
E	663,524.5	453,696.5	622,341.4	453,636.9
F	663,501.0	456,347.1	622,318.0	456,287.4
G	666,224.6	443,088.1	625,041.0	443,028.8
H	666,218.3	445,746.5	625,034.9	445,687.1
I	666,205.3	448,396.9	625,022.0	448,337.4
J	666,193.9	451,046.7	625,010.6	450,987.1
K	666,174.6	453,699.9	624,991.5	453,640.3
L	666,154.8	456,352.9	624,971.7	456,293.2

G:\618.013 XTO Energy - NM\003 Poker Lake Unit\04 - 13-1,13-24 PC - EDDY\Wells\26 - PLU Pierce Canyon 13-24 707H\DWG\13-24 PC 707H.dwg

C-102 Submit electronically Via OCD Permitting	State of New Mexico Energy, Minerals & Natural Resources Department OIL CONVERSION DIVISION		Revised July, 09 2024
	Submittal Type:	<input type="checkbox"/> Initial Submittal	
		<input checked="" type="checkbox"/> Amended Report	
		<input type="checkbox"/> As Drilled	

WELL LOCATION INFORMATION

API Number 30-015-	Pool Code 96473	Pool Name PIERCE CROSSING; BONE SPRING
Property Code	Property Name POKER LAKE UNIT 13-24 PC	Well Number 707H
OGRID No. 373075	Operator Name XTO PERMIAN OPERATING, LLC.	Ground Level Elevation 3,114'
Surface Owner: <input type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input checked="" type="checkbox"/> Federal		Mineral Owner: <input type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input checked="" type="checkbox"/> Federal

Surface Hole Location

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
H	13	24S	29E		2,270 FNL	1,025 FEL	32.218561	-103.932815	EDDY

Bottom Hole Location

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
	1	24S	29E	1	50 FNL	940 FEL	32.253811	-103.932606	EDDY

Dedicated Acres 120.00	Infill or Defining Well INFILL	Defining Well API	Overlapping Spacing Unit (Y/N) Y	Consolidation Code U
Order Numbers.			Well Setbacks are under Common Ownership: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
I	13	24S	29E		2,636 FSL	1,031 FEL	32.217440	-103.932836	EDDY

First Take Point (FTP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
H	13	24S	29E		2,504 FNL	1,027 FEL	32.217916	-103.932823	EDDY

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
	1	24S	29E	1	100 FNL	940 FEL	32.253673	-103.932606	EDDY

Unitized Area or Area of Interest NMNM105422429	Spacing Unit Type: <input checked="" type="checkbox"/> Horizontal <input type="checkbox"/> Vertical	Ground Elevation 3,114'
---	---	-----------------------------------

<p>OPERATOR CERTIFICATIONS</p> <p><i>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and, if the well is vertical or directional well, that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this at this location pursuant to a contract with an owner of a working interest or unleased mineral interest, or a voluntary pooling agreement or a compulsory pooling order of heretofore entered by the division.</i></p> <p><i>If this well is a horizontal well, I further certify that this organization has received the consent of at least one lessee or owner of a working interest or unleased mineral interest in each tract (in the target pool or information) in which any part of the well's completed interval will be located or obtained a compulsory pooling order from the division.</i></p> <p> Signature</p> <p>05/29/2025 Date</p> <p>Manoj Venkatesh Printed Name</p> <p>manoj.venkatesh@exxonmobil.com Email Address</p>	<p>SURVEYOR CERTIFICATIONS</p> <p><i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief</i></p> <p> Signature and Seal of Professional Surveyor</p> <p></p> <p>MARK DILLON HARP 23786 Certificate Number</p> <p>5/22/2025 Date of Survey</p> <p style="text-align: center;">YH</p> <p style="text-align: right;">618.013003.04-26</p>
---	---


Note: No allowable will be assigned to this completion until all interest have been consolidated or a non-standard unit has been approved by the division.

P:\618.013 XTO Energy - NM\003 POKER LAKE Unit\04 - 13-1,13-24 PC - EDDY\Wells\26 - PLU Pierce Canyon 13-24 707H\DWG\13-24 PC 707H.dwg

ACREAGE DEDICATION PLATS

This grid represents a standard section. You may superimpose a non-standard section, or larger area, over this grid. Operators must outline the dedicated areage in a red box, clearly show the well surface location and bottom hole location, if it is directionally drilled, with the dimensions from the section lines in the cardinal directions. If this is a horizontal wellbore show on this plat the location of the First Take Point and Last Take Point, and the point within the completed interval (other than the First Take Point or Last Take Point) that is closest to any outer boundary of the tract.

Surveyors shall use the latest United States government survey or dependent resurvey. Well Locations will be in reference to the New Mexico Principal Meridian. If the land is not surveyed, contact the OCD Engineering Bureau. Independent subdivision surveys will not be accepted.



LEGEND

- SECTION LINE
- TOWNSHIP LINE
- DEDICATED ACREAGE
- 330' BUFFER
- MINERAL LEASE
- WELL BORE
- ▲ PPP
- WELL

WELL COORDINATE TABLE								
WELL	NAD 83 NME X	NAD 83 NME Y	NAD 83 LAT	NAD 83 LON	NAD 27 NME X	NAD 27 NME Y	NAD 27 LAT	NAD 27 LON
SHL	665,198.4	443,477.2	32.218561	-103.932815	624,014.9	443,417.9	32.218437	-103.932326
KOP	665,193.4	443,069.2	32.217440	-103.932836	624,009.9	443,009.9	32.217315	-103.932347
FTP	665,196.7	443,242.7	32.217916	-103.932823	624,013.2	443,183.3	32.217792	-103.932335
LTP	665,215.5	456,250.8	32.253673	-103.932606	624,032.4	456,191.1	32.253549	-103.932115
BHL	665,215.1	456,300.8	32.253811	-103.932606	624,032.0	456,241.1	32.253687	-103.932116
PPP #1	664,993.7	448,398.3	32.232090	-103.933418	623,810.3	448,338.8	32.231966	-103.932928

CORNER COORDINATE TABLE				
CORNER	NAD 83 NME X	NAD 83 NME Y	NAD 27 NME X	NAD 27 NME Y
A	663,576.0	443,093.9	622,392.5	443,034.6
B	663,570.2	445,748.2	622,386.8	445,688.8
C	663,559.1	448,399.9	622,375.8	448,340.4
D	663,547.9	451,051.0	622,364.7	450,991.4
E	663,524.5	453,696.5	622,341.4	453,636.9
F	663,501.0	456,347.1	622,318.0	456,287.4
G	666,224.6	443,088.1	625,041.0	443,028.8
H	666,218.3	445,746.5	625,034.9	445,687.1
I	666,205.3	448,396.9	625,022.0	448,337.4
J	666,193.9	451,046.7	625,010.6	450,987.1
K	666,174.6	453,699.9	624,991.5	453,640.3
L	666,154.8	456,352.9	624,971.7	456,293.2

G:\618.013 XTO Energy - NM\003 Poker Lake Unit\04 - 13-1,13-24 PC - EDDY\Wells\26 - PLU Pierce Canyon 13-24 707H\DWG\13-24 PC 707H.dwg

C-102 Submit electronically Via OCD Permitting	State of New Mexico Energy, Minerals & Natural Resources Department OIL CONVERSION DIVISION		Revised July, 09 2024
	Submittal Type:	<input type="checkbox"/> Initial Submittal	
		<input checked="" type="checkbox"/> Amended Report	
		<input type="checkbox"/> As Drilled	

WELL LOCATION INFORMATION

API Number 30-015-	Pool Code 97753	Pool Name WILDCAT S243006B; LWR BONE SPRING
Property Code	Property Name POKER LAKE UNIT 13-24 PC	Well Number 707H
OGRID No. 373075	Operator Name XTO PERMIAN OPERATING, LLC.	Ground Level Elevation 3,114'
Surface Owner: <input type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input checked="" type="checkbox"/> Federal		Mineral Owner: <input type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input checked="" type="checkbox"/> Federal

Surface Hole Location

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
H	13	24S	29E		2,270 FNL	1,025 FEL	32.218561	-103.932815	EDDY

Bottom Hole Location

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
	1	24S	29E	1	50 FNL	940 FEL	32.253811	-103.932606	EDDY

Dedicated Acres 160.00	Infill or Defining Well INFILL	Defining Well API	Overlapping Spacing Unit (Y/N) Y	Consolidation Code U
Order Numbers.			Well Setbacks are under Common Ownership: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
I	13	24S	29E		2,636 FSL	1,031 FEL	32.217440	-103.932836	EDDY

First Take Point (FTP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
H	13	24S	29E		2,504 FNL	1,027 FEL	32.217916	-103.932823	EDDY

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
	1	24S	29E	1	100 FNL	940 FEL	32.253673	-103.932606	EDDY

Unitized Area or Area of Interest NMNM105422429	Spacing Unit Type: <input checked="" type="checkbox"/> Horizontal <input type="checkbox"/> Vertical	Ground Elevation 3,114'
---	---	-----------------------------------

<p>OPERATOR CERTIFICATIONS</p> <p><i>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and, if the well is vertical or directional well, that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this at this location pursuant to a contract with an owner of a working interest or unleased mineral interest, or a voluntary pooling agreement or a compulsory pooling order of heretofore entered by the division.</i></p> <p><i>If this well is a horizontal well, I further certify that this organization has received the consent of at least one lessee or owner of a working interest or unleased mineral interest in each tract (in the target pool or information) in which any part of the well's completed interval will be located or obtained a compulsory pooling order from the division.</i></p> <p> Signature _____ Date 05/29/2025</p> <p>Manoj Venkatesh Printed Name _____</p> <p>manoj.venkatesh@exxonmobil.com Email Address _____</p>	<p>SURVEYOR CERTIFICATIONS</p> <p><i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief</i></p> <p> Signature and Seal of Professional Surveyor _____</p> <p></p> <p>MARK DILLON HARP 23786 Certificate Number _____ Date of Survey 5/22/2025</p> <p style="text-align: center;">YH 618.013003.04-26</p>
---	---


Note: No allowable will be assigned to this completion until all interest have been consolidated or a non-standard unit has been approved by the division.

P:\618.013 XTO Energy - NM\003 Poker Lake Unit\04 - 13-1,13-24 PC - EDDY\Wells\26 - PLU Pierce Canyon 13-24 707H\DWG\13-24 PC 707H.dwg

ACREAGE DEDICATION PLATS

This grid represents a standard section. You may superimpose a non-standard section, or larger area, over this grid. Operators must outline the dedicated areage in a red box, clearly show the well surface location and bottom hole location, if it is directionally drilled, with the dimensions from the section lines in the cardinal directions. If this is a horizontal wellbore show on this plat the location of the First Take Point and Last Take Point, and the point within the completed interval (other than the First Take Point or Last Take Point) that is closest to any outer boundary of the tract.

Surveyors shall use the latest United States government survey or dependent resurvey. Well Locations will be in reference to the New Mexico Principal Meridian. If the land is not surveyed, contact the OCD Engineering Bureau. Independent subdivision surveys will not be accepted.



LEGEND

- SECTION LINE
- TOWNSHIP LINE
- DEDICATED ACREAGE
- 330' BUFFER
- MINERAL LEASE
- WELL BORE
- ▲ PPP
- WELL

WELL COORDINATE TABLE								
WELL	NAD 83 NME X	NAD 83 NME Y	NAD 83 LAT	NAD 83 LON	NAD 27 NME X	NAD 27 NME Y	NAD 27 LAT	NAD 27 LON
SHL	665,198.4	443,477.2	32.218561	-103.932815	624,014.9	443,417.9	32.218437	-103.932326
KOP	665,193.4	443,069.2	32.217440	-103.932836	624,009.9	443,009.9	32.217315	-103.932347
FTP	665,196.7	443,242.7	32.217916	-103.932823	624,013.2	443,183.3	32.217792	-103.932335
LTP	665,215.5	456,250.8	32.253673	-103.932606	624,032.4	456,191.1	32.253549	-103.932115
BHL	665,215.1	456,300.8	32.253811	-103.932606	624,032.0	456,241.1	32.253687	-103.932116
PPP #1	664,993.7	448,398.3	32.232090	-103.933418	623,810.3	448,338.8	32.231966	-103.932928

CORNER COORDINATE TABLE				
CORNER	NAD 83 NME X	NAD 83 NME Y	NAD 27 NME X	NAD 27 NME Y
A	663,576.0	443,093.9	622,392.5	443,034.6
B	663,570.2	445,748.2	622,386.8	445,688.8
C	663,559.1	448,399.9	622,375.8	448,340.4
D	663,547.9	451,051.0	622,364.7	450,991.4
E	663,524.5	453,696.5	622,341.4	453,636.9
F	663,501.0	456,347.1	622,318.0	456,287.4
G	666,224.6	443,088.1	625,041.0	443,028.8
H	666,218.3	445,746.5	625,034.9	445,687.1
I	666,205.3	448,396.9	625,022.0	448,337.4
J	666,193.9	451,046.7	625,010.6	450,987.1
K	666,174.6	453,699.9	624,991.5	453,640.3
L	666,154.8	456,352.9	624,971.7	456,293.2

G:\618.013 XTO Energy - NM\003 Poker Lake Unit\04 - 13-1,13-24 PC - EDDY\Wells\26 - PLU Pierce Canyon 13-24 707H\DWG\13-24 PC 707H.dwg

DRILLING PLAN: BLM COMPLIANCE
(Supplement to BLM 3160-3)



ExxonMobil
Poker Lake Unit 13-24 PC 707H
Projected TD: 21980' MD / 8992' TVD
SHL: 2270' FNL & 1025' FEL, Section 13, T24S, R29E
BHL: 50' FNL & 940' FEL, Section 1, T24S, R29E
Eddy County, NM

1. Geologic Name of Surface Formation

A. Quaternary

2. Estimated Tops of Geological Markers & Depths of Anticipated Fresh Water, Oil or Gas

Formation	Well Depth	Water/Oil/Gas
Salado	749'	Water
Base of Salt	3156'	Water
Delaware	3359'	Water
Cherry Canyon	4251'	Water/Oil/Gas
Brushy Canyon	5800'	Water/Oil/Gas
Bone Spring Lm.	7106'	Water/Oil/Gas
Avalon Shale	7238'	Water/Oil/Gas
Avalon Lower	7782'	Water/Oil/Gas
1st Bone Spring Lime	7944'	Water/Oil/Gas
1st Bone Spring Sand	8096'	Water/Oil/Gas
2nd Bone Spring Lime	8427'	Water/Oil/Gas
2nd Bone Spring Sand	8955'	Water/Oil/Gas
3rd Bone Spring Lime		
3rd Bone Spring Upper Shale		
3rd Bone Spring Upper Shale Base		
3rd Bone Spring Lower Shale		
rd Bone Spring Lower Shale Marke		
3rd Bone Spring Sand		
Warwink		
Red Hills		
Wolfcamp A		
Wolfcamp B		
Wolfcamp C		
Wolfcamp D		
Landing	8992'	Water/Oil/Gas



	Inclination (°)	Azimuth (°)	True Vertical Depth (ft)	Y Offset (ft)	X Offset (ft)
SHL	0	0	0	0	0
KOP	0	0	8276	-408	-5
LP	90	0	8992	308	-5
FTP	45	0	8782	-198	-5
LTP	90	360	8992	12774	17
BHL	90	360	8992	12824	17

Section 2 Summary:

*** Deepest Expected Groundwater Depth: 40' (per NM State Engineers Office).

No other formations are expected to give up oil, gas or fresh water in measurable quantities. Surface fresh water sands will be protected by setting 9-5/8" inch casing at 724' and circulating cement back to surface.

3. Primary Casing Design

Primary Design:

Hole Size (in.)	MD	Casing TVD	OD Csg	Weight	Grade	Collar	New/Used	SF Burst	SF Collapse	SF Tension
12.25"	0' – 724'	724'	9-5/8"	40	J55	BTC	New	17.78	16.39	5.66
8.75"	0' – 4000'	3993'	7-5/8"	29.7	P110-ICY	Tenaris Wedge 511	New	5.99	8.51	3.53
8.75"	4000' – 8141'	8126'	7-5/8"	29.7	L80-IC	Tenaris Wedge 511	New	3.38	6.60	2.56
6.75"	0' – 8041'	8026'	5-1/2"	20	P110-CY	TPN	New	1.18	3.19	2.55
6.75"	8041' – 21980'	8992'	5-1/2"	20	P110-ICY	Tenaris Wedge 441	New	1.18	3.16	2.75

Section 3 Summary:

XTO will keep casing fluid filled to meet BLM's collapse requirement.
The planned kick off point is located at: 8291' MD / 8276' TVD.

Wellhead:

A multi-bowl wellhead system will be utilized. The well design chosen is: 3-String Slim Non-Potash

Wellhead will be installed by manufacturer's representatives.

Manufacturer will monitor welding process to ensure appropriate temperature of seal.

4. Cement Program

Primary Cementing								
Hole Section	Slurry Type	No. Sacks	Density (ppg)	Yield (ft3/sack)	TOC (ft)	Casing Setting Depth (MD)	Excess (%)	Slurry Description
Surface 1	Lead	126	12.4	2.11	0	724	100%	Surface 1 Class C Lead Cement
Surface 1	Tail	141	14.8	1.33	424	724	100%	Surface 1 Class C Tail Cement
Intermediate 1	Lead							
Intermediate 1	Tail	219	14.8	1.45	5800	8,141	35%	Intermediate 1 Class C Tail Cement
Production 1	Lead							
Production 1	Tail	1011	13.2	1.44	7641	21,980	25%	Production 1 Class C Tail Cement
Remedial Cementing								
Casing	Slurry Type	No. Sacks	Density (ppg)	Yield (ft3/sack)	Cemented Interval	Excess (%)	Slurry Description	
Intermediate 1	Bradenhead Squeeze	543	14.8	1.45	0 - 5800'	35%	Intermediate Class C Bradenhead Squeeze Cement	

Section 4 Summary:

*Bradenhead Squeeze 2nd Stage Offline

5. Pressure Control Equipment

Section 5 Summary:

Once the permanent WH is installed on the casing, the blow out preventer equipment (BOP) will consist of a minimum 5M Hydril and a minimum 10M triple Ram BOP.

All BOP testing will be done by an independent service company. Operator will Test as per 43CFR-3172

Requested Variances

4A) Offline Cementing Variance

XOM requests the option to offline cement and remediate (if needed) surface and intermediate casing strings where batch drilling is approved and if unplanned remediation is needed. XOM will ensure well is static with no pressure on the csg annulus, as with all other casing strings where batch drilling operations occur before moving off the rig. Offline cement operations will then be conducted after the rig is moved off the current well to the next well in the batch sequence. The TA cap will also be installed when applicable per wellhead manufacturer's procedure and pressure inside the casing will be monitored via the valve on the TA cap as per standard batch drilling ops.

5A) Break Test Variance

A break testing variance is requested to ONLY test broken pressure seals on the BOP equipment when moving from wellhead to wellhead for the intermediate hole sections which is in compliance with API Standard 53. The maximum anticipated surface pressure is less than 4800psi and the deepest intermediate casing point does not penetrate the Wolfcamp Formation.

5B) Flex Hose Variance

A variance is requested to allow use of a flex hose as the choke line from the BOP to the Choke Manifold. If this hose is used, a copy of the manufacturer's certification and pressure test chart will be kept on the rig. Attached is an example of a certification and pressure test chart. The manufacturer does not require anchors.

5C) 10M Annular Variance

XOM requests a variance to use a 5000 psi annular BOP with a 10,000 psi BOP stack. The component and compatibility tables attached along with the general well control plans demonstrate how the 5000 psi annular BOP will be protected from pressures that exceed its rated working pressure (RWP). The pressure at which the control of the wellbore is transferred from the annular preventer to another available preventer will not exceed 3500 psi (70% of the RWP of the 5000 psi annular BOP).

8A) Open Hole Logging Variance

Open hole logging will not be done on this well.

10A) Spudder Rig Variance

XOM requests the option to utilize a spudder rig (Atlas Copco RD20 or Equivalent) to set and cement surface casing.

10B) Batch Drilling Variance

XOM requests a variance to be able to batch drill this well. In doing so, XOM will set casing and ensure that the well is cemented properly (unless approval is given for offline cementing) and the well is static. XOM will contact the BLM to skid the rig to drill the remaining wells on the pad. Once surface and intermediate strings are all completed, XOM will begin drilling the production hole on each of the wells.

6. Proposed Mud Circulation System

INTERVAL	Hole Size	Mud Type	MW	Viscosity	Fluid Loss	Comments
			(ppg)	(sec/qt)	(cc)	
0' - 724'	12.25"	FW/Native	8.3 - 8.7	35-40	NC	Fresh Water or Native Water
724' - 8141'	8.75"	BDE/OBM or FW/Brine	9.5 - 10	30-32	NC	Fluid type will be based upon on well conditions. A fully saturated system will be used across the salt interval.
8141' - 21980'	6.75"	OBM	9 - 9.6	50-60	NC - 20	OBM or Cut Brine depending on Well Conditions

Section 6 Summary:

The necessary mud products for weight addition and fluid loss control will be on location at all times.

Pump viscous sweeps as needed for hole cleaning. Pump speed will be recorded on a daily drilling report after mudding up. An EDR (Electronic Drilling Recorder) will be used to detect changes in loss or gain of mud volume. A mud test will be performed every 24 hours to determine: density, viscosity, strength, filtration and pH as necessary. Use available solids controls equipment to help keep mud weight down after mud up. Rig up solids control equipment to operate as a closed loop system.

7. Auxiliary Well Control and Monitoring Equipment

Section 7 Summary:

A Kelly cock will be in the drill string at all times.

A full opening drill pipe stabbing valve having appropriate connections will be on the rig floor at all times.

H2S monitors will be on location when drilling below the 9-5/8" casing.

8. Logging, Coring and Testing Program

Section 8 Summary:

Open hole logging will not be done on this well.

9. Abnormal Pressures and Temperatures / Potential Hazards


Section 9 Summary:

The estimated bottom hole temperature of 156F to 176F. No H2S is expected but monitors will be in place to detect any H2S occurrences. Should these circumstances be encountered the operator and drilling contractor are prepared to take all necessary steps to ensure safety of all personnel and environment. Lost circulation is possible throughout the well.

10. Anticipated Starting Date and Duration of Operations

Section 10 Summary:

Anticipated spud date will be after BLM approval. Move in operations and drilling is expected to take 40 days.



Ground Elevation: 3112.0
RKB Elevation: 3112+30 @ 3142.0usft
Rig Name:



Northing	Easting	Latitude	Longitude
443384.64	624017.92	32° 13' 6.043 N	103° 55' 56.341 W

SECTION DETAILS

MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	Vsect	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
1600.0	0.00	0.00	1600.0	0.0	0.0	0.00	0.00	0.0	
1823.3	4.47	180.67	1823.1	-8.7	-0.1	2.00	180.67	-8.7	
6842.4	4.47	180.67	6826.9	-399.6	-4.6	0.00	0.00	-399.5	
7065.7	0.00	0.00	7050.0	-408.3	-4.7	2.00	180.00	-408.2	
8291.5	0.00	0.00	8275.8	-408.3	-4.7	0.00	0.00	-408.2	KOP Pin 4 PLU 13-24 PC 707H
9416.5	90.00	0.00	8992.0	307.9	-4.7	8.00	0.00	308.0	
10116.5	90.00	0.00	8992.0	1007.9	-4.7	0.00	0.00	1007.9	
10886.5	90.00	344.60	8992.0	1768.7	-107.6	2.00	-90.00	1769.2	
11643.0	90.00	359.73	8992.0	2516.0	-210.4	2.00	90.00	2517.0	
16126.0	90.00	359.73	8992.0	6999.0	-231.6	0.00	0.00	7000.0	
17035.7	90.00	17.92	8992.0	7894.1	-92.6	2.00	90.00	7894.5	
17952.9	90.00	359.58	8992.0	8796.8	46.4	2.00	-90.00	8796.4	
19139.6	90.00	359.58	8992.0	9983.4	37.7	0.00	0.00	9983.1	MP2 PLU 13-24 PC 707H Pln 4
21930.3	90.00	359.58	8992.0	12774.0	17.2	0.00	0.00	12773.7	LTP PLU 13-24 PC 707H Pln 4
21980.2	90.00	359.58	8992.0	12824.0	16.9	0.00	0.00	12823.7	PBHL PLU 13-24 PC 707H Pln 4

DESIGN TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
KOP Pin 4 PLU 13-24 PC 707H	8275.8	-408.3	-4.7	442976.38	624013.17	32° 13' 2.003 N	103° 55' 56.414 W
LP PLU 13-24 PC 707H Pln 4	8992.0	307.9	-4.7	443692.58	624013.17	32° 13' 9.091 N	103° 55' 56.383 W
LTP PLU 13-24 PC 707H Pln 4	8992.0	12774.0	17.2	456158.62	624035.14	32° 15' 12.456 N	103° 55' 55.585 W
MP1 PLU 13-24 PC 707H Pln 4	8992.0	9750.2	-249.5	453134.85	623768.47	32° 14' 42.542 N	103° 55' 58.822 W
MP2 PLU 13-24 PC 707H Pln 4	8992.0	9983.4	37.7	453368.04	624055.63	32° 14' 44.839 N	103° 55' 55.468 W
PBHL PLU 13-24 PC 707H Pln 4	8992.0	12824.0	16.9	456208.60	624034.78	32° 15' 12.950 N	103° 55' 55.587 W



COMPANY ROC

FIELD *HP 532/547/549/552 - Eddy County, NM (NAD 27 NME)
 SITE PLU 13-1-24 PC Pad C - Project for Ayush
 WELL PLU 13-24 PC 707H
 WELLPATH OH
 DESIGN Plan 4
 DEPTHUN1 (ft)

WELL INFO

MAP DATL NAD 1927 (NADCON CONUS)
 MAP SYSTI US State Plane 1927 (Exact solution)
 MAP ZONE New Mexico East 3001
 WELL LAT 32.21835
 WELL LON -103.932
 WELL EW I 624017.9
 WELL NS N 443384.6
 CONVERGI 0.21
 MAGMOD IGRF2020
 DECLINATI 6.4
 NORTH RE Grid
 GROUND E 3112
 KB ELEVN 3142
 VS AZI 359.72

SURVEY TYPE INFORMATION

H 0.00 - 21980.12 PLAN 4 : XOM_R2OWSG MWD+IFR1+MS

SURVEY LIST

Measured MD	Inclination INC	Azimuth AZI	Course CL	Ler TVD	True SSTVD	Vertic TVD	SubSea NS	Local N/-S EW	Local E/-W X	Easting	Northing Y
0	0	0	0	0	0	3142	0	0	0	624017.9	443384.6
100	0	0	0	100	100	3042	0	0	0	624017.9	443384.6
200	0	0	0	100	200	2942	0	0	0	624017.9	443384.6
300	0	0	0	100	300	2842	0	0	0	624017.9	443384.6
400	0	0	0	100	400	2742	0	0	0	624017.9	443384.6
500	0	0	0	100	500	2642	0	0	0	624017.9	443384.6
600	0	0	0	100	600	2542	0	0	0	624017.9	443384.6
700	0	0	0	100	700	2442	0	0	0	624017.9	443384.6
800	0	0	0	100	800	2342	0	0	0	624017.9	443384.6
900	0	0	0	100	900	2242	0	0	0	624017.9	443384.6
1000	0	0	0	100	1000	2142	0	0	0	624017.9	443384.6
1100	0	0	0	100	1100	2042	0	0	0	624017.9	443384.6
1200	0	0	0	100	1200	1942	0	0	0	624017.9	443384.6
1300	0	0	0	100	1300	1842	0	0	0	624017.9	443384.6
1400	0	0	0	100	1400	1742	0	0	0	624017.9	443384.6
1500	0	0	0	100	1500	1642	0	0	0	624017.9	443384.6
1600	0	0	0	100	1600	1542	0	0	0	624017.9	443384.6

1700	2	180.667	100	1699.98	1442.02	-1.745	-0.02	624017.9	443382.9
1800	4	180.667	100	1799.838	1342.162	-6.978	-0.081	624017.8	443377.7
1823.338	4.467	180.667	23.338	1823.112	1318.888	-8.701	-0.101	624017.8	443375.9
1900	4.467	180.667	76.662	1899.541	1242.459	-14.671	-0.171	624017.7	443370
2000	4.467	180.667	100	1999.237	1142.763	-22.458	-0.261	624017.7	443362.2
2100	4.467	180.667	100	2098.934	1043.066	-30.246	-0.352	624017.6	443354.4
2200	4.467	180.667	100	2198.63	943.37	-38.033	-0.443	624017.5	443346.6
2300	4.467	180.667	100	2298.326	843.674	-45.821	-0.533	624017.4	443338.8
2400	4.467	180.667	100	2398.022	743.978	-53.609	-0.624	624017.3	443331
2500	4.467	180.667	100	2497.719	644.281	-61.396	-0.714	624017.2	443323.2
2600	4.467	180.667	100	2597.415	544.585	-69.184	-0.805	624017.1	443315.5
2700	4.467	180.667	100	2697.111	444.889	-76.971	-0.896	624017	443307.7
2800	4.467	180.667	100	2796.807	345.193	-84.759	-0.986	624016.9	443299.9
2900	4.467	180.667	100	2896.504	245.496	-92.546	-1.077	624016.8	443292.1
3000	4.467	180.667	100	2996.2	145.8	-100.334	-1.167	624016.8	443284.3
3100	4.467	180.667	100	3095.896	46.104	-108.121	-1.258	624016.7	443276.5
3200	4.467	180.667	100	3195.592	-53.592	-115.909	-1.349	624016.6	443268.7
3300	4.467	180.667	100	3295.289	-153.289	-123.696	-1.439	624016.5	443260.9
3400	4.467	180.667	100	3394.985	-252.985	-131.484	-1.53	624016.4	443253.2
3500	4.467	180.667	100	3494.681	-352.681	-139.272	-1.62	624016.3	443245.4
3600	4.467	180.667	100	3594.378	-452.378	-147.059	-1.711	624016.2	443237.6
3700	4.467	180.667	100	3694.074	-552.074	-154.847	-1.802	624016.1	443229.8
3800	4.467	180.667	100	3793.77	-651.77	-162.634	-1.892	624016	443222
3900	4.467	180.667	100	3893.466	-751.466	-170.422	-1.983	624015.9	443214.2
4000	4.467	180.667	100	3993.163	-851.163	-178.209	-2.073	624015.8	443206.4
4100	4.467	180.667	100	4092.859	-950.859	-185.997	-2.164	624015.8	443198.6
4200	4.467	180.667	100	4192.555	-1050.56	-193.784	-2.255	624015.7	443190.9
4300	4.467	180.667	100	4292.251	-1150.25	-201.572	-2.345	624015.6	443183.1
4400	4.467	180.667	100	4391.948	-1249.95	-209.359	-2.436	624015.5	443175.3
4500	4.467	180.667	100	4491.644	-1349.64	-217.147	-2.526	624015.4	443167.5
4600	4.467	180.667	100	4591.34	-1449.34	-224.935	-2.617	624015.3	443159.7
4700	4.467	180.667	100	4691.037	-1549.04	-232.722	-2.708	624015.2	443151.9
4800	4.467	180.667	100	4790.733	-1648.73	-240.51	-2.798	624015.1	443144.1
4900	4.467	180.667	100	4890.429	-1748.43	-248.297	-2.889	624015	443136.3
5000	4.467	180.667	100	4990.125	-1848.13	-256.085	-2.979	624014.9	443128.6
5100	4.467	180.667	100	5089.822	-1947.82	-263.872	-3.07	624014.9	443120.8
5200	4.467	180.667	100	5189.518	-2047.52	-271.66	-3.161	624014.8	443113
5300	4.467	180.667	100	5289.214	-2147.21	-279.447	-3.251	624014.7	443105.2
5400	4.467	180.667	100	5388.91	-2246.91	-287.235	-3.342	624014.6	443097.4
5500	4.467	180.667	100	5488.607	-2346.61	-295.022	-3.433	624014.5	443089.6
5600	4.467	180.667	100	5588.303	-2446.3	-302.81	-3.523	624014.4	443081.8
5700	4.467	180.667	100	5687.999	-2546	-310.598	-3.614	624014.3	443074
5800	4.467	180.667	100	5787.695	-2645.7	-318.385	-3.704	624014.2	443066.3
5900	4.467	180.667	100	5887.392	-2745.39	-326.173	-3.795	624014.1	443058.5
6000	4.467	180.667	100	5987.088	-2845.09	-333.96	-3.886	624014	443050.7
6100	4.467	180.667	100	6086.784	-2944.78	-341.748	-3.976	624013.9	443042.9
6200	4.467	180.667	100	6186.481	-3044.48	-349.535	-4.067	624013.9	443035.1

6300	4.467	180.667	100	6286.177	-3144.18	-357.323	-4.157	624013.8	443027.3
6400	4.467	180.667	100	6385.873	-3243.87	-365.11	-4.248	624013.7	443019.5
6500	4.467	180.667	100	6485.569	-3343.57	-372.898	-4.339	624013.6	443011.7
6600	4.467	180.667	100	6585.266	-3443.27	-380.686	-4.429	624013.5	443004
6700	4.467	180.667	100	6684.962	-3542.96	-388.473	-4.52	624013.4	442996.2
6800	4.467	180.667	100	6784.658	-3642.66	-396.261	-4.61	624013.3	442988.4
6842.359	4.467	180.667	42.359	6826.888	-3684.89	-399.559	-4.649	624013.3	442985.1
6900	3.314	180.667	57.641	6884.396	-3742.4	-403.47	-4.694	624013.2	442981.2
7000	1.314	180.667	100	6984.309	-3842.31	-407.507	-4.741	624013.2	442977.1
7065.697	0	0	65.697	7050	-3908	-408.26	-4.75	624013.2	442976.4
7100	0	0	34.303	7084.303	-3942.3	-408.26	-4.75	624013.2	442976.4
7200	0	0	100	7184.303	-4042.3	-408.26	-4.75	624013.2	442976.4
7300	0	0	100	7284.303	-4142.3	-408.26	-4.75	624013.2	442976.4
7400	0	0	100	7384.303	-4242.3	-408.26	-4.75	624013.2	442976.4
7500	0	0	100	7484.303	-4342.3	-408.26	-4.75	624013.2	442976.4
7600	0	0	100	7584.303	-4442.3	-408.26	-4.75	624013.2	442976.4
7700	0	0	100	7684.303	-4542.3	-408.26	-4.75	624013.2	442976.4
7800	0	0	100	7784.303	-4642.3	-408.26	-4.75	624013.2	442976.4
7900	0	0	100	7884.303	-4742.3	-408.26	-4.75	624013.2	442976.4
8000	0	0	100	7984.303	-4842.3	-408.26	-4.75	624013.2	442976.4
8100	0	0	100	8084.303	-4942.3	-408.26	-4.75	624013.2	442976.4
8200	0	0	100	8184.303	-5042.3	-408.26	-4.75	624013.2	442976.4
8291.497	0	0	91.497	8275.8	-5133.8	-408.26	-4.75	624013.2	442976.4
8300	0.68	0	8.503	8284.303	-5142.3	-408.21	-4.75	624013.2	442976.4
8350	4.68	0	50	8334.238	-5192.24	-405.872	-4.75	624013.2	442978.8
8400	8.68	0	50	8383.889	-5241.89	-400.057	-4.75	624013.2	442984.6
8450	12.68	0	50	8433.013	-5291.01	-390.792	-4.75	624013.2	442993.8
8500	16.68	0	50	8481.37	-5339.37	-378.123	-4.75	624013.2	443006.5
8550	20.68	0	50	8528.727	-5386.73	-362.112	-4.75	624013.2	443022.5
8600	24.68	0	50	8574.851	-5432.85	-342.837	-4.75	624013.2	443041.8
8650	28.68	0	50	8619.518	-5477.52	-320.391	-4.75	624013.2	443064.2
8700	32.68	0	50	8662.511	-5520.51	-294.884	-4.75	624013.2	443089.8
8750	36.68	0	50	8703.62	-5561.62	-266.44	-4.75	624013.2	443118.2
8800	40.68	0	50	8742.644	-5600.64	-235.197	-4.75	624013.2	443149.4
8850	44.68	0	50	8779.394	-5637.39	-201.309	-4.75	624013.2	443183.3
8900	48.68	0	50	8813.69	-5671.69	-164.939	-4.75	624013.2	443219.7
8950	52.68	0	50	8845.366	-5703.37	-126.266	-4.75	624013.2	443258.4
9000	56.68	0	50	8874.267	-5732.27	-85.478	-4.75	624013.2	443299.2
9050	60.68	0	50	8900.253	-5758.25	-42.772	-4.75	624013.2	443341.9
9100	64.68	0	50	8923.196	-5781.2	1.642	-4.75	624013.2	443386.3
9150	68.68	0	50	8942.985	-5800.99	47.548	-4.75	624013.2	443432.2
9200	72.68	0	50	8959.524	-5817.52	94.723	-4.75	624013.2	443479.4
9250	76.68	0	50	8972.731	-5830.73	142.936	-4.75	624013.2	443527.6
9300	80.68	0	50	8982.543	-5840.54	191.954	-4.75	624013.2	443576.6
9350	84.68	0	50	8988.912	-5846.91	241.536	-4.75	624013.2	443626.2
9400	88.68	0	50	8991.807	-5849.81	291.442	-4.75	624013.2	443676.1
9416.497	90	0	16.497	8991.997	-5850	307.937	-4.75	624013.2	443692.6

9500	90	0	83.503	8991.997	-5850	391.441	-4.75	624013.2	443776.1
9600	90	0	100	8991.997	-5850	491.441	-4.75	624013.2	443876.1
9700	90	0	100	8991.997	-5850	591.441	-4.75	624013.2	443976.1
9800	90	0	100	8991.997	-5850	691.441	-4.75	624013.2	444076.1
9900	90	0	100	8991.997	-5850	791.441	-4.75	624013.2	444176.1
10000	90	0	100	8991.997	-5850	891.441	-4.75	624013.2	444276.1
10100	90	0	100	8991.997	-5850	991.441	-4.75	624013.2	444376.1
10116.5	90	0	16.497	8991.997	-5850	1007.937	-4.75	624013.2	444392.6
10200	90	358.33	83.503	8991.997	-5850	1091.429	-5.967	624012	444476.1
10300	90	356.33	100	8991.997	-5850	1191.315	-10.625	624007.3	444576
10400	90	354.33	100	8991.997	-5850	1290.978	-18.766	623999.2	444675.6
10500	90	352.33	100	8991.997	-5850	1390.296	-30.381	623987.5	444774.9
10600	90	350.33	100	8991.997	-5850	1489.148	-45.455	623972.5	444873.8
10700	90	348.33	100	8991.997	-5850	1587.414	-63.969	623954	444972.1
10800	90	346.33	100	8991.997	-5850	1684.974	-85.902	623932	445069.6
10886.5	90	344.6	86.497	8991.997	-5850	1768.699	-107.609	623910.3	445153.3
10900	90	344.87	13.503	8991.997	-5850	1781.726	-111.164	623906.8	445166.4
11000	90	346.87	100	8991.997	-5850	1878.696	-135.575	623882.3	445263.3
11100	90	348.87	100	8991.997	-5850	1976.458	-156.587	623861.3	445361.1
11200	90	350.87	100	8991.997	-5850	2074.894	-174.174	623843.7	445459.5
11300	90	352.87	100	8991.997	-5850	2173.884	-188.315	623829.6	445558.5
11400	90	354.87	100	8991.997	-5850	2273.308	-198.993	623818.9	445657.9
11500	90	356.87	100	8991.997	-5850	2373.043	-206.195	623811.7	445757.7
11600	90	358.87	100	8991.997	-5850	2472.969	-209.911	623808	445857.6
11643	90	359.73	42.997	8991.997	-5850	2515.962	-210.436	623807.5	445900.6
11700	90	359.73	57.003	8991.997	-5850	2572.964	-210.705	623807.2	445957.6
11800	90	359.73	100	8991.997	-5850	2672.963	-211.176	623806.7	446057.6
11900	90	359.73	100	8991.997	-5850	2772.962	-211.647	623806.3	446157.6
12000	90	359.73	100	8991.997	-5850	2872.961	-212.119	623805.8	446257.6
12100	90	359.73	100	8991.997	-5850	2972.96	-212.59	623805.3	446357.6
12200	90	359.73	100	8991.997	-5850	3072.959	-213.061	623804.9	446457.6
12300	90	359.73	100	8991.997	-5850	3172.958	-213.532	623804.4	446557.6
12400	90	359.73	100	8991.997	-5850	3272.957	-214.004	623803.9	446657.6
12500	90	359.73	100	8991.997	-5850	3372.956	-214.475	623803.4	446757.6
12600	90	359.73	100	8991.997	-5850	3472.954	-214.946	623803	446857.6
12700	90	359.73	100	8991.997	-5850	3572.953	-215.417	623802.5	446957.6
12800	90	359.73	100	8991.997	-5850	3672.952	-215.889	623802	447057.6
12900	90	359.73	100	8991.997	-5850	3772.951	-216.36	623801.6	447157.6
13000	90	359.73	100	8991.997	-5850	3872.95	-216.831	623801.1	447257.6
13100	90	359.73	100	8991.997	-5850	3972.949	-217.302	623800.6	447357.6
13200	90	359.73	100	8991.997	-5850	4072.948	-217.774	623800.1	447457.6
13300	90	359.73	100	8991.997	-5850	4172.947	-218.245	623799.7	447557.6
13400	90	359.73	100	8991.997	-5850	4272.946	-218.716	623799.2	447657.6
13500	90	359.73	100	8991.997	-5850	4372.944	-219.187	623798.7	447757.6
13600	90	359.73	100	8991.997	-5850	4472.943	-219.658	623798.3	447857.6
13700	90	359.73	100	8991.997	-5850	4572.942	-220.13	623797.8	447957.6
13800	90	359.73	100	8991.997	-5850	4672.941	-220.601	623797.3	448057.6

13900	90	359.73	100	8991.997	-5850	4772.94	-221.072	623796.8	448157.6
14000	90	359.73	100	8991.997	-5850	4872.939	-221.543	623796.4	448257.6
14100	90	359.73	100	8991.997	-5850	4972.938	-222.015	623795.9	448357.6
14200	90	359.73	100	8991.997	-5850	5072.937	-222.486	623795.4	448457.6
14300	90	359.73	100	8991.997	-5850	5172.936	-222.957	623795	448557.6
14400	90	359.73	100	8991.997	-5850	5272.934	-223.428	623794.5	448657.6
14500	90	359.73	100	8991.997	-5850	5372.933	-223.9	623794	448757.6
14600	90	359.73	100	8991.997	-5850	5472.932	-224.371	623793.5	448857.6
14700	90	359.73	100	8991.997	-5850	5572.931	-224.842	623793.1	448957.6
14800	90	359.73	100	8991.997	-5850	5672.93	-225.313	623792.6	449057.6
14900	90	359.73	100	8991.997	-5850	5772.929	-225.785	623792.1	449157.6
15000	90	359.73	100	8991.997	-5850	5872.928	-226.256	623791.7	449257.6
15100	90	359.73	100	8991.997	-5850	5972.927	-226.727	623791.2	449357.6
15200	90	359.73	100	8991.997	-5850	6072.926	-227.198	623790.7	449457.6
15300	90	359.73	100	8991.997	-5850	6172.924	-227.67	623790.3	449557.6
15400	90	359.73	100	8991.997	-5850	6272.923	-228.141	623789.8	449657.6
15500	90	359.73	100	8991.997	-5850	6372.922	-228.612	623789.3	449757.6
15600	90	359.73	100	8991.997	-5850	6472.921	-229.083	623788.8	449857.6
15700	90	359.73	100	8991.997	-5850	6572.92	-229.554	623788.4	449957.6
15800	90	359.73	100	8991.997	-5850	6672.919	-230.026	623787.9	450057.6
15900	90	359.73	100	8991.997	-5850	6772.918	-230.497	623787.4	450157.6
16000	90	359.73	100	8991.997	-5850	6872.917	-230.968	623787	450257.6
16100	90	359.73	100	8991.997	-5850	6972.916	-231.439	623786.5	450357.6
16126.04	90	359.73	26.037	8991.997	-5850	6998.952	-231.562	623786.4	450383.6
16200	90	1.209	73.963	8991.997	-5850	7072.911	-230.956	623787	450457.6
16300	90	3.209	100	8991.997	-5850	7172.831	-227.101	623790.8	450557.5
16400	90	5.209	100	8991.997	-5850	7272.557	-219.762	623798.2	450657.2
16500	90	7.209	100	8991.997	-5850	7371.965	-208.946	623809	450756.6
16600	90	9.209	100	8991.997	-5850	7470.935	-194.668	623823.3	450855.6
16700	90	11.209	100	8991.997	-5850	7569.347	-176.944	623841	450954
16800	90	13.209	100	8991.997	-5850	7667.08	-155.797	623862.1	451051.7
16900	90	15.209	100	8991.997	-5850	7764.016	-131.252	623886.7	451148.7
17000	90	17.209	100	8991.997	-5850	7860.036	-103.339	623914.6	451244.7
17035.74	90	17.924	35.737	8991.997	-5850	7894.106	-92.553	623925.4	451278.7
17100	90	16.639	64.263	8991.997	-5850	7955.467	-73.463	623944.5	451340.1
17200	90	14.639	100	8991.997	-5850	8051.76	-46.507	623971.4	451436.4
17300	90	12.639	100	8991.997	-5850	8148.935	-22.929	623995	451533.6
17400	90	10.639	100	8991.997	-5850	8246.874	-2.756	624015.2	451631.5
17500	90	8.639	100	8991.997	-5850	8345.457	13.987	624031.9	451730.1
17600	90	6.639	100	8991.998	-5850	8444.565	27.279	624045.2	451829.2
17700	90	4.639	100	8991.998	-5850	8544.076	37.104	624055	451928.7
17800	90	2.639	100	8991.998	-5850	8643.869	43.45	624061.4	452028.5
17900	90	0.639	100	8991.998	-5850	8743.823	46.31	624064.2	452128.5
17952.94	90	359.58	52.942	8991.998	-5850	8796.764	46.411	624064.3	452181.4
18000	90	359.58	47.058	8991.998	-5850	8843.821	46.066	624064	452228.5
18100	90	359.58	100	8991.998	-5850	8943.818	45.333	624063.3	452328.5
18200	90	359.58	100	8991.998	-5850	9043.816	44.599	624062.5	452428.5

18300	90	359.58	100	8991.999	-5850	9143.813	43.866	624061.8	452528.5
18400	90	359.58	100	8991.999	-5850	9243.81	43.133	624061.1	452628.5
18500	90	359.58	100	8991.999	-5850	9343.808	42.4	624060.3	452728.4
18600	90	359.58	100	8991.999	-5850	9443.805	41.667	624059.6	452828.4
18700	90	359.58	100	8991.999	-5850	9543.802	40.933	624058.9	452928.4
18800	90	359.58	100	8991.999	-5850	9643.8	40.2	624058.1	453028.4
18900	90	359.58	100	8992	-5850	9743.797	39.467	624057.4	453128.4
19000	90	359.58	100	8992	-5850	9843.794	38.734	624056.7	453228.4
19100	90	359.58	100	8992	-5850	9943.792	38	624055.9	453328.4
19139.61	90	359.58	39.609	8992	-5850	9983.4	37.71	624055.6	453368
19200	90	359.58	60.391	8992	-5850	10043.79	37.267	624055.2	453428.4
19300	90	359.58	100	8992	-5850	10143.79	36.534	624054.5	453528.4
19400	90	359.58	100	8992	-5850	10243.78	35.801	624053.7	453628.4
19500	90	359.58	100	8992.001	-5850	10343.78	35.068	624053	453728.4
19600	90	359.58	100	8992.001	-5850	10443.78	34.334	624052.3	453828.4
19700	90	359.58	100	8992.001	-5850	10543.78	33.601	624051.5	453928.4
19800	90	359.58	100	8992.001	-5850	10643.77	32.868	624050.8	454028.4
19900	90	359.58	100	8992.001	-5850	10743.77	32.135	624050.1	454128.4
20000	90	359.58	100	8992.001	-5850	10843.77	31.401	624049.3	454228.4
20100	90	359.58	100	8992.002	-5850	10943.77	30.668	624048.6	454328.4
20200	90	359.58	100	8992.002	-5850	11043.76	29.935	624047.9	454428.4
20300	90	359.58	100	8992.002	-5850	11143.76	29.202	624047.1	454528.4
20400	90	359.58	100	8992.002	-5850	11243.76	28.469	624046.4	454628.4
20500	90	359.58	100	8992.002	-5850	11343.75	27.735	624045.7	454728.4
20600	90	359.58	100	8992.002	-5850	11443.75	27.002	624044.9	454828.4
20700	90	359.58	100	8992.003	-5850	11543.75	26.269	624044.2	454928.4
20800	90	359.58	100	8992.003	-5850	11643.75	25.536	624043.5	455028.4
20900	90	359.58	100	8992.003	-5850	11743.74	24.803	624042.7	455128.4
21000	90	359.58	100	8992.003	-5850	11843.74	24.069	624042	455228.4
21100	90	359.58	100	8992.003	-5850	11943.74	23.336	624041.3	455328.4
21200	90	359.58	100	8992.003	-5850	12043.74	22.603	624040.5	455428.4
21300	90	359.58	100	8992.004	-5850	12143.73	21.87	624039.8	455528.4
21400	90	359.58	100	8992.004	-5850	12243.73	21.136	624039.1	455628.4
21500	90	359.58	100	8992.004	-5850	12343.73	20.403	624038.3	455728.4
21600	90	359.58	100	8992.004	-5850	12443.72	19.67	624037.6	455828.4
21700	90	359.58	100	8992.004	-5850	12543.72	18.937	624036.9	455928.4
21800	90	359.58	100	8992.004	-5850	12643.72	18.204	624036.1	456028.4
21900	90	359.58	100	8992.005	-5850.01	12743.72	17.47	624035.4	456128.4
21930.27	90	359.58	30.265	8992.005	-5850.01	12773.98	17.248	624035.2	456158.6
21980.25	90	359.58	49.981	8992.005	-5850.01	12823.96	16.882	624034.8	456208.6

Latitude	Longitude	Dogleg	Sev	Build Rate	Turn Rate	Vertical Section
LAT	LON	DLS	BLD	TRN	VS	
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0
32.21835	-103.932	0	0	0	0	0


32.21834	-103.932	2	2	0	-1.745
32.21833	-103.932	2	2	0	-6.978
32.21832	-103.932	2	2	0	-8.7
32.21831	-103.932	0	0	0	-14.67
32.21828	-103.932	0	0	0	-22.457
32.21826	-103.932	0	0	0	-30.244
32.21824	-103.932	0	0	0	-38.031
32.21822	-103.932	0	0	0	-45.818
32.2182	-103.932	0	0	0	-53.605
32.21818	-103.932	0	0	0	-61.392
32.21816	-103.932	0	0	0	-69.179
32.21813	-103.932	0	0	0	-76.966
32.21811	-103.932	0	0	0	-84.753
32.21809	-103.932	0	0	0	-92.54
32.21807	-103.932	0	0	0	-100.327
32.21805	-103.932	0	0	0	-108.114
32.21803	-103.932	0	0	0	-115.901
32.21801	-103.932	0	0	0	-123.688
32.21798	-103.932	0	0	0	-131.475
32.21796	-103.932	0	0	0	-139.262
32.21794	-103.932	0	0	0	-147.049
32.21792	-103.932	0	0	0	-154.836
32.2179	-103.932	0	0	0	-162.623
32.21788	-103.932	0	0	0	-170.41
32.21786	-103.932	0	0	0	-178.197
32.21783	-103.932	0	0	0	-185.984
32.21781	-103.932	0	0	0	-193.771
32.21779	-103.932	0	0	0	-201.558
32.21777	-103.932	0	0	0	-209.345
32.21775	-103.932	0	0	0	-217.132
32.21773	-103.932	0	0	0	-224.919
32.21771	-103.932	0	0	0	-232.706
32.21768	-103.932	0	0	0	-240.493
32.21766	-103.932	0	0	0	-248.28
32.21764	-103.932	0	0	0	-256.067
32.21762	-103.932	0	0	0	-263.854
32.2176	-103.932	0	0	0	-271.641
32.21758	-103.932	0	0	0	-279.428
32.21756	-103.932	0	0	0	-287.215
32.21753	-103.932	0	0	0	-295.002
32.21751	-103.932	0	0	0	-302.789
32.21749	-103.932	0	0	0	-310.576
32.21747	-103.932	0	0	0	-318.363
32.21745	-103.932	0	0	0	-326.15
32.21743	-103.932	0	0	0	-333.937
32.21741	-103.932	0	0	0	-341.724
32.21739	-103.932	0	0	0	-349.511

32.21736	-103.932	0	0	0	-357.298
32.21734	-103.932	0	0	0	-365.085
32.21732	-103.932	0	0	0	-372.872
32.2173	-103.932	0	0	0	-380.659
32.21728	-103.932	0	0	0	-388.446
32.21726	-103.932	0	0	0	-396.233
32.21725	-103.932	0	0	0	-399.532
32.21724	-103.932	2	-2	0	-403.442
32.21723	-103.932	2	-2	0	-407.479
32.21722	-103.932	2	-2	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	0	0	0	-408.232
32.21722	-103.932	8	8	0	-408.181
32.21723	-103.932	8	8	0	-405.844
32.21725	-103.932	8	8	0	-400.029
32.21727	-103.932	8	8	0	-390.764
32.21731	-103.932	8	8	0	-378.096
32.21735	-103.932	8	8	0	-362.085
32.2174	-103.932	8	8	0	-342.81
32.21747	-103.932	8	8	0	-320.364
32.21754	-103.932	8	8	0	-294.857
32.21761	-103.932	8	8	0	-266.413
32.2177	-103.932	8	8	0	-235.171
32.21779	-103.932	8	8	0	-201.283
32.21789	-103.932	8	8	0	-164.914
32.218	-103.932	8	8	0	-126.241
32.21811	-103.932	8	8	0	-85.453
32.21823	-103.932	8	8	0	-42.749
32.21835	-103.932	8	8	0	1.665
32.21848	-103.932	8	8	0	47.571
32.21861	-103.932	8	8	0	94.745
32.21874	-103.932	8	8	0	142.958
32.21887	-103.932	8	8	0	191.974
32.21901	-103.932	8	8	0	241.556
32.21915	-103.932	8	8	0	291.462
32.21919	-103.932	8	8	0	307.957


32.21942	-103.932	0	0	0	391.459
32.2197	-103.932	0	0	0	491.458
32.21997	-103.932	0	0	0	591.457
32.22025	-103.932	0	0	0	691.455
32.22052	-103.932	0	0	0	791.454
32.2208	-103.932	0	0	0	891.453
32.22107	-103.932	0	0	0	991.452
32.22112	-103.932	0	0	0	1007.948
32.22135	-103.932	2	0	-2	1091.445
32.22162	-103.932	2	0	-2	1191.353
32.22189	-103.932	2	0	-2	1291.054
32.22217	-103.932	2	0	-2	1390.428
32.22244	-103.932	2	0	-2	1489.353
32.22271	-103.933	2	0	-2	1587.708
32.22298	-103.933	2	0	-2	1685.374
32.22321	-103.933	2	0	-2	1769.204
32.22324	-103.933	2	0	2	1782.248
32.22351	-103.933	2	0	2	1879.336
32.22378	-103.933	2	0	2	1977.2
32.22405	-103.933	2	0	2	2075.721
32.22432	-103.933	2	0	2	2174.779
32.2246	-103.933	2	0	2	2274.253
32.22487	-103.933	2	0	2	2374.022
32.22515	-103.933	2	0	2	2473.965
32.22526	-103.933	2	0	2	2516.96
32.22542	-103.933	0	0	0	2573.963
32.2257	-103.933	0	0	0	2673.963
32.22597	-103.933	0	0	0	2773.963
32.22625	-103.933	0	0	0	2873.963
32.22652	-103.933	0	0	0	2973.963
32.2268	-103.933	0	0	0	3073.963
32.22707	-103.933	0	0	0	3173.963
32.22735	-103.933	0	0	0	3273.963
32.22762	-103.933	0	0	0	3373.963
32.22789	-103.933	0	0	0	3473.963
32.22817	-103.933	0	0	0	3573.963
32.22844	-103.933	0	0	0	3673.963
32.22872	-103.933	0	0	0	3773.963
32.22899	-103.933	0	0	0	3873.963
32.22927	-103.933	0	0	0	3973.963
32.22954	-103.933	0	0	0	4073.963
32.22982	-103.933	0	0	0	4173.963
32.23009	-103.933	0	0	0	4273.963
32.23037	-103.933	0	0	0	4373.963
32.23064	-103.933	0	0	0	4473.963
32.23092	-103.933	0	0	0	4573.963
32.23119	-103.933	0	0	0	4673.963

32.23147	-103.933	0	0	0	4773.963
32.23174	-103.933	0	0	0	4873.963
32.23202	-103.933	0	0	0	4973.963
32.23229	-103.933	0	0	0	5073.963
32.23257	-103.933	0	0	0	5173.963
32.23284	-103.933	0	0	0	5273.963
32.23312	-103.933	0	0	0	5373.963
32.23339	-103.933	0	0	0	5473.963
32.23367	-103.933	0	0	0	5573.963
32.23394	-103.933	0	0	0	5673.963
32.23422	-103.933	0	0	0	5773.963
32.23449	-103.933	0	0	0	5873.963
32.23477	-103.933	0	0	0	5973.963
32.23504	-103.933	0	0	0	6073.963
32.23532	-103.933	0	0	0	6173.963
32.23559	-103.933	0	0	0	6273.963
32.23587	-103.933	0	0	0	6373.963
32.23614	-103.933	0	0	0	6473.963
32.23642	-103.933	0	0	0	6573.963
32.23669	-103.933	0	0	0	6673.963
32.23697	-103.933	0	0	0	6773.963
32.23724	-103.933	0	0	0	6873.963
32.23752	-103.933	0	0	0	6973.963
32.23759	-103.933	0	0	0	7000
32.23779	-103.933	2	0	2	7073.955
32.23807	-103.933	2	0	2	7173.856
32.23834	-103.933	2	0	2	7273.544
32.23861	-103.933	2	0	2	7372.898
32.23888	-103.933	2	0	2	7471.797
32.23916	-103.933	2	0	2	7570.121
32.23942	-103.933	2	0	2	7667.75
32.23969	-103.933	2	0	2	7764.564
32.23995	-103.933	2	0	2	7860.447
32.24005	-103.933	2	0	2	7894.464
32.24022	-103.932	2	0	-2	7955.731
32.24048	-103.932	2	0	-2	8051.891
32.24075	-103.932	2	0	-2	8148.95
32.24102	-103.932	2	0	-2	8246.789
32.24129	-103.932	2	0	-2	8345.289
32.24156	-103.932	2	0	-2	8444.331
32.24183	-103.932	2	0	-2	8543.793
32.24211	-103.932	2	0	-2	8643.554
32.24238	-103.932	2	0	-2	8743.493
32.24253	-103.932	2	0	-2	8796.433
32.24266	-103.932	0	0	0	8843.49
32.24293	-103.932	0	0	0	8943.49
32.24321	-103.932	0	0	0	9043.49

32.24348	-103.932	0	0	0	9143.49
32.24376	-103.932	0	0	0	9243.489
32.24403	-103.932	0	0	0	9343.489
32.24431	-103.932	0	0	0	9443.489
32.24458	-103.932	0	0	0	9543.488
32.24486	-103.932	0	0	0	9643.488
32.24513	-103.932	0	0	0	9743.488
32.24541	-103.932	0	0	0	9843.487
32.24568	-103.932	0	0	0	9943.487
32.24579	-103.932	0	0	0	9983.097
32.24596	-103.932	0	0	0	10043.49
32.24623	-103.932	0	0	0	10143.49
32.2465	-103.932	0	0	0	10243.49
32.24678	-103.932	0	0	0	10343.49
32.24705	-103.932	0	0	0	10443.49
32.24733	-103.932	0	0	0	10543.49
32.2476	-103.932	0	0	0	10643.49
32.24788	-103.932	0	0	0	10743.49
32.24815	-103.932	0	0	0	10843.48
32.24843	-103.932	0	0	0	10943.48
32.2487	-103.932	0	0	0	11043.48
32.24898	-103.932	0	0	0	11143.48
32.24925	-103.932	0	0	0	11243.48
32.24953	-103.932	0	0	0	11343.48
32.2498	-103.932	0	0	0	11443.48
32.25008	-103.932	0	0	0	11543.48
32.25035	-103.932	0	0	0	11643.48
32.25063	-103.932	0	0	0	11743.48
32.2509	-103.932	0	0	0	11843.48
32.25118	-103.932	0	0	0	11943.48
32.25145	-103.932	0	0	0	12043.48
32.25173	-103.932	0	0	0	12143.48
32.252	-103.932	0	0	0	12243.48
32.25228	-103.932	0	0	0	12343.48
32.25255	-103.932	0	0	0	12443.48
32.25283	-103.932	0	0	0	12543.48
32.2531	-103.932	0	0	0	12643.48
32.25338	-103.932	0	0	0	12743.48
32.25346	-103.932	0	0	0	12773.74
32.2536	-103.932	0	0	0	12823.72



Bleed line will discharge 100' from wellhead for non-H2S situations and 150' from wellhead for H2S situations.



Drilling Operations
Choke Manifold
10M Service

10M Choke Manifold Diagram
 XTO



TenarisHydril Wedge 511



Coupling	Pipe Body
Grade: P110-ICY	Grade: P110-ICY
Body: White	1st Band: White
1st Band: Pale Green	2nd Band: Pale Green
2nd Band: -	3rd Band: Pale Green
3rd Band: -	4th Band: -
	5th Band: -
	6th Band: -

Outside Diameter	7.625 in.	Wall Thickness	0.375 in.	Grade	P110-ICY
Min. Wall Thickness	90.00 %	Pipe Body Drift	API Standard	Type	Casing
Connection OD Option	REGULAR				

Pipe Body Data

Geometry				Performance	
Nominal OD	7.625 in.	Wall Thickness	0.375 in.	Body Yield Strength	1068 x1000 lb
Nominal Weight	29.70 lb/ft	Plain End Weight	29.06 lb/ft	Min. Internal Yield Pressure	11,070 psi
Drift	6.750 in.	OD Tolerance	API	SMYS	125,000 psi
Nominal ID	6.875 in.			Collapse Pressure	7360 psi

Connection Data

Geometry		Performance		Make-Up Torques	
Connection OD	7.625 in.	Tension Efficiency	61.10 %	Minimum	5900 ft-lb
Connection ID	6.787 in.	Joint Yield Strength	653 x1000 lb	Optimum	7100 ft-lb
Make-up Loss	3.704 in.	Internal Pressure Capacity	11,070 psi	Maximum	10,300 ft-lb
Threads per inch	3.28	Compression Efficiency	73.80 %		
Connection OD Option	Regular	Compression Strength	788 x1000 lb	Operation Limit Torques	
		Max. Allowable Bending	45.83 °/100 ft	Operating Torque	55,000 ft-lb
		External Pressure Capacity	7360 psi	Yield Torque	82,000 ft-lb

Notes

For the latest performance data, always visit our website: www.tenaris.com
 For further information on concepts indicated in this datasheet, download the Datasheet Manual from www.tenaris.com

Tenaris has issued this document for general information only, and the information in this document, including, without limitation, any pictures, drawings or designs ("Information") is not intended to constitute professional or any other type of advice or recommendation and is provided on an "as is" basis. No warranty is given. Tenaris has not independently verified any information—if any—provided by the user in connection with, or for the purpose of, the Information contained hereunder. The use of the Information is at user's own risk and Tenaris does not assume any responsibility or liability of any kind for any loss, damage or injury resulting from, or in connection with any Information contained hereunder or any use thereof. The Information in this document is subject to change or modification without notice. Tenaris's products and services are subject to Tenaris's standard terms and conditions or otherwise to the terms resulting from the respective contracts of sale or services, as the case may be, between petitioner and Tenaris. For more complete information please contact a Tenaris's representative or visit our website at www.tenaris.com. ©Tenaris 2025. All rights reserved.



TenarisHydril Wedge 511



Coupling	Pipe Body
Grade: L80-IC	Grade: L80-IC
Body: Red	1st Band: Red
1st Band: Brown	2nd Band: Brown
2nd Band: -	3rd Band: Pale Green
3rd Band: -	4th Band: -
	5th Band: -
	6th Band: -

Outside Diameter	7.625 in.	Wall Thickness	0.375 in.	Grade	L80-IC
Min. Wall Thickness	87.50 %	Pipe Body Drift	API Standard	Type	Casing
Connection OD Option	REGULAR				

Pipe Body Data

Geometry				Performance	
Nominal OD	7.625 in.	Wall Thickness	0.375 in.	Body Yield Strength	683 x1000 lb
Nominal Weight	29.70 lb/ft	Plain End Weight	29.06 lb/ft	Min. Internal Yield Pressure	6890 psi
Drift	6.750 in.	OD Tolerance	API	SMYS	80,000 psi
Nominal ID	6.875 in.			Collapse Pressure	5900 psi

Connection Data

Geometry		Performance		Make-Up Torques	
Connection OD	7.625 in.	Tension Efficiency	61.10 %	Minimum	5900 ft-lb
Connection ID	6.787 in.	Joint Yield Strength	417 x1000 lb	Optimum	7100 ft-lb
Make-up Loss	3.704 in.	Internal Pressure Capacity	6890 psi	Maximum	10,300 ft-lb
Threads per inch	3.28	Compression Efficiency	73.80 %		
Connection OD Option	Regular	Compression Strength	504 x1000 lb	Operation Limit Torques	
		Max. Allowable Bending	29.33 °/100 ft	Operating Torque	35,000 ft-lb
		External Pressure Capacity	5900 psi	Yield Torque	52,000 ft-lb

Notes

For the latest performance data, always visit our website: www.tenaris.com
 For further information on concepts indicated in this datasheet, download the Datasheet Manual from www.tenaris.com

Tenaris has issued this document for general information only, and the information in this document, including, without limitation, any pictures, drawings or designs ("Information") is not intended to constitute professional or any other type of advice or recommendation and is provided on an "as is" basis. No warranty is given. Tenaris has not independently verified any information—if any—provided by the user in connection with, or for the purpose of, the Information contained hereunder. The use of the Information is at user's own risk and Tenaris does not assume any responsibility or liability of any kind for any loss, damage or injury resulting from, or in connection with any Information contained hereunder or any use thereof. The Information in this document is subject to change or modification without notice. Tenaris's products and services are subject to Tenaris's standard terms and conditions or otherwise to the terms resulting from the respective contracts of sale or services, as the case may be, between petitioner and Tenaris. For more complete information please contact a Tenaris's representative or visit our website at www.tenaris.com. ©Tenaris 2024. All rights reserved.



TPN™



Coupling	Pipe Body
Grade: P110-CY	Grade: P110-CY
Body: White	1st Band: White
1st Band: Grey	2nd Band: Grey
2nd Band: -	3rd Band: -
3rd Band: -	4th Band: -
	5th Band: -
	6th Band: -

Outside Diameter	5.500 in.	Wall Thickness	0.361 in.	Grade	P110-CY
Min. Wall Thickness	87.50 %	Pipe Body Drift	API Standard	Type	Casing
Connection OD Option	REGULAR				

Pipe Body Data

Geometry		Performance	
Nominal OD	5.500 in.	Wall Thickness	0.361 in.
Nominal Weight	20.00 lb/ft	Plain End Weight	19.83 lb/ft
Drift	4.653 in.	OD Tolerance	API
Nominal ID	4.778 in.		
		Body Yield Strength	641 x1000 lb
		Min. Internal Yield Pressure	12,640 psi
		SMYS	110,000 psi
		Collapse Pressure	11,100 psi

Connection Data

Geometry		Performance		Make-Up Torques	
Connection OD	6.300 in.	Tension Efficiency	100 %	Minimum	13,860 ft-lb
Coupling Length	8.408 in.	Joint Yield Strength	641 x1000 lb	Optimum	15,400 ft-lb
Connection ID	4.778 in.	Internal Pressure Capacity	12,640 psi	Maximum	16,940 ft-lb
Make-up Loss	4.204 in.	Compression Efficiency	100 %		
Threads per inch	5	Compression Strength	641 x1000 lb	Operation Limit Torques	
Connection OD Option	Regular	Max. Allowable Bending	92 °/100 ft	Operating Torque	26,350 ft-lb
		External Pressure Capacity	11,100 psi	Yield Torque	29,300 ft-lb

Notes

For the latest performance data, always visit our website: www.tenaris.com
 For further information on concepts indicated in this datasheet, download the Datasheet Manual from www.tenaris.com

Tenaris has issued this document for general information only, and the information in this document, including, without limitation, any pictures, drawings or designs ("Information") is not intended to constitute professional or any other type of advice or recommendation and is provided on an "as is" basis. No warranty is given. Tenaris has not independently verified any information—if any—provided by the user in connection with, or for the purpose of, the Information contained hereunder. The use of the Information is at user's own risk and Tenaris does not assume any responsibility or liability of any kind for any loss, damage or injury resulting from, or in connection with any Information contained hereunder or any use thereof. The Information in this document is subject to change or modification without notice. Tenaris's products and services are subject to Tenaris's standard terms and conditions or otherwise to the terms resulting from the respective contracts of sale or services, as the case may be, between petitioner and Tenaris. For more complete information please contact a Tenaris's representative or visit our website at www.tenaris.com. ©Tenaris 2023. All rights reserved.

PI/CIII



TenarisHydril Wedge 441®



Coupling	Pipe Body
Grade: P110-ICY	Grade: P110-ICY
Body: White	1st Band: White
1st Band: Pale Green	2nd Band: Pale Green
2nd Band: -	3rd Band: Pale Green
3rd Band: -	4th Band: -
	5th Band: -
	6th Band: -

Outside Diameter	5.500 in.	Wall Thickness	0.361 in.	Grade	P110-ICY
Min. Wall Thickness	87.50 %	Pipe Body Drift	API Standard	Type	Casing
Connection OD Option	REGULAR				

Pipe Body Data

Geometry				Performance	
Nominal OD	5.500 in.	Wall Thickness	0.361 in.	Body Yield Strength	729 x1000 lb
Nominal Weight	20.00 lb/ft	Plain End Weight	19.83 lb/ft	Min. Internal Yield Pressure	14,360 psi
Drift	4.653 in.	OD Tolerance	API	SMYS	125,000 psi
Nominal ID	4.778 in.			Collapse Pressure	12,300 psi

Connection Data


Geometry		Performance		Make-Up Torques	
Connection OD	5.852 in.	Tension Efficiency	81.50 %	Minimum	15,000 ft-lb
Coupling Length	8.714 in.	Joint Yield Strength	594 x1000 lb	Optimum	16,000 ft-lb
Connection ID	4.778 in.	Internal Pressure Capacity	14,360 psi	Maximum	19,200 ft-lb
Make-up Loss	3.780 in.	Compression Efficiency	81.50 %		
Threads per inch	3.40	Compression Strength	594 x1000 lb	Operation Limit Torques	
Connection OD Option	Regular	Max. Allowable Bending	84.76 °/100 ft	Operating Torque	36,000 ft-lb
		External Pressure Capacity	12,300 psi	Yield Torque	42,000 ft-lb
				Buck-On	
				Minimum	19,200 ft-lb
				Maximum	20,700 ft-lb

Notes

This connection is fully interchangeable with:
 Wedge 441® - 5.5 in. - 0.304 (17.00) in. (lb/ft)
 Wedge 461® - 5.5 in. - 0.304 (17.00) / 0.361 (20.00) / 0.415 (23.00) in. (lb/ft)
 Connections with Dopeless® Technology are fully compatible with the same connection in its doped version

For the latest performance data, always visit our website: www.tenaris.com
 For further information on concepts indicated in this datasheet, download the Datasheet Manual from www.tenaris.com

Tenaris has issued this document for general information only, and the information in this document, including, without limitation, any pictures, drawings or designs ("Information") is not intended to constitute professional or any other type of advice or recommendation and is provided on an "as is" basis. No warranty is given. Tenaris has not independently verified any information –if any- provided by the user in connection with, or for the purpose of, the Information contained hereunder. The use of the Information is at user's own risk and Tenaris does not assume any responsibility or liability of any kind for any loss, damage or injury resulting from, or in connection with any Information contained hereunder or any use thereof. The Information in this document is subject to change or modification without notice. Tenaris's products and services are subject to Tenaris's standard terms and conditions or otherwise to the terms resulting from the respective contracts of sale or services, as the case may be, between petitioner and Tenaris. For more complete information please contact a Tenaris's representative or visit our website at www.tenaris.com. ©Tenaris 2025. All rights reserved.



ALL DIMENSIONS APPROXIMATE

CACTUS WELLHEAD LLC

XTO ENERGY INC
DELAWARE BASIN

20" x 9-5/8" x 7-5/8" x 5-1/2" MBU-T-CFL-R-DBLO Wellhead
With 11" 10M x 7-1/16" 15M CTH-DBLHPS Tubing Head
And 9-5/8", 7-5/8" & 5-1/2" Pin Bottom Mandrel Casing Hangers

DRAWN	VJK	31MAR22
APPRV		
DRAWING NO.		HBE0000479

XTO respectfully requests approval to utilize a spudder rig to pre-set surface casing.

Description of Operations:

1. Spudder rig will move in to drill the surface hole and pre-set surface casing on the well.
 - a. After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
 - b. The spudder rig will utilize fresh water-based mud to drill the surface hole to TD. Solids control will be handled entirely on a closed loop basis. No earth pits will be used.
2. The wellhead will be installed and tested as soon as the surface casing is cut off and WOC time has been reached.
3. A blind flange at the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with needle valves installed on two wing valves.
 - a. A means for intervention will be maintained while the drilling rig is not over the well.
4. Spudder rig operations are expected to take 2-3 days per well on the pad.
5. The BLM will be contacted and notified 24 hours prior to commencing spudder rig operations.
6. Drilling Operations will begin with a larger rig and a BOP stack equal to or greater than the pressure rating that was permitted will be nipped up and tested on the wellhead before drilling operations resume on each well.
 - a. The larger rig will move back onto the location within 90 days from the point at which the wells are secured and the spudder rig is moved off location.
 - b. The BLM will be notified 24 hours before the larger rig moves back on the pre-set locations
7. XTO will have supervision on the rig to ensure compliance with all BLM and NMOCD regulations and to oversee operations.
8. Once the rig is removed, XTO will secure the wellhead area by placing a guard rail around the cellar area.

Subject: Request for a Variance Allowing break Testing of the Blowout Preventer Equipment (BOPE)

XTO Energy requests a variance to ONLY test broken pressure seals on the BOPE and function test BOP when skidding a drilling rig between multiple wells on a pad.

Background

Onshore Oil and Gas Order CFR Title 43 Part 3170, Drilling Operations, Sections III.A.2.i.iv.B states that the BOP test must be performed whenever any seal subject to test pressure is broken. The current interpretation of the Bureau of Land Management (BLM) requires a complete BOP test and not just a test of the affected component. CFR Title 43 Part 3170 states, "Some situation may exist either on a well-by-well basis or field-wide basis whereby it is commonly accepted practice to vary a particular minimum standard(s) established in this order. This situation can be resolved by requesting a variance...". XTO Energy feels the break testing the BOPE is such a situation. Therefore, as per CFR Title 43 Part 3170, XTO Energy submits this request for the variance.

Supporting Documentation

CFR Title 43 Part 3170 became effective on December 19, 1988 and has remained the standard for regulating BLM onshore drilling operations for over 30 years. During this time there have been significant changes in drilling technology. BLM continues to use the variance request process to allow for the use of modern technology and acceptable engineering practices that have arisen since CFR Title 43 Part 3170 was originally released. The XTO Energy drilling rig fleet has many modern upgrades that allow the intact BOP stack to be moved between well slots on a multi-well pad, as well as, wellhead designs that incorporate quick connects facilitating release of the BOP from the wellhead without breaking any BOP stack components apart. These technologies have been used extensively offshore, and other regulators, API, and many operators around the world have endorsed break testing as safe and reliable.




Figure 1: Winch System attached to BOP Stack




Figure 2: BOP Winch System

American Petroleum Institute (API) standards, specification and recommended practices are considered the industry standard and are consistently utilized and referenced by the industry. CFR Title 43 Part 3170 recognizes API recommended Practices (RP) 53 in its original development. API Standard 53, *Well Control Equipment Systems for Drilling Wells* (Fifth Edition, December 2018, Annex C, Table C.4) recognizes break testing as an acceptable practice. Specifically, API Standard 53, Section 5.3.7.1 states “A pressure test of the pressure containing component shall be performed following the disconnection or repair, limited to the affected component.” See Table C.4 below for reference.

62 API STANDARD 53			
Table C.4—Initial Pressure Testing, Surface BOP Stacks			
Component to be Pressure Tested	Pressure Test—Low Pressure ^{3c} psig (MPa)	Pressure Test—High Pressure ^{3c}	
		Change Out of Component, Elastomer, or Ring Gasket	No Change Out of Component, Elastomer, or Ring Gasket
Annular preventer ^b	250 to 350 (1.72 to 2.41)	RWP of annular preventer	MASP or 70% annular RWP, whichever is lower.
Fixed pipe, variable bore, blind, and BSR preventers ^{3d}	250 to 350 (1.72 to 2.41)	RWP of ram preventer or wellhead system, whichever is lower	ITP
Choke and kill line and BOP side outlet valves below ram preventers (both sides)	250 to 350 (1.72 to 2.41)	RWP of side outlet valve or wellhead system, whichever is lower	ITP
Choke manifold—upstream of chokes ^e	250 to 350 (1.72 to 2.41)	RWP of ram preventers or wellhead system, whichever is lower	ITP
Choke manifold—downstream of chokes ^e	250 to 350 (1.72 to 2.41)	RWP of valve(s), line(s), or MASP for the well program, whichever is lower	
Kelly, kelly valves, drill pipe safety valves, IBOPs	250 to 350 (1.72 to 2.41)	MASP for the well program	
³ Pressure test evaluation periods shall be a minimum of five minutes. No visible leaks. The pressure shall remain stable during the evaluation period. The pressure shall not decrease below the intended test pressure. ^b Annular(s) and VBR(s) shall be pressure tested on the largest and smallest OD drill pipe to be used in well program. ^c For pad drilling operations, moving from one wellhead to another within the 21 days, pressure testing is required for pressure-containing and pressure-controlling connections when the integrity of a pressure seal is broken. ^d For surface offshore operations, the ram BOPs shall be pressure tested with the ram locks engaged and the closing and locking pressure vented during the initial test. For land operations, the ram BOPs shall be pressure tested with the ram locks engaged and the closing and locking pressure vented at commissioning and annually. ^e Adjustable chokes are not required to be full sealing devices. Pressure testing against a closed choke is not required.			

The Bureau of Safety and Environmental Enforcement (BSEE), Department of Interior, has also utilized the API standards, specification and best practices in the development of its offshore oil and gas regulations and incorporates them by reference within its regulations.

Break testing has been approved by the BLM in the past with other operators based on the detailed information provided in this document.


XTO Energy feels break testing and our current procedures meet the intent of CFR Title 43 Part 317 0and often exceed it. There has been no evidence that break testing results in more components failing than seen on full BOP tests. XTO Energy's internal standards requires complete BOPE tests more often than that of CFR Title 43 Part 3170 (Every 21 days). In addition to function testing the annular, pipe rams and blind rams after each BOP nipple up, XTO Energy performs a choke drill with the rig crew prior to drilling out every casing shoe. This is additional training for the rig crew that exceeds the requirements of the CFR Title 43 Part 3170.

Procedures

1. XTO Energy will use this document for our break testing plan for New Mexico Delaware basin. The summary below will be referenced in the APD or Sundry Notice and receive approval prior to implementing this variance.
2. XTO Energy will perform BOP break testing on multi-wells pads where multiple intermediate sections can be drilled and cased within the 21-day BOP test window.
 - a. A full BOP test will be conducted on the first well on the pad.
 - b. The first intermediate hole section drilled on the pad will be the deepest. All of the remaining hole sections will be the same depth or shallower.
 - i. Our Lower WC targets set the intermediate casing shoe no deeper than the Wolfcamp B.
 - ii. Our Upper WC targets set the intermediate casing shoe shallower than the Wolfcamp B.
 - c. A Full BOP test will be required if the intermediate hole section being drilled has a MASP over 5M.
 - d. A full BOP test will be required prior to drilling any production hole.
3. After performing a complete BOP test on the first well, the intermediate hole section will be drilled and cased, two breaks would be made on the BOP equipment.
 - a. Between the HCV valve and choke line connection
 - b. Between the BOP quick connect and the wellhead
4. The BOP is then lifted and removed from the wellhead by a hydraulic system.
5. After skidding to the next well, the BOP is moved to the wellhead by the same hydraulic system and installed.
6. The connections mentioned in 3a and 3b will then be reconnected.
7. Install test plug into the wellhead using test joint or drill pipe.
8. A shell test is performed against the upper pipe rams testing the two breaks.
9. The shell test will consist of a 250 psi low test and a high test to the value submitted in the APD or Sundry (e.g. 5,000 psi or 10,000psi).
10. Function test will be performed on the following components: lower pipe rams, blind rams, and annular.

11. For a multi-well pad the same two breaks on the BOP would be made and on the next wells and steps 4 through 10 would be repeated.
12. A second break test would only be done if the intermediate hole section being drilled could not be completed within the 21 day BOP test window.

Note: Picture below highlights BOP components that will be tested during batch operations



Summary

A variance is requested to **ONLY** test broken pressure seals on the BOP equipment when moving from wellhead to wellhead which is in compliance with API Standard 53. API Standard 53 states, that for pad drilling operation, moving from one wellhead to another within 21 days, pressure testing is required for pressure-containing and pressure-controlling connections when the integrity of a pressure seal is broken.


The BOP will be secured by a hydraulic carrier or cradle. The BLM will be contacted if a Well Control event occurs prior to the commencement of a BOPE Break Testing operation.

Based on discussions with the BLM on February 27th 2020 and the supporting documentation submitted to the BLM, we will request permission to **ONLY** retest broken pressure seals if the following conditions are met:

1. After a full BOP test is conducted on the first well on the pad.
2. The first intermediate hole section drilled on the pad will be the deepest. All of the remaining hole sections will be the same depth or shallower.
3. Full BOP test will be required if the intermediate hole section being drilled has a MASP over 5M.
4. Full BOP test will be required prior to drilling the production hole.

Only **ONE** test will occur during each break test procedure.

All valves in red including the upper pipe rams will be shut to test the broken connections.
** Each valve on choke manifold will alternate being tested against during each skid.



The connection between the BOP stack / BOP Quick Connect and wellhead will be broken, as well as, the connection between the HCV and Choke Line on each skid and will be re-tested each time.

The connection between the HCV and kill line connection will **NOT** be broken on each skid and does not need to be retested.



BLACK GOLD®

GATES ENGINEERING & SERVICES NORTH AMERICA
7603 Prairie Oak Dr.
Houston, TX. 77086

PHONE: +1 (281) 602-4100
FAX: +1 (281) 602-4147
EMAIL: gesna.quality@gates.com
WEB: www.gates.com/oilandgas

*NEW CHOKE HOSE
INSTALLED 02-10-2024*

CERTIFICATE OF CONFORMANCE

This is to verify that the items detailed below meet the requirements of the Customer's Purchase Order referenced herein, and are in Conformance with applicable specifications, and that Records of Required Tests are on file and subject to examination. The following items were inspected and hydrostatically tested at **Gates Engineering & Services North America** facilities in Houston, TX, USA.

CUSTOMER:	NABORS DRILLING TECHNOLOGIES USA DBA NABORS DRILLING USA
CUSTOMER P.O.#:	15582803 (TAG NABORS PO #15582803 SN 74621 ASSET 66-1531)
CUSTOMER P/N:	IMR RETEST SN 74621 ASSET #66-1531
PART DESCRIPTION:	RETEST OF CUSTOMER 3" X 45 FT 16C CHOKE & KILL HOSE ASSEMBLY C/W 4 1/16" 10K FLANGES
SALES ORDER #:	529480
QUANTITY:	1
SERIAL #:	74621 H3-012524-1

SIGNATURE: *F. OSMOS*

TITLE: QUALITY ASSURANCE

DATE: 1/25/2024



H3-15/16

1/25/2024 11:48:06 AM

TEST REPORT

CUSTOMER

Company: Nabors Industries Inc.
 Production description: 74621/66-1531
 Sales order #: 529480
 Customer reference: FG1213

TEST OBJECT

Serial number: H3-012524-1
 Lot number:
 Description: 74621/66-1531
 Hose ID: 3" 16C CK
 Part number:


TEST INFORMATION

Test procedure: GTS-04-053
 Test pressure: 15000.00 psi
 Test pressure hold: 3600.00 sec
 Work pressure: 10000.00 psi
 Work pressure hold: 900.00 sec
 Length difference: 0.00 %
 Length difference: 0.00 inch

Fitting 1: 3.0 x 4-1/16 10K
 Part number:
 Description:
 Fitting 2: 3.0 x 4-1/16 10K
 Part number:
 Description:

Visual check:
 Pressure test result: PASS
 Length measurement result: Length: 45 feet

Test operator: Travis





H3-15/16


1/25/2024 11:48:06 AM


TEST REPORT

GAUGE TRACEABILITY

Description	Serial number	Calibration date	Calibration due date
S-25-A-W	110D3PHO	2023-06-06	2024-06-06
S-25-A-W	110IQWDG	2023-05-16	2024-05-16

Comment





XTO Permian Operating, LLC Offline Cementing Variance Request

XTO requests the option to cement the surface and intermediate casing strings offline as a prudent batch drilling efficiency of acreage development.


1. Cement Program

No changes to the cement program will take place for offline cementing.

2. Offline Cementing Procedure


The operational sequence will be as follows. If a well control event occurs, the BLM will be contacted for approval prior to conducting offline cementing operations.

1. Run casing as per normal operations. While running casing, conduct negative pressure test and confirm integrity of the float equipment (float collar and shoe)
2. Land casing with mandrel
3. Fill pipe with kill weight fluid, do not circulate through floats and confirm well is static
4. Set annular packoff shown below and pressure test to confirm integrity of the seal. Pressure ratings of wellhead components and valves is 5,000 psi.
5. After confirmation of both annular barriers and internal barriers, nipple down BOP and install cap flange.
 - a. If any barrier fails to test, the BOP stack will not be nipped down until after the cement job is completed with cement 500ft above the highest formation capable of flow with kill weight mud above or after it has achieved 50-psi compressive strength if kill weight fluid cannot be verified.



Annular packoff with both external and internal seals


XTO Permian Operating, LLC Offline Cementing Variance Request



Wellhead diagram during skidding operations

6. Skid rig to next well on pad.
7. Confirm well is static before removing cap flange, flange will not be removed and offline cementing operations will not commence until well is under control. If well is not static, casing outlet valves will provide access to both the casing ID and annulus. Rig or third party pump truck will kill well prior to cementing or nipping up for further remediation.
 - a. Well Control Plan
 - i. The Drillers Method will be the primary well control method to regain control of the wellbore prior to cementing, if wellbore conditions do not permit the drillers method other methods of well control may be used
 - ii. Rig pumps or a 3rd party pump will be tied into the upper casing valve to pump down the casing ID
 - iii. A high pressure return line will be rigged up to lower casing valve and run to choke manifold to control annular pressure
 - iv. Once influx is circulated out of the hole, kill weight mud will be circulated
 - v. Well will be confirmed static
 - vi. Once confirmed static, cap flange will be removed to allow for offline cementing operations to commence
8. Install offline cement tool
9. Rig up cement equipment

XTO Permian Operating, LLC Offline Cementing Variance Request



Wellhead diagram during offline cementing operations

10. Circulate bottoms up with cement truck
 - a. If gas is present on bottoms up, well will be shut in and returns rerouted through gas buster to handle entrained gas
 - b. Max anticipated time before circulating with cement truck is 6 hrs
11. Perform cement job taking returns from the annulus wellhead valve
12. Confirm well is static and floats are holding after cement job
13. Remove cement equipment, offline cement tools and install night cap with pressure gauge for monitoring.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 474009

CONDITIONS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 474009
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
ward.rikala	Any previous COA's not addressed within the updated COA's still apply.	6/17/2025