Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-101
August 1, 2011

Permit 383848

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator Name and Address	2. OGRID Number
RILEY PERMIAN OPERATING COMPANY, LLC 29 E Reno Avenue, Suite 500 Oklahoma City, OK 73104	372290
	3. API Number 30-015-56848

4. Property Code	5. Property Name	6. Well No.
337359	MARTY FEE SOUTH 11 7	004H

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
H	11	18S	26E	H	1950	N	1040	E	Eddy

8. Proposed Bottom Hole Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
F	7	18S	27E	F	2310	N	2662	W	Eddy

9. Pool Information

RED LAKE;GLORIETA-YESO	51120

Additional Well Information

11. Work Type	12. Well Type	13. Cable/Rotary	14. Lease Type	15. Ground Level Elevation
New Well	OIL		Private	3310
16. Multiple	**17. Proposed Depth**	**18. Formation**	**19. Contractor**	**20. Spud Date**
N	11116	Yeso		6/1/2025
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

☒ **We will be using a closed-loop system in lieu of lined pits**

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	12.25	9.625	36	1250	645	0
Prod	8.75	7	32	3050	125	0
Prod	8.75	5.5	20	11116	2285	2435

Casing/Cement Program: Additional Comments

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Double Ram	3000	2000	

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief. **I further certify I have complied with 19.15.14.9 (A) NMAC ☐ and/or 19.15.14.9 (B) NMAC ☒, if applicable.** Signature:		**OIL CONSERVATION DIVISION**		
Printed Name:	Electronically filed by Spence Laird	Approved By:	Jeffrey Harrison	
Title:	EHSR	Title:	Petroleum Specialist III	
Email Address:	spencelaird@rileypermian.com	Approved Date:	6/20/2025	Expiration Date: 6/20/2027
Date:	4/16/2025 Phone: 405-543-1411	Conditions of Approval Attached		

C-102

Submit Electronically
Via OCD Permitting

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION

Revised July 9, 2024

Submittal Type: ☒ Initial Submittal ☐ Amended Report ☐ As Drilled

Property Name and Well Number

MARTY FEE SOUTH 11 7 4H

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number	Pool Code	Pool Name
30-015- 56848	51120	RED LAKE; GLORIETA-YESO

Property Code	Property Name	Well Number
337359	**MARTY FEE SOUTH 11 7**	**004H**

OGRID No.	Operator Name	Ground Level Elevation
372290	RILEY PERMIAN OPERATING COMPANY LLC	3310'

Surface Owner: ☐ State ☒ Fee ☐ Tribal ☐ Federal
Mineral Owner: ☐ State ☒ Fee ☐ Tribal ☐ Federal

Surface Location

UL or Lot No.	Section	Township	Range	Lot	Feet from the N/S	Feet from the E/W	Latitude	Longitude	County
H	11	18 S	26 E		1950 FNL	1040 FEL	N 32.764374°	W 104.347239°	EDDY

Bottom Hole Location If Different From Surface

UL or Lot No.	Section	Township	Range	Lot	Feet from the N/S	Feet from the E/W	Latitude	Longitude	County
F	7	18 S	27 E		2310 FNL	2662 FWL	N 32.763328°	W 104.317815°	EDDY

Dedicated Acres	Infill or Defining Well	Defining Well API	Overlapping Spacing Unit (Y/N)	Consolidated Code
481.47	Defining	N/A	N	Pending

Order Numbers: Pending
Well Setbacks are under Common Ownership: ☐ Yes ☒ No

Kick Off Point (KOP)

UL or lot no.	Section	Township	Range	Lot	Feet from the N/S	Feet from the E/W	Latitude	Longitude	County
H	11	18 S	26 E		2075 FNL	708 FEL	32.764025	104.346162	Eddy

First Take Point (FTP)

UL or lot no.	Section	Township	Range	Lot	Feet from the N/S	Feet from the E/W	Latitude	Longitude	County
E	12	18 S	26 E		2310 FNL	100 FWL	N 32.763370°	W 104.343538°	EDDY

Last Take Point (LTP)

UL or lot no.	Section	Township	Range	Lot	Feet from the N/S	Feet from the E/W	Latitude	Longitude	County
F	7	18 S	27 E		2311 FNL	2572 FWL	N 32.763328°	W 104.318107°	EDDY

Unitized Area or Area of Uniform Interest	Spacing Unity Type	Ground Floor Elevation
	☒ Horizontal ☐ Vertical	3335'

OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief; and, if the well is a vertical or directional well, that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of a working interest or unleased mineral interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

If this well is a horizontal well, I further certify that this organization has received The consent of at least one lessee or owner of a working interest or unleased mineral interest in each tract (in the target pool or formation) in which any part of the well's completed interval will be located or obtained a compulsory pooling order from the division.

Spence Laird — 04/03/2025
Signature — Date

Spence Laird
Print Name

spencelaird@rileypermian.com
E-mail Address

SURVEYORS CERTIFICATION

MITCHELL L. McDONALD — NEW MEXICO — 29821 — 02/18/2025 — PROFESSIONAL SURVEYOR

Signature and Seal of Professional Surveyor — Date

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

MITCHELL L. MCDONALD, N.M. P.L.S.

Certificate Number	Date of Survey
29821	JANUARY 17, 2025

P:\REPX_...\PRODC\C102_Package\C102_WLE\0_Marty_Fee_11-7_C102_4H_R1.dwg RHOMESLEY 2/18/2025 2:03 PM

Note: No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

C-102	State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION	Revised July 9, 2024
Submit Electronically Via OCD Permitting		Submittal Type: ☒ Initial Submittal ☐ Amended Report ☐ As Drilled

Property Name and Well Number

MARTY FEE SOUTH 11 7 4H

SURFACE LOCATION
NEW MEXICO EAST
NAD 1983
X=537063' Y=641812'
LAT=N32.764374°
LONG=W104.347239°
NAD 1927
X=495884' Y=641749'
LAT=N32.764260°
LONG=W104.346723°
1950' FNL 1040' FEL

FIRST TAKE POINT
NEW MEXICO EAST
NAD 1983
X=538201' Y=641446'
LAT=N32.763370°
LONG=W104.343538°
NAD 1927
X=497022' Y=641384'
LAT=N32.763256°
LONG=W104.343022°
2310' FNL 100' FWL



LOWER MOST PERF.
NEW MEXICO EAST
NAD 1983
X=546018' Y=641431'
LAT=N32.763328°
LONG=W104.318107°
NAD 1927
X=504839' Y=641369'
LAT=N32.763214°
LONG=W104.317592°
2311' FNL 2572' FWL

BOTTOM HOLE LOCATION
NEW MEXICO EAST
NAD 1983
X=546108' Y=641431'
LAT=N32.763328°
LONG=W104.317815°
NAD 1927
X=504929' Y=641368'
LAT=N32.763214°
LONG=W104.317299°
2310' FNL 2662' FWL

Note: Bearings, coordinates and distances (grid) shown hereon are based on the New Mexico State Plane Coordinate System, East Zone, NAD 83-2011 (EPOCH 2010) framework, as derived by OPUS Solution. The elevations shown hereon are based on NAVD 88.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form APD Conditions

Permit 383848

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address:	API Number:
RILEY PERMIAN OPERATING COMPANY, LLC [372290] 29 E Reno Avenue, Suite 500 Oklahoma City, OK 73104	30-015-56848
	Well: MARTY FEE SOUTH 11 7 #004H

OCD Reviewer	Condition
jeffrey.harrison	Administrative order required for non-standard spacing unit prior to production.
jeffrey.harrison	Notify the OCD 24 hours prior to casing & cement.
jeffrey.harrison	A [C-103] Sub. Drilling (C-103N) is required within (10) days of spud.
jeffrey.harrison	File As Drilled C-102 and a directional Survey with C-104 completion packet.
jeffrey.harrison	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string.
jeffrey.harrison	Cement is required to circulate on both surface and production strings of casing.
jeffrey.harrison	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.
jeffrey.harrison	If cement does not circulate on any string, a Cement Bond Log (CBL) is required for that string of casing.
jeffrey.harrison	This well is in the Roswell Aquifer. Casing must be sat and cemented back to surface to protect the Roswell Aquifer.

Company: Riley Permian Operating Co., LLC
Well: Marty Fee South 11-7 4H
County: Eddy County, New Mexico (NAD 83)
Rig: Akita 519
Wellbore: Wellbore #1
Design: Design #1
Date: 15:52, March 17 2025

Geodetic System: US State Plane 1983
Datum: North American Datum 1983
Ellipsoid: GRS 1980
Zone: New Mexico Eastern Zone
System Datum: Mean Sea Level

To convert a Magnetic Direction to a Grid Direction, Add 6.641°
To convert a Magnetic Direction to a True Direction, Add 6.633° East
To convert a True Direction to a Grid Direction, Add 0.008°

Azimuths to Grid North
True North: 0.01°
Magnetic North: 6.64°

Magnetic Field
Strength: 47372.9nT
Dip Angle: 60.32°
Date: 3/13/2025
Model: HDGM2025

SURVEY PROGRAM

Depth From	Depth To	Survey/Plan	Tool
0.00	11115.90	Design #1 (Wellbore #1)	MWD+HRGM

MS Directional

SECTION DETAILS

MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	Annotation
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00	
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.000	0.00	KOP, 2.50°/100' Build
1143.30	16.08	110.99	1134.89	-32.13	83.74	2.50	110.994	83.80	Begin 16.08° Tangent
2099.96	16.08	110.99	2054.11	-127.08	331.17	0.00	0.000	331.41	KOP, 8.00°/100' Build & Turn
2648.93	60.00	110.99	2475.95	-245.33	639.32	8.00	0.001	639.79	Hold 60.00° Inc, 110.99° Azm
2848.93	60.00	110.99	2575.95	-307.39	801.03	0.00	0.000	801.62	Begin 10.00°/100' Build & Turn
3208.82	90.00	90.11	2669.00	-365.49	1137.61	10.00	-37.348	1138.31	Begin 90.00° Lateral
11115.90	90.00	90.11	2669.00	-380.57	9044.67	0.00	0.000	9045.38	PBHL

WELL DETAILS: Marty Fee South 11-7 4H

+N/-S	+E/-W	GL @ 3310.00 Northing	Well @ 3329.00usft (Akita 519) Easting	Latitude	Longitude
0.00	0.00	641811.60	537063.05	32.764374	-104.347239

DESIGN TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
FTP_Marty Fee South 11-7 4H	2669.00	-365.49	1137.61	641446.11	538200.66	32.763370	-104.343538
PBHL_Marty Fee South 11-7 4H	2669.00	-380.57	9044.67	641431.03	546107.72	32.763328	-104.317815











Riley Permian Operating Co., LLC
Marty Fee South 11-7 4H
Akita 519

Riley Permian Operating Co., LLC

Eddy County, New Mexico (NAD 83)
Marty Fee South 11-7 (3H, 4H)
Marty Fee South 11-7 4H

Wellbore #1
Design #1

Anticollision Report

18 March, 2025

Anticollision Report

Company:	Riley Permian Operating Co., LLC	**Local Co-ordinate Reference:**	Well Marty Fee South 11-7 4H
Project:	Eddy County, New Mexico (NAD 83)	**TVD Reference:**	Well @ 3329.00usft (Akita 519)
Reference Site:	Marty Fee South 11-7 (3H, 4H)	**MD Reference:**	Well @ 3329.00usft (Akita 519)
Site Error:	0.00 usft	**North Reference:**	Grid
Reference Well:	Marty Fee South 11-7 4H	**Survey Calculation Method:**	Minimum Curvature
Well Error:	0.00 usft	**Output errors are at**	2.00 sigma
Reference Wellbore	Wellbore #1	**Database:**	TRG_EDMConroe
Reference Design:	Design #1	**Offset TVD Reference:**	Reference Datum

Reference Design #1

Filter type:	NO GLOBAL FILTER: Using user defined selection & filtering criteria		
Interpolation Method:	MD Interval 100.00usft	**Error Model:**	ISCWSA
Depth Range:	Unlimited	**Scan Method:**	Closest Approach 3D
Results Limited by:	Maximum centre distance of 2,000.00usft	**Error Surface:**	Pedal Curve
Warning Levels Evaluated at:	2.00 **Sigma**	**Casing Method:**	Not applied

Survey Tool Program **Date** 3/17/2025

From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
0.00	11,115.90	Design #1 (Wellbore #1)	MWD+HRGM	OWSG MWD + HRGM

Summary

Site Name Offset Well - Wellbore - Design	Reference Measured Depth (usft)	Offset Measured Depth (usft)	Distance Between Centres (usft)	Distance Between Ellipses (usft)	Separation Factor	Warning
Marty Fee South 11-7 (3H, 4H)						
Marty Fee South 11-7 3H - Wellbore #1 - Design #1	500.00	500.00	30.00	26.55	8.700	CC, ES
Marty Fee South 11-7 3H - Wellbore #1 - Design #1	11,115.90	11,535.82	799.34	453.37	2.310	SF
Over The Line 12-11 (1H, 2H)						
Over The Line 12-11 1H - Wellbore #1 - Design #1	3,500.00	2,600.00	458.67	421.03	12.185	SF
Over The Line 12-11 1H - Wellbore #1 - Design #1	3,636.00	2,539.13	442.99	407.82	12.596	CC, ES
Over The Line 12-11 2H - Wellbore #1 - Design #1	3,743.40	2,749.43	76.38	34.47	1.823	CC, ES, SF

Offset Design: Marty Fee South 11-7 (3H, 4H) - Marty Fee South 11-7 3H - Wellbore #1 - Design #1

Offset Site Error: 0.00 usft

Survey Program: 0-MWD+HRGM **Offset Well Error:** 0.00 usft

Rule Assigned:

Reference Measured Depth (usft)	Reference Vertical Depth (usft)	Offset Measured Depth (usft)	Offset Vertical Depth (usft)	Semi Major Axis Reference (usft)	Semi Major Axis Offset (usft)	Azimuth from North (°)	Offset Wellbore Centre +N/-S (usft)	Offset Wellbore Centre +E/-W (usft)	Distance Between Centres (usft)	Distance Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
0.00	0.00	0.00	0.00	0.00	0.00	0.516	30.00	0.27	30.00				
100.00	100.00	100.00	100.00	0.29	0.29	0.516	30.00	0.27	30.00	29.42	0.58	51.662	
200.00	200.00	200.00	200.00	0.65	0.65	0.516	30.00	0.27	30.00	28.70	1.30	23.119	
300.00	300.00	300.00	300.00	1.01	1.01	0.516	30.00	0.27	30.00	27.99	2.01	14.892	
400.00	400.00	400.00	400.00	1.37	1.37	0.516	30.00	0.27	30.00	27.27	2.73	10.983	
500.00	500.00	500.00	500.00	1.72	1.72	0.516	30.00	0.27	30.00	26.55	3.45	8.700	CC, ES
600.00	599.97	599.81	599.80	2.07	2.08	-1.324	30.29	1.32	31.08	26.93	4.15	7.492	
700.00	699.75	699.57	699.51	2.42	2.43	-6.133	31.15	4.46	34.47	29.63	4.84	7.118	
800.00	799.14	799.22	799.00	2.77	2.78	-12.278	32.57	9.69	40.53	34.98	5.55	7.302	
900.00	897.97	898.70	898.20	3.15	3.14	-18.259	34.57	16.99	49.54	43.27	6.27	7.898	
1,000.00	996.04	997.96	996.98	3.54	3.50	-23.311	37.13	26.34	61.63	54.62	7.01	8.793	
1,100.00	1,093.17	1,096.95	1,095.26	3.97	3.87	-27.292	40.24	37.71	76.79	69.03	7.76	9.895	
1,200.00	1,189.37	1,195.72	1,193.05	4.42	4.24	-30.082	43.90	51.10	94.44	85.91	8.53	11.073	
1,300.00	1,285.45	1,294.75	1,290.78	4.90	4.63	-31.059	48.13	66.56	111.97	102.66	9.31	12.022	
1,400.00	1,381.54	1,394.02	1,388.36	5.39	5.03	-30.852	52.92	84.10	128.93	118.81	10.13	12.732	
1,500.00	1,477.63	1,493.43	1,485.67	5.89	5.44	-29.879	58.28	103.71	145.33	134.36	10.97	13.249	
1,600.00	1,573.71	1,592.78	1,582.46	6.40	5.87	-28.388	64.19	125.31	161.25	149.41	11.84	13.616	
1,700.00	1,669.80	1,691.42	1,678.39	6.91	6.31	-26.972	70.26	147.50	177.09	164.35	12.74	13.905	
1,800.00	1,765.88	1,790.07	1,774.31	7.43	6.75	-25.790	76.32	169.68	193.03	179.39	13.64	14.151	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	Riley Permian Operating Co., LLC	**Local Co-ordinate Reference:**	Well Marty Fee South 11-7 4H
Project:	Eddy County, New Mexico (NAD 83)	**TVD Reference:**	Well @ 3329.00usft (Akita 519)
Reference Site:	Marty Fee South 11-7 (3H, 4H)	**MD Reference:**	Well @ 3329.00usft (Akita 519)
Site Error:	0.00 usft	**North Reference:**	Grid
Reference Well:	Marty Fee South 11-7 4H	**Survey Calculation Method:**	Minimum Curvature
Well Error:	0.00 usft	**Output errors are at**	2.00 sigma
Reference Wellbore	Wellbore #1	**Database:**	TRG_EDMConroe
Reference Design:	Design #1	**Offset TVD Reference:**	Reference Datum

Offset Design: Marty Fee South 11-7 (3H, 4H) - Marty Fee South 11-7 3H - Wellbore #1 - Design #1

Offset Site Error: 0.00 usft

Survey Program: 0-MWD+HRGM

Offset Well Error: 0.00 usft

Reference Measured Depth (usft)	Reference Vertical Depth (usft)	Offset Measured Depth (usft)	Offset Vertical Depth (usft)	Semi Major Axis Reference (usft)	Semi Major Axis Offset (usft)	Azimuth from North (°)	Offset Wellbore Centre +N/-S (usft)	Offset Wellbore Centre +E/-W (usft)	Rule Assigned: Distance Between Centres (usft)	Rule Assigned: Distance Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
1,900.00	1,861.97	1,888.71	1,870.23	7.95	7.20	-24.789	82.39	191.87	209.03	194.48	14.56	14.362	
2,000.00	1,958.06	1,987.36	1,966.16	8.47	7.65	-23.931	88.46	214.06	225.10	209.62	15.48	14.543	
2,099.96	2,054.11	2,085.96	2,062.05	9.00	8.10	-23.188	94.52	236.24	241.21	224.80	16.41	14.701	
2,200.00	2,147.99	2,183.70	2,157.10	9.59	8.56	-23.634	100.53	258.23	262.03	244.68	17.35	15.101	
2,300.00	2,236.14	2,278.27	2,249.05	10.32	9.00	-25.923	106.35	279.50	292.24	273.95	18.30	15.973	
2,400.00	2,316.89	2,367.85	2,336.17	11.22	9.42	-29.322	111.86	299.65	332.23	313.02	19.21	17.293	
2,500.00	2,388.66	2,450.71	2,416.74	12.29	9.81	-33.178	116.96	318.29	382.38	362.31	20.07	19.048	
2,600.00	2,450.06	2,527.87	2,491.75	13.57	10.17	-36.943	121.73	335.73	442.63	421.75	20.88	21.197	
2,700.00	2,501.48	2,624.37	2,583.33	15.03	10.69	-38.934	129.69	364.85	509.10	487.20	21.90	23.247	
2,800.00	2,551.48	2,738.21	2,684.97	16.58	11.43	-38.590	143.14	414.06	572.74	549.50	23.25	24.636	
2,900.00	2,599.89	2,869.47	2,790.38	18.21	12.50	-36.104	163.69	489.20	630.89	605.76	25.13	25.106	
3,000.00	2,636.98	3,015.02	2,888.48	19.99	14.03	-32.389	191.95	592.60	684.16	656.46	27.70	24.697	
3,100.00	2,660.24	3,140.00	2,955.04	21.89	15.66	-30.018	219.82	694.53	731.52	701.01	30.51	23.975	
3,200.00	2,668.95	3,226.07	2,998.07	23.84	16.89	-30.923	239.47	766.42	778.17	745.54	32.63	23.848	
3,300.00	2,669.00	3,720.08	3,120.00	25.80	25.53	0.112	294.65	1,230.08	799.63	757.23	42.40	18.858	
3,400.00	2,669.00	3,820.08	3,120.00	27.81	27.51	0.112	294.46	1,330.08	799.63	753.76	45.86	17.434	
3,500.00	2,669.00	3,920.08	3,120.00	29.88	29.55	0.112	294.26	1,430.08	799.62	750.23	49.40	16.187	
3,600.00	2,669.00	4,020.08	3,120.00	31.98	31.62	0.112	294.07	1,530.08	799.62	746.63	52.99	15.089	
3,700.00	2,669.00	4,120.08	3,120.00	34.11	33.73	0.112	293.87	1,630.08	799.62	742.98	56.63	14.119	
3,800.00	2,669.00	4,220.08	3,120.00	36.27	35.87	0.112	293.68	1,730.08	799.61	739.30	60.31	13.258	
3,900.00	2,669.00	4,320.08	3,120.00	38.45	38.03	0.112	293.48	1,830.08	799.61	735.58	64.02	12.489	
4,000.00	2,669.00	4,420.08	3,120.00	40.64	40.21	0.112	293.29	1,930.08	799.61	731.84	67.76	11.800	
4,100.00	2,669.00	4,520.08	3,120.00	42.85	42.41	0.112	293.09	2,030.08	799.60	728.08	71.52	11.179	
4,200.00	2,669.00	4,620.08	3,120.00	45.07	44.62	0.112	292.90	2,130.08	799.60	724.29	75.30	10.618	
4,300.00	2,669.00	4,720.08	3,120.00	47.31	46.84	0.112	292.70	2,230.08	799.59	720.49	79.10	10.108	
4,400.00	2,669.00	4,820.08	3,120.00	49.55	49.07	0.112	292.51	2,330.08	799.59	716.68	82.91	9.644	
4,500.00	2,669.00	4,920.08	3,120.00	51.80	51.31	0.112	292.31	2,430.07	799.59	712.85	86.74	9.219	
4,600.00	2,669.00	5,020.08	3,120.00	54.06	53.56	0.112	292.11	2,530.07	799.58	709.01	90.57	8.828	
4,700.00	2,669.00	5,120.08	3,120.00	56.32	55.82	0.112	291.92	2,630.07	799.58	705.17	94.41	8.469	
4,800.00	2,669.00	5,220.08	3,120.00	58.59	58.08	0.112	291.72	2,730.07	799.58	701.31	98.27	8.137	
4,900.00	2,669.00	5,320.08	3,120.00	60.87	60.35	0.112	291.53	2,830.07	799.57	697.45	102.12	7.829	
5,000.00	2,669.00	5,420.08	3,120.00	63.15	62.62	0.112	291.33	2,930.07	799.57	693.58	105.99	7.544	
5,100.00	2,669.00	5,520.08	3,120.00	65.43	64.90	0.112	291.14	3,030.07	799.56	689.70	109.86	7.278	
5,200.00	2,669.00	5,620.08	3,120.00	67.72	67.18	0.112	290.94	3,130.07	799.56	685.82	113.74	7.030	
5,300.00	2,669.00	5,720.08	3,120.00	70.01	69.47	0.112	290.75	3,230.07	799.56	681.94	117.62	6.798	
5,400.00	2,669.00	5,820.08	3,120.00	72.30	71.75	0.112	290.55	3,330.07	799.55	678.05	121.51	6.580	
5,500.00	2,669.00	5,920.08	3,120.00	74.60	74.05	0.112	290.36	3,430.07	799.55	674.15	125.40	6.376	
5,600.00	2,669.00	6,020.08	3,120.00	76.89	76.34	0.112	290.16	3,530.07	799.55	670.25	129.29	6.184	
5,700.00	2,669.00	6,120.08	3,120.00	79.19	78.63	0.112	289.97	3,630.07	799.54	666.35	133.19	6.003	
5,800.00	2,669.00	6,220.08	3,120.00	81.49	80.93	0.112	289.77	3,730.07	799.54	662.45	137.09	5.832	
5,900.00	2,669.00	6,320.08	3,120.00	83.80	83.23	0.112	289.57	3,830.07	799.53	658.54	140.99	5.671	
6,000.00	2,669.00	6,420.08	3,120.00	86.10	85.53	0.112	289.38	3,930.07	799.53	654.64	144.90	5.518	
6,100.00	2,669.00	6,520.08	3,120.00	88.41	87.84	0.112	289.18	4,030.07	799.53	650.72	148.80	5.373	
6,200.00	2,669.00	6,620.08	3,120.00	90.72	90.14	0.112	288.99	4,130.07	799.52	646.81	152.71	5.236	
6,300.00	2,669.00	6,720.08	3,120.00	93.03	92.45	0.112	288.79	4,230.07	799.52	642.90	156.62	5.105	
6,400.00	2,669.00	6,820.08	3,120.00	95.34	94.76	0.112	288.60	4,330.07	799.52	638.98	160.54	4.980	
6,500.00	2,669.00	6,920.08	3,120.00	97.65	97.06	0.112	288.40	4,430.07	799.51	635.06	164.45	4.862	
6,600.00	2,669.00	7,020.08	3,120.00	99.96	99.37	0.112	288.21	4,530.07	799.51	631.14	168.37	4.749	
6,700.00	2,669.00	7,120.08	3,120.00	102.27	101.69	0.112	288.01	4,630.07	799.50	627.22	172.28	4.641	
6,800.00	2,669.00	7,220.08	3,120.00	104.59	104.00	0.112	287.82	4,730.07	799.50	623.30	176.20	4.537	
6,900.00	2,669.00	7,320.08	3,120.00	106.90	106.31	0.112	287.62	4,830.07	799.50	619.37	180.12	4.439	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	Riley Permian Operating Co., LLC	**Local Co-ordinate Reference:**	Well Marty Fee South 11-7 4H
Project:	Eddy County, New Mexico (NAD 83)	**TVD Reference:**	Well @ 3329.00usft (Akita 519)
Reference Site:	Marty Fee South 11-7 (3H, 4H)	**MD Reference:**	Well @ 3329.00usft (Akita 519)
Site Error:	0.00 usft	**North Reference:**	Grid
Reference Well:	Marty Fee South 11-7 4H	**Survey Calculation Method:**	Minimum Curvature
Well Error:	0.00 usft	**Output errors are at**	2.00 sigma
Reference Wellbore	Wellbore #1	**Database:**	TRG_EDMConroe
Reference Design:	Design #1	**Offset TVD Reference:**	Reference Datum

Offset Design: Marty Fee South 11-7 (3H, 4H) - Marty Fee South 11-7 3H - Wellbore #1 - Design #1

Offset Site Error: 0.00 usft

Survey Program: 0-MWD+HRGM

Offset Well Error: 0.00 usft

Reference Measured Depth (usft)	Reference Vertical Depth (usft)	Offset Measured Depth (usft)	Offset Vertical Depth (usft)	Semi Major Axis Reference (usft)	Semi Major Axis Offset (usft)	Azimuth from North (°)	Offset Wellbore Centre +N/-S (usft)	Offset Wellbore Centre +E/-W (usft)	Rule Assigned: Distance Between Centres (usft)	Rule Assigned: Distance Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
7,000.00	2,669.00	7,420.08	3,120.00	109.22	108.62	0.112	287.43	4,930.07	799.49	615.45	184.05	4.344	
7,100.00	2,669.00	7,520.08	3,120.00	111.54	110.94	0.112	287.23	5,030.07	799.49	611.52	187.97	4.253	
7,200.00	2,669.00	7,620.08	3,120.00	113.85	113.25	0.112	287.04	5,130.07	799.49	607.59	191.89	4.166	
7,300.00	2,669.00	7,720.08	3,120.00	116.17	115.57	0.112	286.84	5,230.07	799.48	603.67	195.82	4.083	
7,400.00	2,669.00	7,820.08	3,120.00	118.49	117.89	0.112	286.64	5,330.07	799.48	599.74	199.74	4.003	
7,500.00	2,669.00	7,920.08	3,120.00	120.81	120.21	0.112	286.45	5,430.07	799.47	595.81	203.67	3.925	
7,600.00	2,669.00	8,020.08	3,120.00	123.13	122.52	0.112	286.25	5,530.07	799.47	591.87	207.60	3.851	
7,700.00	2,669.00	8,120.08	3,120.00	125.45	124.84	0.112	286.06	5,630.07	799.47	587.94	211.52	3.780	
7,800.00	2,669.00	8,220.08	3,120.00	127.77	127.16	0.112	285.86	5,730.07	799.46	584.01	215.45	3.711	
7,900.00	2,669.00	8,320.08	3,120.00	130.09	129.48	0.112	285.67	5,830.07	799.46	580.08	219.38	3.644	
8,000.00	2,669.00	8,420.08	3,120.00	132.41	131.80	0.112	285.47	5,930.07	799.46	576.14	223.31	3.580	
8,100.00	2,669.00	8,520.08	3,120.00	134.74	134.12	0.112	285.28	6,030.07	799.45	572.21	227.24	3.518	
8,200.00	2,669.00	8,620.08	3,120.00	137.06	136.44	0.112	285.08	6,130.07	799.45	568.27	231.17	3.458	
8,300.00	2,669.00	8,720.08	3,120.00	139.38	138.77	0.112	284.89	6,230.07	799.44	564.34	235.11	3.400	
8,400.00	2,669.00	8,820.08	3,120.00	141.71	141.09	0.112	284.69	6,330.07	799.44	560.40	239.04	3.344	
8,500.00	2,669.00	8,920.08	3,120.00	144.03	143.41	0.112	284.50	6,430.07	799.44	556.47	242.97	3.290	
8,600.00	2,669.00	9,020.08	3,120.00	146.35	145.73	0.112	284.30	6,530.07	799.43	552.53	246.91	3.238	
8,700.00	2,669.00	9,120.08	3,120.00	148.68	148.06	0.112	284.11	6,630.07	799.43	548.59	250.84	3.187	
8,800.00	2,669.00	9,220.08	3,120.00	151.00	150.38	0.112	283.91	6,730.07	799.43	544.65	254.77	3.138	
8,900.00	2,669.00	9,320.08	3,120.00	153.33	152.70	0.112	283.71	6,830.07	799.42	540.71	258.71	3.090	
9,000.00	2,669.00	9,420.08	3,120.00	155.65	155.03	0.112	283.52	6,930.07	799.42	536.78	262.64	3.044	
9,100.00	2,669.00	9,520.08	3,120.00	157.98	157.35	0.112	283.32	7,030.07	799.41	532.84	266.58	2.999	
9,200.00	2,669.00	9,620.08	3,120.00	160.30	159.68	0.112	283.13	7,130.07	799.41	528.90	270.51	2.955	
9,300.00	2,669.00	9,720.08	3,120.00	162.63	162.00	0.112	282.93	7,230.07	799.41	524.96	274.45	2.913	
9,400.00	2,669.00	9,820.08	3,120.00	164.96	164.33	0.112	282.74	7,330.07	799.40	521.02	278.39	2.872	
9,500.00	2,669.00	9,920.08	3,120.00	167.28	166.65	0.112	282.54	7,430.07	799.40	517.08	282.32	2.832	
9,600.00	2,669.00	10,020.08	3,120.00	169.61	168.98	0.112	282.35	7,530.07	799.40	513.14	286.26	2.793	
9,700.00	2,669.00	10,120.08	3,120.00	171.94	171.30	0.112	282.15	7,630.07	799.39	509.19	290.20	2.755	
9,800.00	2,669.00	10,220.08	3,120.00	174.26	173.63	0.112	281.96	7,730.06	799.39	505.25	294.14	2.718	
9,900.00	2,669.00	10,320.08	3,120.00	176.59	175.95	0.112	281.76	7,830.06	799.38	501.31	298.07	2.682	
10,000.00	2,669.00	10,420.08	3,120.00	178.92	178.28	0.112	281.57	7,930.06	799.38	497.37	302.01	2.647	
10,100.00	2,669.00	10,520.08	3,120.00	181.24	180.61	0.112	281.37	8,030.06	799.38	493.43	305.95	2.613	
10,200.00	2,669.00	10,620.08	3,120.00	183.57	182.93	0.112	281.17	8,130.06	799.37	489.49	309.89	2.580	
10,300.00	2,669.00	10,720.08	3,120.00	185.90	185.26	0.112	280.98	8,230.06	799.37	485.54	313.83	2.547	
10,400.00	2,669.00	10,820.08	3,120.00	188.23	187.59	0.112	280.78	8,330.06	799.37	481.60	317.77	2.516	
10,500.00	2,669.00	10,920.08	3,120.00	190.56	189.91	0.112	280.59	8,430.06	799.36	477.66	321.70	2.485	
10,600.00	2,669.00	11,020.08	3,120.00	192.88	192.24	0.112	280.39	8,530.06	799.36	473.71	325.64	2.455	
10,700.00	2,669.00	11,120.08	3,120.00	195.21	194.57	0.112	280.20	8,630.06	799.36	469.77	329.58	2.425	
10,800.00	2,669.00	11,220.08	3,120.00	197.54	196.90	0.112	280.00	8,730.06	799.35	465.83	333.52	2.397	
10,900.00	2,669.00	11,320.08	3,120.00	199.87	199.23	0.112	279.81	8,830.06	799.35	461.88	337.46	2.369	
11,000.00	2,669.00	11,420.08	3,120.00	202.20	201.55	0.112	279.61	8,930.06	799.34	457.94	341.40	2.341	
11,100.00	2,669.00	11,520.08	3,120.00	204.53	203.88	0.112	279.42	9,030.06	799.34	454.00	345.34	2.315	
11,111.91	2,669.00	11,531.99	3,120.00	204.80	204.16	0.112	279.39	9,041.97	799.34	453.53	345.81	2.311	
11,115.90	2,669.00	11,535.82	3,120.00	204.90	204.25	0.098	279.39	9,045.80	799.34	453.37	345.97	2.310 SF	

Anticollision Report

Company:	Riley Permian Operating Co., LLC	**Local Co-ordinate Reference:**	Well Marty Fee South 11-7 4H
Project:	Eddy County, New Mexico (NAD 83)	**TVD Reference:**	Well @ 3329.00usft (Akita 519)
Reference Site:	Marty Fee South 11-7 (3H, 4H)	**MD Reference:**	Well @ 3329.00usft (Akita 519)
Site Error:	0.00 usft	**North Reference:**	Grid
Reference Well:	Marty Fee South 11-7 4H	**Survey Calculation Method:**	Minimum Curvature
Well Error:	0.00 usft	**Output errors are at**	2.00 sigma
Reference Wellbore	Wellbore #1	**Database:**	TRG_EDMConroe
Reference Design:	Design #1	**Offset TVD Reference:**	Reference Datum

Offset Design: Over The Line 12-11 (1H, 2H) - Over The Line 12-11 1H - Wellbore #1 - Design #1

Offset Site Error: 0.00 usft

Survey Program: 0-MWD+HRGM

Offset Well Error: 0.00 usft

Reference Measured Depth (usft)	Reference Vertical Depth (usft)	Offset Measured Depth (usft)	Offset Vertical Depth (usft)	Semi Major Axis Reference (usft)	Semi Major Axis Offset (usft)	Azimuth from North (°)	Offset Wellbore Centre +N/-S (usft)	Offset Wellbore Centre +E/-W (usft)	Rule Assigned: Distance Between Centres (usft)	Distance Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
700.00	699.75	4,266.76	2,661.00	2.42	45.47	0.316	299.99	9.81	1,984.54	1,965.97	18.57	106.853	
800.00	799.14	4,256.57	2,661.00	2.77	45.25	0.316	299.93	20.00	1,886.99	1,868.36	18.63	101.268	
900.00	897.97	4,242.34	2,661.00	3.15	44.95	0.316	299.85	34.23	1,790.48	1,771.78	18.70	95.756	
1,000.00	996.04	4,224.09	2,661.00	3.54	44.57	0.316	299.75	52.48	1,695.28	1,676.51	18.78	90.279	
1,100.00	1,093.17	4,201.86	2,661.00	3.97	44.09	0.316	299.63	74.71	1,601.70	1,582.81	18.89	84.803	
1,200.00	1,189.37	4,176.31	2,661.00	4.42	43.56	0.316	299.49	100.26	1,509.79	1,490.74	19.05	79.255	
1,300.00	1,285.45	4,150.39	2,661.00	4.90	43.01	0.316	299.35	126.18	1,418.65	1,399.33	19.32	73.433	
1,400.00	1,381.54	4,124.47	2,661.00	5.39	42.47	0.316	299.20	152.10	1,328.29	1,308.59	19.69	67.454	
1,500.00	1,477.63	4,098.55	2,661.00	5.89	41.92	0.316	299.06	178.01	1,238.86	1,218.67	20.19	61.357	
1,600.00	1,573.71	4,072.64	2,661.00	6.40	41.38	0.316	298.92	203.93	1,150.59	1,129.74	20.85	55.189	
1,700.00	1,669.80	4,046.72	2,661.00	6.91	40.85	0.316	298.78	229.85	1,063.77	1,042.07	21.70	49.024	
1,800.00	1,765.88	4,020.80	2,661.00	7.43	40.31	0.316	298.63	255.77	978.78	955.99	22.79	42.949	
1,900.00	1,861.97	3,994.88	2,661.00	7.95	39.77	0.316	298.49	281.68	896.14	871.97	24.17	37.071	
2,000.00	1,958.06	3,968.96	2,661.00	8.47	39.24	0.316	298.35	307.60	816.57	790.65	25.92	31.507	
2,099.96	2,054.11	3,943.06	2,661.00	9.00	38.71	0.316	298.21	333.51	741.08	713.00	28.08	26.395	
2,200.00	2,147.99	3,910.94	2,661.00	9.59	38.06	0.316	298.03	365.62	674.18	643.54	30.64	22.006	
2,300.00	2,236.14	3,866.93	2,661.00	10.32	37.17	0.316	297.79	409.63	621.81	588.35	33.46	18.582	
2,400.00	2,316.89	3,811.87	2,661.00	11.22	36.06	0.316	297.48	464.69	586.39	550.14	36.25	16.175	
2,500.00	2,388.66	3,746.83	2,661.00	12.29	34.78	0.316	297.12	529.73	568.79	530.15	38.64	14.722	
2,555.46	2,424.07	3,706.92	2,661.00	13.00	34.00	0.316	296.90	569.64	566.36	526.66	39.70	14.267	
2,600.00	2,450.06	3,673.08	2,661.00	13.57	33.34	0.316	296.72	603.48	567.83	527.47	40.35	14.071	
2,700.00	2,501.48	3,592.87	2,661.00	15.03	31.82	0.316	296.28	683.69	579.84	538.41	41.42	13.997	
2,800.00	2,551.48	3,511.85	2,661.00	16.58	30.31	0.316	295.83	764.71	598.16	556.01	42.14	14.194	
2,900.00	2,599.89	3,429.55	2,661.00	18.21	28.83	0.316	295.38	847.01	620.65	578.09	42.56	14.584	
3,000.00	2,636.98	3,339.61	2,661.00	19.99	27.27	0.316	294.88	936.95	640.66	597.95	42.72	14.998	
3,100.00	2,660.24	2,831.35	2,526.32	21.89	18.42	35.474	134.92	1,382.04	622.15	583.18	38.97	15.964	
3,200.00	2,668.95	2,769.29	2,495.30	23.84	17.48	32.253	98.42	1,421.49	575.31	536.15	39.16	14.691	
3,300.00	2,669.00	2,705.63	2,463.46	25.80	16.52	28.658	60.97	1,461.95	527.85	488.86	38.98	13.540	
3,400.00	2,669.00	2,641.96	2,431.63	27.81	15.58	24.034	23.52	1,502.42	487.95	449.66	38.29	12.743	
3,500.00	2,669.00	2,600.00	2,410.05	29.88	14.98	15.322	-0.92	1,528.82	458.67	421.03	37.64	12.185 SF	
3,600.00	2,669.00	2,550.00	2,381.71	31.98	14.30	5.125	-28.89	1,559.04	444.13	408.35	35.78	12.413	
3,636.00	2,669.00	2,539.13	2,375.17	32.74	14.17	0.109	-34.79	1,565.42	442.99	407.82	35.17	12.596 CC, ES	
3,700.00	2,669.00	2,515.12	2,360.27	34.11	13.86	-8.835	-47.58	1,579.23	446.58	412.93	33.65	13.271	
3,800.00	2,669.00	2,480.10	2,337.42	36.27	13.44	-23.371	-65.60	1,598.71	466.34	435.34	31.00	15.041	
3,900.00	2,669.00	2,450.00	2,316.76	38.45	13.08	-36.776	-80.47	1,614.77	501.86	473.39	28.46	17.631	
4,000.00	2,669.00	2,418.36	2,294.08	40.64	12.74	-47.643	-95.45	1,630.96	550.46	524.38	26.08	21.106	
4,100.00	2,669.00	2,400.00	2,280.48	42.85	12.54	-55.886	-103.83	1,640.01	609.47	585.04	24.44	24.942	
4,200.00	2,669.00	2,366.26	2,254.68	45.07	12.20	-62.248	-118.59	1,655.96	676.11	653.45	22.66	29.836	
4,300.00	2,669.00	2,350.00	2,241.89	47.31	12.04	-66.817	-125.41	1,663.33	748.87	727.22	21.65	34.589	
4,400.00	2,669.00	2,322.14	2,219.45	49.55	11.78	-70.518	-136.62	1,675.44	826.06	805.44	20.62	40.066	
4,500.00	2,669.00	2,300.00	2,201.17	51.80	11.58	-73.330	-145.11	1,684.61	906.82	886.90	19.92	45.521	
4,600.00	2,669.00	2,284.57	2,188.21	54.06	11.45	-75.461	-150.79	1,690.75	990.30	970.80	19.50	50.785	
4,700.00	2,669.00	2,267.86	2,173.97	56.32	11.32	-77.204	-156.74	1,697.17	1,075.98	1,056.81	19.17	56.134	
4,800.00	2,669.00	2,250.00	2,158.53	58.59	11.17	-78.653	-162.83	1,703.76	1,163.43	1,144.52	18.91	61.525	
4,900.00	2,669.00	2,250.00	2,158.53	60.87	11.17	-79.630	-162.83	1,703.76	1,252.46	1,233.54	18.91	66.215	
5,000.00	2,669.00	2,224.53	2,136.14	63.15	10.98	-80.760	-171.07	1,712.66	1,342.40	1,323.71	18.69	71.811	
5,100.00	2,669.00	2,200.00	2,114.17	65.43	10.79	-81.710	-178.49	1,720.68	1,433.63	1,415.09	18.54	77.313	
5,200.00	2,669.00	2,200.00	2,114.17	67.72	10.79	-82.284	-178.49	1,720.68	1,525.45	1,506.83	18.61	81.948	
5,300.00	2,669.00	2,176.55	2,092.95	70.01	10.63	-83.003	-185.27	1,728.00	1,618.06	1,599.52	18.53	87.302	
5,400.00	2,669.00	2,145.30	2,064.66	72.30	10.41	-83.710	-194.29	1,737.75	1,710.95	1,692.52	18.44	92.795	
5,500.00	2,669.00	2,114.04	2,036.37	74.60	10.19	-84.343	-203.32	1,747.50	1,804.07	1,785.69	18.38	98.168	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	Riley Permian Operating Co., LLC	**Local Co-ordinate Reference:**	Well Marty Fee South 11-7 4H
Project:	Eddy County, New Mexico (NAD 83)	**TVD Reference:**	Well @ 3329.00usft (Akita 519)
Reference Site:	Marty Fee South 11-7 (3H, 4H)	**MD Reference:**	Well @ 3329.00usft (Akita 519)
Site Error:	0.00 usft	**North Reference:**	Grid
Reference Well:	Marty Fee South 11-7 4H	**Survey Calculation Method:**	Minimum Curvature
Well Error:	0.00 usft	**Output errors are at**	2.00 sigma
Reference Wellbore	Wellbore #1	**Database:**	TRG_EDMConroe
Reference Design:	Design #1	**Offset TVD Reference:**	Reference Datum

Offset Design: Over The Line 12-11 (1H, 2H) - Over The Line 12-11 1H - Wellbore #1 - Design #1

Offset Site Error: 0.00 usft

Survey Program: 0-MWD+HRGM

Offset Well Error: 0.00 usft

Reference Measured Depth (usft)	Reference Vertical Depth (usft)	Offset Measured Depth (usft)	Offset Vertical Depth (usft)	Semi Major Axis Reference (usft)	Semi Major Axis Offset (usft)	Azimuth from North (°)	Offset Wellbore Centre +N/-S (usft)	Offset Wellbore Centre +E/-W (usft)	Rule Assigned: Distance Between Centres (usft)	Distance Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
5,600.00	2,669.00	2,082.79	2,008.08	76.89	9.97	-84.913	-212.34	1,757.25	1,897.37	1,879.02	18.35	103.416	
5,700.00	2,669.00	2,051.54	1,979.80	79.19	9.76	-85.428	-221.37	1,767.00	1,990.83	1,972.48	18.34	108.540	

Anticollision Report

Company:	Riley Permian Operating Co., LLC	**Local Co-ordinate Reference:**	Well Marty Fee South 11-7 4H
Project:	Eddy County, New Mexico (NAD 83)	**TVD Reference:**	Well @ 3329.00usft (Akita 519)
Reference Site:	Marty Fee South 11-7 (3H, 4H)	**MD Reference:**	Well @ 3329.00usft (Akita 519)
Site Error:	0.00 usft	**North Reference:**	Grid
Reference Well:	Marty Fee South 11-7 4H	**Survey Calculation Method:**	Minimum Curvature
Well Error:	0.00 usft	**Output errors are at**	2.00 sigma
Reference Wellbore	Wellbore #1	**Database:**	TRG_EDMConroe
Reference Design:	Design #1	**Offset TVD Reference:**	Reference Datum

Offset Design: Over The Line 12-11 (1H, 2H) - Over The Line 12-11 2H - Wellbore #1 - Design #1

Offset Site Error: 0.00 usft

Survey Program: 0-MWD+HRGM

Offset Well Error: 0.00 usft

Reference Measured Depth (usft)	Reference Vertical Depth (usft)	Offset Measured Depth (usft)	Offset Vertical Depth (usft)	Semi Major Axis Reference (usft)	Semi Major Axis Offset (usft)	Azimuth from North (°)	Offset Wellbore Centre +N/-S (usft)	Offset Wellbore Centre +E/-W (usft)	Rule Assigned: Distance Between Centres (usft)	Rule Assigned: Distance Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
1,000.00	996.04	1,533.35	1,525.27	3.54	5.92	105.451	-530.06	1,897.95	1,988.23	1,979.35	8.88	223.893	
1,100.00	1,093.17	1,620.67	1,609.33	3.97	6.35	105.522	-528.30	1,874.35	1,939.57	1,930.02	9.56	202.911	
1,200.00	1,189.37	1,694.08	1,680.01	4.42	6.72	105.562	-526.83	1,854.56	1,887.86	1,877.67	10.19	185.247	
1,300.00	1,285.45	1,742.01	1,726.35	4.90	6.95	105.554	-525.92	1,842.40	1,837.14	1,826.41	10.73	171.270	
1,400.00	1,381.54	4,529.45	3,135.00	5.39	40.96	0.318	-30.78	150.28	1,753.66	1,737.07	16.59	105.680	
1,500.00	1,477.63	4,503.53	3,135.00	5.89	40.40	0.317	-30.92	176.20	1,657.78	1,641.29	16.49	100.528	
1,600.00	1,573.71	4,477.61	3,135.00	6.40	39.85	0.317	-31.07	202.11	1,561.97	1,545.57	16.40	95.235	
1,700.00	1,669.80	4,451.70	3,135.00	6.91	39.30	0.317	-31.21	228.03	1,466.28	1,449.95	16.33	89.807	
1,800.00	1,765.88	4,425.78	3,135.00	7.43	38.75	0.317	-31.35	253.95	1,370.70	1,354.43	16.27	84.244	
1,900.00	1,861.97	4,399.86	3,135.00	7.95	38.20	0.316	-31.50	279.87	1,275.28	1,259.04	16.24	78.541	
2,000.00	1,958.06	4,373.94	3,135.00	8.47	37.65	0.316	-31.64	305.78	1,180.04	1,163.81	16.24	72.684	
2,099.96	2,054.11	4,348.03	3,135.00	9.00	37.11	0.316	-31.78	331.69	1,085.08	1,068.81	16.27	66.674	
2,200.00	2,147.99	4,315.92	3,135.00	9.59	36.43	0.316	-31.96	363.80	992.84	976.53	16.31	60.870	
2,300.00	2,236.14	4,271.91	3,135.00	10.32	35.52	0.316	-32.20	407.81	907.38	890.96	16.42	55.270	
2,400.00	2,316.89	4,216.85	3,135.00	11.22	34.38	0.316	-32.50	462.87	830.83	814.11	16.71	49.707	
2,500.00	2,388.66	4,151.81	3,135.00	12.29	33.05	0.316	-32.86	527.91	765.31	747.99	17.32	44.181	
2,600.00	2,450.06	4,078.06	3,135.00	13.57	31.56	0.316	-33.27	601.66	712.76	694.44	18.32	38.908	
2,700.00	2,501.48	3,997.85	3,135.00	15.03	29.97	0.316	-33.71	681.87	673.11	653.40	19.71	34.146	
2,800.00	2,551.48	3,916.83	3,135.00	16.58	28.40	0.316	-34.16	762.89	638.03	616.52	21.51	29.662	
2,900.00	2,599.89	3,834.53	3,135.00	18.21	26.84	0.316	-34.61	845.19	607.52	583.95	23.57	25.772	
3,000.00	2,636.98	3,744.59	3,135.00	19.99	25.20	0.316	-35.11	935.13	586.73	561.40	25.33	23.163	
3,100.00	2,660.24	3,207.44	2,981.56	21.89	16.13	67.608	-207.37	1,399.59	513.33	488.51	24.82	20.682	
3,200.00	2,668.95	3,142.79	2,949.24	23.84	15.28	68.736	-243.36	1,442.48	438.03	413.77	24.26	18.056	
3,300.00	2,669.00	3,076.36	2,916.02	25.80	14.43	71.686	-280.34	1,486.55	367.07	344.33	22.74	16.139	
3,400.00	2,669.00	2,984.88	2,867.12	27.81	13.38	80.615	-330.00	1,545.73	295.97	275.84	20.13	14.702	
3,500.00	2,669.00	2,899.09	2,812.84	29.88	12.52	92.257	-372.66	1,596.57	221.09	204.04	17.05	12.964	
3,600.00	2,669.00	2,828.78	2,762.69	31.98	11.92	109.843	-404.30	1,634.28	146.14	129.91	16.23	9.006	
3,700.00	2,669.00	2,771.16	2,718.15	34.11	11.48	151.381	-427.79	1,662.27	85.45	54.02	31.44	2.718	
3,743.40	2,669.00	2,749.43	2,700.62	35.05	11.32	-179.926	-436.03	1,672.10	76.38	34.47	41.91	1.823	CC, ES, SF
3,800.00	2,669.00	2,723.65	2,679.31	36.27	11.15	-149.949	-445.37	1,683.22	91.57	46.40	45.17	2.027	
3,900.00	2,669.00	2,684.12	2,645.67	38.45	10.90	-125.327	-458.71	1,699.12	160.64	122.44	38.19	4.206	
4,000.00	2,669.00	2,650.00	2,615.76	40.64	10.69	-115.219	-469.25	1,711.68	245.82	212.15	33.67	7.301	
4,100.00	2,669.00	2,622.74	2,591.31	42.85	10.54	-109.632	-477.00	1,720.92	335.97	304.85	31.11	10.798	
4,200.00	2,669.00	2,600.00	2,570.58	45.07	10.42	-106.097	-483.01	1,728.08	428.51	398.99	29.52	14.515	
4,300.00	2,669.00	2,577.73	2,550.01	47.31	10.30	-103.749	-488.48	1,734.60	522.49	494.03	28.46	18.359	
4,400.00	2,669.00	2,559.55	2,533.01	49.55	10.21	-101.967	-492.64	1,739.56	617.47	589.79	27.68	22.305	
4,500.00	2,669.00	2,550.00	2,524.03	51.80	10.16	-100.458	-494.71	1,742.03	713.24	686.16	27.09	26.333	
4,600.00	2,669.00	2,529.45	2,504.54	54.06	10.06	-99.497	-498.92	1,747.04	809.49	782.85	26.64	30.386	
4,700.00	2,669.00	2,516.87	2,492.53	56.32	10.01	-98.604	-501.31	1,749.89	906.25	879.97	26.27	34.492	
4,800.00	2,669.00	2,500.00	2,476.32	58.59	9.93	-97.926	-504.30	1,753.46	1,003.41	977.43	25.97	38.635	
4,900.00	2,669.00	2,500.00	2,476.32	60.87	9.93	-97.187	-504.30	1,753.46	1,100.83	1,075.10	25.73	42.778	
5,000.00	2,669.00	2,486.31	2,463.09	63.15	9.87	-96.695	-506.55	1,756.14	1,198.52	1,172.99	25.52	46.956	
5,100.00	2,669.00	2,477.99	2,455.00	65.43	9.83	-96.229	-507.84	1,757.68	1,296.44	1,271.09	25.35	51.140	
5,200.00	2,669.00	2,470.39	2,447.61	67.72	9.80	-95.823	-508.96	1,759.01	1,394.56	1,369.36	25.20	55.332	
5,300.00	2,669.00	2,450.00	2,427.68	70.01	9.71	-95.541	-511.73	1,762.31	1,492.99	1,467.94	25.05	59.610	
5,400.00	2,669.00	2,450.00	2,427.68	72.30	9.71	-95.182	-511.73	1,762.31	1,591.31	1,566.36	24.95	63.773	
5,500.00	2,669.00	2,450.00	2,427.68	74.60	9.71	-94.866	-511.73	1,762.31	1,689.82	1,664.95	24.87	67.934	
5,600.00	2,669.00	2,450.00	2,427.68	76.89	9.71	-94.586	-511.73	1,762.31	1,788.50	1,763.69	24.81	72.088	
5,700.00	2,669.00	2,450.00	2,427.68	79.19	9.71	-94.335	-511.73	1,762.31	1,887.32	1,862.57	24.76	76.236	
5,800.00	2,669.00	2,450.00	2,427.68	81.49	9.71	-94.110	-511.73	1,762.31	1,986.26	1,961.55	24.71	80.375	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	Riley Permian Operating Co., LLC	**Local Co-ordinate Reference:**	Well Marty Fee South 11-7 4H
Project:	Eddy County, New Mexico (NAD 83)	**TVD Reference:**	Well @ 3329.00usft (Akita 519)
Reference Site:	Marty Fee South 11-7 (3H, 4H)	**MD Reference:**	Well @ 3329.00usft (Akita 519)
Site Error:	0.00 usft	**North Reference:**	Grid
Reference Well:	Marty Fee South 11-7 4H	**Survey Calculation Method:**	Minimum Curvature
Well Error:	0.00 usft	**Output errors are at**	2.00 sigma
Reference Wellbore	Wellbore #1	**Database:**	TRG_EDMConroe
Reference Design:	Design #1	**Offset TVD Reference:**	Reference Datum

Reference Depths are relative to Well @ 3329.00usft (Akita 519)
Offset Depths are relative to Offset Datum
Central Meridian is -104.333334

Coordinates are relative to: Marty Fee South 11-7 4H
Coordinate System is US State Plane 1983, New Mexico Eastern Zone
Grid Convergence at Surface is: -0.008°



CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company:	Riley Permian Operating Co., LLC	**Local Co-ordinate Reference:**	Well Marty Fee South 11-7 4H
Project:	Eddy County, New Mexico (NAD 83)	**TVD Reference:**	Well @ 3329.00usft (Akita 519)
Reference Site:	Marty Fee South 11-7 (3H, 4H)	**MD Reference:**	Well @ 3329.00usft (Akita 519)
Site Error:	0.00 usft	**North Reference:**	Grid
Reference Well:	Marty Fee South 11-7 4H	**Survey Calculation Method:**	Minimum Curvature
Well Error:	0.00 usft	**Output errors are at**	2.00 sigma
Reference Wellbore	Wellbore #1	**Database:**	TRG_EDMConroe
Reference Design:	Design #1	**Offset TVD Reference:**	Reference Datum

Reference Depths are relative to Well @ 3329.00usft (Akita 519)
Offset Depths are relative to Offset Datum
Central Meridian is -104.333334

Coordinates are relative to: Marty Fee South 11-7 4H
Coordinate System is US State Plane 1983, New Mexico Eastern Zone
Grid Convergence at Surface is: -0.008°



CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

DRILLING PROGRAM

Riley Exploration-Permian, LLC

Marty Fee South Pad

Marty Fee South 4H

Lot H Section 11, Township 18 South, Range 26 East, 6th P.M.

Eddy County, New Mexico

Owner: Bureau of Land Management

Land code: Exempt Agricultural Land

1. Geologic Name of Surface Formation

Quaternary

Estimated Tops of Important Geologic Markers:

Top	TC Thickness	Subsea	Top from KB	Lithology	Expected Fluids
Quaternary	353	3,339	**-10**	Salt/Red beds	Usable Water
Queen	417	2,986	**344**	ANHY/Dolomite	None
Grayburg	247	2,569	**761**	ANHY/Dolomite	Natural Gas, Oil
San Andres	1320	2,322	**1,008**	ANHY/Dolomite	Natural Gas, Oil
Glorieta	95	1,002	**2,328**	ANHY/Dolomite	Natural Gas, Oil
Paddock	121	907	**2,423**	ANHY/Dolomite	Natural Gas, Oil
Lower Paddock	125	786	**2,544**	ANHY/Dolomite	Natural Gas, Oil
Target		661	**2,669**	ANHY/Dolomite	Natural Gas, Oil

Target @ 0' VS	TVD	INC
	2,669	**90.00**

2. Blowout Prevention

Variance Requested for flex hose

Riley Permian requests a variance to use a flex line from the BOP to the choke manifold. Documentation will be attached in the APD and be readily available. No external damage to the flex line. Flex line to be installed as straight as possible with no bends.

Riley Permian will be utilize a 5M BOP

Condition	Specify what type and where?
BH Pressure at Deepest TVD	~1400 psi
Abnormal Temperature	No
BH Temperature at Deepest TVD	105-deg F

BOP/BOPE will be tested by an independent service company to 250 psi low and 70% of working pressure high unless otherwise required, as per Onshore Order 2 requirements. The System may be upgraded to a higher

pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed with be functional and tested.

Pipe rams will be operationally checked each 24-horu period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.

	Y	Are anchors required by manufacturer?
	A conventional wellhead system will be employed. The wellhead and connection to the BOPE will meet all API 6A requirements. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. See attached schematics.	

3. BOP Break Testing Request

Riley Exploration Permian LLC requests permission to adjust the BOP break testing requirements as follows:

BOP break test under the following conditions:

- After a full BOP test is conducted
- When skidding to drill the production section, where the surface casing point is shallower than the 3 Bone Spring or 10,000' TVD
- When skidding to drill a production section that does not penetrate the 3rd Bone Spring or deeper

If the kill line is broken prior to skid, four tests will be performed:

- The void between the wellead and the spool (one on each side for two tests)
- The spool between the kill lines and the choke manifold (consisting of two tests)

If the kill line is not broken prior to skid, two tests will be performed:

- The void between the wellhead and the pipe rams

4. Casing Program

All casing strings will be test in accordance with onshore oil and gas order #2 III.B.1.h.

Casing Formation Set Interval	Hole Size (in.)	Casing Interval		Casing Size (in.)	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	Body SF Tension	Joint SF Tension
		From (ft.)	To (ft.)								
San Andres	12.25	0	1250	9.625	36	J-55	BTC	1.125	1.2	1.4	1.4
N/A	8.75	0	3050	7	32	HCL-80	BTC	1.125	1.2	1.4	1.4
Yeso	8.75	3050	11116	5.5	20	HCL-80	BTC	1.125	1.2	1.4	1.4
								SF Values will MEET or EXCEED			

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

5. Cement Program:

Casing String	Top (ft.)	Bottom (ft.)	% Excess
Surface (Lead)	0	950	100%
Surface (Tail)	875	1250	100%
Production (Lead)	0	2300	35%+
Production (Tail)	2435	11116	35%+

Casing String	# Sx	Wt. (lb/gal)	Yld (ft3/sk)	H20 (gal/sk)	500# Compressive Strength (hours)	Slurry Description
Surface (lead)	450	12.8	1.43	6.65	6:44	50/50 Poz C Premium Plus
Surface (tail)	195	14.8	1.33	6.32	8:05	Class C Premium Plus
Production (lead)	125	11.5	2.29	12.63	N/A	50/50 Poz C Premium Plus
Production (tail)	2285	13.7	1.31	5.61	N/A	35/65 Poz C Premium Plus

6. Types and Characteristics of the Proposed Mud System:

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times. The following is a general list of products: Barite, Bentonite, Gypsum, Lime, Soda Ash, Caustic Soda, Nut Plug, Cedar Fiber, Cotton Seed Hulls, Drilling Paper, Salt Water Clay, CACL2. Riley will utilize a closed mud system.

Depth		Type	Weight (ppg)	Viscosity (cp)	Water Loss
From (ft.)	To (ft.)				
0	1250	Water-Based Mud	8.6-8.9	32-36	N/C
1250	TD	Water-Based Mud	8.6-8.10	32-37	N/C

PVT/Pason/Visual Monitoring will be used to monitor the loss or gain of fluid.

7. Logging, Testing and Coring Program:

Logging, Coring and Testing.	
Yes	Will run GR from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
No	Logs are planned based on well control or offset log information.
No	Drill stem test? If yes, explain
No	Coring? If yes, explain

Additional logs planned		Interval
No	Resistivity	
No	Density	
No	CBL	
Yes	Mud log	SCP - TD
No	PEX	

8. Drilling Conditions

Pump high viscosity sweeps as needed for hole cleaning. The mud system will be monitored visually/manually as well as with an electronic PVT. The necessary mud products for additional weight and fluid loss control will be on location at all times. Appropriately weighted mud will be used to isolate potential gas, oil, and water zones until such time as casing can be cemented into place for zonal isolation.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.	
N	H2S is present
Y	H2S Plan attached

Total estimated cuttings volume: 990 bbls

NOTES REGARDING THE BLOWOUT PREVENTERS

Marty Fee 4H

Eddy County, New Mexico

1. Drilling nipple to be so constructed that it can be removed without use of a welder through rotary table opening, with minimum I.D. equal to preventer bore.

2. Wear ring to be properly installed in head.

3. Blow out preventer and all fittings must be in good condition, 3000 psi WP minimum.

4. All fittings to be flanged.

5. Safety valve must be available on rig floor at all times with proper connections, valve to be full 3000 psi WP minimum.

6. All choke and fill lines to be securely anchored especially ends of choke lines.

7. Equipment through which bit must pass shall be at least as large as the diameter of the casing being drilled through.

8. Kelly cock on Kelly.

9. Extension wrenches and hands wheels to be properly installed.

10. Blow out preventer control to be located as close to driller's position as feasible.

11. Blow out preventer closing equipment to include minimum 40-gallon accumulator, two independent sources of pump power on each closing unit installation all API specifications.

Riley Permian

Exhibit 10

Minimum BOP and Choke Requirements

3M and 5M Systems



BOP - Minimum Requirements

	Description		ID (in.)	Nom. OD (in.)	Optional	Note
1	Annular				Yes - 2M	
2A	Double Gate	Pipe Ram	3 1/8		No	
2B		Blind Ram				
3A	Kill Line	Gate	2		No	
3A		Gate				
3B		Check Valve				
		Line		2		
4	Mud Cross		2 1/16		No	Kill Line - 2" min. Choke Line - 3" min.
5A	Choke Line	Gate - Manual (2)	3 1/8		No	
5B		Gate - Remote (2)				
5C		Line		3	No	
5D		Targeted Tee			No	
6	Single Gate - Pipe Ram				Yes - 2M and 3M	

(1) Only one required in 2M system
(2) Choke line valve order is interchangable
(3) Remote operated hydraulic choke required on 5M and 10M systems

Choke Manifold - Minimum Requirements

			3000 MWP			5000 MWP			10000 MWP		
	Description		ID (in.)	Nominal OD (in. unless otherwise noted)	Rating (psi)	ID (in.)	Nominal OD (in. unless otherwise noted)	Rating (psi)	ID (in.)	Nominal OD (in. unless otherwise noted)	Rating (psi)
7	Cross - 3" x 3" x 3" x 2"				3,000			5,000			10,000
8	Valve	Gate (2)	2 1/16		3,000	2 1/16		5,000	3 1/8		10,000
9		Plug									
9	Pressure Gauge				3,000			5,000			10,000
10	Valve	Gate (2)	3 1/8		3,000	3 1/8		5,000	3 1/8		10,000
		Plug									
11	Remote Operated Adjustable Choke (3)		2 1/16		3,000			5,000			10,000
12	Manual Adjustable Choke		2 1/16		3,000			5,000			10,000
13	Line			3	3,000		3	5,000		3	10,000
14	Line			2	3,000		2	5,000		2	10,000
15	Gas Separator (4)			2' x 5'			2' x 5'			2' x 5'	

(1) Only one required in 2M system
(2) Gate valves only to be used for 10M system
(3) Remote chokes are required for 5M and 10M systems
(4) Gas separator is optional for 2M and 3M systems

Riley Permian Operating Company, LLC

Onshore Order #6
Hydrogen Sulfide Drilling Operation Plan

I. HYDROGEN SULFIDE TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards an characteristics of hydrogen sulfide (H2S)
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H2S detectors alarms warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H2S on metal components. If high tensile tubular are to be used, personnel well be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H2S Drilling Operations Plan and Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H2S zone (within 3 days or 500 feet) and weekly H2S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H2S Drilling Operations Plan and the Public Protection Plan. **The concentrations of H2S of wells in this area from surface to TD are low enough that a contingency plan is not required.**

II. H2S SAFETY EQUIPMENT AND SYSTEMS

Note: All H2S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonable expected to contain H2S.

1. **Well Control Equipment:**

   A. Flare line.
   B. Choke manifold.
   C. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit.
   D. Auxiliary equipment may include if applicable: annular preventer & rotating head.

2. **Protective equipment for essential personnel:**

A. Mark II Survive air 30-minute units located in the doghouse and at briefing areas, as indicated on well site diagram.

3. H2S detection and monitoring equipment:

A. 3x portable H2S monitors positioned on location for best coverage and response. These units have warning lights and audible sirens when H2S levels of 20 PPM are reached.

4. Visual warning systems:

A. Wind direction indicators as shown on well site diagram (Exhibit #8).
B. Caution/Danger signs (Exhibit #7) shall be posted on roads providing direct access to location. Signs will be painted a high visibility yellow with black lettering of sufficient size to be readable at a reasonable distance from the immediate location. Bilingual signs will be used, when appropriate. See example attached.

5. Mud program:

A. The mud program has been designed to minimize the volume of H2S circulated to surface. Proper mud weight, safe drilling practices and the use of H2S scavengers will minimize hazards when penetrating H2S bearing zones.

6. Metallurgy:

A. All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H2S service.
B. All elastomers used for packing and seals shall be H2S trim.

7. Communication:

A. Radio communications in company vehicles including cellular telephone and 2-way radio.
B. Land line (telephone) communication at Office.

8. Well testing:

A. Drill stem testing will be performed with a minimum number of personnel in the immediate vicinity, which are necessary to safely and adequately conduct the test. The drill stem testing will be conducted during daylight hours and formation fluids will not be flowed to the surface. All drill-stem-testing operations conducted in an H2S environment will use the closed chamber method of testing.

B. There will be no drill stem testing.

Exhibit #7

WARNING

YOU ARE ENTERING AN H2S AREA
AUTHORIZED PERSONNEL ONLY

1. BEARDS OR CONTACT LENSES NOT ALLOWED
2. HARD HATS REQUIRED
3. SMOKING IN DESIGNATED AREAS ONLY
4. BE WIND CONSCIOUS AT ALL TIMES
5. CHECK WITH RILEY PERMIAN OPERATING COMPANY MAN AT OFFICE

RILEY PERMIAN OPERATING COMPANY, LLC
1-405-415-8699



DRILLING LOCATION H2S SAFTY EQUIPMENT
Exhibit # 8



EMERGENCY CONTACT LIST – EDDY COUNTY

Artesia	Cellular	Office
Spence Laird	575-703-7382	405-420-8415
Steve Forister	505-400-4571	405-666-0113
Travis Kerr	713-823-6933	
Justing Sappington	361-550-0494	

Agency Call List (575)

Artesia

State Police.....746-2703

City Police.....746-2703

Sheriff's Office.....746-9888

Ambulance.....911

Fire Department.....746-2701

LEPC (Local Emergency Planning Committee.....746-2122

NMOCD.....748-1283

Carlsbad

State Police.....885-3137

City Police.....885-2111

Sheriff's Office.....887-7551

Ambulance.....911

Fire Department.....885-2111

LEPC (Local Emergency Planning Committee.....887-3798

Bureau of Land Management.....887-6544

New Mexico Emergency Response Commission.....(505)476-9690

24 Hour.....(505)827-9126

National Emergency Response Center (Washington)……(800)424-8802

Emergency Services

Boots & Coots IWC……1-800-256-9688 or (281)931-8884

Cudd pressure Control…….(915)699-0139 or (915)563-3356

Halliburton……..746-2757

Par Five……..748-9539

Flight For Life-Lubbock, TX……(806)743-9911

Aerocare-Lubbock, TX……..(806)747-8923

Med Flight Air Amb-Albuquerque, NM…….(505)842-4433

Lifeguard Air Med Svc. Albuquerque, NM……(505)272-3115

State of New Mexico
Energy, Minerals and Natural Resources Department

Submit Electronically
Via E-permitting

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

Section 1 – Plan Description

Effective May 25, 2021

I. Operator: Riley Permian Operating Company LLC **OGRID:** 372290 **Date:** 04 / 04 / 2025

II. Type: ☑ Original ☐ Amendment due to ☐ 19.15.27.9.D(6)(a) NMAC ☐ 19.15.27.9.D(6)(b) NMAC ☐ Other.

If Other, please describe: _____

III. Well(s): Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
Marty Fee South 11-7 3H	30-015-PENDING	H - 11-18S-26E	1920' FNL 1040' FEL	450	700	4,000
Marty Fee South 11-7 4H	30-015-PENDING	H - 11-18S-26E	1950' FNL 1040' FEL	450	700	4,000

IV. Central Delivery Point Name: Marty South Pad CTB [See 19.15.27.9(D)(1) NMAC]

V. Anticipated Schedule: Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
Marty Fee South 11-7 3H	30-015-PENDING	6/1/2025	6/8/2025	9/1/2025	10/1/2025	10/1/2025
Marty Fee South 11-7 4H	30-015-PENDING	6/1/2025	6/8/2025	9/1/2025	10/1/2025	10/1/2025

VI. Separation Equipment: ☑ Attach a complete description of how Operator will size separation equipment to optimize gas capture.

VII. Operational Practices: ☑ Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

VIII. Best Management Practices: ☑ Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

Section 2 – Enhanced Plan
EFFECTIVE APRIL 1, 2022

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

☑ Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

IX. Anticipated Natural Gas Production:

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

X. Natural Gas Gathering System (NGGS):

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

XI. Map. ☐ Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

XII. Line Capacity. The natural gas gathering system ☐ will ☐ will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

XIII. Line Pressure. Operator ☐ does ☐ does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

☐ Attach Operator's plan to manage production in response to the increased line pressure.

XIV. Confidentiality: ☐ Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

Section 3 - Certifications

Effective May 25, 2021

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

☑ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

☐ Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system. ***If Operator checks this box, Operator will select one of the following:***

Well Shut-In. ☐ Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

Venting and Flaring Plan. ☐ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- **(a)** power generation on lease;
- **(b)** power generation for grid;
- **(c)** compression on lease;
- **(d)** liquids removal on lease;
- **(e)** reinjection for underground storage;
- **(f)** reinjection for temporary storage;
- **(g)** reinjection for enhanced oil recovery;
- **(h)** fuel cell production; and
- **(i)** other alternative beneficial uses approved by the division.

Section 4 - Notices

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature:	Spence Laird
Printed Name:	Spence Laird
Title:	EHSR Manager
E-mail Address:	spencelaird@rileypermian.com
Date:	4/14/25
Phone:	405-543-1411

OIL CONSERVATION DIVISION **(Only applicable when submitted as a standalone form)**
Approved By:
Title:
Approval Date:
Conditions of Approval:

Natural Gas Management Plan – Attachment

VI. Separation equipment will be sized by construction engineering staff based on anticipated daily production to ensure adequate capacity.

VII. Riley Permian Operating Company LLC ("Riley") will take the following actions to comply with the regulations listed in 19.15.27.8:

A. Riley will maximize the recovery of natural gas by minimizing waste, as defined by 19.15.2 NMAC, of natural gas through venting and flaring. Spur will ensure that our wells will be connected to a natural gas gathering system with sufficient capacity to transport natural gas.

B. All drilling operations will be equipped with a rig flare at least 100 feet from the nearest surface hole location. Rig flare will be utilized to combust any natural gas that is brought to surface during normal operations. In the case of emergency, flaring volumes will be reported appropriately.

C. During completion operations any natural gas brought to surface will be flared. Immediately following completion operations, wells will flow to permanent separation equipment. Produced natural gas from separation equipment will be sent to sales. If natural gas does not meet gathering pipeline specifications, Riley will flare for 60 days or until natural gas meets the pipeline specifications. Riley will ensure flare is properly sized and is equipped with an automatic igniter or continuous pilot. Gas samples will be taken twice per week and natural gas will be routed into a gathering system as soon as the pipeline specifications are met.

D. Natural gas will not be flared with the exception of 19.15.27.8(D)(1-4). If there is no adequate takeaway for the separator gas, wells will be shut-in until that natural gas gathering system is available with exception of emergency or malfunction situations. Volumes will be reported appropriately.

E. Riley will comply with performance standards pursuant to 19.15.27.8(E)(1-8). All equipment will be designed and sized to handle maximum pressures to minimize waste. Storage tanks constructed after May 25, 2021 will be equipped with an automatic gauging system that reduces venting of natural gas. Flare stacks installed or replaced after May 25, 2021 will be equipped with an automatic ignitor or continuous pilot. Riley will conduct AVO inspections as described in 19.15.27.8(E)(5)(a) with frequencies specified in 19.15.27.8(E)(5)(b) and (c). All emergencies or malfunctions will be resolved as quickly and safely as possible to minimize waste.

F. The volume of natural gas that is vented or flared as the result of an emergency or malfunction during drilling and/or completion operations will be estimated and reported accordingly. The volume of natural gas that is vented, flared, or beneficially used during production operations will be measured and reported accordingly. Riley will install equipment to measure the volume of natural gas flared from existing piping or a flowline piped from equipment such as high-pressure separators, heater treaters, or VRUs associated with a well of facility associated with a well authorized by an APD after May 25, 2021 that has an average daily production of less than 60,000 cubic feet of natural gas.

If metering is not practicable due to circumstances such as low flow rate or low pressure venting or flaring, Riley will estimate the volume of flared or vented natural gas. Measuring equipment will conform to industry standards and will not be equipped with a manifold that allows the diversion of natural gas around the metering element except for the sole purpose of inspecting and servicing equipment.

VIII. For maintenance activities involving production equipment and compression, venting be limited to the depressurization of the subject equipment to ensure safe working conditions. For maintenance of production equipment, the associated producing wells will be shut-in to eliminate venting. For maintenance of VRUs, all natural gas normally routed to the VRU will be routed to flare.