

Sante Fe Main Office  
Phone: (505) 476-3441

General Information  
Phone: (505) 629-6116

Online Phone Directory  
<https://www.emnrd.nm.gov/ocd/contact-us>

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form C-101  
August 1, 2011

Permit 390799

**APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE**

1. Operator Name and Address DEVON ENERGY PRODUCTION COMPANY, LP 333 West Sheridan Ave. Oklahoma City, OK 73102		2. OGRID Number 6137
		3. API Number 30-025-54804
4. Property Code 335061	5. Property Name NORTH THISTLE 10 STATE COM	6. Well No. 218H

**7. Surface Location**

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
B	10	23S	33E		550	N	1830	E	Lea

**8. Proposed Bottom Hole Location**

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	15	23S	33E	P	20	S	700	E	Lea

**9. Pool Information**

BRINNINSTOOL;BONE SPRING	7320
--------------------------	------

**Additional Well Information**

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3601
16. Multiple N	17. Proposed Depth 21583	18. Formation Bone Spring	19. Contractor	20. Spud Date 10/20/2025
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

☒ We will be using a closed-loop system in lieu of lined pits

**21. Proposed Casing and Cement Program**

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1162	879	0
Int1	12.25	9.625	40	5206	724	0
Prod	8.75	5.5	20	21583	2605	4706

**Casing/Cement Program: Additional Comments**

Please see attached drill plan for Int 1 Intermediate Squeeze info.
---

**22. Proposed Blowout Prevention Program**

Type	Working Pressure	Test Pressure	Manufacturer
Double Ram	5000	5000	
Blind	5000	5000	
Annular	5000	5000	
Annular	5000	5000	
Blind	5000	5000	
Double Ram	5000	5000	

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify I have complied with 19.15.14.9 (A) NMAC <input checked="" type="checkbox"/> and/or 19.15.14.9 (B) NMAC <input checked="" type="checkbox"/> if applicable.	<b>OIL CONSERVATION DIVISION</b>	
Signature:		
Printed Name: Electronically filed by Jeff Walla	Approved By: Jeffrey Harrison	
Title: Supervisor Land	Title: Petroleum Specialist III	
Email Address: Jeff.Walla@dmn.com	Approved Date: 7/7/2025	Expiration Date: 7/7/2027
Date: 5/22/2025	Phone: 575-748-9925	Conditions of Approval Attached

C-102  Submit Electronically Via OCD Permitting	State of New Mexico Energy, Minerals & Natural Resources Department <b>OIL CONSERVATION DIVISION</b>		Revised July, 2024	
			Submittal Type:	<input checked="" type="checkbox"/> Initial Submittal
				<input type="checkbox"/> Amended Report
		<input type="checkbox"/> As Drilled		

## WELL LOCATION INFORMATION

API Number <b>30-025-54804</b>	Pool Code <b>7320</b>	Pool Name <b>BRINNINSTOOL;BONE SPRING</b>
Property Code <b>335061</b>	Property Name <b>NORTH THISTLE 10 STATE COM</b>	Well Number <b>218H</b>
OGRID No. <b>6137</b>	Operator Name <b>DEVON ENERGY PRODUCTION COMPANY, L.P.</b>	Ground Level Elevation <b>3600.8'</b>
Surface Owner: <input checked="" type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input type="checkbox"/> Federal		Mineral Owner: <input checked="" type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input type="checkbox"/> Federal

## Surface Location

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
B	10	23-S	33-E		550' N	1830' E	32.324983	103.557609	LEA

## Bottom Hole Location

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
P	15	23-S	33-E		20' S	700' E	32.297511	103.553939	LEA

Dedicated Acres <b>160</b>	Infill or Defining Well <input type="checkbox"/>	Defining Well API <input checked="" type="checkbox"/>	Overlapping Spacing Unit (Y/N) <b>Y</b>	Consolidation Code <b>C</b>
Order Numbers			Well setbacks are under Common Ownership: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

## Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
A	10	23-S	33-E		50' N	700' E	32.326364	103.553950	LEA



## First Take Point (FTP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
A	10	23-S	33-E		100' N	700' E	32.326227	103.553950	LEA

## Last Take Point (LTP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
P	10	23-S	33-E		100' S	700' E	32.312255	103.553946	LEA

Spacing Unit Type		Horizontal	Vertical	Ground Floor Elevation:
		<input checked="" type="checkbox"/>	<input type="checkbox"/>	


<b>OPERATOR CERTIFICATIONS</b> I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and, if the well is a vertical or directional well, that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of a working interest or unleased mineral interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.  If this well is a horizontal well, I further certify that this organization has received the consent of at least one lessee or owner of a working interest or unleased mineral interest in each tract (in the target pool or formation) in which any part of the well's completed interval will be located or obtained a compulsory pooling order from the division.		<b>SURVEYOR CERTIFICATIONS</b> I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under supervision, and that the same is true and correct to the best of my belief.	
Signature  Date <b>5/22/2025</b>		Signature and Seal of Professional Surveyor 	
Printed Name <b>Rebecca Deal, Regulatory Analyst</b> Email Address <b>rebecca.deal@dvn.com</b>		Certificate Number <b>23261</b>	Date of Survey <b>04/2025</b>

## ACREAGE DEDICATION PLATS

This grid represents a standard section. You may superimpose a non-standard section, or larger area, over this grid. Operators must outline the dedicated acreage in a red box, clearly show the well surface location and bottom hole location, if it is directionally drilled, with the dimensions from the section lines in the cardinal directions. If this is a horizontal wellbore show on this plat the location of the First Take Point and Last Take Point, and the point within the Completed interval (other than the First Take Point or Last Take Point) that is closest to any outer boundary of the tract.

Surveyors shall use the latest United States government survey or dependent resurvey. Well locations will be in reference to the New Mexico Principal Meridian. If the land is not surveyed contact the OCD Engineering Bureau. Independent subdivision surveys will not be acceptable.

<b>NORTH THISTLE 10 STATE CDM 218H</b> GEOIDETIC COORDINATES NAD 83 NMSP EAST SURFACE LOCATION 550' FNL 1830' FEL SECTION 10 EL: 3600.8' N:482828.57/E:780954.05 LAT:32.324983/LDN:103.557609
<b>KICK OFF POINT</b> 50' FNL 700' FEL SECTION 10 N:483339.02/E:782080.52 LAT:32.326364/LDN:103.553950
<b>FIRST TAKE POINT</b> 100' FNL 700' FEL SECTION 10 N:483289.02/E:782080.92 LAT:32.326227/LDN:103.553950
<b>LAST TAKE POINT</b> 100' FSL 700' FEL SECTION 10 N:478206.23/E:782119.24 LAT:32.312255/LDN:103.553946
<b>BOTTOM HOLE LOCATION</b> 20' FSL 700' FEL SECTION 15 N:472842.24/E:782160.31 LAT:32.297511/LDN:103.553939



A = N:483357.66 E:777494.32
B = N:483371.16 E:780150.63
C = N:483395.50 E:782780.10
D = N:480752.40 E:782801.00
E = N:478110.23 E:782819.94
F = N:475468.20 E:782840.20
G = N:472826.18 E:782860.45
H = N:472811.30 E:780219.55
I = N:472796.69 E:777577.35
J = N:475436.03 E:777556.56
K = N:478077.69 E:777535.68
L = N:478095.15 E:780174.27

Sante Fe Main Office  
Phone: (505) 476-3441

General Information  
Phone: (505) 629-6116

Online Phone Directory  
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

Form APD Comments

Permit 390799

PERMIT COMMENTS

Operator Name and Address: DEVON ENERGY PRODUCTION COMPANY, LP [6137] 333 West Sheridan Ave. Oklahoma City, OK 73102		API Number: 30-025-54804
		Well: NORTH THISTLE 10 STATE COM #218H

Created By	Comment	Comment Date
rdeal	Only completing the first mile of well, production from Sec 10.	5/22/2025
jeffrey.harrison	Defining well for HSU	7/1/2025
jeffrey.harrison	At time of approval of original permit, proposed well design is to complete and produce from the portion of the well contained in section 10 and to use the portion of the lateral in section 15 for data collection/observation.	7/7/2025

Sante Fe Main Office  
Phone: (505) 476-3441

General Information  
Phone: (505) 629-6116

Online Phone Directory  
<https://www.emnrd.nm.gov/oecd/contact-us>

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form APD Conditions

Permit 390799

**PERMIT CONDITIONS OF APPROVAL**

Operator Name and Address: DEVON ENERGY PRODUCTION COMPANY, LP [6137] 333 West Sheridan Ave. Oklahoma City, OK 73102	API Number: 30-025-54804
	Well: NORTH THISTLE 10 STATE COM #218H

OCD Reviewer	Condition
jeffrey.harrison	Prior to any completion activities for the data observation portion of the lateral penetrating Units A-H-I-P of section 15 of 23S 33E, please submit a C-103 NOI Change of Plans as well as a separate C-104 completion report.
jeffrey.harrison	Notify the OCD 24 hours prior to casing & cement.
jeffrey.harrison	A [C-103] Sub. Drilling (C-103N) is required within (10) days of spud.
jeffrey.harrison	File As Drilled C-102 and a directional Survey with C-104 completion packet.
jeffrey.harrison	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string.
jeffrey.harrison	Cement is required to circulate on both surface and intermediate1 strings of casing.
jeffrey.harrison	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.
jeffrey.harrison	If cement does not circulate on any string, a Cement Bond Log (CBL) is required for that string of casing.

State of New Mexico  
Energy, Minerals and Natural Resources DepartmentSubmit Electronically  
Via E-permittingOil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505**NATURAL GAS MANAGEMENT PLAN**

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

**Section 1 – Plan Description****Effective May 25, 2021****I. Operator:** Devon Energy Production Company, L.P. **OGRID:** 6137 **Date:** 4 / 22 / 2025**II. Type:** ☒ Original ☐ Amendment due to ☐ 19.15.27.9.D(6)(a) NMAC ☐ 19.15.27.9.D(6)(b) NMAC ☐ Other.

If Other, please describe: \_\_\_\_\_

**III. Well(s):** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
See Attached						

**IV. Central Delivery Point Name:** PARSELTONGUE 10 CTB 1 [See 19.15.27.9(D)(1) NMAC]**V. Anticipated Schedule:** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
See Attached						

**VI. Separation Equipment:** ☒ Attach a complete description of how Operator will size separation equipment to optimize gas capture.**VII. Operational Practices:** ☒ Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.**VIII. Best Management Practices:** ☒ Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

**Section 2 – Enhanced Plan****EFFECTIVE APRIL 1, 2022**

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

☒ Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

**IX. Anticipated Natural Gas Production:**

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

**X. Natural Gas Gathering System (NGGS):**

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

**XI. Map.** ☐ Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

**XII. Line Capacity.** The natural gas gathering system ☐ will ☐ will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

**XIII. Line Pressure.** Operator ☐ does ☐ does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

☐ Attach Operator's plan to manage production in response to the increased line pressure.

**XIV. Confidentiality:** ☐ Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

### **Section 3 - Certifications**

**Effective May 25, 2021**

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

☒ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

☐ Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

***If Operator checks this box, Operator will select one of the following:***

**Well Shut-In.** ☐ Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

**Venting and Flaring Plan.** ☐ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

### **Section 4 - Notices**

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:


(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.



I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature: 
Printed Name: Jeff Walla
Title: Surface Land and Regulatory Manager
E-mail Address:
Date:
Phone:
<b>OIL CONSERVATION DIVISION</b> <b>(Only applicable when submitted as a standalone form)</b>
Approved By:
Title:
Approval Date:
Conditions of Approval:

## PARSELTONGUE 10 CTB 2

Well Name	API	SHL - STR & Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
NORTH THISTLE 10 STATE COM 218H		10-23S-33E, 550 FNL & 1830 FEL	(+/-)1075bopd, (+/-) 836mcf/d, (+/-)2043bwpd		
NORTH THISTLE 15-10 STATE COM 205H		10-23S-33E, 176 FNL & 1393 FWL	(+/-)1075bopd, (+/-) 836mcf/d, (+/-)2043bwpd		
NORTH THISTLE 15-10 STATE COM 206H		10-23S-33E, 176 FNL & 1453 FWL	(+/-)1075bopd, (+/-) 836mcf/d, (+/-)2043bwpd		
NORTH THISTLE 15-10 STATE COM 207H		10-23S-33E, 550 FNL & 1920 FEL	(+/-)1075bopd, (+/-) 836mcf/d, (+/-)2043bwpd		
NORTH THISTLE 15-10 STATE COM 208H		10-23S-33E, 550 FNL & 1860 FEL	(+/-)1075bopd, (+/-) 836mcf/d, (+/-)2043bwpd		
NORTH THISTLE 15-10 STATE COM 215H		10-23S-33E, 176 FNL & 1423 FWL	(+/-)1075bopd, (+/-) 836mcf/d, (+/-)2043bwpd		
NORTH THISTLE 15-10 STATE COM 216H		10-23S-33E, 176 FNL & 1483 FWL	(+/-)1075bopd, (+/-) 836mcf/d, (+/-)2043bwpd		
NORTH THISTLE 15-10 STATE COM 217H		10-23S-33E, 550 FNL & 1890 FEL	(+/-)1075bopd, (+/-) 836mcf/d, (+/-)2043bwpd		
PARSELTONGUE 15-10 STATE COM 900H		10-23S-33E, 176 FNL & 1363FWL	(+/-)1075bopd, (+/-) 836mcf/d, (+/-)2043bwpd		
PARSELTONGUE 15-10 STATE COM 906H		10-23S-33E, 550 FNL & 1800 FEL	(+/-)1075bopd, (+/-) 836mcf/d, (+/-)2043bwpd		

Well Name	API	Anticipated Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
NORTH THISTLE 10 STATE COM 218H		10/20/25	11/19/2025	3/19/2026	3/19/2026	3/19/2026
NORTH THISTLE 15-10 STATE COM 205H		10/13/25	11/12/2025	3/12/2026	3/12/2026	3/12/2026
NORTH THISTLE 15-10 STATE COM 206H		09/26/25	10/26/2025	2/23/2026	2/23/2026	2/23/2026
NORTH THISTLE 15-10 STATE COM 207H		09/09/25	10/9/2025	2/6/2026	2/6/2026	2/6/2026
NORTH THISTLE 15-10 STATE COM 208H		09/26/25	10/26/2025	2/23/2026	2/23/2026	2/23/2026
NORTH THISTLE 15-10 STATE COM 215H		09/12/25	10/12/2025	2/9/2026	2/9/2026	2/9/2026
NORTH THISTLE 15-10 STATE COM 216H		08/28/25	9/27/2025	1/25/2026	1/25/2026	1/25/2026
NORTH THISTLE 15-10 STATE COM 217H		10/13/25	11/12/2025	3/12/2026	3/12/2026	3/12/2026
PARSELTONGUE 15-10 STATE COM 900H		10/24/25	11/23/2025	3/23/2026	3/23/2026	3/23/2026
PARSELTONGUE 15-10 STATE COM 906H		10/27/25	11/26/2025	3/26/2026	3/26/2026	3/26/2026



## VI. Separation Equipment

Devon Energy Production Company, L.P. utilizes a "stage separation" process in which oil and gas separation is carried out through a series of separators operating at successively reduced pressures. Hydrocarbon liquids are produced into a high-pressure inlet separator, then carried through one or more lower pressure separation vessels before entering the storage tanks. The purpose of this separation process is to attain maximum recovery of liquid hydrocarbons from the fluids and allow maximum capture of produced gas into the sales pipeline. Devon utilizes a series of Low-Pressure Compression units to capture gas off the staged separation and send it to the sales pipeline. This process minimizes the amount of flash gas that enters the end-stage storage tanks that is subsequently vented or flared.



## VII. Operational Practices

Devon Energy Production Company, L. P. will employ best management practices and control technologies to maximize the recovery and minimize waste of natural gas through venting and flaring.

- During drilling operations, Devon will utilize flares and/or combustors to capture and control natural gas, where technically feasible. If flaring is deemed technically in-feasible, Devon will employ best management practices to minimize or reduce venting to the extent possible.
- During completions operations, Devon will utilize Green Completion methods to capture gas produced during well completions that is otherwise vented or flared. If capture is technically in-feasible, flares and/or combustors will be used to capture and control flow back fluids entering into frac tanks during initial flowback. Upon indication of first measurable hydrocarbon volumes, Devon will turn operations to onsite separation vessels and flow to the gathering pipeline.
- During production operations, Devon will take every practical effort to minimize waste of natural gas through venting and flaring by:
  - Designing and constructing facilities in a manner consistent to achieve maximum capture and control of hydrocarbon liquids & produced gas
  - Utilizing a closed-loop capture system to collect and route produced gas to sales line via low pressure compression, or to a flare/combustor
  - Flaring in lieu of venting, where technically feasible
  - Utilizing auto-ignitors or continuous pilots, with thermocouples connected to Scada, to quickly detect and resolve issues related to malfunctioning flares/combustors
  - Employ the use of automatic tank gauging to minimize storage tank venting during loading events
  - Installing air-driven or electric-driven pneumatics & combustion engines, where technically feasible to minimize venting to the atmosphere
  - Confirm equipment is properly maintained and repaired through a preventative maintenance and repair program to ensure equipment meets all manufacturer specifications
  - Conduct and document AVO inspections on the frequency set forth in Part 27 to detect and repair any onsite leaks as quickly and efficiently as is feasible



#### VIII. Best Management Practices during Maintenance


Devon Energy Production Company, L.P. will utilize best management practices to minimize venting during active and planned maintenance activities. Devon is operating under guidance that production facilities permitted under NOI permits have no provisions to allow high pressure flaring and high pressure flaring is only allowed in disruption scenarios so long as the duration is less than eight hours. When technically feasible, flaring during maintenance activities will be utilized in lieu of venting to the atmosphere. Devon will work with third-party operators during scheduled maintenance of downstream pipeline or processing plants to address those events ahead of time to minimize venting. Actions considered include identifying alternative capture approaches or planning to temporarily reduce production or shut in the well to address these circumstances.



Well: NORTH THISTLE 10 STATE COM 218H  
County: Lea  
Wellbore: Permit Plan  
Design: Permit Plan #1

Geodetic System: US State Plane 1983  
Datum: North American Datum 1927  
Ellipsoid: Clarke 1866  
Zone: 3001 - NM East (NAD83)

MD	INC	AZI	TVD	NS	EW	VS	DLS	Comment
(ft)	(°)	(°)	(ft)	(ft)	(ft)	(ft)	(°/100ft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
2000.00	0.00	65.57	2000.00	0.00	0.00	0.00	0.00	Start Tangent
2500.00	10.00	65.57	2497.47	18.00	39.63	-13.12	2.00	Hold Tangent
9123.62	10.00	65.57	9020.46	493.69	1086.83	-359.80	0.00	Drop to Vertical
9623.62	0.00	65.57	9517.93	511.69	1126.45	-372.92	2.00	Hold Vertical
10757.74	0.00	179.56	10652.04	511.69	1126.45	-372.92	0.00	KOP
11657.74	90.00	179.56	11225.00	-61.25	1130.81	196.41	10.00	Landing Point
21583.11	90.00	179.56	11225.00	-9986.33	1206.26	10058.92	0.00	BHL



Key Depths	MD	TVD
	(ft)	(ft)
Rustler	1137.00	1137.00
Salt	1620.00	1620.00
Base of Salt	1620.00	1620.00
Delaware	5148.78	5106.00
Cherry Canyon	6119.52	6062.00
Brushy Canyon	7337.02	7261.00
Bone Spring 1st	9104.88	9002.00
Bone Spring 2nd / Point of Penetration	10772.70	10667.00
exit	16200.00	11225.01

SHL  
KOP  
Point of Penetration  
Exit  
BHL

MD	TVD	Lat	Long	Section Footages
(ft)	(ft)	(°)	(°)	
0.00	0.00	32.3249	-103.5577	550' FNL, 1830' FEL of Sec 10 in T23S, R33E
10757.74	10652.04	32.3263	-103.5539	50' FNL, 700' FEL of Sec 10 in T23S, R33E
10772.70	10667.00	32.3262	-103.5540	100' FNL, 700' FEL of Sec 10 in T23S, R33E
16200.00	11225.01	32.3123	-103.5539	100' FSL, 700' FEL of Sec 10 in T23S, R33E
21583.11	11225.00	32.2974	-103.5540	20' FSL, 700' FEL of Sec 15 in T23S, R33E

	Y	X	MD
KOP	483340	782081	10757.74

NORTH THISTLE 10 STATE COM 218H



Well: NORTH THISTLE 10 STATE COM 218H  
 County: Lea  
 Wellbore: Permit Plan  
 Design: Permit Plan #1

Geodetic System: US State Plane 1983  
 Datum: North American Datum 1927  
 Ellipsoid: Clarke 1866  
 Zone: 3001 - NM East (NAD83)

MD	INC	AZI	TVD	NS	EW	VS	DLS	Comment
(ft)	(°)	(°)	(ft)	(ft)	(ft)	(ft)	(°/100ft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
100.00	0.00	65.57	100.00	0.00	0.00	0.00	0.00	
200.00	0.00	65.57	200.00	0.00	0.00	0.00	0.00	
300.00	0.00	65.57	300.00	0.00	0.00	0.00	0.00	
400.00	0.00	65.57	400.00	0.00	0.00	0.00	0.00	
500.00	0.00	65.57	500.00	0.00	0.00	0.00	0.00	
600.00	0.00	65.57	600.00	0.00	0.00	0.00	0.00	
700.00	0.00	65.57	700.00	0.00	0.00	0.00	0.00	
800.00	0.00	65.57	800.00	0.00	0.00	0.00	0.00	
900.00	0.00	65.57	900.00	0.00	0.00	0.00	0.00	
1000.00	0.00	65.57	1000.00	0.00	0.00	0.00	0.00	
1100.00	0.00	65.57	1100.00	0.00	0.00	0.00	0.00	
1137.00	0.00	65.57	1137.00	0.00	0.00	0.00	0.00	Rustler
1200.00	0.00	65.57	1200.00	0.00	0.00	0.00	0.00	
1300.00	0.00	65.57	1300.00	0.00	0.00	0.00	0.00	
1400.00	0.00	65.57	1400.00	0.00	0.00	0.00	0.00	
1500.00	0.00	65.57	1500.00	0.00	0.00	0.00	0.00	
1600.00	0.00	65.57	1600.00	0.00	0.00	0.00	0.00	
1620.00	0.00	65.57	1620.00	0.00	0.00	0.00	0.00	Salt, Base of Salt
1700.00	0.00	65.57	1700.00	0.00	0.00	0.00	0.00	
1800.00	0.00	65.57	1800.00	0.00	0.00	0.00	0.00	
1900.00	0.00	65.57	1900.00	0.00	0.00	0.00	0.00	
2000.00	0.00	65.57	2000.00	0.00	0.00	0.00	0.00	Start Tangent
2100.00	2.00	65.57	2099.98	0.72	1.59	-0.53	2.00	
2200.00	4.00	65.57	2199.84	2.89	6.35	-2.10	2.00	
2300.00	6.00	65.57	2299.45	6.49	14.29	-4.73	2.00	
2400.00	8.00	65.57	2398.70	11.53	25.38	-8.40	2.00	
2500.00	10.00	65.57	2497.47	18.00	39.63	-13.12	2.00	Hold Tangent
2600.00	10.00	65.57	2595.95	25.18	55.44	-18.35	0.00	
2700.00	10.00	65.57	2694.43	32.36	71.25	-23.59	0.00	
2800.00	10.00	65.57	2792.91	39.55	87.06	-28.82	0.00	
2900.00	10.00	65.57	2891.39	46.73	102.87	-34.05	0.00	
3000.00	10.00	65.57	2989.87	53.91	118.68	-39.29	0.00	
3100.00	10.00	65.57	3088.35	61.09	134.49	-44.52	0.00	
3200.00	10.00	65.57	3186.83	68.27	150.30	-49.76	0.00	
3300.00	10.00	65.57	3285.31	75.45	166.11	-54.99	0.00	
3400.00	10.00	65.57	3383.79	82.64	181.92	-60.22	0.00	
3500.00	10.00	65.57	3482.27	89.82	197.73	-65.46	0.00	
3600.00	10.00	65.57	3580.75	97.00	213.54	-70.69	0.00	
3700.00	10.00	65.57	3679.23	104.18	229.35	-75.93	0.00	
3800.00	10.00	65.57	3777.72	111.36	245.16	-81.16	0.00	
3900.00	10.00	65.57	3876.20	118.54	260.97	-86.39	0.00	
4000.00	10.00	65.57	3974.68	125.73	276.78	-91.63	0.00	
4100.00	10.00	65.57	4073.16	132.91	292.59	-96.86	0.00	
4200.00	10.00	65.57	4171.64	140.09	308.40	-102.10	0.00	
4300.00	10.00	65.57	4270.12	147.27	324.21	-107.33	0.00	
4400.00	10.00	65.57	4368.60	154.45	340.02	-112.56	0.00	
4500.00	10.00	65.57	4467.08	161.64	355.83	-117.80	0.00	
4600.00	10.00	65.57	4565.56	168.82	371.64	-123.03	0.00	
4700.00	10.00	65.57	4664.04	176.00	387.45	-128.27	0.00	
4800.00	10.00	65.57	4762.52	183.18	403.26	-133.50	0.00	
4900.00	10.00	65.57	4861.00	190.36	419.07	-138.73	0.00	
5000.00	10.00	65.57	4959.48	197.54	434.88	-143.97	0.00	
5100.00	10.00	65.57	5057.97	204.73	450.69	-149.20	0.00	
5148.78	10.00	65.57	5106.00	208.23	458.40	-151.75	0.00	Delaware
5200.00	10.00	65.57	5156.45	211.91	466.50	-154.44	0.00	
5300.00	10.00	65.57	5254.93	219.09	482.31	-159.67	0.00	
5400.00	10.00	65.57	5353.41	226.27	498.12	-164.90	0.00	
5500.00	10.00	65.57	5451.89	233.45	513.93	-170.14	0.00	
5600.00	10.00	65.57	5550.37	240.64	529.74	-175.37	0.00	
5700.00	10.00	65.57	5648.85	247.82	545.55	-180.61	0.00	
5800.00	10.00	65.57	5747.33	255.00	561.36	-185.84	0.00	
5900.00	10.00	65.57	5845.81	262.18	577.17	-191.07	0.00	
6000.00	10.00	65.57	5944.29	269.36	592.98	-196.31	0.00	
6100.00	10.00	65.57	6042.77	276.54	608.79	-201.54	0.00	
6119.52	10.00	65.57	6062.00	277.95	611.88	-202.56	0.00	Cherry Canyon
6200.00	10.00	65.57	6141.25	283.73	624.60	-206.78	0.00	
6300.00	10.00	65.57	6239.73	290.91	640.41	-212.01	0.00	
6400.00	10.00	65.57	6338.22	298.09	656.22	-217.24	0.00	
6500.00	10.00	65.57	6436.70	305.27	672.03	-222.48	0.00	

NORTH THISTLE 10 STATE COM 218H



**Well:** NORTH THISTLE 10 STATE COM 218H  
**County:** Lea  
**Wellbore:** Permit Plan  
**Design:** Permit Plan #1

**Geodetic System:** US State Plane 1983  
**Datum:** North American Datum 1927  
**Ellipsoid:** Clarke 1866  
**Zone:** 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
6600.00	10.00	65.57	6535.18	312.45	687.84	-227.71	0.00	
6700.00	10.00	65.57	6633.66	319.63	703.65	-232.95	0.00	
6800.00	10.00	65.57	6732.14	326.82	719.46	-238.18	0.00	
6900.00	10.00	65.57	6830.62	334.00	735.27	-243.41	0.00	
7000.00	10.00	65.57	6929.10	341.18	751.08	-248.65	0.00	
7100.00	10.00	65.57	7027.58	348.36	766.89	-253.88	0.00	
7200.00	10.00	65.57	7126.06	355.54	782.70	-259.12	0.00	
7300.00	10.00	65.57	7224.54	362.73	798.51	-264.35	0.00	
7337.02	10.00	65.57	7261.00	365.38	804.36	-266.29	0.00	Brushy Canyon
7400.00	10.00	65.57	7323.02	369.91	814.32	-269.58	0.00	
7500.00	10.00	65.57	7421.50	377.09	830.13	-274.82	0.00	
7600.00	10.00	65.57	7519.99	384.27	845.94	-280.05	0.00	
7700.00	10.00	65.57	7618.47	391.45	861.75	-285.29	0.00	
7800.00	10.00	65.57	7716.95	398.63	877.56	-290.52	0.00	
7900.00	10.00	65.57	7815.43	405.82	893.37	-295.75	0.00	
8000.00	10.00	65.57	7913.91	413.00	909.18	-300.99	0.00	
8100.00	10.00	65.57	8012.39	420.18	924.99	-306.22	0.00	
8200.00	10.00	65.57	8110.87	427.36	940.80	-311.46	0.00	
8300.00	10.00	65.57	8209.35	434.54	956.61	-316.69	0.00	
8400.00	10.00	65.57	8307.83	441.72	972.42	-321.92	0.00	
8500.00	10.00	65.57	8406.31	448.91	988.23	-327.16	0.00	
8600.00	10.00	65.57	8504.79	456.09	1004.04	-332.39	0.00	
8700.00	10.00	65.57	8603.27	463.27	1019.85	-337.63	0.00	
8800.00	10.00	65.57	8701.75	470.45	1035.66	-342.86	0.00	
8900.00	10.00	65.57	8800.24	477.63	1051.47	-348.09	0.00	
9000.00	10.00	65.57	8898.72	484.82	1067.28	-353.33	0.00	
9100.00	10.00	65.57	8997.20	492.00	1083.09	-358.56	0.00	
9104.88	10.00	65.57	9002.00	492.35	1083.86	-358.82	0.00	Bone Spring 1st
9123.62	10.00	65.57	9020.46	493.69	1086.83	-359.80	0.00	Drop to Vertical
9200.00	8.47	65.57	9095.85	498.76	1097.99	-363.49	2.00	
9300.00	6.47	65.57	9194.99	504.14	1109.83	-367.41	2.00	
9400.00	4.47	65.57	9294.53	508.09	1118.51	-370.29	2.00	
9500.00	2.47	65.57	9394.34	510.59	1124.02	-372.11	2.00	
9600.00	0.47	65.57	9494.30	511.65	1126.36	-372.89	2.00	
9623.62	0.00	65.57	9517.93	511.69	1126.45	-372.92	2.00	Hold Vertical
9700.00	0.00	179.56	9594.30	511.69	1126.45	-372.92	0.00	
9800.00	0.00	179.56	9694.30	511.69	1126.45	-372.92	0.00	
9900.00	0.00	179.56	9794.30	511.69	1126.45	-372.92	0.00	
10000.00	0.00	179.56	9894.30	511.69	1126.45	-372.92	0.00	
10100.00	0.00	179.56	9994.30	511.69	1126.45	-372.92	0.00	
10200.00	0.00	179.56	10094.30	511.69	1126.45	-372.92	0.00	
10300.00	0.00	179.56	10194.30	511.69	1126.45	-372.92	0.00	
10400.00	0.00	179.56	10294.30	511.69	1126.45	-372.92	0.00	
10500.00	0.00	179.56	10394.30	511.69	1126.45	-372.92	0.00	
10600.00	0.00	179.56	10494.30	511.69	1126.45	-372.92	0.00	
10700.00	0.00	179.56	10594.30	511.69	1126.45	-372.92	0.00	
10757.74	0.00	179.56	10652.04	511.69	1126.45	-372.92	0.00	KOP
10772.70	1.50	179.56	10667.00	511.50	1126.45	-372.72	10.00	Bone Spring 2nd / Point of Penetration
10800.00	4.23	179.56	10694.26	510.14	1126.46	-371.37	10.00	
10900.00	14.23	179.56	10792.85	494.12	1126.59	-355.46	10.00	
11000.00	24.23	179.56	10887.15	461.24	1126.84	-322.78	10.00	
11100.00	34.23	179.56	10974.31	412.47	1127.21	-274.32	10.00	
11200.00	44.23	179.56	11051.68	349.32	1127.69	-211.56	10.00	
11300.00	54.23	179.56	11116.90	273.69	1128.26	-136.41	10.00	
11400.00	64.23	179.56	11168.00	187.88	1128.92	-51.14	10.00	
11500.00	74.23	179.56	11203.42	94.50	1129.63	41.65	10.00	
11600.00	84.23	179.56	11222.09	-3.61	1130.37	139.14	10.00	
11657.74	90.00	179.56	11225.00	-61.25	1130.81	196.41	10.00	Landing Point
11700.00	90.00	179.56	11225.00	-103.51	1131.13	238.41	0.00	
11800.00	90.00	179.56	11225.00	-203.51	1131.89	337.77	0.00	
11900.00	90.00	179.56	11225.00	-303.50	1132.65	437.14	0.00	
12000.00	90.00	179.56	11225.00	-403.50	1133.41	536.51	0.00	
12100.00	90.00	179.56	11225.00	-503.50	1134.17	635.87	0.00	
12200.00	90.00	179.56	11225.00	-603.49	1134.93	735.24	0.00	
12300.00	90.00	179.56	11225.00	-703.49	1135.69	834.61	0.00	
12400.00	90.00	179.56	11225.00	-803.49	1136.45	933.97	0.00	
12500.00	90.00	179.56	11225.00	-903.49	1137.21	1033.34	0.00	
12600.00	90.00	179.56	11225.00	-1003.48	1137.97	1132.71	0.00	
12700.00	90.00	179.56	11225.00	-1103.48	1138.73	1232.07	0.00	
12800.00	90.00	179.56	11225.00	-1203.48	1139.49	1331.44	0.00	



NORTH THISTLE 10 STATE COM 218H



**Well:** NORTH THISTLE 10 STATE COM 218H  
**County:** Lea  
**Wellbore:** Permit Plan  
**Design:** Permit Plan #1

**Geodetic System:** US State Plane 1983  
**Datum:** North American Datum 1927  
**Ellipsoid:** Clarke 1866  
**Zone:** 3001 - NM East (NAD83)

MD	INC	AZI	TVD	NS	EW	VS	DLS	Comment
(ft)	(°)	(°)	(ft)	(ft)	(ft)	(ft)	(°/100ft)	
12900.00	90.00	179.56	11225.00	-1303.47	1140.26	1430.81	0.00	
13000.00	90.00	179.56	11225.00	-1403.47	1141.02	1530.17	0.00	
13100.00	90.00	179.56	11225.00	-1503.47	1141.78	1629.54	0.00	
13200.00	90.00	179.56	11225.00	-1603.47	1142.54	1728.91	0.00	
13300.00	90.00	179.56	11225.00	-1703.46	1143.30	1828.27	0.00	
13400.00	90.00	179.56	11225.00	-1803.46	1144.06	1927.64	0.00	
13500.00	90.00	179.56	11225.00	-1903.46	1144.82	2027.01	0.00	
13600.00	90.00	179.56	11225.00	-2003.45	1145.58	2126.37	0.00	
13700.00	90.00	179.56	11225.00	-2103.45	1146.34	2225.74	0.00	
13800.00	90.00	179.56	11225.00	-2203.45	1147.10	2325.11	0.00	
13900.00	90.00	179.56	11225.00	-2303.44	1147.86	2424.47	0.00	
14000.00	90.00	179.56	11225.00	-2403.44	1148.62	2523.84	0.00	
14100.00	90.00	179.56	11225.00	-2503.44	1149.38	2623.21	0.00	
14200.00	90.00	179.56	11225.00	-2603.44	1150.14	2722.57	0.00	
14300.00	90.00	179.56	11225.00	-2703.43	1150.90	2821.94	0.00	
14400.00	90.00	179.56	11225.00	-2803.43	1151.66	2921.31	0.00	
14500.00	90.00	179.56	11225.00	-2903.43	1152.42	3020.67	0.00	
14600.00	90.00	179.56	11225.00	-3003.42	1153.18	3120.04	0.00	
14700.00	90.00	179.56	11225.00	-3103.42	1153.94	3219.41	0.00	
14800.00	90.00	179.56	11225.00	-3203.42	1154.70	3318.77	0.00	
14900.00	90.00	179.56	11225.00	-3303.42	1155.46	3418.14	0.00	
15000.00	90.00	179.56	11225.00	-3403.41	1156.22	3517.51	0.00	
15100.00	90.00	179.56	11225.00	-3503.41	1156.99	3616.87	0.00	
15200.00	90.00	179.56	11225.00	-3603.41	1157.75	3716.24	0.00	
15300.00	90.00	179.56	11225.00	-3703.40	1158.51	3815.61	0.00	
15400.00	90.00	179.56	11225.00	-3803.40	1159.27	3914.97	0.00	
15500.00	90.00	179.56	11225.00	-3903.40	1160.03	4014.34	0.00	
15600.00	90.00	179.56	11225.00	-4003.40	1160.79	4113.71	0.00	
15700.00	90.00	179.56	11225.01	-4103.39	1161.55	4213.07	0.00	
15800.00	90.00	179.56	11225.01	-4203.39	1162.31	4312.44	0.00	
15900.00	90.00	179.56	11225.01	-4303.39	1163.07	4411.81	0.00	
16000.00	90.00	179.56	11225.01	-4403.38	1163.83	4511.17	0.00	
16100.00	90.00	179.56	11225.01	-4503.38	1164.59	4610.54	0.00	
16200.00	90.00	179.56	11225.01	-4603.38	1165.35	4709.91	0.00	exit
16300.00	90.00	179.56	11225.01	-4703.38	1166.11	4809.27	0.00	
16400.00	90.00	179.56	11225.01	-4803.37	1166.87	4908.64	0.00	
16500.00	90.00	179.56	11225.01	-4903.37	1167.63	5008.01	0.00	
16600.00	90.00	179.56	11225.01	-5003.37	1168.39	5107.37	0.00	
16700.00	90.00	179.56	11225.01	-5103.36	1169.15	5206.74	0.00	
16800.00	90.00	179.56	11225.01	-5203.36	1169.91	5306.11	0.00	
16900.00	90.00	179.56	11225.01	-5303.36	1170.67	5405.47	0.00	
17000.00	90.00	179.56	11225.01	-5403.36	1171.43	5504.84	0.00	
17100.00	90.00	179.56	11225.01	-5503.35	1172.19	5604.21	0.00	
17200.00	90.00	179.56	11225.01	-5603.35	1172.95	5703.57	0.00	
17300.00	90.00	179.56	11225.01	-5703.35	1173.72	5802.94	0.00	
17400.00	90.00	179.56	11225.01	-5803.34	1174.48	5902.31	0.00	
17500.00	90.00	179.56	11225.01	-5903.34	1175.24	6001.67	0.00	
17600.00	90.00	179.56	11225.01	-6003.34	1176.00	6101.04	0.00	
17700.00	90.00	179.56	11225.01	-6103.34	1176.76	6200.41	0.00	
17800.00	90.00	179.56	11225.01	-6203.33	1177.52	6299.77	0.00	
17900.00	90.00	179.56	11225.01	-6303.33	1178.28	6399.14	0.00	
18000.00	90.00	179.56	11225.01	-6403.33	1179.04	6498.51	0.00	
18100.00	90.00	179.56	11225.01	-6503.32	1179.80	6597.87	0.00	
18200.00	90.00	179.56	11225.01	-6603.32	1180.56	6697.24	0.00	
18300.00	90.00	179.56	11225.01	-6703.32	1181.32	6796.61	0.00	
18400.00	90.00	179.56	11225.01	-6803.31	1182.08	6895.97	0.00	
18500.00	90.00	179.56	11225.01	-6903.31	1182.84	6995.34	0.00	
18600.00	90.00	179.56	11225.01	-7003.31	1183.60	7094.71	0.00	
18700.00	90.00	179.56	11225.01	-7103.31	1184.36	7194.07	0.00	
18800.00	90.00	179.56	11225.01	-7203.30	1185.12	7293.44	0.00	
18900.00	90.00	179.56	11225.01	-7303.30	1185.88	7392.81	0.00	
19000.00	90.00	179.56	11225.01	-7403.30	1186.64	7492.17	0.00	
19100.00	90.00	179.56	11225.01	-7503.29	1187.40	7591.54	0.00	
19200.00	90.00	179.56	11225.01	-7603.29	1188.16	7690.91	0.00	
19300.00	90.00	179.56	11225.01	-7703.29	1188.92	7790.27	0.00	
19400.00	90.00	179.56	11225.01	-7803.29	1189.68	7889.64	0.00	
19500.00	90.00	179.56	11225.01	-7903.28	1190.45	7989.01	0.00	
19600.00	90.00	179.56	11225.01	-8003.28	1191.21	8088.37	0.00	
19700.00	90.00	179.56	11225.01	-8103.28	1191.97	8187.74	0.00	
19800.00	90.00	179.56	11225.01	-8203.27	1192.73	8287.11	0.00	

NORTH THISTLE 10 STATE COM 218H



**Well:** NORTH THISTLE 10 STATE COM 218H  
**County:** Lea  
**Wellbore:** Permit Plan  
**Design:** Permit Plan #1

**Geodetic System:** US State Plane 1983  
**Datum:** North American Datum 1927  
**Ellipsoid:** Clarke 1866  
**Zone:** 3001 - NM East (NAD83)

MD	INC	AZI	TVD	NS	EW	VS	DLS	Comment
(ft)	(°)	(°)	(ft)	(ft)	(ft)	(ft)	(°/100ft)	
19900.00	90.00	179.56	11225.01	-8303.27	1193.49	8386.47	0.00	
20000.00	90.00	179.56	11225.01	-8403.27	1194.25	8485.84	0.00	
20100.00	90.00	179.56	11225.01	-8503.27	1195.01	8585.21	0.00	
20200.00	90.00	179.56	11225.01	-8603.26	1195.77	8684.57	0.00	
20300.00	90.00	179.56	11225.01	-8703.26	1196.53	8783.94	0.00	
20400.00	90.00	179.56	11225.01	-8803.26	1197.29	8883.31	0.00	
20500.00	90.00	179.56	11225.01	-8903.25	1198.05	8982.67	0.00	
20600.00	90.00	179.56	11225.01	-9003.25	1198.81	9082.04	0.00	
20700.00	90.00	179.56	11225.01	-9103.25	1199.57	9181.41	0.00	
20800.00	90.00	179.56	11225.01	-9203.25	1200.33	9280.77	0.00	
20900.00	90.00	179.56	11225.01	-9303.24	1201.09	9380.14	0.00	
21000.00	90.00	179.56	11225.01	-9403.24	1201.85	9479.51	0.00	
21100.00	90.00	179.56	11225.01	-9503.24	1202.61	9578.87	0.00	
21200.00	90.00	179.56	11225.01	-9603.23	1203.37	9678.24	0.00	
21300.00	90.00	179.56	11225.01	-9703.23	1204.13	9777.61	0.00	
21400.00	90.00	179.56	11225.01	-9803.23	1204.89	9876.97	0.00	
21500.00	90.00	179.56	11225.01	-9903.23	1205.65	9976.34	0.00	
21503.11	90.00	179.56	11225.01	-9906.33	1205.68	9979.43	0.00	
21583.11	90.00	179.56	11225.00	-9986.33	1206.26	10058.92	0.00	BHL



**Devon Energy**  
333 West Sheridan Avenue  
Oklahoma City, Oklahoma 73102-5015

# **Hydrogen Sulfide (H<sub>2</sub>S) Contingency Plan**

**For**



**North Thistle 10 State Com 218H**

**Sec-10, T-23S, R-33E  
550' FNL & 1830' FEL  
LAT. = 32.324983° N (NAD83)  
LONG = 103.557609° W**

**Lea County, NM**

## North Thistle 10 State Com 218H

This is an open drilling site. H<sub>2</sub>S monitoring equipment and emergency response equipment will be used within 500' of zones known to contain H<sub>2</sub>S, including warning signs, wind indicators and H<sub>2</sub>S monitors.



Assumed 100 ppm ROE = 3000' (Radius of Exposure)  
100 ppm H<sub>2</sub>S concentration shall trigger activation of this plan.

### Escape

Crews shall escape upwind of escaping gas in the event of an emergency release of gas. Escape can be facilitated from the location entrance road. Crews should then block the entrance to the location from the lease road so as not to allow anyone traversing into a hazardous area. The blockade should be at a safe distance outside of the ROE. There are no homes or buildings in or near the ROE.

**Assumed 100 ppm ROE = 3000'**

**100 ppm H<sub>2</sub>S concentration shall trigger activation of this plan.**

### Emergency Procedures

In the event of a release of gas containing H<sub>2</sub>S, the first responder(s) must

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H<sub>2</sub>S monitors and air packs in order to control the release.
- Use the "buddy system" to ensure no injuries occur during the response
- Take precautions to avoid personal injury during this operation.
- Contact operator and/or local officials to aid in operation. See list of phone numbers attached.
- Have received training in the
  - Detection of H<sub>2</sub>S, and
  - Measures for protection against the gas, and
  - Equipment used for protection and emergency response.

### **Ignition of Gas Source**

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO<sub>2</sub>). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Highway Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas

### **Characteristics of H<sub>2</sub>S and SO<sub>2</sub>**

<b>Common Name</b>	<b>Chemical Formula</b>	<b>Specific Gravity</b>	<b>Threshold Limit</b>	<b>Hazardous Limit</b>	<b>Lethal Concentration</b>
<b>Hydrogen Sulfide</b>	<b>H<sub>2</sub>S</b>	<b>1.189 Air = 1</b>	<b>10 ppm</b>	<b>100 ppm/hr</b>	<b>600 ppm</b>
<b>Sulfur Dioxide</b>	<b>SO<sub>2</sub></b>	<b>2.21 Air = 1</b>	<b>2 ppm</b>	<b>N/A</b>	<b>1000 ppm</b>

### **Contacting Authorities**

Devon Energy Corp. personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. Devon Energy Corp. Company response must be in coordination with the State of New Mexico's 'Hazardous Materials Emergency Response Plan' (HMER)

## Hydrogen Sulfide Drilling Operation Plan

### I. HYDROGEN SULFIDE (H<sub>2</sub>S) TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards and characteristics of hydrogen sulfide (H<sub>2</sub>S)
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H<sub>2</sub>S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H<sub>2</sub>S metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H<sub>2</sub>S Drilling Operations Plan.

**There will be weekly H<sub>2</sub>S and well control drills for all personnel in each crew.**

### II. HYDROGEN SULFIDE TRAINING

Note: All H<sub>2</sub>S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H<sub>2</sub>S.

#### 1. Well Control Equipment

- A. Flare line
- B. Choke manifold – Remotely Operated
- C. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment may include if applicable: annular preventer and rotating head.

E. Mud/Gas Separator

**2. Protective equipment for essential personnel:**

30-minute SCBA units located at briefing areas, as indicated on well site diagram, with escape units available in the top doghouse. As it may be difficult to communicate audibly while wearing these units, hand signals shall be utilized.

Fire extinguishers are located at various locations around the rig. First Aid supplies are located in the top doghouse and the rig manager's office.

**3. H<sub>2</sub>S detection and monitoring equipment:**

Portable H<sub>2</sub>S monitors positioned on location for best coverage and response. These units have warning lights which activate when H<sub>2</sub>S levels reach 10 ppm and audible sirens which activate at 10 ppm.

Sensor locations:

- Bell nipple
- Possum Belly/Shale shaker
- Rig floor
- Choke manifold
- Cellar

**Visual warning systems:**

- A. Wind direction indicators as shown on well site diagram
- B. Caution/ Danger signs shall be posted on roads providing direct access to locations. Signs will be painted a high visibility yellow with black lettering of sufficient size to be reasonable distance from the immediate location. Bilingual signs will be used when appropriate.

**4. Mud program:**

The mud program has been designed to minimize the volume of H<sub>2</sub>S circulated to surface. Proper mud weight, safe drilling practices and the use of H<sub>2</sub>S scavengers will minimize hazards when penetrating H<sub>2</sub>S bearing zones.



**5. Metallurgy:**

- A. All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold lines, and valves shall be H<sub>2</sub>S trim.
- B. All elastomers used for packing and seals shall be H<sub>2</sub>S trim.

**6. Communication:**

- A. Company personnel have/use cellular telephones in the field.
- B. Land line (telephone) communications at Office

**7. Well testing:**


- A. Drill stem testing will be performed with a minimum number of personnel in the immediate vicinity, which are necessary to safety and adequately conduct the test. The drill stem testing will be conducted during daylight hours and formation fluids will not be flowed to the surface. All drill-stem-testing operations conducted in an H<sub>2</sub>S environment will use the closed chamber method of testing.
- B. There will be no drill stem testing.

<b><u>Devon Energy Corp. Company Call List</u></b>			
<b>Employee/Company Contact Representative</b>	<b>Position</b>	<b>Phone Number</b>	<b>After Hours Number</b>
Jonathan Fisher (North)	Drilling Manager	832-967-7912	
Jason Hildebrand (South)	Drilling Manager	405-552-6514	
Rich Downey	Drilling VP	405-228-2415	
Josh Harvey	EHS Manager	405-228-2440	918-500-5536
Laura Wright	EHS Supervisor	405-552-5334	832-969-8145
Robert Glover	EHS Professional	575-703-5712	575-703-5712
Lane Frank	Lead EHS	580-579-7052	580-579-7052
Rickey Porter	Lead EHS	903-720-8315	903-720-8315
Ronnie Handy	Lead EHS	918-839-2046	918-839-2046
Brock Vise	Lead EHS	918-413-3291	918-413-3291



<b>Agency Call List</b>		
<b><u>Lea County (575)</u></b>	<b>Hobbs</b>	
	Lea County Communication Authority	397-9265
	State Police	885-3138
	City Police	397-9265
	Sheriff's Office	396-3611
	<b>Ambulance</b>	<b>911</b>
	Fire Department	397-9308
	LEPC (Local Emergency Planning Committee)	393-2870
	NMOCD	393-6161
	US Bureau of Land Management (Closed)	393-0002
<b><u>Eddy County (575)</u></b>	<b>Carlsbad</b>	
	State Police	885-3137
	City Police	885-2111
	Sheriff's Office	887-7551
	<b>Ambulance</b>	<b>911</b>
	Fire Department	885-3125
	LEPC (Local Emergency Planning Committee)	887-3798
	US Bureau of Land Management	234-5972
	NM Emergency Response Commission (Santa Fe)	(505) 476-9600
	24 HR	(505) 827-9126
	National Emergency Response Center	(800) 424-8802
	National Pollution Control Center: Direct	(703) 872-6000
	For Oil Spills	(800) 280-7118
	<b>Emergency Services</b>	
	Wild Well Control	(281) 784-4700
	Cudd Pressure Control	(915) 699-0139 (915) 563-3356
	Halliburton	(575) 746-2757
	B. J. Services	(575) 746-3569
	Native Air – Emergency Helicopter – Hobbs	(575) 347-9836
	For Air Ambulance - <b>Eddy County</b> Dispatch	(575)-616-7155
<b><u>Give GPS position:</u></b>	For Air Ambulance - <b>Lea County</b> (LCCA)	(575)-397-9265
	Poison Control (24/7)	(800) 222-1222
	Oil & Gas Pipeline 24 Hour Service	(800) 364-4366
	NOAA – Website - <a href="http://www.nhc.noaa.gov">www.nhc.noaa.gov</a>	
	National Pollution Control Center	202-795-6958
	NPCC – Oil Spills	800-280-7118

# Devon Energy - Well Pad Rig Location Layout Safety Equipment Location



## NORTH THISTLE 10 STATE COM 218H

**1. Geologic Formations**

TVD of target	11225	Pilot hole depth	N/A
MD at TD:	21583	Deepest expected fresh water	

**Basin**

Formation	Depth (TVD) from KB	Water/Mineral Bearing/Target Zone?	Hazards*
Rustler	1137		
Salt	1620		
Base of Salt	1620		
Delaware	5106		
Cherry Canyon	6062		
Brushy Canyon	7261		
Bone Spring 1st	9002		
Bone Spring 2nd	10667		

\*H2S, water flows, loss of circulation, abnormal pressures, etc.

## NORTH THISTLE 10 STATE COM 218H

**2. Casing Program**

Hole Size	Csg. Size	Wt (PPF)	Grade	Conn	Casing Interval		Casing Interval	
					From (MD)	To (MD)	From (TVD)	To (TVD)
17 1/2	13 3/8	54 1/2	J-55	BTC	0	1162	0	1162
12 1/4	9 5/8	40	J-55	BTC	0	5206	0	5206
8 3/4	5 1/2	20	P110	DWC / C-IS+	0	21583	0	11225

•All casing strings will be tested in accordance with 43 CFR 3172. Must have table for contingency casing.

**3. Cementing Program (3-String Primary Design)**

Casing	# Sks	TOC	Wt. (lb/gal)	Yld (ft3/sack)	Slurry Description
Surface	879	Surf	13.2	1.4	Lead: Class C Cement + additives
Int 1	570	Surf	9.0	3.3	Lead: Class C Cement + additives
	154	4706	13.2	1.4	Tail: Class H / C + additives
Int 1 Intermediate Squeeze	741	Surf	9.0	3.3	Squeeze Lead: Class C Cement + additives
	570	Surf	9.0	3.3	Lead: Class C Cement + additives
	154	4706	13.2	1.4	Tail: Class H / C + additives
Production	516	4706	9.0	3.3	Lead: Class H / C + additives
	2089	10758	13.2	1.4	Tail: Class H / C + additives

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Casing String	% Excess
Surface	50%
Intermediate	30%
Production	10%

Devon Energy requests to offline cement on intermediate strings that are set in formations shallower than the Wolfcamp. Prior to commencing offline cementing operations, the well will be monitored for any abnormal pressures and confirmed to be static. A dual manifold system (equipped with chokes) for the returns will also be utilized as a redundancy. All equipment used for offline cementing will have a minimum 5M rating to match intermediate sections' 5M BOPE requirements.

## NORTH THISTLE 10 STATE COM 218H

**4. Pressure Control Equipment (Three String Design)**

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
Int 1	13-5/8"	5M	Annular	X	50% of rated working pressure
			Blind Ram	X	5M
			Pipe Ram		
			Double Ram	X	
			Other*		
Production	13-5/8"	5M	Annular	X	50% of rated working pressure
			Blind Ram	X	5M
			Pipe Ram		
			Double Ram	X	
			Other*		
			Annular (5M)		
			Blind Ram		
			Pipe Ram		
			Double Ram		
			Other*		

## NORTH THISTLE 10 STATE COM 218H

**5. Mud Program (Three String Design)**

Section	Type	Weight (ppg)
Surface	FW Gel	8.5-9
Intermediate	Brine	10-10.5
Production	WBM	8.5-9

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

**6. Logging and Testing Procedures**

Logging, Coring and Testing	
X	Will run GR/CNL from TD to surface (horizontal well - vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain.
	Coring? If yes, explain.

Additional logs planned		Interval
	Resistivity	
	Density	
X	CBL	Production casing
	Mud log	KOP to TD
	PEX	

**7. Drilling Conditions**

Condition	Specify what type and where?
BH pressure at deepest TVD	5253
Abnormal temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogen Sulfide (H<sub>2</sub>S) monitors will be installed prior to drilling out the surface shoe. If H<sub>2</sub>S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of 43 CFR 3176. If Hydrogen Sulfide is encountered measured values and formations will be provided to the BLM.

N	H <sub>2</sub> S is present
Y	H <sub>2</sub> S plan attached.

## NORTH THISTLE 10 STATE COM 218H

**8. Other facets of operation**

Is this a walking operation? Potentially

- 1 If operator elects, drilling rig will batch drill the surface holes and run/cement surface casing; walking the rig to next wells on the pad.
- 2 The drilling rig will then batch drill the intermediate sections and run/cement intermediate casing; the wellbore will be isolated with a blind flange and pressure gauge installed for monitoring the well before walking to the next well.
- 3 The drilling rig will then batch drill the production hole sections on the wells with OBM, run/cement production casing, and install TA caps or tubing heads for completions.

NOTE: During batch operations the drilling rig will be moved from well to well however, it will not be removed from the pad until all wells have production casing run/cemented.

Will be pre-setting casing? Potentially

- 1 Spudder rig will move in and batch drill surface hole.
  - a. Rig will utilize fresh water based mud to drill surface hole to TD. Solids control will be handled entirely on a closed loop basis.
- 2 After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (43 CFR 3172, all COAs and NMOCD regulations).
- 3 The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
- 4 A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with a pressure gauge installed on the wellhead.
- 5 Spudder rig operations is expected to take 4-5 days per well on a multi-well pad.
- 6 The NMOCD will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 7 Drilling operations will be performed with drilling rig. At that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
  - a. The NMOCD will be contacted / notified 24 hours before the drilling rig moves back on to the pad with the pre-set surface casing.

Attachments

X Directional Plan  
           Other, describe

C-102  Submit Electronically Via OCD Permitting	State of New Mexico Energy, Minerals & Natural Resources Department <b>OIL CONSERVATION DIVISION</b>		Revised July, 2024	
			Submittal Type:	<input checked="" type="checkbox"/> Initial Submittal
				<input type="checkbox"/> Amended Report
		<input type="checkbox"/> As Drilled		

## WELL LOCATION INFORMATION

API Number	Pool Code 7320	Pool Name BRINNINSTOOL;BONE SPRING
Property Code	Property Name NORTH THISTLE 10 STATE COM	Well Number 218H
OGRID No. 6137	Operator Name DEVON ENERGY PRODUCTION COMPANY, L.P.	Ground Level Elevation 3600.8'
Surface Owner: <input checked="" type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input type="checkbox"/> Federal		Mineral Owner: <input checked="" type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input type="checkbox"/> Federal

## Surface Location

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
B	10	23-S	33-E		550' N	1830' E	32.324983	103.557609	LEA

## Bottom Hole Location

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
P	15	23-S	33-E		20' S	700' E	32.297511	103.553939	LEA

Dedicated Acres 160	Infill or Defining Well <input type="checkbox"/>	Defining Well API <input checked="" type="checkbox"/>	Overlapping Spacing Unit (Y/N) Y	Consolidation Code C
Order Numbers			Well setbacks are under Common Ownership: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

## Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
A	10	23-S	33-E		50' N	700' E	32.326364	103.553950	LEA



## First Take Point (FTP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
A	10	23-S	33-E		100' N	700' E	32.326227	103.553950	LEA

## Last Take Point (LTP)

UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	Longitude	County
P	10	23-S	33-E		100' S	700' E	32.312255	103.553946	LEA

Spacing Unit Type		Horizontal	Vertical	Ground Floor Elevation:
		<input checked="" type="checkbox"/>	<input type="checkbox"/>	

<b>OPERATOR CERTIFICATIONS</b> I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and, if the well is a vertical or directional well, that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of a working interest or unleased mineral interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.  If this well is a horizontal well, I further certify that this organization has received the consent of at least one lessee or owner of a working interest or unleased mineral interest in each tract (in the target pool or formation) in which any part of the well's completed interval will be located or obtained a compulsory pooling order from the division.		<b>SURVEYOR CERTIFICATIONS</b> I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under supervision, and that the same is true and correct to the best of my belief.	
Signature 		Signature and Seal of Professional Surveyor 	
Date 5/22/2025			
Printed Name Rebecca Deal, Regulatory Analyst		Certificate Number 23261	
Email Address rebecca.deal@dvn.com		Date of Survey 04/2025	




## ACREAGE DEDICATION PLATS

This grid represents a standard section. You may superimpose a non-standard section, or larger area, over this grid. Operators must outline the dedicated acreage in a red box, clearly show the well surface location and bottom hole location, if it is directionally drilled, with the dimensions from the section lines in the cardinal directions. If this is a horizontal wellbore show on this plat the location of the First Take Point and Last Take Point, and the point within the Completed interval (other than the First Take Point or Last Take Point) that is closest to any outer boundary of the tract.

Surveyors shall use the latest United States government survey or dependent resurvey. Well locations will be in reference to the New Mexico Principal Meridian. If the land is not surveyed contact the OCD Engineering Bureau. Independent subdivision surveys will not be acceptable.

<b>NORTH THISTLE 10 STATE CDM 218H</b> GEOIDETIC COORDINATES NAD 83 NMSP EAST SURFACE LOCATION 550' FNL 1830' FEL SECTION 10 EL: 3600.8' N:482828.57/E:780954.05 LAT:32.324983/LDN:103.557609
<b>KICK OFF POINT</b> 50' FNL 700' FEL SECTION 10 N:483339.02/E:782080.52 LAT:32.326364/LDN:103.553950
<b>FIRST TAKE POINT</b> 100' FNL 700' FEL SECTION 10 N:483289.02/E:782080.92 LAT:32.326227/LDN:103.553950
<b>LAST TAKE POINT</b> 100' FSL 700' FEL SECTION 10 N:478206.23/E:782119.24 LAT:32.312255/LDN:103.553946
<b>BOTTOM HOLE LOCATION</b> 20' FSL 700' FEL SECTION 15 N:472842.24/E:782160.31 LAT:32.297511/LDN:103.553939



A = N:483357.66 E:777494.32
B = N:483371.16 E:780150.63
C = N:483395.50 E:782780.10
D = N:480752.40 E:782801.00
E = N:478110.23 E:782819.94
F = N:475468.20 E:782840.20
G = N:472826.18 E:782860.45
H = N:472811.30 E:780219.55
I = N:472796.69 E:777577.35
J = N:475436.03 E:777556.56
K = N:478077.69 E:777535.68
L = N:478095.15 E:780174.27