Sante Fe Main Office Phone: (505) 476-3441			Stat	e of N	ew M	exico						Αι	Form C-103 ugust 1, 2011	
General Information	Energy, Minerals and Natural Resources									Permit 341588				
Phone: (505) 629-6116		.				Divisio			W	ELL API I	NUMBER 30-025-511	100		
Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us		•					<i>)</i> 1		5.		Type of Leas			
			1220	S. St	Franc	cis Dr.			0		State & Gas Leas	- NI-		
			San	ta Fe,	NM 8	7505			0.	State Oil	& Gas Leas	e No.		
(DO NOT USE THIS FORM FOR PROPOSALS I (FORM C-101) FOR SUCH PROPOSALS.)	SUNDRY NO					VOIR. USE "/	APPLICATIO	N FOR PER			ame or Unit A			
1. Type of Well: Oil									8.	. Well Nun	nber 061H			
Name of Operator Spur Energy Partners LLC									9.	OGRID N	lumber 328947			
3. Address of Operator 9655 Katy Freeway, Suite 500, H	ouston, TX 7702	24							10	0. Pool na	me or Wildo	at		
 -	om the N 17S Range	33E	NMPM	Cou	from the <u>I</u> nty <u>Lea</u>	<u> </u>	line							
	11. Elevation (Sho		, KB, B1, GR	, etc.)										
Pit or Below-grade Tank Application or Closur	е													
Pit Type Depth to Groundwater	Distance from r			Distance	from neare	st surface wat	er							
	v-Grade Tank: Voli		bbls; C	Construction N	Material		_							
12. Check Appropriate Box to Indicate Nature o NOTICE PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING Other:			☐ COMMENCE DRILLING OPNS.				JENT REPO	ALTER CASING PLUG AND ABANDON						
13. Describe proposed or completed operations Attach wellbore diagram of proposed completion 04/12/2023 Spud well. Drill 17-1/2" hole to 1476 class C w/ additives 14.8ppg 1.33 yield. Full retu	or recompletion. . 04/15/2023 RIH 8	& set 13-3/8" 54	1.5# J-55 BT0	C csg @ 1476	6', pump 40l	obl FWS, then	n cmt w/ 935	sxs class C	w/ additive	es 12.4ppg	g 1.77 yield f	followed by	•	
Date String Fluid	Hole	Csg	Weight	Grade	Est	Dpth	Sacks	Yield	Class	1"	Pres	Pres	Open	
Туре	Size	Size	lb/ft	1.55	TOC	Set	4000	4 77	0	Dpth	Held	Drop	Hole	
04/15/23 Surf FreshWater 05/22/23 Int1 FreshWater	17.5 12.25	13.375 9.625	54.5 36	J-55 J-55	0 0	1476 3207	1280 1035	1.77 1.68	C C	0 0	2055 2816	0 0	N N	
06/05/23 Prod Brine	8.75	7	32	L-80	0	6914	2525	2.4	C	0	7272	0	N	
06/05/23	8.75	5.5	20	L-80	0	14777	2525	2.4	С	0	7352	0	N	
I hereby certify that the information above is to NMOCD guidelines □, a general permit □ or					further certi	fy that any pit	or below-gra	ade tank ha	s been/will	be constr	ucted or clos	sed accord	ing to	
SIGNATURE Electronically	ATURE <u>Electronically Signed</u> TIT			Regulator	Regulatory Director DATE					11/7/2				
Type or print name Sarah Chapn	nan	E-mail add	dress	schapmaı	n@spuren	ergy.com		Telepho	one No.	83:	2-930-861	3	-	
For State Use Only:														
APPROVED BY: Keith Dziokor	nski	TITLE		Petroleum	n Specialis	st A		DATE		<u>7/1</u>	7/2025 8:1	6:08 AM		

Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

COMMENTS

Action 341588

COMMENTS

Operator:	OGRID:
Spur Energy Partners LLC	328947
9655 Katy Freeway	Action Number:
Houston, TX 77024	341588
	Action Type:
	[C-103] EP Drilling / Cement

Comments

Created By	Comment	Comment Date
schapman01	05/21/2023 NU BOP, test to 250# low 2500# high, good test. Test 13-3/8" csg to 1500# for 30 minutes, good test. Drill 12-1/4" hole to 3207'. 05/22/2023 RIH & set 9-5/8" 36# J-55 BTC csg @ 3207', pump 40bbl FWS, then cmt w/ 720 sxs class C w/ additives 12.8ppg 1.68 yield followed by 315 sxs class C w/ additives 14.8ppg 1.39 yield. Full returns throughout job, circ 117 sxs to surface. Test 9-5/8" csg top 1500# for 30min, good test. Drill 8-3/4" hole to 6579'V/14777'M – TD reached on 06/05/2023. RIH & set 7" 32# L-80 BK-HT csg @ 6914' then crossover and set 5-1/2" 20# L-80 BK-HT csg @ 14777', pump 40bbl FWS, then cmt w/ 580 sxs class C w/ additives 11.4ppg 2.40 yield followed by tail job w/ 1945 sxs class C w/ additives 13.2ppg and 1.4 yield. Full returns throughout job, circ 288 sxs cmt to surface. Pressure test csg to 1500# for 30 minutes, good test. 06/07/2023 RD and rig release.	