U.S. Department of the Interior BUREAU OF LAND MANAGEMENT		Sundry Print Report 06/23/2025
Well Name: PATTON 18 FEDERAL	Well Location: T24S / R31E / SEC 18 / SWSE / 32.2104745 / -103.8138844	County or Parish/State: EDDY / NM
Well Number: 8H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM89819	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001541343	Operator: OXY USA INCORPORATED	

Notice of Intent

Sundry ID: 2853991

Type of Submission: Notice of Intent

Date Sundry Submitted: 05/21/2025

Date proposed operation will begin: 06/21/2025

Type of Action: Plug and Abandonment

Time Sundry Submitted: 06:33

Procedure Description: OXY PROPOSES TO PA THE SUBJECT WELL. THE CURRENT WELLBORE, PROPOSED WELLBORE, AND PA PROCEDURE ARE ATTACHED. A PREP RIG MIGHT BE USED TO PULL EQUIPMENT BEFORE SETTING PLUGS FOR PA OPERATIONS. SEE ATTACHED PA PREP RIG PROCEDURE.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

PATTON_18_FEDERAL_008H_PA_NOI_SUB_5.21.2025_20250521063335.pdf

Received by OCD: 6/23/2025 11:36:13 AM Well Name: PATTON 18 FEDERAL	Well Location: T24S / R31E / SEC 18 / SWSE / 32.2104745 / -103.8138844	County or Parish/State: EDDY 7 of 2 NM
Well Number: 8H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM89819	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001541343	Operator: OXY USA INCORPORATED	
)

Conditions of Approval

Specialist Review

Patton_18_Federal_8H_Sundry_ID_2853991_P_A_20250623082727.pdf

State: TX

State:

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: STEPHEN JANACEK

Name: OXY USA INCORPORATED

Title: Regulatory Engineer

Street Address: 5 Greenway Plaza, Suite 110

City: Houston

Phone: (713) 497-2417

Email address: stephen_janacek@oxy.com

Field

Representative Name: Street Address: City: Phone: Email address:

BLM Point of Contact

BLM POC Name: LONG VO BLM POC Phone: 5759885402 Disposition: Approved Signature: Long Vo Signed on: MAY 21, 2025 06:33 AM

BLM POC Title: Petroleum Engineer BLM POC Email Address: LVO@BLM.GOV Disposition Date: 06/23/2025

Zip:

Received by OCD: 6/23/2025 11:36:13 AM

ecciveu by OCD. 0/25/2025 11.50.15 AM				I uge 5 0j		
Form 3160-5 UNITED STATES (June 2019) DEPARTMENT OF THE INTERIOR			FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2021 5. Lease Serial No.			
	BUR	EAU OF LAND MAN	AGEMENT	5. Lease Serial No.		
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name		
	UBMIT IN T	TRIPLICATE - Other instr	uctions on page 2	7. If Unit of CA/Agreement, Na	ame and/or No.	
1. Type of Well Oil Well	Gas W	/ell Other		8. Well Name and No.		
2. Name of Operator				9. API Well No.		
3a. Address			3b. Phone No. <i>(include area code)</i>	10. Field and Pool or Explorate	ory Area	
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)			11. Country or Parish, State			
	12. CHE	CK THE APPROPRIATE B	OX(ES) TO INDICATE NATURE (OF NOTICE, REPORT OR OTH	ER DATA	
TYPE OF SUBMISS	SION		TYPI	E OF ACTION		
Notice of Intent		Acidize	Deepen [Hydraulic Fracturing	Production (Start/Resume) Reclamation	Water Shut-Off Well Integrity	
Subsequent Report		Casing Repair Change Plans	New Construction	Recomplete Temporarily Abandon	Other	
Final Abandonment	Notice	Convert to Injection	Plug Back	Water Disposal		
the proposal is to deepe the Bond under which the completion of the invol-	n directiona he work wil ved operatio lonment No	Ily or recomplete horizontal l be perfonned or provide th ons. If the operation results in	ly, give subsurface locations and me e Bond No. on file with BLM/BIA. 1 n a multiple completion or recomple	asured and true vertical depths of Required subsequent reports mus stion in a new interval, a Form 31	k and approximate duration thereof. If f all pertinent markers and zones. Attach t be filed within 30 days following 60-4 must be filed once testing has been le operator has detennined that the site	

14. I hereby certify that the foregoing is true and correct. Name (<i>Printed/Typed</i>)		
1	Title	
Signature	Date	
THE SPACE FOR FEDE	RAL OR STATE OF	FICE USE
Approved by		
	Title	Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant of certify that the applicant holds legal or equitable title to those rights in the subject leas which would entitle the applicant to conduct operations thereon.		
Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any any false, fictitious or fraudulent statements or representations as to any matter within		illfully to make to any department or agency of the United Stat

(Instructions on page 2)

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

0. SHL: SWSE / 150 FSL / 1700 FEL / TWSP: 24S / RANGE: 31E / SECTION: 18 / LAT: 32.2104745 / LONG: -103.8138844 (TVD: 0 feet, MD: 0 feet) BHL: NWNE / 336 FNL / 1714 FEL / TWSP: 24S / RANGE: 31E / SECTION: 18 / LAT: 0.0 / LONG: 0.0 (TVD: 0 feet, MD: 0 feet) OXY USA INC.

PATTON 18 FEDERAL 008H

30-015-41343

NOI TO PERMANENTLY ABANDON THIS WELL VIA CEMENT PLUGGING.

PROPOSED PLUGGING PROCEDURE


- 1. POOH WITH CURRENT 2-7/8" TBG AND BHA
 - a. HEAL SYSTEM STUCK IN HOLE AND PUSHED DOWN TO 8405'. UNABLE TO RETRIEVE.
- 2. SET CIBP AT 8355' VIA WORKSTRING. LEAK TEST TO 500 PSI FOR 30 MINUTES
- 3. SPOT 215 SX CMT (118 SX CL C FOLLOWED BY 97 SX CL H) FROM 8355' TO 6455'. WOC AND TAG
- 4. SPOT 301 SX CL C CMT FROM 5255' TO 2600'. WOC AND TAG
- 5. SPOT 283 SX CL C CMT FROM 2500' TO SURFACE
- 6. VERIFY CMT TO SURFACE

FORMATION TOPS

	Тор
Name	Meas. Depth
Rustler	602
Top salt	930'
Buse Satt	2530'
Delaware	42651
Bell Camon	4285'
Chenny Campon	5205
Brushy Carolon	6505
Bone Spring	8105
1ST Bove Spring	9099
2 and Bone Spring	9886 ⁽
3Ry Bone Spring	10306'
Wo (fcamp	11487'


.

CURRENT WELLBORE



.

PROPOSED WELLBORE



PA PREP WORK PROCEDURE

The subject well might be pre-plugged prior to PA rig operations. The plugging rig will come in within 90 days of equipment removal to begin plugging this well.

Prep rig steps

- 1. Notify BLM or OCD prior to rig up.
- 2. MIRU prep rig. Prep equipment to pull pump/rods in the hole (if well has rods).
- 3. LD rods and pump, switchover to pull tbg.
- 4. ND wellhead & NU BOP.
- 5. POOH and LD tbg & BHA.
- 6. RU WL unit. Run and set CIBP.
- 7. If required, run CBL from top of plug to surface and submit to OCD
- 8. RD wireline unit.
- 9. Dump bail cmt as needed on top of CIBP.
- 10. Tag TOC & ensure well control steps followed below prior to rig off.

Well control precautions

- 1. Run official MIT test to ensure pressure holds after CIBP is set.
- 2. Ensure well control prior to rig off by tagging TOC on top of CIBP.
- 3. NU WH flange and ensure all valves are closed when moving prep rig off location, no WS tubing left in hole.

R	U.S. Department of the Interior BUREAU OF LAND MANAGEMENT		Sundry Print Report 06/18/2025
	Well Name: PATTON 18 FEDERAL	Well Location: T24S / R31E / SEC 18 / SWSE / 32.2104745 / -103.8138844	County or Parish/State: EDDY / NM
	Well Number: 8H	Type of Well: OIL WELL	Allottee or Tribe Name:
	Lease Number: NMNM89819	Unit or CA Name:	Unit or CA Number:
	US Well Number: 3001541343	Operator: OXY USA INCORPORATED	

Notice of Intent

Sundry ID: 2853991

Type of Submission: Notice of Intent

Date Sundry Submitted: 05/21/2025

Date proposed operation will begin: 06/21/2025

Type of Action: Plug and Abandonment

Time Sundry Submitted: 06:33

Procedure Description: OXY PROPOSES TO PA THE SUBJECT WELL. THE CURRENT WELLBORE, PROPOSED WELLBORE, AND PA PROCEDURE ARE ATTACHED. A PREP RIG MIGHT BE USED TO PULL EQUIPMENT BEFORE SETTING PLUGS FOR PA OPERATIONS. SEE ATTACHED PA PREP RIG PROCEDURE.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

PATTON_18_FEDERAL_008H_PA_NOI_SUB_5.21.2025_20250521063335.pdf

APPROVAL SUBJECT TO GENERAL REQUIREMENTS AND SPECIAL STIPULATIONS ATTACHED

Received by OCD: 6(23/2025 11 Well Name: PATTON 181		ocation: T24S / R31E / SEC 18 / 32.2104745 / -103.8138844	/ County or Parish/State: EDDY/ of 26
Well Number: 8H	Туре с	of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM89	819 Unit or	r CA Name:	Unit or CA Number:
US Well Number: 300154	1343 Operat	tor: OXY USA INCORPORATE	

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: STEPHEN JANACEK

Signed on: MAY 21, 2025 06:33 AM

Name: OXY USA INCORPORATED

Title: Regulatory Engineer

Street Address: 5 Greenway Plaza, Suite 110

City: Houston

State: TX

Phone: (713) 497-2417

Email address: stephen_janacek@oxy.com

Field

Representative Name: Street Address: City: Phone: Email address:

State:

Zip:

APPROVED by Long Vo Petroleum Engineer Carlsbad Field Office 575-988-50402 LVO@BLM.GOV

Received by OCD: 6/23/2025 11:36:13 AM

ecetvea by OCD: 0/23/2025 11:30:13 AM				Page 12 of		
Form 3160-5 UNITED STATES June 2019) DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT			FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2021 5. Lease Serial No.			
Do not u	se this f	IOTICES AND REPO form for proposals a Use Form 3160-3 (A	6. If Indian, Allottee or Tribe Name			
	UBMIT IN	TRIPLICATE - Other instr	uctions on page 2	7. If Unit of CA/Agreement, Na	ame and/or No.	
1. Type of Well	🗌 Gas V	Vell Other		8. Well Name and No.		
2. Name of Operator				9. API Well No.		
3a. Address 3b. Phone No. (include area control			3b. Phone No. (include area code)	10. Field and Pool or Exploratory Area		
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)			11. Country or Parish, State			
	12. CHE	CK THE APPROPRIATE B	OX(ES) TO INDICATE NATURE (DF NOTICE, REPORT OR OTH	ER DATA	
TYPE OF SUBMISS	SION		TYPI	E OF ACTION		
Notice of Intent		Acidize	Deepen Hydraulic Fracturing	Production (Start/Resume) Reclamation	Water Shut-Off Well Integrity	
Subsequent Report		Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete Temporarily Abandon	Other	
Final Abandonment	Notice	Convert to Injection	Plug Back	Water Disposal		
the proposal is to deepe the Bond under which t completion of the invol	en directiona he work wil ved operation lonment No	Ily or recomplete horizontal l be perfonned or provide th ons. If the operation results in	ly, give subsurface locations and me e Bond No. on file with BLM/BIA. n a multiple completion or recomple	asured and true vertical depths of Required subsequent reports mus tion in a new interval, a Form 31	k and approximate duration thereof. If f all pertinent markers and zones. Attach t be filed within 30 days following 60-4 must be filed once testing has been te operator has detennined that the site	

14. I hereby certify that the foregoing is true and correct. Name (<i>Printed/Typed</i>)			
1	ĩitle		
Signature	Date		
THE SPACE FOR FEDEL	RAL OR STATE OFICE USE		
Approved by Long Vo	Petroleum Engineer	6-22-2025 Date	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			
Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any any false, fictitious or fraudulent statements or representations as to any matter within		department or agency of the United States	

(Instructions on page 2)

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

0. SHL: SWSE / 150 FSL / 1700 FEL / TWSP: 24S / RANGE: 31E / SECTION: 18 / LAT: 32.2104745 / LONG: -103.8138844 (TVD: 0 feet, MD: 0 feet) BHL: NWNE / 336 FNL / 1714 FEL / TWSP: 24S / RANGE: 31E / SECTION: 18 / LAT: 0.0 / LONG: 0.0 (TVD: 0 feet, MD: 0 feet) OXY USA INC.

PATTON 18 FEDERAL 008H

30-015-41343

NOI TO PERMANENTLY ABANDON THIS WELL VIA CEMENT PLUGGING.

PROPOSED PLUGGING PROCEDURE

- 1. POOH WITH CURRENT 2-7/8" TBG AND BHA
 - a. HEAL SYSTEM STUCK IN HOLE AND PUSHED DOWN TO 8405'. UNABLE TO RETRIEVE.
- 2. TIH with gauge ring and tag top of fish.
- 3. SET CIBP AT 8355' VIA WORKSTRING. LEAK TEST TO 500 PSI FOR 30 MINUTES
- 4. SPOT 215 SX CMT (118 SX CL C FOLLOWED BY 97 SX CL H) FROM 8355' TO 6455'. WOC AND TAG
- 5. SPOT 301 SX CL C CMT FROM 5255' TO 2500'. WOC AND TAG
- 6. SPOT 283 SX CL C CMT FROM 2500' TO SURFACE
- 7. VERIFY CMT TO SURFACE

FORMATION TOPS


	Тор
Name	Meas. Depth
Rustlen	602'
Top salt	930'
Buse Satt	2530'
Delaware	42651
Bell Camon	4285'
Chenny Canyon	5205'
Brushy Canyon	6505
Bone Spring	8105
1ST Bove Sprins	9099
2 mill Bone Spring	9886 ¹
3Ry Bone Spring	10306'
Wolfcamp	แนยา '



Received by OCD: 6/23/2025 11:36:13 AM

Secretary Potash, Prairie Chicken


CURRENT WELLBORE



.

.

PROPOSED WELLBORE



REVISED 9:21 am, Jun 22, 2025

PA PREP WORK PROCEDURE

The subject well might be pre-plugged prior to PA rig operations. The plugging rig will come in within 90 days of equipment removal to begin plugging this well.

Prep rig steps

- 1. Notify BLM or OCD prior to rig up.
- 2. MIRU prep rig. Prep equipment to pull pump/rods in the hole (if well has rods).
- 3. LD rods and pump, switchover to pull tbg.
- 4. ND wellhead & NU BOP.
- 5. POOH and LD tbg & BHA.
- 6. RU WL unit. Run and set CIBP.
- 7. If required, run CBL from top of plug to surface and submit to OCD
- 8. RD wireline unit.
- 9. Dump bail cmt as needed on top of CIBP.
- 10. Tag TOC & ensure well control steps followed below prior to rig off.

Well control precautions

- 1. Run official MIT test to ensure pressure holds after CIBP is set.
- 2. Ensure well control prior to rig off by tagging TOC on top of CIBP.
- 3. NU WH flange and ensure all valves are closed when moving prep rig off location, no WS tubing left in hole.

Lesser Prairie Chicken Area

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

<u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Lea County, call 575-689-5981. Eddy County, please email notifications to: <u>BLM NM CFO PluggingNotifications@BLM.GOV</u>. The Eddy County inspector on call phone, 575-361-2822, will remain active as a secondary contact.

<u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

<u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.

<u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours for Class C or accelerated cement (calcium chloride) and 6 hours for Class H. Tagging the plug means running in the hole with a string of tubing or drill pipe and placing sufficient weight on the plug to ensure its integrity. Other methods of tagging the plug may be approved by the BLM authorized officer or BLM field representative.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

Fluid used to mix the cement in R111Q shall be saturated with the salts common to the section penetrated, and in suitable proportions but not less than 1% and not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.

<u>Above Ground Level Marker</u>: If outside of Lesser Prairie-Chicken Habitat an above ground level marker shall be utilized. All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified** *BY PHONE* (numbers listed in 2. Notifications) a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 14th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds). A weep hole shall be left if a metal plate is welded in place.

<u>Below Ground Level Marker:</u> If within Lesser Prairie-Chicken Habitat a below ground level marker shall be utilized. All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified *BY PHONE* (numbers listed in 2. Notifications) a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 14th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¹/₄ inch thick and welded in place. A weep hole shall be left in the plate and/or casing. The following information shall be permanently inscribed on the plate: well name and number, name of operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

Operator to verify the ground marker type with the BLM before setting dry hole Marker.

Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.

Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

<u>Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:</u> From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any/all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.

For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.

The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.

Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and

access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.

It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.

At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech/Environmental Protection Specialist 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist 575-234-5987

Jose Martinez-Colon Environmental Protection Specialist 575-234-5951

Angela Mohle Environmental Protection Specialist 575-234-9226

Robert Duenas Environmental Protection Specialist 575-234-2229

Terry Gregston Environmental Protection/HAZMAT Specialist 575-234-5958

•

Sundry ID	2853991			-		-	•
Plug Type	Тор	Bottom	Length	Тад	Sacks	Cement Class	Notes
							Spot cement from 2500' to surface.
Surface Plug	0.00			Tag/Verify	236.00	С	Verify at surface.
Fresh Water @ 160	108.40		101.60				
Top of Salt @ 930	870.70			Tag/Verify			
11.75 inch- Shoe Plug	870.70			Tag/Verify			
Base of Salt @ 2580	2504.20	2630.00	125.80	Tag/Verify			
8.625 inch- Shoe Plug	4114.93		142.07	Tag/Verify			
Delaware @ 4265	4172.35	4315.00	142.65	If solid			
							Spot cement from 5255' to 2500'.
DV tool plug	4182.25		142.75	Tag/Verify	260.00	С	WOC and Tag.
Bonesprings @ 8105	6455.00	8155.00	1700.00	II SOIIU			
				If solid base no need to Tag (CIBP present and/or Mechanic al Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforatio			Set CIBP at 8355'. Leak test CIBP. Spot cement from 8355' to 6455'.
CIBP Plug	8320.00	8355.00	35.00	ns	223.00	н	WOC and Tag.
Wolfcamp @ 11487	11322.13		214.87				
5.5 inch- Shoe Plug	14265.40	14510.00	244.60	Tag/Verify			

No more than 2000' is to be allowed between plugs in open hole, and no more than 3000' between plugs in cased hole. Class H >7500' Class C<7500'

Fluid used to mix the cement in R111P shall be saturated with the salts common to the section penetrated, and in suitable proportions, but not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.

Medium, Secretary: Top of salt to surface If no salt take the deepest fresh water or Karst Depth

High, Critical: Bottom of Karst to surface or Deepest fresh water, whichever is greater R111P: 50 Feet from Base of Salt to surface.

Class C: 1.32 ft^3/sx Class H: 1.06 ft^3/sx

Onshore Order 2.III.G Drilling Abandonment Requirements: "All formations bearing usable-quality water, oil, gas, or geothermal resources, and/or a prospectively valuable deposit of minerals shall be protected.

Cave Karst/Potash Cement Requirement: Wild Life 11.75 inch- Shoe Plug @ 8.625 inch- Shoe Plug @ 5.5 inch- Shoe Plug @ Top of Salt to surface Secretary Within Lesser Prairie Chicken Area 930.00 4207.00 14460.00

DV Tool @

4275.00

8355.00

CIBP @

Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:
OXY USA INC	16696
P.O. Box 4294	Action Number:
Houston, TX 772104294	477874
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	Adhere to current Plug & Abandon (P&A) Conditions Of Approvals (COA).	7/18/2025

CONDITIONS

Page 26 of 26

Action 477874