

Well Name: SOUTH BLANCO FEDERAL 26	Well Location: T24N / R8W / SEC 26 / NENW / 36.290619 / -107.651764	County or Parish/State: SAN JUAN / NM
Well Number: 4	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM138391	Unit or CA Name:	Unit or CA Number:
US Well Number: 3004525219	Operator: EPIC ENERGY LLC	

Notice of Intent

Sundry ID: 2872688

Type of Submission: Notice of Intent	Type of Action: Other
Date Sundry Submitted: 09/09/2025	Time Sundry Submitted: 01:51
Date proposed operation will begin: 09/09/2025	

Procedure Description: Epic Energy plans to set packer 100' above Gallup perforations to isolate potential frac hit. Wellbore diagrams with exact depths will be submitted in subsequent report.

Surface Disturbance

Is any additional surface disturbance proposed?: No

Well Name: SOUTH BLANCO FEDERAL 26	Well Location: T24N / R8W / SEC 26 / NENW / 36.290619 / -107.651764	County or Parish/State: SAN JUAN / NM
Well Number: 4	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM138391	Unit or CA Name:	Unit or CA Number:
US Well Number: 3004525219	Operator: EPIC ENERGY LLC	

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: ARLEEN SMITH	Signed on: SEP 09, 2025 01:51 PM
Name: EPIC ENERGY LLC	
Title: Regulatory Specialist	
Street Address: 332 RD 3100	
City: AZTEC	State: NM
Phone: (505) 327-4892	
Email address: ARLEEN@WALSHENG.NET	

Field

Representative Name:		
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		

BLM Point of Contact

BLM POC Name: KENNETH G RENNICK	BLM POC Title: Petroleum Engineer
BLM POC Phone: 5055647742	BLM POC Email Address: krennick@blm.gov
Disposition: Approved	Disposition Date: 09/09/2025
Signature: Kenneth Rennick	

WALSH ENGINEERING & PRODUCTION CORPORATION

Epic Energy

RBP Procedure

Well: South Blanco 26-4
Location: 660' FNL & 2295' FWL
Sec. 26, T24N, R08W
San Juan County, New Mexico
API: 30-045-25219

Field: Lybrook - Gallup
Elevation: 6842' GL
By: Mark Thompson

Background/Purpose

Set RBP to isolate production zones and safeguard well integrity during nearby offset fracturing treatments.

Procedure:

Prior to rig move ensure anchors and road are in shape for rig and associated equipment

1. MIRU Service Unit. Hold safety meeting with all personnel on location and explain job procedure and possible hazards.
2. ND WH, NU BOP, RU rig floor and 2 3/8" handling tools.
3. POOH 2 3/8" production string including set at ~5569'.
4. TIH with 4.5" casing scraper to approx 5205'.
5. TIH with Retrievable Bridge Plug (RBP) and running tools to approx 5198'.
6. Set RBP @ approx 5198' using third party procedure. (~150' above top perf)
7. Fill hole with water. POOH.
8. RDMO

Mark Thompson

Walsh Engineering and Production

Well/Facility:	South Blanco Federal 26 #004	Well Status:	Producing	Date Drawn:	May 9, 2025 (CM)
Operator:	Epic Energy	Orig Oper:	Mesa Petroleum Co.		
Lease/Op Agmt:		KB:			
Field:	Lybrook Gallup	API #:	30-045-25219		
County:	San Juan	GR/KB:	6842' GL		
State:	NM	TD:	5680'		
Spud:	1/16/1982	PBTD:	5637.26'		
Comp. Date:	10/19/1982	WI:	98.890000		
1st Prod:	11/3/1982	NRI:	83.130000		
Wellhead Conn:					
Surface Loc:	660' FNL & 2295' FWL				
Sec-Twn-Rge:	Sec 26 / T24N / R08W				
Pumper:	Jimmie McKinney				
Foreman:	Mike Veazey				
Anchor Tested					
Notes:	Been down since April 2022. Eng plan and recommendation				

SET RBP ~150' ABOVE TOP PERF AT ~5198'



WALSH
ENGINEERING & PRODUCTION CORP.

Casing Record						
Surface						
OD	WT/FT	GRADE	Top	Bottom	Thread	Bit Size
8 5/8"	24	J55	0	261.05	ST&C	12 1/4"

Production						
OD	WT/FT	GRADE	Top	Bottom	Thread	Bit Size
4 1/2"	10.5	J55	0	5676'	ST&C	7 7/8"
						DC TOOL @3071'

Cement		
String/Stage	Cement Type and Volume	TOC/Method
Surface	Lead: 225 sks Class "B" Tail:	Circulated Surface
1st Stage Production	Lead: 450 sks Class "B" Tail: 150 sks "Self Stressed"	Circ 20 bbls Surface
2nd Stage Production	Lead: 400 sks 65/35 POZ Tail: 50 sks Class "B"	Circ 25 bbls Surface

Perforations (Depth, SPF, EHD)
5348-5459: 1 jspf, 0.35 ehd

Stimulation Detail
5348-5459: 2250 gals 7.5% HCL Acid, Frace'd 71,000 gals crude oil, 116,000 20/40 Sand.

Released to Imaging: 10/17/2025 10:16:24 AM

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/oecd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 515791

CONDITIONS

Operator: EPIC ENERGY, L.L.C. 332 Road 3100 Aztec, NM 87410	OGRID: 372834
	Action Number: 515791
	Action Type: [C-103] NOI Workover (C-103G)

CONDITIONS

Created By	Condition	Condition Date
andrew.fordyce	Return the well to production when offset completion operations are concluded.	10/17/2025