

1625 N. French Dr., Hobbs, NM 88240

District II

811 S. First St., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural ResourcesForm C-104
Revised August 1, 2011Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit one copy to appropriate District Office

☐ AMENDED REPORT**I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT**

¹ Operator name and Address XTO Energy, Inc. 6401 HOLIDAY HILL ROAD BLDG 5 MIDLAND, TX 79707		² OGRID Number 373075
		³ Reason for Filing Code/ Effective Date NW
⁴ API Number 30 - 015-46659	⁵ Pool Name PURPLE SAGE; WOLFCAMP (GAS)	⁶ Pool Code 98220
⁷ Property Code 325469	⁸ Property Name POKER LAKE UNIT 17 TWR	⁹ Well Number 707H

II. ¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South Line	Feet from the	East/West line	County
A	20	24S	31E		95	North	1035	East	EDDY

¹¹ Bottom Hole Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	29	24S	31E		241	South	1144	East	Eddy
¹² Lse Code F	¹³ Producing Method Code F	¹⁴ Gas Connection Date	¹⁵ C-129 Permit Number	¹⁶ C-129 Effective Date	¹⁷ C-129 Expiration Date				

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
373075	XTO Permian OP	G/W
34053	Plains Marketing, LP	Oil

IV. Well Completion Data

²¹ Spud Date 7/10/2020	²² Ready Date 11/15/2021	²¹⁷⁷⁰ MDTD 11870 TVD	²¹⁷⁵³ MBTD 11870 TVD	²⁵ Perforations 12,237 - 21,654	²⁶ DHC, MC
²⁷ Hole Size	²⁸ Casing & Tubing Size	²⁹ Depth Set	³⁰ Sacks Cement		
14.75	11.75	886	911		
9.875	7.625	10,954	2690		
6.75	5.5	21,755	925		
	2-7/8	11211			

V. Well Test Data

³¹ Date New Oil 11/16/21	³² Gas Delivery Date 11/17/21	³³ Test Date 11/17/21	³⁴ Test Length 24 hrs	³⁵ Tbg. Pressure 637	³⁶ Csg. Pressure 336
³⁷ Choke Size	³⁸ Oil 1970	³⁹ Water 4974	⁴⁰ Gas 5554		⁴¹ Test Method Flowing
⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief. Signature: <i>Cassie Evans</i>			OIL CONSERVATION DIVISION		
Printed name: Cassie Evans			Approved by:		
Title: Regulatory Analyst			Title:		
E-mail Address: cassie.evans@exxonmobil.com			Approval Date:		
Date: 12/25/2021		Phone: 432.218.3671			

District I

1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III

1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102

Revised August 1, 2011

Submit one copy to appropriate

District Office

☒ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

AS-DRILLED PLAT

¹ API Number 30-015-46659	² Pool Code 98220	³ Pool Name PURPLE SAGE; WOLFCAMP (GAS)
⁴ Property Code 325469	⁵ Property Name POKER LAKE UNIT 17 TWR	⁶ Well Number 707H
⁷ OGRID No. 373075	⁸ Operator Name XTO PERMIAN OPERATING, LLC.	⁹ Elevation 3,522'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	20	24 S	31 E		95	NORTH	1,035	EAST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	29	24 S	31 E		241	SOUTH	1,144	EAST	EDDY

¹² Dedicated Acres 640	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division. AS-DRILLED BOTTOM HOLE PLOTTED FROM DATA FURNISHED BY XTO ENERGY.

	SHL (NAD83 NME) Y = 440,484.7 X = 707,945.2 LAT. = 32.209822 °N LONG. = 103.794642 °W KOP (NAD83 NME) Y = 440,505.3 X = 707,792.9 LAT. = 32.209880 °N LONG. = 103.795134 °W FTP (NAD83 NME) Y = 439,785.9 X = 707,836.6 LAT. = 32.207902 °N LONG. = 103.795004 °W CORNER COORDINATES (NAD83 NME) A - Y = 440,586.4 N , X = 708,979.7 E B - Y = 440,577.6 N , X = 707,657.5 E C - Y = 437,947.7 N , X = 708,996.2 E D - Y = 437,938.4 N , X = 707,674.2 E E - Y = 435,304.7 N , X = 709,012.3 E F - Y = 435,296.6 N , X = 707,690.8 E G - Y = 432,663.6 N , X = 709,028.9 E H - Y = 432,655.5 N , X = 707,707.7 E I - Y = 430,022.4 N , X = 709,045.5 E J - Y = 430,014.3 N , X = 707,724.7 E SHL (NAD27 NME) Y = 440,425.9 X = 666,761.1 LAT. = 32.209698 °N LONG. = 103.794158 °W KOP (NAD27 NME) Y = 440,446.4 X = 666,609.0 LAT. = 32.209757 °N LONG. = 103.794649 °W FTP (NAD27 NME) Y = 439,727.0 X = 666,652.7 LAT. = 32.207778 °N LONG. = 103.794520 °W CORNER COORDINATES (NAD27 NME) A - Y = 440,527.6 N , X = 667,795.6 E B - Y = 440,518.8 N , X = 666,473.4 E C - Y = 437,889.0 N , X = 667,812.0 E D - Y = 437,879.7 N , X = 666,490.0 E E - Y = 435,246.1 N , X = 667,828.0 E F - Y = 435,238.0 N , X = 666,506.6 E G - Y = 432,605.0 N , X = 667,844.5 E H - Y = 432,596.9 N , X = 666,523.3 E I - Y = 429,963.9 N , X = 667,861.0 E J - Y = 429,955.8 N , X = 666,540.2 E	¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Cassie Evans</i> 12/24/2021 Signature Date Cassie Evans Printed Name Cassie.evans@exxonmobil.com E-mail Address
		¹⁸ SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 10-21-2021 Date of Survey Signature and Seal of Professional Surveyor: <i>Mark Dillon Harp</i> MARK DILLON HARP 23786 Certificate Number JC 2018010217

Intent ☐ As Drilled ☒

API # 30-015-46659		
Operator Name: XTO PERMIAN OPERATING, LLC.	Property Name: POKER LAKE UNIT 17 TWR	Well Number 707H

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
A	20	24S	31E		73	FNL	1,187	FEL	EDDY
Latitude 32.209880					Longitude 103.795134				NAD 83

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
A	20	24S	31E		793	FNL	1,148	FEL	EDDY
Latitude 32.207902					Longitude 103.795004				NAD 83

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
P	29	24S	31E		357	FSL	1,145	FEL	EDDY
Latitude 32.182024					Longitude 103.794957				NAD 83

Is this well the defining well for the Horizontal Spacing Unit? ☐Is this well an infill well? ☐

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #		
Operator Name:	Property Name:	Well Number

KZ 06/29/2018

Schlumberger

XTO Poker Lake Unit 17 TWR 707H 0 to 21770' MD Survey Geodetic

Report
(Def Survey)

Report Date: September 23, 2020 - 10:11 AM
Client: XTO Energy
Field: NM Eddy County (NAD 27)
Structure / Slot: XTO Poker Lake Unit 17 TWR 707H / XTO Poker Lake Unit 17 TWR 707H
Well: XTO Poker Lake Unit 17 TWR 707H
Borehole: XTO Poker Lake Unit 17 TWR 707H
UWI / API#: Unknown / 30-015-46659
Survey Name: XTO Poker Lake Unit 17 TWR 707H 0 to 21770' MD
Survey Date: September 09, 2020
Tort / AHD / DDI / ERD Ratio: 255.650' / 10561.165 ft / 6.695' / 0.889
Coordinate Reference System: NAD27 New Mexico State Plane, Eastern Zone, US Feet
Location Lat / Long: N 32° 12' 34.91337", W 103° 47' 38.96824"
Location Grid N/E Y/X: N 440425.900 ftUS, E 666761.100 ftUS
CRS Grid Convergence Angle: 0.2874 °
Grid Scale Factor: 0.99994094
Version / Patch: 2.10.820.4

Survey / DLS Computation: Minimum Curvature / Lubinski
Vertical Section Azimuth: 179.650 ° (Grid North)
Vertical Section Origin: 0.000 ft, 0.000 ft
TVD Reference Datum: RKB
TVD Reference Elevation: 3555.000 ft above MSL
Seabed / Ground Elevation: 3522.000 ft above MSL
Magnetic Declination: 6.744 °
Total Gravity Field Strength: 998.4267mgn (9.80665 Based)
Gravity Model: GARM
Total Magnetic Field Strength: 47736.000 nT
Magnetic Dip Angle: 59.870 °
Declination Date: September 09, 2020
Magnetic Declination Model: IFR1+MS
North Reference: Grid North
Grid Convergence Used: 0.2850 °
Total Corr Mag North->Grid North: 6.4590 °
Local Coord Referenced To: Well Head

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (ft/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
Surface	0.00	0.00	0.00	0.00	0.00	0.00	0.00	N/A	440425.90	666761.10	32.209698	-103.794158	0.00	0.00
	149.00	0.55	40.68	149.00	-0.54	0.54	0.47	0.37	440426.44	666761.57	32.209700	-103.794156	0.72	40.68
	211.00	0.84	35.72	210.99	-1.13	1.14	0.93	0.48	440427.04	666762.03	32.209701	-103.794155	1.47	39.14
	303.00	0.62	49.74	302.99	-2.00	2.01	1.70	0.31	440427.91	666762.80	32.209704	-103.794152	2.63	40.26
	394.00	0.44	103.58	393.98	-2.23	2.24	2.41	0.56	440428.14	666763.51	32.209704	-103.794150	3.30	47.12
	486.00	0.59	93.30	485.98	-2.11	2.13	3.23	0.19	440428.03	666764.33	32.209704	-103.794147	3.87	56.58
	576.00	0.10	130.12	575.98	-2.03	2.05	3.75	0.57	440427.95	666764.85	32.209704	-103.794146	4.28	61.30
	669.00	0.65	279.26	668.97	-2.07	2.09	3.29	0.79	440427.99	666764.39	32.209704	-103.794147	3.90	57.64
	760.00	0.77	279.59	759.97	-2.26	2.27	2.18	0.13	440428.17	666763.28	32.209704	-103.794151	3.15	43.84
	811.00	0.70	287.94	810.96	-2.42	2.43	1.55	0.25	440428.33	666762.65	32.209705	-103.794153	2.88	32.55
11-3/4" Casing	894.00	0.85	280.85	893.96	-2.69	2.70	0.46	0.21	440428.60	666761.56	32.209706	-103.794156	2.74	9.77
	972.00	0.99	276.15	971.95	-2.88	2.88	-0.77	0.21	440428.78	666760.33	32.209706	-103.794160	2.98	345.01
	1063.00	0.78	271.11	1062.94	-2.99	2.97	-2.17	0.25	440428.87	666758.93	32.209706	-103.794165	3.68	323.86
	1153.00	0.97	268.81	1152.92	-2.99	2.97	-3.55	0.21	440428.87	666757.55	32.209706	-103.794169	4.62	309.95
	1248.00	0.79	278.41	1247.91	-3.08	3.05	-5.00	0.24	440428.95	666756.10	32.209707	-103.794174	5.85	301.39
	1342.00	1.00	284.81	1341.90	-3.39	3.35	-6.43	0.25	440429.25	666754.67	32.209707	-103.794179	7.25	297.54
	1437.00	0.87	282.69	1436.89	-3.77	3.72	-7.94	0.14	440429.62	666753.16	32.209709	-103.794183	8.77	295.13
	1532.00	1.78	288.23	1531.86	-4.40	4.34	-10.04	0.97	440430.24	666751.06	32.209710	-103.794190	10.94	293.39
	1627.00	2.91	290.85	1626.78	-5.75	5.66	-13.70	1.19	440431.56	666747.40	32.209714	-103.794202	14.82	292.46
	1721.00	3.90	290.06	1720.61	-7.72	7.61	-18.93	1.05	440433.51	666742.17	32.209719	-103.794219	20.40	291.90
	1816.00	3.98	288.38	1815.39	-9.91	9.76	-25.09	0.15	440435.66	666736.01	32.209725	-103.794239	26.92	291.25
	1911.00	4.15	288.90	1910.15	-12.10	11.91	-31.47	0.18	440437.81	666729.63	32.209731	-103.794259	33.65	290.73
	2005.00	4.30	285.50	2003.90	-14.19	13.95	-38.09	0.31	440439.85	666723.02	32.209737	-103.794281	40.56	290.12
	2099.00	4.37	285.43	2097.63	-16.12	15.85	-44.94	0.07	440441.75	666716.17	32.209742	-103.794303	47.65	289.43
	2194.00	4.65	283.53	2192.33	-18.03	17.71	-52.17	0.33	440443.61	666708.94	32.209748	-103.794326	55.09	288.75
	2288.00	4.79	283.89	2286.01	-19.91	19.55	-59.68	0.15	440445.44	666701.42	32.209753	-103.794350	62.80	288.13
	2383.00	5.07	283.40	2380.66	-21.88	21.47	-67.62	0.30	440447.37	666693.49	32.209758	-103.794376	70.94	287.62
	2478.00	5.36	281.37	2475.27	-23.78	23.32	-76.05	0.36	440449.22	666685.05	32.209763	-103.794403	79.54	287.05
	2573.00	5.75	281.45	2569.82	-25.66	25.14	-85.06	0.41	440451.04	666676.04	32.209768	-103.794432	88.70	286.46
	2667.00	6.00	278.22	2663.33	-27.35	26.77	-94.54	0.44	440452.67	666666.56	32.209773	-103.794463	98.26	285.81
	2762.00	5.86	285.40	2757.82	-29.41	28.77	-104.13	0.79	440454.67	666656.97	32.209779	-103.794494	108.03	285.45
	2857.00	5.24	301.38	2852.38	-33.01	32.32	-112.51	1.75	440458.22	666648.90	32.209789	-103.794521	117.06	286.03
	2952.00	5.09	311.94	2947.00	-38.12	37.39	-119.35	1.01	440463.29	666641.76	32.209803	-103.794543	125.07	287.40
	3047.00	3.85	331.31	3041.71	-43.77	43.01	-124.02	2.04	440468.91	666637.09	32.209818	-103.794558	131.26	289.13
	3140.00	2.18	0.72	3134.59	-48.28	47.52	-125.49	2.39	440473.42	666635.61	32.209831	-103.794563	134.19	290.74
	3235.00	2.11	12.63	3229.52	-51.79	51.03	-125.09	0.47	440476.93	666636.02	32.209840	-103.794561	135.10	292.19
	3330.00	2.03	5.07	3324.46	-55.17	54.41	-124.56	0.30	440480.31	666636.55	32.209849	-103.794560	135.92	293.60
	3424.00	1.46	359.24	3418.41	-58.03	57.27	-124.43	0.63	440483.17	666636.68	32.209857	-103.794559	136.97	294.72
	3518.00	0.84	22.96	3512.40	-59.86	59.10	-124.17	0.82	440485.00	666636.94	32.209862	-103.794558	137.52	295.45
	3611.00	1.68	40.18	3605.37	-61.52	60.77	-123.03	0.98	440486.67	666638.08	32.209867	-103.794555	137.22	296.29
	3705.00	1.99	60.17	3699.33	-63.37	62.64	-120.72	0.75	440488.53	666640.39	32.209872	-103.794547	136.00	297.42
	3800.00	2.00	76.24	3794.27	-64.57	63.85	-117.68	0.59	440489.75	666643.43	32.209875	-103.794537	133.89	298.48
	3893.00	1.87	113.44	3887.22	-64.33	63.63	-114.71	1.33	440489.53	666646.39	32.209875	-103.794528	131.18	299.02
	3986.00	1.76	139.24	3980.17	-62.63	61.95	-112.39	0.88	440487.84	666648.72	32.209870	-103.794520	128.33	298.86
	4081.00	3.05	171.35	4075.09	-59.02	58.34	-111.06	1.91	440484.24	666650.05	32.209860	-103.794516	125.45	297.72
	4175.00	3.17	168.61	4168.95	-54.00	53.32	-110.17	0.20	440479.22	666650.94	32.209846	-103.794513	122.39	295.83
	4273.00	2.53	166.37	4266.83	-49.23	48.56	-109.12	0.66	440474.48	666651.99	32.209833	-103.794510	119.44	293.99
	4368.00	1.01	187.51	4361.78	-46.36	45.70	-108.74	1.71	440471.59	666652.37	32.209825	-103.794509	117.95	292.79
	4463.00	0.45	259.69	4456.78	-45.47	44.80	-109.21	1.02	440470.70	666651.89	32.209823	-103.794510	118.01	292.30
	4557.00	0.39	243.21	4550.78	-45.26	44.59	-109.86	0.14	440470.49	666651.25	32.209822	-103.794512	118.57	292.09
	4651.00	0.44	226.56	4644.77	-44.87	44.20	-110.41	0.14	440470.09	666650.70	32.209821	-103.794514	118.93	291.82
	4746.00	0.41	240.90	4739.77	-44.46	43.78	-110.97	0.12	440469.68	666650.14	32.209820	-103.794516	119.30	291.53
	4841.00	0.38	228.78	4834.77	-44.09	43.41	-111.50	0.09	440469.31	666649.60	32.209819	-103.794518	119.66	291.27
	4936.00	0.54	208.09	4929.77	-43.49	42.81	-111.95	0.24	440468.70	666649.15	32.209817	-103.794519	119.86	290.92
	5029.00	0.57	196.30	5022.76	-42.67	41.98	-112.31	0.10	440467.88	666648.80	32.209815	-103.794520	119.90	290.50
	5124.00	0.60	186.54	5117.76	-41.73	41.04	-112.52	0.14	440466.94	666648.58	32.209813	-103.794521	119.78	290.04
	5219.00	0.57	203.79	5212.75	-40.80	40.12	-112.77	0.19	440466.01	666648.33	32.209810	-103.794522	119.69	289.58
	5313.00	0.72	230.37	5306.75	-40.00	39.31	-113.42	0.35	440465.21	666647.69	32.209808	-103.794524	120.04	289.12
	5407.00	0.78	235.54	5400.74	-39.27	38.57	-114.40	0.10	440464.47	666646.71	32.209806	-103.794527	120.73	288.63
	5502.00	0.82	237.74	5495.73	-38.55	37.84	-115.51	0.05	440463.74	666645.60	32.209804	-103.794531	121.55	288.14
	5597.00	0.79	243.16	5590.72	-37.90	37.19	-116.67	0.09	440463.08	666644.44	32.209802	-103.794534	122.45	287.68
	5691.00	0.73	247.31	5684.71	-37.38	36.66	-117.80	0.09	440462.56	666643.31	32.209801	-103.794538	123.37	287.29
	5786.00	0.77	258.26	5779.70	-37.02	36.30	-118.98	0.16	440462.20	666642.13	32.209800	-103.794542	124.39	286.97
	5880.00	0.84	263.11	5873.69	-36.82	36.09	-120.28	0.10	440461.98	666640.83	32.209799	-103.794546	125.58	286.70
	5975.00	1.00	256.06	5968.68	-36.55	35.80	-121.78	0.21	440461.70	666639.33	32.209798	-103.794551	126.93	286.38
	6070.00	1.02	249											

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
	8628.00	0.32	12.07	8621.49	-45.82	44.95	-142.40	0.40	440470.85	666618.71	32.209824	-103.794617	149.32	287.52
	8723.00	0.15	2.21	8716.49	-46.20	45.34	-142.34	0.18	440471.23	666618.77	32.209825	-103.794617	149.38	287.67
	8817.00	0.18	149.98	8810.49	-46.20	45.33	-142.26	0.34	440471.23	666618.85	32.209825	-103.794617	149.30	287.67
	8909.00	0.46	96.38	8902.48	-46.03	45.17	-141.82	0.41	440471.06	666619.29	32.209824	-103.794616	148.84	287.67
	9003.00	1.18	103.04	8996.47	-45.76	44.90	-140.50	0.77	440470.80	666620.61	32.209824	-103.794611	147.50	287.72
	9097.00	1.96	96.92	9090.44	-45.33	44.49	-137.96	0.85	440470.39	666623.15	32.209822	-103.794603	144.96	287.87
	9191.00	2.17	86.30	9184.38	-45.24	44.41	-134.59	0.46	440470.31	666626.52	32.209822	-103.794592	141.73	288.26
	9286.00	2.23	87.64	9279.31	-45.41	44.61	-130.95	0.08	440470.50	666630.16	32.209823	-103.794580	138.34	288.81
	9380.00	1.98	89.46	9373.24	-45.47	44.70	-127.50	0.28	440470.59	666633.61	32.209823	-103.794569	135.10	289.32
	9473.00	1.51	93.93	9466.20	-45.39	44.63	-124.67	0.53	440470.53	666636.44	32.209823	-103.794560	132.41	289.70
	9568.00	1.00	72.03	9561.18	-45.55	44.80	-122.63	0.73	440470.70	666638.48	32.209823	-103.794554	130.56	290.07
	9663.00	0.87	353.91	9656.17	-46.51	45.77	-121.92	1.24	440471.67	666639.19	32.209826	-103.794551	130.23	290.58
	9758.00	2.00	325.32	9751.14	-48.60	47.85	-122.94	1.37	440473.75	666638.17	32.209831	-103.794555	131.92	291.27
	9853.00	1.34	308.41	9846.10	-50.67	49.90	-124.75	0.86	440475.80	666636.36	32.209837	-103.794560	134.36	291.80
	9948.00	1.07	291.25	9941.08	-51.69	50.92	-126.45	0.47	440476.81	666634.66	32.209837	-103.794566	136.31	291.93
	10042.00	1.39	279.38	10035.06	-52.20	51.42	-128.39	0.43	440477.32	666632.72	32.209841	-103.794572	138.31	291.83
	10136.00	1.12	219.28	10129.04	-51.69	50.89	-130.10	1.36	440476.79	666631.01	32.209840	-103.794578	139.70	291.37
	10231.00	1.89	214.70	10224.00	-49.69	48.89	-131.58	0.82	440474.78	666629.53	32.209834	-103.794582	140.37	290.38
	10325.00	2.40	218.72	10317.94	-46.89	46.08	-133.69	0.57	440471.97	666627.42	32.209827	-103.794589	141.41	289.02
	10420.00	2.49	214.81	10412.85	-43.66	42.83	-136.11	0.20	440468.73	666624.99	32.209818	-103.794597	142.69	287.47
	10515.00	2.63	214.51	10507.76	-40.19	39.34	-138.53	0.15	440465.24	666622.58	32.209808	-103.794605	144.00	285.85
	10609.00	2.56	215.59	10601.66	-36.72	35.86	-140.97	0.09	440461.75	666620.14	32.209799	-103.794613	145.46	284.27
	10703.00	2.40	208.06	10695.57	-33.29	32.41	-143.12	0.39	440458.31	666617.99	32.209789	-103.794620	146.74	282.76
	10797.00	2.61	205.30	10789.48	-29.63	28.74	-144.96	0.26	440454.64	666616.15	32.209779	-103.794626	147.78	281.21
	10905.00	3.20	213.15	10897.34	-24.90	23.99	-147.66	0.66	440449.89	666613.45	32.209766	-103.794635	149.59	279.23
7 5/8" Casing	10974.00	2.09	232.89	10866.27	-22.53	21.62	-149.72	2.05	440447.52	666611.39	32.209760	-103.794642	151.27	278.22
	10989.00	1.91	239.95	10981.26	-22.25	21.33	-150.15	2.05	440447.23	666610.96	32.209759	-103.794643	151.66	278.09
	11084.00	1.35	308.07	11076.23	-22.16	21.23	-152.40	1.98	440447.13	666608.71	32.209759	-103.794650	153.87	277.93
	11179.00	5.91	156.61	11171.09	-18.35	17.42	-151.34	7.50	440443.32	666609.77	32.209748	-103.794647	152.34	276.57
	11274.00	11.40	188.71	11265.02	-4.56	3.64	-150.82	7.49	440429.54	666610.29	32.209710	-103.794645	150.86	271.38
	11369.00	20.36	183.13	11356.30	21.26	-22.20	-151.15	9.56	440403.70	666607.96	32.209639	-103.794653	154.75	261.75
	11463.00	28.75	173.57	11441.76	60.15	-61.08	-151.51	9.85	440364.83	666609.60	32.209632	-103.794649	163.35	248.04
	11558.00	35.99	177.11	11521.95	110.83	-111.73	-147.54	7.87	440314.18	666613.57	32.209393	-103.794637	185.07	232.86
	11653.00	44.56	177.43	11594.36	172.13	-173.02	-144.63	9.02	440252.89	666616.48	32.209225	-103.794628	225.50	219.89
FTP [330° FNL, 145° FWL]	11735.00	50.70	175.84	11649.60	232.60	-233.46	-141.03	7.63	440192.45	666620.08	32.209058	-103.794618	272.75	211.14
	11748.00	51.68	175.61	11657.75	242.70	-243.56	-140.28	7.63	440182.35	666620.83	32.209031	-103.794615	281.07	209.94
	11843.00	59.93	176.21	11711.09	321.04	-321.87	-134.70	8.70	440104.05	666626.41	32.208815	-103.794599	348.92	202.71
	11938.00	68.40	177.63	11752.45	406.37	-407.18	-130.14	9.02	440018.75	666630.96	32.208581	-103.794585	427.47	197.73
	12032.00	75.69	174.32	11781.42	495.53	-496.30	-123.82	8.45	439929.63	666637.29	32.208336	-103.794566	511.51	194.01
	12127.00	83.72	175.09	11798.38	588.58	-589.29	-115.21	8.49	439836.64	666645.90	32.208080	-103.794540	600.45	191.06
	12222.00	88.41	177.19	11804.90	683.12	-683.82	-108.84	5.41	439742.12	666652.27	32.207820	-103.794521	692.43	189.04
	12317.00	88.62	180.74	11807.36	778.09	-778.76	-107.12	3.74	439647.19	666653.99	32.207559	-103.794517	786.09	187.83
	12412.00	88.77	182.15	11809.53	873.02	-873.70	-109.52	1.49	439552.25	666651.59	32.207298	-103.794526	880.54	187.14
	12506.00	88.47	181.91	11811.79	966.91	-967.62	-112.84	0.41	439458.34	666648.26	32.207040	-103.794538	974.18	186.65
	12601.00	88.84	180.09	11814.02	1061.85	-1062.57	-114.50	1.95	439363.39	666646.61	32.206779	-103.794545	1068.72	186.15
	12696.00	88.84	180.24	11815.95	1156.83	-1157.55	-114.77	0.16	439268.42	666646.33	32.206518	-103.794548	1163.23	185.66
	12791.00	88.97	180.14	11817.76	1251.81	-1252.54	-115.09	0.17	439173.44	666646.02	32.206257	-103.794550	1257.81	185.25
	12886.00	89.03	180.39	11819.42	1346.79	-1347.52	-115.33	0.02	439078.46	666645.58	32.205996	-103.794553	1352.46	184.90
	12981.00	88.98	179.38	11821.07	1441.77	-1442.50	-115.34	1.06	438983.48	666645.77	32.205735	-103.794554	1447.11	184.57
	13076.00	89.31	178.29	11822.49	1536.76	-1537.49	-115.13	1.10	438888.50	666645.98	32.205474	-103.794555	1541.80	184.28
	13171.00	88.48	180.15	11824.32	1631.74	-1632.47	-115.56	0.90	438793.53	666645.54	32.205213	-103.794558	1636.56	184.05
	13266.00	89.04	180.32	11826.37	1726.71	-1727.45	-115.95	0.62	438698.56	666645.16	32.204951	-103.794561	1731.34	183.84
	13361.00	89.61	180.27	11827.49	1821.70	-1822.44	-116.44	0.60	438603.57	666644.67	32.204690	-103.794564	1826.16	183.66
	13456.00	91.12	181.20	11828.89	1916.67	-1917.43	-117.66	1.87	438508.59	666643.45	32.204429	-103.794569	1921.03	183.51
	13550.00	90.58	180.54	11825.49	2010.64	-2011.40	-119.09	0.91	438414.62	666642.02	32.204171	-103.794575	2014.93	183.39
	13645.00	88.41	179.09	11826.33	2105.63	-2106.39	-118.78	2.75	438319.64	666642.33	32.203910	-103.794576	2109.74	183.23
	13740.00	89.43	178.73	11828.12	2200.60	-2201.36	-116.97	1.14	438224.68	666644.13	32.203649	-103.794572	2204.46	183.04
	13835.00	87.87	178.09	11830.36	2295.55	-2296.29	-114.34	1.77	438129.75	666646.77	32.203388	-103.794565	2299.14	182.85
	13930.00	88.13	178.60	11833.67	2390.47	-2391.19	-111.60	0.60	438034.85	666649.51	32.203127	-103.794557	2393.80	182.67
	14025.00	88.44	179.35	11836.52	2485.42	-2486.13	-109.90	0.85	437939.92	666651.21	32.202866	-103.794553	2488.56	182.53
	14119.00	88.88	180.19	11838.72	2579.39	-2580.11	-109.52	1.01	437845.95	666651.59	32.202608	-103.794554	2582.43	182.43
	14214.00	89.01	177.85	11840.47	2674.36	-2675.07	-107.90	2.47	437750.99	666653.21	32.202347	-103.794550	2677.25	182.31
	14309.00	88.22	177.30	11842.76	2769.27	-2769.96	-103.88	1.01	437656.11	666657.23	32.202086	-103.794539	2771.90	182.15
	14404.00	87.80	180.60	11846.23	2864.17	-2864.84	-101.81	1.90	437561.24	666660.29	32.201825	-103.794539	2865.91	182.02
	14499.00	87.52	178.65	11850.77	2959.07	-2959.73	-98.87	3.03	437466.35	666662.24	32.201564	-103.794525	2961.38	181.91
	14594.00	86.89	179.67	11854.90	3053.96	-3054.61	-97.48	1.26	437371.48	666663.63	32.201303	-103.794522	3056.16	181.83
	14689.00	89.01	179.29	11858.30	3148.89	-3149.54	-96.61	2.27	437276.55	666664.49	32.201042	-103.794521	3151.02	181.76
	14784.00	87.16	181.12	11861.48	3243.82	-3244.48	-96.95	2.74	437181.62	666664.15	32.200781	-103.794524	3245.92	181.71
	14879.00	91.67	180.65	11862.45	3338.77	-3339.44	-98.42	4.77	437086.67	666662.69	32.200520	-103.794530	3340.89	181.69

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS ("/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth [°]
	19622.00	90.09	179.63	11871.37	8080.80	-8081.39	-71.71	0.44	432345.00	666689.40	32.187486	-103.794521	8081.71	180.51
	19717.00	90.12	180.00	11871.19	8175.80	-8176.39	-71.40	0.39	432250.01	666689.71	32.187225	-103.794521	8176.70	180.50
	19812.00	88.65	179.31	11872.21	8270.79	-8271.38	-70.83	1.71	432155.02	666690.28	32.186963	-103.794521	8271.68	180.49
	19907.00	90.26	178.93	11873.12	8365.78	-8366.36	-69.37	1.74	432060.05	666691.74	32.186702	-103.794518	8366.65	180.48
	20002.00	89.60	179.60	11873.23	8460.78	-8461.35	-68.15	0.99	431965.06	666692.95	32.186441	-103.794515	8461.63	180.46
	20097.00	90.49	179.19	11873.16	8555.78	-8556.35	-67.15	1.03	431870.08	666693.96	32.186180	-103.794514	8556.61	180.45
	20192.00	89.98	179.27	11872.77	8650.77	-8651.34	-65.87	0.54	431775.09	666695.23	32.185919	-103.794511	8651.59	180.44
	20287.00	90.14	179.40	11872.67	8745.77	-8746.33	-64.77	0.22	431680.10	666696.34	32.185658	-103.794509	8746.57	180.42
	20381.00	90.67	179.62	11872.01	8839.77	-8840.32	-63.96	0.61	431586.12	666697.14	32.185399	-103.794508	8840.56	180.41
	20477.00	89.64	177.97	11871.75	8935.75	-8936.30	-61.94	2.03	431490.15	666699.16	32.185136	-103.794503	8936.51	180.40
	20572.00	90.89	178.47	11871.31	9030.72	-9031.25	-58.99	1.42	431395.20	666702.11	32.184875	-103.794495	9031.44	180.37
	20666.00	90.92	179.21	11869.82	9124.70	-9125.22	-57.09	0.79	431301.24	666704.01	32.184616	-103.794490	9125.40	180.36
	20761.00	90.92	179.41	11868.30	9219.68	-9220.20	-55.95	0.21	431206.26	666705.16	32.184355	-103.794488	9220.37	180.35
	20856.00	90.16	179.30	11867.40	9314.68	-9315.19	-54.88	0.81	431111.28	666706.23	32.184094	-103.794486	9315.35	180.34
	20951.00	89.94	179.74	11867.32	9409.68	-9410.18	-54.08	0.52	431016.29	666707.02	32.183833	-103.794485	9410.34	180.33
	21046.00	89.73	179.49	11867.59	9504.68	-9505.18	-53.44	0.34	430921.30	666707.66	32.183572	-103.794485	9505.33	180.32
	21141.00	90.02	179.70	11867.80	9599.68	-9600.18	-52.77	0.38	430826.31	666708.33	32.183311	-103.794484	9600.32	180.31
	21236.00	89.80	179.78	11867.95	9694.68	-9695.18	-52.34	0.25	430731.31	666708.76	32.183050	-103.794484	9695.32	180.31
	21331.00	89.92	179.32	11868.18	9789.68	-9790.17	-51.59	0.50	430636.32	666709.51	32.182788	-103.794483	9790.31	180.30
	21426.00	89.48	179.08	11868.68	9884.67	-9885.16	-50.27	0.53	430541.34	666710.83	32.182527	-103.794481	9885.29	180.29
	21521.00	89.82	179.10	11869.26	9979.67	-9980.15	-48.76	0.36	430446.36	666712.34	32.182266	-103.794477	9980.27	180.28
	21616.00	89.78	179.53	11869.59	10074.66	-10075.14	-47.62	0.45	430351.37	666713.48	32.182005	-103.794475	10075.25	180.27
LTP [330' FSL, 176' FWL]	21683.00	89.55	179.23	11869.98	10141.66	-10142.14	-46.90	0.56	430284.38	666714.20	32.181821	-103.794474	10142.24	180.26
	21711.00	89.45	179.11	11870.23	10169.66	-10170.13	-46.50	0.56	430256.39	666714.61	32.181744	-103.794473	10170.24	180.26
Last Survey	21744.00	89.41	179.13	11870.56	10202.66	-10203.13	-45.99	0.14	430223.40	666715.11	32.181653	-103.794472	10203.23	180.26
Projection to Bit [240' FSL, 176' FWL]	21770.00	89.41	179.13	11870.82	10228.65	-10229.12	-45.59	0.00	430197.40	666715.51	32.181582	-103.794471	10229.22	180.26

Survey Type: Def Survey

Survey Error Model: ISCWSA Rev 0 *** 3-D 95.000% Confidence 2.7955 sigma
Survey Program:

Description	Part	MD From (ft)	MD To (ft)	EOU Freq (ft)	Hole Size	Casing Diameter (in)	Survey Tool Type	Borehole / Survey
	1	0.000	33.000	1/96.425	14.750	11.750	NAL_MWD_IFR1-Depth Only	XTO Poker Lake Unit 17 TWR 707H / XTO Poker Lake Unit 17
	1	33.000	33.000	Act Stns	14.750	11.750	NAL_MWD_IFR1-Depth Only	XTO Poker Lake Unit 17 TWR 707H / XTO Poker Lake Unit 17
	1	33.000	894.000	Act Stns	14.750	11.750	NAL_MWD_IFR1	XTO Poker Lake Unit 17 TWR 707H / XTO Poker Lake Unit 17
	1	894.000	10974.000	Act Stns	9.875	7.625	NAL_MWD_IFR1+MS	XTO Poker Lake Unit 17 TWR 707H / XTO Poker Lake Unit 17
Schlumberger / xBolt G2	1	10974.000	21770.000	Act Stns	6.750	5.500	NAL_MWD_IFR1+MS	XTO Poker Lake Unit 17 TWR 707H / XTO Poker Lake Unit 17

...XTO Poker Lake Unit 17 TWR 707H/XTO Poker Lake Unit 17 TWR 707H 0 to 21770' MD



Measurement While Drilling (MWD) Survey Certification

State of: New Mexico
County of: Eddy

I, Adam Wentworth, certify that; I am employed by Geoguidance Drilling Services, Inc.; that I did on the day(s) of 7/9/2020 through 03 Aug 2020 conduct or supervise the taking of a directional MWD survey from a depth of 149 feet to a depth of 10,905 feet; that the data is true, correct, complete and within the limitations of the tool as set forth by Geoguidance Drilling Services, Inc.; that I am authorized and qualified to make this report; that this survey was conducted at the request of XTO Energy Inc. for POKER LAKE UNIT 17 TWR #707H A.P.I. No. 30-015-46659 in Eddy County, New Mexico Field; and that I have reviewed this report and find that it conforms to the principles and procedures as set forth by Geoguidance Drilling Services, Inc.

Survey Instrument Type

MWD

A handwritten signature in black ink, appearing to read "Adam Wentworth", is written over a horizontal line.

Adam Wentworth
MWD Coordinator
Geoguidance Drilling
Services, Inc.

12/25/2021

Well Name: POKER LAKE UNIT 17
TWR**Well Location:** T24S / R31E / SEC 20 /
NENE / 32.209822 / -103.794641**County or Parish/State:** EDDY /
NM**Well Number:** 707H**Type of Well:** OIL WELL**Allottee or Tribe Name:****Lease Number:** NMLC0061705B,
NMLC061705B**Unit or CA Name:** POKER LAKE**Unit or CA Number:**
NMNM071016X, NMNM71016X**US Well Number:** 3001546659**Well Status:** Drilling Well**Operator:** XTO PERMIAN
OPERATING LLC**Subsequent Report****Sundry ID:** 2636450**Type of Submission:** Subsequent Report**Type of Action:** Drilling Operations**Date Sundry Submitted:** 09/28/2021**Time Sundry Submitted:** 05:45**Date Operation Actually Began:** 07/27/2021

Actual Procedure: XTO PERMIAN OPERATING LLC respectfully submits this sundry notice to report the completion operations of the referenced well. KOP @ depth 11,098 ft. PBTD = 21,753 ft. 6/20/21 Run RCB/GR/CCL 6/29/21 Pressure test 5.5 in csg to 8,590 psi for 30min test good, open sleeve. 7/27/21 Perf and frac 47 stages, 1128 total shots, from 12,237 to 21,654 using 479,342 bbls of fluid and 23,383,680 lbs Proppant. Tag and drill out plugs. 8/19/21 Run 2-7/8 L80 6.5# tubing set at 11,226 ft. 8/19/21 Packer setting depth 11,211 ft.

Well Name: POKER LAKE UNIT 17
TWR

Well Location: T24S / R31E / SEC 20 /
NENE / 32.209822 / -103.794641

County or Parish/State: EDDY /
NM

Well Number: 707H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMLC0061705B,
NMLC061705B

Unit or CA Name: POKER LAKE

Unit or CA Number:
NMNM071016X, NMNM71016X

US Well Number: 3001546659

Well Status: Drilling Well

Operator: XTO PERMIAN
OPERATING LLC

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: CASSIE EVANS

Signed on: SEP 28, 2021 05:45 PM

Name: XTO PERMIAN OPERATING LLC

Title: Regulatory Analyst

Street Address: 6401 Holiday Hill Road, Bldg 5

City: Midland

State: TX

Phone: (432) 218-3671

Email address: CASSIE.EVANS@EXXONMOBIL.COM

Field Representative

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: Jonathon W Shepard

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972

BLM POC Email Address: jshepard@blm.gov

Disposition: Accepted

Disposition Date: 11/10/2021

Signature: Jonathon Shepard

Submit To Appropriate District Office Two Copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505				Form C-105 Revised April 3, 2017												
WELL COMPLETION OR RECOMPLETION REPORT AND LOG																		
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)								5. Lease Name or Unit Agreement Name POKER LAKE UNIT 17 TWR										
								6. Well Number: 707H										
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER																		
8. Name of Operator XTO PERMIAN OPERATING LLC.						9. OGRID 373075												
10. Address of Operator 6401 HOLIDAY HILL RD BLDG #5, MIDLAND TX 79707						11. Pool name or Wildcat PURPLE SAGE;WOLFCAMP (GAS)												
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County								
Surface:	A	20	24S	31E		95	North	1035	East	Eddy								
BH:	P	20	24S	31E		241	South	1144	East	Eddy								
13. Date Spudded 7/10/2020	14. Date T.D. Reached 9/21/2020		15. Date Rig Released 9/24/2020		16. Date Completed (Ready to Produce) 10/15/2021			17. Elevations (DF and RKB, RT, GR, etc.) 3523 GL										
18. Total Measured Depth of Well 21,770			19. Plug Back Measured Depth 21,753		20. Was Directional Survey Made? Yes			21. Type Electric and Other Logs Run CBL										
22. Producing Interval(s), of this completion - Top, Bottom, Name 12,237 - 21,654 PURPLE SAGE;WOLFCAMP (GAS)																		
23. CASING RECORD (Report all strings set in well)																		
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED								
11 3/4"		54.0		886'		14 3/4"		911										
7 5/8"		29.7		10,954'		9 7/8"		2690										
5.5 "		23.0		21,755'		6 3/4"		925										
24. LINER RECORD						25. TUBING RECORD												
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN		SIZE	DEPTH SET	PACKER SET										
						2 7/8"	11,226	11,211										
26. Perforation record (interval, size, and number) 12,237 - 21,654, 2spf, 1128 Total Shots 47 stages						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>DEPTH INTERVAL</th> <th>AMOUNT AND KIND MATERIAL USED</th> </tr> <tr> <td>12,237 - 21,654</td> <td>479,342 bbl fluid + 23,383,680 lbs proppant</td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> </table>					DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED	12,237 - 21,654	479,342 bbl fluid + 23,383,680 lbs proppant				
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED																	
12,237 - 21,654	479,342 bbl fluid + 23,383,680 lbs proppant																	
28. PRODUCTION																		
Date First Production 11/16/21		Production Method (<i>Flowing, gas lift, pumping - Size and type pump</i>)				Well Status (<i>Prod. or Shut-in</i>) Producing												
Date of Test 11/17/21	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 1970	Gas - MCF 5554	Water - Bbl. 4974	Gas - Oil Ratio 2,819											
Flow Tubing Press. 637	Casing Pressure 336	Calculated 24-Hour Rate	Oil - Bbl. 1970	Gas - MCF 5554	Water - Bbl. 4974	Oil Gravity - API - (<i>Corr.</i>)												
29. Disposition of Gas (<i>Sold, used for fuel, vented, etc.</i>) Sold								30. Test Witnessed By										
31. List Attachments C-104 NW, C-102 & Supplement , Directional Survey (Log uploaded to NMOCD)																		
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.								33. Rig Release Date:										
34. If an on-site burial was used at the well, report the exact location of the on-site burial:																		
Latitude				Longitude				NAD83										
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief Printed Signature <u>Cassie Evans</u> Name Cassie Evans Title Regulatory Analyst Date 12/25/2021 E-mail Address cassie.evans@xtoenergy.com																		

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt 964'	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt 4,164'	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand 4,364'	T. Morrison	
T. Drinkard	T. Bone Springs	T. Todilto	
T. Abo	T. Rustler 604'	T. Entrada	
T. Wolfcamp 11,570'	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

From	To	Thickness In Feet	Lithology

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

03/19/2022

Well Name: POKER LAKE UNIT 17
TWR

Well Location: T24S / R31E / SEC 20 /
NENE / 32.209822 / -103.794641

County or Parish/State: EDDY /
NM

Well Number: 707H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMLC0061705B,
NMLC061705B

Unit or CA Name: POKER LAKE

Unit or CA Number:
NMNM071016X, NMNM71016X

US Well Number: 3001546659

Well Status: Producing Oil Well

Operator: XTO PERMIAN
OPERATING LLC

Notification

Sundry ID: 2662559

Type of Submission: Notification

Type of Action: First Production

Date Sundry Submitted: Mar 17, 2022

Time Sundry Submitted: 7:39:41 AM

First Production Date: Nov 16, 2021

Wellbore Code

Completion Code

US Well Number: 3001546659

00

X1

First Production Remarks: Ready Date 11/15/2021
First prod date 11/16/2021

Disposition: Accepted

Accepted Date: 03/17/2022

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 136095

ACKNOWLEDGMENTS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 136095
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/oed/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 136095

CONDITIONS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 136095
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
crystal.walker	None	10/20/2025