Cestififity Copy Po Appropriate District 28 PM	State of New Mexico	Form C-103 <sup>1</sup>		
Office District I – (575) 393-6161	Energy, Minerals and Natural Resources	Revised July 18, 2013		
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.		
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-025-24111		
<u>District III</u> – (505) 334-6178	1220 South St. Francis Dr.	5. Indicate Type of Lease		
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505	STATE X FEE		
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	Santa 1 C, 14W 07505	6. State Oil & Gas Lease No.		
87505				
	AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name		
	TO DRILL OR TO DEEPEN OR PLUG BACK TO A			
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		NORTH VACUUM ABO EAST UNIT		
1. Type of Well: Oil Well Gas V	Well Other INJECTION	8. Well Number 003		
2. Name of Operator		9. OGRID Number		
CROSS TIMBERS ENERGY, LLC		298299		
3. Address of Operator		10. Pool name or Wildcat		
	ST, FORT WORTH, TX 76102	VACUUM; ABO, NORTH		
4. Well Location				
		feet from theWline		
Section 07	1 2	MPM County LEA		
11.	Elevation (Show whether DR, RKB, RT, GR, etc.	.)		
	4012' GL			
12. Check Appro	opriate Box to Indicate Nature of Notice	, Report or Other Data		
NOTICE OF INTEN	ITION TO:	SSEQUENT REPORT OF:		
	JG AND ABANDON   REMEDIAL WOR			
		RILLING OPNS. P AND A		
	ILTIPLE COMPL CASING/CEMEN			
DOWNHOLE COMMINGLE	ETIT LE COMIT L' GAGING/GEMEN	U 30B		
CLOSED-LOOP SYSTEM				
OTHER:	☐ OTHER:			
	operations. (Clearly state all pertinent details, ar			
	SEE RULE 19.15.7.14 NMAC. For Multiple Co	ompletions: Attach wellbore diagram of		
proposed completion or recomple	etion.			
-	959593 and cBZL2521959594, Cross Timbers E	nergy requests approval of the following		
procedure:				
1) Release packer and POOH - s				
2) MIRU wireline – run CBL/CCLfrom 8,600' to Surface				
Run Casing Inspection Log 80				
4) RBIH w/ Tbg String and redre				
	depth – 8,580'. Pressure test backside.	salvan Cantaat NMOCD & min MIT taat		
6) Release from packer. Circula per OCD representative's directive	te backside with packer fluid. Latch back into pa	icker. Contact NWOCD & run WITT test		
per OCD representative's directive				
Spud Date:	Rig Release Date:			
I hereby certify that the information above	is true and complete to the best of my knowledge	ge and belief.		
SIGNATURE Counia Blaula	TITLE REGULATORY ANA	LYST DATE 10/03/2025		
SIGNATURE CALLE	ck title regulatory ana	LISIDAIL_10/03/2023		
	OCK E-mail address: _cblaylock@txopartn			
For State Use Only				
	~L 11711			
APPROVED BY:	TITLE Staff Manu	gerDATE11/5/2025		
Conditions of Approval (if any):		-		

Well: North Vacuum Abo East Unit #3

**API**: 30-025-24111

North Vacuum Abo East Unit 3:

Elevation:

Spud: 4/14/72

Complete Well: 5/13/72 **Abo: Initial Completion** 

**5/72:** Perforate 8657, 62-63, 95-97, 8704-06, 15-18, 40, 47-52, 57-59 (1 JSPF, 23 shots. Acidize w/10,000 gals 15% NEA with 25 RNCBS.

4011.7 GL

IP: 124 BO/6 BW/121 MCF.

**5/79: Conv to WIW:** Pump 500 gals 15% HCL+1000 gals Xylene+ 6 gals Adafoam. Pull prod equip. TIH w/ Bare Injection tubing and Baker NB packer . Set packer at 8600. Acidize with 5,000 gals of 15% FEA, 5.5 BPM, 4200 psi. Initial injection: 150 BWIPD/0 psi.

6/98: Pull and repair tubing

5/07: POH w/ 2 3/8" bare steel tubing & Baker Lok-Set packer, RIH w/packer picker and mill over permanent packer, tag fill, no perfs covered, RIH w/ 2 3/8" EUE 8rd J-55 IPC tbg & 5 ½" Baker Lok-set packer, Set packer @ 8580', Circ packer fluid, Run chart for 30 min, Held OK, RWTI on 5/31/07

05/25: POOH w/ tbg & pkr. Scan and replace tubing as needed. RTI

12 3/4" 34# in 17 ½" hole. Set at 296'. Cemented with 450 sx. H Cement Circulated

8-5/8" 28# in 11" hole Set at 3220'. Cemented with 1400 sx. Cmt Circulated

## **Tubing/Packer Detail: (5/15/25)**

2-3/8" 4.6# EUE 8RD J-55 IPC & bare tbg with Arrowset 1X Packer @ 8580'

8657, 62-63, 95-97, 8704-06, 15-18, 40, 47-52, 57-59 (1 JSPF, 23 shots)

Abo Perfs:

5-½",15.5# and 17# in 7-7/8" hole Set at 8850'. Cemented with 2300 sx. Cmt Circulated

**PBTD** 

8850'

TD

Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

## State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Action 512160

## **CONDITIONS**

Operator:	OGRID:
CROSS TIMBERS ENERGY, LLC	298299
400 West 7th Street	Action Number:
Fort Worth, TX 76102	512160
	Action Type:
	[C-103] NOI Workover (C-103G)

## CONDITIONS

Created By	Condition	Condition Date
gcordero	Pressure test required accordance with 19.15.25.14 NMAC.	11/5/2025
gcordero	if the workover requires tubing change same tube size shall be replaced as prescribed by the respective order and the packer shall not be set more than 100 ft above the top of the injection interval.	11/5/2025