

Submit 1 Copy To Appropriate District Office  
 District I – (575) 393-6161  
 1625 N. French Dr., Hobbs, NM 88240  
 District II – (575) 748-1283  
 811 S. First St., Artesia, NM 88210  
 District III – (505) 334-6178  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV – (505) 476-3460  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources  
 OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

Form C-103 Revised August 1, 2011

|   |
|---|
| WELL API NO.<br>30-025-38576 and 30-025-42139   |
| 5. Indicate Type of Lease<br>STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No.<br>V07530-0001   |
| 7. Lease Name or Unit Agreement Name<br>Linam AGI   |
| 8. Wells Number 1 and 2   |
| 9. OGRID Number 36785   |
| 10. Pool name or Wildcat<br>Wildcat   |

|  |  |
|--|--|
| SUNDRY NOTICES AND REPORTS ON WELLS<br>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) |  |
| 1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other  |  |
| 2. Name of Operator<br>DCP Operating Company, LP   |  |
| 3. Address of Operator<br>6900 E. Layton Ave, Suite 900, Denver CO 80237   |  |
| 4. Well Location<br>Unit Letter K; 1980 feet from the South line and 1980 feet from the West line<br>Section 30 Township 18S Range 37E NMPM County Lea   |  |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.)<br>3736 GR  |  |

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

|  |   |  |  |
|--|---|--|--|
| NOTICE OF INTENTION TO:                        |   | SUBSEQUENT REPORT OF:                            |  |
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/>           | ALTERING CASING <input type="checkbox"/>   |
| TEMPORARILY ABANDON <input type="checkbox"/>   | CHANGE PLANS <input type="checkbox"/>     | COMMENCE DRILLING OPNS. <input type="checkbox"/> | P AND A <input type="checkbox"/>   |
| PULL OR ALTER CASING <input type="checkbox"/>  | MULTIPLE COMPL <input type="checkbox"/>   | CASING/CEMENT JOB <input type="checkbox"/>       | OTHER: Monthly Report pursuant to Workover C-103 <input checked="" type="checkbox"/> |
| OTHER: <input type="checkbox"/>                |   |  |  |

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

## Report for the Month ending June 30, 2025 Pursuant to Workover C-103 for Linam AGI #1 and AGI #2

This is the 158<sup>th</sup> monthly submittal of data as agreed between DCP and OCD relative to injection pressure, TAG temperature, casing annulus pressure, and bottom hole data for Linam AGI #1. Since the data for both wells provide the best overall picture of the performance of the AGI system, the data for both wells are analyzed and presented herein even though that analysis is required only on a quarterly basis for AGI #2.

All flow was directed to AGI #1 for the entirety of June. Injection parameters being monitored for AGI #1 (used exclusively for the month) were as follows (Figures 1, 2, 3, 4): Average Injection Rate: 171,889 scf/hr, Average TAG Injection Pressure: 1,499 psig, Average TAG Temperature: 110°F, Average Annulus Pressure: 5 psig, Average Pressure Differential: 1,494 psig. Bottom hole (BH) sensors provided the average BH pressure for the entire period of 4,258 psig and BH temperature of 136 °F (Figures 8 and 9).


The recorded injection parameters for AGI #2 for the month were: Average Injection Rate 0 scf/hr (No flow to AGI #2 for the month), Average Injection Pressure: 1,122 psig, Average TAG Temperature: 92°F, Average Annulus Pressure: 292 psig, average Pressure Differential: 830 psig (Figures 5, 6, 7). The wells responded positively to the switchover in flow to AGI #1, and all injection parameters show the correlative behavior of annular pressure with flowrate and injection pressure with temperature, confirming the wells are functioning properly.


The Linam AGI #1 and AGI #2 wells are serving as a safe, effective, and environmentally friendly system to dispose of, and permanently sequester, Class II wastes consisting of H<sub>2</sub>S and CO<sub>2</sub>. The Linam AGI Facility permanently sequestered 5,018 Metric Tons of CO<sub>2</sub> for this month (Figure 10). The two wells provide the required redundancy to the plant that allows for operation with disposal to either or both wells. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE Consultant to DCP Operating Company, LP/ Geolex, Inc. DATE 7/7/2025  
 Type or print name Alberto A. Gutierrez, RG E-mail address: [aag@geolex.com](mailto:aag@geolex.com) PHONE: 505-842-8000


**For State Use Only**

APPROVED BY: \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
 Conditions of Approval (if any): \_\_\_\_\_


**Figure #1: Linam AGI #1 and #2 Combined TAG Injection Flow Rate**


**Figure #2: Linam AGI #1 Surface TAG Injection Pressure and Annular Pressure**

**Figure #3: Linam AGI #1 TAG Injection Pressure, Casing Annulus Pressure and TAG Injection Temperature**




**Figure #4: Linam AGI #1 TAG Injection Pressure and Casing Annular Pressure Differential**





**Figure #5: Linam AGI #2 Injection Pressure, Rate and Casing Annulus Pressure**

**Figure #6: Linam AGI #2 TAG Injection Pressure, Casing Annulus Pressure and TAG Injection Temperature**




**Figure #7: Linam AGI #2 TAG Injection Pressure and Casing Annular Pressure Differential (psig)**




**Figure #8: Linam AGI #1 Bottom Hole Pressure and Temperature**

**Figure #9: Linam AGI #1 Surface Injection Pressure and Bottom Hole Pressure**




## CO2 Sequestered (metric tons)

**Figure #10: Linam AGI Facility Daily Metric Tons of Carbon Sequestered**

**DCP LINAM AGI #1**  
**WELLBORE SCHEMATIC (WORKOVER)**

**Location:** 1980' FSL, 1980' FWL  
**STR:** 30-T18S-R37E  
**County, St.:** LEA, NEW MEXICO

**SURFACE CASING:**

13 3/8", 48.00#/ft, H40, STC at 530'

**INTERMEDIATE CASING:**

9 5/8", 40.00#/ft, J55, LTC at 4212'

**PRODUCTION CASING:**

7", 26.00#/ft, L80, STC at 9200'

PBTD = 9137'

**TUBING:**

Subsurface Safety Valve at 250 ft

3 1/2", 9.2#/ft, L80, Hunting SLF to 8304'

3 1/2", 9.2 #/ft, G3 CRA, VAMTOP from 8302' to 8602'

3 1/2", 9.2 #/ft., G3 CRA, VAMTOP 20'-30' between packers

**PACKER:**

Permanent Production Packer (2)

Upper Packer Placement Subject to Pipe Scanner Results  
of the 7" Casing

Adjustable Choke


Check valve

**PERFORATIONS:****Primary Target**      **Secondary Target**

|                    |                  |
|--------------------|------------------|
| Lower Bone Springs | Brushy Canyon    |
| 8710' - 8730'      | 5000' to 5300'   |
| 8755' - 8765'      | (Not perforated) |
| 8780' - 8795'      |                  |
| 8780' - 8890'      |                  |
| 8925' - 8930'      |                  |
| 8945' - 8975'      |                  |
| 8985' - 9000'      |                  |
| 9045' - 9085'      |                  |
|                    |                  |
|                    |                  |
|                    |                  |
|                    |                  |

Well Name: Linam AGI #2  
 API: 30-025-42139  
 STR: Sec. 30, T18S-R37E  
 County, St.: Lea County, New Mexico

Footage: 2120 FSL & 2120 FWL  
 Well Type: AGI - Wolfcamp  
 KB/GL: 3763'/3738  
 Lat, Long: 32.715837, -103.293543



Sante Fe Main Office  
Phone: (505) 476-3441

General Information  
Phone: (505) 629-6116

Online Phone Directory  
<https://www.emnrd.nm.gov/ocd/contact-us>

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 490447

**CONDITIONS**

|   |                |
|---|----------------|
| Operator:<br><br>DCP OPERATING COMPANY, LP<br>2331 Citywest Blvd<br>Houston, TX 77042 | OGRID:         |
|   | 36785          |
|   | Action Number: |
|   | 490447         |

Action Type:  
[C-103] Sub. General Sundry (C-103Z)

**CONDITIONS**

| Created By     | Condition | Condition Date |
|----------------|-----------|----------------|
| anthony.harris | None      | 1/6/2026       |