

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

| | | |
|---|--|--|
| Well Name: DICK & DONNA 2729 FED COM | Well Location: T22S / R28E / SEC 26 / SWNW / 32.3663203 / -104.062892 | County or Parish/State: EDDY / NM |
| Well Number: 202H | Type of Well: OIL WELL | Allottee or Tribe Name: |
| Lease Number: NMNM26684A | Unit or CA Name: | Unit or CA Number: |
| US Well Number: 3001557583 | Operator: MATADOR PRODUCTION COMPANY | |

Notice of Intent

Sundry ID: 2892833

Type of Submission: Notice of Intent

Type of Action: APD Change

Date Sundry Submitted: 01/26/2026

Time Sundry Submitted: 02:27

Date proposed operation will begin: 01/26/2026

Procedure Description: BLM Bond # NMB001079 & Surety Bond # RLB0015172 Matador requests the option to amend the well design of the Dick & Donna 2729 Fed Com #202H and make the following changes to the current APD:
- Option to drill intermediate hole size of 8.75" OH -Option to run intermediate casing type of 7-5/8" MO-FXL - Cement volumes will be adjusted accordingly to reflect change of intermediate hole size

NOI Attachments

Procedure Description

Dick__Donna_2729_Fed_Com_202H_Sundry_Info_20260126142703.pdf

Dick__Donna_2729_Fed_Com_202H_Csg_Specs_7.625in_29.7lb_MO_FXL_20260126141525.pdf

Well Name: DICK & DONNA 2729 FED COM

Well Location: T22S / R28E / SEC 26 / SWNW / 32.3663203 / -104.062892

County or Parish/State: EDDY / NM

Well Number: 202H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM26684A

Unit or CA Name:

Unit or CA Number:

US Well Number: 3001557583

Operator: MATADOR PRODUCTION COMPANY

Conditions of Approval

Additional

Dick__Donna_2729_Fed_Com_202H_Casing_Table_Spec_20260205140924.pdf

Dick__Donna_2729_Fed_Com_202H_Sundry_Info_20260205140924.pdf

DICK__DONNA_2729_FED_COM_202H_Sundry_2892833_COA_20260205135042.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: DEBBIE CREED

Signed on: JAN 26, 2026 02:14 PM

Name: MATADOR PRODUCTION COMPANY

Title: BLM Tech

Street Address: 5400 LBJ FREEWAY

City: DALLAS

State: TX

Phone: (972) 371-5426

Email address: DEBBIE.CREED@MATADORRESOURCES.COM

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: CHRISTOPHER WALLS

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752342234

BLM POC Email Address: CWALLS@BLM.GOV

Disposition: Approved

Disposition Date: 02/05/2026

Signature: Chris Walls

Form 3160-5
(October 2024)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0220
Expires: October 31, 2027

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2

7. If Unit of CA/Agreement, Name and/or No.

1. Type of Well

Oil Well Gas Well Other

8. Well Name and No.

2. Name of Operator

9. API Well No.

3a. Address

3b. Phone No. (include area code)

10. Field and Pool or Exploratory Area

4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)

11. Country or Parish, State

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

| TYPE OF SUBMISSION | TYPE OF ACTION | | | |
|---|---|---|--|---|
| <input type="checkbox"/> Notice of Intent | <input type="checkbox"/> Acidize | <input type="checkbox"/> Deepen | <input type="checkbox"/> Production (Start/Resume) | <input type="checkbox"/> Water Shut-Off |
| <input type="checkbox"/> Subsequent Report | <input type="checkbox"/> Alter Casing | <input type="checkbox"/> Hydraulic Fracturing | <input type="checkbox"/> Reclamation | <input type="checkbox"/> Well Integrity |
| <input type="checkbox"/> Final Abandonment Notice | <input type="checkbox"/> Casing Repair | <input type="checkbox"/> New Construction | <input type="checkbox"/> Recomplete | <input type="checkbox"/> Other |
| | <input type="checkbox"/> Change Plans | <input type="checkbox"/> Plug and Abandon | <input type="checkbox"/> Temporarily Abandon | |
| | <input type="checkbox"/> Convert to Injection | <input type="checkbox"/> Plug Back | <input type="checkbox"/> Water Disposal | |

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)

Title

Signature

Date

THE SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

0. SHL: SWNW / 1698 FNL / 1231 FWL / TWSP: 22S / RANGE: 28E / SECTION: 26 / LAT: 32.3663203 / LONG: -104.062892 (TVD: 0 feet, MD: 0 feet)
PPP: SENE / 2312 FNL / 330 FEL / TWSP: 22S / RANGE: 28E / SECTION: 27 / LAT: 32.3646308 / LONG: -104.0679661 (TVD: 9670 feet, MD: 10109 feet)
PPP: NENW / 2312 FNL / 0 FEL / TWSP: 22S / RANGE: 28E / SECTION: 28 / LAT: 32.3646406 / LONG: -104.084031 (TVD: 9670 feet, MD: 15069 feet)
PPP: NESW / 2313 FNL / 1317 FWL / TWSP: 22S / RANGE: 28E / SECTION: 28 / LAT: 32.364647 / LONG: -104.0968034 (TVD: 9670 feet, MD: 19013 feet)
BHL: SWNW / 2248 FNL / 340 FWL / TWSP: 22S / RANGE: 28E / SECTION: 29 / LAT: 32.3646544 / LONG: -104.1167849 (TVD: 9670 feet, MD: 25182 feet)

CONFIDENTIAL

Casing Table Specification Sheet

Dick & Donna 2729 Fed Com 202H
SHL: 1698' FNL & 1231' FWL Section 26
BHL: 2248' FNL & 340' FWL Section 29
Township/Range: 22S 28E
Elevation Above Sea Level: 3116

| String | Hole Size (in) | Set MD (ft) | Set TVD (ft) | Casing Size (in) | Wt. (lb/ft) | Grade | Joint | Collapse | Burst | Tension |
|----------------|----------------|-------------|--------------|------------------|-------------|-------|----------------|----------|-------|---------|
| Surface | 17.5 | 0 - 350 | 0 - 350 | 13.375 | 54.5 | J-55 | BUTT | 1.125 | 1.125 | 1.8 |
| Intermediate 1 | 8.75 | 0 - 9109 | 0 - 8997 | 7.625 | 29.7 | P-110 | MO-FXL | 1.125 | 1.125 | 1.8 |
| Production | 6.75 | 0 - 25182 | 0 - 9670 | 5.5 | 20 | P-110 | Hunting TLW-SC | 1.125 | 1.125 | 1.8 |

Drill Plan

Dick & Donna 2729 Fed Com 202H
SHL: 1698' FNL & 1231' FWL Section 26
BHL: 2248' FNL & 340' FWL Section 29
Township/Range: 22S 28E
Elevation Above Sea Level: 3116

Sundry Request

Matador requests the option to amend the well design of the Dick & Donna 2729 Fed Com #202H and make the following changes to the current APD:

- Option to drill intermediate hole size of 8.75" OH
- Option to run intermediate casing type of 7-5/8" MO-FXL
- Cement volumes will be adjusted accordingly to reflect change of intermediate hole size

Drilling Operation Plan

Proposed Drilling Depth: 25182' MD / 9670' TVD

Type of well: Horizontal well, no pilot hole

Permitted Well Type: Oil

Geologic Name of Surface Formation: Quaternary Deposits

KOP Lat/Long (NAD83): 32.3646301 N / -104.0670592 W

TD Lat/Long (NAD83): 32.3646544 N / -104.1167849 W

1. Estimated Tops

| Formation | MD (ft) | TVD (ft) | Thickness (ft) | Lithology | Resource |
|----------------------|---------------|--------------|----------------|------------------|------------------------|
| Rustler | 289 | 289 | 173 | Anhydrite | Barren |
| Salado (Top of Salt) | 462 | 462 | 800 | Salt | Barren |
| Castile | 1,262 | 1,262 | 1,448 | Salt | Barren |
| Lamar (Base of Salt) | 2,719 | 2,710 | 28 | Salt | Barren |
| Bell Canyon | 2,747 | 2,738 | 835 | Sandstone | Oil/Natural Gas |
| Cherry Canyon | 3,590 | 3,573 | 1,205 | Sandstone | Oil/Natural Gas |
| Brushy Canyon | 4,807 | 4,778 | 1,432 | Sandstone | Oil/Natural Gas |
| Bone Spring Lime | 6,253 | 6,210 | 514 | Carbonate | Oil/Natural Gas |
| Avalon Shale | 6,772 | 6,724 | 293 | Shale | Oil/Natural Gas |
| 1st Bone Spring Carb | 7,067 | 7,017 | 264 | Carbonate | Oil/Natural Gas |
| 1st Bone Spring Sand | 7,334 | 7,281 | 268 | Sandstone | Oil/Natural Gas |
| 2nd Bone Spring Carb | 7,605 | 7,549 | 489 | Carbonate | Oil/Natural Gas |
| 2nd Bone Spring Sand | 8,098 | 8,038 | 358 | Sandstone | Oil/Natural Gas |
| 3rd Bone Spring Carb | 8,460 | 8,396 | 285 | Carbonate | Oil/Natural Gas |
| 3rd Bone Spring Sand | 8,747 | 8,681 | 910 | Sandstone | Oil/Natural Gas |
| KOP | 9,209 | 9,097 | - | Sandstone | Oil/Natural Gas |
| Wolfcamp A | 9,759 | 9,591 | 441 | Shale | Oil/Natural Gas |
| TD | 25,182 | 9,670 | - | Shale | Oil/Natural Gas |

2. Notable Zones

Wolfcamp A is the goal. All perforations will be within the setback requirements as prescribed or permitted by the New Mexico Oil Conservation Division. OSE estimated ground water depth at this location is 103'.

3. Pressure Control

Equipment

A 12,000' 5000-psi BOP stack consisting of 3 rams with 2 pipe rams, 1 blind ram, and one annular preventer will be utilized below surface casing to TD. See attachments for BOP and choke manifold diagrams.

An accumulator complying with Title 43 CFR 3172 requirements for the pressure rating of the BOP stack will be present. A rotating head will also be installed as needed.

Testing Procedure

BOP will be inspected and operated as required in Title 43 CFR 3172. Kelly cock and sub equipped with a full opening valve sized to fit the drill pipe and collars will be available on the rig floor in the open position.

A third party company will test the BOPs.

After setting surface casing, a minimum 5M BOPE system will be installed. Test pressures will be 250 psi low and 5000 psi high with the annular preventer being tested to 250 psi low and 2500 psi high before drilling below surface shoe. In the event that the rig drills multiple wells on the pad and any seal subject to test pressures are broken, a full BOP test will be performed when the rig returns and the 5M BOPE system is re-installed.

Variance Request

Matador requests a variance to have the option of running a multi-bowl wellhead assembly for setting the Intermediate 1 and Production Strings. The BOPs will not be tested again unless any flanges are separated.

Matador requests a variance to drill this well using a co-flex line between the BOP and choke manifold. Certification for proposed co-flex hose is attached. The hose is not required by the manufacturer to be anchored. If the specific hose is not available, then one of equal or higher rating will be used.

Matador requests a variance to have the option of batch drilling this well with other wells on the same pad. In the event that this well is batch drilled, the wellbore will be secured with a blind flange of like pressure. When the rig returns to this well and BOPs are installed, the operator will perform a full BOP test.

Matador request the option to offline cement surface casing. The "Offline Cementing - Surface Procedure" is attached for review. No changes in cement program are necessary.

Matador request the option to offline cement intermediate casing. The "Offline Cementing - Intermediate Casing" Procedure is attached for review. No changes in cement program are necessary.

Matador request the option to break test the BOP during batch drilling operations. The "Modified BOP Testing Procedure for Batch Drilling" Procedure is attached for review.

Drill Plan**4. Casing & Cement**

All casing will be API and new. See attached casing assumption worksheet.

| String | Hole Size (in) | Set MD (ft) | Set TVD (ft) | Casing Size (in) | Wt. (lb/ft) | Grade | Joint | Collapse | Burst | Tension |
|----------------|----------------|-------------|--------------|------------------|-------------|-------|----------------|----------|-------|---------|
| Surface | 17.5 | 0 - 350 | 0 - 350 | 13.375 | 54.5 | J-55 | BUTT | 1.125 | 1.125 | 1.8 |
| Intermediate 1 | 8.75 | 0 - 9109 | 0 - 8997 | 7.625 | 29.7 | P-110 | MO-FXL | 1.125 | 1.125 | 1.8 |
| Production | 6.75 | 0 - 25182 | 0 - 9670 | 5.5 | 20 | P-110 | Hunting TLW-SC | 1.125 | 1.125 | 1.8 |

- All casing strings will be tested in accordance with Title 43 CFR 3172.7(b)(8)

- Rustler top will be validated via drilling parameters (i.e. reduction in ROP) and surface casing setting depth revised accordingly if needed

- All non-API joint connections will be of like or greater quality, and as run specification sheets will be on location for review

Variance Request

Matador request a variance to wave the centralizer requirement for the 7-5/8" casing and the 5-1/2" SF/Flush casing in the 6-3/4" hole.

If a DV tool is used, depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above the current shoe. Lab reports with the 500 psi compressive strength time for the cement will be onsite for review. Option to cancel 2nd stage cement if cement is circulated on 1st stage.

Matador request a variance to utilize a surface setting rig. If this is used, Matador request the option to drill either 17.5" or 20" surface hole, cement volumes will be adjusted accordingly.

Primary Cement Design - DV/Packer 2-Stage Cement

| String | Type | Sacks | Yield | Cu. Ft. | Weight | Percent Excess | Top of Cement (ft) | Class | Blend |
|------------------------------|------------|-------|-------|---------|--------|----------------|--------------------|-------|--|
| Surface | Lead | 30 | 1.72 | 49 | 13.5 | 50% | 0 | C | 5% NaCl + LCM |
| | Tail | 250 | 1.38 | 347 | 14.8 | 50% | 50 | C | 5% NaCl + LCM |
| Intermediate 1 w/ DV @ 2760' | Stg 2 Tail | 260 | 1.78 | 459 | 13.5 | 10% | 0 | A/C | 5% NaCl + LCM |
| | Stg 1 Lead | 750 | 1.84 | 1373 | 12.5 | 50% | 0 | A/C | Bentonite + 1% CaCl ₂ + 8% NaCl + LCM |
| | Stg 1 Tail | 130 | 1.33 | 167 | 14.8 | 50% | 8109 | A/C | 5% NaCl + LCM |
| Production | Tail | 1260 | 1.35 | 1697 | 13.2 | 25% | 8909 | A/C | Fluid Loss + Dispersant + Retarder + LCM |

5. Mud Program

An electronic Pason mud monitoring system complying with Title 43 CFR 3172 will be used. All necessary mud products (barite, bentonite, LCM) for weight addition and fluid loss control will be on location at all times. Mud program is subject to change due to hole conditions.

Drill Plan

| Hole Section | Hole Size (in) | Mud Type | Interval MD (ft) | Density (lb/gal) | Viscosity | Fluid Loss |
|----------------|----------------|-----------------------|------------------|------------------|-----------|------------|
| Surface | 17.5 | Spud Mud | 0 - 350 | 8.4 - 8.8 | 28-30 | NC |
| Intermediate 1 | 8.75 | Diesel Brine Emulsion | 350 - 9109 | 8.8 - 9.7 | 28-30 | NC |
| Production | 6.75 | OBM | 9109 - 25182 | 9.6 - 11.7 | 30-55 | <20 |

6. Cores, Test, & Logs

No core or drill stem test is planned.

No electric logs are planned at this time. GR will be collected through the MWD tools from Intermediate casing to TD. CBL with CCL will be run as far as gravity will let it fall to top of curve. We will be running a Neutron log on one of the wells on each pad.

7. Down Hole Conditions

No abnormal pressure or temperature is expected. Bottom hole pressure is 5883 psi. Maximum anticipated surface pressure is 3756 psi. Expected bottom hole temperature is 161 F.

In accordance with Title 43 CFR 3176, Matador does not anticipate that there will be enough H₂S from the surface to the Bone Spring formations to meet the BLM's minimum requirements for the submission of an "H₂S Drilling Operation Plan" or "Public Protection Plan" for the drilling and completion of this well. Since we have an H₂S safety package on all wells, attached is an "H₂S Drilling Operations Plan". Adequate flare lines will be installed off the mud/gas separator where gas may be flared safely. All personnel will be familiar with all aspects of safe operation of equipment being used.

Directional Anti-Collision Measures

Matador will be monitoring real time anti-collision while drilling these wells to maximize separation factor and minimize anti-collision concerns. Matador will also be performing a gyro survey on the Little Squaw 001 prior to spud of this well in order to maximize separation factor and minimize anti-collision concern against it. The Little Squaw 001 will also be shut in during drilling and completions operations to mitigate operational risk.

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

| | |
|-----------------------------|--|
| OPERATOR'S NAME: | MATADOR PRODUCTION COMPANY |
| WELL NAME & NO.: | DICK & DONNA 2729 FED COM 202H |
| APD ID: | 10400103528 |
| LOCATION: | Section 26, T.22 S., R.28 E. NMP. |
| COUNTY: | <input type="text" value="Eddy County, New Mexico"/> |

COA

| H ₂ S | <input type="radio"/> No | | <input checked="" type="radio"/> Yes | |
|----------------------------|---|---|---|--|
| Potash / WIPP | <input checked="" type="radio"/> None | <input type="radio"/> Secretary | <input type="radio"/> R-111-Q | <input type="checkbox"/> Open Annulus <input type="checkbox"/> WIPP |
| Cave / Karst | <input type="radio"/> Low | <input checked="" type="radio"/> Medium | <input type="radio"/> High | <input type="radio"/> Critical |
| Wellhead | <input type="radio"/> Conventional | <input checked="" type="radio"/> Multibowl | <input type="radio"/> Both | <input type="radio"/> Diverter |
| Cementing | <input type="checkbox"/> Primary Squeeze | <input type="checkbox"/> Cont. Squeeze | <input type="checkbox"/> EchoMeter | <input checked="" type="checkbox"/> DV Tool |
| Special Req | <input type="checkbox"/> Capitan Reef | <input type="checkbox"/> Water Disposal | <input checked="" type="checkbox"/> COM | <input type="checkbox"/> Unit |
| Waste Prev. | <input type="radio"/> Self-Certification | <input checked="" type="radio"/> Waste Min. Plan | <input type="radio"/> APD Submitted prior to 06/10/2024 | |
| Additional Language | <input checked="" type="checkbox"/> Flex Hose | <input type="checkbox"/> Casing Clearance | <input type="checkbox"/> Pilot Hole | <input checked="" type="checkbox"/> Break Testing |
| | <input type="checkbox"/> Four-String | <input checked="" type="checkbox"/> Offline Cementing | <input type="checkbox"/> Fluid-Filled | |

SEE ORIGINAL COA FOR ALL OTHER REQUIREMENTS.

Note: This confirms that the operator is approved to drill an 8-3/4" hole for the intermediate section and run 7-5/8" casing with MO-FXL flush joints. Adjust cement accordingly.

A. CASING

Note: Surface casing set depth was adjusted per BLM geologist's recommendation. *"The operator proposes to set surface casing to a depth of 350 feet; This will be in the salt formation. Instead the BLM suggests the Rustler formation at 290' feet for the APD well casing set depth and rock type."*

1. The 13-3/8 inch surface casing shall be set at approximately **290 ft.** (a minimum of 70 feet (Eddy County) into the Rustler Anhydrite, above the salt, and below usable fresh water) and cemented to the surface. **If salt is encountered, set casing at least 25 ft. above the salt.**
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic-type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours**

- or **500 psi compressive strength**, whichever is greater. (This is to include the lead cement)
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Note: Operator has requested to have the option to drill either 17-1/2" or 20" surface hole. Both hole sizes meet title 43 CFR 3172 clearance requirements between casing-coupling and hole. This option is granted; adjust cement volume accordingly.

2. The 7-5/8 inch intermediate casing shall be set in a competent bed at approximately **9,109 ft.** (8,997 ft. TVD). The minimum required fill of cement behind the 7-5/8 inch intermediate casing is:

Option 1 (Single Stage): Cement to surface. If cement does not circulate see B.1.a, c-d above. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to Cave/Karst.

Option 2 (Two-Stage): The operator has proposed to utilize a DV tool. Operator may adjust depth of DV tool. Adjust cement volume accordingly. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. **First stage to DV tool:** Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- b. **Second stage above DV tool: Cement to surface.** If cement does not circulate, contact the appropriate BLM office. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to Cave/Karst. Excess cement for the 2nd stage is less than 25%. More cement might be needed.

❖ In Medium Cave/Karst Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.

3. Operator has proposed to set 5-1/2-inch production casing at approximately **25,182 ft.** (9,670 ft. TVD). The minimum required fill of cement behind the production casing is:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification. Operator shall use one of the approved methods for cement verification located in the **General Requirements, Section A.1.**

Offline Cementing

Operator has been (**Approved**) to pump the proposed cement program offline in the **Surface and intermediate(s) intervals**. Offline cementing should commence within 24 hours of landing the casing for the interval. Notify the BLM 4hrs prior to the commencement of any offline cementing procedure at **Eddy County: 575-361-2822.**

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Contact Eddy County Petroleum Engineering Inspection Staff:

Email or call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220;
BLM_NM_CFO_DrillingNotifications@BLM.GOV; (575) 361-2822.

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - i. Notify the BLM when moving in and removing the Spudder Rig.
 - ii. Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - iii. BOP/BOPE test to be conducted per **43 CFR 3172** as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the doghouse or stairway area.
3. For intervals in which cement to surface is required, cement to surface should be verified with a visual check and density or pH check to differentiate cement from spacer and drilling mud. The results should be documented in the driller's log and daily reports.

A. CASING & CEMENTING

1. The current acceptable methods of cement verification are as follows:
 - i. Observing cement circulated to surface,
 - ii. Cement Bond Log (CBL),
 - iii. Temperature log within 8-10 hours after completing the cement job,
 - iv. Echometer (if a second-stage bradenhead is being utilized and operator was granted approval prior to operations.)
2. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80,

or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

3. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends of both lead and tail cement, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
5. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
6. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
7. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
8. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
9. Whenever a casing string is cemented in the R-111-Q potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in **43 CFR 3172**.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is

to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.

3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - i. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - ii. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - iii. Manufacturer representative shall install the test plug for the initial BOP test.
 - iv. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR 3172.6(b)(9) must be followed.
 - v. If the cement does not circulate and one-inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - i. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
 - ii. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (Only applies to single stage cement jobs, prior to the cement setting up.)
 - iii. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve open. The operator also has the option of utilizing an independent tester to test without a plug

- (i.e. against the casing) pursuant to **43 CFR 3172** with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for 8 hours or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- iv. The test shall be run on a 5000-psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one-hour chart. A circular chart shall have a maximum 2-hour clock. If a twelve hour or twenty-four-hour chart is used, tester shall make a notation that it is run with a two hour clock.
 - v. The results of the test shall be reported to the appropriate BLM office.
 - vi. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
 - vii. The BOP/BOPE test shall include a low-pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
 - viii. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per **43 CFR 3172**.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area. Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

SA 02/05/2026

Drill Plan

Dick & Donna 2729 Fed Com 202H
SHL: 1698' FNL & 1231' FWL Section 26
BHL: 2248' FNL & 340' FWL Section 29
Township/Range: 22S 28E
Elevation Above Sea Level: 3116

Sundry Request

Matador requests the option to amend the well design of the Dick & Donna 2729 Fed Com #202H and make the following changes to the current APD:

- Option to drill intermediate hole size of 8.75" OH
- Option to run intermediate casing type of 7-5/8" MO-FXL
- Cement volumes will be adjusted accordingly to reflect change of intermediate hole size

Drilling Operation Plan

Proposed Drilling Depth: 25182' MD / 9670' TVD

Type of well: Horizontal well, no pilot hole

Permitted Well Type: Oil

Geologic Name of Surface Formation: Quaternary Deposits

KOP Lat/Long (NAD83): 32.3646301 N / -104.0670592 W

TD Lat/Long (NAD83): 32.3646544 N / -104.1167849 W

1. Estimated Tops

| Formation | MD (ft) | TVD (ft) | Thickness (ft) | Lithology | Resource |
|----------------------|---------------|--------------|----------------|------------------|------------------------|
| Rustler | 289 | 289 | 173 | Anhydrite | Barren |
| Salado (Top of Salt) | 462 | 462 | 800 | Salt | Barren |
| Castile | 1,262 | 1,262 | 1,448 | Salt | Barren |
| Lamar (Base of Salt) | 2,719 | 2,710 | 28 | Salt | Barren |
| Bell Canyon | 2,747 | 2,738 | 835 | Sandstone | Oil/Natural Gas |
| Cherry Canyon | 3,590 | 3,573 | 1,205 | Sandstone | Oil/Natural Gas |
| Brushy Canyon | 4,807 | 4,778 | 1,432 | Sandstone | Oil/Natural Gas |
| Bone Spring Lime | 6,253 | 6,210 | 514 | Carbonate | Oil/Natural Gas |
| Avalon Shale | 6,772 | 6,724 | 293 | Shale | Oil/Natural Gas |
| 1st Bone Spring Carb | 7,067 | 7,017 | 264 | Carbonate | Oil/Natural Gas |
| 1st Bone Spring Sand | 7,334 | 7,281 | 268 | Sandstone | Oil/Natural Gas |
| 2nd Bone Spring Carb | 7,605 | 7,549 | 489 | Carbonate | Oil/Natural Gas |
| 2nd Bone Spring Sand | 8,098 | 8,038 | 358 | Sandstone | Oil/Natural Gas |
| 3rd Bone Spring Carb | 8,460 | 8,396 | 285 | Carbonate | Oil/Natural Gas |
| 3rd Bone Spring Sand | 8,747 | 8,681 | 910 | Sandstone | Oil/Natural Gas |
| KOP | 9,209 | 9,097 | - | Sandstone | Oil/Natural Gas |
| Wolfcamp A | 9,759 | 9,591 | 441 | Shale | Oil/Natural Gas |
| TD | 25,182 | 9,670 | - | Shale | Oil/Natural Gas |

2. Notable Zones

Wolfcamp A is the goal. All perforations will be within the setback requirements as prescribed or permitted by the New Mexico Oil Conservation Division. OSE estimated ground water depth at this location is 103'.

3. Pressure Control

Equipment

A 12,000' 5000-psi BOP stack consisting of 3 rams with 2 pipe rams, 1 blind ram, and one annular preventer will be utilized below surface casing to TD. See attachments for BOP and choke manifold diagrams.

An accumulator complying with Title 43 CFR 3172 requirements for the pressure rating of the BOP stack will be present. A rotating head will also be installed as needed.

Testing Procedure

BOP will be inspected and operated as required in Title 43 CFR 3172. Kelly cock and sub equipped with a full opening valve sized to fit the drill pipe and collars will be available on the rig floor in the open position.

A third party company will test the BOPs.

After setting surface casing, a minimum 5M BOPE system will be installed. Test pressures will be 250 psi low and 5000 psi high with the annular preventer being tested to 250 psi low and 2500 psi high before drilling below surface shoe. In the event that the rig drills multiple wells on the pad and any seal subject to test pressures are broken, a full BOP test will be performed when the rig returns and the 5M BOPE system is re-installed.

Variance Request

Matador requests a variance to have the option of running a multi-bowl wellhead assembly for setting the Intermediate 1 and Production Strings. The BOPs will not be tested again unless any flanges are separated.

Matador requests a variance to drill this well using a co-flex line between the BOP and choke manifold. Certification for proposed co-flex hose is attached. The hose is not required by the manufacturer to be anchored. If the specific hose is not available, then one of equal or higher rating will be used.

Matador requests a variance to have the option of batch drilling this well with other wells on the same pad. In the event that this well is batch drilled, the wellbore will be secured with a blind flange of like pressure. When the rig returns to this well and BOPs are installed, the operator will perform a full BOP test.

Matador request the option to offline cement surface casing. The "Offline Cementing - Surface Procedure" is attached for review. No changes in cement program are necessary.

Matador request the option to offline cement intermediate casing. The "Offline Cementing - Intermediate Casing" Procedure is attached for review. No changes in cement program are necessary.

Matador request the option to break test the BOP during batch drilling operations. The "Modified BOP Testing Procedure for Batch Drilling" Procedure is attached for review.

Drill Plan**4. Casing & Cement**

All casing will be API and new. See attached casing assumption worksheet.

| String | Hole Size (in) | Set MD (ft) | Set TVD (ft) | Casing Size (in) | Wt. (lb/ft) | Grade | Joint | Collapse | Burst | Tension |
|----------------|----------------|-------------|--------------|------------------|-------------|-------|----------------|----------|-------|---------|
| Surface | 17.5 | 0 - 350 | 0 - 350 | 13.375 | 54.5 | J-55 | BUTT | 1.125 | 1.125 | 1.8 |
| Intermediate 1 | 9.875 | 0 - 9109 | 0 - 8997 | 7.625 | 29.7 | P-110 | BUTT | 1.125 | 1.125 | 1.8 |
| Production | 6.75 | 0 - 25182 | 0 - 9670 | 5.5 | 20 | P-110 | Hunting TLW-SC | 1.125 | 1.125 | 1.8 |

- All casing strings will be tested in accordance with Title 43 CFR 3172.7(b)(8)

- Rustler top will be validated via drilling parameters (i.e. reduction in ROP) and surface casing setting depth revised accordingly if needed

- All non-API joint connections will be of like or greater quality, and as run specification sheets will be on location for review

Variance Request

Matador request a variance to wave the centralizer requirement for the 7-5/8" casing and the 5-1/2" SF/Flush casing in the 6-3/4" hole.

If a DV tool is used, depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above the current shoe. Lab reports with the 500 psi compressive strength time for the cement will be onsite for review. Option to cancel 2nd stage cement if cement is circulated on 1st stage.

Matador request a variance to utilize a surface setting rig. If this is used, Matador request the option to drill either 17.5" or 20" surface hole, cement volumes will be adjusted accordingly.

Primary Cement Design - DV/Packer 2-Stage Cement

| String | Type | Sacks | Yield | Cu. Ft. | Weight | Percent Excess | Top of Cement (ft) | Class | Blend |
|------------------------------|------------|-------|-------|---------|--------|----------------|--------------------|-------|--|
| Surface | Lead | 30 | 1.72 | 49 | 13.5 | 50% | 0 | C | 5% NaCl + LCM |
| | Tail | 250 | 1.38 | 347 | 14.8 | 50% | 50 | C | 5% NaCl + LCM |
| Intermediate 1 w/ DV @ 2760' | Stg 2 Tail | 430 | 1.78 | 762 | 13.5 | 10% | 0 | A/C | 5% NaCl + LCM |
| | Stg 1 Lead | 1470 | 1.84 | 2703 | 12.5 | 50% | 0 | A/C | Bentonite + 1% CaCl ₂ + 8% NaCl + LCM |
| | Stg 1 Tail | 260 | 1.33 | 343 | 14.8 | 50% | 8109 | A/C | 5% NaCl + LCM |
| Production | Tail | 1260 | 1.35 | 1697 | 13.2 | 25% | 8909 | A/C | Fluid Loss + Dispersant + Retarder + LCM |

5. Mud Program

Drill Plan

An electronic Pason mud monitoring system complying with Title 43 CFR 3172 will be used. All necessary mud products (barite, bentonite, LCM) for weight addition and fluid loss control will be on location at all times. Mud program is subject to change due to hole conditions.

| Hole Section | Hole Size (in) | Mud Type | Interval MD (ft) | Density (lb/gal) | Viscosity | Fluid Loss |
|----------------|----------------|-----------------------|------------------|------------------|-----------|------------|
| Surface | 17.5 | Spud Mud | 0 - 350 | 8.4 - 8.8 | 28-30 | NC |
| Intermediate 1 | 9.875 | Diesel Brine Emulsion | 350 - 9109 | 8.8 - 9.7 | 28-30 | NC |
| Production | 6.75 | OBM | 9109 - 25182 | 9.6 - 11.7 | 30-55 | <20 |

6. Cores, Test, & Logs

No core or drill stem test is planned.

No electric logs are planned at this time. GR will be collected through the MWD tools from Intermediate casing to TD. CBL with CCL will be run as far as gravity will let it fall to top of curve. We will be running a Neutron log on one of the wells on each pad.

7. Down Hole Conditions

No abnormal pressure or temperature is expected. Bottom hole pressure is 5883 psi. Maximum anticipated surface pressure is 3756 psi. Expected bottom hole temperature is 161 F.

In accordance with Title 43 CFR 3176, Matador does not anticipate that there will be enough H₂S from the surface to the Bone Spring formations to meet the BLM's minimum requirements for the submission of an "H₂S Drilling Operation Plan" or "Public Protection Plan" for the drilling and completion of this well. Since we have an H₂S safety package on all wells, attached is an "H₂S Drilling Operations Plan". Adequate flare lines will be installed off the mud/gas separator where gas may be flared safely. All personnel will be familiar with all aspects of safe operation of equipment being used.

Directional Anti-Collision Measures

Matador will be monitoring real time anti-collision while drilling these wells to maximize separation factor and minimize anti-collision concerns. Matador will also be performing a gyro survey on the Little Squaw 001 prior to spud of this well in order to maximize separation factor and minimize anti-collision concern against it. The Little Squaw 001 will also be shut in during drilling and completions operations to mitigate operational risk.

Casing Specs - 7-5/8" 29.7lb MO-FXL

Dick & Donna 2729 Fed Com 202H
 SHL: 1698' FNL & 1231' FWL Section 26

Township/Range: 22S 28E
 Elevation Above Sea Level: 3116'

| | | | | | |
|--|---|--|------|-----------------------------------|--|
| Metal One Corp. Metal One | MO-FXL Pipe Body: SeAH *Grade: P110HC (SMYS125ksi) Connection Data Sheet | | Page | MAI FXL 7.625 29.7 SeAH P110HC | |
| | | | Date | 29-May-20 | |
| | | | Rev. | 0 | |

| Geometry | <u>Imperial</u> | | <u>S.I.</u> | |
|---|-------------------------------|-----------------|--------------|-----------------|
| Pipe Body | | | | |
| Grade * | P110HC | | P110HC | |
| Pipe OD (D) | 7 5/8 | in | 193.68 | mm |
| Weight | 29.70 | lb/ft | 44.25 | kg/m |
| Actual weight | 29.04 | | 43.26 | kg/m |
| Wall Thickness (t) | 0.375 | in | 9.53 | mm |
| Pipe ID (d) | 6.875 | in | 174.63 | mm |
| Pipe body cross section | 8.537 | in ² | 5,508 | mm ² |
| Drift Dia. | 6.750 | in | 171.45 | mm |
| Connection | | | | |
| Box OD (W) | 7.625 | in | 193.68 | mm |
| PIN ID | 6.875 | in | 174.63 | mm |
| Make up Loss | 4.219 | in | 107.16 | mm |
| Box Critical Area | 5.714 | in ² | 3686 | mm ² |
| Joint load efficiency | 70 | % | 70 | % |
| Thread Taper | 1 / 10 (1.2" per ft) | | | |
| Number of Threads | 5 TPI | | | |
| Performance | | | | |
| Performance Properties for Pipe Body | | | | |
| S.M.Y.S. * | 1,067 | kips | 4,747 | kN |
| M.I.Y.P. * | 10,760 | psi | 74.21 | MPa |
| Collapse Strength * | 6,800 | psi | 46.90 | MPa |
| Note S.M.Y.S.= Specified Minimum YIELD Strength of Pipe body M.I.Y.P. = Minimum Internal Yield Pressure of Pipe body * SeAH P110HC YS: 125-140 ksi; Collapse: 6,800 psi | | | | |
| Performance Properties for Connection | | | | |
| Tensile Yield load | 747 kips (70% of S.M.Y.S.) | | | |
| Min. Compression Yield | 747 kips (70% of S.M.Y.S.) | | | |
| Internal Pressure | 8,610 psi (80% of M.I.Y.P.) | | | |
| External Pressure | 100% of Collapse Strength | | | |
| Max. DLS (deg. /100ft) | 30 | | | |
| Recommended Torque | | | | |
| Min. | 15,500 | ft-lb | 21,000 | N-m |
| Opti. | 17,200 | ft-lb | 23,300 | N-m |
| Max. | 18,900 | ft-lb | 25,600 | N-m |
| Operational Max. | 23,600 | ft-lb | 32,000 | N-m |
| Note : Operational Max. torque can be applied for high torque application | | | | |

The diagram illustrates a pipe joint with various dimensions labeled. 'Make up loss' is the length of the joint. 'Box critical area' is the area of the box end. 'Pin critical area' is the area of the pin end. 'd' is the pipe ID and 'D' is the box OD.

MO-FXL

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 552768

CONDITIONS

| | |
|---|--|
| Operator: MATADOR PRODUCTION COMPANY One Lincoln Centre Dallas, TX 75240 | OGRID: 228937 |
| | Action Number: 552768 |
| | Action Type: [C-103] NOI Change of Plans (C-103A) |

CONDITIONS

| Created By | Condition | Condition Date |
|-------------|--|----------------|
| ward.rikala | Any previous COA's not addressed within the updated COA's still apply. | 3/17/2026 |