

State of New Mexico  
Energy, Minerals and Natural Resources Department

---

**Susana Martinez**  
Governor

**Ken McQueen**  
Cabinet Secretary

**Matthias Sayer**  
Deputy Cabinet Secretary

**David R. Catanach** Division Director  
Oil Conservation Division



Administrative Order SWD 1676  
June 8 2017

**ADMINISTRATIVE ORDER  
OF THE OIL CONSERVATION DIVISION**

Pursuant to the provisions of Division Rule 19 15 26 8(B) NMAC Ray Westall Operating Inc (the operator ) seeks an administrative order to authorize the Ritz Federal SWD Well No 4 located 890 feet from the North line and 2110 feet from the East line Unit B of Section 35 Township 18 South Range 30 East NMPM Eddy County New Mexico for the commercial disposal of produced water

**THE DIVISION DIRECTOR FINDS THAT**

The application has been duly filed under the provisions of Division Rules 19 15 26 8(B) NMAC and satisfactory information has been provided that affected parties as defined in said rule have been notified and no objection was received within the required suspense period The applicant has presented satisfactory evidence that all requirements prescribed in Rule 19 15 26 8 NMAC have been met and the operator is in compliance with Rule 19 15 5 9 NMAC

**IT IS THEREFORE ORDERED THAT**

The applicant Ray Westall Operating Inc (OGRID 119305) is hereby authorized to utilize its Ritz Federal SWD Well No 4 (API 30 015 25142) located 890 feet from the North line and 2110 feet from the East line Unit B of Section 35, Township 18 South, Range 30 East, NMPM, Eddy County for commercial disposal of oil field produced water (UIC Class II only) in the Grayburg formation through perforations from 3726 feet below surface to 3794 feet below surface Injection will occur through internally coated 2 7/8 inch or smaller tubing and a packer set within 100 feet of the uppermost perforation

**IT IS FURTHER ORDERED THAT**

The operator shall take all steps necessary to ensure that the disposed water enters only the approved disposal interval and is not permitted to escape to other formations or onto the surface This includes the completion and construction of the well as proposed in the application and if necessary as determined by the Bureau of Land Management

*The operator shall conduct a swab test of the new perforations for hydrocarbon potential analysis of hydrocarbon content The Division s District II office shall be noticed prior to this test and given the opportunity to witness the swab test The operator shall supply the Division s*

*District II office and the Bureau of Land Management Carlsbad office a Sundry notice with the results of the swab test prior to commencing injection*

*In conjunction with squeeze cementing the current production perforations the operator shall conduct remedial cementing of the 5½ inch production casing from approximately 3000 feet to surface. If the cement does not circulate to surface the operator shall complete a cement bond log (or equivalent) for the 5½ inch production casing to demonstrate the final placement of cement including top of cement. The operator shall supply the Division's District II office and the Bureau of Land Management Carlsbad office with copies of the log prior to commencing injection.*

After installing tubing the casing tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing tubing or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The well shall pass an initial mechanical integrity test ( MIT ) prior to initially commencing disposal and prior to resuming disposal each time the disposal packer is unseated. All MIT procedures and schedules shall follow the requirements in Division Rule 19 15 26 11(A) NMAC. The Division Director retains the right to require at any time wireline verification of completion and packer setting depths in this well.

The wellhead injection pressure on the well shall be limited to **no more than 745 psi**. In addition the disposal well or system shall be equipped with a pressure limiting device in workable condition which shall at all times limit surface tubing pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the disposed fluid from the target formation. Such proper showing shall be demonstrated by sufficient evidence including but not limited to an acceptable Step Rate Test.

The operator shall notify the supervisor of the Division's District II office of the date and time of the installation of disposal equipment and of any MIT so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of disposal to the Division's District office. The operator shall submit monthly reports of the disposal operations on Division Form C 115 in accordance with Division Rules 19 15 26 13 and 19 15 7 24 NMAC.

Without limitation on the duties of the operator as provided in Division Rules 19 15 29 and 19 15 30 NMAC or otherwise the operator shall immediately notify the Division's District II office of any failure of the tubing casing or packer in the well or of any leakage or release of water oil or gas from around any produced or plugged and abandoned well in the area and shall take such measures as may be timely and necessary to correct such failure or leakage.

The injection authority granted under this order is not transferable except upon Division approval. The Division may require the operator to demonstrate mechanical integrity of any injection well that will be transferred prior to approving transfer of authority to inject.

The Division may revoke this injection order after notice and hearing if the operator is in violation of Rule 19 15 5 9 NMAC.

The disposal authority granted herein shall terminate two (2) years after the effective date of this Order if the operator has not commenced injection operations into the subject well. One year after the last date of reported disposal into this well, the Division shall consider the well abandoned and the authority to dispose will terminate *ipso facto*. The Division, upon written request mailed by the operator prior to the termination date, may grant an extension thereof for good cause.

Compliance with this Order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.



DAVID R. CATANACH  
Director

DRC/prg

cc Oil Conservation Division – Artesia District Office  
Bureau of Land Management – Carlsbad Field Office  
Well File 30 015 25142