

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South St. Frances, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Frances
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-007-20427
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Coalbed Methane		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator EL PASO ENERGY RATON, L.L.C.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 190, Raton, NM 87740		7. Lease Name or Unit Agreement Name: VPR B
4. Well Location Unit Letter <u>N</u> : <u>703</u> feet from the <u>South</u> line and <u>1409</u> feet from the <u>West</u> line Section <u>28</u> Township <u>30N</u> Range <u>18E</u> NMPM COLFAX County		8. Well No. 46
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8320' (GL)		9. Pool name or Wildcat

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

07/23/03 Spud @ 1:45 a.m. Drill 11" surface hole to 350'. Run 8 jts. of 8 5/8", 24#, J55 ST&C casing to 344'. Halliburton mixed and pumped 105 sx Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 45 psi with 6% salt, 5#/sx gilsonite, .3% versaset and .25 #/sk flocele. Circulate 10 bbl of cement to surface. WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.

07/24/03 Drill 7 7/8" hole from 350' - 2810'. Reached TD 2810' at 11:00 p.m.

07/25/03 MIRU Schlumberger & log well. Ran 12 jts of 5 1/2", 17#, J55 and 51 jts. of 5 1/2", 15.5#, J55 LT&C casing to 2684'. MIRU Halliburton. Mix and pump 40 bbls gel pre flush. Pumped 394 sx Midcon II PP, 13 ppg, yield 2.04 at 4 bpm with 40 psi, 6% salt, 5 lb/sx Gilsonite, .3% Versaset, .1% Super CBL and 1/4 #/sk flocele. Bumped plug on fly with 1300 psi. Full returns. Circulated 41 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Field Adm. Specialist DATE 07-30-03

Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785
(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 7/31/03
Conditions of approval, if any: