Energy, Minerals and Natural Resources	Submit 3 Copies To Appropriate District Office	State of New Mex	rico	Form C-103		
District and Ave. Anresia, NM \$210 DISTRICT SUPPORTS ON WILLS STATE FEE S. Indicate Type of Lease STATE FEE S. STATE	District I	Energy, Minerals and Natur	al Resources	May 27, 2004		
Dil Consider Dil Consider Distance				WELL API NO. 30-007-20883		
1220 Statists Design 1220 Statists Design 1220 Statists	1301 W. Grand Ave., Artesia, NM 88210			5. Indicate Type of Lease		
Sample Pe. NM NY 2015 16				STATE ☐ FEE ☒		
SUNDRY NOTICES AND REPORTS ON WELLS ON NOTISET HIS FORM FOR PROPOSALS 10 DUBLIC OR TO DELEPHOR PRINCE BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PREMIT" (FORM C-101) FOR SUCH 1. Type of Well: Oil Well 38. Well Number 384 9. OGRID Number 180514 12. Name of Operator ELPASO E& P COMPANY, L.P. 10. Pool name of Wildcat Stubblefield Canyon — Vermejo Gas 4. Well Location Unit Letter M : 971 feet from the South line and 1177 feet from the West line Section 28 Township 31N Range 21E NMPM Colfax County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 8. SLEO (GL) 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CAMBRICE BRILLING OPNS PAND A TEMPORARILY ABANDON CHANGE PLANS COMMENCE BRILLING OPNS PAND A TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PAND A TEMPORARILY ABANDON CHANGE PLANS CAMBRICEMENT JOB PAND A	District IV	Santa Fe, NM 87:	505	6. State Oil & Gas Lease No.		
SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name DISTRICTS FORK FOR PROPOSALS TO BUILD OR 10 DEPTRE PROPOSALS TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMIT" (FORM C-10) FOR PLG BACK 10 A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMIT" (FORM C-10) FOR SUCH POR PROPOSALS 3.		COUL NOT 30	Pri 2 16			
DIFFERENT RESERVOIR, USE 'APPLICATION FOR PERMIT' FORM C-101) FOR SUCH VPR A		CES AND REPORTS ON WELLS		7. Lease Name or Unit Agreement Name		
PROPOSALS) Type of Well: Oil Well Gas Well Other Coalbed Methane S. Well Number 384				_		
2. Name of Operator EL PASO E & P COMPANY, L.P. 3. Address of Operator PO BOX 190, RATON, NM 87740 4. Well Location Unit Letter M : 971 feet from the South line and 1177 feet from the West line Section 28 Township 31N Range 21E NMPM Colfax County						
EL PASO E & P COMPANY, L.P. 3. Address of Operator PO BOX 190, RATON, NM 87740 4. Well Location Unit Letter M : 971 feet from the South line and 1177 feet from the West line Section 28 Township 31N Range 21E NMPM Colfax County				8. Well Number 384		
3. Address of Operator PO BOX 190, RATON, NM 87740 10. Pool name or Wildcand Stubblefield Canyon – Vermejo Cas	•			9. OGRID Number 180514		
4. Well Location Unit Letter M : 971 feet from the South line and 1177 feet from the West line Section 28 Township 31N Range 21E NMPM Colfax County County County Colfax County						
A. Well Location	•					
Unit Letter M : 971 feet from the South line and 1177 feet from the West line Section 28 Township 31N Range 21E NMPM Colfax County 11. Elevation (Show whether DR, REB, RT, GR, etc.)		7 150, KATON, NW 67740		Stubbleffeld Canyon - Vermejo Gas		
Section 28 Township 31N Range 21E NMPM Coffax County		071 fact from the South	line and 11	77 foot from the West Line		
Pit or Below-grade Tank Application or Closure State State Distance from nearest surface water Distance from nearest surface						
Starting any proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Perf 2 ²⁸ Stage - Frac'd 2 ²⁸ Stage - Pumped 399.550 scf 70% quality nitrogen foam with 20% Linear gel with 16,347 lbs 20/40 sand. Power of the stage - Pumped 124/134 scf 70% quality nitrogen foam with 20% Linear gel with 13,034 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 124/134 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 124/134 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 124/134 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 124/134 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 130/133, 1354-1357, 1425-1428'' 36 Holes - Prac'd 3 ³⁸ stage - Pumped 134/134 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 144/31 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 144/31 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 144/31 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 144/31 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 144/31 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 144/31 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 144/31 scf 70% quality nitrogen foam with 20% Linear gel with 13,777 lbs 20/40 sand. Pref'd 4 ³⁸ stage - Pumped 144/31 scf 70% quality nitrogen foam with 20% Linear gel with	Section 28 Towns	. 1				
Pit Dec				· · · · · · · · · · · · · · · · · · ·		
Pit Liner Thickness: mil Below-Grade Tank: Volume bolds: Construction Material	Pit or Below-grade Tank Application or		<i>)</i>			
Pit Liner Thickness: mil Below-Grade Tank: Volume bolds: Construction Material						
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PAND A						
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PAND A PULL OR ALTER CASING MULTIPLE COMPL OTHER: OTHER: Completion OTHER: OTH						
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB OTHER: OTHER: Completion OTHER: Compl	12. Check A	ppropriate Box to indicate Na	nure of Notice,	Report of Other Data		
TEMPORARILY ABANDON	NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
OTHER: OTHER: Completion OTHER: OTHER: OTHER: Completion DITER: OTHER:				K ☐ ALTERING CASING ☐		
OTHER: OTHER: Completion Secrible proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Oy211/07 Superior ran Cement Bond Log. Estimated top of cement at 1500'.				_		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 09/21/07 Superior ran Cement Bond Log. Estimated top of cement at 1500'. 09/21/07 Superior Wireline perf'd 1" stage - 1948'-1951', 1986'-1989' 24 Holes HES frac'd 1" stage - Pumped 405.332 sef 70% quality nitrogen foam with 20# Linear gel with 8,067 lbs 20/40 sand. Perf'd 2" stage - Pumped 399,550 sef 70% quality nitrogen foam with 20# Linear gel with 16,347 lbs 20/40 sand. Shot squeeze perf's at 1470' − 1471' 4 Holes 09/25/07 HES pumped 193 sks midcon cement down hole. Circulated 7 bbls of cement to pit. 09/25/07 Superior ran Cement Bond Log. Estimated top of cement at surface. 10/04/07 Perf'd 3" stage - Pumped 224,124 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 3" stage - Pumped 224,124 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 24,124 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 141,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. Perf'd 4" stage - Pumped 141,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. Perf'd 4" stage - Pumped 141,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. Perf'd 4" stage - Pumped 141,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 141,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 140,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 140,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 140,431 sef 70% quality nitr	PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT	T JOB 🔲		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 09/21/07 Superior ran Cement Bond Log. Estimated top of cement at 1500'. 09/21/07 Superior Wireline perf'd 1" stage - 1948'-1951', 1986'-1989' 24 Holes HES frac'd 1" stage - Pumped 405.332 sef 70% quality nitrogen foam with 20# Linear gel with 8,067 lbs 20/40 sand. Perf'd 2" stage - Pumped 399,550 sef 70% quality nitrogen foam with 20# Linear gel with 16,347 lbs 20/40 sand. Shot squeeze perf's at 1470' − 1471' 4 Holes 09/25/07 HES pumped 193 sks midcon cement down hole. Circulated 7 bbls of cement to pit. 09/25/07 Superior ran Cement Bond Log. Estimated top of cement at surface. 10/04/07 Perf'd 3" stage - Pumped 224,124 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 3" stage - Pumped 224,124 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 24,124 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 141,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. Perf'd 4" stage - Pumped 141,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. Perf'd 4" stage - Pumped 141,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. Perf'd 4" stage - Pumped 141,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 141,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 140,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 140,431 sef 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4" stage - Pumped 140,431 sef 70% quality nitr	OTHER:		OTHER:	Completion 🖂		
or recompletion. 09/21/07 Superior ran Cement Bond Log. Estimated top of cement at 1500'. 09/21/07 Superior Wireline perf'd 1" stage - 1948'-1951', 1986'-1989' 24 Holes HES frac'd 1" stage - Pumped 405,332 scf 70% quality nitrogen foam with 20# Linear gel with 8,067 lbs 20/40 sand. Perf'd 2"d stage - Pumped 399,550 scf 70% quality nitrogen foam with 20# Linear gel with 16,347 lbs 20/40 sand. Shot squeeze perfs at 1470' - 1471' 4 Holes 09/25/07 HES pumped 193 sks mideon cement down hole. Circulated 7 bbls of cement to pit. 09/26/07 Superior ran Cement Bond Log. Estimated top of cement at surface. 10/04/07 Perf'd 3"d stage - 1300'-1303', 1354'-1357', 1425'-1428' 36 Holes Frac'd 3"d stage - Pumped 224,124 scf 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4"h stage - Pumped 241,124 scf 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. 10/08/07 RIH tubing, rods and pump. Well is ready to be tested and put on production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines \(\sqrt{\text{n}} \) a general permit \(\sqrt{\text{or an analyst}} \) DATE \(\sqrt{\text{1126/2007}} \) Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785	13. Describe proposed or comple	eted operations. (Clearly state all pe	ertinent details, and	d give pertinent dates, including estimated date		
09/21/07 Superior Wireline perf'd 1st stage - 1948'-1951', 1986'-1989' 24 Holes HES frac'd 1"stage - Pumped 405,332 scf 70% quality nitrogen foam with 20# Linear gel with 8,067 lbs 20/40 sand. Perf'd 2"d stage - 1726'-1729', 1736'-1739', 1747'-1750' 36 Holes Frac'd 2"d stage - Pumped 399,550 scf 70% quality nitrogen foam with 20# Linear gel with 16,347 lbs 20/40 sand. Shot squeeze perfs at 1470' − 1471' 4 Holes 09/25/07 HES pumped 193 sks midcon cement down hole. Circulated 7 bbls of cement to pit. Superior ran Cement Bond Log. Estimated top of cement at surface. 10/04/07 Perf'd 3"d stage - 1300'-1303', 1354'-1357', 1425'-1428' 36 Holes Frac'd 4"b stage - Pumped 224,124 scf 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. 10/08/07 RIH tubing, rods and pump. Well is ready to be tested and put on production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines □, a general permit □ or an (attached) alternative OCD-approved plan □. SIGNATURE □ TITLE Regulatory Analyst DATE 11/26/2007 Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785 For State Use Only APPROVED BY:		,				
09/21/07 Superior Wireline perf'd 1st stage - 1948'-1951', 1986'-1989' 24 Holes HES frac'd 1"stage - Pumped 405,332 scf 70% quality nitrogen foam with 20# Linear gel with 8,067 lbs 20/40 sand. Perf'd 2"d stage - 1726'-1729', 1736'-1739', 1747'-1750' 36 Holes Frac'd 2"d stage - Pumped 399,550 scf 70% quality nitrogen foam with 20# Linear gel with 16,347 lbs 20/40 sand. Shot squeeze perfs at 1470' − 1471' 4 Holes 09/25/07 HES pumped 193 sks midcon cement down hole. Circulated 7 bbls of cement to pit. Superior ran Cement Bond Log. Estimated top of cement at surface. 10/04/07 Perf'd 3"d stage - 1300'-1303', 1354'-1357', 1425'-1428' 36 Holes Frac'd 4"b stage - Pumped 224,124 scf 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. 10/08/07 RIH tubing, rods and pump. Well is ready to be tested and put on production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines □, a general permit □ or an (attached) alternative OCD-approved plan □. SIGNATURE □ TITLE Regulatory Analyst DATE 11/26/2007 Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785 For State Use Only APPROVED BY:	00/21/07 Superior von Coment Pand I	og Fetimeted top of gement at 1500	,			
HES frac'd 1st stage - Pumped 405,332 scf 70% quality nitrogen foam with 20# Linear gel with 8,067 lbs 20/40 sand. 1726'-1729', 1736'-1739', 1747'-1750' 36 Holes Frac'd 2nd stage - Pumped 399,550 scf 70% quality nitrogen foam with 20# Linear gel with 16,347 lbs 20/40 sand. Shot squeeze perfs at 1470' - 1471' 4 Holes 09/25/07 Superior ran Cement Bond Log. Estimated top of cement at surface. 10/04/07 Perf'd 3nd stage - Pumped 193 sks midcon cement down hole. Circulated 7 bbls of cement to pit. 10/04/07 Perf'd 3nd stage - Pumped 193 sks midcon cement down hole. Circulated 7 bbls of cement to pit. 10/04/07 Perf'd 3nd stage - Pumped 124,124' scf 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. 10/08/07 RIH tubing, rods and pump. Well is ready to be tested and put on production. 1 hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan . SIGNATURE Title Regulatory Analyst DATE 11/26/2007 Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785 For State Use Only APPROVED BY: January Analyst DATE 11/26/2007 TITLE DISTRICT SUPERVISOR						
Frac'd 2 nd stage - Pumped 399,550 scf 70% quality nitrogen foam with 20# Linear gel with 16,347 lbs 20/40 sand. Shot squeeze perfs at 1470' - 1471' 4 Holes 09/25/07 HES pumped 193 sks midcon cement down hole. Circulated 7 bbls of cement to pit. 09/26/07 Superior ran Cement Bond Log. Estimated top of cement at surface. 10/04/07 Perf'd 3 rd stage - 1300'-1303', 1354'-1357', 1425'-1428' 36 Holes Frac'd 4 rd stage - Pumped 224,124 scf 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4 th stage - Pumped 141,431 scf 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. 10/08/07 RIH tubing, rods and pump. Well is ready to be tested and put on production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE SIGNATURE TITLE Regulatory Analyst DATE 11/26/2007 Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785	HES frac'd 1st stage - Pumped 405,332 scf 70% quality nitrogen foam with 20# Linear gel with 8,067 lbs 20/40 sand.					
Shot squeeze perfs at 1470' - 1471' 4 Holes 09/25/07 HES pumped 193 sks midcon cement down hole. Circulated 7 bbls of cement to pit. 09/26/07 Superior ran Cement Bond Log. Estimated top of cement at surface. 10/04/07 Perf'd 3 rd stage - 1300'-1303', 1354'-1357', 1425'-1428' 36 Holes Frac'd 3 rd stage - Pumped 224,124 scf 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4 th stage - Pumped 141,431 scf 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. 10/08/07 RIH tubing, rods and pump. Well is ready to be tested and put on production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan . SIGNATURE Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785 For State Use Only APPROVED BY: LA Markin TITLE DISTRICT SUPERVISOR DATE 12/3/02						
09/25/07 Superior ran Cement Bond Log. Estimated top of cement at surface. 10/04/07 Perf'd 3 rd stage - 1300'-1303', 1354'-1357', 1425'-1428' 36 Holes Frac'd 3 rd stage - Pumped 224,124 scf 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4 th stage - Pumped 141,431 scf 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. 10/08/07 RIH tubing, rods and pump. Well is ready to be tested and put on production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines □, a general permit □ or an (attached) alternative OCD-approved plan □. SIGNATURE □ TITLE Regulatory Analyst □ DATE 11/26/2007 Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785 For State Use Only APPROVED BY:	, ,					
1300'-1303', 1354'-1357', 1425'-1428' 36 Holes Frac'd 3rd stage - Pumped 224,124 scf 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4th stage - Pumped 141,431 scf 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. 10/08/07 RIH tubing, rods and pump. Well is ready to be tested and put on production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan . SIGNATURE TITLE Regulatory Analyst DATE 11/26/2007 Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785 For State Use Only APPROVED BY: DATE 12/3/07						
Frac'd 3 rd stage - Pumped 224,124 scf 70% quality nitrogen foam with 20# Linear gel with 13,034 lbs 20/40 sand. Perf'd 4 th stage - Frac'd 4 th stage - Pumped 141,431 scf 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. 10/08/07 RIH tubing, rods and pump. Well is ready to be tested and put on production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines _, a general permit _ or an (attached) alternative OCD-approved plan SIGNATURE						
Perf'd 4th stage - Frac'd 4th stage - Pumped 141,431 scf 70% quality nitrogen foam with 20# Linear gel with 13,777 lbs 20/40 sand. 10/08/07 RIH tubing, rods and pump. Well is ready to be tested and put on production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan . SIGNATURE TITLE Regulatory Analyst DATE 11/26/2007 Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785 For State Use Only APPROVED BY: January TITLE DISTRICT SUPERVISOR DATE 12/3/07						
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines, a general permit or an (attached) alternative OCD-approved plan SIGNATURE	Perf'd 4 th stage - 1151'-1154', 1170'-1181' 56 Holes					
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines, a general permit or an (attached) alternative OCD-approved plan SIGNATURE						
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan . SIGNATURE TITLE Regulatory Analyst DATE 11/26/2007 Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785 For State Use Only APPROVED BY: SIGNATURE DISTRICT SUPERVISOR DATE 12/3/07	10/08/07 RIH tubing, rods and pun	1p. Well is ready to be tested and	put on production	on.		
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan . SIGNATURE TITLE Regulatory Analyst DATE 11/26/2007 Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785 For State Use Only APPROVED BY: SIGNATURE DISTRICT SUPERVISOR DATE 12/3/07						
SIGNATURE Study Mitchell TITLE Regulatory Analyst DATE 11/26/2007 Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785 For State Use Only APPROVED BY: SIGNATURE TITLE DISTRICT SUPERVISOR DATE 11/26/2007 Title DISTRICT SUPERVISOR DATE 12/3/07	I hereby certify that the information a grade tank has been/will be constructed or c	bove is true and complete to the bes	st of my knowledge , a general permit []	e and belief. I further certify that any pit or below- or an (attached) alternative OCD-approved plan		
Type or print name Shirley & Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785 For State Use Only APPROVED BY: ITTLE DISTRICT SUPERVISOR DATE /2/3/07	(d), e.	1 1				
APPROVED BY: Sal Martin TITLE DISTRICT SUPERVISOR DATE 12/3/07						
			riadriad ai	INFRIMAN		
	APPROVED BY: Conditions of Approval (if any):	Martino TITLE	DISTRICT SI	UPEKVIOUK DATE /2/3/07		