Submit 3 Copies To Appropriate District Office	State of New Mexico	Form C-103
District I	Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240 District II	, and any or your part of the state of the s	
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	5-007-20900 5-100 STATE FEE STATE
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr. V	TEE C
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
87505		2 21
	TICES AND REPORTS ON WELLS POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPI	LICATION FOR PERMIT" (FORM C-101) FOR SUCH	VPR B
PROPOSALS.) 1. Type of Well: Oil Well	Gas Well Other Coalbed Methane	8. Well Number 300
2. Name of Operator	Gas well Other Coansed Methane	9. OGRID Number 180514
	PASO E & P COMPANY, L.P.	3. OGIGD Number 100314
3. Address of Operator		10. Pool name or Wildcat
	BOX 190, RATON, NM 87740	Van Bremmer – Vermejo Gas
4. Well Location		
	140 feet from the South line and 1061	
Section 30 Town		Colfax County
	11. Elevation (Show whether DR, RKB, RT, GR, etc. 8,058' (GL)	
Pit or Below-grade Tank Application		
Pit typeDepth to Ground	lwaterDistance from nearest fresh water well Dis	stance from nearest surface water
Pit Liner Thickness: m	il Below-Grade Tank: Volumebbls; C	onstruction Material
12 Check	Appropriate Box to Indicate Nature of Notice,	Report or Other Data
		•
		SSEQUENT REPORT OF:
PERFORM REMEDIAL WORK		
TEMPODADII V ADANDONI - C		
		ILLING OPNS. P AND A
	☐ CHANGE PLANS ☐ COMMENCE DR ☐ MULTIPLE COMPL ☐ CASING/CEMEN	_
PULL OR ALTER CASING [OTHER:	MULTIPLE COMPL ☐ CASING/CEMEN ☐ OTHER:	T JOB ☐ Completion ☑
PULL OR ALTER CASING OTHER: 13. Describe proposed or completed	MULTIPLE COMPL CASING/CEMEN OTHER: d operations. (Clearly state all pertinent details, and give pertinent date	Completion es, including estimated date of starting any proposed work
PULL OR ALTER CASING OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple	MULTIPLE COMPL CASING/CEMEN OTHER: d operations. (Clearly state all pertinent details, and give pertinent date Completions: Attach wellbore diagram of proposed completion or rec	Completion es, including estimated date of starting any proposed work
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. I	MULTIPLE COMPL CASING/CEMEN OTHER: d operations. (Clearly state all pertinent details, and give pertinent date Completions: Attach wellbore diagram of proposed completion or rec Estimated top of cement at 330'.	Completion es, including estimated date of starting any proposed work
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. III. HES pumped 45 sks cem	MULTIPLE COMPL CASING/CEMEN OTHER: d operations. (Clearly state all pertinent details, and give pertinent date Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface.	Completion es, including estimated date of starting any proposed work
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. Hes pumped 45 sks cem 02/14/08 Weatherford ran CBL. Hes pumped 45 sks cem 02/14/08 Weatherford perf'd 1st st	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface. Estimated top of cement at surface. Estimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes	Completion Ses, including estimated date of starting any proposed work completion.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. HES frac'd 1st stage - P	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface. Estimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes umped 435,396 scf 70% quality nitrogen with 25# linear	Completion Ses, including estimated date of starting any proposed work completion.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. HES frac'd 1st stage - Perf'd 2nd stage - Perf'd 2nd stage -	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface. Estimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes umped 435,396 scf 70% quality nitrogen with 25# linear 2163'-2172', 2259'-2263' 52 Holes	Completion Ses, including estimated date of starting any proposed work completion.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. If 01/30/08 HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. If Weatherford perf'd 1st st HES frac'd 1st stage - Perf'd 2nd stage - Frac'd 2nd stage - Pumperf'd 3rd stage - Pumperf'	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date. Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface. Estimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes umped 435,396 scf 70% quality nitrogen with 25# linear 2163'-2172', 2259'-2263' 52 Holes mped 312,486 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 1	Completion Ses, including estimated date of starting any proposed work completion. The gel foam with 35,046 lbs 20/40 sand. The gel foam with 28,963 lbs 20/40 sand. The gel foam with 28,963 lbs 20/40 sand. The gel foam with 28,963 lbs 20/40 sand.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. HES frac'd 1st stage - Pumper'd 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pumper'd 3rd stage -	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface. Estimated top of cement at surface. Estimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes umped 435,396 scf 70% quality nitrogen with 25# linear 2163'-2172', 2259'-2263' 52 Holes mped 312,486 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 Inped 379,185 scf 70% quality nitrogen with 25# linear gel	Completion Ses, including estimated date of starting any proposed work completion. The gel foam with 35,046 lbs 20/40 sand. The gel foam with 28,963 lbs 20/40 sand. The gel foam with 28,963 lbs 20/40 sand. The gel foam with 28,963 lbs 20/40 sand.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. If O1/30/08 HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. If Weatherford ran CBL. If Weatherford perf'd 1st st HES frac'd 1st stage - Frac'd 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 4th stage - O3/21/08 Frac'd 4th stage - Pumperf'd 4	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date. Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface. Estimated top of cement at 330'. Estimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes umped 435,396 scf 70% quality nitrogen with 25# linear 2163'-2172', 2259'-2263' 52 Holes mped 312,486 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 Inped 379,185 scf 70% quality nitrogen with 25# linear gel 1081'-1084', 1139'-1142', 1157'-1162' 44 Holes mped 558,679 scf 70% quality nitrogen with 25# linear gel 1081'-1084', 1139'-1142', 1157'-1162' 44 Holes	Completion Ses, including estimated date of starting any proposed work completion. The gel foam with 35,046 lbs 20/40 sand. The foam with 28,963 lbs 20/40 sand. The foam with 30,742 lbs 20/40 sand.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. If 01/30/08 HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. If Weatherford ran CBL. If Weatherford perf'd 1st st HES frac'd 1st stage - Perf'd 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pumperf'd 4th stage - Pumperf'd 4th stage - Pumperf'd 5th stag	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date. Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface. Estimated top of cement at 330'. Estimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes umped 435,396 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 Imped 379,185 scf 70% quality nitrogen with 25# linear gel 1791'-1084', 1139'-1142', 1157'-1162' 44 Holes 1984', 1139'-1142', 1157'-1162' 44 Holes 1984', 760'-763', 774'-777', 817'-820', 839'-843' 52 Holes	Completion Ses, including estimated date of starting any proposed work completion. The gel foam with 35,046 lbs 20/40 sand. If foam with 28,963 lbs 20/40 sand. Holes foam with 30,742 lbs 20/40 sand. If foam with 24,281 lbs 20/40 sand.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. If 01/30/08 HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. If Weatherford ran CBL. If Weatherford perf'd 1st st HES frac'd 1st stage - Perf'd 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pumperf'd 4th stage - Pumperf'd 4th stage - Pumperf'd 5th stag	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date. Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface. Estimated top of cement at 330'. Estimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes umped 435,396 scf 70% quality nitrogen with 25# linear 2163'-2172', 2259'-2263' 52 Holes mped 312,486 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 Inped 379,185 scf 70% quality nitrogen with 25# linear gel 1081'-1084', 1139'-1142', 1157'-1162' 44 Holes mped 558,679 scf 70% quality nitrogen with 25# linear gel 1081'-1084', 1139'-1142', 1157'-1162' 44 Holes	Completion Ses, including estimated date of starting any proposed work completion. The gel foam with 35,046 lbs 20/40 sand. If foam with 28,963 lbs 20/40 sand. Holes foam with 30,742 lbs 20/40 sand. If foam with 24,281 lbs 20/40 sand.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. If 01/30/08 HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. If Weatherford ran CBL. If Weatherford perf'd 1st st HES frac'd 1st stage - Perf'd 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pumperf'd 4th stage - Pumperf'd 4th stage - Pumperf'd 5th stage - Pumperf'd 5th stage - Frac'd 5th stage - Pumperf'd 5th stage - Frac'd 5th stage - Pumperf'd 5th stage -	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date. Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface. Estimated top of cement at 330'. Estimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes umped 435,396 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 Imped 379,185 scf 70% quality nitrogen with 25# linear gel 1791'-1084', 1139'-1142', 1157'-1162' 44 Holes 1984', 1139'-1142', 1157'-1162' 44 Holes 1984', 760'-763', 774'-777', 817'-820', 839'-843' 52 Holes	Completion Ses, including estimated date of starting any proposed work completion. The gel foam with 35,046 lbs 20/40 sand. If foam with 28,963 lbs 20/40 sand. Holes foam with 30,742 lbs 20/40 sand. If foam with 24,281 lbs 20/40 sand.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. It 01/30/08 HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. It 03/20/08 Weatherford perf'd 1st st HES frac'd 1st stage - Perf'd 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 4th stage - Pum Perf'd 5th stage - Pum Perf'd 5th stage - Frac'd 5th stage - Frac'd 5th stage - Frac'd 5th stage - Frac'd 5th stage - Pum Perf'd 5th stage - Frac'd 5th stage - Pum Perf'd 5th stage - Frac'd 5th stage - Pum O4/03/08 Coil Tubing clean out. 04/04/08 RIH tubing, rods and pu	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date. Completions: Attach wellbore diagram of proposed completion or red. Estimated top of cement at 330'. Lent down hole. Circulated to surface. Estimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes umped 435,396 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 Inped 379,185 scf 70% quality nitrogen with 25# linear gel 1791'-1084', 1139'-1142', 1157'-1162' 44 Holes aped 558,679 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes aped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes	Completion Ses, including estimated date of starting any proposed work completion. The gel foam with 35,046 lbs 20/40 sand. The foam with 28,963 lbs 20/40 sand. The foam with 30,742 lbs 20/40 sand. The foam with 24,281 lbs 20/40 sand. The foam with 24,281 lbs 20/40 sand. The foam with 29,003 lbs 20/40 sand.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. It 01/30/08 HES pumped 45 sks cem 02/14/08 Weatherford perf'd 1st st HES frac'd 1st stage - Perf'd 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pumperf'd 4th stage - Pumperf'd 4th stage - Pumperf'd 5th stage - Frac'd 5th stage -	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date. Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface. Estimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes umped 435,396 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 Imped 379,185 scf 70% quality nitrogen with 25# linear gel 1791'-1084', 1139'-1142', 1157'-1162' 44 Holes inped 558,679 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-770', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-770', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-770', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-770', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-770', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-770', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-770', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-770', 817'-820', 839'-843' 52 Holes inped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-780', 817'-820', 817'-820', 817'-820', 817'-820', 817'-820', 817'-820', 817'-820', 817'-820', 817'-820', 817'-820', 817'-820	Completion Ses, including estimated date of starting any proposed work completion. Togel foam with 35,046 lbs 20/40 sand. I foam with 28,963 lbs 20/40 sand. Holes foam with 30,742 lbs 20/40 sand. I foam with 24,281 lbs 20/40 sand. I foam with 29,003 lbs 20/40 sand.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. It 01/30/08 HES pumped 45 sks cem 02/14/08 Weatherford perf'd 1st st HES frac'd 1st stage - Perf'd 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pum Perf'd 4th stage - Pum Perf'd 5th stage - Pum Perf'd 5th stage - Frac'd 5th stage - Frac'd 5th stage - Frac'd 5th stage - Pum Perf'd 5th stage - Pu	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date. Completions: Attach wellbore diagram of proposed completion or recent down hole. Circulated to surface. Estimated top of cement at 330'. Settimated top of cement at surface. age - 2381'-2384', 2341'-2346' 32 Holes umped 435,396 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 Imped 312,486 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 Imped 379,185 scf 70% quality nitrogen with 25# linear gel 1081'-1084', 1139'-1142', 1157'-1162' 44 Holes apped 558,679 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-770', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-770', 817'-820', 839'-843' 52 Holes apped 323,120 scf 70% quality nitrogen with 25# linear gel 1760'-763', 774'-770', 817'-820', 839'-843' 52 Holes	Completion ses, including estimated date of starting any proposed work completion. gel foam with 35,046 lbs 20/40 sand. foam with 28,963 lbs 20/40 sand. Holes foam with 30,742 lbs 20/40 sand. foam with 24,281 lbs 20/40 sand. foam with 29,003 lbs 20/40 sand. ge and belief. I further certify that any pit or below or an (attached) alternative OCD-approved plan .
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. If 01/30/08 HES pumped 45 sks cem 02/14/08 Weatherford part CBL. If 03/20/08 Weatherford part of 1st stage - Pumper of 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pumper of 4th stage - Pumper of 5th stage - P	MULTIPLE COMPL OTHER: doperations. (Clearly state all pertinent details, and give pertinent date. Completions: Attach wellbore diagram of proposed completion or received to possible of cement at 330'. Settimated top of cement at 330'. Settimated top of cement at surface. Settimated top of cement at 330'. S	Completion Es, including estimated date of starting any proposed work completion. The gel foam with 35,046 lbs 20/40 sand. If oam with 28,963 lbs 20/40 sand. Holes foam with 30,742 lbs 20/40 sand. If oam with 24,281 lbs 20/40 sand. If oam with 29,003 lbs 20/40 sand.
OTHER: 13. Describe proposed or completer SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. If 01/30/08 HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. If 03/20/08 Weatherford perf'd 1st st HES frac'd 1st stage - Perf'd 2nd stage - Frac'd 3nd stage - Pum Perf'd 3nd stage - Pum Perf'd 4th stage - Pum Perf'd 4th stage - Pum Perf'd 5th stage - Pum Perf'd	MULTIPLE COMPL OTHER: doperations. (Clearly state all pertinent details, and give pertinent date. Completions: Attach wellbore diagram of proposed completion or received to the completions. Attach wellbore diagram of proposed completion or received to the completion of cement at 330'. Estimated top of cement at 330'. Estimated top of cement at surface. Estimated top of cement at 330'. Estimate	Completion Es, including estimated date of starting any proposed work completion. The gel foam with 35,046 lbs 20/40 sand. If oam with 28,963 lbs 20/40 sand. Holes foam with 30,742 lbs 20/40 sand. If oam with 24,281 lbs 20/40 sand. If oam with 29,003 lbs 20/40 sand.
OTHER: 13. Describe proposed or completed SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. If 01/30/08 HES pumped 45 sks cem 02/14/08 Weatherford part CBL. If 03/20/08 Weatherford part of 1st stage - Pumper of 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pumper of 4th stage - Pumper of 5th stage - P	MULTIPLE COMPL OTHER: d operations. (Clearly state all pertinent details, and give pertinent date of Completions: Attach wellbore diagram of proposed completion or received down hole. Circulated to surface. Estimated top of cement at 330'. The state of the surface of the surface of the surface of the surface. Estimated top of cement at 330'. The surface of the surface. Estimated top of cement at 330'. Estimated top of cem	Completion Es, including estimated date of starting any proposed work completion. Egel foam with 35,046 lbs 20/40 sand. Foam with 28,963 lbs 20/40 sand. Foam with 30,742 lbs 20/40 sand. Foam with 24,281 lbs 20/40 sand. Foam with 29,003 lbs 20/40 sand. Ege and belief. I further certify that any pit or below or an (attached) alternative OCD-approved plan . Analyst DATE 06/11/2008 OM Telephone No. (505) 445-6785
OTHER: 13. Describe proposed or completer SEE RULE 1103. For Multiple 01/24/08 Weatherford ran CBL. If 01/30/08 HES pumped 45 sks cem 02/14/08 Weatherford ran CBL. If 03/20/08 Weatherford perf'd 1st st HES frac'd 1st stage - Perf'd 2nd stage - Frac'd 3nd stage - Pum Perf'd 3nd stage - Pum Perf'd 4th stage - Pum Perf'd 4th stage - Pum Perf'd 5th stage - Pum Perf'd	MULTIPLE COMPL OTHER: doperations. (Clearly state all pertinent details, and give pertinent date. Completions: Attach wellbore diagram of proposed completion or received down hole. Circulated to surface. Sestimated top of cement at 330'. Sent down hole. Circulated to surface. Sestimated top of cement at surface. Sage - 2381'-2384', 2341'-2346' 32 Holes sumped 435,396 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 Inped 379,185 scf 70% quality nitrogen with 25# linear gel 1791'-1794', 1816'-1819', 1836'-1838', 1874'-1883' 68 Inped 379,185 scf 70% quality nitrogen with 25# linear gel 1781'-1084', 1139'-1142', 1157'-1162' 44 Holes 1760'-763', 774'-777', 817'-820', 839'-843' 52 Holes 1791'-1794' structure and complete to the best of my knowledge or closed according to NMOCD guidelines TITLE Regulatory A Mitchell E-mail address: shirley.mitchell@elpaso.com	Completion Es, including estimated date of starting any proposed work completion. The gel foam with 35,046 lbs 20/40 sand. If oam with 28,963 lbs 20/40 sand. Holes foam with 30,742 lbs 20/40 sand. If oam with 24,281 lbs 20/40 sand. If oam with 29,003 lbs 20/40 sand.