

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

October 13, 2009

WELL API NO. 30-021-20444	
5. Indicate Type of Lease STATE ☐ FEE ☒	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name WBDU	
8. Well Number 091G	
9. OGRID Number 495	
10. Pool name or Wildcat West Bravo Dome CO2 Gas	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☐ Gas Well ☒ Other X CO2	
2. Name of Operator Hess Corporation	
3. Address of Operator PO Box 840 Seminole TX 79360	
4. Well Location Unit Letter G : 1850 feet from the NORTH line and 1980 feet from the EAST line Section 9 Township 18N Range 29E NMPM County HARDING	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 5434 GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Request Approval ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Requesting approval for the tubingless completion.

This well has fiberglass casing from surface to the productive interval (TUBB).

Steel casing will be used across the TUBB.

The fiberglass casing must penetrate the Cimarron at a minimum.

The optimum point for the setting the fiberglass casing

is at the midpoint of the Cimarron formation.

Spud Date:

08/01/2007

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rita C. Smith

TITLE ENGINEERING TECH

DATE 1/8/2010

Type or print name Rita C. Smith

E-mail address: rsmith@hess.com

PHONE: 432-758-6726

For State Use Only

APPROVED BY:

Ed Martin

TITLE

DISTRICT SUPERVISOR

DATE 1/21/10

Conditions of Approval (if any):