


AKM MEASUREMENT SERVICES,LLC. Natural Gas Analysis Report
 GPA 2172-09/API 14.5 Report with GPA 2145-16 Physical Properties

	Sample Information
Sample Name	LOST TANK 18 FACILITY PROD 2
Technician	ANTHONY DOMINGUEZ
Analyzer Make & Model	INFICON MICRO GC
Last Calibration/Validation Date	12-15-2023
Meter Number	16412P
Air temperature	59
Flow Rate (MCF/Day)	19315
Heat Tracing	HEATED HOSE & GASIFIER
Sample description/mtr name	LOST TANK 18 FACILITY PROD 2
Sampling Method	FILL & EMPTY
Operator	OCCIDENTAL PETROLEUM, OXY USA INC
State	NEW MEXICO
Region Name	PERMIAN_RESOURCES
Asset	NEW MEXICO
System	LOST TANK
FLOC	OP-DELNE-BT010
Sample Sub Type	CTB
Sample Name Type	METER
Vendor	AKM MEASUREMENT
Cylinder #	38967
Sampled by	SCOTT
Sample date	12-11-2023
Analyzed date	12-19-2023
Method Name	C9
Injection Date	2023-12-19 17:22:49
Report Date	2023-12-19 17:24:34
EZReporter Configuration File	1-16-2023 OXY GPA C9+ H2S #2.cfgx
Source Data File	c9df624d-557a-4940-b08e-304ec2186c4a
NGA Phys. Property Data Source	GPA Standard 2145-16 (FPS)
Data Source	INFICON Fusion Connector

Component Results

Component Name	Peak Area	Raw Amount	Response Factor	Norm Mole%	Gross HV (Dry) (BTU / Ideal cu.ft.)	Relative Gas Density (Dry)	GPM (Dry) (Gal. / 1000 cu.ft.)	
Nitrogen	33914.5	1.9299	0.00005691	1.9234	0.0	0.01860	0.212	
Methane	970996.0	70.7503	0.00007286	70.5121	713.8	0.39057	12.003	
CO2	27471.0	1.3080	0.00004761	1.3036	0.0	0.01981	0.223	
Ethane	291718.9	13.4465	0.00004609	13.4012	237.7	0.13913	3.599	
H2S	0.0	0.0000	0.00000000	0.0000	0.0	0.00000	0.000	
Propane	234132.9	7.6719	0.00003277	7.6461	192.8	0.11641	2.115	
iso-butane	91468.0	1.0116	0.00001106	1.0082	32.9	0.02023	0.331	
n-Butane	233710.5	2.5698	0.00001100	2.5611	83.7	0.05140	0.811	
iso-pentane	50142.9	0.4900	0.00000977	0.4883	19.6	0.01216	0.179	
n-Pentane	56869.7	0.5337	0.00000938	0.5319	21.4	0.01325	0.194	
hexanes	36640.0	0.3612	0.00000986	0.3600	17.2	0.01071	0.149	
heptanes	31543.0	0.1905	0.00000604	0.1899	10.5	0.00657	0.088	
octanes	12956.0	0.0696	0.00000537	0.0694	4.3	0.00274	0.036	
nonanes+	1475.0	0.0048	0.00000326	0.0048	0.3	0.00021	0.003	
Total:		100.3379		100.0000	1334.2	0.80179	19.943	

Results Summary

Result	Dry	Sat.	
Total Un-Normalized Mole%	100.3379		
Pressure Base (psia)	14.730		
Temperature Base (Deg. F)	60.00		
Flowing Temperature (Deg. F)	83.3		

Result	Dry	Sat.	
Flowing Pressure (psia)	100.2		
Gross Heating Value (BTU / Ideal cu.ft.)	1334.2	1311.0	
Gross Heating Value (BTU / Real cu.ft.)	1340.0	1317.3	
Relative Density (G), Real	0.8049	0.8022	

Monitored Parameter Report

Parameter	Value	Lower Limit	Upper Limit	Status	
Total un-normalized amount	100.3379	97.0000	103.0000	Pass	

**UPSET FLARING EVENT SPECIFIC JUSTIFICATIONS FORM****Facility Id#** fAPP2226965761**Facility:** Lost Tank 18 CPF**Duration of Event:** 30 Minutes**Start Time:** 09:30 AM**Cause:** Emergency Flare > Equipment Malfunction > Multiple Compression Equipment Issues**Method of Flared Gas Measurement:** Gas Flare Meter**Operator:** OXY USA, Inc.**Flare Date:** 07/14/2025**MCF Flared:** 1107**End Time:** 10:00 AM**1. Reason why this event was beyond Operator's control:**

This emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. Oxy engages in respectable and good facility operation practices while also maintaining its continuous facility equipment preventative maintenance program. In this case, there were sudden and unexpected compression equipment malfunctions, which in turn prompted high field pressure to occur which then triggered a flaring incident to occur at the Lost Tank 18 CPF. This event is out of OXY's control yet OXY made every effort to control and minimize emissions as much as possible by working safely and diligently.

2. Steps Taken to limit duration and magnitude of venting or flaring:

It is OXY's policy to route its stranded gas to a flare during an unforeseen and unavoidable emergency or malfunction, that is beyond OXY's control to avoid, prevent or foresee, to minimize emissions as much as possible as part of the overall steps taken to limit duration and magnitude of flaring. The flare at this facility has 98% combustion efficiency to lessen emissions as much as possible. OXY production technicians must assess whether compressor malfunctions are due to damage and immediate repair is needed, or whether there are other reasons for its cause. In this case, there were sudden and unexpected compression equipment malfunctions, which in turn prompted high field pressure to occur which then triggered a flaring incident to occur at the Lost Tank 18 CPF. Lost Tank 18 CPF was operating and running normally, and field pressure was within safe and acceptable levels prior to the unexpected compressor malfunctions. OXY's field and operations teams diligently oversee the facility and field pressure to swiftly identify any deviations from standard operational parameters. Although flaring is not OXY's preferred method for handling excess gas, it is necessary to ensure the safety of our operations, equipment, and field personnel. Notwithstanding proper gas compressor design and operation, various forms of mechanical or technical issues can be sudden, reasonably unforeseeable, and unexpected which can cause compressor unit malfunctions to occur without warning or advance notice. Compressor engines are designed to operate in a precise manner and when malfunctions occur, it disrupts the compression unit's operating manner and robs the compression engine of power, thus causing an automatic shutdown of the unit. The occurrence of this event was beyond OXY's control. OXY took all possible measures to manage and reduce emissions to the greatest extent.

3. Corrective Actions taken to eliminate the cause and reoccurrence of venting or flaring:

Oxy is limited in the corrective actions available to them to eliminate the cause and potential reoccurrence of compressor malfunctions as notwithstanding compressor engine design and operation, compressors are inherently dynamic and even the smallest alarms, false or true, can be sudden, reasonably unforeseeable and unexpected which can cause compression malfunctions to occur, thereby, triggering the unit's sensors to automatically shut down the unit to avoid catastrophic damage to the internal engine components. Oxy continually strives to maintain and operate all its equipment in a manner consistent with good practices for minimizing emissions and reducing the number of emission events. Oxy has a strong and positive equipment preventative maintenance program in place.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

DEFINITIONS

Action 490506

DEFINITIONS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 490506
	Action Type: [C-129] Venting and/or Flaring (C-129)

DEFINITIONS

<p>For the sake of brevity and completeness, please allow for the following in all groups of questions and for the rest of this application:</p> <ul style="list-style-type: none">• this application's operator, hereinafter "this operator";• venting and/or flaring, hereinafter "vent or flare";• any notification or report(s) of the C-129 form family, hereinafter "any C-129 forms";• the statements in (and/or attached to) this, hereinafter "the statements in this";• and the past tense will be used in lieu of mixed past/present tense questions and statements.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

QUESTIONS

Action 490506

QUESTIONS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 490506
	Action Type: [C-129] Venting and/or Flaring (C-129)

QUESTIONS

Prerequisites <i>Any messages presented in this section, will prevent submission of this application. Please resolve these issues before continuing with the rest of the questions.</i>	
Incident Well	Unavailable.
Incident Facility	[fAPP2226965761] Lost Tank 18 CPF

Determination of Reporting Requirements <i>Answer all questions that apply. The Reason(s) statements are calculated based on your answers and may provide additional guidance.</i>	
Was this vent or flare caused by an emergency or malfunction	Yes
Did this vent or flare last eight hours or more cumulatively within any 24-hour period from a single event	No
Is this considered a submission for a vent or flare event	Yes, major venting and/or flaring of natural gas.
<i>An operator shall file a form C-141 instead of a form C-129 for a release that, includes liquid during venting and/or flaring that is or may be a major or minor release under 19.15.29.7 NMAC.</i>	
Was there at least 50 MCF of natural gas vented and/or flared during this event	Yes
Did this vent or flare result in the release of ANY liquids (not fully and/or completely flared) that reached (or has a chance of reaching) the ground, a surface, a watercourse, or otherwise, with reasonable probability, endanger public health, the environment or fresh water	No
Was the vent or flare within an incorporated municipal boundary or within 300 feet from an occupied permanent residence, school, hospital, institution or church in existence	No

Equipment Involved	
Primary Equipment Involved	Other (Specify)
Additional details for Equipment Involved. Please specify	Emergency Flare > Equipment Malfunction > Multiple Compression Equipment Issues

Representative Compositional Analysis of Vented or Flared Natural Gas <i>Please provide the mole percent for the percentage questions in this group.</i>	
Methane (CH4) percentage	71
Nitrogen (N2) percentage, if greater than one percent	2
Hydrogen Sulfide (H2S) PPM, rounded up	0
Carbon Dioxide (CO2) percentage, if greater than one percent	1
Oxygen (O2) percentage, if greater than one percent	0
<i>If you are venting and/or flaring because of Pipeline Specification, please provide the required specifications for each gas.</i>	
Methane (CH4) percentage quality requirement	Not answered.
Nitrogen (N2) percentage quality requirement	Not answered.
Hydrogen Sulfide (H2S) PPM quality requirement	Not answered.
Carbon Dioxide (CO2) percentage quality requirement	Not answered.
Oxygen (O2) percentage quality requirement	Not answered.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

QUESTIONS, Page 2

Action 490506

QUESTIONS (continued)

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 490506
	Action Type: [C-129] Venting and/or Flaring (C-129)

QUESTIONS

Date(s) and Time(s)	
Date vent or flare was discovered or commenced	07/14/2025
Time vent or flare was discovered or commenced	09:30 AM
Time vent or flare was terminated	10:00 AM
Cumulative hours during this event	1

Measured or Estimated Volume of Vented or Flared Natural Gas	
Natural Gas Vented (Mcf) Details	Not answered.
Natural Gas Flared (Mcf) Details	Cause: Other Other (Specify) Natural Gas Flared Released: 1,107 Mcf Recovered: 0 Mcf Lost: 1,107 Mcf.
Other Released Details	Not answered.
Additional details for Measured or Estimated Volume(s). Please specify	Gas Flare Meter
Is this a gas only submission (i.e. only significant Mcf values reported)	Yes, according to supplied volumes this appears to be a "gas only" report.

Venting or Flaring Resulting from Downstream Activity	
Was this vent or flare a result of downstream activity	No
Was notification of downstream activity received by this operator	Not answered.
Downstream OGRID that should have notified this operator	Not answered.
Date notified of downstream activity requiring this vent or flare	Not answered.
Time notified of downstream activity requiring this vent or flare	Not answered.

Steps and Actions to Prevent Waste	
For this event, this operator could not have reasonably anticipated the current event and it was beyond this operator's control.	True
Please explain reason for why this event was beyond this operator's control	This emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. Oxy engages in respectable and good facility operation practices while also maintaining its continuous facility equipment preventative maintenance program. In this case, there were sudden and unexpected compression equipment malfunctions, which in turn prompted high field pressure to occur which then triggered a flaring incident to occur at the Lost Tank 18 CPF. This event is out of OXY's control yet OXY made every effort to control and minimize emissions as much as possible by working safely and diligently.
	It is OXY's policy to route its stranded gas to a flare during an unforeseen and unavoidable emergency or malfunction, that is beyond OXY's control to avoid, prevent or foresee, to minimize emissions as much as possible as part of the overall steps taken to limit duration and magnitude of flaring. The flare at this facility has 98% combustion efficiency to lessen emissions as much as possible. OXY production technicians must assess whether compressor malfunctions are due to damage and immediate repair is needed, or whether there are other reasons for its cause. In this case, there were sudden and unexpected compression equipment malfunctions, which in turn prompted high field pressure to occur which then triggered a flaring incident to occur at the Lost Tank 18 CPF. Lost Tank 18 CPF was operating and running normally, and field pressure was within safe and acceptable

Steps taken to limit the duration and magnitude of vent or flare	levels prior to the unexpected compressor malfunctions. OXY's field and operations teams diligently oversee the facility and field pressure to swiftly identify any deviations from standard operational parameters. Although flaring is not OXY's preferred method for handling excess gas, it is necessary to ensure the safety of our operations, equipment, and field personnel. Notwithstanding proper gas compressor design and operation, various forms of mechanical or technical issues can be sudden, reasonably unforeseeable, and unexpected which can cause compressor unit malfunctions to occur without warning or advance notice. Compressor engines are designed to operate in a precise manner and when malfunctions occur, it disrupts the compression unit's operating manner and robs the compression engine of power, thus causing an automatic shutdown of the unit. The occurrence of this event was beyond OXY's control. OXY took all possible measures to manage and reduce emissions to the greatest extent.
Corrective actions taken to eliminate the cause and reoccurrence of vent or flare	Oxy is limited in the corrective actions available to them to eliminate the cause and potential reoccurrence of compressor malfunctions as notwithstanding compressor engine design and operation, compressors are inherently dynamic and even the smallest alarms, false or true, can be sudden, reasonably unforeseeable and unexpected which can cause compression malfunctions to occur, thereby, triggering the unit's sensors to automatically shut down the unit to avoid catastrophic damage to the internal engine components. Oxy continually strives to maintain and operate all its equipment in a manner consistent with good practices for minimizing emissions and reducing the number of emission events. Oxy has a strong and positive equipment preventative maintenance program in place.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/oed/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 490506

ACKNOWLEDGMENTS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 490506
	Action Type: [C-129] Venting and/or Flaring (C-129)

ACKNOWLEDGMENTS

<input checked="" type="checkbox"/>	I acknowledge that I am authorized to submit a <i>Venting and/or Flaring</i> (C-129) report on behalf of this operator and understand that this report can be a complete C-129 submission per 19.15.27.8 and 19.15.28.8 NMAC.
<input checked="" type="checkbox"/>	I acknowledge that upon submitting this application, I will be creating a new incident file (assigned to this operator) to track any C-129 forms, pursuant to 19.15.27.7 and 19.15.28.8 NMAC and understand that this submission meets the notification requirements of Paragraph (1) of Subsection G and F respectively.
<input checked="" type="checkbox"/>	I hereby certify the statements in this report are true and correct to the best of my knowledge and acknowledge that any false statement may be subject to civil and criminal penalties under the Oil and Gas Act.
<input checked="" type="checkbox"/>	I acknowledge that the acceptance of any C-129 forms by the OCD does not relieve this operator of liability should their operations have failed to adequately investigate, report, and remediate contamination that poses a threat to groundwater, surface water, human health, or the environment.
<input checked="" type="checkbox"/>	I acknowledge that OCD acceptance of any C-129 forms does not relieve this operator of responsibility for compliance with any other applicable federal, state, or local laws and/or regulations.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 490506

CONDITIONS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 490506
	Action Type: [C-129] Venting and/or Flaring (C-129)

CONDITIONS

Created By	Condition	Condition Date
marialuna2	If the information provided in this report requires an amendment, submit a [C-129] Amend Venting and/or Flaring Incident (C-129A), utilizing your incident number from this event.	7/30/2025