Santa Fe Main Office
Phone: (505) 476-3441
General Information
Phone: (505) 629-6116

Online Phone Directory Visit:
https://www.emnrd.nm.gov/ocd/contact-us/

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised July 18, 2013

WELL API NO. 30-015-34865

5. Indicate Type of Lease STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name: Poker BIX

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

8. Well Number #001

2. Name of Operator: EOG Resources, Inc.

9. OGRID Number 7377

3. Address of Operator: 5509 Champions Dr., Midland, TX 79706

10. Pool name or Wildcat: Poker Lake; Delaware, East

4. Well Location
Unit Letter D : 330 feet from the North line and 330 feet from the West line
Section 23 Township 24S Range 31E NMPM County Eddy

11. Elevation *(Show whether DR, RKB, RT, GR, etc.)* 3562' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK	☐	PLUG AND ABANDON	☒	REMEDIAL WORK	☐	ALTERING CASING	☐
TEMPORARILY ABANDON	☐	CHANGE PLANS	☐	COMMENCE DRILLING OPNS.	☐	P AND A	☐
PULL OR ALTER CASING	☐	MULTIPLE COMPL	☐	CASING/CEMENT JOB	☐		
DOWNHOLE COMMINGLE	☐						
CLOSED-LOOP SYSTEM	☐						
OTHER:	☐			OTHER:			☐

Notify OCD 24 hrs. prior to any work done,gilbert.cordero@emnrd.nm.gov so a SG may be assigned.

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

EOG PROPOSES TO PLUG THIS WELL USING THE ATTACHED PROCEDURE. CURRENT AND PROPOSED WELLBORE DIAGRAMS ARE ALSO ATTACHED

Spud Date: 7/17/2006 Rig Release Date:

SEE ATTACHED COA's MUST BE PLUGGED BY 7/15/27

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Morgan Hrncirik TITLE SR. Regulatory Administrator DATE 6/30/2026

Type or print name Morgan Hrncirik E-mail address: morgan_hrncirik@eogresources.com PHONE: 832-627-5450

For State Use Only

APPROVED BY: Gilbert Cordero TITLE Petroleum Supervisor DATE 7/15/26
Conditions of Approval (if any):

4/1/26
P&A

Poker BIX #001 P&A
Capital AFE# 184016

Well Name	Poker BIX #001 P&A				
Surface Location	32.209110,-103.755520 NAD83			AFE/Sub Code	184016/231
RKB – Sea Level		Area/Field	Livingston Ridge	Spud Date	7/17/06
G.L. Elevation	3,562’	County/Province	Eddy	Original Rig Contractor	-
API	30-015-34865	State / Country	NM	Formation	
Comp Date	7/17/06	Total MD	8,508’	Top Perf	8,171
KOP	-	Average Lateral TVD	-	Wellhead MFG	-

.

STRING NAME	STRING OD	STRING WEIGHT	DESCRIPTION	FINAL DEPTH
SURFACE	13-3/8	48	13-3/8 H40	732’
INTERMEDIATE	8.625	32	8-5/8 J-55	4,442’
PRODUCTION	5.5	17 & 15.5	5 1/2 J55	8,508’

Summary of Procedure: Pull TBG, Spot cement, Run CIBP & dump bail cement, run Rcbl, abandon

APPROVED GC 7/15/26

PROCEDURE:

1. Notify BLM & State 24 hours before beginning work.
2. MIRU & Kill well.
3. ND/NU WH/BOP
4. Release TAC
5. TOOH Entire string of 2-7/8” Production TBG, evaluate the tbg, if you want to re use or use the current tbg. EOT is8 419 td is 8508.
6. TIH & spot or dump bail Class H cement from TD or tag of fill to cover bone springs - WOC & Tag @ 8326' or higher
7. TOOH
8. TIH & set CIBP @ 8,121’ – 50’ above perf @ 8171
9. Test csg to 500 psi/30min
10. Spot 25 sxs Class H cement from 8121 to 7894 (to perf @ 7,140’) this covers perfs or dump bail 36’ of cement on top of plug
11. If csg test passed, do not need to woc or tag.
12. Run RCBL with zero psi, keep hole loaded, log to surface
13. TOOH
14. Spot 25 sxs class c cement from 6,629’ to 6376’. - T Brushy Canyon
15. Spot 15 sx cmt 5404' - 5304' - T Cherry Canyon
16. Spot 55 sxs class c cement from 4,622’ to 4,065’
17. This covers Delaware, int. shoe, & bottom of salt.
18. WOC & Tag.
19. Est toc based off of records was 700’. However believe cbl will show further down. If so, plan to perf @ 1,062’

Released to Imaging: 7/15/2026 2:51:33 PM

22. Circulate 260 sxs class c cement around to surface - WOC & Bubble test
23. Dig out cellar, cut off wellhead and verify cement behind all casing strings.
24. Install dry hole marker, clean location and RDMO.

Production Engineer: _____ **Date:** 5/15/26

Chris Caskey

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division
Standard Plugging Conditions

This document provides OCD's general plugging conditions of approval. It should be noted that the list below may not cover special plugging programs in unique and unusual cases, and OCD expressly reserves the right to impose additional requirements to the extent dictated by project conditions. The OCD also reserves the right to approve deviations from the below conditions if field conditions warrant a change. A C-103F NOI to P&A must be approved prior to plugging operations. Failure to comply with the conditions attached to a plugging approval may result in a violation of 19.15.5.11 NMAC, which may result in enforcement actions, including but not limited to penalties and a requirement that the well be re-plugged as necessary.

1. Notify OCD office at least 24 hours before beginning work and seek prior approval to implementing any changes to the C-103 NOI to PA.
    - North Contact,
    - South Contact, Gilbert Cordero, 575-626-0830, gilbert.cordero@emnrd.nm.gov

2. A Cement Bond Log is required to ensure strata isolation of producing formations, protection of water and correlative rights. A CBL must be run or be on file that can be used to properly evaluate the cement behind the casing.

    Note: Logs must be submitted to OCD via OCD permitting. A copy of the log may be emailed to OCD inspector for faster review times, but emailing does not relieve the operators obligation to submit through OCD permitting.

3. Once Plugging operations have commenced, the rig must not rig down until the well is fully plugged without OCD approval. If gap in plugging operations exceeds 30 days, the Operator must file a subsequent sundry of work performed and revised NOI for approval on work remaining. At no time shall the rig be removed from location if it will result in waste or contamination of fresh water.

4. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.

5. Fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
    - North, water or mud laden fluids
    - South, mud laden fluids

6. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to an OCD permitted disposal facility.

7. Class of cement shall be used in accordance with the below table for depth allowed.

Class	TVD Lower Limit (feet)
Class A/B	6,000
Class I/II	6,000
Class C or III	6,000
Class G and H	8,000
Class D	10,000

Class E	14,000
Class F	16,000

8. After cutting the well head any “top off cement jobs” must remain static for 30 minutes. Any gas bubbles or flow during this 30 minutes shall be reported to the OCD for approval of next steps.

9. Trucking companies being used to haul oilfield waste fluids (Commercial or Private) to a disposal facility shall have an approved OCD C-133 permit.
    - A copy of this permit shall be available in each truck used to haul waste products.
    - It is the responsibility of the Operator and Contractor to verify that this permit is in place prior to performing work.
    - Drivers shall be able to produce a copy upon request of an OCD Compliance Officer.

10. Filing a [C-103] Sub. Plugging (C-103P) will serve as notification that the well has been plugged.

11. A [C-103] Sub. Release After P&A (C-103Q) shall be filed no later than a year after plugging and a site inspection by OCD Compliance officer to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to meet OCD standards before bonding can be released.

12. Produced water or brine-based fluids may not be used during any part of plugging operations without prior OCD approval.

13. Cementing;
    - All cement plugs will be neat cement and a minimum of 100’ in length. 50’ of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
    - If cement does not exist between or behind the casing strings at recommended formation depths, the casing perforations will be shot at 50’ below the formation top and the cement retainer shall be set no more than 50’ from the perforations.
    - WOC (Wait on Cement) time will be:
        - 4 hours for accelerated (calcium chloride) cement.
        - 6 hours on regular cement.
    - Operator must tag all cement plugs unless it meets the below condition.
        - The operator has a passing pressure test for the casing annulus and the plug is only an inside plug.
    - If perforations are made operator must tag all plugs using the work string to tag unless given approval to tag with wireline by the correct contact from COA #1 of this document.
        - This includes plugs pumped underneath a cement retainer to ensure retainer seats properly after cement is pumped.
    - Cement can only be bull-headed with specific prior approval.
    - Squeeze pressures are not to exceed the exposed formations frac gradient or the burst pressure of the casing.

14. A cement plug is required to be set from 50’ below to 50’ above (straddling) formation tops, casing shoes, casing stubs, any attempted casing cut offs, anywhere the casing is perforated, DV tools.
    - Perforation/Formation top plug. (When there is less than 100ft between the top perforation to the formation top.) These plugs are required to be started no greater than

50ft from the top perforation. However, the plug should be set below the formation top or as close to the formation top as possible for the maximum isolation between the formations. The plug is required to be a 100ft cement plug plus excess.

- Perforation Plug when a formation top is not included. These plugs are required to be started within 50ft of the top perforation. The plug is required to be a 100ft cement plug plus excess.
- Cement caps on top of bridge plugs or cement retainers for perforation plugs, that are not straddling a formation top, may be set using a bailer with a minimum of 35’ of cement in lieu of the 100’ plug. The bridge plug or retainer must be set within 50ft of the perforations.
- Perforations are required below the surface casing shoe if cement does not exist behind the casing, a 30-minute minimum wait time will be required immediately after perforating to determine if gas and/or water flows are present. If flow is present, the well will be shut-in for a minimum of one hour and the pressure recorded. If gas is detected contact the OCD office for directions.

15. No more than 3000 feet is allowed between cement plugs in cased hole and no more than 2000 feet is allowed in open hole.

16. Formation Tops to be isolated with cement plugs, but not limited to are:
    - Northwest See Figure A
    - South (Artesia) See Figure B
    - Potash See Figure C
        - In the R-111-P (Or as subsequently revised) Area a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, woe 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
    - South (Hobbs) See Figure D1 and D2
    - Areas not provided above will need to be reviewed with the OCD on a case by case basis.

17. Markers
    - Dry hole marker requirements 19.15.25.10.
      The operator shall mark the exact location of plugged and abandoned wells with a steel marker not less than four inches in diameter set in cement and extending at least four feet above mean ground level. The marker must include the below information:
        1. Operator name
        2. Lease name and well number
        3. API number
        4. Unit letter
        5. Section, Township and Range

    - AGRICULTURE (Below grade markers)
      In Agricultural areas a request can be made for a below ground marker. For a below ground marker the operator must file their request on a C-103 notice of intent, and it must include the following;
        A) Aerial photo showing the agricultural area
        B) Request from the landowner for the below ground marker.

C) Subsequent plugging report for a well using a below ground marker must have an updated C-102 signed by a certified surveyor for SHL.

Note: A below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to OCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to OCD. OCD requires a current survey to verify the location of the below ground marker, however OCD will accept a GPS coordinate that were taken with a GPS that has an accuracy of within 15 feet.

18. If work has not commenced within 1 year of the approval of this procedure, the approval is automatically expired. After 1 year a new [C-103] NOI Plugging (C-103F) must be submitted and approved prior to work.

Figure A

North Formations to be isolated with cement plugs are:

- San Jose
- Nacimiento
- Ojo Alamo
- Kirtland
- Fruitland
- Picture Cliffs
- Chacra (if below the Chacra Line)
- Mesa Verde Group
- Mancos
- Gallup
- Basin Dakota (plugged at the top of the Graneros)
- Deeper formations will be reviewed on a case-by-case basis

Figure B

South (Artesia) Formations to be isolated with cement plugs are:


- Fusselman
- Montoya
- Devonian
- Morrow
- Strawn
- Atoka
- Permo-Penn
- Wolfcamp
- Bone Springs
- Delaware , in certain areas where the Delaware is subdivided into;
    - 1. Bell Canyon
    - 2. Cherry Canyon
    - 3. Brushy Canyon
- Any salt sections
- Abo
- Yeso
- Glorieta
- San Andres
- Greyburg
- Queen
- Yates

Figure D1 and D2

South (Hobbs) Formations to be isolated with cement plugs are:

The plugging requirements in the Hobbs Area are based on the well location within specific areas of the Area (See Figure D1). The Formations in the Hobbs Area to be isolated with cement plugs are (see Figure D2)

Figure D1 Map



Released to Imaging: 7/15/2026 2:51:33 PM
Received by OCD: 6/30/2026 10:17:30 AM

Figure D2 Formation Table

100' Plug to isolate upper and lower fresh water zones (typically 250' to 350')						
Northwest Shelf	**Captan Reef Area**	**Transition Zone**	**San Simon Channel**	**South Vacuum Structure**	**Delaware Basin**	**Central Basin Platform**
Granit Wash (Detrital basement material and fractured pre-Cambrian basement rock)	Siluro-Devonian	Morrow	Siluro-Devonian	Ellenburger	Siluro-Devonian	Granit Wash (Detrital basement material, fractured pre-Cambrian basement rock and fracture Mafic Volcanic intrusives).
Montoya	Mississippian	Atoka	Morrow	Mckee	Morrow	Ellenburger
Fusselman	Morrow	Strawn	Wolfcamp	Siluro-Devonian	Atoka	Connell
Woodford	Atoka	Cisco	Abo Reef	Woodford	Strawn	Waddell
Siluro-Devonian	Strawn	Pennsylvanian	Bone Spring	Mississippian	Pennsylvanian	Mckee
Chester	Pennsylvanian	Wolfcamp	Delaware	Barnett Shale	Lower Wolfcamp	Simpson Group
Austin	Wolfcamp	Bone Spring	San Andres	Morrow	Upper Wolfcamp	Montoya
Mississippian	Abo Reef, if present	Delaware	Queen	Atoka	Wolfcamp	Fusselman
Morrow	Abo, if present	San Andres	Yates	Strawn	Third Bone Spring Sand (Top of Wolfbone)	Silurian
Atoka	Queen, if present	Grayburg-San Andres	Base of Salt	Canyon	First Bone Spring Sand (Top of Lower Bone Spring)	Devonian
Lower Pennsylvanian	Bone Spring	Queen	Rustler	Pennsylvanian	Bone Spring	Strawn
Cisco-Canyon	Delaware	Seven Rivers		Blinebry	Brushy Canyon	Pennsylvanian
Pennsylvanian	Base Capitan Reef	Yates		Bone Spring	Delaware (Base of Salt)	Wolfcamp
Bough	Seven Rivers	Base of Salt		San Andres	Rustler	Abo
Wolfcamp	Yates	Rustler		Queen		Abo Reef
Abo	Top Capitan Reef			Base of Salt		Drinkard
Abo Reef, if present	Base of Salt			Rustler		Tubb
Yeso (Township 15 South to Township 17 South)	Rustler					Blinebry
Drinkard or Lower Yeso (Township 15 South to Township 17 South)						Paddock
Tubb (Township 15 South to Township 17 South)						Glorieta
Blinebry (Township 15 South to Township 17 South)						San Andres
Paddock (Township 15 South to Township 17 South)						Grayburg
Glorieta						Grayburg-San Andres
San Andres						Queen
Queen (Township 15 South to Township 17 South)						Seven Rivers
Seven Rivers (Township 15 South to Township 17 South)						Yates
Yates (Township 15 South to Township 17 South)						Base of Salt
Base of Salt						Rustler
Rustler						

Page 12 of 23

EXHIBIT "A"
CASE 9316
ORDER **R-111-P**

CONSOLIDATED LAND **DESCRIPTION** OF THE KNOWN POTASH **LEASING AREA,** AS OF FEBRUARY **3, 1988**

EDDY **COUNTY,** NEW MEXICO

TOWNSHIP **18** SOUTH, RANGE 30 EAST, **NMPM**

Section **10:** **SE/4** SE/4
Section 11: S/2 SW/4
Section 13: W/2 SW/4 and SE/4 SW/4
Section 14: W/2 NE/4, NW/4 and S/2
Section 15: E/2 NE/4, SE/4 SW/4 and SE/4
Section 22: N/2, N/2 SW/4, SE/4 SW/4 and SE/4
Section 23: **All**
Section 24: N/2 **NW/4,** SW/4 NW/4 and NW/4 SW/4
Section 26: NE/4, N/2 NW/4 and SE/4 NW/4
Section 27: N/2 NE/4 and NE/4 NW/4

TOWNSHIP 19 SOUTH, RANGE 29 EAST, NMPM

Section 11: SE/4 SE/4
Sec**tion** 12: SE/4 NE/4 and S/2
Section 13: All
Section 14: NE/4, SE/4 NW/4 and S/2
Section 15: SE/4 SE/4
Section 22: NE/4, E/2 W/2 and SE/4
Section 23: All
Section 24: All
Section 25: NW/4 NW/4
Section 26: N/2 NE/4 AND NW/4
Section 27: NE/4 AND E/2 NW/4

TOWNSHIP 19 SOUTH, RANGE 30 **EAST**, NMPM

Section **2:** SW/4
Section 3: W/2 SW/4, SE/4 SW/4, S/2 SE/4 and NE/4 SE/4
Section 4: Lots 3 and 4. SW/4 NE/4, S/2 NW/4 and S/2
Section 5: Lots 1, 2. and 3, S/2 NE/4, S/2 NW/4 and S/2
Section 6: S/2 SE/4 and NE/4 SE/4
Sections 7 to 10 **inclusive**
Section 11: S/2 NE/4, NW/4 NW/4 and S/2
Section 12: NE/4, S/2 NW/4 and S/2
Section 13: NE/4, W/2, N/2 SE/4 and SW/4 SE/4
Sections 14 to 18 inclusive
Section 19: Lots 1, 2, and 3, NE/4, E/2 NW/4, NE/4 SW/4, E/2 SE/4 and NW/4 SE/4
Sections 20 to 23 inclusive

Received by OCD: 6/30/2026 10:17:30 AM
Released to Imaging: 7/15/2026 2:51:33 PM

Section 24: NW/4. NW/4 SW/4 and S/2 SW/4

Received by OCD: 6/30/2026 10:17:30 AM

Released to Imaging: 7/15/2026 2:51:33 PM

Page 14 of 23

Section 25: NW/4 NW/4
Section 26: NE/4 NE/4, W/2 NE/4, W/2, W/2 SE/4 and SE/4 SE/4
Section **27:** All
Section **28:** All
Section 29: E/2, E/2 NW/4 and **NW/4** NW/4
Sect ion 32: E/2 and SE/4 SW/4
Section 33 to 35 **inclusive**
Section 36: NW/4 NW/4, S/2 NW/4 and S/2

TOWNSHIP 19 SOUTH, RANGE **31** EAST, NMPM
Section 7: Lots 1, 2, and **3** and E/2 NW/4
Section 18: Lots **1, 2,** and 3 and SW/4 NE/4, E/2 NW/4 and NE/4 SW/4
Section **31**: Lot 4
Section 34: SE/4 SE/4
Section 35: S/2 SW/4 and SW/4 SE/4
Section 36: S/2 SE/4

LEA COUNTY, NEW **MEXICO**

TOWNSHIP 19 SOUTH, RANGE **32** EAST, NMPM
Section **31**: Lot 4
Section 33: Lots 1 to 4 inclusive and N/2 S/2
Section 34: Lots 1 to 4 inclusive and N/2 S/2
Section 35: Lots 1 to 4 inclusive and N/2 S/2
Section **36**: Lots 1 to 4 inclusive, SE/4 NE/4, NW/4 SW/4 and NE/4 SE/4

TOWNSHIP 19 SOUTH, RANGE 33 EAST, NMPM
Section 22: SE/4 NE/4, E/2 SW/4 and SE/4
Section 23: S/2 NW/4, SW/4. W/2 SE/4 and SE/4 SE/4
Section 25: SW/4 NW/4, W/2 SW/4 and SE/4 SW/4
Section 26: All
Section 27: All
Section 28: S/2 SE/4 and NE/4 SE/4
Section 30: Lots 2 to 4 inclusive, S/2 NE/4, SE/4 **NW/4.** E/2 SW/4 and SE/4
Section 31: All
Section 32: NE/4, S/2 NW/4 and S/2
Sections 33 to 35 **inclusive**
Section 36: W/2 NE/4, SE/4 NE/4, NW/4 and S/2

TOWNSHIP **19 SOUTH,** RANGE 34 EAST, NMPM
Section 31 Lots 3 and 4

Received by OCD: 6/30/2026 10:17:30 AM

Released to Imaging: 7/15/2026 2:51:33 PM

Page 15 of 23

EXHIBIT "A" con'd

EDDY COUNTY, NEW **MEXICO**

TOWNSHIP 20 SOUTH, **RANGE** 29 **EAST**, NMPM
Section **1**: SE/4 NE/4 and E/2 SE/4
Section 13: SW/4 **NW/4,** W/2 SW/4 AND SE/4 SW/4
Section 14: NW/4 NE/4, S/2 NE/4, NW/4 and S/2
Section15: E/2 E/2, SE/4 SW/4 and W/2 SE/4
Section 22: E/2 and E/2 NW/4
Section 23: All
Section 24: SW/4 NE/4, W/2, W/2 SE/4 and SE/4 SE/4
Section 25: N/2, SW/4, W/2 SE/4 and NE/4 SE/4
Section 26: All
Section 27: E/2
Section 34: NE/4
Section 35: N/2
Section 36: W/2 NE/4 AND NW/4

TOWNSHIP 20 SOUTH, **RANGE** 30 **EAST**, NMPM
Sections 1 to 4 inclusive
Section 5: Lots 1 to 3 inclusive, S/2 N/2 and S/2
Section 6 Lots 5, 6, and 7, S/2 NE/4, E/2 SW/4 and SE/4
Section 7 Lots 1 and 2. E/2 and E/2 NW/4
Sections 8 to 17 inclusive
Section 18 E/2
Section 19 E/2 and SE/4 SW/4
Sections 20 to 29 inclusive
Section 30: Lots 1 to 3 inclusive , E/2 and E/2 W/2
Section 31 E/4 and E/2 SE/4
Sections 32 to 35 inclusive

TOWNSHIP 20 SOUTH, RANGE **31** EAST, NMPM
Section 1 Lots 1 to3 inclusive, S/2 N/2 and S/2
Section **2**: All
Section 3: Lots 1 and 2, S/2 NE/4 and SE/4
Section **6**: Lots 4 to 7 inclusive , SE/4 NW/4, E/2 SW/4, W/2 SE/4 and SE/4 SE/4
Section 7: All
Section 8: S/2 N/2 and S/2
Section 9: S/2 NW/4, SW/4, W/2 SE/4 and SE/4 SE/4
Section 10: E/2 and SW/4
Section 11 to 36 **inclusive**

Received by OCD: 6/30/2026 10:17:30 AM

Released to Imaging: 7/15/2026 2:51:33 PM

Page 16 of 23

EXHIBIT "A" **con'd**

LEA **COUNTY**, NEW **MEXICO**

TOWNSHIP 20 SOUTH, RANGE 32 EAST, NMPM
Sections 1 to 4 inclusive
Section 5: S/2 SE/4
Section 6: Lots 4 to 7 inclusive, SE/4 NW/4, E/2 SW/4 and SW/4 SE/4
Sections 7 to 36 inclusive

TOWNSHIP 20 **SOUTH**, RANGE 33 EAST, NMPM
Sections 1 to 36 inclusive

TOWNSHIP 20 **SOUTH, RANGE 34 EAST,** NMPM
Section 6: Lots 3 to 7 **inclusive**, SE/4 NEW/4, E/2SW/4, W/2 SE/4 AND SE/4 SE/4
Section 7: **All**
Section 8: SW/4, S/2 NW/4, W/2 SE/4 and SE/4 SE/4
Section 16: W/2 NW/4, SE/4 NW/4, SW/4 and S/2 SE/4
Sections 17 to 21 inclusive
Section 22: N/2 **NW/4,** SW/4 **NW/4,** W/2 **SE/4,** and SE/4 SE/4
Section 26: SW/4, W/2 SE/4 and SE/4 SE/4
Sections 27 to 35 inclusive
Section 36: SW/4 NW/4 and W/2 SW/4

EDDY COUNTY, NEW **MEXICO**

TOWNSHIP 21 SOUTH, RANGE 29 EAST, NMPM
Sections 1 to 3 inclusive
Section 4: Lots 1 through 16, NE/4 SW/4 and SE/4
Section 5: Lot 1
Section **10**: N/2 NE/4, SE/4 NE/4 and SE/4 SE/4
Sections **11** to **14 inclusive**
Section 15: E/2 NE/4 and NE/4 SE/4
Section 23: N/2 NE/4
Section 24: E/2, N/2NW/4 and SE/4NW/4
Section 25: NE/4 NE/4 and S/2 SE/4
Section 35: Lots 2 to 4 inclusive, S/2 NE/4, NE/4 SW/4 and N/2 SE/4
Section 36: Lots 1 to 4 inclusive, NE/4, E/2 NW/4 AND N/2 S/2

TOWNSHIP 21 SOUTH, **RANGE** 30 EAST, NMPM
Sections 1 to 36 inclusive

Received by OCD: 6/30/2026 10:17:30 AM

Released to Imaging: 7/15/2026 2:51:33 PM

Page 17 of 23

TOWNSHIP 21 SOUTH, RANGE 31 EAST, NMPM
Sections 1 to 36 inclusive

LEA **COUNTY**, NEW **MEXICO**

TOWNSHIP 21 SOUTH, **RANGE** 32 EAST, NMPM
Sections 1 to 27 inclusive
Section 28: N/2 and N/2 S/2
Sections 29 to 31 inclusive
Section 32: NW/4 NE/4, NW/4 and **NW/4** SW/4
Section 34: N/2 NE/4
Section 35: N/2 N/2
Section 36: E/2, N/2 NW/4, SE/4 **NW/4** and NE/4 SW/4

TOWNSHIP **21 SOUTH, RANGE** 33 EAST, NMPM
Section 1: Lots 2 to 7 **inclusive**, Lots 10 to 14 inclusive, N/2 SW/4 and SW/4 SW/4
Sections 2 to 11 inclusive
Section 12: NW/4 NW/4 and SW/4 SW/4
Section 13: N/2 NW/4, S/2 N/2 and S/2
Sections 14 to 24 inclusive
Section 25: N/2. SW/4 and W/2 SE/4
Sections 26 to 30 inclusive
Section **31**: Lots 1 to 4 inclusive, NE/4, E/2 W/2, N/2 SE/4 and SW/4 SE/4
Section 32: N/2 and NW/4 SW/4
Section 33: N/2
Section 34: NE/4, N/2 NW/4 and E/2 SE/4
Section 35: **All**
Section 36: W/2 NE/4, NW/4 and S/2

TOWNSHIP 21 SOUTH, RANGE 34 EAST, NMPM
Section 17: **W/2**
Section 18: All
Section 19: Lots 1 to 4 inclusive, NE/4, E/2 W/2, N/2 SE/4 and SW/4 SE/4
Section 20: NW/4 NW/4
Section **30:** Lots 1 and 2 and NE/4 NW/4
Section 31: Lots 3 and 4

EDDY COUNTY, NEW **MEXICO**

TOWNSHIP 22 **SOUTH, RANGE** 28 EAST, NMPM
Section 36: E/2 E/2

Received by OCD: 6/30/2026 10:17:30 AM

Released to Imaging: 7/15/2026 2:51:33 PM

Page 18 of 23

TOWNSHIP 22 SOUTH, RANGE 29 EAST, NMPM
Sections 1 and 2 inclusive
Section 3 SE/4 SW/4 and SE/4
Section 9 S/2 NE/4 and S/2
Sections **10** to 16 inclusive
Section 17 S/2 SE/4
Section 19 SE/4 NE/4 and E/2 SE/4
Sections 20 to 28 inclusive
Section 29 N/2 N/2, S/2 NE/4 and SE/4
Section 30 NE/4 NE/4
Section 31 Lots 1 to 4 inclusive, S/2 NE/4, E/2 W/2 and SE/4
Sections 32 to 36 inclusive

TOWNSHIP 22 **SOUTH, RANGE** 30 EAST, NMPM
Sections 1 to 36 inclusive

TOWNSHIP 22 SOUTH, RANGE 31 EAST, NMPM
Sections 1 to 11 inclusive
Section 12: NW/4 **NE/4**, NW/4 and NW/4 **SW/4**
Section 13: S/2 NW/4 and **SW/4**
Sections **14** through 23 **inclusive**
Section 24: W/2
Section 25: NW/4
Section 26: NE/4 AND N/2 NW/4
Sections 27 to 34 **inclusive**

LEA COUNTY, NEW **MEXICO**

TOWNSHIP 22 SOUTH, RANGE **32 EAST,** NMPM
Section 1: Lot 1
Section 6: Lots 2 to 7 inclusive and SE/4 NW/4

TOWNSHIP 22 SOUTH, RANGE **33** EAST NMPM
Section 1: Lots 1 to 4 inclusive, S/2 N/2 and N/2 S/2
Section 2: All
Section 3: Lot **1**, SE/4 NE/4 and SE/4
Section 6: Lot 4
Section 10: NE/4
Section 11: NW/4 NE/4 AND NW/4

TOWNSHIP 22 **SOUTH,** RANGE 34 EAST NMPM
Section 6: Lots 4 to 6 inclusive

Received by OCD: 6/30/2026 10:17:30 AM
Released to Imaging: 7/15/2026 2:51:33 PM

Page 19 of 23

EDDY COUNTY, NEW **MEXICO**

TOWNSHIP 23 SOUTH, RANGE **28 EAST**, NMPM
Section 1: Lot 1

TOWNSHIP 23 SOUTH, **RANGE** 29 EAST, NMPM
Sections 1 to 5 **inclusive**
Section 6: Lots 1 to 6 inclusive, S/2 NE/4, SE/4 NW/4, E/2 SW/4 and SE/4
Section 7: NE/4 and NE/4 NW/4
Section 8: N/2, N/2 SW/4, SE/4 SW/4 and SE/4
Sections 9 to **16 inclusive**
Section 17: NE/4 and E/2 SE/4
Sections 21 to 23 **inclusive**
Section 24: **N/2**, SW/4 and N/2 SE/4
Section 25: W/2 NW/4 and NW/4 SW/4
Section 26: All
Section 27: **All**
Section 28: N/2, N/2 SW/4, SE/4 SW/4 and SE/4
Section 33: N/2 NE/4 and NE/4 NW/4
Section 34: NE/4, E/2 NW/4, NW/4 **NW/4**, NE/4 SW/4 and SE/4
Section 35: All
Section 36: W/2 NE/4, NW/4 and N/2 SW/4

TOWNSHIP 23 **SOUTH, RANGE 30 EAST**, NMPM
Sections 1 to 18 inclusive
Section 19 N/2, N/2 SW/4, SE/4 SW/4 and SE/4
Section 20 **All**
Section 21 All
Section 22 N/2, S/2 SW/4, N/2 S/2 and SE/4 SE/4
Sections 23 to 25 inclusive
Section 26 E/2, SE/4 NW/4 and **SW/4**
Section 27 N/2 NW/4, SW/4 NW/4, SE/4 SW/4, S/2 SE/4 and NE/4 SE/4
Section 28 N/2 and SW/4 Sect ion 29 N/2 and SE/4
Section 30 N/2 NE/4
Section 32 N/2 NE/4
Section 33 SE/4 NE/4, N/2 NW/4, NE/4 SE/4 and S/2 SE/4
Sections 34 to 36 inclusive

TOWNSHIP 23 SOUTH, RANGE 31 EAST, NMPM
Section 2: Lot 4, SW/4 **NW/4** and W/2 SE/4
Sections 3 to 7 **inclusive**
Section 8: NE/4 NE/4, W/2 NE/4 and W/2
Section 9: N/2 N/2
Section 10: NW/4 NW/4 and SE/4 SE/4
Section **11**: S/2 NE/4, S/2 SW/4 and SE/4

Received by OCD: 6/30/2026 10:17:30 AM
Released to Imaging: 7/15/2026 2:51:33 PM

Page 20 of 23

Section 12: SW/4 NW/4 and SW/4
Section 13: SW/4 **NE/4**, W/2 and W/2 SE/4
Section 14: All
Section 15: E/2, SE/4 NW/4 and **SW/4**
Section 16: SW/4 and S/2 SE/4
Section 17: NW/4 and S/2
Sections 18 to 23 inclusive
Section 24: W/2 NE/4 and W/2
Section **25**: W/2 NE/4, NW/4, N/2 SW/4 and NW/4 SE/4
Section 26 to 34 inclusive
Section 35: N/2 NW/4 and SW/4 NW/4

TOWNSHIP 24 SOUTH, **RANGE** 29 **EAST**, NMPM
Section 2: Lots 2 to 4 inclusive
Section 3: Lot 1

TOWNSHIP 24 **SOUTH, RANGE 30** EAST, NMPM
Section **1**: Lots 1 to 4 inclusive, S/2 N/2, SW/4 and NW/4 SE/4
Sect**ion** 2: All
Section 3: All
Section 4: Lots 1 and 2, S/2 NE/4, SE/4 NW/4, SW/4 SW/4. E/2 SW/4 and SE/4
Section 9: N/2, N/2 SW/4, SE/4 SW/4 and SE/4
Section 10: All
Section 11: All
Section 12: W/2 NW/4 and NW/4 SW/4
Section 14: W/2 NE/4 and **NW/4**
Section 15: NE/4 and N/2 NW/4

TOWNSHIP 24 SOUTH, **RANGE 31 EAST,** NMPM
Sect**ion** 3: Lots 2 to 4 inclusive, SW/4 NE/4, S/2 NW/4, SW/4 and W/2 SE/4
Section 4: All
Section 5: Lots 1 to 4 inclusive, S/2 N/2, N/2 S/2 and SE/4 SE/4
Section 6: Lots 1 to 6 inclusive, S/2 NE/4, SE/4 NW/4, NE/4 SW/4 and N/2 SE/4
Section 9: E/2 and NW/4
Section 10: W/2 NE/4 and W/2
Section **35**: Lots 1 to 4 inclusive, S/2 N/2 and N/2 S/2
Section **36**: Lots 1 and 2, SW/4 NW/4 and N/2 SW/4

TOWNSHIP 25 SOUTH, **RANGE 31 EAST,** NMPM
Section **1**: Lots 3 and 4 and S/2 NW/4
Section 2: Lots 1 to 4 inclusive and S/2 N/2

Received by OCD: 6/30/2026 10:17:30 AM
Released to Imaging: 7/15/2026 2:51:33 PM

Well Name:	Poker Bix #001
Location:	330FNL 330 FWL
County:	Eddy, NM
Lat/Long:	32.209110,-103.755520 NAD83
API #:	30-015-34865
Spud Date:	7/17/06
Compl. Date:	1/16/07

Formation Tops

Top of Salt	1,012
Bottom of Salt	4,278
Delaware	4,572
Brushy Canyon	6,579
Bone Spring	8,376

Current Wellbore Diagram:


KB: 3579
GL: 3562

17-1/2" Hole

13-3/8" 48# H-40 J55 @ 732'
Cmt w/ 780 sx Class C (circ) to surface

11"" Hole

Cement to Surface
8-5/8" 32# 24# J-55 HC80 to 4,472'
Cmt w/ 1,400 sx Class C (circ) to surface



5-1/2" 17# & 15.5# J55 LTC Prod CSG to 8,508';
1,000 sx Class H cmt
Est toc 700'
7-7/8" Vertical to 8508

Perforate 8171' to 8,314'

TAC set 8329
2-7/8" TBG to 8,419 on 11/30/21

Not to Scale
By: CC 5/15/26

Well Name:	Poker Bix #001
Location:	330FNL 330 FWL
County:	Eddy, NM
Lat/Long:	32.209110,-103.755520 NAD83
API #:	30-015-34865
Spud Date:	7/17/06
Compl. Date:	1/16/07

eog resources

Formation Tops	
Top of Salt	1,012
Bottom of Salt	4,278
Delaware	4,572
Brushy Canyon	6,579
Bone Spring	8,376

Proposed Wellbore Diagram:

KB: 3579
GL: 3562


17-1/2" Hole

13-3/8" 48# H-40 J55 @ 732'
Cmt w/ 780 sx Class C (circ) to surface

11"" Hole

Cement to Surface
8-5/8" 32# 24# J-55 HC80 to 4,472'
Cmt w/ 1,400 sx Class C (circ) to surface

5-1/2" 17# & 15.5# J55 LTC Prod CSG to 8,508';
1,000 sx Class H cmt
Est toc 700'
7-7/8" Vertical to 8508



Circulate 260 sxs class c cement to surface
Depending on cbl ~perf @ 1062

WOC & tag
Cement covers Delaware, int shoe &
Bottom of salt
Spot 55 sxx Class C cement from 4,622' to 4,065'

Not to Scale	
By: CC	5/15/26

Spacer plug do not need to woc or tag
Spot 25 sxs Class C cement from 6629' to 6376'

Run CBL & gyro
If csg test succesful no need to woc and tag
Spot 25 sxs Claas H Cmt from 8,121' to 7,894'
Test CSG 500 psi for 10 min
Set CIBP @ 8,121' - 50' above top perf
Perforate 8171' to 8,314'
No need to test, perfs above, do not woc
Cement covers Bone Springs to bottom perf.
Spot 21 sxs Class H cement from 8,508' to 8,318'

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 600740

CONDITIONS

Operator: EOG RESOURCES INC 5509 Champions Drive Midland, TX 79706	OGRID: 7377
	Action Number: 600740
	Action Type: [C-103F] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	A Cement Bond Log (CBL) is required to be submitted to electronic permitting.	7/15/2026
gcordero	Submit Cement Bond Logs (CBL) prior to submittal of C-103P.	7/15/2026