

VIII

Geologic

Data

VJ SAU #132

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1620	T. Canyon
T. Salt	1750	T. Strawn
B. Salt	2680	T. Atoka
T. Yates	2835	T. Miss
T. 7 Rivers	3195	T. Devonian
T. Queen	3781	T. Silurian
T. Grayburg	4104	T. Montoya
T. San Andres	4407	T. Simpson
T. Glorieta		T. McKee
T. Paddock		T. Ellenburger
T. Blinbry		T. Gr. Wash
T. Tubb		T. Delaware Sand
T. Drinkard		T. Bone Springs
T. Abo		T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
 No. 2, from _____ to _____

No. 3, from _____ to _____
 No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from _____ to _____ feet
 No. 2, from _____ to _____ feet
 No. 3, from _____ to _____ feet


LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
1580	1620	40	DOLOMITE				
1620	1700	80	ANHYDRITE				
1700	1750	50	SHALE				
1750	2600	850	SALT				
2600	3040	440	SALT/SHALE/ANHY				
3040	3770	730	ANHY/DOLOMITE				
3770	3860	90	DOLOMITE/SAND/ANHY				
3860	4000	140	DOLOMITE/ANHYDRITE				
4000	4120	120	SAND/DOLOMITE/ANHY				
4120	4600	480	DOLOMITE				

ChevronTexaco
15 Smith Road
Midland, TX 79705


Vacuum Grayburg San Andreas Unit # 132
Lea County, New Mexico


265	2.65	1/2	0.88	2.32	2.32
537	2.72	3/4	1.31	3.57	5.89
779	2.42	1/2	0.88	2.12	8.01
1025	2.46	1	1.75	4.31	12.31
1279	2.54	1	1.75	4.45	16.76
1550	2.71	1	1.75	4.74	21.50
2056	5.06	1/2	0.88	4.43	25.93
2564	5.08	1 1/2	2.63	13.34	39.26
3072	5.08	2 1/4	3.94	20.00	59.26
3581	5.09	1 1/2	2.63	13.36	72.63
4088	5.07	2	3.50	17.75	90.37
4600	5.12	1 1/2	2.63	13.44	103.81



Michael Roghair - General Manager

The attached instrument was acknowledged before me on the 20th day of May, 2004 by
Michael Roghair - General Manager, CapStar Drilling, L.P.





Notary Public