



NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

BILL RICHARDSON
Governor
Joanna Prukop
Cabinet Secretary

Mark E. Fesmire, P.E.
Director
Oil Conservation Division

ADMINISTRATIVE ORDER SWD-967

APPLICATION OF NEARBURG PRODUCING COMPANY FOR PRODUCED WATER DISPOSAL, EDDY COUNTY, NEW MEXICO.

ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Rule 701(B), Nearburg Producing Company made application to the New Mexico Oil Conservation Division on January 10, 2005, for permission to utilize for produced water disposal its proposed McKittrick 11 Federal Well No. 5 (API No. 30-015-33611) to be located 1200 feet from the North line and 1,490 feet from the West line (the bottom hole location being 1,677 feet from the South line and 882 feet from the West line) of Section 11, Township 22 South, Range 24 East, NMPM, Eddy County, New Mexico.

THE DIVISION DIRECTOR FINDS THAT:

- (1) The application has been duly filed under the provisions of Rule 701(B) of the Division Rules and Regulations;
- (2) Satisfactory information has been provided that all offset operators and surface owners have been duly notified;
- (3) The applicant has presented satisfactory evidence that all requirements prescribed in Rule 701 will be met; and
- (4) One objection was received within the waiting period prescribed by said rule, but was subsequently dropped.

IT IS THEREFORE ORDERED THAT:

The applicant is hereby authorized to utilize its proposed McKittrick 11 Federal Well No. 5 (API No. 30-015-33611) to be located 1200 feet from the North line and 1,490 feet from the West line (the bottom hole location being 1,677 feet from the South line and 882 feet from the West line) of Section 11, Township 22 South, Range 24 East, NMPM, Eddy County, New Mexico, in such manner as to permit the injection of produced water for disposal purposes into

the Cisco and Canyon formations through a perforated interval from approximately 8,556 feet to 9,187 feet MD (or 8,212 feet to 8,812 feet TVD) and through plastic-lined tubing set with a packer located within 100 feet of the top of the injection interval.

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

As preparation for injection:

- (a) The cement job on the 7-inch casing shall be designed to raise cement to the surface. If cement does not circulate, a cement bond log shall be run and supplied to the Artesia district office of the Division.
- (b) The injection interval shall be swab tested, a sample of formation water analyzed in an approved lab, and the water analysis supplied to the Engineering Bureau of the Division in Santa Fe.
- (c) The operator shall estimate the initial reservoir pressure of the injection interval, i.e. from stable fluid levels, and submit this in writing to the Engineering Bureau of the Division in Santa Fe (referencing SWD-967).

After installing injection tubing, the casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer.

The wellhead injection pressure on the well shall be limited to **no more than 1,642 psi**. In addition, the injection well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface injection pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the injection formation. Such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the Artesia district office of the Division of the date and time of the installation of disposal equipment and of any mechanical integrity test so that the same may be inspected and witnessed.

The operator shall immediately notify the supervisor of the Artesia district office of the

Division of the failure of the tubing, casing, or packer in said well and shall take such steps as may be timely and necessary to correct such failure or leakage.

PROVIDED FURTHER THAT, jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh water or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the injection authority granted herein.

The operator shall provide written notice of the date of commencement of injection to the Artesia district office of the Division.

The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Rule Nos. 706 and 1120 of the Division Rules and Regulations.

The injection authority granted herein shall terminate one year after the effective date of this order if the operator has not commenced injection operations into the subject well, provided however, the Division, upon written request by the operator, may grant an extension thereof for good cause shown.

Approved at Santa Fe, New Mexico, on February 16, 2005.



MARK E. FESMIRE, P.E.
Director

MEF/wvjj

cc: Oil Conservation Division – Artesia
Bureau of Land Management - Carlsbad