112421 412

EME E-21 EOL 2013

CLOSURE

RICE Operating Company

122 West Taylor • Hobbs, New Mexico 88240 Phone: (575) 393-9174 • Fax: (575) 397-1471

April 1, 2014

Mr. Leonard Lowe

New Mexico Energy, Minerals, & Natural Resources Oil Conservation Division, Environmental Bureau 1220 S. St. Francis Drive Santa Fe, New Mexico 87505

RE: Termination Request

EME E-21 EOL: UL/E, Sec. 21, T20S, R37E

RICE Operating Company - Eunice Monument Eumont SWD System

Mr. Lowe:

Rice Operating Company (ROC) is the service provider (agent) for the EME Saltwater Disposal (SWD) System and has no ownership of any portion of the pipeline, well, or facility. The System is owned by a consortium of oil producers, System Parties, who provide all operating capital on a percentage ownership/usage basis.

Background

In 2013, ROC initiated work on the former E-21 EOL. The site is located in UL/E, Sec. 21, T20S, R37E. NM OSE records indicate that groundwater would likely be encountered at a depth of approximately 26 +/- feet. The site was delineated using a backhoe to collect soil samples at regular intervals, creating a 5x7x7-ft deep excavation. Each sample was field titrated for chlorides and field screened using a PID for hydrocarbons, resulting in concentrations similar to background. The 7-ft sample was sent to a commercial laboratory for analysis of chloride and TPH, resulting in a chloride concentration and a gasoline range organics (GRO) concentration below detectable limits, and a diesel range organics (DRO) concentration of 59.9 mg/kg. The excavation was backfilled with clean, imported blows and and contoured to the surrounding area. A sample of the blows and was submitted to a commercial laboratory for analysis of chloride, resulting in a concentration below detectable limits. The sample was also field tested for hydrocarbons using a PID, resulting in a reading of 3.8 ppm. On 1/8/2014, the site was seeded with a blend of native vegetation and is expected to return to a productive capacity at a normal rate. The junction box site map, area map, final report, photo documentation, laboratory analysis, PID sheet, chloride graph, and revegetation form are attached.

Recommendations

Site investigation demonstrates that residual chloride and hydrocarbons in the vadose zone will not with reasonable probability contaminate groundwater in excess of NMOCD standards. This site meets the requirements of the NMOCD-approved Revised Junction Box Upgrade Work Plan (July 16, 2003). As such, ROC request termination of the regulatory file, or similar closure status.

Please contact me at (575)393-2967 if you have any questions or wish to discuss this site. Thank you for your time and consideration.

Sincerely,

RICE Operating Company

Hack Conder

Environmental Manager

enclosures

RICE OPERATING COMPANY JUNCTION BOX FINAL REPORT

BOX LOCATION

ļ	SWD SYSTEM	JUNCTION	UNIT	SECTION	TOWNSHIP	RANGE	COUNTY	BOX D	IMENSIONS - F	EET
	Eunice Monument	E-21 EOL	E	21	20S	37E	Lea	Length	Width	Depth
	Eumont (EME)			L	<u> </u>	L			Eliminated	
	LAND TYPE: I	BLM	STATE	_ FEE LA	NDOWNER	Millard I	Deck Estate	OTHER		
	Depth to Groui	ndwater	26	_feet	NMOCD	SITE ASSI	ESSMENT	RANKING S	CORE:	20
	Date Started	12/9	/2013	_ Date Co	mpleted	1/8/2014	OCE) Witness	No	
	Soil Excavated	9.1	cubic ya	rds Exc	cavation Le	ngth5	Widt	h7	Depth	7 feet
	Soil Disposed	48	cubic ya	rds Of	fsite Facility	Sund	dance	Location	Eunice,	NM
FINA	L ANALYT	ICAL RE	SULTS:	Sampl	e Date <u>12/</u>	9/2013,12/1	8/2013	Sample De	pth	7'
		TPH and (Chloride lab	oratory test i procedures		-		roved lab and	testing	
	Sample	PID (fi	eld) G	RO	DRO	Chloride			IDE FIELD T	ESTS
	Location	ррп		g/kg	mg/kg	mg/kg		LOCATION	DEPTH	mg/kg
	URCE 7' GRAE	3 0.0) <5	50.0	59.9	<16.0		background	6"	117
E	BLOWSAND	3.8	3			<16.0			4'	58
							ve	rtical delineation trench at the	5'	149
Gener	al Description	of Remed	ial Action:	This junction	on and line we	ere eliminated	<u>յ</u> յւ	inction (source)	6'	86
during t	he pipeline repla	cement/upgr	ade program	. After the fo	rmer junction	box was			7'	87
remove	d, an investigatti	on was cond	lucted, using	a backhoe to	collect soil sa	amples at				
regular	intervals, creatin	g a 5x7x7 ft	deep excavat	tion. Chloride	field test perf	ormed on ea	ch sample	yielded low con	centrations of	chloride.
Organio	vapors were m	easured usin	g a PID whicl	h also yielded	low concentr	ations. The c	leepest san	nple, 7 ft. below	ground surface	ce
(BGS)	was sent to a cor	mmerical lab	oratory for ar	nalysis of chlo	ride and TPH	l, which confi	rmed low co	oncentrations of	each. The site	e was
bac	kfilled with clean,	, imported so	il to ground:	surface and c	ontoured to t	he surroundir	ng area. A s	ample of the im	ported soil wa	as sent to a
comme	rcial laboratory f	or analysis o	f chloride, res	sulting in a lov	v concentration	on. On 1/8/20	14, the site	was seeded wi	ith a blend of n	ative
vegetat	ion and is expec	ted to return	to a producti	ve capacity at	t a normal rat	e.				
					,					
										vegetation form
IHE	REBY CERTIF	Y THAT TH	HE INFORM	ATION ABO			MPLETE	TO THE BEST	T OF MY KN	OWLEDGE
					AND BEL	IEF.				
RI	EPORT					///	,	7	Rice Environm	ental Consulting
ASS	SEMBLED BY	Laura Flor	res SIG	MATURE	alle	a K	Ores	OMPANY	<u> </u>	Safety
SITE SI	JPERVISOR	Dyllan Yarbr	rough SIG	SNATURE .	, , ,	Vot available		COMPANY		nental Consulting Safety
22 00		- jiiaii Tarbi	ough ore		/			_ 001411 7141		
PROJE	CT LEADER	Kyle Norm	an SIG	SNATURE	hyle 1	/a		DATE	2-2	8-14
					,					

Site Map

24	19	20	21	22	23
25	30	29	28	27	26
25		2			130
19S 36E	198 37E	MO	NUMENT		
9178 9	(學) "美国	设建设、人类数			The 1984 Ha
1		学 计			
36	31	32	33	34	35
			* 1		
30 E			BiyWaller	Rd.	
被巡	To the				
1	6	5	4	3	2
	T AT	The state of the s			
	2. 美国				
	10000000000000000000000000000000000000	4	The same		
12	7	. 8	4	10	11
208 36E			20S 37E		
Jan Ro			. 4		
Made	N. N.	1.4			
13	18	17	16	15	14
		IN THE			
	Internal Control		EME E 21 EOL	11/	
24	19	20	2		23
			Source: Est, Digital@iote Getmapping, Asroetts, Je	, Scofje, kostoo, USDA, U K., ISF, svisslopo, and Se S	SSS, AEX.
					N



EME E-21 EOL

Unit Letter E, Section 21, T20S, R37E Lea County, NM



0 2,500 5,000 HHH Feet

Drawing date: 2/19/14 LF

Area Map





EME E-21 EOL

Unit Letter E, Section 21, T20S, R37E Lea County, NM



0 620 1,240 HHH Feet

Drawing date: 2/19/14 LF

EME E-21 EOL

UL/E Sec.21 (T20S-R37E)



Excavating site, facing west

12/09/2013



Backfilling excavation, facing northwest

12/20/2013



Collecting sample, facing northeast

12/09/2013



Seeding site, facing south

1/08/2014



December 10, 2013

KYLE NORMAN

Rice Operating Company

112 W. Taylor

Hobbs, NM 88240

RE: EME E-21 EOL

Enclosed are the results of analyses for samples received by the laboratory on 12/09/13 16:35.

Cardinal Laboratories is accredited through Texas NELAP under certificate number T104704398-13-5. Accreditation applies to drinking water, non-potable water and solid and chemical materials. All accredited analytes are denoted by an asterisk (*). For a complete list of accredited analytes and matrices visit the TCEQ website at www.tceq.texas.gov/field/qa/lab-accreditehtml.

Cardinal Laboratories is accreditated through the State of Colorado Department of Public Health and Environment for:

Method EPA 552.2

Haloacetic Acids (HAA-5)

Method EPA 524.2

Total Trihalomethanes (TTHM)

Method EPA 524.4

Regulated VOCs (V1, V2, V3)

Accreditation applies to public drinking water matrices.

Celeg & Keine

This report meets NELAP requirements and is made up of a cover page, analytical results, and a copy of the original chain-of-custody. If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Celey D. Keene

Lab Director/Quality Manager



Analytical Results For:

Rice Operating Company KYLE NORMAN 112 W. Taylor Hobbs NM, 88240

Fax To:

(575) 397-1471

Received:

12/09/2013

Reported:

12/10/2013

Project Name:

EME E-21 EOL

Project Number: Project Location: NONE GIVEN

NOT GIVEN

Sampling Date:

12/09/2013

Sampling Type:

Soil

Sampling Condition: Sample Received By: Cool & Intact

Jodi Henson

Sample ID: VERTICAL @ SOURCE @ 7' (H302968-01)

Chloride, SM4500CI-B	mg,	/kg	Analyze	d By: AP					
Analyte	Result	Reporting Limit	Analyzed	Method Blank	BS	% Recovery	True Value QC	RPD	Qualifier
Chloride	<16.0	16.0	12/10/2013	ND	416	104	400	3.92	
TPH 8015M	mg	/kg	Analyze	d By: ck					
Analyte	Result	Reporting Limit	Analyzed	Method Blank	BS	% Recovery	True Value QC	RPD	Qualifier
GRO C6-C10	<50.0	50.0	12/10/2013	ND	198	99.0	200	3.86	
DRO >C10-C28	59.9	50.0	12/10/2013	ND	207	103	200	3.24	
Surrogate: 1-Chlorooctane	104	% 65.2-14	0						
Surrogate: 1-Chlorooctadecane	111	% 63.6-15	4						

Cardinal Laboratories *=Accredited Analyte

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiaries, affiliates or successors arising out of or related to the performance of the services hereunder by Cardinal, regardless of whether such claim is based upon any of the above stated reasons or otherwise. Results relate only to the samples identified above. This report shall not be reproduced except in full with written approval of Cardinal Laboratories.

Celeg D. Keene



Notes and Definitions

ND Analyte NOT DETECTED at or above the reporting limit

RPD Relative Percent Difference

** Samples not received at proper temperature of 6°C or below.

*** Insufficient time to reach temperature.

Chloride by SM4500CI-B does not require samples be received at or below 6°C

Samples reported on an as received basis (wet) unless otherwise noted on report

Cardinal Laboratories *=Accredited Analyte

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim ansing, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiaries, affiliates or successors arising out of or related to the performance of the services hereunder by Cardinal, regardless of whether such claim is based upon any of the above stated reasons or otherwise. Results relate only to the samples identified above. This report shall not be reproduced except in full with written approval of Cardinal Laboratornes.

Celey & Keine



CHAIN-OF-CUSTODY-AND-ANALYSIS-REQUEST

88240	2476
ΣŽ	393-2476
Hobbs	(575)
	FAX
t Marland	393-2326
East	393
101	(575)

Company Name:	ie: Pyce			0/157/10		ANALYSIS	ANALYSIS REQUEST		
Project Manag	Project Manager: Kyle Norwan		P.O. #:				_		L
Address:	<i>(</i>)		Company:						
City:	State: Λ) Μ	Zip:	Attn:						
Phone #:	Fax#:		Address:					-	
Project #:	Project Owner:	•	City:						
Project Name:			State;	Zip:					
Project Locatic	Project Location: EME EAI EOL		Phone #:						
Sampler Name:	: KARANOTA (G WIS		Fax #:						
FOR LAB USE ONLY		MATRIX	PRESERV.	SAMPLING					
Lab I.D.	Sample I.D.	.9 ОР (С)ОМР. ВЯЗИВЕР ВЭТАМЕР ВЭТАМЕ	: 00F 34SE:		sobides PP				
H302968		GROU WASTI WASTI DIL	SLUDO OTHER OTHER OTHER OTHER	DATE TIME	17				
	Vertide @ saxce @ 71	G -	7	12-9-13 23:05	7				
									-
	5								
The state of the s									
LEASE NOTE: Liability a	PLEASE NOTE: Liablity and Damages. Cardinars liability and client's exclusive remedy for any claim arising		ed or tort, shall be limited	whether based in contract or tort, shall be limited to the amount paid by the client for the	the				

analyses. All claims including those for negligence and any other cause whatsoever shall be deemed wahved unless made in writing and recaived by Cardinal within 30 days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequental damages, including without limitation, business intarruptions, loss of use, or base of profits incurred by client, its substitutions,

Fax Result: Tres | REMARKS: @ M Ail result + 10: Time: Delivered By: (Circle One) Affiliates or successors arising out of Relinquished By: CHRANJA L Relinquished By:

KUS H lueinheimer@rice-ecs.com KNOFMAN @ rice-ecs.com Acomber & rices sud . Com Klewis & rice-ecs.com Kjones@piceswd.com

† Cardinal cannot accept verbal changes. Please fax written changes to (575) 393-2326

Sampler - UPS - Bus - Other:

RICE ENVIRONMENTAL CONSULTING & SAFETY

122 West Taylor Hobbs, NM 88240 PHONE: (505) 393-9174 FAX: (505) 397-1471 PID METER CALIBRATION & FIELD REPORT FORM

CK.		MODEL: PGM 7300	SERIAL NO:	590-000508
MODEL		MODEL: PGM 7300	SERIAL NO:	590-000504
NO.	X	MODEL: PGM 7320	SERIAL NO:	592-903318
		MODEL: PGM 7300	SERIAL NO:	590-000183

GAS COMPOSITION: ISOBUTYLENE 100PPM / AIR: BALANCE

LOT NO: HAL-248-100-1	EXPIRATION DATE: 7/1/2015
	METER READING ACCURACY: 100

ACCURACY: +/- 2%

COMPANY RICE OPERATING

SYSTEM	JUNCTION	UNIT	SECTION	TOWN SHIP	RANGE
EME	E-21 EOL	Е	21	20S	37E

SAMPLE ID	PID	SAMPLE ID	PID
Background @ 6"	0.8		
Source @ 3'	1.2		
Source @ 4'	0.2	······	
Source @ 5'	0.3		
Source (a) 3	0.3		
Source @ 6'	0.5		
Source @ 7'	1.1		
Source @ 8'	0		
6			
Source @ 9'	0		
Source @ 10'	0		
Source (a) 10	0		
Source @ 11'	0		
			7,774,7
Source @ 12'	0		

I verify that I have calibrated the above instrument in accordance to the manufacture operation manual.

SIGNATURE:	Not available	DATE:	12/9/2013



December 26, 2013

KYLE NORMAN Rice Operating Company 112 W. Taylor

RE: EME E-21 EOL

Hobbs, NM 88240

Enclosed are the results of analyses for samples received by the laboratory on 12/18/13 16:00.

Cardinal Laboratories is accredited through Texas NELAP under certificate number T104704398-13-5. Accreditation applies to drinking water, non-potable water and solid and chemical materials. All accredited analytes are denoted by an asterisk (*). For a complete list of accredited analytes and matrices visit the TCEQ website at www.tseg.texes.gov/field/ga/lab_accred_certif.html.

Cardinal Laboratories is accreditated through the State of Colorado Department of Public Health and Environment for:

Method EPA 552.2 Haloacetic Acids (HAA-5) Method EPA 524.2 Total Trihalomethanes (TTHM) Regulated VOCs (V1, V2, V3)

Method EPA 524.4

Accreditation applies to public drinking water matrices.

Celey & Keine

This report meets NELAP requirements and is made up of a cover page, analytical results, and a copy of the original chain-of-custody. If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Celey D. Keene

Lab Director/Quality Manager



PHONE (575) 393-2326 ° 101 E. MARLAND ° HOBBS, NM 88240

Analytical Results For:

Rice Operating Company KYLE NORMAN 112 W. Taylor

Hobbs NM, 88240

Fax To:

(575) 397-1471

Received:

12/18/2013

Reported:

12/26/2013

Project Name:

EME E-21 EOL

Project Number: Project Location: NONE GIVEN

Sampling Date:

12/18/2013

Sampling Type:

Soil

Sampling Condition: Sample Received By: ** (See Notes)

Kathy Perez

Sample ID: BLOW SAND (H303072-01)

Chloride, SM4500CI-B mg/kg

Analyzed By: CK

Analyte	Result	Reporting Limit	Analyzed	Method Blank	BS	% Recovery	True Value QC	RPD	Qualifier
Chloride	<16.0	16.0	12/26/2013	ND	432	108	400	3.77	

Cardinal Laboratories

*=Accredited Analyte

PLEASE NOTE: Liability and Damages, Cardinal's liability and clent's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of use, or loss of profits incurred by client, its subsidiaries, affiliates or successors arising out of or related to the performance of the services hereunder by Cardinal, regardless of whether such claims is based upon any of the above stated reasons or otherwise. Results relate only to the samples identified above. This report shall not be reproduced except in full with written approval of Cardinal Laboratories.

Celey D. Keine



Notes and Definitions

ND Analyte NOT DETECTED at or above the reporting limit

RPD Relative Percent Difference

** Samples not received at proper temperature of 6°C or below.

*** Insufficient time to reach temperature.

Chloride by SM4500CI-B does not require samples be received at or below 6°C

Samples reported on an as received basis (wet) unless otherwise noted on report

Cardinal Laboratories *=Accredited Analyte

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiaries, affiliates or successors arising out of or related to the performance of the services hereunder by Cardinal, regardless of whether such claims is based upon any of the above stated reasons or otherwise. Results relate only to the samples identified above. This report shall not be reproduced except in full with written approval of Cardinal Laboratories.

Celey D. Kune

CHAIN-OF-CUSTODY AND ANALYSIS REQUEST

ARDINAL LABORATORIES
101 East Marland, Hobbs, NM 88240 2111 Beechwood, Abilene, TX 79603 (505) 393-2326 FAX (505) 393-2476 (325) 673-7001 FAX (325)673-7020

Company Name: RICE Operating	jing		BILL TO					ANALYSIS	YSIS	REQUEST		
Project Manager: Kyle Norman	and the second control of the second control	general, i (1975). I Salanya dan dan dan dan dan dan dan dan dan da	P.O.#:		<u></u>	_						
Address: 112 W. Taylor	e experience " (MM) code and programme and describe the programme and the contract contract of the annual contract of the cont	ent deserve al 1 figure d'Assent (16 téléphine théa seath i decontraparation de decorrange à constitue de la c	Company:					SI				
city: Hobbs	State: NM	Zip: 88240	Attn:	and and any or account to the long gard				ıoi				
Phone #:	Fax #:		Address:					и\				
Project#:	Project Owne	<u>:</u>	City:			IAI	Н	/ /S				
Project Namo: EME	E-21 E0L		State: Zip:		39t	X I2	Ч	uo				
Project Location:			Phone #:			(3 .		ite	SC			
Sampler Namo: Dyllan Yarbrough	dþ		Fax#:					CS	1			
FOR UAB USE ONLY		MATRIX	PRESERV. SAMPLING					Э				
Lab I.D. Sam UZ OZOTĄ	Sample I.D.	CONTAINERS CONTAINERS ROUNDWATER VASTEWATER OIL SIL	лиев: СОО/ВАSE. ОТНЕВ: ОТНЕВ:	ш Х Е		11	L	Complet	**************************************			
2	THE RESIDENCE AND ADDRESS OF THE PROPERTY OF T	S S A	0 2 /		+	\downarrow			t	-		T
13/ Ew Sim			2/3/13	2,55								
PLEASE NOTE: Labidity and Damages, Carland's bandity and obside sixthane remore that be day claim analyses. At darm including these for neglegions and any observative whethere in that he deemed man server. In no guest staff of carland the place for the place in or consequented demages, including staff or server and of desired for the reformance of services for the remove the formation to Carland (or server).	dry and clerifa exchance temory for any clein and any clein and any clear states whatsoever that he deemed was all or consequented defenges, including without first channels of senters have market by Cambral results.		und whether based in contract, at time, there is needed to the amount paid by the about to the and unhear made in withing and received by Carded within 30 days, after competius or the applicable. Addin, business impropries, the COMPT, by the top of poths received by dens, it is ubstantiant of the about the about the above shad is active to the property.	and by the chert for the entire correspond to the a chert, the substitution asserts as of the asserts or otherwise.	and board	-			1		-	7
///	Timp:	SIIB Received By:		Phone Result Pax Result: REMARKS:	<u>::</u>	U Yes C	8 8 3 0	Add'l Phone #: Add'l Fax #:	hone #:			
Relinguished BV:	Date: Time:	Received By:	2	email results knorman@ri	sults n@ric	Se-ec	s.con	t;hco	nder(email results knorman@rice-ecs.com;hconder@rice-ecs.com;	;moc	
Delivered By: (Circle One)	TO THE PROPERTY OF THE PROPERT	Sample Condition	on CHECKED BY:	Lweinho Lpena@	simer grices	@rice wd.c	ecs om;d	.com yarbr	, kjon ough	Lweinheimer@rice-ecs.com; kjones@riceswd.com; Lpena@riceswd.com;dyarbrough@rice-ecs.com	/d.com; com	

† Cardinal cannot accept verbal changes. Please fax written changes to 505-393-2476

Sampler - UPS - Bus - Other; Delivered By: (Circle One)

Sample Condition Cool Intact

RICE ENVIRONMENTAL CONSULTING & SAFETY

122 West Taylor Hobbs, NM 88240 PHONE: (505) 393-9174 FAX: (505) 397-1471 PID METER CALIBRATION & FIELD REPORT FORM

	444	COMPANY	
		ACCURACY: +/- 2%	
	METER	R READING ACCURACY: 100	
LOT NO: HAL-248-1	00-1	EXPIRATION DATE: 7/1/2015	
	GAS COMPOSITION	I: ISOBUTYLENE 100PPM / AIR: BALANCE	
	MODEL: PGM 7300	SERIAL NO: 590-000183	
NO. X	MODEL: PGM 7320	SERIAL NO: 590-000304 SERIAL NO: 592-903318	
CK. MODEL	MODEL: PGM 7300 MODEL: PGM 7300	SERIAL NO: 590-000508 SERIAL NO: 590-000504	

SYSTEM	JUNCTION	UNIT	SECTION	TOWN SHIP	RANGE
ЕМЕ	E-21 EOL	Е	21	20S	37E

RICE OPERATING

SAMPLE ID	PID	SAMPLE ID	PID
BLOWSAND	3.8		

I verify that I have calibrated the above instrument in accordance to the manufacture operation manual.


SIGNATURE:	Not Available	DATE:	12/18/2013

EME E-21 EOL Unit 'E', Sec. 21, T20S, R37E

Backhoe samples at junction (source)

[Cl] ppm	85	149	98	L8
Depth bgs (ft)	4	5	9	7







Hobbs, NM 88241 Phone: (575) 393-4411 Fax: (575) 393-0293

					VEGET	ΓΑΤΙ	ON FOR	RM					
1. General Informat	ion												
Site name: EM	E E-21	EOL											
U/L	T	Section		Townsh	ip	Rang	je	Co	unty	Latit	ude	Longitude	
E		21		20		37		L	ea	32 33.	730'N	103 15.646'V	N
Contact Name: Had	k Cond	ler											
Email:	mlar,	<u>Frico-ees.com</u>											
Site size:													
2. Soils			ot rip	caliche sub	osoils; caliche	rocks bro	ght to the surf	ace by rip	ping shall be	removed.			
Salvaged from site	\perp	Bioremediated		X Im	ported		Blended			Depth (in)			
Texture:	Top				Describe	soil & su				Light brown	n fine sand		
Soil prep methods:		Rip		D	epth (in)		D	isc X	<u> </u>	Depth (in)		Rollerpack	
Date completed:													
3. Bioremediation Fertilizer				Нау			Trick or adoptions of the latest or the late		Other		**************************************		Τ
				Hay					Other				<u>L_</u>
Type:				1					Describe:		(1 D		
Lbs/acre:				<u> </u>					5 bags B	ioNhance,	b bags Po	otting mix	
4. Seeding	*Auc	nch seed bag tags to th	his for	rm. Seed bo	ng tags shall co	ontain the	site name and .	S-T-R.					
Custom Seed Mix	Х	Prescribed Mix		Se	ed Mix Name		lbs. of Blue Gra Vheat	mma, 6 lbs	. Side Oats, &	6 lbs of Winter	Date:	1/8/2014	
Broadcast						1	Лethod:	Porta	able seeder				
Soil conditions durin	g seed:	Dry	X	Damp	We	t							
Observations:		The amendments	and s	seed were	raked into th	e soil.							
5. Certification		by certify that the inform	ation i	n this form a				<u></u>	nowledge and t	pelief.		1000	
Name: Jose Flor	es	1		//	Title:	Enviro	nmental Tech	1			Date:	1/8/2014	
Signature:		Jase	/	100	4.5								

RICE Operating Company

122 West Taylor • Hobbs, New Mexico 88240011 MAS 32 A 10: 17
Phone: (575) 393-9174 • Fax: (575) 397-1471

April 1, 2014

Mr. Leonard Lowe New Mexico Energy, Minerals, & Natural Resources Oil Conservation Division, Environmental Bureau 1220 S. St. Francis Drive Santa Fe, New Mexico 87505

RE: JUNCTION BOX UPGRADE REPORT for 2013

EME SWD SYSTEM Lea County, New Mexico

Mr. Lowe:

Rice Operating Company (ROC) takes this opportunity to submit the Junction Box Upgrade results for the year 2013. Enclosed is a list of the completed junction boxes and their respective closure/disclosure dates. These boxes are located in the Eunice-Monument-Eumont (EME) Salt Water Disposal (SWD) System located in the vicinity of Eunice, New Mexico.

ROC completed 11 junction boxes in 2013.

Enclosed are the 2008 results (17 sites evaluated with 22 sampling locations) from the PID/BTEX study described in the NMOCD-approved Revised Junction Box Upgrade Work Plan (July 16, 2003). A third-party analysis, conducted by Peter Galusky, Jr. Ph.D. of Texerra, concluded from the data collected thus far that field-composited values tend to produce slightly higher BTEX numbers above the point at which BTEX concentrations become significant. This is likely due to the fact that BTEX is volatile and quickly biodegradable. This analysis was submitted to NMOCD on March 12, 2009. An appropriate number of sample sites could not be obtained to conduct a 2013 BTEX comparison analysis. Peter Galusky, Jr. Ph.D. of Texerra also compared ROC's 2013 chloride field tests to chloride laboratory analyses; the analysis is also enclosed. The study of this data continues to validate the accuracy of the chloride field tests employed by ROC.

ROC is the service provider (agent) for the EME SWD System and has no ownership of any portion of the pipeline, well, or facility. The System is owned by a consortium of oil producers, System Parties, who provide all operating capital on a percentage ownership/usage basis.

Replacement/closure projects of this magnitude require System Party AFE approval and work begins as funds are received.

Thank you for your consideration of this Junction Box Upgrade Report for 2013.

RICE OPERATING COMPANY

Hack Conder

Environmental Manager

enclosures as stated

cc: SC, file, Mr. Geoffrey Leking

NMOCD, District I Office 1625 N. French Drive Hobbs, NM 88240

Rice Operating Company EME SWD System Junction Box Upgrade Project 2013 Completed Boxes

		Leg	al De	erip	ion	mphhimin in the section	e se andalestale		
	Jet Box Name	Unit	360	Ŧ	R	Completion Date	OCD Assessment Score	Report Status	Case Number
1	B-19 EOL	В	19	198	37E	6/28/2013	20	Closure	
2	E-21 EOL	E	21	20S	37E	1/8/2014	20	Closure	
3	JCT. D-19	D	19	198	37E	5/10/2013	20	Closure	-
4	JCT. D-20	D	20	198	37E	6/10/2013	20	Closure	
5	JCT. F-26	F	26	205	36E	11/7/2012	0	Closure	
6	JCT. H-4	Н	4	20S	36E	6/7/2013	20	Closure	
7	JCT. I-9	I	9	20\$	36E	6/7/2013	20	Closure	
8	JCT. K-19	K	19	198	37E	6/11/2013	20	Closure	
9	M-9 EOL	M	9	215	36E	6/24/2013	0	Closure	
10	O-28 EOL	0	28	20\$	36E	n/a	0	Closure	
11	P-5 EOL	Р	5	215	36E	6/24/2013	0	Closure	

L. Peter Galusky, Jr. Ph.D., P.G.

Texerra

505 N Big Spring, Suite 404 Midland, Texas 79701 Tel: 432-634-9257 E-mail: lpg@texerra.com

March 10th, 2009

Mr. Brad Jones New Mexico Energy, Minerals, & Natural Resources Oil Conservation Division, Environmental Bureau 1220 S. St. Francis Drive Santa Fe, New Mexico 87504

Re: Comparison of Field versus Lab Compositing of BTEX soil samples

Rice Operating Company, Junction Box Upgrade Work Plan

Sent via Certified Mail w/ Return Receipt No. 7006 0100 0001 2438 3944

Dear Mr. Jones:

On behalf of Rice Operating Company (ROC) I am submitting the attached comparison and analysis of field versus laboratory soil compositing for soil BTEX samples. This is to address the question of whether it is better to mix multiple samples in the field or to do so in the laboratory in order to produce a composite, representative sample for analysis. This work was undertaken in support of ROC's Junction Box Upgrade Work Plan to ensure the quality of their field analysis program.

In brief, this work indicates that field compositing of soil samples generally gives rise to *slightly* higher BTEX values than does laboratory compositing of multiple samples. This is presumably due to the likelihood that field compositing and packaging of soil samples better preserves sample integrity. It would therefore appear that field compositing would represent the better method of procuring soil samples for subsequent analysis of BTEX.

Please call me if you have any questions or wish to discuss any of the details of this study.

ROC is the service provider (agent) for various Salt Water Disposal Systems (SWDs) and has no ownership of any portion of pipeline, well or facility. The SWD Systems that ROC operates are owned by a consortium of oil producers, System Partners, who provide all operating capital on a percentage ownership/usage basis.

Sincerely,

L. Peter Galusky, Jr. Ph.D.

Principal

Copy: Rice Operating Company,

Edward Hansen (NMOCD) sent certified mail w/ return receipt

No. 7006 0100 0001 2438 3937

Attachment: As noted, above.

Rice Operating Company Comparison of Field Compositing versus Laboratory Compositing of Soil BTEX Samples¹

The careful mixing of multiple soil samples is critical in order to produce a representative, composite sample from a respective study area (such as a excavation face or bottom). Field technicians typically take four or five "grab" samples from excavation walls and/or bottom and send each of these to a laboratory for analysis of the composite, or mixed, sample. It would be far simpler, however, to composite such samples in the field. This study was undertaken to determine if field compositing produced results substantially different than laboratory compositing for the analysis of BTEX. Data were provided by Rice Operating Company encompassing 22 sampling locations over the period of 2004 through 2008.

A comparison of lab-composited soil samples versus field-composited soil samples revealed a close correspondence for total BTEX between the two methods (Figure 1).




Figure 1 - Laboratory versus field-composited soil samples analyzed for BTEX.

The high R² value (0.9836) of the best-fit statistical regression line indicates a high degree of reliability in using the field-compositing method over the range of values observed. Below a "field-composited BTEX" value of 0.61 ppm the "lab-composited BTEX" values are slightly lower. However, above a field-composited BTEX value of 0.61 the lab-composited values run slightly lower. In other words, the field-composited values tended to produce slightly higher BTEX numbers above the point at which BTEX concentrations become significant.

There is a reason for this. BTEX is volatile and quickly biodegradable. The compositing and "packaging" of soil samples in the field minimize the handling and aeration that occur in the laboratory. Thus, field-composited soil samples lose less BTEX to evaporation and/or biodegradation prior to laboratory analysis. In other words, the field compositing and packaging of soil samples better preserves sample integrity, and for this reasons would appear to represent the better method of procuring soil samples for subsequent analysis of BTEX.

2

¹ Prepared 03-12-09 by L. Peter Galusky, Jr. of Texerra.

L. Peter Galusky, Jr. Ph.D., P.G.

Texerra LLC

20055 Laredo Lane Monument, CO 80132 Tel: 719-339-6791 E-mail: lpg@texerra.com

March 25th, 2014

Mr. Leonard Lowe New Mexico Energy, Minerals, & Natural Resources Oil Conservation Division, Environmental Bureau 1220 S. St. Francis Drive Santa Fe, New Mexico 87505

Re: Comparison of 2013 Laboratory versus Field Measured Soil Chloride Values Rice Operating Company, Junction Box Upgrade Work Plan

Mr. Lowe:

The attached comparison and analysis of 2013 laboratory versus field measured soil chloride values is submitted in support of Rice Operating Company's (ROC's) Junction Box Upgrade Work Plan to ensure the quality of their field analysis program.

In brief, this work indicates that Rice's 2013 field chloride measurement efforts provided a reasonable qualitative approximation of the laboratory-measured (and presumed true) values.

ROC is the service provider (agent) for various Salt Water Disposal Systems (SWDs) and has no ownership of any portion of pipeline, well or facility. The SWD Systems that ROC operates are owned by a consortium of oil producers, System Parties, who provide all operating capital on a percentage ownership/usage basis.

Please call me if you have any questions or wish to discuss this study.

Sincerely,

L. Peter Galusky, Jr. Ph.D.

Principal

Copy: Glenn VonGonten, NMOCD; Rice Operating Company

Attachment: As noted, above.

Rice Operating Company Comparison of Laboratory to Field Measured Soil Chloride Concentrations Based upon 2013 Field Data

A representative sample of 29 pairs of laboratory versus field measured soil chloride values was compared to determine how well field measurements matched laboratory measurements. It is assumed that laboratory measurements better represent the "true" values due to the controlled environment that a laboratory provides. A simple plot of the laboratory versus field measured soil chloride values is given below (Figure 1).




Figure 1 – Laboratory versus field measured soil chloride measurements (n = 29 paired sets).

A straight line fit to the data confirms a general linear trend over a wide range of soil chloride concentrations, and the R^2 value (0.90) indicates that field measurements provide a reliable approximation of laboratory-measured values. Based on the best-fit line of lab vs field measured values, field measured values overestimate lab measure values below a field measured value of 723 mg/kg and above this underestimate the lab-measured values. This is indicated in the graph where the (blue) best-fit line of lab vs field measured chlorides crosses the (black) line which would indicate a 1:1 correspondence.

Texerra LLC 2

	Junc	Iunction Box Upg	30x	Upgr	ade	Pro	gam	Clo	Sur	e/Dis	sclos	nre	Submi	ssic	ons f	rade Progam Closure/Disclosure Submissions for 2013	
									S 199	3.5							
BD																Closures	Closures Disclosures
Closure	4															4	
Disclosure	8																80
EME																	
Closure	11															11	
Disclosure	0																0
Total	23															15	8