

State of New Mexico
Energy, Minerals and Natural Resources Department

Susana Martinez
Governor

Ken McQueen
Cabinet Secretary

Matthias Sayer
Deputy Cabinet Secretary

Heather Riley, Division Director
Oil Conservation Division



Administrative Order SWD-1741
June 19, 2018

**ADMINISTRATIVE ORDER
OF THE OIL CONSERVATION DIVISION**

Pursuant to the provisions of Division Rule 19.15.26.8B, NMAC, Ray Westall Operating, Inc. (the "Operator") seeks an administrative order to utilize its proposed Guardian 25 State Com Well No. 1 ("Subject well") located 1980 feet from the North line and 1980 feet from the West line, Unit F of Section 25, Township 19 South, Range 27 East, NMPM, Eddy County, New Mexico, for the purpose of commercial disposal of produced water.

THE DIVISION DIRECTOR FINDS THAT:

The application has been duly filed under the provisions of Division Rule 19.15.26.8B, NMAC and satisfactory information has been provided that affected parties as defined in said rule have been notified and no objections have been received within the prescribed waiting period. The applicant has presented satisfactory evidence that all requirements prescribed in Rule 19.15.26.8 NMAC have been met and the operator is in compliance with Rule 19.15.5.9 NMAC.

IT IS THEREFORE ORDERED THAT:

The applicant, Ray Westall Operating, Inc. (OGRID 119305), is hereby authorized to utilize its Guardian 25 State Com Well No. 1 (API 30-015-36577) located 1980 feet from the North line and 1980 feet from the West line, Unit F of Section 25, Township 19 South, Range 27 East, NMPM, Eddy County, for commercial disposal of oil field produced water (UIC Class II only) in the interval consisting of the Cisco and Canyon formations through perforations from approximately 8840 feet to 9550 feet. Injection will occur through internally-coated, 4" ¹/₂-inch or smaller tubing and a packer set within 100 feet of the top perforation.

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the disposed water enters only the approved disposal interval and is not permitted to escape to other formations or onto the surface. This includes the completion and construction of the well as described in the application with the following modifications and, if necessary, as modified by the District Supervisor.

The operator shall run a CET/CBL (or equivalent) after the plugs and the cement have been cleaned out to approximately 9650 feet. Operator shall submit a copy to the Artesia District Office and Santa Fe Engineering Bureau Office of the Division before commencing further

workover operations. Further, Applicant shall have a meeting with the Artesia District Office to discuss the results of the CET/CBL. After the meeting with the Artesia District Office, the Operator shall provide to the Artesia District Office and Santa Fe Engineering Bureau Office a Sundry notice for all required work over operations.

The operator shall conduct a swab test of the new perforations for hydrocarbon potential analysis of hydrocarbon content. The Division's District office shall be noticed prior to this test and given the opportunity to witness the swab test. The operator shall supply the Division's District office and Santa Fe Engineering Bureau office a Sundry notice with the results of the swab test prior to commencing injection.

Within two years after commencing disposal, the operator shall conduct an injection survey, consisting of a tracer/temperature log or equivalent, over the entire injection interval using representative disposal rates. Copies of the survey results shall be provided to the Division's Artesia District office and Santa Fe Engineering Bureau office.

After installing tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The well shall pass an initial mechanical integrity test ("MIT") prior to initially commencing disposal and prior to resuming disposal each time the disposal packer is unseated. All MIT procedures and schedules shall follow the requirements in Division Rule 19.15.26.11A. NMAC. The Division Director retains the right to require at any time wireline verification of completion and packer setting depths in this well.

The wellhead injection pressure on the well shall be limited to **no more than 1768 psi**. In addition, the disposal well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface tubing pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the disposed fluid from the target formation. Such proper showing shall be demonstrated by sufficient evidence including but not limited to an acceptable Step-Rate Test.

The operator shall notify the supervisor of the Division's District II office of the date and time of the installation of disposal equipment and of any MIT so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of disposal to the Division's District office. The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Division Rules 19.15.26.13 and 19.15.7.24 NMAC.

Without limitation on the duties of the operator as provided in Division Rules 19.15.29 and 19.15.30 NMAC, or otherwise, the operator shall immediately notify the Division's District II

office of any failure of the tubing, casing or packer in the well, or of any leakage or release of water, oil or gas from around any produced or plugged and abandoned well in the area, and shall take such measures as may be timely and necessary to correct such failure or leakage.

The injection authority granted under this order is not transferable except upon Division approval. The Division may require the operator to demonstrate mechanical integrity of any injection well that will be transferred prior to approving transfer of authority to inject.

The Division may revoke this injection permit after notice and hearing if the operator is in violation of Rule 19.15.5.9 NMAC.

The disposal authority granted herein shall terminate one year after the effective date of this Order if the operator has not commenced injection operations into the subject well. One year after the last date of reported disposal into this well, the Division shall consider the well abandoned, and the authority to dispose will terminate *ipso facto*. The Division, upon written request mailed by the operator prior to the termination date, may grant an extension thereof for good cause.

Compliance with this order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.



HEATHER RILEY
Director

HR/mam

cc: Oil Conservation Division – Artesia District Office
New Mexico State Land Office – Oil, Gas and Minerals Division
Well File 30-015-36577