



March 8, 2019

New Mexico Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Attention: Heather Riley

Re: Injection Permit Extension
SWD-1685

Ms. Riley:

Solaris Water Midstream is requesting an extension on the Injection Permit (SWD-1685) on our Solaris Brininstool SWD #1 in Lea Co., NM. This permit is due to expire on July 25, 2019. Plans for drilling this well will not be until the 4th quarter of 2019.

I have enclosed a copy of the approved permit for your convenience.
If you need additional information I can be contacted at bonnie.atwater@solarismidstream.com or 432-203-9020 ext 9046.

Thank you.

Sincerely,

A handwritten signature in black ink that reads "Bonnie Atwater". The signature is written in a cursive, flowing style.

Bonnie Atwater
Regulatory Tech

/ba
Enclosure

State of New Mexico
Energy, Minerals and Natural Resources Department

Susana Martinez
Governor

Ken McQueen
Cabinet Secretary

Matthias Sayer
Deputy Cabinet Secretary

David R. Catanach, Division Director
Oil Conservation Division



Administrative Order SWD-1685
July 25, 2017

**ADMINISTRATIVE ORDER
OF THE OIL CONSERVATION DIVISION**

Pursuant to the provisions of Division Rule 19 15 26 8B NMAC, Solaris Water Midstream, LLC (the "operator") seeks an administrative order for its Solaris Brininstool SWD Well No 1 ("proposed well") with a location of 2390 feet from the North line and 615 from the East line, Unit H of Section 29, Township 25 South, Range 33 East, NMPM, Lea County, New Mexico, for the purpose of commercial disposal of produced water

THE DIVISION DIRECTOR FINDS THAT

The application has been duly filed under the provisions of Division Rule 19 15 26 8B NMAC and satisfactory information has been provided that affected parties as defined in said rule have been notified and no objections have been received within the prescribed waiting period. The applicant has presented satisfactory evidence that all requirements prescribed in Rule 19 15 26 8 NMAC have been met and the operator is in compliance with Rule 19 15 5 9 NMAC.

Injection will occur through either an internally-coated, 5-1/2-inch or smaller tubing inside the surface and intermediate casings, and a 5-inch flush joint or small tubing inside the liner. Further, a packer shall be set within 100 feet of the uppermost perforation.

IT IS THEREFORE ORDERED THAT

The applicant, Solaris Water Midstream, LLC (OGRID 371643), is hereby authorized to utilize its Solaris Brininstool SWD Well No 1 (API 30-025-⁹³⁹⁰⁸pending) with a location of 2390 feet from the North line and 615 from the East line, Unit H of Section 29, Township 25 South, Range 33 East, NMPM, Lea County, for disposal of oil field produced water (UIC Class II only) through an open hole interval consisting of the Devonian and Silurian formations from 17600 feet to approximately 19600 feet.

This permit does not allow disposal into the Ellenburger formation (lower Ordovician) or lost circulation intervals directly on top and obviously connected to this formation.

Prior to commencing disposal, the operator shall submit mudlog and geophysical logs information, to the Division's District geologist and Santa Fe Bureau Engineering office, showing evidence agreeable that only the permitted formation is open for disposal including a summary of

depths (picks) for contacts of the formations which the Division shall use to amend this order for a final description of the depth for the injection interval.

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the disposed water enters only the approved disposal interval and is not permitted to escape to other formations or onto the surface. This includes the completion and construction of the well as proposed in the application and, if necessary, as modified by the District Supervisor.

The operator shall circulate the cement behind the casing to surface for all surface and intermediate casings.

The operator shall run a CBL (or equivalent) across the 7-3/4-inch liner from 500 feet above the top of liner to the bottom of the liner to demonstrate a good cement across the 7-3/4-inch liner, and good bond between the liner and the 10-3/4-inch casing.

Within two years after commencing disposal, the operator shall conduct an injection survey, consisting of a temperature log or equivalent, over the entire injection interval using representative disposal rates. Copies of the survey results shall be provided to the Division's District I office and Santa Fe Engineering Bureau office.

After installing tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The well shall pass an initial mechanical integrity test ("MIT") prior to initially commencing disposal and prior to resuming disposal each time the disposal packer is unseated. All MIT procedures and schedules shall follow the requirements in Division Rule 19.15.26.11A. NMAC. The Division Director retains the right to require at any time wireline verification of completion and packer setting depths in this well.

The wellhead injection pressure on the well shall be limited to **no more than 3520 psi, but may be modified by the Division Director following the completion of the initial Step-Rate Test.** In addition, the disposal well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface tubing pressure to the maximum allowable pressure for this well. The operator shall install and maintain a chart recorder showing casing and tubing pressures during disposal operations.

The Director of the Division may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the disposed fluid from the target formations. Such proper showing shall be demonstrated by sufficient evidence including but not limited to an acceptable Step-Rate Test.

The operator shall notify the supervisor of the Division's District I office of the date and

time of the installation of disposal equipment and of any MIT so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of disposal to the Division's District I office. The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Division Rules 19.15 26.13 and 19 15.7.24 NMAC.

The injection authority granted under this order is not transferable except upon Division approval. The Division may require the operator to demonstrate mechanical integrity of any injection well that will be transferred prior to approving transfer of authority to inject.

The Division may revoke this injection order after notice and hearing if the operator is in violation of Rule 19 15.5.9 NMAC.

The disposal authority granted herein shall terminate two (2) years after the effective date of this Order if the operator has not commenced injection operations into the subject well. One year after the last date of reported disposal into this well, the Division shall consider the well abandoned, and the authority to dispose will terminate *ipso facto*. The Division, upon written request mailed by the operator prior to the termination date, may grant an extension thereof for good cause.

Compliance with this Order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.



DAVID R. CATANACH
Director

DRC/mam

cc: Oil Conservation Division – Hobbs District Office
Bureau of Land Management - Carlsbad
Administrative application – pMAM1718757682