Jones, William V., EMNRD

Sam Brandon [sbrandon@yatespetroleum.com]

From: Sent:

To: Subject:

Tuesday, March 13, 2012 3:17 PM Jones, William V., EMNRD Shocker SWD #1

Attachments: Well data.xls

AO SED-1302

done. 900' FEL to 1040' FNL and 990' FEL), the actual setting depths of the casing strings, and the addition of another liner. Please let me know what else needs to be Attached is an updated spreadsheet of well data. The original is Sheet 1, the revised data is Sheet 2. Changes include the revised location (original 900' FNL and

down. They are moving the rig off today and we will run a CBL when we can. I'll send a copy of the logs when I get them. Do you want paper or LAS? Our cement job on the 5" liner was a pretty big flop. We had good circulation, pumped Mud Push and 3 barrels of cement and the pressure went up and shut us

Thanks,

Sam Brandon
Area Engineer/Senior Production Engineer
Yates Petroleum Corporation
105 S. 4th St.
Artesia, NM 88210
575-748-4281

Vell Name: Shocker SWD #1 Field:		Casing Program	
ocation: _1040' FNL & 990' FEL Se		Size/Wt/Grade/Conn	Depth
GL: <u>2990'</u> Zero: A0 Spud Date: Co	GL: KB: _3016.5' ompletion Date:	20" 94# J55	390'
Comments:		13 3/8" 48, 54.5, 61, 68# J55	2818'
		9 5/8" 40 & 43.5 HCK55, N80, Q125	10069'
		7" 32# P110 & Q125	13144'
{ s s		5"18# P110	15200'
		0 10#1 110	10200
	0" csg @ 390'. Cmtd w/ 810 sx, Cmt circ		
		OUDDENIT CONFIGU	D 4 T 1 C
		CURRENT CONFIGU	RAIIC
13	3/8" csg @ 2818'. Cmtd w/ 2080 sx. Cm	t circ.	
nakar Ctaga			
acker Stage ol @ 4324'			
			•
DV @ 7201'			
0.5%	2" and @ 10060! Contd 1at ato/ 1040 av	(and airs) and atm w/860 av /s	
and	8" csg @ 10069'. Cmtd 1st stg w/ 1040 sx 3rd stg w/ 1040 sx (cmt circ)	(cmt circ), 2nd stg w/860 sx (c	mt circ)
	are eight to re en (eine eine)		
3 - 7" lin.	or @ 12114 Contd/ 500		
	er @ 13144'. Cmtd w/ 500 sx.		
14 11			
{}			
5" line	r @ 15200'. Cement job failed.		

III. Well Data

Actual

Α.

Lease Name: Shocker SWD #1 1)

Location: 1040' FNL & 990' FEL Sec. 32-25S-29E

30-015-39470

2) Hole/Casing/Cement:

20" 94# J55 set @ 390'. 26" hole size. 810 sacks cement. TOC = surface.

13 3/8" 48#, 54.5#, 61# and 68# set at 2818'. 17.5" hole size. 2080 sacks cement.

TOC = surface

9 5/8" 40#, 43.5# set at 10069'. 12.25" hole size. 2940 sx cement.

TOC = surface

7" 32# liner set at 9738-13144'. 8.25' hole size. 500 sx cement. TOC 9739'(designed)

5" 18# liner set at 12827'-15200'. 6" hole size. *(See below)

Open hole - 5.875", 15200' to 15700'

20" 1.32 cu ft/s 0.9599 316.767 cu ft. 239.975 13-3/8" 0.6946 2014.34 cu ft. 1.32 cu ft/s 1526.015

9-5/8" 0.3132 2912.76 cu ft. 3.04/1.59 1081.776 679.5849 1761.361221

7" 0.1268 722.76 cu ft. 1.59 681.8491

3) Tubing

3.5" 9.3# P110 internally coated with TK500 to 12800'

2.875" 6.4# L80 internally coated with TK500 from 12800 to 15150'

4.) Packer

5" Halliburton TWS permanent packer

В.

VII.

- 1) Injection formation: Devonian
- 2) Injection interval: 15200' to 15700'
- 3) This well will be drilled for injection
- 4) There will be no other perforated intervals in the well
- 5) Next higer productive zone: Morrow. Next lower productive zone: None
- IV. Is this an expansion of an existing project?
- V١ No wells in the Area of Review have penetrated the proposed injection interval.
 - 1) Proposed average and maximum daily rate and volume of fluids to be injected:

Avg vol = 10000 bpd, Max vol = 15000 bpd

Avg rate = 13500 bpd, Max rate = 20000 bpd

- 2) This will be a closed system
- 3) Proposed average and maximum pressure: Avg = 1000 psi, Max = 3100 psi.
- 4) Sources of water: frac flowback water, Delaware and Bone Springs. Analyses attached.
- 5) Analysis of disposal zone water: To be obtained when drilled.
- VIII. Geologic data on the injection zone. See Attachment D.
- IX. Stimulation program: Open hole interval will be stimulated with 15000 gallons of 15% NEFE HCI, flushed to total depth.
- Χ Attach appropriate logging and test data on the well. To be attached upon completion.
- XI. Attach a chemical analysis of fresh water from two or more fresh water wells (if available and producing) within one mile of any injection or disposal well showing location of wells and dates samples were taken. One fresh water well was found within one mile. Well location: approximately 1 mile south of Shocker 32 State Com No. 3H. Sample taken 8/24/11. Analysis attached.
- XII. See Attachment E.
- XIII. See Attachment F.
 - * When cementing the 5" liner, after pumping "Mud Push" and 3 barrels of cement, well suddenly pressured up.