

State of New Mexico
Energy, Minerals and Natural Resources Department

Susana Martinez
Governor

Ken McQueen
Cabinet Secretary

Matthias Sayer
Deputy Cabinet Secretary

Heather Riley, Division Director
Oil Conservation Division



Administrative Order SWD-1748
September 4, 2018

**ADMINISTRATIVE ORDER
OF THE OIL CONSERVATION DIVISION**

Pursuant to the provisions of Division Rule 19.15.26.8(B) NMAC, XTO Energy, Inc. (the “operator”) seeks an administrative order for its Corral Canyon 16 State SWD Well No. 1 (the “proposed well”) with a location of 990 feet from the North line and 1280 feet from the West line, Unit letter D of Section 16, Township 25 South, Range 29 East, NMPM, Eddy County, New Mexico, for the purpose of produced water disposal.

THE DIVISION DIRECTOR FINDS THAT:

The application has been duly filed under the provisions of Division Rule 19.15.26.8(B) NMAC and satisfactory information has been provided that affected parties as defined in said rule have been notified and no objections have been received within the prescribed waiting period. The applicant has presented satisfactory evidence that all requirements prescribed in Rule 19.15.26.8 NMAC have been met and the operator is in compliance with Rule 19.15.5.9 NMAC.

Application for Disposal in Devonian and Silurian Formations: Due to the potential for the projected injection volume of the proposed well to impact an area greater than the one-half mile radius applied in Division Form C-108 and Division rule, the applicant has provided the following supplementary information:

1. Notification following Division Rule 19.15.26.8(B) NMAC for a radius of one mile from the surface location of the proposed well;
2. An expanded Area of Review for wells penetrating the disposal interval for a radius of one mile from the surface location of the proposed well; and
3. A statement by a qualified person assessing the potential of induced-seismic events associated with the disposal activities for the predicted service life of the proposed well.

IT IS THEREFORE ORDERED THAT:

The applicant, XTO Energy, Inc. (OGRID 5380), is hereby authorized to utilize its Corral Canyon 16 State SWD Well No. 1 (API 30-015-44387) with a location of 990 feet from the North line and 1280 feet from the West line, Unit letter D of Section 16, Township 25 South, Range 29 East, NMPM, Eddy County, for disposal of oil field produced water (UIC Class II only) through open-hole completion into an interval consisting of the Devonian and Silurian formations from

approximately 15100 feet to approximately 16660 feet. Injection will occur through a tubing system with internally-coated, 4.5-inch or smaller tubing within the 7-inch liner and a packer set within 100 feet of the top of the disposal interval.

This permit does not allow disposal into formations below the Silurian formations including the Montoya formation and the Ellenburger formation (lower Ordovician) or lost circulation intervals directly on top and obviously connected to these formations.

Prior to commencing disposal, the operator shall submit mudlog and geophysical logs, to the Division's District geologist and Santa Fe Bureau Engineering office, showing evidence agreeable that only the permitted formation is open for disposal including a summary of depths (picks) for contacts of the formations which the Division shall use to amend this order for a final description of the depth for the injection interval. If significant hydrocarbon shows occur while drilling, the operator shall notify the Division's District II and the operator shall be required to receive written permission prior to commencing disposal.

If cement does not circulate on any casing string excluding the 7-inch liner, the operator shall run a cement bond log (CBL) or other log to determine top of cement and shall notify the Artesia District with the top of cement on the emergency phone number prior to continuing with any further cement activity with the proposed well. If cement did not tie back in to next higher casing shoe, the operator shall perform remedial cement job to bring cement, at a minimum, 200 feet above the next higher casing shoe.

The 7-inch liner shall have no less than a 200-foot tie back with the 9 $\frac{5}{8}$ -inch intermediate casing. The operator shall run a CBL (or equivalent) for the 7-inch liner sufficient to demonstrate the placement of cement along the liner and the cement tie back with the 9 $\frac{5}{8}$ -inch intermediate casing. The operator shall provide a copy of the CBL to the Division's District II prior to commencing disposal.

Prior to commencing disposal, the operator shall obtain a bottom-hole pressure measurement representative of the open-hole completion. This information shall be provided with the written notice of the date of commencement of disposal.

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the disposed water enters only the approved disposal interval and is not permitted to escape to other formations or onto the surface. This includes the completion and construction of the well as described in the application and, if necessary, as modified by the District Supervisor.

After installing tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The well shall pass an initial mechanical integrity test ("MIT") prior to initially

commencing disposal and prior to resuming disposal each time the disposal packer is unseated. All MIT procedures and schedules shall follow the requirements in Division Rule 19.15.26.11(A) NMAC. The Division Director retains the right to require at any time wireline verification of completion and packer setting depths in this well.

Without limitation on the duties of the operator as provided in Division Rules 19.15.29 and 19.15.30 NMAC, or otherwise, the operator shall immediately notify the Division's District II office of any failure of the tubing, casing or packer in the well, or of any leakage or release of water, oil or gas from around any produced or plugged and abandoned well in the area, and shall take such measures as may be timely and necessary to correct such failure or leakage.

If the disposal well fails a MIT or if there is evidence that the mechanical integrity of said well is impacting correlative rights, the public health, any underground sources of fresh water, or the environment, the Division Director shall require the well to be shut-in within 24 hours of discovery and the operator shall redirect all disposal waters to another facility. The operator shall take the necessary actions to address the impacts resulting from the mechanical integrity issues in accordance with Division Rule 19.15.26.10 NMAC, and the well shall be tested pursuant to Rule 19.15.26.11 NMAC prior to returning to injection.

The wellhead injection pressure on the well shall be limited to **no more than 3020 psi**. In addition, the disposal well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface tubing pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the disposed fluid from the target formations. Such proper showing shall be demonstrated by sufficient evidence including but not limited to an acceptable step-rate test.

The operator shall notify the supervisor of the Division's District II office of the date and time of the installation of disposal equipment and of any MIT so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of disposal to the Division's District II office. The operator shall submit monthly reports of the disposal operations that includes number of days of operation, injection volume, and injection pressure on Division Form C-115, in accordance with Division Rules 19.15.26.13 and 19.15.7.24 NMAC.

The injection authority granted under this order is not transferable except upon Division approval. The Division may require the operator to demonstrate mechanical integrity of any injection well that will be transferred prior to approving transfer of authority to inject.

The Division may revoke this injection order after notice and hearing if the operator is in violation of Rule 19.15.5.9 NMAC.

The disposal authority granted herein shall terminate one (1) year after the effective date of this Order if the operator has not commenced injection operations into the subject well. One year after the last date of reported disposal into this well, the Division shall consider the well

abandoned, and the authority to dispose will terminate *ipso facto*. The Division, upon written request mailed by the operator prior to the termination date, may grant an extension thereof for good cause.

Compliance with this Order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.



HEATHER RILEY

Director

HR/prg

cc: Oil Conservation Division – Artesia District Office
State Land Office - Oil, Gas and Minerals Division
Well file 30-015-44387

Attachment: Proposed well completion diagram from C-108 application

Corral Canyon 16 State SWD #1

Proposed SWD Schematic (Nov 6, 2017)

County: Eddy

SHL: 990' FNL, 1280' FWL
Sec 16, T 25S, R 29E

BHL: 990' FNL, 1280' FWL
Sec 16, T 25S, R 29E



AFE # 1702983

XTO ID # 720334

API # TBD

Elevation 3006'

Rig: TBD (RKB -25')

<u>Geology</u>	<u>Casing & Cement</u>	<u>Wellhead</u>	<u>Hole Size</u>	<u>General Notes</u>
TVD	<u>Lead (100% OH excess)</u> 660 sx 13.5ppg Poz/Class C Top of Lead @ 0'		24"	
467' Rustler	<u>Tail (100% OH excess)</u> 350 sx 14.8ppg Class C Top of Tail @ 600'			
	20" 94# J-55 BTC		850' MD	
893' Top Salt	<u>Lead (100% OH excess)</u> 1015 sx 12.8ppg Poz/Class C Top of Lead @ 0'		17-1/2"	
2,741' Base Salt	<u>Tail (100% OH excess)</u> 320 sx 14.8ppg Class C Top of Tail @ 2275'			
	13-3/8" 68# J-55 BTC		2947' MD	
2,947' Delaware	<u>Lead (100% OH excess)</u> 2500 sx 12.9ppg Poz/Class C Top of Lead @ 0		12-1/4"	
6,729' Bone Spring	<u>Tail (100% OH excess)</u> 135 sx 14.4ppg Class C Top of Tail @ 10050'			
9,923' Wolfcamp				
	9-5/8" 47# P-110 LTC		10300' MD	} 200' min
11,789' Cisco 12,026' Canyon 12,327' Strawn 12,521' Atoka 13,121' Morrow	<u>Lead (100% OH excess)</u> 520 sx 11ppg Poz/Class C Top of Lead @ 10200'		8-3/4"	
14,131' Barnett 14,571' Mississippian 14,923' Woodford 15,081' Devonian	<u>Tail (100% OH excess)</u> 65 sx 13.2ppg Poz/Class C Top of Tail @ 14660'			Tubing OD 4.5" / 13.5# / P-110 w/CS Packer at 15,000 ft
	7" 32# P-110 BTC		15100' MD	
	Open Hole to TD		6"	
		16660' MD		

Approvals (not required for planning schematics)

Prepared by: _____ Date _____

Reviewed by: _____ Date _____

Reviewed by: _____ Date _____

Approved by: _____ Date _____