



AE Order Number Banner

Report Description

This report shows an AE Order Number in Barcode format for purposes of scanning. The Barcode format is Code 39.



App Number: pCS1826341898

3RF - 28

ENDURING RESOURCES, LLC

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-147
Revised April 3, 2017

Recycling Facility and/or Recycling Containment

Type of Facility: Recycling Facility Recycling Containment*
Type of action: Permit Registration
 Modification Extension
 Closure Other (explain) _____

* At the time C-147 is submitted to the division for a Recycling Containment, a copy shall be provided to the surface owner.

Be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.

1.
Operator: Enduring Resources, LLC (For multiple operators attach page with information) OGRID #: 372286
Address: 332 Road 3100, Aztec, New Mexico 97410
Facility or well name (include API# if associated with a well): NEU 2207-16B Water Recycle Facility
OCD Permit Number: _____ (For new facilities the permit number will be assigned by the district office)
U/L or Qtr/Qtr NW/4 NE/4 Section 16 Township 22N Range 7W County: Sandoval
Surface Owner: Federal State Private Tribal Trust or Indian Allotment

2.
 Recycling Facility: Conditions Attached.
Location of recycling facility (if applicable): Latitude 36.144262 Longitude -107.576376 NAD83
Proposed Use: Drilling* Completion* Production* Plugging*
**The re-use of produced water may NOT be used until fresh water zones are cased and cemented*
 Other, *requires permit for other uses. Describe use, process, testing, volume of produced water and ensure there will be no adverse impact on groundwater or surface water.*
 Fluid Storage
 Above ground tanks Recycling containment Activity permitted under 19.15.17 NMAC explain type _____
 Activity permitted under 19.15.36 NMAC explain type: _____ Other explain _____
 For multiple or additional recycling containments, attach design and location information of each containment
 Closure Report (required within 60 days of closure completion): Recycling Facility Closure Completion Date: _____

NMOC
AUG 20 2018
DISTRICT III

3.
 Recycling Containment:
 Annual Extension after initial 5 years (attach summary of monthly leak detection inspections for previous year)
Center of Recycling Containment (if applicable): Latitude 36.144262 Longitude -107.576376 NAD83
 For multiple or additional recycling containments, attach design and location information of each containment
 Lined Liner type: Thickness 45 mil LLDPE HDPE PVC Other _____
 String-Reinforced
Liner Seams: Welded Factory Other _____ Volume: 309,800 bbl Dimensions: L 360 x W 360 x D 20
 Recycling Containment Closure Completion Date: _____

47

4.

Bonding:

- Covered under bonding pursuant to 19.15.8 NMAC per 19.15.34.15(A)(2) NMAC (These containments are limited to only the wells owned or operated by the owners of the containment.)
- Bonding in accordance with 19.15.34.15(A)(1). Amount of bond \$ _____ (work on these facilities cannot commence until bonding amounts are approved)
- Attach closure cost estimate and documentation on how the closure cost was calculated.

5.

Fencing:

- Four foot height, four strands of barbed wire evenly spaced between one and four feet
- Alternate. Please specify 8' Tall Chain Link Fencing

6.

Signs:

- 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers
- Signed in compliance with 19.15.16.8 NMAC

7.

Variances:

Justifications and/or demonstrations that the proposed variance will afford reasonable protection against contamination of fresh water, human health, and the environment.

Check the below box only if a variance is requested:

- Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. If a Variance is requested, include the variance information on a separate page and attach it to the C-147 as part of the application.
- If a Variance is requested, it must be approved prior to implementation.**

8.

Siting Criteria for Recycling Containment

Instructions: The applicant must provide attachments that demonstrate compliance for each siting criteria below as part of the application. Potential examples of the siting attachment source material are provided below under each criteria.

General siting

Ground water is less than 50 feet below the bottom of the Recycling Containment.

NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells

- Yes No
- NA

Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.

- Yes No
- NA

- Written confirmation or verification from the municipality; written approval obtained from the municipality

Within the area overlying a subsurface mine.

- Yes No

- Written confirmation or verification or map from the NM EMNRD-Mining and Minerals Division

Within an unstable area.

- Yes No

- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; topographic map

Within a 100-year floodplain. FEMA map

- Yes No

Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).

- Yes No

- Topographic map; visual inspection (certification) of the proposed site

Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.

- Yes No

- Visual inspection (certification) of the proposed site; aerial photo; satellite image

Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.

- Yes No

- NM Office of the State Engineer - iWATERS database search; visual inspection (certification) of the proposed site

Within 500 feet of a wetland.

- Yes No

- US Fish and Wildlife Wetland Identification map; topographic map; visual inspection (certification) of the proposed site

9.

Recycling Facility and/or Containment Checklist:

Instructions: Each of the following items must be attached to the application. Indicate, by a check mark in the box, that the documents are attached.

- Design Plan - based upon the appropriate requirements.
- Operating and Maintenance Plan - based upon the appropriate requirements.
- Closure Plan - based upon the appropriate requirements.
- Site Specific Groundwater Data -
- Siting Criteria Compliance Demonstrations -
- Certify that notice of the C-147 (only) has been sent to the surface owner(s)

10.

Operator Application Certification:

I hereby certify that the information and attachments submitted with this application are true, accurate and complete to the best of my knowledge and belief.

Name (Print): James McDaniel Title: HSE Supervisor
 Signature:  Date: 8/20/2018
 e-mail address: jmcdaniel@eduringresources.com Telephone: 505-636-9731

11.

OCD Representative Signature:  Approval Date: 9/20/18

Title: Environmental Spec. OCD Permit Number: 3RF-28

- OCD Conditions _____
- Additional OCD Conditions on Attachment _____

Smith, Cory, EMNRD

From: Smith, Cory, EMNRD
Sent: Thursday, September 20, 2018 12:09 PM
To: James McDaniel
Cc: Billings, Bradford, EMNRD; Fields, Vanessa, EMNRD; Andrea Felix; Powell, Brandon, EMNRD
Subject: Enduring NEU 2207-16B Water Recycling Facility and Containment assigned 3RF-28

Mr. McDaniel

OCD has received the Recycling facility and Containment for Enduring NEU 2207-16B Water Recycling Facility submitted on September 11, 2018. After subsequent Enduring submissions and OCD review the registration has been approved with the following conditions of approval:

- Enduring will construct a sump as describe in the Design plan (But not in the signed Engineering documents) and will meet all the requirements of 19.15.34.12 NMAC
- Enduring will submit an as built engineering diagram of the completed recycling containment within 90 days of construction completion.

The NEU 2207-16B Water Recycling Facility has been assigned as Permit/Registration Number 3RF-28. Please take note of the Permit/Registration number, as this will be what Enduring uses on form C-148 to account for produce water usage. You may review your permit at [OCD Online](#) by searching for 3RF-28. As a Reminder Since Enduring indicated that the facility is covered under bonding Pursuant to 19.15.8 NMAC, This containment use is limited to **ONLY** the wells owned or operated by Enduring.

The application has been sent up for scanning and should appear in the online data base soon. If you have any questions please give me a call.

Cory Smith
Environmental Specialist
Oil Conservation Division
Energy, Minerals, & Natural Resources
1000 Rio Brazos, Aztec, NM 87410
(505)334-6178 ext 115
cory.smith@state.nm.us

Mr. Cory Smith
Oil Conservation Division
1000 Rio Brazos Rd.
Aztec, New Mexico 87410
Email: cory.smith@state.nm.us
Phone (505) 334-6178 Ext 115

NMOC
SEP 11 2018
DISTRICT III

Re: Variance Request for 19.15.34 NMAC

Mr. Smith,

Please accept this letter as a variance request as outlined in 19.15.34.16 NMAC. Enduring Resources, LLC (Enduring) is proposing to install a six foot chain link fence surrounding the recycling containment in lieu of the fencing requirements listed in 19.15.34.12.D NMAC. We believe this will provide better protection than the requirements listed in 19.15.34.12.D NMAC.

Enduring Resources, LLC (Enduring) is proposing to mitigate migratory birds pursuant to the attached *Migratory Bird Mitigation Plan* as required in 19.15.34.12.E. We believe this will provide equal or better protection than the requirements listed in 19.15.34.12.E NMAC.

Respectfully Submitted,



James McDaniel, CHMM #15676
HSE Supervisor
Enduring Resources, LLC



Enduring Resources, LLC Recycling Facility and /or Recycling Containment

Documents provided to Surface Owner- Certification

NEU 2207-16B Water Recycle Facility

Enduring Resources, LLC is certifying that a copy of the submitted C-147 filed on Monday August 20, 2018 to the NMOCD District III office has been provided to the New Mexico State Land Office as required.

New Mexico State Land Office project # is BL2613

A handwritten signature in blue ink, appearing to read 'Andrea Felix', written over a horizontal line.

Andrea Felix, Regulatory Manager

8-20-2018

Andrea Felix

From: Winscott, John <jwinscott@slo.state.nm.us>
To: Andrea Felix
Sent: Monday, August 20, 2018 8:19 AM
Subject: Read: BL2613: Copy of C-147 submitted to NMOCD

Your message

To:
Subject: BL2613: Copy of C-147 submitted to NMOCD
Sent: Monday, August 20, 2018 8:20:44 AM (UTC-07:00) Mountain Time (US & Canada)

was read on Monday, August 20, 2018 8:18:44 AM (UTC-07:00) Mountain Time (US & Canada).



New Mexico Office of the State Engineer
Water Column/Average Depth to Water

(quarters are 1=NW 2=NE 3=SW 4=SE)
(quarters are smallest to largest) (NAD83 UTM in meters)

No records found.

PLSS Search:

Section(s): 16 **Township:** 22N **Range:** 07W

The data is furnished by the NMOSE ISC and is accepted by the recipient with the expressed understanding that the OSE ISC make no warranties, expressed or implied, concerning the accuracy, completeness, reliability, usability, or suitability for any particular purpose of the data.

8/20/18 5:38 AM

WATER COLUMN/ AVERAGE
DEPTH TO WATER



N Escavada Unit 317H
N Escavada Unit 318H

NEU 2207-16B



1000 Feet




36.144262 -107.576376 X Q

Show search results for 36.144262 -...

Legend

Registered Mines

- Aggregate, Stone etc.
- Coal
- Gypsum
- Humate
- Industrial Minerals (Other)
- Metals
- Perlite
- Potash
- PM Pumice
- Red Dog, Scoria
- Salt
- U Uranium
- ZE Zeolites





National Flood Hazard Layer FIRMette



FEMA

Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT

36°8'56.70"N



- SPECIAL FLOOD HAZARD AREAS**
 - Without Base Flood Elevation (BFE) Zone A, V, A99
 - With BFE or Depth
 - Regulatory Floodway Zone AE, AO, AH, VE, AF

- OTHER AREAS OF FLOOD HAZARD**
 - 0.2% Annual Chance Flood Hazard, Area of 1% annual chance flood with average depth less than one foot or with drainage areas of less than one square mile Zone J
 - Future Conditions 1% Annual Chance Flood Hazard Zone X
 - Area with Reduced Flood Risk due to Levee. See Notes. Zone X
 - Area with Flood Risk due to Levee Zone D

- OTHER AREAS**
 - NO SCREEN Area of Minimal Flood Hazard Zone X
 - Effective LOMRs
 - Area of Undetermined Flood Hazard Zone

- GENERAL STRUCTURES**
 - Channel, Culvert, or Storm Sewer
 - Levee, Dike, or Floodwall

- OTHER FEATURES**
 - Cross Sections with 1% Annual Chance Water Surface Elevation
 - Coastal Transect
 - Base Flood Elevation Line (BFE)
 - Limit of Study
 - Jurisdiction Boundary
 - Coastal Transect Baseline
 - Profile Baseline
 - Hydrographic Feature

- MAP PANELS**
 - Digital Data Available
 - No Digital Data Available
 - Unmapped



This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The base map shown complies with FEMA's base map accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on 5/9/2018 at 7:55:44 AM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: base map imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.

Source: Esri, DigitalGlobe, GeoEye, Earthstar Geographics, CNES/Airbus DS, USDA, USGS, AeroGRID, IGN, and the GIS User Community

0 250 500 1 000 1 500 2 000 Feet 1:6,000

36°8'27.65"N

107°34'15.04"W



Ground Rod Drilling Log

Company: WPX Energy

Well: North Escanaba UTSB S29H Date: 10-25-2016

Location: Solo T30N E2W

State: Michigan

Rig: Shiny #1

Ground Rod Depth: 340'

Water Depth: 0'

Diameter: 10"

Post: 88 gal.

Latitude: 36.916522

Longitude: -101.514754

DEPTH FORMATION OTHER

<u>D-60</u>	Sand Stone, Shale, Sand w/ Shale w/ Sand	<u>PVC</u>
<u>60-100</u>	Sand Stone, Shale, Sand w/ Shale w/ Sand	
<u>100-140</u>	Sand Stone, Shale, Sand w/ Shale w/ Sand	
<u>140-190</u>	Sand Stone, Shale, Sand w/ Shale w/ Sand	
<u>190-250</u>	Sand Stone, Shale, Sand w/ Shale w/ Sand	
<u>250-300</u>	Sand Stone, Shale, Sand w/ Shale w/ Sand	
<u>300-340</u>	Sand Stone, Shale, Sand w/ Shale w/ Sand	
	Sand Stone, Shale, Sand w/ Shale w/ Sand	
	Sand Stone, Shale, Sand w/ Shale w/ Sand	
	Sand Stone, Shale, Sand w/ Shale w/ Sand	

GROUNDWATER DEPTH LOG

Company: WPX Energy Location: North Escanaba UTSB S29H

Well Name: 36.146522/101.514754

Date	Time	Depth	Comments
<u>10/25/16</u>	<u>8 am</u>	<u>30'</u>	<u>drilled 30'</u>
	<u>11 am</u>	<u>30'</u>	<u>tested no water</u>
	<u>11:30</u>	<u>55'</u>	<u>drilled to 55'</u>
	<u>1:10</u>	<u>55'</u>	<u>tested no water</u>
	<u>1:45</u>	<u>105'</u>	<u>drilled to 105'</u>
	<u>2:45</u>	<u>105'</u>	<u>tested no water set 60' casing</u>
	<u>10/23/16 8:30 am</u>	<u>105'</u>	<u>no water</u>
	<u>11:45</u>	<u>340'</u>	<u>finished ground rod</u>




BASEMAPS >

MAP LAYERS >

- Wetlands 1 ?
- Riparian 1 ?
- Riparian Mapping Areas 1 ?
- Data Source 1 ?
 - Source Type
 - Image Scale
 - Image Year
- Areas of Interest ?
- FWS Managed Lands 1 ?
- Historic Wetland Data 1 ?



Measure



LEGEND

Wetlands

- Estuarine and Marine Deepwater
- Estuarine and Marine Wetland
- Freshwater Emergent Wetland
- Freshwater Forested/Shrub Wetland
- Freshwater Pond
- Lake
- Other
- Riverine

Riparian

- Forested/Shrub
- Herbaceous

Riparian Mapping Areas

- Riparian Mapping Areas

1:2,257
36.146 | -107.578



Design & Construction Plan

NEU 2207-16B Water Recycle Facility



Enduring Resources, LLC

332 Road 3100

Aztec, New Mexico 87410

Prepared by:
James McDaniel
HSE Supervisor

NMOCD
SEP 11 2018
DISTRICT III

Introduction

This Design and Construction Plan is designed to meet the requirements of NMAC 19.15.34.13, which outlines the requirements for design and construction criteria for a produced water recycling containment. Enduring Resources, LLC (Enduring) will construct this recycling containment in accordance with the following design and construction plan.

1. **The operator shall design and construct a recycling containment to ensure the confinement of produced water, to prevent releases and to prevent overtopping due to wave action or rainfall.**

The recycling containment has been designed the containment to meet the above criteria, ensuring the confinement of produced water, the prevention of releases, and the prevention of overtopping due to wave action or rainfall.

2.

- a. **A recycling containment shall have a properly constructed foundation and interior slopes consisting of a firm, unyielding base, smooth and free of rocks, debris, sharp edges or irregularities to prevent the liner's rupture or tear.**

The recycling containment has been designed, and will be constructed, to have a properly constructed foundation, 95% compaction, and an unyielding base, free of rocks debris and sharp edges.

- b. **Geotextile is required under the liner when needed to reduce localized stress-strain or protuberances that otherwise may compromise the liner's integrity. The operator shall construct the containment in a levee with an inside grade no steeper than two horizontal feet to one vertical foot (2H:1V). The levee shall have an outside grade no steeper than three horizontal feet to one vertical foot (3H:1V). The top of the levee shall be wide enough to install an anchor trench and provide adequate room for inspection and maintenance.**

Geotextile will be placed under the liner the secondary liner in order to reduce stress-strain on the liner. The containment levee has been designed to have an inside grade no steeper than 2H:1V, and an outside grade no steeper than 3H:1V.

3.

- a. **Each recycling containment shall incorporate, at a minimum, a primary (upper) liner and a secondary (lower) liner with a leak detection system appropriate to the site's conditions.**

The recycling containment is designed to have a 45 mil, string reinforced LLDPE liner as the primary liner, and a 45 mil, string reinforced LLDPE liner as the secondary liner.

- b. **The edges of all liners shall be anchored in the bottom of a compacted earth-filled trench. The anchor trench shall be at least 18 inches deep.**

The edges of the liners will be constructed in such a way as to be anchored in the bottom of a compacted earthen trench, which will be at least 18 inches deep.

4.

- a. **All primary (upper) liners in a recycling containment shall be geomembrane liners composed of an impervious, synthetic material that is resistant to ultraviolet light, petroleum hydrocarbons, salts and acidic and alkaline solutions. All primary liners shall be 30-mil flexible PVC, 45-mil LLDPE string reinforced or 60-mil HDPE liners.**

The primary liner will be a 45-mil, LLDPE, string reinforced liner that is composed of material that is resistant to ultraviolet light, petroleum hydrocarbons, salt solutions, acidic

NMOCD

SEP 11 2018

DISTRICT III

solutions and alkaline solutions. Liner compatibility meets the conductivity requirement of 1×10^{-9} cm/sec.


- b. **Secondary liners shall be 30-mil LLDPE string reinforced or equivalent with a hydraulic conductivity no greater than 1×10^{-9} cm/sec. Liner compatibility shall meet or exceed the EPA SW-846 method 9090A or subsequent relevant publications.** The secondary liner will be a 45-mil, LLDPE, string reinforced liner that is composed of material that is resistant to ultraviolet light, petroleum hydrocarbons, salt solutions, acidic solutions and alkaline solutions. Liner compatibility meets the conductivity requirement of 1×10^{-9} cm/sec.

5. **The operator of a recycling containment shall minimize liner seams and orient them up and down, not across, a slope of the levee. Factory welded seams shall be used where possible. The operator shall ensure field seams in geosynthetic material are thermally seamed. Prior to field seaming, the operator shall overlap liners four to six inches. The operator shall minimize the number of field seams and corners and irregularly shaped areas. There shall be no horizontal seams within five feet of the slope's toe. Qualified personnel shall perform field welding and testing.**

Liner material will be factory welded by the manufacturer by qualified personnel. The liner material will overlap a minimum of 4 inches. No horizontal seam will be placed within 5 feet of the slopes toe. All welding and testing will be completed by qualified personnel.

6. **At a point of discharge into or suction from the recycling containment, the operator shall insure that the liner is protected from excessive hydrostatic force or mechanical damage. External discharge or suction lines shall not penetrate the liner.**

External discharge or suction lines will not penetrate the liner. The liner will be protected from excessive hydrostatic force or mechanical damage, and the point of discharge and suction from the containment is specifically designed to eliminate damage from suction or discharge in and out of the containment. The suction area will be protected by two additional layers of 45-mil string reinforced liners, and will have pumps set on top of 8" concrete pads in the bottom of the pond. The inlet pipe area will be protected by two additional layers of 45-mil string reinforced liner, and the outlet will discharge onto an 8" concrete pad in the bottom of the pond.



7. **The operator of a recycling containment shall place a leak detection system between the upper and lower geomembrane liners that shall consist of 200-mil geonet or two feet of compacted soil with a saturated hydraulic conductivity of 1×10^{-5} cm/sec or greater to facilitate drainage. The leak detection system shall consist of a properly designed drainage**

NMOCD

02 11 2018

DISTRICT III

and collection and removal system placed above the lower geomembrane liner in depressions and sloped to facilitate the earliest possible leak detection.

The containment has been designed with a leak detection system made up of a conductive geocomposite material, at least 200 mm thick. The pond is comprised of a 45 mil liner base, with a 200 mm geocomposite material for leak detection, and overlaid with an additional 45 mil liner. The bottom of the pond will be sloped to a sump which will have a 2" HDPE pipe inserted between the liners, as seen on the attached *Leak Detection System Details* page. The pipe will be checked during the weekly inspection for the presence of water using a bailer. In the event water is detected in the leak detection sump, the electric-conductivity grid will be utilized to determine the location of the leak.

- 8. The operator of a recycling containment shall design the containment to prevent run-on of surface water. The containment shall be surrounded by a berm, ditch or other diversion to prevent run-on of surface water.**

The containment will be surrounded by a berm to prevent the run-on of surface water.

- 9. Prior to constructing containment, the operator shall strip and stockpile the topsoil for use as the final cover or fill at the time of closure.**

Approximately 6" of topsoil will be stripped and stockpiled for final cover at the time of closure. The topsoil will be stored at an adjacent staging area, represented on the *Figure 4*, and on the attached *Aerial Photograph*.

- 10. The operator shall post an upright sign no less than 12 inches by 24 inches with lettering not less than two inches in height in a conspicuous place on the fence surrounding the containment. The operator shall post the sign in a manner and location such that a person can easily read the legend. The sign shall provide the following information: the operator's name, the location of the site by quarter-quarter or unit letter, section, township and range, and emergency telephone numbers.**

A sign meeting these requirements will be posted.

- 11. The operator shall fence or enclose a recycling containment in a manner that deters unauthorized wildlife and human access and shall maintain the fences in good repair. The operator shall ensure that all gates associated with the fence are closed and locked when responsible personnel are not onsite. Recycling containments shall be fenced with a four foot fence that has at least four strands of barbed wire evenly spaced in the interval between one foot and four feet above ground level.**

The containment will be surrounded with a six foot, chain link fence topped with barbed wire. All gates leading in and out of the containment will be closed and locked when personnel are not on-site. The fencing will be kept in good repair, and shall be inspected as part of the weekly inspection performed at the containment facility.

- 12. The operator shall ensure that a recycling containment is screened, netted or otherwise protective of wildlife, including migratory birds. The operator shall on a monthly basis inspect for and, within 30 days of discovery, report the discovery of dead migratory birds or other wildlife to the appropriate wildlife agency and to the division district office in order to facilitate assessment and implementation of measures to prevent incidents from reoccurring.**

Enduring Resources will install a bird deterrent system pursuant to the attached *Migratory Bird Mitigation Plan*. The containment will be inspected weekly for dead migratory birds, and will report and found accordingly.

NMOGD

SEP 11 2018

DISTRICT III

ENDURING RESOURCES, LLC NEU 2207-16B WATER RECYCLE FACILITY

1185' FNL & 1365' FEL, SECTION 16, T22N, R7W, N.M.P.M.
SANDOVAL COUNTY, NEW MEXICO




Figure 4. NEU 2207-16B Soil Staging Area Surveyor's Drawing

NAME OF TOPO MAP : LYBROOK

⊕ PRODUCING WELL

⊗ PLUGGED & ABANDONED WELL



STAGING
AREA FOR
TOPSOIL

NEU 2207-16B

NMOCB

SEP 11 2018

DISTRICT III



Memorandum

TO: Enduring Resources – Eric Stevens, P.E.
FROM: Souder Miller & Associates – Heather McDaniel, P.E.
DATE: August 29, 2018
RE: Recommended Recycling Containment Liner System



After review of New Mexico Oil Conservation District's (NMOCD) Title 19 Natural Resources and Wildlife Chapter 15 Oil and Gas, Part 34 Produced Water, Drilling Fluids, and Liquid Oil Field Waste, SMA is recommending the following liner system for full briny water containment at NEU 2207-16B in Sandoval County, New Mexico. The liner system is described below in order of installation.

- **Per NMOCD 19.15.34.12.2: “a recycling containment shall have a properly constructed foundation and interior slopes consisting of a firm, unyielding base, smooth and free of rocks, debris, sharp edges or irregularities to prevent the liner’s rupture or tear.”** The final subgrade shall be scarified to a minimum depth of 12 inches, moisture conditioned to within 2% +/- Optimum Moisture and compacted to 95% of maximum dry density as determined by a Standard Proctor (ASTM 698).
- Install manufacturer recommended DrainTube gas ventilation geocomposite grid produced by Afitex Texel. This layer is intended to vent in situ gases that have potential to create “whales” in the produced water pit that would decrease storage capacity. The product consists of a drainage layer and a filter layer comprised of short synthetic staple fibers of 100% polypropylene needle-punched together with perforated corrugated polypropylene pipes regularly spaced, up to 4 pipes per meter, inside. The pipes have two perforations per corrugation at 180° and alternating at 90°. https://www.draintube.net/docs/en/download/technical_data_sheets/draintube_300p_st_series_fos.pdf
- **Per NMOCD 19.15.34.12.4: “Secondary containment liner shall be 30-mil LLDPE string reinforced or equivalent.”** The secondary containment liner will be 45-mil LLDPE string reinforced with a single sided conductive coating for initial leak detection and shall cover the bottom and sides of the pit including the minimum three (3) feet of freeboard per **NMOCD 19.15.17.11.G.9**. Integrity of the secondary liner shall be tested using the Conductive-Backed Geomembrane Spark Testing Method (ASTM D7240).
- Install manufacturer recommended Geoconduct 250 geocomposite with a conductive grid between non-woven needle-punched geotextiles produced by Afitex Texel. The product consists of two geotextile layers comprised of short synthetic fibers of 100% polypropylene or polyester which are needle punched together with a structural conductive grid. The conductive grid comprises two conductive inox cables forming a 50 mm x 50 mm network. Geoconduct is compatible with geoelectrical leak location surveys. https://www.draintube.net/docs/en/download/technical_data_sheets/geoconduct_250_fos.pdf



- Per NMOCD 19.15.34.12.4: “The primary liners in a recycling containment shall be geomembrane liners composed of an impervious, synthetic material that is resistant to ultraviolet light, petroleum hydrocarbons, salt and acidic and alkaline solutions. All primary liners shall be 30-mil flexible PVC, 45-mil LLDPE string reinforced or 60-mil HDPE liners.” The primary containment liner shall be 45-mil LLDPE string reinforced with a single sided texture to increase traction for emergency escape from the pit and shall cover the bottom and sides of the pit including the minimum three (3) feet of freeboard per NMOCD 19.15.17.11.G.9. Integrity of the primary liner shall be tested using the Dipole Method – Water Covered Geomembrane (ASTM D7007).
- Per NMOCD 19.15.34.12.2: the liner system shall be anchored as designed in a 2 FT x 2.5 FT anchor trench and topped with 6 inches of road base.
- Owner has also agreed to an annually scheduled leak detection survey of the primary liner utilizing the Dipole Method – Water Covered Geomembrane (ASTM D7007).
<http://www.linersurvey.net/wp-content/uploads/2013/01/LINER-INTEGRITY-SURVEY-GUIDE.pdf>

ENDURING RESOURCES 16B RECYCLING CONTAINMENT PIT PROJECT CONSTRUCTION PLANS



SITE CONTROL

CENTER OF PRODUCED WATER PIT Lat 36°8'39"N Long 107°34'35"W



SECTION 16, TOWNSHIP 22 NORTH, RANGE 7 WEST, NEW MEXICO PRINCIPAL MERIDIAN,
SANDOVAL COUNTY, NEW MEXICO

SANDOVAL COUNTY, NEW MEXICO
August 2018

PROJECT DESCRIPTION:
NORTH ESCAVADA RECYCLING PIT

SHEET LIST TABLE

SHEET NUMBER	SHEET TITLE
G100	COVER
G101	GENERAL NOTES AND LEGEND
C101	SITE MAP
C102	SITE GRADING AND DRAINAGE PLAN
C103	SITE PROFILE
C104	SITE CROSS-SECTIONS
C105	LINER BALLAST TUBES AND PIT GEOCOMPOSITE VENTILATION GRID LAYOUT
C106	GEOCOMPOSITE DETAILS
C107	LINER AND BALLAST TUBE DETAILS
C108	PIT ACCESS ROAD AND DRAINAGE DETAILS
C109	CHAIN LINK SECURITY FENCE DETAILS
C110	EROSION CONTROL PLAN
C111	SITE EROSION AND SEDIMENTATION CONTROL DETAILS



VICINITY MAP
NTS

THESE DETAILED PLANS AND SPECIFICATIONS WERE PREPARED UNDER MY
DIRECTION AND SUPERVISION ON BEHALF OF SOUDER, MILLER & ASSOCIATES.

Heather D. McDaniel
HEATHER D. MCDANIEL, P.E. NM #22047
PROJECT MANAGER

8-17-2018
DATE

© Copyright 2018. All Rights Reserved.



Rev #	Date	Description	By	CHK'd




SOUDER, MILLER & ASSOCIATES
3000 W. 14th Avenue
Lakewood, CO 80214
Phone (303) 238-0001 Fax (303) 234-0745
www.smaonline.com
Setting the Standard & Rocky Mountains
Albuquerque, Colorado, Pennsylvania, Florida, Las Vegas, Nevada, Idaho, PA, NY
Utah, Utah, New Mexico, Lakewood, CO, 2008 & AZ, TX, PA, NY



© Copyright 2015 Souder, Miller & Associates - All Rights Reserved

Final Design - 180' Round Diameter (157.73m) Circular NEU Water Recycle Facility

Project No. 15-001-001-001, NEU Water Recycle Facility, Sandovail County, NE



PROPOSED SITE EARTHWORK

APPROXIMATE FILL:
 56,889 CU YD
 41,705 CU YD
 15,184 CU YD
 4,436 CU YD

APPROXIMATE NET CUT:
 TOPSOIL REMOVAL (0.50 DEPTH)

Material Impact on PMF Parameters

Storm Event	Substrate	PM Volume Reduced (Q)	Impact on PMF
Maximum Storage	1,289,421.00	0.000	0.000
24 Hr. 24 Hr.	1,768,800.00	1,757,051.50	0.139
24 Hr. 24 Hr.	261,120.00	1,772,448.50	0.139
24 Hr. 24 Hr.	2,826,240.00	1,665,928.00	0.139

Time of Concentration (Minutes)

2 Year, 24 Hour	5 Year, 24 Hour	10 Year, 24 Hour	25 Year, 24 Hour	50 Year, 24 Hour	100 Year, 24 Hour
1.42	0.88	1.50	4.50	5.98	8.24
1.42	0.88	1.50	4.50	5.98	8.24
1.42	0.88	1.50	4.50	5.98	8.24













Rev	Date	Description	By	Chk'd

ENDURING RESOURCES SANDOVAL COUNTY, NM

ENDURING RESOURCES NEU 2207-16B WATER RECYCLE FACILITY SITE GRADING AND DRAINAGE PLAN

SOUDEY, MILLER & ASSOCIATES
 Engineering • Environmental • Surveying
 Serving the Southwest & Rocky Mountains
 8000 West Fourthteenth Avenue
 Lakewood, CO 80124
 Phone (303) 239-9911 Toll-Free (877) 749-7819 Fax (303) 239-0745
 www.soudermiller.com

Sheet: **C-102**








© Copyright 2018 Souder, Miller & Associates - All Rights Reserved

ENDURING RESOURCES
 SANDHILL COUNTY, NM
 ENDURING RESOURCES NEU 2207-16B
 WATER RECYCLE FACILITY
 LINER AND BALLAST TUBE DETAILS

DESIGNED BY: HDM
 DRAWN BY: EBR
 CHECKED BY: HDM
 DATE: August 2018
 SCALE: Horiz: N/A
 Vert: N/A
 PROJECT NO: 9127383
 SHEET: C107

THIS DRAWING IS INCOMPLETE AND SHOULD NOT BE USED FOR CONSTRUCTION UNLESS IT IS ENDED AS NOTED AND DATED.

www.soudermiller.com
 Phone: (505) 338-9611 Fax: (505) 338-4145



Gate Leaf Width (ft)	Gate Leaf Height (ft)	Gate Leaf Depth (ft)	Gate Leaf Material	Gate Leaf Finish	Gate Leaf Weight (lb)
7' to 12'	4.00'	6.00'	1/2\"/>		

Copyright 2018 Souder, Miller & Associates - All Rights Reserved

P:\Security Resources - 1887\Drawn\Drawn\1872829\CAD\CAD1 - NEU.J1850\A045\27383\NEU_Cover.dwg, 8/17/2018 2:17:09 PM, GP7



Project No.	8172829
Client	ENDURING RESOURCES
Location	NEU 2207-16B
Scale	AS SHOWN
Date	August 2018
Drawn By	JM
Checked By	JM
Project Manager	JM
Scale	AS SHOWN
Printed No.	8172829
Sheet	C109

ENDURING RESOURCES SANDOVAL COUNTY, NM

ENDURING RESOURCES NEU 2207-16B WATER RECYCLE FACILITY CHAIN LINK SECURITY FENCE DETAILS

SOUDEY MILLER & ASSOCIATES


Engineering • Environmental • Surveying

Serving the Southwest & Rocky Mountains

8000 West Fourteenth Avenue
Lakewood, CO 80214

Phone (303) 219-9611 Toll-Free (877) 299-0942 Fax (303) 219-4745
www.soudermiller.com

Rev #	Date	Description	By	CHK'D



- NOTES:**
1. ALL FACILITY INFORMATION CAN BE FOUND ON SHEETS C101 AND C102.
 2. ALL SLOPES SHALL HAVE WADDLES PLACED.
 3. CONTRACTOR SHALL ADD GRASS SEED AND MULCH TO ALL UNPAVED/UNGRAVELED SURFACES THROUGHOUT THE SITE.
 4. ALL SOIL STOCKPILES ARE TO HAVE WATTLE/FIBER ROLL PLACED AROUND THEM.

PERMANENT BMPs

- (GS) GRASS SEEDING
- (MU) MULCH
- (RR) RIP RAP
- (EB) EARTHEN BERM

TEMPORARY BMPs

- (WD) 10" DIA WATTLE/FIBER ROLL
- (CWO) CONCRETE WASHOUT

DATE	BY	CHKD													
<p>SOUDEY MILLER & ASSOCIATES Engineering • Environmental • Surveying <i>SMA</i> Serving the Southwest & Rocky Mountains 8000 N. Kent Road, Suite 200, Littleton, CO 80120 Phone: (303) 219-9411 • Toll-Free: (877) 294-9412 • Fax: (303) 219-9745 www.soudeymiller.com</p>															
<p>SARASOTA COUNTY, FLA ENDING RESOURCES NEU 2207-16B WATER RECYCLE FACILITY EROSION CONTROL PLAN</p>															
<p>THIS DRAWING IS INCOMPLETE AND NOT TO BE USED FOR CONSTRUCTION UNLESS IT IS STAMPED, SIGNED AND DATED</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Designed</td> <td>Drawn</td> <td>Checked</td> </tr> <tr> <td>HDM</td> <td>GJF</td> <td>HDM</td> </tr> </table> <p>Date: August 2018 Scale: Horiz: 1" = 40' Vert: N/A Project No: 9127383 Sheet: C110</p>										Designed	Drawn	Checked	HDM	GJF	HDM
Designed	Drawn	Checked													
HDM	GJF	HDM													

Operations and Maintenance Plan

NEU 2207-16B Water Recycle Facility



NMOCB
SEP 11 2018
DISTRICT III

Enduring Resources, LLC
332 Road 3100
Aztec, New Mexico 87410

Prepared by:
James McDaniel
HSE Supervisor

Introduction

This Operations and Maintenance (O&M) plan is designed to meet the requirements of NMAC 19.15.34.13, which outlines the requirements for O&M of a produced water recycling containment. Enduring Resources, LLC (Enduring) will operate this recycling containment in accordance with the following O&M plan.

Operations and Maintenance Plan

1. Enduring will inspect the recycling containment and associated leak detection systems weekly while the containment is holding fluids. An inspection log will be maintained by Enduring, and will be available for review upon request by the division.
2. Enduring will remove and visible oil from the surface of the recycling containment upon discovery.
3. Enduring will maintain a minimum of three (3) feet of freeboard in the containment at all times.
4. Oil absorbent booms will be stored on-site in the event oil is discovered in the recycling containment. The booms will be deployed for the removal of oil if it is discovered.
5. The injection and withdrawal of fluids from the containment shall be accomplished through a header, diverter or other hardware that prevents damage to the liner by erosion, fluid jets or impact from installation and removal of hoses or pipes.
6. If a leak is discovered in the containments primary liner above the liquid level in the containment, Enduring will repair the primary liner within 48 hours, or request an extension on repair within the 48-hour time limit.
7. If a leak is discovered in the containments primary liner below the liquid level in the containment, Enduring will notify the division office of the leak, remove all fluids above the leak level, and repair the primary liner within 48 hours, or request an extension on repair within the 48-hour time limit.
8. The recycling containment will be operated in such a way to prevent the collection of surface water.
9. The recycling containment will not be used for the storage or discharge of hazardous waste.
10. Enduring will consider the recycling containment to have ceased operations if less than 20% of the total fluid volume is used every six (6) months following the first withdrawal of produced water for use. Enduring will report cessation of operations to the appropriate division district office. If additional time is needed for closure, Enduring will request an extension from the appropriate division district office prior to the expiration of the initial six (6) month time period.

NMOC D

SEP 11 2018

DISTRICT III

Closure Plan

NEU 2207 16B Water Recycle Facility



Enduring Resources, LLC
332 Road 3100
Aztec, New Mexico 87410

Prepared by:
James McDaniel
HSE Supervisor

NMOCB
SEP 11 2018
DISTRICT III

Introduction

This closure plan is designed to meet the requirements of NMAC 19.15.34.14, which outlines the requirements for closure of a produced water recycling containment. Enduring Resources, LLC (Enduring) will perform the following actions upon final closure of this produced water recycling containment.

Closure Plan

1. Upon cessation of operations (Defined as the use of less than 20% of the pond's total fluid capacity), Enduring will remove all fluids within 60 days of the official date of cessation.
2. Enduring will close the produced water containment within six (6) months from the official date of cessation. If Enduring will require more than 6 months to complete closure activities, an extension request will be filed prior to the six (6) month time limit for closure.
3. Closure activities will consist of the following:
 - a. Removal of all containment contents
 - b. Removal of liners and associated leak detection equipment for disposal at a division approved facility.
 - c. Removal of all equipment associated with the continued operation of the recycling containment.
 - d. A 5-point composite soil sample will be collected in the containment area under the location of the liner, and the sample will be analyzed for the constituents listed in *Table I*.
 - e. Additional grab samples of any obvious wet or stained areas will be collected and analyzed for the constituents listed in *Table I*, in addition to the 5-point composite sample.
 - f. If the closure sample(s) collected return results equal to or less than the values listed in *Table I*, backfill activities will begin.
 - g. If the closure sample(s) collected return results above the values listed in *Table I*, Enduring will report the elevated sample values to the NMOCD, and additional delineation may be required at that time.
4. The surface area of the former containment area will be backfilled with non-waste containing earthen material to a safe and stable condition that blends with the surrounding undisturbed areas. Topsoil and subsoil will be replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns.
5. The area will be reclaimed and reseeded pursuant to the requirements listed in 19.15.34.14.
 - a. Once Enduring has closed the recycling containment, we will reclaim the containment's location to a safe and stable condition that blends with the surrounding undisturbed area and matches the existing grade. Topsoils and subsoils shall be replaced to their original relative positions and contoured so as to prevent ponding and erosion. The disturbed area shall then be reseeded in the first favorable growing season following closure of a recycling containment. Enduring will restore the impacted surface area to the condition that existed prior to the construction of the recycling containment.
 - b. Reclamation of all disturbed areas no longer in use shall be considered complete when all ground surface disturbing activities at the site have been completed, and a uniform vegetative cover has been established that reflects a life-form ratio of plus or minus fifty percent (50%) of pre-disturbance levels and a total percent plant cover of at least seventy percent (70%) of pre-disturbance levels, excluding noxious weeds.
 - c. The re-vegetation and reclamation obligations imposed by federal, state trust land or tribal agencies on lands managed by those agencies shall supersede these provisions and govern the obligations of any operator subject to those provisions, provided that the other requirements provide equal or better protection of fresh water, human health and the environment.

NMOCD

SEP 11 2018

DISTRICT III

6. Within 60 days of final closure completion, Enduring will submit a closure report on form C-147, including required attachments, to document all closure activities including sampling results and the details on any backfilling, capping or covering, where applicable. The closure report will certify that all information in the report and attachments is correct and that Enduring has complied with all applicable closure requirements and conditions specified in division rules or directives.
7. Enduring will notify the NMOCD when the site has been reseeded and has achieved final revegetation.

Table I			
Closure Criteria for Recycling Containments			
Depth below bottom of containment to groundwater less than 10,000 mg/l TDS	Constituent	Method*	Limit**
51 feet - 100 feet	Chloride	EPA 300.0	10,000 mg/kg
	TPH (GRO+DRO+MRO)	EPA SW-846 Method 8015M	2,500 mg/kg
	GRO+DRO	EPA SW-846 Method 8015M	1,000 mg/kg
	BTEX	EPA SW-846 Method 8021B or 8260B	50 mg/kg
	Benzene	EPA SW-846 Method 8021B or 8260B	10 mg/kg
> 100 feet	Chloride	EPA 300.0	20,000 mg/kg
	TPH (GRO+DRO+MRO)	EPA SW-846 Method 8015M	2,500 mg/kg
	GRO+DRO	EPA SW-846 Method 8015M	1,000 mg/kg
	BTEX	EPA SW-846 Method 8021B or 8260B	50 mg/kg
	Benzene	EPA SW-846 Method 8021B or 8260B	10 mg/kg

* Or other test methods approved by the division.

** Numerical limits or natural background level, whichever is greater.

[19.15.34.14 NMAC - N, 3/31/15]

NMOCD

SEP 11 2018

DISTRICT III

Enduring Resources, LLC's

Recycling Containment

Migratory Bird Mitigation Plan

Enduring Resources, LLC (Enduring) is proposing this Migratory Bird Mitigation Plan (Mitigation Plan) in compliance with the New Mexico Oil Conservation Division (NMOCD) Rule 19.15.34.12.E. Enduring shall ensure that the recycling containment is protective of wildlife by implementing the following proposed Mitigation Plan. Enduring employees will inspect the containment weekly for and, within 30 days of discovery, report the discovery of dead migratory birds or other wildlife to the appropriate wildlife agency and to the division district office in order to facilitate assessment and implementation of measures to prevent incidents from reoccurring. This Mitigation Plan will utilize a combination of visual and audio deterrents to discourage wildlife, particularly birds and bats, from the recycling containment in order to mitigate potential impacts. This Mitigation Plan would be implemented while the Recycling Containment is active and in use, as to not desensitize birds to the deterrents.

The following mitigations will be implemented to reduce any wildlife impacts that may occur from the Recycling Containment:

- The following visual bird deterrents will be installed (Appendix A):
 - Bird-X Prowler Owl decoys will be installed at all four corners of the Containment.
 - Scare-Eye Balloons will be installed along the perimeter of the Containment.
- A Bird-X BroadBand PRO System will be installed at the Containment facility. It utilizes sonic (naturally-recorded bird distress calls & predator cries) to deter birds; as well as, ultrasonic high-frequency sound waves to deter bats. Bird propane cannons were avoided, so as not to disturb other wildlife species.
- The containment will be inspected on a monthly basis when water is present in the containment. All inspectors will insure the containment is receiving only filtered produced water with no hydrocarbons, as well as being trained to inspect the premises for, and respond to any wildlife incident, should it occur.
- Inspection will include:
 - An inspection of the filtration system and all visual and audio deterrents to insure they are in working order and functioning properly.
 - A thorough search of the entire containment facility, and just beyond, for the presence of any wildlife (entrapped, injured, dead, etc.).
- In the event a wildlife incident should occur, James McDaniel with Enduring will be contacted immediately and he will notify the appropriate wildlife agency and division district office. Enduring, appropriate wildlife agency, and division district office will then work collaboratively to address the incident appropriately to insure the incident does not reoccur.

Appendix A:
Visual and Audio Deterrents



All Bird-X Products

Electronic Bird Control >

- Sonic Bird Control
- Ultrasonic Bird Control
- Other Electronic Bird Deterrents
- Solar Panel Products

Bird Spikes

- Bird Spikes Kits
- Stainless Steel Spikes
- Plastic Spikes

Bird Netting

Drones

Laser Bird Control

Shock Track Systems

Bird Balls

Bird Wire

Visual Scares and Predator Decoys


Bird Gels, Taste Aversions, & OvoControl® P

For Songbird Lovers

Remote Control Drone

Retail Products

Accessories




BroadBand PRO

- ✓ Combines SONIC and ULTRASONIC Bird Control Technology
- ✓ Creates Uninviting Environment For Birds
- ✓ Covers Up To SIX ACRES

IN STOCK - AVAILABLE IMMEDIATELY!

Deter Birds With Multi-Faceted Sonic and Ultrasonic Attack! The BroadBand PRO's 4-speaker system simultaneously emits sounds that are both audible and inaudible to humans that confuse, disorient, and intimidate pest birds - keeping them away.

Starting at \$850.00 NOW \$725.00 (15% SAVINGS!)



Voltage Options: BroadBand PRO 110v (\$725)

Quantity: 1

Price: **\$725.00**

Product Total: **\$725.00**

ADD TO CART >

[Reviews](#) [Details](#) [Applications](#) [Benefits](#) [Add & Combine](#) [Specs](#) [Case Studies](#)

Guarantee • Warranty

Backed by our 30 Day Electronics Performance Satisfaction Guarantee AND our 6-Month Manufacturer's Warranty Against Material Defects.

- Option to add 3 Visual Scares to package for added efficacy
- Emits a combination of audible noises & high-frequency sound waves that are silent-to-most-humans
 - SONIC: Uses naturally-recorded bird distress calls & predator ones, covers up to 6 acres
 - ULTRASONIC: Uses high-frequency sound waves, covers up to 3,600 sq. ft.
- 4 speakers included – 4 independent speakers with 100 ft. of wire each
- Fully programmable – control volume, sound delays, & daylight / night operation
- Weather resistant – NEMA type box is designed to withstand outdoor use
- Option to add an assortment of three (3) high-quality [visual scare products](#)

All Bird-X Products

Electronic Bird Control

- [Sonic Bird Control](#)
- [Ultrasonic Bird Control](#)
- [Other Electronic Bird Deterrents](#)
- [Solar Panel Products](#)

Bird Spikes

- [Bird Spikes Kits](#)
- [Stainless Steel Spikes](#)
- [Plastic Spikes](#)

Bird Netting

Drones

Laser Bird Control

Shock Track Systems

Bird Balls

Bird Wire

Visual Scares and Predator Decoys >

Bird Gels, Taste Aversions, & OvoControl® P

For Songbird Lovers

Remote Control Drone

Retail Products

Accessories



Prowler Owl

- ✓ Proven Visual Scare
- ✓ **Saves Money on Cleanup & Repair**
- ✓ Eliminates Bird & Small Pest Problems
- ✓ Money-Back Guarantee

Decades proven visual deterrent, improved with dynamic realism & movement! Scare away birds & small pests with this predator replica of the most-feared aerial predator, the Great Horned Owl, which catches & eats nearly everything it can catch.

- Lifelike, wind-catching design increases effectiveness
- Accurate plumage & hunting flight pose
- Intimidating, glassy eyes "follow" pests
- Flexible wings move & flap in the wind realistically

Without movement, an owl scare is useless – don't be fooled by imitations that are immobile! Install Prowler Owl decoy in any open outdoor area where pest birds or small critters are a problem.

Quantity 1

Price **\$ 39.25**

Product Total: **\$ 39.25**

ADD TO CART >

 **Quality Guarantee**

Guaranteed to be manufactured to specifications & free from defect at the time of purchase.

[Reviews](#) [Details](#) [Applications](#) [Benefits](#) [Add & Combine](#) [Specs](#)

- Predator owl replica, life-size owl
- Owl scare repels pest birds & other small animals
- Always-moving "hunting" posture keeps birds away
- 4-foot wingspan & accurate markings
- Safe, humane, non-toxic, silent
- Covers up to 6,000 sq. ft.



Best control for today's environment.

Search

Call US: 800.463.3634

Home About News Blog Interviews BSA Retail Products Contact

Bird Products

Animal/Rodent Products

Insect Products

Interactive Problem Solver

Knowledge Center

FREE Evaluation



All Bird-X Products

Electronic Bird Control
Sonic Bird Control
Ultrasonic Bird Control
Other Electronic Bird
Deterrents
Solar Panel Products

Bird Spikes
Bird Spikes Kits
Stainless Steel Spikes
Plastic Spikes

Bird Netting

Drones

Laser Bird Control

Shock Track Systems

Bird Balls

Bird Wire

Visual Scares and Predator
Decoys >

Bird Gels, Taste Aversions,
& OvaControl® P

For Songbird Lovers

Remote Control Drone

Scare-Eye Balloons

- ✓ Simple, Highly Effective Bird Repellent
- ✓ Reduce Time & Energy Spent on Cleanup
- ✓ Reflective Mylar Eyes and Tails included

(3-Pack)

Keep birds away with these simple vinyl ball visual deterrents that move with the wind & intimidate pest birds within visible range

- Includes three balloons - one white, one yellow, one black
- Easy to use, cost-effective solution - hang the balloons anywhere
- Balloons move in the wind for fear of movement

Scare Eye® balloons are useful in many applications - homes, gardens, barns, tree garages, marinas, doorways, & many more



Quality Guarantee

Guaranteed to be manufactured to specifications and free from defect at the time of purchase.

Quantity 1

Price \$ 32.55

Product Total \$ 32.55

ADD TO CART >

Reviews

Details

Applications

Benefits

Add & Combine

Specs

- Predator decoy, 3D balloons
- Three balloons included: one (1) white, one (1) black, and one (1) yellow
- Includes mylar eyes, mylar tails, and strings for each balloon
- Weatherproof, vinyl, inflatable balloon
- Design exaggerates the glaring stare and gaping mouth of natural predators
- Wind causes the Scare-Eye Balloons to move in the wind, increasing efficacy
- Easy installation