300

BILL SELTZER

214 WEST TEXAS, SUITE 507 MIDLAND, TEXAS 79701 OF CONSERVATION DIVISION RECEIVED

'92 fmile Hm 8 26

March 9, 1992

Mr. William J. LeMay, Director Oil Conservation Division New Mexico Department of Energy Minerals and Natural Resources State Land Office Building Santa Fe, New Mexico 87503

1 21

Re: Application of Collins & Ware, Inc. for Administrative Approval of an Unorthodox location for its Muley Federal No. 1 Well located 1433 FSL and 1459 FEL of Section 26, T-23-S, R-25-E, Eddy County, New Mexico.

Dear Mr. LeMay:

Collins & Ware, Inc. hereby request administrative approval of an unorthodox well location for its Muley Federal No. 1 Well. The proposed location is in the Muley Unit composed of Federal, State and Fee lands and will test the Morrow Formation at approximately 12,200' and is located 1433 FSL and 1459 FEL of Section 26, T-23-S, R-25-E, N.M.P.M., Eddy County, New Mexico. This location is necessary due to topography conditions in the area. The proposed proration unit will consist of the S/2 of Section 26. The BLM has advised us of their approval at the requested location.

Attached please find copy of letter dated February 13, 1992 addressed to the BLM, along with Notice of Staking, Exhibits 2 and 2a and Exhibit 5, and copy of Form 3160-3, C-102, Drilling and Completion program together with Surface Use and Operation Plan.

The Muley Unit has been approved by the BLM, Commissioner of Public Lands and the OCD under Order No. R-9638, all attached.

Collins & Ware, Inc. is the operator of the offsetting spacing units to the North, Northeast, East, Southeast, and South. Yates Petroleum Corporation is the operator of the spacing unit to the Southwest and Santa Fe Energy to the West and Northwest.

Attached to this application are letters requesting Waivers from all offsetting operators.

The attached plat also indicates the S/2 of Section 26, T-23-S, R-25-E has been dedicated to the proration unit with the well location and identifying the leasehold ownership of the leases.

In the absence of the offsetting operators executing Waivers to the unorthodox location and after 20 days from the date of this application, we request the Division Director to grant Collins & Ware, Inc. an exception to this location based upon topographical conditions.

Reference is hereby made to OCD case No. 1043 and Order No. R-9638 for geological information and discussion.

Your consideration of this application is appreciated.

Yours very truly,

Bill Seltzer

BS/kp Atchs.

cc: Collins & Ware, Inc. 303 W. Wall, Suite 2200 Midland, Texas 79701

M.B. Williams
Supervisor
Oil Conservation Division
District #
P.O. Drawer DD
Artesia, New Mexico 88210

OIL CONSERV HOMENS DIVIGIO AS 15

RECEIVED

BILL SELTZER

214 WEST TEXAS, SUITE 507 MIDLAND, TEXAS 79701

'92 MAR 19 AM 9 02

March 16, 1992

Re: Administrative Order
NSL-3105

Mr. William J. LeMay Oil Conservation Commission P.O. Box 2088 Santa Fe, new Mexico 87501

Dear Mr. LeMay:

Reference is hereby made to the above Administrative Order.

Attached please find Waivers from Santa Fe Energy Operating Partners, L.P. and Yates Petroleum Corporation.

Thank you for your prompt attention.

Yours very truly,

Bill Seltzer

BS/kp Atchs.

WAIVER

The undersigned party has no objection to Collins & Ware, Inc.'s application to drill a 12,200' Morrow Test at an unorthodox location in Eddy County, New Mexico, to-wit:

> 1433 FSL and 1459 FEL of T-23-S, R-25-E, Eddy County, New Mexico

> > SANTA FE ENERGY OPERATING

APPROVED

PARTNERS,

Printed Name: T.S. Parker

Title: Attorney-in-Fact

Date: March 12, 1992

WAIVER

The undersigned party has no objection to Collins & Ware, Inc.'s application to drill a 12,200' Morrow Test at an unorthodox location in Eddy County, New Mexico, to-wit:

1433 FSL and 1459 FEL of Section 26, T-23-S, R-25-E, Eddy County, New Mexico

YATES PETROLEUM CORPORATION

By: Name:

Title: / Atty-in-/Fret

Date: 3-12-92

RB

BILL SELTZER

214 WEST TEXAS, SUITE \$07 MIDLAND, TEXAS 79701

Certified #P 046 665 861

March 9, 1992

Re: T-23-S, R-25-E Section 26: S/2

Eddy County, New Mexico

Muley Federal #1

Santa Fe Energy Operating Partners, L.P. 550 W. Texas, Suite 1330 Midland, Texas 79701

Gentlemen:

I am representing Collins & Ware, Inc. of Midland, Texas.

Collins & Ware, Inc. has been granted approval from the BLM, Commissioner of Public Lands and OCD, State of New Mexico to form a 5757.40 acre Federal-State and Fee Exploratory Unit as shown on the attached plat marked Exhibit "A".

The BLM inspectors have approved a location for the test well as 1433 FSL and 1459 FEL of Section 26, T-23-S, R-25-E, as shown on the attached plat. No legal locations within the S/2 of Section 26 would be approved because of topographical conditions.

We are requesting the OCD, State of New Mexico for an administrative approval of this unorthodox location and we request you to execute the attached Waiver and return in the enclosed envelop.

Your immediate attention will be appreciated.

Yours very truly,

Bill Seltzer

BS/kp

Atch: Waiver


WAIVER

The undersigned party has no objection to Collins & Ware, Inc.'s application to drill a 12,200' Morrow Test at an unorthodox location in Eddy County, New Mexico, to-wit:

1433 FSL and 1459 FEL of Section 26, T-23-S, R-25-E, Eddy County, New Mexico

SANTA FE ENERGY OPERATING PARTNERS, L.P.

3y:		*
Printed	Name:	
Title:		
Date:		
		



Form 3160-3 (November 1983)

SUBMIT IN TRIPLICATE. (Other instructions on

Form approved. Budget Bureau No. 1004-0136

		ITED STATE			side)	Expires August 31, 1985
	DEPARTMEN			₹		G. LEARE DESIGNATION AND BERIAL NO.
	BUREAU O	F LAND MANA	GEMENT			NM 51073
APPLICATIO	N FOR PERMIT	TO DRILL,	DEEPEN,	OR PLUG	BACK	G. IF INDIAN, ALLOTTER OR TRIDE NAME
1a. TYPE OF WORK						-
b. Tire of Well	RILL 🖾	DEEPEN		PLUG BA	ACK [7. UNIT AUBERMENT NAME
MEI'F	WELL OTHER	٠	BINGI, B Zone	X ZONE		S. FARM OR LEASE NAME
2. NAME OF OPERATOR						Muley Federal
Collins & W				·		D. WELL NO.
3. ADDRESS OF OPERATOR	•					1
	Suite 2200, Mid					10. FIELD AND POOL, OR WILDCAT Unde
At surface	tepore location ciently an	d in accordance w	ith any state re	quirements.")		Horseshoe Bend (Strawn-
	1459' FEL of S	ec. 26				AND SURVEI OR AREA MOTTOW)
At proposed prod. zo Same	пе			:		
	AND DIRECTION FROM NE.	AREST TOWN OR FO	ST OFFICE.			Sec. 26, T23S, R25E
6 air miles so	outhwest of Car	lsbad. NM a	irport			· Eddy NM
10. DISTANCE FROM PROF LOCATION TO NEARES	USED*	,	10. NO. OF AC	RES IN LEASE		F ACRES ASSIGNED
PROPERTY OF LEARS (Also to pencest dri	LINE, FT 1/	433' FS	1440		70 71	320
18. DISTANCE FROM PROJ	POSED LOCATION*	······································	10. PROPOSED	DEPTH	20. ROTAL	RY OR CABLE TOOLS
TO MEAREST WELL, I OR APPLIED FOR, ON TH	DRILLING, COMPLETED,	4/V	12200'		Ro	tary
21. ELEVATIONS (Show wh	nether DF, RT, GR, etc.)		<u>'</u>			22. AI'FROX. DATE WORK WILL START*
3519.9 GR			•			Soon after approval
23.		PROPOSED CASI	ING AND CEME	NTING PROGRA	\M	
SIZE OF HOLE	BIZE OF CABING	WEIGHT PERF	OOT 85	TTING DEPTH	1	QUANTITY OF CEMENT
812E OF HOLE					450 50	
	13.375" 9.625"	48-61#		350°	450 sz 625 sz	ζ
17.5"	13.375"		3 18	3501	625 sx	ς
17.5" 12.25" 8.5/8.75"	13.375" 9.625" 5.5"	48-61# 40-43# 15.5-20#	18 122	350' 300' 300'	625 system of the upp	c c lent to fill to 600' abov permost productive zone
17.5" 12.25" 8.5/8.75" the Operator pro	13.375" 9.625" 5.5" poses to drill	48-61# 40-43# 15.5-20# to a depth	3 18 122 sufficien	350' 300' 300'	625 sy suffic- the upp the Mor	dent to fill to 600' abovermost productive zone crow and/or the Strawn fo
17.5" 12.25" 8.5/8.75" the Operator producti	13.375" 9.625" 5.5" poses to drill ve, 5.5" casing	48-61# 40-43# 15.5-20# to a depth will be se	3 18 122 sufficien	350' 300' 200' at to test	625 system of the uppose the Moral TD. If r	K Lent to fill to 600' abovermost productive zone crow and/or the Strawn fo
17.5" 12.25" 8.5/8.75" ne Operator productiill be plugged	13.375" 9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i	48-61# 40-43# 15.5-20# to a depth will be seen a manner	sufficient and cem consisten	350' 300' 300' t to test tented to ' t with Fe	625 system of the uppose the Morror TD. If referral are	dent to fill to 600' above the strawn for the Strawn for the well and State regulations and
17.5" 12.25" 8.5/8.75" he Operator production of the plugged ecording to pru	13.375" 9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin	48-61# 40-43# 15.5-20# to a depth will be sen a manner g practice.	sufficient and cemt consistent. Specific	350' 300' 200' t to test ented to ' t with Fed programs	625 system of the uppose the Morror TD. If referral are	Rent to fill to 600' abovermost productive zone crow and/or the Strawn fo
17.5" 12.25" 8.5/8.75" ne Operator production in the plugged ecording to pruder #1 are out	13.375" 9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att	sufficient and cem consistent Specific acliments:	350' 300' 200' t to test ented to ' t with Fed programs	625 system of the uppose the Morror TD. If referral are	dent to fill to 600' above the strawn for the Strawn for the well and State regulations and
17.5" 12.25" 8.5/8.75" ne Operator production in the plugged ecording to pruder #1 are out	13.375" 9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att	sufficient and cem consistent Specific acliments:	350' 300' 200' t to test ented to ' t with Fed programs	625 system of the uppose the Morror TD. If referral are	dent to fill to 600' above permost productive zone row and/or the Strawn for the well and State regulations and
17.5" 12.25" 8.5/8.75" he Operator production of the production	13.375" 9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing atte	sufficient and cem consistent Specific acluments:	350' 300' 200' t to test ented to ' t with Fed programs	625 system of the uppose the Morror TD. If referral are	dent to fill to 600' above permost productive zone row and/or the Strawn for the well and State regulations and
17.5" 12.25" 8.5/8.75" ne Operator production of the plugged ecording to prunder #1 are out 1. Well Loca 2. Drilling Exhibits 3. Surface U	13.375" 9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att e Dedication ut Prevente g Plan	sufficient and cem consistent Specific acluments:	350' 300' 200' t to test ented to ' t with Fed programs	625 system of the uppose the Morror TD. If referral are	dent to fill to 600' above the strawn for the Strawn for the well and State regulations and
17.5" 12.25" 8.5/8.75" he Operator productiful be plugged coording to pruder #1 are out 1. Well Loca 2. Drilling Exhibits 3. Surface U Exhibit #	13.375" 9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin 2 - Existing Ro	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att e Dedication ut Prevente g Plan ads	sufficient and cem consistent Specific acluments:	350' 300' 200' t to test ented to ' t with Fed programs	625 system of the uppose the Morror TD. If referral are	dent to fill to 600' above the strawn for the Strawn for the well and State regulations and
17.5" 12.25" 8.5/8.75" he Operator production of the production of	13.375" 9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin 2 - Existing Ro 2A - Planned Ac	48-61# 40-43# 15.5-20# to a depth will be send a manner g practice. llowing att e Dedication ut Prevente g Plan ads cess Roads	sufficient and cemt consistent Specific acliments: on Plat	350' 300' 200' It to test ented to ' t with Fed programs	625 system of the uppose the Morror TD. If referral are	dent to fill to 600' above the strawn for the Strawn for the well and State regulations and
17.5" 12.25" 8.5/8.75" he Operator productiful be plugged according to pruceder #1 are out 1. Well Loca 2. Drilling Exhibits 3. Surface U Exhibit # Exhibit # Exhibit #	13.375" 9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin 2 - Existing Ro 2A - Planned Ac 3 - One-Mile Ra	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att e Dedication ut Prevente g Plan ads cess Roads dius Map an	sufficient and cemt consistent Specific acliments: on Plat	350' 300' 200' It to test ented to ' t with Fed programs	625 system of the uppose the Morror TD. If referral are	dent to fill to 600' above permost productive zone row and/or the Strawn for the well and State regulations and
17.5" 12.25" 8.5/8.75" he Operator productiful be plugged according to prunder #1 are out 1. Well Loca 2. Drilling Exhibits 3. Surface U Exhibit # Exhibit # Exhibit #	9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin 2 - Existing Ro 2A - Planned Ac 3 - One-Mile Ra 3A - Well Statu	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att e Dedication ut Prevente g Plan ads cess Roads dius Map ans	sufficient and cemt consistent Specific acliments: on Plat	350' 300' 200' It to test ented to ' t with Fed programs	625 system of the uppose the Morror TD. If referral are	dent to fill to 600' above permost productive zone row and/or the Strawn for the well and State regulations and
17.5" 12.25" 8.5/8.75" he Operator productiful be plugged according to prunder #1 are out 1. Well Loca 2. Drilling Exhibits 3. Surface U Exhibit # Exhibi	9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin 2 - Existing Ro 2A - Planned Ac 3 - One-Mile Ra 3A - Well Statu 4 - Drilling Ri	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att e Dedication ut Prevente g Plan ads cess Roads dius Map an s g Layout	sufficient and cem consistent Specific achments: on Plat	350' 300' 300' 300' 300' 300' 300' 300'	suffiction suffice the uppose the MorID. If rederal areacording	dent to fill to 600' abovermost productive zone row and/or the Strawn for the well and State regulations and ang to Onshore Oil & Gas
17.5" 12.25" 8.5/8.75" he Operator productiful be plugged coording to prunder #1 are out 1. Well Loca 2. Drilling Exhibits 3. Surface U Exhibit # Exhibit # Exhibit # Exhibit # Exhibit # Exhibit #	9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin 2 - Existing Ro 2A - Planned Ac 3 - One-Mile Ra 3A - Well Statu 4 - Drilling Ri 5 - Production programs 5 - Production programs	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att e Dedication ut Prevente g Plan ads cess Roads dius Map an s g Layout Facilli le derre	sufficient and cement and cements: Specific achments: on Plat	050' 000' to test tented to ' t with Fer programs oundary	suffice the upper the Morror of the Morror o	dent to fill to 600' above permost productive zone row and/or the Strawn for the well and State regulations and
17.5" 12.25" 8.5/8.75" he Operator productiful be plugged according to prunted #1 are out 1. Well Loca 2. Drilling Exhibits 3. Surface U Exhibit # Exh	9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin 2 - Existing Ro 2A - Planned Ac 3 - One-Mile Ra 3A - Well Statu 4 - Drilling Ri 5 - Production Fromoroged Program in R 5 reproduction of program in Control Program in Control Fill or deepen directional	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att e Dedication ut Prevente g Plan ads cess Roads dius Map an s g Layout Facilli le derre	sufficient and cement and cements: Specific achments: on Plat	050' 000' to test tented to ' t with Fer programs oundary	suffice the upper the Morror of the Morror o	lent to fill to 600' abovermost productive zone row and/or the Strawn for some productive, the well of State regulations and and to Onshore Oil & Gas
17.5" 12.25" 8.5/8.75" he Operator productiful be plugged coording to prunder #1 are out 1. Well Loca 2. Drilling Exhibits 3. Surface U Exhibit # Exhi	9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin 2 - Existing Ro 2A - Planned Ac 3 - One-Mile Ra 3A - Well Statu 4 - Drilling Ri 5 - Production Fromoroged Program in R 5 reproduction of program in Control Program in Control Fill or deepen directional	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att e Dedication ut Prevente g Plan ads cess Roads dius Map an s g Layout Facilli le derre	sufficient and cement and cement and cements: on Specific acliments: on Platers d Lease Billion of Platers and Lease Billion on Rubsurf	oundary	suffice the upper the Morror of the Morror o	dent to fill to 600' above permost productive zone crow and/or the Strawn for non-productive, the well and State regulations and ang to Onshore Oil & Gas
17.5" 12.25" 8.5/8.75" he Operator production of the production	13.375" 9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin 2 - Existing Ro 2A - Planned Ac 3 - One-Mile Ra 3A - Well Statu 4 - Drilling Ri 5 - Production Profosed Production Fill or deepen directional	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att e Dedication ut Prevente g Plan ads cess Roads dius Map an s g Layout Facilli le derre	sufficient and cement and cement and cements: Specific achments: On Plat Layout the consumption on subsurf	oundary	suffice the upper the Morror of the Morror o	lent to fill to 600' abovermost productive zone row and/or the Strawn for sone productive, the well of State regulations and and to Onshore Oil & Gas
17.5" 12.25" 8.5/8.75" he Operator productiful be plugged according to prunted #1 are out 1. Well Loca 2. Drilling Exhibits 3. Surface U Exhibit # Exh	9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin 2 - Existing Ro 2A - Planned Ac 3 - One-Mile Ra 3A - Well Statu 4 - Drilling Ri 5 - Production Profosed P	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att e Dedication ut Prevente g Plan ads cess Roads dius Map an s g Layout Facilities in possible perfinent	sufficient and cement and cement and cements: Specific achments: On Plat Layout the consumption on subsurf	oundary	suffice the upper the Morror of the Morror o	dent to fill to 600' above the strawn for the Strawn for the Strawn for the strawn for the productive, the well and State regulations and ang to Onshore Oil & Gas the strawn for the stra
17.5" 12.25" 8.5/8.75" he Operator productiful be plugged according to prunder #1 are out 1. Well Loca 2. Drilling Exhibits 3. Surface U Exhibit # Exh	9.625" 5.5" poses to drill ve, 5.5" casing and abandoned i dent engineerin lined in the fo tion and Acreag Program #1 & 1A - Blowo se and Operatin 2 - Existing Ro 2A - Planned Ac 3 - One-Mile Ra 3A - Well Statu 4 - Drilling Ri 5 - Production Profosed P	48-61# 40-43# 15.5-20# to a depth will be seen a manner g practice. llowing att e Dedication ut Prevente g Plan ads cess Roads dius Map an s g Layout Facilities in possible perfinent	sufficient and cement and cement and cements: Specific achments: On Plat Layout the consumption on subsurf	oundary	suffice the upper the Morror of the Morror o	dent to fill to 600' above the strawn for the Strawn for the Strawn for the strawn for the productive, the well and State regulations and ang to Onshore Oil & Gas the strawn for the stra

O D Coll. 1

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-102 Revised 1-1-89

OIL CONSERVATION DIVISION

DISTRICT | P.O. Box 1980, Hobbs, NM 88240

P.O. Box 2088 Santa Fe, New Mexico 87504-2088

DISTRICT II P.O. Drawer DD, Artesia, NM 88216

WELL LOCATION AND ACREAGE DEDICATION PLAT

DISTRICT III
1900 Rio Brasos Rd., Asteo, NM 87410

All Dictange must be from the outer houndaries of the section

			יו או	Statices illust	<u></u>	8 00151	DOMINATIO	13 01 1110 36611011		1
Operator Collin	is & Wa	re			Leave	Mii	lev Fe	ed. Unit		Well No.
			mahip				10) 10		County	<u> </u>
Unit Letter	Section 26	Tor	23 Sc	outh	Range 25	East		100	County	ddy
Actual Footage Loca		(0));	23 30	10 011	1 2	Lust		NMP	<u> </u>	uuy .
4.450		Fast		_	143	3			m the South	h
Ground Level Elev.	from the	ucing Format	line ar	<u> </u>	Pool	<u> </u>			m the Journ	Dedicated Acreege:
3519.9	11/	trawn -			1	Joe	Horse	shöe Bend		320 Acres
				/						320 Acres
1. Outline the ac	reals dedi	oated to the	sapleof se	I ph colored	benefit or	hachur	* marks	on the plat best		
2. If more than	ODe lease	is dedicated	to the well	. outline eacl	and iden	utty ti	TO OMITORIE	hip thereof (bo	th as to workh	ng interest and royalty).
/	.\									
unitization, fo			ownership	is dedicated t	the well	L, have	the inte	rest of all owns	ors been conso.	lidated by communitization.
Yes	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	``	f answer is	yes type	of consoli	dation				
	_ _ مارو•	_ `_						2/2-4 4 /77		
If answer is "no"		ADOLS SDG O	act descri	DODE ADICU	DAYS ACCU	ащу ве	Hear Coarse	manted. (Use re	MALSO SIGE OF	
		igned to the	well uni	t all interes	ts have b	een o	onsolidat	ed (by comm	unitization, u	nitization, forced-pooling.
otherwise) or un	atil a non	-standard u	nit, elimin	ating such is	nterest, h	as bee	n approv	red by the Divi	eton.	
\ <u>\</u>									OPERA	TOR CERTIFICATION
		 -				1			7.3-	oby certify the the information
				1		1		1	1	vin is true and complete to the
ļ	. 1					- 1			1	souledge and ballef.
	ĺ					1				
]					1		İ	Signature	V // -
	ļ		•	ĺ		- 1		İ	0,00	rane Miller
}	i					i			Printed Nex	D4
L	ا 4			<u>L</u>		! 				ane Akins
				T					Position	
	ſ					1		ļ	Agent	<u>,,</u>
				•		l		İ	Company	· C II T
	1					1			<u> </u>	ns & Ware, Inc.
	· j					Ī			Date	
	1					í		·	Februa	ary 13, 1992
		•				1			SURVRY	OR CERTIFICATION
1	j				•	1		1	Bowar	
Commence of the control of the contr									I hereby worth	the that the well location shown
	1]	•	Ţ		1	on this plat	was plotted from field notes of
		•		Į.					artual survey	e made by me or undermy and that the same is true and
	1					Ţ			served to t	he best of my knowledge and
	i			1 .		Ĺ			bodies.	
	i						200		Date Surve	y ed
1	ì				3509.7	135	828.9		1 - '	ruary 7, 1992
	į				į	0.11	145	9'	Signature &	
#	+			十一一一	· — -;-	<u>-</u> 1-+i-				d Surveyor
1	1				3514,5	T3 2	37.9	1		
1	ł			Ì				į.		ERED LAND
1	i i			1		1			10.01	CRED LAND TO
•	1					iú		H	D.S. C	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1
	1					4	•		Wing	1//1/2012
	į					!			(IH)	W V WWW
1	1					!			Certificate	No. 8/2 10/6) W. WEST. 2 676
				4					1/ = 3	RONALD I ADSON, " TETT
	202				200		1000	500	11Ent	202 MEDIAN S
0 530 660	990 152	0 1650 198	W 2310 2	D40 20	000 15	500	1000	500 0	W 'V	111 - 0 (44) 11
										William Mark

DRILLING PROGRAM

COLLINS & WARE, INC. MULEY FEDERAL WELL NO. 1

1433' FSL & 1459'FEL Sec. 26, T23S, R25E, Eddy County, NM

The following information is filed in accordance with "Onshore Oil and Gas Order" Nos. 1 & 2:

SURFACE FORMATION: Seven Rivers

2. ESTIMATED TOPS OF GEOLOGIC MARKERS:

Delaware	2550'
Bone Springs	5200'
Wolfcamp	8200'
Strawn	9850'
Atoka	10200'
Morrow Clastics	10900'

3. ESTIMATED DEPTH TO FRESH WATER:

Possible fresh water at 100-300'

ANTICIPATED POSSIBLE HYDROCARBON BEARING ZONES:

Strawn

Gas/Cond.

Morrow

Gas.

No other formations are anticipated to give up commercial quantities of hydrocarbons.

The fresh water sands will be protected by setting 13 3/8" casing at 350' and circulating cement back to surface. Intermediate 9 5/8" casing will be set at 1800' and cement circulated back to surface. Any shallower zones above TD that contain commercial quantities of oil and/or gas will have cement circulated across them by single/double stage cementing techniques.

4. PROPOSED CASING AND CEMENTING PROGRAM:

Casing:

Hole Size	Interval	Casing OD	Weight, Grade, Joint, Condition
17.5"	0-350'	13 3/8"	48-61#, K-55, ST&C, New
12.25"	0-1800'	9 5/8"	24-32#, J-55&S-80, ST&C, New
8.5/8.75"	0-12200'	5 1/2"	15.5-20#, K-55&N-80, LT&C, New

Cement:

13 3/8" Surface Csg: Cemented with 450 sacks of Class "C" with 2% CaCl. Circulate cement.

9 5/8" Intermediate: Cemented with 425 sacks of light cement tailed in with 200 sacks of Class "C" with 1% CaCl. Cement to circulate.

5 1/2" Prod. Casing: Cemented with sufficient sacks of Class "H" with additives to fill to 600' above the uppermost productive zone.

Page 2 - Drilling Program Collins & Ware Muley Federal No. 1

5. PRESSURE CONTROL EQUIPMENT:

Blowout prevention equipment, while drilling the 12 1/4" hole, will be either a 1500 psi working pressure double ram type preventer or a 1500 psi working pressure annular type preventer.

Blowout prevention equipment, while drilling below the 9 5/8" casing seat, will be a 3000 psi working pressure BOP stack.

BOP sketches are shown on Exhibits 1 & 1A.

6. CIRCULATING MEDIUM:

Surface to 350' : Fresh water spud mud - Viscosity 28 to 36 as

required for hole cleaning, 8.5-8.8#/gal.

350' to 1800' : Fresh water with pH control, weight 8.4-9.2#/gal

LCM sweeps as required to clean hole.

1800' to 10,300': Brine water conditioned as necessary for con-

trol of hole, 28-50 viscosity, wt 10.5#/gal,

pH 9-10.

10,300' to T.D. : Water-based drilling fluid conditioned as neces-

sary for control of weight, viscosity, pH and water loss. Wt 9-10.5#, Viscosity 30-50, pH 9-10 (control with lime), filtrate while drilling Strawn/Morrow sections will be 10 cc or less.

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept at the well site at all times.

7. AUXILIARY WELL CONTROL AND MONITORING EQUIPMENT:


- A. A kelly cock will be used.
- B. A full-opening stabbing valve with proper drill pipe connections will be on the rig floor at all times.
- C. The drilling fluids system will be visually monitored at all times.
- D. A mud-logging unit will monitor drilling penetration rate and hydrocarbon shows from somewhere below the intermediate casing.

8. TESTING, LOGGING, AND CORING PROGRAMS:

- A. Four drill stem tests are planned.
- B. Compensated Neutron Log Litho-density GR and Dual Laterolog with MSFL Log/GR from total depth back to intermediate casing. Gamma Ray log will be continued back to surface.
- C. A mud-logging unit will be used below 2300'.
- D. No cores anticipated.
- E. Other testing procedures may be used after the production casing has been set depending on shows and other testing indicators.

Page 3 - Drilling Program
Collins & Ware Muley Federal No. 1


- 9. ABNORMAL CONDITIONS, PRESSURES, TEMPERATURES, & POTENTIAL HAZARDS:
 No abnormal pressures or temperatures are anticipated. The estimated bottom hole temperature (BHT) at TD is 148 F and the estimated maximum bottom hole pressure (BHP) is about 6000 psi. No hydrogen sulphide (H2S) or other hazardous fluids are known to exist at this depth in this area. No major lost circulation zones have been reported in wells in this area below the base of the Capitan Reef.
- 10. ANTICIPATED STARTING DATE AND DURATION OF OPERATIONS:
 It is planned that operations will commence shortly after approval of this application, with drilling and completion operations lasting about 60-90 days. A decision as to design and installation of permanent facilities will be made after adequate testing of the well.



1500 PSI WORKING PRESSURE

IN USE WHILE DRILLING BELOW SURFACE CASING

Exhibit No. 1 BOP ARRANGEMENT



BOP STACK

3000 PSI WORKING PRESSURE

IN USE WHILE DRILLING BELOW 9-5/8" CASING SEAT

Exhibit No. IA BOP ARRANGEMENT

SURFACE USE AND OPERATIONS PLAN FOR

COLLINS & WARE, INC.

MULEY FEDERAL WELL NO. 1

1433' FSL & 1459' FEL SEC. 26, T.23 S., R.25 E.

EDDY COUNTY, NEW MEXICO

LOCATED: 6 air miles southwest of Carlsbad, NM Airport

FEDERAL LEASE NUMBER: NM-51073

LEASE ISSUED: June 1, 1982 HBP

ACRES IN LEASE: 1440

TERM: Ten Years

LESSEE: Collins & Ware, Inc.

SURFACE OWNERSHIP: Roland Fech (505) 885-1250

353 Dark Canyon Rd. Carlsbad, NM 88220

GRAZING PERMITTEE: Roland Fech (505) 885-1250

353 Dark Canyon Rd. Carlsbad, NM 88220

POOL: Undesignated Horseshoe Bend - Strawn/Morrow

POOL RULES: Statewide Rules - 320-acre spacing for gas

EXHIBITS: 2. Existing roads

- 2A. Planned access roads
- 3. One-Mile Radius Map showing lease boundary and wells
- 3A. Well Status
- 4. Drilling Rig Layout
- 5. Production Facilities Layout

Page 2 - Surface Use and Operating Plan Collins & Ware Muley Federal No. 1

1. EXISTING ROADS:

A. Exhibit No. 2 is a portion of a road map showing the location of the proposed well as staked. Point "A" on the plat is on US 62-180 approximately 2.5 miles southwest of Carlsbad, NM city limits and about 8.2 miles south of the intersection of US 285 and one mile south of the Port of Entry. At Point "A", turn west on County Road 408. Travel generally west and south for about 6.5 miles to location just off the road to the east.

2. PLANNED ACCESS ROAD:

- A. Length and Width: The new road will be 12' wide and is less than 100' long to service the Muley Federal Well No. 1 and is too short to be shown on Exhibit No. 2A.
- B. Surfacing Material: Caliche, watered, compacted and graded.
- C: Maximum Grade: Less than one per cent (1%).
- D. Turnouts: None necessary.
- E. Drainage Design: N/A
- F. Culverts: None needed.
- G. Cuts and Fills: None necessary.
- H. Gates and Cattleguards: None necessary.
- I. Existing access roads to the proposed wellsite will be used in their present state. Off-lease access approval, if necessary, will be executed under the Muley Federal No. 1 location.

3. LOCATION OF EXISTING WELLS:

- A. Existing wells within a one-mile radius are shown on Exhibit No.
 - 3. There is only one well and its status is shown on Exhibit No. 3A. There are no disposal, injection, or observation wells within the one-mile radius.

4. LOCATION OF EXISTING AND/OR PROPOSED FACILITIES:

A. Necessary production facilities for this proposed well will be located on the well pad. A layout of the production facilities is shown in Exhibit No. 5.

5. LOCATION AND TYPE OF WATER SUPPLY:

A. It is not planned that a water supply well will be drilled. Water necessary for drilling operations will be purchased and trucked from commercial water stations to the well site, or will be moved to the well site by temporary pipeline laid on the ground alongside existing and proposed roads.

Page 3 - Surface Use and Operating Plan
Collins & Ware Muley Federal No. 1

6. SOURCE OF CONSTRUCTION MATERIALS:

A. Caliche needed for construction work will be taken, if present, from a pit opened on-site within the 400' X 450' work area. Otherwise, caliche will be taken from an existing pit on Federal land in the NW/4 of NE/4 of Sec. 26, T.23S., R.25E., Eddy County. Caliche will be trucked to well site over existing and proposed roads. Location of the nearest caliche pit is shown on Exhibit No. 2A.

7. METHODS OF HANDLING WASTE MATERIAL:

- A. Drill cuttings will be disposed of in the drilling pits.
- B. Drilling fluids will be contained in steel tanks during drilling operations. The reserve pit will contain any excess drilling fluid or flow from the well during drilling and completion operations. The reserve pit will be an earthen pit about 150' X 150' X 6' deep and fenced on three sides prior to drilling. The pit will be plastic-lined (5-7 mil thickness) to minimize loss of drilling fluids and saturation of the ground with brine water. The drilling fluids will be allowed to evaporate in the drilling pits until the pits are dry.
- C. Water produced during tests will be disposed of in the drilling pits. After the well is permanently placed on production, produced water will be collected in fiberglass or steel tanks until hauled by transport to an approved disposal system.
- D. Oil produced during tests will be stored in test tanks until sold
- E. Trash, waste paper, garbage and junk will be stored in a covered, above-ground container. All waste material will be contained to prevent scattering by the wind. Location of the trash container is shown on Exhibit No. 5. No toxic waste or hazardous chemicals will be produced by this operation. The container will be emptied when full and taken to an authorized disposal facility.
- F. All trash and debris will be removed from the well site within 30 days after finishing drilling and/or completion operations. No adverse materials will be left on location. The reserve pit will be completely fenced and kept closed until it is dried. When the reserve pit is dry enough to break out and fill in, as weather permits, the unused portion of the well site will be leveled and restored to BLM specifications. Only that part of the pad required for production facilities will be kept in use. In the event of a dry hole, only a dry hole marker will remain.
- G. If required, a portable, chemical toilet will be provided on the location for human waste during the drilling and completion operations.

8. ANCILLARY FACILITIES:

A. No airstrip, campsite, or other facilities will be built as a result of the operations of this well.

Page 4 - Surface Use and Operating Plan Collins & Ware Muley Federal No. 1

9. WELL SITE LAYOUT:

- A. Exhibit No. 4 shows the relative location and dimensions of the well pad, mud pits, reserve pit, and the location and orientation of major drilling rig components. No permanent living facilities are planned, but a temporary foreman/toolpusher's trailer will be on location during the drilling and completion operations.
- B. Clearing and levelling of the well site will be required. Top soil, if available, will be stockpiled per BLM specifications as determined at the on-site inspection. No major cuts will be required.
- C. The pad and pit area are staked and flagged.

10. PLANS FOR RESTORATION OF THE SURFACE:

- A. After completion of drilling and/or completion operations, all equipment and other material not needed for operations will be removed from the well site. Pits, after allowing to dry, will be broken out and levelled. The location will also be levelled and cleaned of all trash and junk to leave the well site in an as aesthetically pleasing condition as possible. Any part of the pad not needed for production facilities will have the top soil replaced and reseeded. Any tank battery constructed will be low profile and surface facilities will be painted either Desert Tan or Juniper green. This should be accomplished within 120 days.
- B. Any unguarded pits containing fluids will be fenced.
- C. After abandonment, all equipment, trash, and junk will be removed and the well site will be cleaned. Any special rehabilitation requirements of the surface management agency will be complied with and accomplished as rapidly as possible.

11. OTHER INFORMATION:

- A. Topography The land surface in the area is a bottom area between steep hills. In the immediate area of the well site, land slope is gentle to the northwest.
- B. Soil Top soil at the well site is a dark clay and quite rocky.
- C. Flora and Fauna The vegetation cover is heavy and includes brambles, sand sage, yucca, weeds, and range grasses. Wildlife in the area is that typical of semi-arid desert land and includes coyotes, rabbits, rodents, reptiles, dove and quail.
- D. Ponds and Streams There is a dry stream bed a few hundred feet to the west of the location. No other lakes, ponds, or streams in the area.
- E. Residences and other Structures There are no occupied dwellings or other structures, other than oil field related equipment, within a mile of the proposed well site.
- F. Archaeological, Historical, and Cultural Sites None observed. However, an archaeological reconnaissance is to be accomplished and a report furnished.
- G. Land Use Oil and gas production, grazing and wildlife habitat.
- H. Surface Ownership Federal.

Page 5 - Surface Use and Operating Plan Collins & Ware Muley Federal No. 1

12. OPÉRATOR'S REPRESENTATIVE:

James F. O'Briant O'Briant Engineering P.O. Box 10487 Midland, TX 79702 Telephone: (915) 683-5511


13. CERTIFICATION:


I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions which currently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and, that the work associated with the operations proposed herein will be performed by Collins & Ware, Inc. and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

Date: 2/20/92

G. Thane Akins, P.E.

Agent for Collins & Ware, Inc.










EXHIBIT NO. 3A

STATUS OF WELLS WITHIN ONE-MILE RADIUS Collins & Ware Muley Federal No. 1 Well Sec. 26, T23S, R25E, Eddy County, NM

Sec. 35, T23S, R25E

Pecos Valley Drlg McIntyre No. 1, 330'FW & 330'FNL, Dry Hole(TD 3371')





Tank Battery is low profile with special paint.

EXHIBIT NO. 5

PRODUCTION FACILITIES LAYOUT
COLLINS & WARE, INC. MULEY FEDERAL NO. 1

Eddy County, New Mexico Scale: None

FFICE PHONE 915 - 684-5381

BILL SELTZER

214 WEST TEXAS, SUITE 507 MIDLAND, TEXAS 79701

Certified #P 046 665 860

March 9, 1992

T-23-S, R-25-ESection 26: S/2.

Eddy County, New Mexico

Muley Federal #1

Mr. Robert Bullock Yates Petroleum Corporation 105 South Fourth Street Artesia, New Mexico 88210

Dear Mr. Bullock:

I am representing Collins & Ware, Inc. of Midland, Texas.

Collins & Ware, Inc. has been granted approval from the BLM, Commissioner of Public Lands and OCD, State of New Mexico to form a 5757.40 acre Federal-State and Fee Exploratory Unit as shown on the attached plat marked Exhibit "A".

The BLM inspectors have approved a location for the test well as 1433 FSL and 1459 FEL of Section 26, T-23-S, R-25-E, as shown on the attached plat. No legal locations within the S/2 of Section 26 would be approved because of topographical conditions.

We are requesting the OCD, State of New Mexico for an administrative approval of this unorthodox location and we request you to execute the attached Waiver and return in the enclosed envelop.

Your immediate attention will be appreciated.

Yours very truly,
Bill Seltzer

BS/kp

Atch: Waiver

WAIVER

The undersigned party has no objection to Collins & Ware, Inc.'s application to drill a 12,200' Morrow Test at an unorthodox location in Eddy County, New Mexico, to-wit:

1433 FSL and 1459 FEL of Section 26, T-23-S, R-25-E, Eddy County, New Mexico

YATES PETROLEUM CORPORATION

By:			
Printed	Name:		
Title:		_	
Date:			

23

+

S

	TC	WNS	HIF	2:	35	ou	th		RAN	GE	25	E	L 5 7	4		NM	PM								
	197	1 700	の変				- 1/2 - 1/2 - 1/2	· W	· P	月腾	囊	體	讀								()機		灣		1000
		- B	1	d)	1 3 m			源		in the second	*	東京 1	で電視												
		e		14°5 14'5 14'5	5.je '' :		د ا کو به فروان آ	注輸	響	Si di		藝						V							
				4.4	مهر الهوار معار	pil 3	- 22 55 g ²	漂	瓣				·模									標			•
		95.	3		, 84. 200	S. C.	3.			· Age	. *		遊								權			- 100 A	
	X	28	7 <u>-</u>	1 05 4 05	(1) (1) (1)		۱ 🖺		鬱	· · · · · · · · · · · · · · · · · · ·			靈	- 1	0 —			- 1	l 1 –			。 一 1	2		
		19 19 19 19	y ism	i in			· ·						75 A				,				香香	- 100	i iligili		
	1.5	14.00	¥9	1 3 A		4.19K	差。																		
	- 5	1 (P)	i Age	4	3		*		柳				- 100												,
	440	-1		う機能	樂	-1	7		23.33	-1	6 -			-1	5 -			- 1	4 –			-1	3—		
								12.00															·特殊 不理	5 A 2	3
	- 1	(4) (4) (4)	7 . A.				: 續	Till Single		饕		30									- Wa	40			
	- 5			# (A)	486		, 33 1.20						•	P P S										多沙 斯	
		-1	9 –			-2	0			– 2	1—		響響		2	Company Company		- 2	3=	14 M	· 黎	-2	4 —	1. 海豚	# (1) # 2
	- <u>新</u>	O S Re-											il.	是被			機								٠,٠
		100			響響		を必要 と必要		4."		事の機能	機						が選が	是 計劃 計劃			できる。		07/88%。 (17/88%)	
产的数		強	海縣 法	1 14 h							響	機能	一樓					198		150					
	# # # # # # # # # # # # # # # # # # #	 −3	0 –		が	- 2	9 –			-2	8 –			_2	7-			-2	6-			- 2	5 –		
	284 . 23	1 高			海海			海鄉						(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)					1.48	***		が報			; *:
	37			1.7	.,4		- 100 1000					疆	1	/		F 1250				ė A	- W				
			NE 1	139	2					2.5 2.5 2.5			7		220		1 機					藏			
	\vdash	- 3	1-			− .3	2 –			— 3	3 -		7		4-			3	5 -			—3	6-		
					* *	-1.2	7 A. 4			, H	AL.		/		1				- Get		海	,18 Ph		1	
	/p. 1/2.	<u></u>	j.,	1				Mar Mar				k in the		ES.	No.		1480	AL.							
	$\overline{\mathcal{D}}_{\epsilon}$	250		pt	102	. l	0/2	S	ec.	34	CK	2-5	2	5 2	. 9	-/-	76)				かが		4 24	がない
				f -							100 Jan 1	- <u>-</u>	0.97 () 3			2621.16	os era n	d'in mili	The said of	198.5Yest7	e Barre	at the same	A 3.2	N 15	435

Descrip	tion: W/2	Sec 34 (R-5252	9-1-76		
		4. 性情,		and the state of		(有)是1940(3)
Sp. Service Control	The state of the s			一个的人		
		talki en kirki talisi				
Mark 19 Martin 19	7.数机制物	Control of the Contro	The second			
ta to patro substituti	·····································				THE BOOK OF STREET	
			Hilliam			
				middle Fill	第一种地位	
		有工程的			CAN THE SERVICE	性學字編的特
				a him house		
•		The state of the s				A Property of the Parket
		1. 通過工作時			1. 温度量温度	

...

