

STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT OIL CONSERVATION DIVISION



1935 - 198

STATE LAND OFFICE BUILDING

SANTA FE. NEW MEXICO 87501 (505) 827-5800

POST OFFICE BOX 2088

December 10, 1985

APPLICATION OF LYNX PETROLEUM CONSULTANTS INC.
TO EXPAND ITS WATERFLOOD PROJECT IN THE
MALJAMAR GRAYBURG POOL IN LEA COUNTY,
NEW MEXICO.

ORDER No. WFX-554

ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Order No. R-3155, Lynk Petroleum Consultants, Inc. has made application to the Division on September 30, 1985 for permission to expand its Northeast Maljamar Waterflood Project in the Maljamar Grayburg Pool in Lea County, New Mexico.

NOW, on this 9th day of December, 1985, the Division Director finds:

- 1. That application has been filed in due form.
- 2. That satisfactory information has been provided that all offset operators have been duly notified of the application.
- 3. That no objection has been received within the waiting period as prescribed by Rule 701B.
- 4. That the proposed injection well is ϵ ligible for conversion to water injection under the terms of Rule 701.
- 5. That the proposed expansion of the above referenced waterflood project will not cause waste nor impair correlative rights.
 - 6. That the application should be approved.

IT IS THEREFORE ORDERED:

That the applicant, Lynx Petroleum Consultants Inc., be and the same is hereby authorized to inject water into the Grayburg formation through plastic-lined tubing set in a packer at approximately 3900 feet in the following described well for purposes of secondary recovery to wit:

State "BD" No. 2 well 2310' FNL and 2310' FEL of Section 7, T-17-S, R-33-E, Lea County, New Mexico

IT IS FURTHER ORDERED:

That the operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

That the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing, or packer.

That the injection well or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 838 psi.

That the Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Grayburg formation. That such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

That the operator shall notify the supervisor of the Division's Hobbs District Office before injection is commenced through said well.

That the operator shall immediately notify the Supervisor of the Division's Hobbs District Office of the failure of the tubing, casing, or packer in said well or the leakage of water from or around said well and shall take such steps as may be timely or necessary to correct such failure or leakage.

That the subject well shall be governed by all provisions of Division Order No. R-3155 and Rules 702, 703, 704, 705, and 706 not inconsistent herewith.

DONE at Santa Fe, New Mexico, on the day and year hereinabove designated.

STATE OF NEW MEXICO OIL CONSERVATION DIVISION

R. L. STAMETS,

Director

SEAL