

SCHLUMBERGER**SONIC LOG**SCHLUMBERGER WELL SURVEYING CORPORATION
Houston, Texas

COUNTY <u>ROOSEVELT</u> FIELD or LOCATION <u>MILNESAND</u> WELL <u>NEW MEXICO FEDERAL</u> F # <u>14</u> COMPANY <u>SUNRAY DX OIL COMPANY</u>	COMPANY <u>SUNRAY DX OIL</u> <u>MILNESAND UNIT #514</u> COMPANY	Other Surveys <u>LL, MLL</u>
	WELL <u>NEW MEXICO FEDERAL</u> <u>F # 14</u>	Location of Well <u>1980' FROM S/L</u> <u>1980' FROM E/L</u> <u>Correct</u> <u>M.dl.</u>
	FIELD <u>MILNESAND</u>	
	LOCATION <u>SEC. 24-8S 34E</u>	
	COUNTY <u>ROOSEVELT</u>	Elevation: K.B.: <u>4242</u> D.F.: <u>4241</u> or G.L.: <u>4232</u>
STATE <u>NEW MEXICO</u>		

Log Depths Measured From <u>KB</u> <u>10.4</u> Ft. above <u>GL</u>			
RUN No.	<u>ONE</u>		
Date	<u>11-23-62</u>		
First Reading	<u>4746</u>		
Last Reading	<u>0</u>		
Feet Measured	<u>4746</u>		
Csg. Schlum.			
Csg. Driller	<u>357</u>		
Depth Reached	<u>4752</u>		
Bottom Driller	<u>4750</u>		
Mud Nat.	<u>SALT GEL, STARCH, OIL</u>		
Dens. Visc.	<u>10.4</u> <u>38</u>		
Mud Resist.	<u>.068</u> @ <u>65</u> °F	@ °F	@ °F
" Res. BHT	<u>.052</u> @ <u>90</u> °F	@ °F	@ °F
" pH	- @ °F	@ °F	@ °F
" Wtr. Loss	<u>12.8</u> CC 30 min	CC 30 min	CC 30 min
" Rmf (M)	<u>.047</u> @ <u>65</u> °F	@ °F	@ °F
Bit Size	<u>7 7/8"</u>		
Spacing:			
T <u>3</u> R <u>1</u> R ₂	<u>SURE</u> To <u>4746</u>	To	To
T <u> </u> R <u> </u> R ₂	To	To	To
Opr. Rig Time	<u>3 HOURS</u>		
Truck No.	<u>3701-HOBBS</u>		

FOLD HERE

SPEED 30/60 FPM
400 TC 271
82.5 800 SENS.
450 82.5
70 450
82.5 800 SENS.