



INTER-OFFICE CORRESPONDENCE / SUBJECT:

TELECOPY COVER SHEET

DATE: DEC 2, 1993PANAFAX UF-620
(915) 368-1554TO: BEN STONE NMOCFROM: JIM STEVENS - PHILLIPS4

PAGES IN ADDITION TO THIS COVER SHEET.

IF THERE ARE ANY PROBLEMS WITH THIS TRANSMISSION, PLEASE CALL


(915)

HUMBLE NO. 22 IS EXXON STATE K #22 WHICH IS P.A.'s
HUMBLE NO. 12 IS EVASSAU 3202-012 ACTIVE PRODUCER
PHILLIPS NO. 8 UL "G" IS EVASSAU 3202-008 ACTIVE INJECTION
PHILLIPS NO. 8 UL "K" IS EVASSAU 3229-008 ACTIVE PRODUCER

CALL IF YOU HAVE ANY QUESTIONS 915-368-1376
I'LL BE AWAY DEER HUNTING NEXT WEEK, SO IF YOU HAVE
ANY QUESTIONS CALL ROGER BECKER AT 915-368-1550

STATE K NO. 22
API# 3002520713
(VGEU 02-05)

Humble No. 22



KB ELEV: 3959'
PBTD: 6175'
TD: 6210'

WELL SERV: APPROVAL - NON-AVE
 PHILLIPS PETROLEUM COMPANY--PREMIAN BASIN REGION

REBO 3972

CHFD 12 (ASSUMED)

GLO 3980

AREA: NORTH

SUBAREA: BUCKEYE

Date: 02/05/91

LEASE & WELL NO.: RYGSAR 3201-012

LEGAL DESCRIPTION: 1975 FSL & 1980 FSL SEC 32-T17S-R35E

LEA COUNTY, NEW MEXICO

FIELD: EAST VACUUM

STATUS: ACTIVE PRODUCER

BOPD: 19 BHPD: 70 MCFD: 20

TGB: 4.577' of 2-7/8" OD, 6.5 #/ft, Gr. J-55

PACKER: NA

PKR TYPE: NA

STIMULATION HISTORY:

INTERVAL	DATE	TYPE	GALLONS	MP	ISDP	IR	TURBULARS
1. 4150-4650	07-71	ACID	2500	1200	?	?	?
2.							
3.							
4.							

HOLE/CASING CONDITION: UNKNOWN

WORKOVER PROPOSAL: CLEAN OUT AND STIMULATE WELL. RETURN TO OPERATION.

RECOMMENDED PROCEDURE: SEE ATTACHED.

COMPLETED: 01-40

BOP FLANGE CONNECTION: 8-5/8" BRD ?

CASING: 10-3/4" 40.5# SET W/ 150 SK @ 244' EST TOC: SURF

7-5/8" 26.4# SET W/ 400 SK @ 1536' EST TOC: SURF

5-1/2" 17# SET W/ 250 SK @ 4150' EST TOC: 418'

PROJECT ECONOMICS:

\$ 15 PER BO

10 BOPD MCFPD

AARR 205 %

PAYOUT .7 YRS

MYR 2.4 TIMES

NPV @ 13% 7.8(M\$)

PI: 2.1

ECONOMIC LIFE 2 YRS

CASE NAME SNOW/3202012

EST. COMPL. DATE 03/91

FORM 452 COST ESTIMATE ATTACHED

CHECKED BY:

RESV. ENGR.: L.A. SUGG

PROD. ENGR.: K.E. SNOW

APPROVED:

PPCO: W.I. 29.457

R.I. 25.636

CHARGE TO

GROSS

NET

EXPENSE

60-2502

\$ 23,257 \$ 6,851

INVESTMENT

-

\$ 0 \$ 0

TOTAL

60-2502

\$ 23,257 \$ 6,851

CENTRAL FILES

D.J. FISHER

R.D. DUNHAM

S.D. MCCOY

J.C. FONTENOT

K.E. SNOW

D.A. BROWN

W.J. MUELLER

L.A. SUGG

M.V. NAVARRETTA

J. KUCHINSKI

L.M. SANDERS

D.S. FAUER

4-3/4" OPEN HOLE.

TD: 4650'

Record 36-91
 269

RKB @ 3971
CHF @
GL @ 3961

Category Code: ONE Date DECEMBER 18, 1992
Area NORTH Subarea EVGSAU
Lease & Well No. EVGSAU 3229-008
Legal Description 1300' FSL & 2400' FWL, SEC 32, T17S, R35E
LEA COUNTY State: NEW MEXICO
Field EAST VACUUM
Status: WAG INJ SHUT-IN MA BOPD 400 BOPD NA MCFD
Tbg: 140 JTS of 2-7/8" OD, 6.5 #/ft, Gr. J-55 IPC
4250' of " OD, #/ft, Gr.
Packer: 4250' Packer Type: BAKER LOC-SET
Date Drilled/Completed: APR 1980/JUL 1980 // WATER INJ OCT 1985
Hole/Casing-Condition: CASING INSP LOG RUN IN 1988 & 1991. BAD BELOW 4270'
Stimulation History: 1980 - 29,500 GALS 15% HCl IN 5 STAGES W/130 BALLS.
1991 - 10,000 GALS 15% CHIC HCl W/11000# SALT BLOCK.

WELLHEAD DESCRIPTION:

PROPOSAL: PULL TUBING TO LOCATE TBG LEAK. CLEAN-OUT WELL AND ACIDIZE TO
IMPROVE INJECTION RATE. RETURN BACK TO INJECTION.

JUSTIFICATION:

THIS WELL HAS DEVELOPED ANNULUS PRESSURE AND HAS BEEN SHUT-IN.
THEREFORE THE WELL NEEDS TO BE PULLED TO REPAIR THE LEAK. SINCE
THE WELL IS ONLY TAKING 400 BOPD, WHILE THE DESIRED RATE IS 1100
BOPD, AN ACID JOB NEEDS TO BE DONE TO IMPROVE INJECTIVITY.

THIS WORK IS EASILY JUSTIFIED AS THE WELL IS SURROUNDED BY WELLS
WHICH PRODUCE 1144 BOPD. OF THIS, 375 BOPD IS ALLOCATABLE TO THIS
PATTERN AT THE ESTIMATED EXPENDITURE OF \$24,000, THE WELL NEEDS
TO ACCOUNT FOR ONLY 30 BOPD TO GIVE AN AARR OF 500+%.

8-5/8" 24# K-55 @ 353'
TOC @ SURFACE

BAKER LOC-SET PKR @ 4250'

PERFORATIONS:

4330' - 4342'	12'	12 HOLES
4345' - 4362'	17'	13 HOLES
4364' - 4368'	4'	4 HOLES
4372' - 4375'	3'	3 HOLES
4380' - 4397'	17'	17 HOLES
4402' - 4410'	8'	8 HOLES
4422' - 4424'	2'	2 HOLES
4442' - 4455'	13'	13 HOLES
4460' - 4462'	2'	2 HOLES
4466' - 4478'	12'	12 HOLES
4482' - 4488'	6'	6 HOLES
4500' - 4504'	4'	4 HOLES
4511' - 4519'	8'	8 HOLES
4524' - 4530'	6'	6 HOLES
4533' - 4538'	5'	5 HOLES
4567' - 4569'	2'	2 HOLES
4572' - 4576'	4'	4 HOLES
4580' - 4588'	8'	8 HOLES
4591' - 4593'	2'	2 HOLES
4597' - 4602'	5'	5 HOLES
4610' - 4615'	5'	5 HOLES
4617' - 4621'	4'	4 HOLES
4625' - 4630'	5'	5 HOLES
4644' - 4646'	2'	2 HOLES
4640' - 4651'	11'	8 HOLES

TOTAL 154' 154 HOLES

5-1/2" 14# K-55 @ 4800'
TOC @ SURFACE (1400 SXs)

PBTD= 4750'
TD= 4800'

Checked by:

Prod. Engr. R. L. Becker

Approved 12/18/92

PROJECT ECONOMICS @ \$
BOPD MCFD
AARR 500 %
PAYOUT YRS.
NTER TIMES
NPV @ 13%
NPVR @ 13%
ECONOMIC LIFE 3 YRS.
EST. COMPL. DATE DEC 92
PPCO: W.I. 29.45684 %
R.I. 25.77456 %

Copies: R. L. Becker
(1) Central Files
S. H. Oden (3)
L. M. Sanders
M. L. Moore
D. R. Wier
(r) L. D. Hallenbeck
S. D. McCoy
(r) K. E. Snow
R. W. Chambers
L. S. Malone

CHARGE TO	GROSS COST	NET COST
EXPENSE AFE 63-2502	\$ 24,800	\$ 7,305
INVESTMENT AFE	\$	\$
TOTAL	\$ 24,800	\$ 7,305

SWD/INJECTION WELL DATA SHEET

RKB @ 3963.3
CHF @ 11.7
GL 3951.6

Date 08-20-91

District WORTH Subdistrict EVGSAU
Lease & Well No. EVGSAU #3202-W008 API No.: 30-025-26400
Legal Description 2630' FNL. 1468' FEL. SEC. 32.
T-17-S. R-35-E. LEA COUNTY State: NEW MEXICO

Field: VACUUM GB/SA Formation: GB/SA
Well Classification: INJECTION Status: ACTIVE

Average Injection Volume: 1016 BVPD 2379 MCFD

Normal H2O Inj. Pressure: 746 psi Authorized H2O Inj. Pressure: 1350 psi
NORMAL CO2 INJ. PRESSURE: 807 psi Authorized CO2 Inj. Pressure: 1800 psi
Permitted Injection Interval: 4371' to 4634'
Completed Injection Interval: 4366' to 4610'

Date Well Drilled: 10-22-79 Date Converted to Inj/SWD: 06-11-80

CBL Run? Yes: X No: Is it available? Yes: X No:

Temp Survey Run? Yes: No: X Is it available? Yes: No:

8 5/8" 24#, K-55 Csg @356'
TOC @ SURFACE

Injection well pressure measurement method: GAUGE
Frequency of pressure measurement: WEEKLY - MONTHLY

Does well have any plugging tendency? Yes: X No:
If so, how often? FIVE YEARS

Date of last HS or Mechanical Integrity Test: 08-27-90
Required Test Frequency:

Has well ever failed an HS or Mechanical Integrity Test? Yes: No: X
If so:

When?
Why?

How was it corrected?

Does well penetrate any usable water source? Yes: X No:
If yes, then:

Name of usable water source: DEALLALA/SANTA ROSA
Depth to top of the source: 0 Feet
Depth to bottom of source: 1530 Feet

2-7/8" J-55 IPC Tbg @ 4343'

BAKER LOC-SET Pk+ @ 4343'

Top of GB/SA @4042'
Perfs: 4366'-4610'
94'-94 SHOTS

5-1/2" 14#, K-55Csg @4800'
TOC @ SURFACE

TD: 4800'
PBD: 4748'

Checked by:
Prod. Engr.
Resv. Engr.

