of the early r submittal.

### OIL CONSERVATION DIVISION

POST OFFICE BOX 2088
STATE LAND OFFICE BUILDING
OOKS WE WAS A STARA

38

FORM C-108 Revised 7-1-81

_	Purpose: Secondary Recovery X Pressure Maintenance Disposal Storage					
1.	Purpose: X Secondary Recovery X Pressure Maintenance Disposal Storage Application qualifies for administrative approval? X yesno					
II.	Operator: Devon Energy Operating Corporation					
	Address: 20 N. Broadway, Suite 1500, Oklahoma City, OK 73102-8260					
	Contact party: Randy Jackson Phone: (405) 552-4560					
III.	Well data: Complete the data required on the reverse side of this form for each well proposed for injection. Additional sheets may be attached if necessary.					
IV.	Is this an expansion of an existing project? $\overline{x}$ yes $\overline{x}$ no If yes, give the Division order number authorizing the project $\overline{x}$ .					
٧.	Attach a map that identifies all wells and leases within two miles of any proposed injection well with a one-half mile radius circle drawn around each proposed injection well. This circle identifies the well's area of review. Refer to Attachment V					
* VI.	Attach a tabulation of data on all wells of public record within the area of review which penetrate the proposed injection zone. Such data shall include a description of each well's type, construction, date drilled, location, depth, record of completion, and a schematic of any plugged well illustrating all plugging detail. Refer to Attachment V.					
VII.	Attach data on the proposed operation, including: Refer to Attachment VII					
	<ol> <li>Proposed average and maximum daily rate and volume of fluids to be injected;</li> <li>Whether the system is open or closed;</li> <li>Proposed average and maximum injection pressure;</li> <li>Sources and an appropriate analysis of injection fluid and compatibility with the receiving formation if other than reinjected produced water; and</li> <li>If injection is for disposal purposes into a zone not productive of oil or gas at or within one mile of the proposed well, attach a chemical analysis of</li> </ol>					
	the disposal zone formation water (may be measured or inferred from existing literature, studies, nearby wells, etc.).					
*VIII.	Attach appropriate geological data on the injection zone including appropriate lithologic detail, geological name, thickness, and depth. Give the geologic name, and depth to bottom of all underground sources of drinking water (aquifers containing waters with total dissolved solids concentrations of 10,000 mg/l or less) overlying the proposed injection zone as well as any such source known to be immediately underlying the injection interval. Refer to Attachment VIII					
IX.	Describe the proposed stimulation program, if any. We anticipate acidizing the existing					
* X.	perfs 3364'-3910' with 15% NEFE prior to the start of injection. Attach appropriate logging and test data on the well. (If well logs have been filed with the Division they need not be resubmitted.) Copies of current logs are on file.					
* XI.	Attach a chemical analysis of fresh water from two or more fresh water wells (if available and producing) within one mile of any injection or disposal well showing location of wells and dates samples were taken. There are no known producing fresh wate wells within one mile of the proposed injection well.					
XII.	Applicants for disposal wells must make an affirmative statement that they have examined available geologic and engineering data and find no evidence of open faults or any other hydrologic connection between the disposal zone and any underground source of drinking water. Refer to Attachment XII					
XIII.	Applicants must complete the "Proof of Notice" section on the reverse side of this form.					
xiv.	Refer to Attachment XIV.					
	I hereby certify that the information submitted with this application is true and correct to the best of my knowledge and belief.					
	Name: Randy Jackson Title District Engineer					
	Signature: Rang Jackson Date: 11/18/94					

### III. WELL DATA

- A. The following well data must be submitted for each injection well covered by this application. The data must be both in tabular and schematic form and shall include:
  - (1) Lease name; Well No.; location by Section, Township, and Range; and footage location within the section.
  - (2) Each casing string used with its size, setting depth, sacks of cement used, hole size, top of cement, and how such top was determined.
  - (3) A description of the tubing to be used including its size, lining material, and setting depth.
  - (4) The name, model, and setting depth of the packer used or a description of any other seal system or assembly used.

Division District offices have supplies of Well Data Sheets which may be used or which may be used as models for this purpose. Applicants for several identical wells may submit a "typical data sheet" rather than submitting the data for each well.

- B. The following must be submitted for each injection well covered by this application. All items must be addressed for the initial well. Responses for additional wells need be shown only when different. Information shown on schematics need not be repeated.
  - (1) The name of the injection formation and, if applicable, the field or pool name.
  - (2) The injection interval and whether it is perforated or open-hole.
  - (3) State if the well was drilled for injection or, if not, the original purpose of the well.
  - (4) Give the depths of any other perforated intervals and detail on the sacks of cement or bridge plugs used to seal off such perforations.
  - (5) Give the depth to and name of the next higher and next lower oil or gas zone in the area of the well, if any.

### XIV. PROOF OF NOTICE

All applicants must furnish proof that a copy of the application has been furnished, by certified or registered mail, to the owner of the surface of the land on which the well is to be located and to each leasehold operator within one-half mile of the well location.

Where an application is subject to administrative approval, a proof of publication must be submitted. Such proof shall consist of a copy of the legal advertisement which was published in the county in which the well is located. The contents of such advertisement must include:

- (1) The name, address, phone number, and contact party for the applicant;
- (2) the intended purpose of the injection well; with the exact location of single wells or the section, township, and range location of multiple wells;
- (3) the formation name and depth with expected maximum injection rates and pressures; and
- (4) a notation that interested parties must file objections or requests for hearing with the Oil Conservation Division, P. O. Box 2088, Santa Fe, New Mexico 87501 within 15 days.
  - NO ACTION WILL BE TAKEN ON THE APPLICATION UNTIL PROPER PROOF OF NOTICE HAS BEEN SUBMITTED.

NOTICE: Surface owners or offset operators must file any objections or requests for hearing of administrative applications within 15 days from the date this application was mailed to them.

### **ATTACHMENT III (tabular)**

### **WELL DATA**

- A. (1) H. E. West "B" #38 2085' FNL & 1980' FWL Section 10-T17S-R31E Eddy County, NM
  - (2) <u>Casing Data</u>: Also see Attachment III (schematic).

    <u>Surface</u>: 8 5/8" set @ 596'in a 12 1/4" hole, cemented with 400 sx. Circulated.

    <u>Production</u>: 5 1/2" set @ 3960'in a 7 7/8" hole, cmt'd w/1300 sx. Est. TOC @ surface. Circ'd.

    <u>Liners</u>: None.
  - (3) Injection Tubing: 2 3/8", 4.7#, J-55, 8rd EUE plastic coated set at 3315'.
  - (4) Packer: Baker, tension (or equivalent) set @ 3178' in tension.
- B. (1) <u>Injection Formation</u>: The injection formation will be the Grayburg San Andres from 3228' to 4090'.
  - (2) <u>Injection Interval</u>: The injection interval is to be from perforations @ 3228' to 4090'.
  - (3) Original Purpose of Well: The well was originally drilled, completed and tested as a producer from perforations 3364'-3910' overall (120 holes).
  - (4) Added Perforated Intervals: Will deepen well from 3960' to 4090', 6 1/2" hole. Will inject thru perfs and open hole.
  - (5) <u>Higher/Lower Oil Zones</u>: The top of the Seven Rivers is at +/- 2198' and there is no known lower oil zone.

Schematic: See Attachment III (schematic).



## **WELLBORE SCHEMATIC**

WELL: H. E. West "B" No.38 LOCATION: 2085 FN4 & 1980 FWL 10-175-31 E Eddy Co., N.M.

Present

8 1/8" c 596'w/ 400 sx. circ. (121/4" Hole)

Treatments: 3364-3910'
Acidized W/ 7000 gals.
15% NEFE HCl.
Frac'd w/ 20,000 T-3
gelled water w/ 5800#
20-40 sand.

120 Holes btm. perf. 3910'


T.D. 3960' (71/8"hole)

51/2"@ 3960 w/ 1300 sx. circ.



## **WELLBORE SCHEMATIC**

WELL: H. E. West "B" No.38 LOCATION: 2085 FN4 > 1980 FW4 10-175-31E Eddy Co. IV.M.



85/8" @ 596'w/ 400 sx. circ. (121/4" Hole)

Treatments: 3364-3910'
Acidized w/ 7000 gals.
15% NEFE HCl.
Frac'd w/ 20,000 T-3
gelled water w/ 5800#
20-40 sand.

-23/8" plastic lined tbg.

Baker Loc Set pkr. @ 3115'IN tension

120 Holes btm. perf. 3910'

PBTD 3937'

T.D. 3960 (7% "hole)

5/2"e 3960 w/ 1300 sx. circ.

Deepen from 3960 to 4090'
6/4" Open hove

# LARGE FORMAT EXHIBIT HAS BEEN REMOVED AND IS LOCATED IN THE NEXT FILE

# ATTACHMENT VI

8 5/8" @ 602' w/400 sx. Circ. 5 1/2" @ 4008' w/1250 sx. Circ. Completed as a producer from Grayburg San Andres thru perfs 3301'-3943' (169 holes).	TD 4008' PBTD 3935'	Producing Oil	2/15/89	1/2/89	660' FSL & 2020' FWL Sec. 10-17S-31E	H. E. West "B" #41
8 5/8" @ 641' w/400 sx. Circ to surface. 5 1/2" @ 3895' w/1250 sx. Circ to surface. Completed in the Grayburg San Andres as a producer from perfs 3398'-3524', 3546'-3599', and 3614'-3791'.	TD 4001'	Producing Oil	2/89		2105' FNL & 660' FEL Sec. 10-17S-31E	H. E. West "B" #42
8 5/8" @ 541' w/400 sx. Circ to surface. 5 1/2" @ 3883 w/1300 sx. Circ to surface. Completed as a producer from Grayburg San Andres: Perfs: 3199'-3821' (166 holes). Acidized w/6000 gals acid Frac'd w/23,000 gals 30# gelled water + 15,000# 20/40 sand.	TD 3883' PBTD 3861	Producing Oil	11/10/88	10/15/88	1980' FNL & 660' FEL Sec. 9-17S-31E	H. E. West "B" #36
8 5/8" @ 582' w/450 sx. Circulated. 5 1/2" @ 3954' w/1600 sx. Circulated. Completed in the Grayburg San Andres from perforations 3314'-3754' (62 holes).	TD 3954°	Producing Oil	9/27/88	8/13/88	1980' FSL & 660' FWL Sec. 10-17S-31E	H. E. West "B" #32
Surface: 10 3/4" @ 785' w/100 sx. Intermediate: 5 1/2" @ 3501' w/100 sx. Liner: 4" from 3323' to 3953' w/ 65 sx. Perforated: 3373'-3941' (39 shots). Acidized w/13,000 gals acid. Frac'd w/25,000 gals x-linked gel and 9200# 20/40 sand.	TD 3955' PBTD 3954'	Injection	3/13/64 Deepened in 8/89	2/28/64	660° FNL & 1980° FWL Sec. 10-17S-31E	H. E. West "B" #19
COMPLETION RECORD	<u> ДЕРТН/РВТД</u>	TYPE OF WELL	COMPLETION DATE	SPUD DATE	LOCATION	WELL NAME

# ATTACHMENT VI

				-
H. E. West "B" #50	H. E. West "B" #51	H. E. West "B" #52	H. E. West "B" #40	WELL NAME
50' FSL & 1400 FWL Sec. 3-17S-31E	1337 FNL & 1363 FWL Sec. 10-17S-31E	1250' FNL & 100' FWL Sec. 10-17S-31E	560' FNL & 660' FWL Sec. 10-17S-31E	LOCATION
3/4/93	3/16/93	3/21/93	12/22/88	SPUD DATE
7/21/93	9/1/93	5/17/93	2/2/89	COMPLETION DATE
Producing Oil	Producing Oil	Producing Oil	Producing Oil	TYPE OF WELL
TD 4356' PBTD 4285'	TD 4372' PBTD 4321'	TD 4335' PBTD 4284'	TD 4021' PBTD 3956'	DEPTH/PBTD
13 3/8" @ 576' w/250 sx. Circ to surface. 5 1/2" @ 4356' w/1900 sx. Circ. to surface. Completed in the Grayburg San Andres as a producer thru perfs 3300'-4052' (286 holes).	8 5/8" @ 575' w/250 sx. Circ to surface. 5 1/2" @ 4372' w/1300 sx. Circ to surface. Completed in the Grayburg San Andres as a producer thru perfs 3308'-3398' overall (118 holes).	8 5/8" @ 626' w/500 sx. Circ. to surface. 5 1/2" @ 4335' w/1200 sx. Circ. to surface. Completed in the Grayburg San Andres as a producer thru perfs 4080'-4198' overall (145 holes).	8 5/8" @ 603' w/350 sx. Circ to surface. 5 1/2" @ 4021' w/1250 sx. Circ to surface. The well was completed as a producer from the Grayburg San Andres thru perfs 3345'-3941' (170 holes). Acidized w/11,000 gals acid. Frac'd w/36,000 gals x-linked gelled water and 76,000# 20/40 sand.	COMPLETION RECORD

# ATTACHMENT VI

H. E. West "B" #13	H E. West "B" #14	H. E. West "B" #15	H. E. Wcst "B" #1	WELL NAME
1980' FNL & 660' FWL Sec. 10-17S-31E	1980' FSL & 1980' FWL Sec. 10-17S-31E	1980' FNL & 1980' FEL Sec. 10-17S-31E	660' FNL & 1980' FEL Sec. 10-17S-31E	LOCATION
	11/9/57	4/14/89	AA	SPUD DATE
10/57	1/12/58	8/26/89	9/29/89	COMPLETION DATE
Injection	Injection	Producing Oil	Producting Oil	TYPE OF WELL
TD 3900' PBTD 3720' CIBP	TD 3950' PBTD 3932'	TD 3952' PBTD 3952'	TD 5515' PBTD 3950'	DEPTH/PBTD
10 3/4" @ 739' w/100 sx.  7" @ 3525' w/100 sx.  5" liner set from 3094'-3897' w/150 sx cmt.  Completed in the Grayburg San Andres as a producer from perforations 3318'-26' and 3356'-74'. The well was deepened to 3900' and a 5" liner set. The well was perf'd 3737'-3864', 3568'-3696' and 3312'-3559'. A cast iron bridge plug was set @ 3720' and the well converted to water injection.	8 5/8" @ 762' w/100 sx cmt.  7" @ 3563' w/100 sx cmt.  Initial completion was open hole as an oil producer.  Deepened from original TD of 3632 to 3950'. Ran 5" liner from 3255' to 3950' and cemented w/170 sx. Perf'd 3317'-3900' (89 holes) and acidized w/21,000 gals acid. Well converted to injection.	10 3/4" @ 780' w/200 sx. TOC @ 440' (calc.). 5 1/2" @ 3728' w/100 sx. TOC @ 3290' (CBL). Completed from perfs: 3372'-3540' overall. Well was deepened to 3952'. Ran 4" liner from 3119'-3952', cmt w/50 sx. The well was perf'd 3368'-3916' & converted to injection.	8 5/8" @ 810' w/400 sx cmt. 4 1/2" @ 5515' w/850 sx cmt. Well completed as a producer from Grayburg San Andres thru perforations 3380'-3754' & 3800'-3935'.	COMPLETION RECORD

### **ATTACHMENT VII**

### **PROPOSED OPERATION**

- 1. Average daily injection rate 500 BWPD. Maximum daily injection rate 600 BWPD.
- 2. Type of system closed.
- 3. Average injection pressure 1900 psi.

  Maximum injection pressure 2500 psi.
- 4. Source of injection water Produced water from the Keel West plus make up water from Keel West fresh water system.
- 5. N. A.

### **ATTACHMENT VIII**

### **GEOLOGY AND LITHOLOGY**

The proposed injection zone is in the Greyburg San Andres from 3364' to 3910'. The Greyburg formation consists primarily of quartz sand with cementation. The San Andres formation consists primarily of dolomite with intermingled stringers of quartz sand with dolomite cementation.

Surface formation is cretaceous and has no known source of drinking water. Also, there are no known sources of drinking water overlying or underlying the proposed injection zone.

### **ATTACHMENT XII**

Upon examination of the available geologic and engineering data, no evidence of open faults or any other hydrologic connection between the injection zone and any underground source of drinking water was found.

### ATTACHMENT XIV

### **PROOF OF NOTICE**

Devon Energy Operating Corporation (applicant) is the operator of all wells within the area of review. The Bureau of Land Management is the surface owner. They have been notified by BLM Sundry Notice.

### PROOF OF PUBLICATION

Proof of publication from the Carlsbad Current-Argus is enclosed.

## Affidavit of Publication

State of New Mexico,					
County of Eddy, ss.					
A 37 77					
Amy McKay, being first duly sworn, on oath says:					
being first dury sworm, on oath says.					
That she is Business Manager					
of the Carlsbad Current-Argus, a newspaper pub-					
lished daily at the City of Carlsbad, in said county					
of Eddy, state of New Mexico and of general paid					
circulation in said county; that the same is a duly					
qualified newspaper under the laws of the state wherein legal notices and advertisements may be					
published; that the printed notice attached hereto					
was published in the regular and entire edition of					
said newspaper and not in supplement thereof on					
the date as follows, to wit:					
November 15 , 1994					
,19					
, 19					
,19					
That the cost of publication is \$_25.70,					
and that payment thereof has been made and will					
be assessed as court costs.					
Umy/May					
Subscribed and swom to before me this					
11 A 1/11 / Oct					
16 15 day of 10/50 ember , 1994					
16 th day of November, 1994  Donne Crump					
My commission expires 8/01/98					
Notary Public					

Nº 16144

November 15, 1994

### Legal Advertisement

Notice is hereby given that Devon Energy Operating Corporation is applying to the New Mexico Oil Conservation Division to convert the following well to an injection well for secondary recovery purposes:

H.E. West "B" #38 2085' FNL & 1980' FWL Section 10-T17S-R31E Eddy County, NM

The intended purpose of this well is to inject produced water's into the Grayburg-San Andres formations to enhance oil production through secondary recovery. Maximum injection rates of 600 bwpd and a maximum pressure of 2500 psig are expected.

t interested parties must file objections or requests for hearing within 15 days to the following commission:

Oil Conservation Division P.O. Box 2088 Santa Fe, NM 87501

Randy Jackson District Engineer Devon Energy Operating Corporation 20 North Broadway, Suite 1500 Oklahoma City, OK (405) 552-4560

WEST B 36,38,40,44 +47	AAI package
SENDER:  Complete items 1 and/or 2 for additional services. Complete items 3, and 4s & b. Print your name and address on the reverse of this form so th return this card to you. Attach this form to the front of the mailpiece, or on the back does not permit. Write "Return Receipt Requested" on the mailpiece below the art	if space 1. Addressee's Address
The Return Receipt Fee will provide you the signature of the pers to and the date of delivery.	Z. LINESHICLEU DENVEIV
3. Article Addressed to:	4a. Article Number
	P 080 276 169
Bureau of Land Management P.O. Box 1778 Carlsbad, NM 88221-1778	4b. Service Type Registered Insured Certified COD Fances Mail Return Receipt for
Carlsbad, NM 88221-1778	Merchandise
<u></u>	7. Date of Delivery
5. Signature (Addressee)	Addresses is Address (Only if requested and fee is paid)
6. Signature (Agent)	į.
PS Form 3811, November 1990 + U.S. GPO: 1861-281	7-006 DOMESTIC RETURN RECEIPT
Postmark or Date WEST B 36, 38, 40  WEST B 44 + 47  AAI Packet	