

APPLICATION OF PHILLIPS PETROLEUM  
COMPANY TO EXPAND ITS EAST VACUUM  
GRAYBURG SAN ANDRES PRESSURE MAINTENANCE  
PROJECT IN THE VACUUM GRAYBURG SAN ANDRES  
POOL IN LEA COUNTY, NEW MEXICO

ORDER PMX NO. 93

ADMINISTRATIVE ORDER  
OF THE OIL CONSERVATION DIVISION

Under the provisions of Order No. R-5897 Phillips Petroleum Company has made application to the Division on September 15, 1980, for permission to expand its East Grayburg San Andres Pressure Maintenance Project in the Vacuum Grayburg San Andres Pool in Lea County, New Mexico.

NCW, on this 18th day of September, 1980, the Division Director finds:

1. That application has been filed in due form.
2. That the proposed injection well is eligible for conversion to water injection under the terms of Order No. R-5897.
3. That the proposed expansion of the above referenced pressure maintenance project will not cause waste nor impair correlative rights.
4. That the application should be approved.

IT IS THEREFORE ORDERED:

That the applicant, Phillips Petroleum Company, be and the same is hereby authorized to inject water into the San Andres formation through plastic-lined tubing set in a packer at approximately 4360 feet in the following described well for purposes of pressure maintenance, to wit:

East Vacuum Unit, Tract 2801, Well No. 015 in Unit O of Section 28, Township 17 South, Range 35 East, NMPM, Lea County, New Mexico, and through plastic lined tubing set in a packer at approximately 4775 feet in the following described well for purposes of pressure maintenance, to wit;

East Vacuum Unit, Tract 2801, Well No. 012 in Unit M of Section 28, Township 17 South, Range 35 East, NMPM, Lea County, New Mexico.

IT IS FURTHER ORDERED:

That the operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

That the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing, or packer.

That the injection well or system shall be equipped with a non-off valve or device which will limit the surface wellhead


pressure to a maximum of 865 pounds per square inch; provided however that the Division Director may administratively authorize a pressure limitation in excess of the above upon the operators establishing that such higher pressure will not result in fracturing of the confining strata.

That the operator shall notify the supervisor of the Division's Hobbs District Office before injection is commenced through said well;

That the operator shall immediately notify the Supervisor of the Division's Hobbs District Office of the failure of the tubing, casing, or packer in said well or the leakage of water from or around said well and shall take such steps as may be timely or necessary to correct such failure or leakage.

DONE at Santa Fe, New Mexico, on the day and year hereinabove designated.

STATE OF NEW MEXICO  
OIL CONSERVATION DIVISION

  
JOE D. RAMFY  
Division Director

SEAL