

ILLEGIBLE



MICRO-SEISMOGRAM[®] LOG-CASED HOLE

COMPANY Co. pass WELL No. 27 - 241 FIELD O.S. County Sea State N.Y.	COMPANY		COM - NY	
	WELL		BBB UN 27 - 241	
	FIELD		11	
	COUNTY		STATE NEW MEXICO	
Location		281 NW		Other Services:
Sec. 27M		Twp. 18-		Rge. 38-
Permanent Datum		Ground Level		Elev. 3616'
Log Measured From		K. B. - 8		Ft. Above Perm. Datum
Drilling Measured From		Kelly Bus. ing		Elev. K.B. 3644'
				D.F.
				G.L. 3620'
Run No.	- 000 -			
Date & Time Survey	1-25-8			
Date & Time Cementing				
Type Cementing Operation				
Depth Driller	4090		P.L.G.	
Depth Welex	4076			
Logged Interval	390		to 4068	
Casing Driller	5-1 2"		@ 4225	
Float Collar—D.V. Tool				
Squeeze Depth				
Amount & Type Cement				
Amount & Type Admix				
Type Fluid in Hole	Water			
Fluid Level	Full			
Salinity PPM Cl				
Weight lb/gal—Vis.				
Approx. Logged Cem. Top				
Calculated Cement Top	2620			
Max. Hole Temperature			°F	
Tool No.				
Spacing Recorded	4'			
Equipment—Location	2922		to S	
Recorded by	Welex			
Witnessed by	Mr. Jack Gray			

Fold Here

CASING RECORD

BORE HOLE RECORD

Schlumberger

BHC - SONIC

COMPANY: SHELL WESTERN E & P INC.

WELL: NORTH HOBBS UNIT #27-241

FIELD: NORTH HOBBS UNIT (G-SA)

COUNTY: LEA

STATE: NEW MEXICO

NATION: USA

LOCATION:

SEC: 27

TWP: 18-S

RGE: 38-E

PERMANENT DATUM: GL

ELEVATIONS-

ELEV. OF PERM. DATUM: 3637.0 F

KB:

LOG MEASURED FROM: DF

DF: 3643.0 F

6.0 F ABOVE PERM. DATUM

GL: 3637.0 F

DRLG. MEASURED FROM: DF

DATE: 13 JUL 87

RUN NO: TWO

DEPTH-DRILLER: 4350.0 F

DEPTH-LOGGER: 4345.0 F

BTM. LOG INTERVAL: 4350.0 F

TOP LOG INTERVAL: 4060.0 F

CASING-DRILLER: 4060.0 F

CASING-LOGGER: 4060.0 F

CASING: 7

WEIGHT:

BIT SIZE: 6 1/8

DEPTH: 4350.0 F