STATE OF NEW MEXICO



ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION

GAPREY CARRUTHERS
GOVERNOR

POST OFFICE BOX 2088 STATE LAND OFFICE BUILDING SANTA FE, NEW MEXICO 87504 (505) 827-5800

ORDER SWD-334

THE APPLICATION OF PARKER & PARSLEY PETROLEUM COMPANY

ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Rule 701(b), Parker and Parsley Petroleum Company made application to the New Mexico Oil Conservation Division on December 15, 1987, for permission to complete for salt water disposal its Flower Draw Unit Well No. 2 located in Unit G of Section 2, Township 26 South, Range 28 East, NMPM, Eddy County, New Mexico.

The Division Director finds:

- (I) That application has been duly filed under the provisions of Rule 701(C) of the Division Rules and Regulations;
- (2) That satisfactory information has been provided that all offset operators and surface owners have been duly notified; and
- (3) That the applicant has presented satisfactory evidence that all requirements prescribed in Rule 701(C) will be met.
- (4) That no objections have been received within the waiting period prescribed by said rule.

IT IS THEREFORE ORDERED:

That the applicant herein, Parker and Parsley Petroleum Company is hereby authorized to complete its Flower Draw Unit Well No. 2, located in Unit G of Section 2, Township 26 South, Range 28 East, NMPM, Eddy County, New Mexico, in such a manner as to permit the injection of salt water for disposal purposes into the Delaware formation at approximately 2550 feet to approximately 2890 feet through 2 3/8-inch plastic lined tubing set in a packer located at approximately 2500 feet.

IT IS FURTHER ORDERED:

That the operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

That the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing, or packer.

That prior to commencing injection operations into the well, the casing shall be pressure tested from the surface to the packer setting depth to assure the integrity of the casing.

That the injection well or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 510 psi.

That the Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Delaware formation.

That the operator shall notify the supervisor of the Artesia district office of the Division of the date and time of the installation of disposal equipment, and of the mechanical integrity test so that the same may be inspected and witnessed.

That the operator shall immediately notify the supervisor of the Division's Artesia district office of the failure of the tubing, casing, or packer, in said well or the leakage of water from or around said well and shall take such steps as may be timely and necessary to correct such failure or leakage.

PROVIDED FURTHER, That jurisdiction of this cause is hereby retained by the Division for such further order or orders as may seem necessary or convenient for the prevention of waste and/or protection of correlative rights; upon failure of applicant to comply with any requirement of this order after notice and hearing, the Division may terminate the authority hereby granted in the interest of conservation. That applicant shall submit monthly reports of the disposal operations in accordance with Rule 704 and II20 of the Division Rules and Regulations.

Approved at Santa Fe, New Mexico, on this 16th day of February, 1987.

STATE OF NEW MEXICO
OIL CONSERVATION DIVISION

WILLIAM J. LEMAY

Director