

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/4	12 1/2	130	110	HOWCO		
11"	8-5/8	3380	100	HOWCO		
7-3/4	---	6652			9.5 Vis. 60	hole full

#### PLUGS AND ADAPTERS

Heaving plug—Material Lane Wells Length 48" Depth Set 3370  
 Adapters—Material \_\_\_\_\_ Size 8-5/8

#### RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment \_\_\_\_\_

#### RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

#### TOOLS USED

Rotary tools were used from 0 feet to 6,652 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
 Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

#### PRODUCTION

Put to producing \_\_\_\_\_ 19\_\_\_\_\_  
 The production of the first 24 hours was \_\_\_\_\_ barrels of fluid of which \_\_\_\_\_ % was oil; \_\_\_\_\_ % emulsion; \_\_\_\_\_ % water; and \_\_\_\_\_ % sediment. Gravity, Be \_\_\_\_\_  
 If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_  
 Rock pressure, lbs. per sq. in. \_\_\_\_\_

#### EMPLOYEES

Jack Wisdom Driller Reece Williamson Driller  
Percy Collier Driller \_\_\_\_\_ Driller

#### FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 5

day of OCTOBER 1948

Jack E. O'Connell  
 Notary Public

My Commission Expires Sept. 9, 1951  
 My Commission expires \_\_\_\_\_

Albuquerque, N. M.

Place \_\_\_\_\_ Date \_\_\_\_\_  
 Name Tom Bolack

Position Superintendent

Representing F. H. Carpenter  
 Company or Operator.

Address Sour Lake, Texas