

Santa Fe, New Mexico

HOEBS OFFICE

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). **SUBMIT IN TRIPLICATE.**

AREA 610 ACRES
LOCATE WELL CORRECTLY

NORTH'S REALTY COMPANY, INC. Company or Operator Lease
Well No. in NWNE of Sec. T.

R. Fee _____, N. M. P. M., _____ ²³ Field, _____ ²² on _____ County.

Well 1E _____ feet south of the North line and _____ feet west of the East line of _____ Wildcat _____ Bearpaw _____

If State land the oil and gas lease is No. _____ Assignment No. _____

If patented land the owner is _____, Address _____

If Government land the permittee Worwins Realty Co., Address 815 So. Hill St. Los Angeles, Cal.

The Lessee is _____, Address _____

Drilling commenced _____ 19____ Drilling was completed _____ 19____

Name of drilling contractor _____ Address _____

Elmer Fisher 303 Cornell Avenue Albuquerque, New M.

Elevation above sea level at top of casing _____ feet.

The information given is to be kept confidential until _____ 19____

No. 1, from None to _____ No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 1230 to 1320 feet. Not Known

No. 2, from 1405 to 1460 feet.

No. 3, from _____ to _____ feet.

No. 4, from _____ to _____ feet.

CASING RECORD

[illegible]

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED

Formation shut off

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____

Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		None				

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to producing _____, 19 _____

The production of the first 24 hours was _____ barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

_____, Driller _____, Driller

_____, Driller _____, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 25th

day of February, 1946

W. W. Vaughan
Notary Public

My Commission expires Oct. 24, 1949

Place _____ Date _____
Name J. W. Bury
Position President
Representing Marino Realty Co.
Company or Operator.
Address 815-60-Hill St
N. Y. C.

FORMATION RECORD

00000001

FROM	TO	THICKNESS IN FEET	FORMATION
0	2	2	Top Soil
2	30	28	Gypsum & Caliche
30	200	170	Gray Soft Sand
200	240	40	Red Clay
240	245	5	Gypsum
245	300	55	Sand
245	300	55	Sand
300	425	125	Red Shale (Shells)
425	465	40	Gypsum (Hard)
465	550	85	Clay with Gypsum
550	600	50	Hard Gypsum
600	640	40	White Sand & Sand Rock
640	800	160	Gypsum & Clay
800	900	100	Red Yellow & white Shale
900	1025	125	Gypsum & Clay
1025	1100	75	Gypsum & Red Shale
1100	1140	40	Red Shale
1140	1200	60	Coarse Sand
1200	1210	10	Lime Shells
1210	1240	30	Red Shale
1240	1280	40	Gray Lime
1280	1320	40	Coarse Sand
1320	1360	40	Water Sand
1320	1360	40	Water Sand
1360	1390	30	Lime Shells
1390	1405	15	Red Shale
1405	1460	55	Fine Sand
1460	1475	15	Lime Shells
1475	1530	55	Coarse Sand & Gravel
1530	1580	50	Fine Soft Sand
1580	1640	60	Soft Sand
1640	1650	10	Lime Hard
1650	1690	30	Sand Soft
1690	1760	70	Soft Sand
1760	1770	10	Gray Shale
1770	1790	20	Black Sand
1790	1810	20	Brown Lime
1810	1820	10	Gray Sand
1820	1830	10	Gray Sand
1830	1840	10	Gray Sand
1840	1874	34	Red Sandy Shale
1874	1900	24	Red Sand
1900	1938	38	Gypsum Rock
1938	1984	46	Gray Coarse Sand
1984	2020	36	Gray Shale
2020	2063	43	Fine Gray Sand
2063	2074	11	Red Sticky Shale
2074	2130	56	Gypsum Rock
2130	2200	70	Gray Shale
2200	2213	13	Gray Shale
2213	2243	30	Lava Rock
2243	2270	27	Gray Shale
2270	2400	130	Gray Sand & Gravel
2400	2460	60	Fine Gray Sand
2460	2500	40	Red Sandy Shale
2500	2520	20	Gypsum Rock
2520	2570	50	Red Sandy Shale

2520
2570
2607
2613
2632
2655
2725
2750 TD

2570
2605
2613
2622
2655
2725
2750

10
35
0
12
23
70
55

Red Shale
Red Shale
Red Shale & Limestone
Coarse Gravel
Lava Flow
Dark Gray Shale
Red Shale Sandy
Red Shale - Hard Layers Sand