

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-55

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	N/A

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Wildcat	7. Unit Agreement Name- None
2. Name of Operator TransOcean Oil, Inc.	8. Farm or Lease Name State 2094
3. Address of Operator 1700 First City East Bldg., 1111 Fannin, Houston, Texas 77002	9. Well No. 1
4. Location of Well UNIT LETTER D, 330' FEET FROM THE North LINE AND 330' FEET FROM THE West LINE, SECTION 2 TOWNSHIP 2N RANGE 14W NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 7511' GL	12. County Catron

### Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Received verbal permission June 30, 1977 from New Mexico Conservation Comm. (Carl Ulvog) in Santa Fe to P & A well.

- Set cmt plug w/ 25 sx CI "H" @ 5200-5125' (Yeso) (8.8# mud)  
Set cmt plug w/ 25 sx CI "H" @ 4455-4380' (Glorietta) (8.8# mud)  
Set cmt plug w/ 25 sx CI "H" @ 4130-4060' (San Andres) (8.8# mud)  
Set cmt plug w/ 25 sx CI "H" @ 2805-2730' (Dakota) (8.8# mud)  
Set cmt plug w/ 25 sx CI "H" @ 565-490' (1/2 in, 1/2 out surf csg) (8.8# mud)  
Set cmt plug w/ 10 sx @ surf w/ Dry Hole Marker.
- A steel marker was placed 4' above ground level.
- Loc was cleared of all junk and pits were filled & loc leveled.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>C. S. Jones</u>	TITLE <u>Mgr, Western Drlg. Div.</u>	DATE <u>7/18/77</u>
APPROVED BY <u>Carl Ulvog</u>	TITLE <u>SENIOR PETROLEUM GEOLOGIST</u>	DATE <u>5/8/78</u>
CONDITIONS OF APPROVAL, IF ANY:		