

30.006.05022

✓	1 N.M. & Ariz. Land Co.		Log #1095	
ACME OIL CO.		1 Santa Fe		27-7N-4W
COMPANY		WELL NO.		LEASE
Loc. 1838' fr. N L 150' fr. W L		County		Valencia
Spud. 3-22-26		Comp. 3-31-31		Field Wildcat
T.D. 4965'6" P.B.		T.Pay		CSG. RECORD
I.P. D&A		Size		Depth
Well History		15		9
SR 07-07-28: Located SWcorNW¼ of sec. S.D. @		12-1/2		660
2650 with hole full of water.		10		1511
SR 07-14-28: Drlg. 2882.		8-1/4		2680
SR 07-21-28: S.D. @ 3000 with engine trouble.		5-3/16		4965'6"
SR 08-10-28: U.R. 8½" pipe to T.D. 3180.		FORMATION RECORD		
SR 08-25-28: Drlg. 3233 in black lime & shale;		Elev. 6100' approx.		
Set 8½" @ 3140.		T.		
SR 09-01-28: Drlg. lime @ 3295.		T.		
SR 09-21-28: Drlg. 3550 in limestone.		T.		
SR 10-05-28: U.R. 6-5/8" @ 3440.		T.		
SR 10-13-28: S.D. @ 3550; fshg. for cleaning out		T.		
string; 6-5/8" set 3480, will pro-		T.		
bably carry to 3520.		T.		
SR 10-26-28: Cleaning out.		T.		
SR 11-01-28: Cleaning out @ 3540.		T.		

*See survey on Williams & Gore

Same S-T-R - Footage's listed on 102

- SR 11-17-28: Drlg. 3622 in black lime.
SR 11-23-28: T.D. 3625 in gray lime - gas @ bottom. Pulling 6-5/8" to S.R. to bottom.
SR 01-18-29: T.D. 3645; U.R. 6-5/8" to 3600.
SR 02-22-29: S.D. 3645 in lime; salt water (3000' in hole) @ 3507-20). Show GAS 3560-3610 - inc. wtr. 3610-17 - strong show of GAS 3640-45.
SR 03-01-29: T.D. 3645 - drlg. up show & joint of csg.
SR 03-08-29: T.D. 3645 - drlg. on iron (joint csg.)
SR 04-19-29: T.D. 3670 - 8 1/4" @ 3660 cem. w/70 sxs. to shut off wtr. Waiting for cem. to set; GAS 3660-70; will test.
SR 05-10-29: Drlg. 3670 in lime & shale; carrying about 1800' wtr.; will try to find seat to cem. pipe to shut off wtr.
SR 06-14-29: T.D. 3800 grey wtr. sand; running 5-3/16" csg. 8" cem. 3660'.
SR 09-06-29: Drlg. 4006 lime; set 5-3/16" 3997.
SR 10-25-29: Drlg. 4205 granite; first arkose 4034; 5-3/16" 4110.
SR 11-22-29: Drlg. 4535 sand.
SR 12-05-29: T.D. 4535 grey sand; show GAS 4530-35; SR 5-3/16".
SR 02-14-29: T.D. 4535 sand; U.R. 4170 5-3/16".

- SR 03-06-30: T.D. 4630 grey sand - fishing bit.
SR 04-04-30: Drlg. by tools 4630 grey sand.
SR 06-18-30: S.D. 4690 sand tools out.
SR 12-19-30: Drlg. 4951 sand (grey & sharp).

C-105 Rpts: Ftg. 158' FWL.

No other information available from scout rpts. due to a gap from 1931 to May 1932. Other information was taken from driller's log.

- *PSR 05-21-34: Acme Oil & Dev. Co., #1 N.M. & Ariz. Land Co., abandoned several yrs. ago at a little below 4000; workmen now busy pulling the csg.