

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____
Allottee _____
Lease No. 14-20-602-5580

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Operating: Pueblo of Acoma /1

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

Feb. 13, 1960

Well No. 1 is located 1900 ft. from N line and 1900 ft. from E line of sec. 2

NW 1/4 of SE 1/4 of Sec. 2
(1/4 Sec. and Sec. No.)

7 N
(Twp.)

7 W
(Range)

-
(Meridian)

Wildcat
(Field)

Valencia
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is Appx. 6336 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Well spudded 4 p.m. 2-1-60. On 2-3-60 ran 11 fts. (294.93') 13 3/8" OD casing; cemented w/300 sbs common 12% gel, and 100 sbs common 4% gel cement. Seated at 309'. Gist Ridgid centralizers at 302' and 278'. Larkin guide shoe at 308' and Larkin float collar at 278'. Circulated appx. 150 sacks cement. Tested 13 3/8" casing, 30 minutes o.k.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Sun Oil Company

Address Box 2792

Odessa, Texas

By O. J. Wilson

Title Area Superintendent