

OIL CONSERVATION COMMISSION

P. O. BOX 871

SANTA FE, NEW MEXICO

March 23, 1961

Mr. William C. Briggs  
Rodey, Dickason, Sloan, Akin & Robb  
Attorneys at Law  
First National Bank Building  
Albuquerque, New Mexico

Re: Oil Conservation Commission  
v. Tri-State Insurance Company,  
Valencia County, No. 10270

Dear Mr. Briggs:

The subject wells should be plugged as outlined  
below:

Williams & Gore Well No. 1-A, NE/4 NW/4, Section  
27, Township 7 North, Range 4 West, Valencia County,  
New Mexico.

This well should be cleaned out to a depth  
of 3705 feet and filled with heavy plugging mud.  
A 25-sack cement plug should be spotted at a  
depth of 250 feet by means of tubing, and a 10-  
sack cement plug should be set at the surface.  
A steel pipe four inches in diameter should be  
set as a marker in the top of the cement and  
should extend four feet above the surface of  
the terrain.

Hawaiian-New Mexico Oil Ventures Well No. 1,  
SW/4 SW/4, Section 27, Township 7 North, Range  
4 West, Valencia County, New Mexico.

This well should be cleaned out to a depth  
of 3604 feet and filled completely from total  
depth to the surface with cement. A steel pipe