

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	5	5	Surface Soil
5	30	25	Lime, Black
30	51	21	Lime, Gray - 3 Bailers per hr., 11" Bailer water 51 to 56 ft.
51	56	5	Shale, Black
56	62	6	Lime, Black, hard - Set 15" Casing at 58 ft.
62	250	188	Shale, Blue
250	265	15	Lime, Black
265	280	15	Shale, Blue
280	290	10	Shale, Brown
290	295	5	Lime, Black
295	395	100	Shale, Brown
395	405	10	Lime, light
405	420	15	Shale, Black
420	430	10	Lime, light, sandy
430	445	15	Sand, Gray
445	450	5	Shale, Brown
450	480	30	Lime, light, sandy, hard
480	495	15	Shale, Blue
495	508	13	Sand, Gray
508	530	22	Shale, Blue
530	574	44	Sand, white
574	590	16	Shale, green
590	600	10	Shale, Pink
600	625	25	Shale, dark
625	668	43	Sand, gray - fresh water level 200 ft.
668	725	57	Shale, green - Reduced hole at 670 ft. to 10 in.
725	740	15	Lime, gray
740	757	17	Shale, pink
757	762	5	Lime, gray, hard, sharp
762	770	8	Sand, gray, hard, sharp
770	830	60	Lime, brown, sandy, sharp
830	852	22	Sand, brown, sharp
852	855	3	Shale, red
855	864	9	Lime, gray, sharp
864	880	16	Dolomite, hard
880	896	16	Shale, red
896	922	26	Lime, gray, sandy-set 8" casing at 907' -Not cemented
922	925	3	Shale, brown, mixed gyp
925	930	5	Shale, pink
930	960	30	Sand, pink, white - water at 960' - 3 Bailers per hr.
960	1004	44	Sand, white - water level 200' - increased to 14 Bailers
1004	1010	6	Shale, red
1010	1030	20	Sand, red
1030	1035	5	Shale, red
1035	1070	35	Lime, sandy, red
1070	1121	51	Lime, red rock
1121	1155	34	Lime, gray
1155	1157	2	Shale, red
1157	1176	19	Lime, red
1176	1195	19	Lime, gray
1195	1292	97	Red rock lime shells - wet hole cave
1292	1320	28	Lime, pink
1320	1338	18	Lime, gray
1338	1362	24	Lime, broken
1362	1365	3	Lime, gray
1365	1417	52	Shale, red